



Crypto IPsec Transform Set Configuration Mode Commands

The Crypto IPsec Transform Set Configuration Mode is used to configure properties for system transform sets.

Transform Sets are used to define IPsec security associations (SAs). IPsec SAs specify the IPsec protocols to use to protect packets.

Command Modes

Exec > Global Configuration > Context Configuration > Crypto IPsec Transform Set Configuration

configure > **context** *context_name* > **crypto ipsec transform-set** *transform_set_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-crypto-trans)#
```



Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [end, on page 1](#)
- [exit, on page 2](#)
- [mode, on page 2](#)

end

Exits the current configuration mode and returns to the Exec mode.

Product

All

Privilege

Security Administrator, Administrator

Syntax Description

end

Usage Guidelines

Use this command to return to the Exec mode.

exit

Exits the current mode and returns to the parent configuration mode.

| | |
|---------------------------|--|
| Product | All |
| Privilege | Security Administrator, Administrator |
| Syntax Description | <code>exit</code> |
| Usage Guidelines | Use this command to return to the parent configuration mode. |

mode

Configures the IPSec encapsulation mode for an existing or new transform set. For a new transform set, you must specify transform set parameters as described for the `crypto ipsec transform-set` command in the *Context Configuration Mode Commands* chapter.

| | |
|---------------------------|--|
| Product | PDSN HA GGSN PDIF |
| Privilege | Security Administrator |
| Syntax Description | <code>mode { transport tunnel }</code> |

transport

Specifies that the transform set only protects the upper layer protocol data portions of an IP datagram, leaving the IP header information unprotected. Default: Disabled



Important This mode should only be used if the communications end-point is also the cryptographic end-point.

tunnel

Specifies that the transform set protects the entire IP datagram.

This mode should be used if the communications end-point is different from the cryptographic end-point as in a VPN. Default: Enabled

| | |
|-------------------------|--|
| Usage Guidelines | This command specifies the encapsulation mode for the transform set. |
|-------------------------|--|

Example

The following command configures the transforms set's encapsulation mode to transport:

```
mode transport
```

mode