



# ACS Group-of-Prefixed-URLs Configuration Mode Commands



**Important** This configuration mode is customer specific. For more information, contact your Cisco account representative.

**Command Modes** The ACS Group-of-Prefixed-URLs Configuration Mode is used to create and configure groups of prefixed URLs.

Exec > ACS Configuration > ACS Group-of-Prefixed-URLs Configuration

**active-charging service** *service\_name* > **group-of-prefixed-urls** *group\_name*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-acs-grp-of-prefixed-urls) #
```



**Important** The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [end, on page 1](#)
- [exit, on page 2](#)
- [prefixed-url, on page 2](#)

## end

Exits the current configuration mode and returns to the Exec mode.

|                    |  |
|--------------------|--|
| Product            | All  |
| Privilege          | Security Administrator, Administrator        |
| Syntax Description | <b>end</b>                                   |
| Usage Guidelines   | Use this command to return to the Exec mode. |

## exit

Exits the current mode and returns to the parent configuration mode.

|                           |  |
|---------------------------|--|
| <b>Product</b>            | All  |
| <b>Privilege</b>          | Security Administrator, Administrator                        |
| <b>Syntax Description</b> | <b>exit</b>  |
| <b>Usage Guidelines</b>   | Use this command to return to the parent configuration mode. |

## prefixed-url

This command allows you to add or remove URLs from the current group of prefixed URLs.



**Important** A maximum of 10 URLs can be added per group.

|                      |   |
|----------------------|---|
| <b>Product</b>       | ACS   |
| <b>Privilege</b>     | Security Administrator, Administrator   |
| <b>Command Modes</b> | Exec > ACS Configuration > ACS Group-of-Prefixed-URLs Configuration<br><b>active-charging service</b> <i>service_name</i> > <b>group-of-prefixed-urls</b> <i>group_name</i> |

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-acs-grp-of-prefixed-urls)#
```

**Syntax Description** **[ no ] prefixed-url** *url*

**no**

If added previously, removes the specified URL from the current group of prefixed URLs.

**url**

Specifies the URL to add/remove.

*url* must be an alphanumeric string of 1 through 63 characters.

**Usage Guidelines** Use this command to add or remove URLs to be filtered from the group of prefixed URLs.

### Example

The following command adds the URL *http://abc.net* to the current group of prefixed URLs:

```
prefixed-url http://abc.net
```