



# SaMOG Service Configuration Mode Commands

---

## Command Modes

Creates SaMOG service and enters SaMOG service configuration mode.

Exec > Global Configuration > Context Configuration > SAMOG Service Configuration

**configure** > **context** *context\_name* > **samog-service** *samog\_service\_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-samog-service)#
```



---

## Important

Available commands or keywords/variables vary based on platform type, product version, and installed license(s).

- [associate](#), on page 2
- [do show](#), on page 4
- [end](#), on page 5
- [exit](#), on page 6
- [max-sessions](#), on page 7
- [timeout](#), on page 8

# associate

SaMOG associates another service to this SaMOG service.

---

## Product

SaMOG

---

## Command Modes

Exec > Global Configuration > Context Configuration > SaMOG Service Configuration

**configure** > **context** *context\_name* > **samog-service** *samog\_service\_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-samog-service)#
```

---

## Syntax Description

```
associate { cgw-service cgw_service_name | dhcp-service dhcp_service_name [ level
  { system | user } ] | dhcpv6-service dhcpv6_service_name | mrme-service
mrme_service_name | subscriber-map subscriber_map_name }
no associate { cgw-service | dhcp-service | dhcpv6-service | mrme-service
  | subscriber-map }
```

### no

Disables the association of the service with the SaMOG service.

The **no associate dhcp-service** command does not disassociate existing sessions, and only new sessions will not be established. Existing sessions continue to use the DHCPv4 service to which it was bound during session establishment.

The **no associate dhcpv6-service** command stops the SaMOG service from processing DHCPv6 packets.

### **cgw-service** *cgw\_service\_name*

The CGW service should be configured before associating the same with SaMOG service.

*cgw\_service\_name* must be an alphanumeric string between 1 and 63 characters.

### **dhcp-service** *dhcp\_service\_name* [ **level** { **system** | **user** } ]

Specifies the DHCPv4 service to associate with the SaMOG service. DHCPv4 is optional while starting an SaMOG service.

*dhcp\_service\_name* must be an alphanumeric string from 1 through 63.

While the association of the DHCPv4 service with the SaMOG service is optional, DHCPv4 service must be associated with the SaMOG service for the SaMOG Ethernet over GRE (EoGRE) feature to function. If no DHCPv4 service is configured and associated, and at least one EoGRE access type Radius client exist, the output of the **show configuration errors** command will display a warning under the **SaMOG service system errors** section.




---

## Important

The associated DHCPv4 service must not be used for any service other than SaMOG, as packets are always forwarded over the EoGRE tunnel only.

---

**level { system | user }**: Specifies the processing level of the DHCP server messages. **system** will enable DHCP server messages to be processed at the system and user-level. **user** will enable DHCP server messages to be processed at the user-level only. The default value for processing DHCP messages is user level.

**dhcpv6-service *dhcpv6\_service\_name***

Specifies the DHCPv6 service to associate with the SaMOG service, to process DHCPv6 packets. Configure the DHCPv6 server using the **bind address** command in the DHCPv6 Service Configuration Mode.

*dhcpv6\_service\_name* must be an alphanumeric string from 1 through 63 characters.

**mrme-service *mrme\_service\_name***

The MRME service should be configured before associating the same with SaMOG service.

*mrme\_service\_name* must be an alphanumeric string from 1 through 63 characters.

**subscriber-map *subscriber\_map\_name***

The subscriber map service should be configured before associating the same with SaMOG service.

*subscriber\_map\_name* must be an alphanumeric string from 1 through 63 characters.

---

**Usage Guidelines**

Use this command to associate the SaMOG service to CGW service, DHCPv4 service, MRME service, or Subscriber Mapping.

**Example**

The following command associates subscriber-map *smap* with SaMOG Service.

```
associate subscriber-map smap
```

The following command associates cgw-service *cgw* with SaMOG Service.

```
associate cgw-service cgw
```

The following command associates mrme-service *mrme* with SaMOG Service.

```
associate mrme-service mrme
```

# do show

Executes all **show** commands while in Configuration mode.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Syntax Description**

**do show**

---

**Usage Guidelines**

Use this command to run all Exec mode **show** commands while in Configuration mode. It is not necessary to exit the Config mode to run a **show** command.

The pipe character | is only available if the command is valid in the Exec mode.



---

**Caution**

There are some Exec mode **show** commands which are too resource intensive to run from Config mode. These include: **do show support collection**, **do show support details**, **do show support record** and **do show support summary**. If there is a restriction on a specific **show** command, the following error message is displayed:

```
Failure: Cannot execute 'do show support' command from Config mode.
```

---

# end

Exits the current configuration mode and returns to the Exec mode.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Syntax Description**

**end**

---

**Usage Guidelines**

Use this command to return to the Exec mode.

# exit

Exits the current mode and returns to the parent configuration mode.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Syntax Description**

**exit**

---

**Usage Guidelines**

Use this command to return to the parent configuration mode.

# max-sessions

Configures maximum number of subscribers SAMOG service can support, ranging from 0 to 4000000.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > Global Configuration > Context Configuration > SAMOG Service Configuration

**configure** > **context** *context\_name* > **samog-service** *samog\_service\_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-samog-service)#
```

---

**Syntax Description**

**max-sessions** *max\_sessions*

**default max-sessions**

**max-sessions** *max\_sessions*

Configures maximum number of subscribers SAMOG service can support.

*max\_sessions* is an integer value between 0 and 4000000.

**default**

Sets the default value, 4000000 for Max Sessions.

---

**Usage Guidelines**

Use this command to configure the maximum number of subscribers SAMOG service can support.

**Example**

Use the following command to configure the maximum number of subscribers SAMOG service can support:

```
max-sessions 500
```

# timeout

Configures the session's time-to-live (TTL) settings under SAMOG service.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > Global Configuration > Context Configuration > SAMOG Service Configuration

**configure** > **context** *context\_name* > **samog-service** *samog\_service\_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-samog-service)#
```

---

**Syntax Description**

```
timeout { absolute absolute_value | idle idle_value | setup-timeout
setup_timeout_value }
```

```
default timeout [ absolute | idle | setup-timeout ]
```

```
no timeout [ absolute | idle ]
```

**default**

Sets/restores the default value assigned for timeout.

The default value of absolute and idle timeout is *0*, which indicates the function is disabled.

The default value of setup-timeout is *60*.

**no**

Enables / Disables the timeout option.

**absolute** *absolute\_value*

Specifies the maximum duration of the session, in seconds, before the system automatically terminates the session.

*absolute\_value* must be an integer between *0* and *2147483647*.

**idle** *idle\_value*

Specifies the maximum duration a session can remain idle, in seconds, before the system automatically terminates the session. Zero indicates that the timeout function is disabled. Default is *0*.

*idle\_value* must be an integer between *0* and *2147483647*.

**setup-timeout** *setup\_timeout\_value*

Specifies the maximum time allowed for session setup in seconds. Default is *60* seconds.

*setup\_timeout\_value* must be an integer between *0* and *1000000*.

---

**Usage Guidelines**

Use this command to configure the session's time-to-live (TTL) settings under SAMOG service.



**Example**

Use the following command to configure the setup-timeout to 500 seconds:

```
timeout setup-timeout 500
```

Use the following command to configure the absolute timeout to 120 seconds:

```
timeout absolute 120
```

■ timeout