



# Traffic Optimization Profile Configuration Mode Commands

---

The Traffic Optimization Profile Configuration Mode allows you to configure and manage properties of Cisco Ultra Traffic Optimization solution.

---

## Command Modes

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim) #
```



---

## Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

---

- [data-record](#), on page 2
- [efd-flow-cleanup-interval](#), on page 3
- [end](#), on page 4
- [exit](#), on page 5
- [heavy-session detection-threshold](#), on page 6
- [mode](#), on page 7
- [stats-interval](#), on page 8
- [stats-options](#), on page 9

# data-record

This command enables Traffic Optimization Data Record (TODR) generation.

---

**Product**

P-GW

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim)#
```

---

**Syntax Description**

**data-record** [ **large-flows-only** | **managed-large-flows-only** ]  
**no data record**

**no**

If previously configured, disables generation of TODR.

**data-record**

Enables the Traffic Optimization Data Record (TODR) generation

- **large-flows-only**: Enables the traffic optimization data record generation for large flows.

**managed-large-flows-only**: Enables the traffic optimization data record generation for managed large flows.

The keywords - **large-flows-only** and **managed-large-flows-only** when configured along with **data-record** enables the CUTO library to stream the respective statistics as part of the **stats-options** command, to the external server. The user can configure a combination of the **stats-options** keywords **flow-trace** and **flow-analyst** and the **data-record** command to notify the CUTO library accordingly.




---

**Note** One of the above the two keywords can be configured as part of the data-record, which will enable the CUTO library to stream the respective statistics.

---

The default behavior of the **data-record** command is not affected with the above implementation . If it is configured without any of the options, then TODR's will be generated for all standard and large flows, which is the existing behavior.

---

**Usage Guidelines**

Use this command to generate TODR.

# efd-flow-cleanup-interval

This configures EFD flow command cleanup interval.

---

**Product**

P-GW

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim) #
```

---

**Syntax Description**

[ no ] **efd-flow-cleanup-interval**

**no**

If previously configured, disables EFD flow cleanup interval.

**efd-flow-cleanup-interval**

Configures EFD flow cleanup interval. The interval value is an integer that ranges from 10 to 5000 milliseconds.

---

**Usage Guidelines**

Use this command to configure EFD flow cleanup interval.

# end

Exits the current configuration mode and returns to the Exec mode.

---

**Product** All

---

**Privilege** Security Administrator, Administrator

---

**Syntax Description** `end`

---

**Usage Guidelines** Use this command to return to the Exec mode.

# exit

Exits the current mode and returns to the parent configuration mode.

---

**Product**

All

---

**Privilege**

Security Administrator, Administrator

---

**Syntax Description**

**exit**

---

**Usage Guidelines**

Use this command to return to the parent configuration mode.

# heavy-session detection-threshold

Configures the threshold value for the TCP flow to be considered for the Traffic Optimization.

---

## Product

P-GW

---

## Privilege

Security Administrator, Administrator

---

## Command Modes

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim)#
```

---

## Syntax Description

**heavy-session detection-threshold** *bytes*

### heavy-session

Specifies the heavy session configuration for the Traffic Optimization.

### detection-threshold *bytes*

Specifies the detection threshold, in bytes. Beyond which, it is considered as heavy session. The *bytes* must be an integer from 1 to 4294967295.

To get optimum Traffic Optimization benefit, it is recommended to not set it less than 3 MB.

---

## Usage Guidelines

Use this command to set the threshold value for the TCP flow.

### Example

The following command sets the threshold value to *3145728* bytes:

```
heavy-session detection-threshold 3145728
```

# mode

Configures the operating mode for the Cisco Ultra Traffic Optimization engine.

---

**Product**

P-GW

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim) #
```

---

**Syntax Description**

**mode [ active | passive ]**

**mode**

Sets the mode of operation for Traffic Optimization.

**active**

The mode where both Traffic Optimization and flow monitoring is done on the packet.

**passive**

The mode where no flow-control is performed but monitoring is done on the packet.

---

**Usage Guidelines**

Use this command to set the operating mode for the Cisco Ultra Traffic Optimization engine.

**Example**

The following command sets the operating mode to **active**:

```
mode active
```

# stats-interval

This command configures the flow statistics collection and reporting interval.

---

## Product

P-GW

---

## Privilege

Security Administrator, Administrator

---

## Command Modes

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim)#
```

---

## Syntax Description

[ **no** ] **stats-interval**

### **no**

If previously configured, disables collection of flow statistics.

### **stats-interval**

Configures the flow statistics collection and reporting interval in seconds. The interval value is an integer that ranges from 1 to 60 seconds.

---

## Usage Guidelines

Use this command to collect and report flow statistics.



# stats-options

This command configures options to collect the flow statistics.

---

**Product**

P-GW

---

**Privilege**

Security Administrator, Administrator

---

**Command Modes**

Exec > ACS Configuration > Traffic Optimization Profile Configuration

**active-charging service** *service\_name* > **traffic-optimization-profile**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-traffic-optim) #
```

---

**Syntax Description**

```
[ no ] stats-options { flow-analyst [ flow-trace ] | flow-trace [ flow-analyst ] }
```

**no**

If previously configured, disables trace collection and reporting.

**flow-analyst**

Enables flow analysis, and large trace collection and reporting.

**flow-trace**

Enables flow trace collection and reporting.

---

**Usage Guidelines**

Use this command to enable trace collection and reporting.

