



show pgw

This chapter describes the output of the **show pgw** command.

- [show pgw-service all, on page 1](#)
- [show pgw-service name, on page 3](#)
- [show pgw-service statistics all, on page 7](#)
- [show pgw-service statistics all-name, on page 37](#)

show pgw-service all

Displays configuration information for all P-GW services configured on the system.

Table 1: show pgw-service all Command Output Descriptions

| Field | Description |
|----------------------------|---|
| Service name | The name of the P-GW service configured and running on the system. |
| Service-ID | The system-generated identification number associated with the P-GW service name. |
| Context | The context name where the P-GW service is configured. |
| Status | Indicates whether the P-GW service is started or not. |
| EGTP Service | The eGTP service name configured for use by this service. |
| LMA Service | The LMA service name configured for use by this service. |
| GGSN Service | The GGSN service name associated with this service. |
| IPNE Service | Not supported in this release. |
| S-GW Interface Excluded | Excludes the specified interface. |
| Priority message Excluded: | Indicates if the priority message is specified. The valid values are Yes and No. The default value is No. |
| Session-Delete-Delay Timer | Indicates whether there is a delay in terminating a session. |

| Field | Description |
|-----------------------------------|---|
| Session-Delete-Delay Timeout | Specifies the time (msecs) to retain a session before terminating it. |
| PLMN ID List | The Public Land Mobile Network identifier list associated with this P-GW service. A PLMN contains a Mobile Country Code (MCC) and Mobile Network Code (MNC). Up to five PLMN IDs can be configured for each P-GW service. |
| Newcall Policy | The newcall policy configured for this P-GW service. Specifies whether the P-GW will accept or reject requests for a static IP address if the address is already in use by another session |
| dns-client Context Name | The context where the DNS client is configured and used by this service. |
| gx-li context | Refer to the <i>Lawful Intercept Configuration Guide</i> . |
| gx-li transport | Refer to the <i>Lawful Intercept Configuration Guide</i> . |
| QCI-QoS Mapping Table Name | The QoS Class Index to QoS mapping table configured for use with this service. |
| Authorize | Enables/disables subscriber session authorization with HSS over S6b Diameter interface. |
| S6b IPv6 Reporting | Specifies whether IPv6 address reporting through AAR towards the S6b interface is enabled or disabled. |
| Duplicate Subscriber Addr Request | Specifies whether the P-GW will accept or reject requests for a static IP address if the address is already in use by another session. |
| Fqdn-name | The name of Fully Qualified Domain Name (FQDN) which is used for authorization over S6b interface between P-GW and 3GPP AAA/HSS. |
| SAEGW service | Specifies whether P-GW service is part of SAEGW service. |
| EGTP Cause Code Handling | Specifies whether eGTP cause handling has been enabled for this P-GW service. |
| Temp Failure | Specifies whether eGTP cause handling for temporary failure (cause code 110) has been enabled for this P-GW service. |
| Retry Timeout | Specifies the time to wait (in seconds) before reattempting Create Bearer Request (CBR)/Modify Bearer Request (MBR)/Update Bearer Request (UBR) when the P-GW receives a temporary failure response from a peer. |
| Maximum Retry | Specifies the maximum number of retries to attempt. The P-GW discards CBR/MBR/UBR after the maximum number of retries are exceeded. |

| Field | Description |
|--|--|
| EGTP Modify bearer res with CHARGING-ID | Indicates whether Modify Bearer Response message with Charging-ID is enabled or disabled. |
| EGTP Modify bearer res with CHARGING-FQDN or CHARGING-GW-ADDRESS | Indicates whether Modify Bearer Response message with Charging FQDN or Charging Gateway address is enabled or disabled. |
| EGTP Modify bearer res with MSISDN | Indicates whether Modify Bearer Response message with MSISDN is enabled or disabled. |
| EGTP SGW Restoration Handling | |
| Session Hold Timer | Displays if the session Hold Timer is valid or not. |
| Timeout | Displays the Configured Session Hold Timer timeout value in seconds. |
| EGTP Modify bearer cmd negotiate qos | Displays the configuration of the egtp modify-bearer-cmd-negotiate-qos command, either Enabled (P-GW ignores the new QoS value in the modify bearer command and uses old QoS value which is already applied) or Disabled (Default, P-GW accepts new QoS value from modify bearer command while PCRF is unreachable or disabled). |
| EGTP Bit Rate in Rounded Kpbs | Enable/Disable rounded down Kbps value of Bit Rate on GTP interface. |
| EGTP Suppress Update Bearer Request (no bitrate change) | Indicates if the UBR Suppression feature is enabled or disabled. |
| P-CSCF Restoration solution | Indicates the type of mechanism being used for P-CSCF failure detection. Can be either HSS-based (Private Extn) or HSS-Based MME-Triggered (Rel12). |
| P-CSCF Restoration supported for Emergency PDNs | Indicates whether P-CSCF Restoration is enabled for Emergency PDNs. Important This functionality is license dependent. For more information, contact your Cisco account representative. |
| Re-Auth After s6b Triggered P-CSCF Restoration | Indicates whether Re-Auth after S6b triggered P-CSCF Restoration of WLAN is enabled. Important This functionality is license dependent. For more information, contact your Cisco account representative. |

show pgw-service name

Displays configuration information for all P-GW services configured on the system.

Table 2: show pgw-service name Command Output Descriptions

| Field | Description |
|------------------------------|---|
| Service name | The name of the P-GW service configured and running on the system. |
| Service-ID | The system-generated identification number associated with the P-GW service name. |
| Context | The context name where the P-GW service is configured. |
| Status | Indicates whether the P-GW service is started or not. |
| EGTP Service | The eGTP service name configured for use by this service. |
| LMA Service | The LMA service name configured for use by this service. |
| GGSN Service | The GGSN service name associated with this service. |
| IPNE Service | Not supported in this release. |
| Peer Map | |
| Session-Delete-Delay Timer | Indicates whether there is a delay in terminating a session. |
| Session-Delete-Delay Timeout | Specifies the time (msecs) to retain a session before terminating it. |
| PLMN ID List | The Public Land Mobile Network identifier list associated with this P-GW service. A PLMN contains a Mobile Country Code (MCC) and Mobile Network Code (MNC). Up to five PLMN IDs can be configured for each P-GW service. |
| Newcall Policy | The newcall policy configured for this P-GW service. Specifies whether the P-GW will accept or reject requests for a static IP address if the address is already in use by another session |
| dns-client Context Name | The context where the DNS client is configured and used by this service. |
| gx-li context | Refer to the <i>Lawful Intercept Configuration Guide</i> . |
| gx-li transport | Refer to the <i>Lawful Intercept Configuration Guide</i> . |
| Internal QoS Application | The QoS application configured for use with this service. |
| QCI-QoS Mapping Table Name | The QoS Class Index to QoS mapping table configured for use with this service. |
| Authorize | Enables/disables subscriber session authorization with HSS over S6b Diameter interface. |
| Setup Timeout | Specifies the maximum amount of time the P-GW service allows for the setting up of PDP contexts. |

| Field | Description |
|---|--|
| Message Timestamp Drift | Specifies the drift time configuration to take care of NTP drift issues. |
| S6b IPv6 Reporting | Specifies if the IPv6 address reporting through AAR towards the S6b interface is enabled or disabled. |
| Retain MDN | Enables MDN/MSISDN value to be retained as negotiated during the call setup (retrieved from S6b interface or Create Session Request). |
| Duplicate Subscriber Addr Request | Specifies whether the P-GW will accept or reject requests for a static IP address if the address is already in use by another session. |
| Duplicate Subscriber Addr Request IPv6 | Specifies whether the P-GW will accept or reject requests for an IPv6 IP address if the address is already in use by another session. |
| Qos Negotiation Profile Rel8 for Gy interface | |
| DCNR | Enables 5G New radio Functionality for subscriber session in the PGW service. |
| Fqdn-name | The name of Fully Qualified Domain Name (FQDN) which is used for authorization over S6b interface between P-GW and 3GPP AAA/HSS. |
| SAEGW service | Specifies whether P-GW service is part of SAEGW service. |
| EGTP Overcharging Protection | |
| EGTP Cause Code Handling | Specifies whether eGTP cause handling has been enabled for this P-GW service |
| Temp Failure | Specifies whether eGTP cause handling for temporary failure (cause code 110) has been enabled for this P-GW service. |
| Retry Timeout | Specifies the time to wait (in seconds) before reattempting Create Bearer Request (CBR)/Modify Bearer Request (MBR)/Update Bearer Request (UBR) when the P-GW receives a temporary failure response from a peer. |
| Maximum Retry | Specifies the maximum number of retries to attempt. The P-GW discards CBR/MBR/UBR after the maximum number of retries are exceeded. |
| EGTP SGW Restoration Handling | Specifies if the eGTP S-GW restoration handling is enabled or not. |
| Session Hold Timer | Displays if the session Hold Timer is valid or not. |
| Timeout | Displays the Configured Session Hold Timer timeout value in seconds. |

| Field | Description |
|--|---|
| EGTP Modify bearer cmd negotiate qos | Displays the configuration of the egtp modify-bearer-cmd-negotiate-qos command, either Enabled (P-GW accepts new QoSvalue from modify bearer command while PCRF is unreachable; or Disabled (Default, P-GW ignores the new QoS value in the modify bearer command and uses stored QoS value from PCRF). |
| EGTP GnGp Modify bearer res with APN-AMBR | |
| EGTP Modify bearer res with CHARGING-ID | Indicates whether Modify Bearer Response message with Charging-ID is enabled or disabled. |
| EGTP Modify bearer res with CHARGING-FQDN or CHARGING-GW-ADDRESS | Indicates whether Modify Bearer Response message with Charging FQDN or Charging Gateway address is enabled or disabled. |
| EGTP Modify bearer res with MSISDN | Indicates whether Modify Bearer Response message with MSISDN is enabled or disabled. |
| EGTP Modify Bearer Response with Context Not Found cause if IMEI/IMEISV mismatch | |
| EGTP Bit Rate in Rounded Down Kbps | Enable/Disable rounded down Kbps value of Bit Rate on GTP interface. |
| EGTP Suppress Update Bearer Request (no bitrate change) | Indicates if the UBR Suppression feature is enabled or disabled. |
| EGTP Create Session Response with APN-AMBR IE | |
| EGTP Ignore ULI IE with SAI/RAI/CGI in Change Notification Req for EUTRAN | Indicates that egtp change-notification-req rat-type eutran ignore-uli-with-rai-sai-cgi CLI is enabled or disabled under P-GW services. |
| GTP-C Load Control Profile | Indicates the GTP-C load control profile. |
| GTP-C Overload Control Profile | Indicates the GTP-C overload control profile. |
| P-CSCF Restoration solution | Indicates the type of mechanism being used for P-CSCF failure detection. Can be either HSS-based (Private Extn) or HSS-Based MME-Triggered (Rel12). |
| P-CSCF Restoration supported for Emergency PDNs | Indicates whether P-CSCF Restoration is enabled for Emergency PDNs. Note This functionality is license dependent. For more information, contact your Cisco account representative. |
| Re-Auth After s6b Triggered P-CSCF Restoration | Indicates whether Re-Auth after S6b triggered P-CSCF Restoration of WLAN is enabled. Note This functionality is license dependent. For more information, contact your Cisco account representative. |
| GTP-C Cause Code Mapping (Gx Failure) | |

| Field | Description |
|---------------------------------|---|
| eMPS Profile Name | Indicates the eMPS Profile name used to define attributes of an eMPS session. |
| GTPC Outgoing Throttling | Specifies if outgoing throttling has been enabled, which indicates the number of messages that were removed from the queue (due to any collision, or max retransmission expired). |
| RLF Template Name | Specifies the template name for RLF for throttling support. |
| Throttling override | |
| Throttling override Policy | Configures the Throttling Override Policy that can be used at the GGSN/P-GW nodes to selectively bypass throttling for a configured message type or for all messages in emergency call or priority call or call for the configured APN. |
| GTPC Incoming Throttling Params | Specifies if the incoming throttling of GTPC has been configured. It includes following parameters. |
| Message Rate (per sec) | Indicates the number of messages per second. Default: 20000 |
| Delay Tolerance (secs) | Indicates the delay tolerance in seconds. Default: 5 |
| Queue Size | Indicates the queue size. Default: 10000 |
| S-GW Interface Excluded | Excludes the specified interface. |
| Priority message Excluded: | Indicates if the priority message is specified. The valid values are Yes and No. The default value is No. |

show pgw-service statistics all

The following command output applies to release 14.0 and higher.

Table 3: show pgw-service statistics all Command Output Descriptions

| Field | Description |
|---------------------------|--|
| VPN Name | The name of the context in which the P-GW service is configured. |
| Subscribers Total: | |
| Active | The total number of active subscribers. |
| Total S6b Assume Positive | The total number of subscribers in the assume positive state. |
| PDNs Total: | |
| Active | The total number of active PDN sessions. |
| Setup | The total number of setup PDN sessions. |

| Field | Description |
|---|---|
| Released | The total number of released PDN sessions. |
| Rejected | The total number of rejected PDN sessions. |
| PDNs By PDN-Type: | |
| IPv4 PDNs: | |
| Active | The total number of active PDN sessions using IPv4. |
| Setup | The total number of setup PDN sessions using IPv4. |
| Released | The total number of released PDN sessions using IPv4. |
| IPv6 PDNs: | |
| Active | The total number of active PDN sessions using IPv6. |
| Setup | The total number of setup PDN sessions using IPv6. |
| Released | The total number of released PDN sessions using IPv6. |
| IPv4v6 PDNs: | |
| Active | The total number of active PDN sessions using IPv4v6. |
| Setup | The total number of setup PDN sessions using IPv4v6. |
| Released | The total number of released PDN sessions using IPv4v6. |
| DCNR Secondary RAT Data PDN Statistics | |
| PDNs By PLMN-Type: | |
| Home Subscriber PDNs: | |
| Active | Subscriber PLMN Statistics - Home subscribers sessions active |
| Setup | Subscriber PLMN Statistics - Home subscribers sessions setup |
| Released | Subscriber PLMN Statistics - Home subscribers sessions released |
| Visiting Subscriber PDNs: | |
| Active | Subscriber PLMN Statistics - Visiting subscribers sessions active |
| Setup | Subscriber PLMN Statistics - Visiting subscribers sessions setup |
| Released | Subscriber PLMN Statistics - Visiting subscribers sessions released |
| Roaming Subscriber PDNs: | |
| Active | Subscriber PLMN Statistics - Roaming subscribers sessions active |

| Field | Description |
|---------------------------------|--|
| Setup | Subscriber PLMN Statistics - Roaming subscribers sessions setup |
| Released | Subscriber PLMN Statistics - Roaming subscribers sessions released |
| PDNs By Emergency-Type: | |
| Emergency PDNs: | |
| Active | Total Active Emergency PDNs |
| Authentic IMSI | Total Active Emergency PDNs (Auth-IMSI) |
| Un-Authentic IMSI | Total Active Emergency PDNs (Unauth-IMSI) |
| Only IMEI | Total Active Emergency PDNs (Only IMEI) |
| Setup | Total Emergency PDNs setup |
| Authentic IMSI | Total Emergency PDNs (Auth-IMSI) setup |
| Un-Authentic IMSI | Total Emergency PDNs (Unauth-IMSI) setup |
| Only IMEI | Total Emergency PDNs (Only IMEI) setup |
| Rejected | Total Emergency PDNs rejected |
| Non-Emergency PDNs: | |
| Active | The total number of active non-emergency PDNs. |
| Setup | The total number of setup non-emergency PDNs. |
| PDNs Rejected By Reason: | |
| No Resource | The total number of PDNs rejected - No Resource. |
| Missing or unknown APN | The total number of PDNs rejected - Missing or unknown APN. |
| APN sel-Mode mismatch | The total number of PDNs rejected - APN selection-mode mismatch. |
| PDN-Type not supported | The total number of PDNs rejected - Preferred PDN-Type not supported. |
| APN restr violation | The total number of PDNs rejected - APN restriction violation . |
| Subs auth failed | The total number of PDNs rejected - Subscriber authentication failed. |
| static addr not allow | The total number of PDNs rejected - Subscriber static address not allowed. |

| Field | Description |
|-------------------------------------|--|
| static addr not alloc | The total number of PDNs rejected - Subscriber static address not allocated. |
| Dynamic addr not alloc | The total number of PDNs rejected - Dynamic address not allocated. |
| static addr not present | The total number of PDNs rejected - Subscriber static address not present. |
| Invalid QCI Value | The total number of PDNs rejected - Due to the receipt of invalid QoS Class Identifiers (QCIs). |
| Apn-Denied No Subscription | The total number of subscriber sessions disconnected due to denial of APN as requested APN was not subscribed to subscriber. |
| System Failure | The total number of PDNs to ease debugging. |
| PDNs Released By Reason: | |
| Network initiated release | The total number of PDNs released due to a network-initiated release. |
| Admin disconnect | The total number of PDNs released due to an administrative disconnect. |
| GTP-U error ind | The total number of PDNs released due to a GTP-U error indication. |
| SGW path failure | The total number of PDNs released due to an S-GW path failure. |
| Local fallback timeout | The total number of PDNs released due to the local policy timeout when Gx is not reachable. |
| UE P-CSCF Reselect not supported | The total number of UEs released due to P-CSCF Re-selection not being supported. |
| MME initiated release | The total number of PDNs released due to an MME initiated release. |
| S4 SGSN initiated release | The total number of PDNs released due to an S4 SGSN initiated release |
| Bearerers Total: | |
| Active | The total number of active bearers. |
| Setup | The total number of bearers setup. |
| Released | The total number of number of bearers released. |
| Rejected | The total number of rejected bearers. |
| Bearerers By Emergency-Type: | |

| Field | Description |
|---------------------------------------|--|
| Emergency Bearers: | |
| Active | The total number of Active Emergency bearers. |
| Authentic IMSI | The total number of Active Emergency bearers (Authentic-IMSI). |
| Un-Authentic IMSI | The total number of Active Emergency bearers (Unauthentic-IMSI). |
| Only IMEI | The total number of Active Emergency bearers (Only IMEI). |
| Setup | The total number of Emergency bearers setup. |
| Authentic IMSI | The total number of Emergency bearers (Authentic-IMSI) setup. |
| Un-Authentic IMSI | The total number of Emergency bearers (Unauthentic-IMSI) setup. |
| Only IMEI | The total number of Emergency bearers (Only IMEI) setup. |
| Rejected | The total number of Emergency bearers rejected. |
| Non-Emergency Bearers: | |
| Active | The total number of Active Non-Emergency bearers |
| Setup | The total number of Setup Non-Emergency bearers |
| eMPS PDN | |
| Current Active | |
| Cumulative Activated | |
| Cumulative De-activated | |
| DCNR PDN Statistics | |
| Active | The total number of current active SGW DCNR PDNs. |
| Setup | The total number of SGW PDNs that are setup as DCNR PDN. |
| Released | The total number of SGW DCNR PDNs released. |
| Bearers by QoS characteristics | |
| Active: QCI n | The total number of active bearers for QCI n. Where n is a QCI value of 1 through 9 or a QCI value of 65, 66, 69, or 70. |
| Non-Std QCI (Non-GBR) | The total number of active non-standard non-GBR bearers. |
| Non-Std QCI (GBR) | The total number of active non-standard GBR bearers |
| Setup: QCI n | The total number of bearers setup for QCI n. Where n is a QCI value of 1 through 9 or a QCI value of 65, 66, 69, or 70. |

| Field | Description |
|-----------------------------------|--|
| Non-Std QCI (Non-GBR) | The total number of non-standard non-GBR bearers setup. |
| Non-Std QCI (GBR) | The total number of non-standard GBR bearers setup. |
| Released: QCI n | The total number of released bearers for QCI n. Where n is a QCI value of 1 through 9 or a QCI value of 65, 66, 69, or 70. |
| Dedicated Bearers By Type: | |
| UE-initiated: | |
| Active | Total bearers active - UE-initiated |
| Setup | Total bearers setup - UE-initiated |
| Network-initiated: | |
| Active | Total bearers active - Network-initiated |
| Setup | Total bearers setup - Network-initiated |
| Bearer Modifications: | |
| UE-initiated: | |
| QoS Modifications | Total bearers modified - UE-initiated Quality of Service (QoS) modification |
| TFT Modifications | Total bearers modified - UE-initiated Traffic Flow Template modification |
| Network-initiated: | |
| QoS Modifications | Total bearers modified - Network-initiated Quality of Service modification |
| TFT Modifications | Total bearers modified - Network-initiated Traffic Flow Template modification |
| Failures: | |
| UE-initiated-mod-fail: | Total bearers modification failure - UE-initiated modification failed |
| QOS changed | Total bearer modification failures - UE-initiated Quality of Service |
| No res available | Total bearer modification failures - UE-initiated Quality of Service - No resource available |
| Semantic err in TFT | Total bearers modification failures - UE-initiated Quality of Service - Semantic error in Traffic Flow Template operation |
| Syntact err in TFT | Total bearer modification failures - UE-initiated Quality of Service - Syntax error in Traffic Flow Template operation |

| Field | Description |
|------------------------|---|
| Semantic err in fltr | Total bearer modification failures - UE-initiated Quality of Service - Semantic error in packet filter |
| Syntact err in fltr | Total bearer modification failures - UE-initiated Quality of Service - syntax error in packet filter |
| No memory available | Total bearer modification failures - UE-initiated Quality of Service - No resource available |
| System failure | Total bearers modification failure - UE-initiated Quality of Service - System failure |
| No QOS changed | Total bearer modification failures - UE-initiated |
| No res available | Total bearer modification failures - UE-initiated - No resource available |
| Semantic err in TFT | Total bearers modification failures - UE-initiated - Semantic error in Traffic Flow Template operation |
| Syntact err in TFT | Total bearer modification failures - UE-initiated - Syntax error in Traffic Flow Template operation |
| Semantic err in fltr | Total bearer modification failures - UE-initiated - Semantic error in packet filter |
| Syntact err in fltr | Total bearer modification failures - UE-initiated - syntax error in packet filter |
| No memory available | Total bearer modification failures - UE-initiated - No resource available |
| System failure | Total bearers modification failure - UE-initiated - System failure |
| NW-initiated-mod-fail: | Total bearers modification failure - Network-initiated modification failed |
| QOS changed | Total bearer modification failures - Network-initiated Quality of Service |
| No res available | Total bearers modification failure - Network-initiated Quality of Service - No resource available |
| Semantic err in TFT | Total bearers modification failure - Network-initiated Quality of Service - Semantic error in Traffic Flow Template operation |
| Syntact err in TFT | Total bearers modification failure - Network-initiated Quality of Service - syntax error in Traffic Flow Template operation |
| Semantic err in fltr | Total bearers modification failure - Network-initiated Quality of Service - Semantic error in packet filter |
| Syntact err in fltr | Total bearers modification failure - Network-initiated Quality of Service - syntax error in packet filter |
| No memory available | Total bearers modification failure - Network-initiated Quality of Service - No memory available |

| Field | Description |
|--|--|
| System failure | Total bearers modification failure - Network-initiated Quality of Service - System failure |
| No QOS changed | Total bearer modification failures - Network-initiated |
| No res available | Total bearers modification failure - Network-initiated - No resource available |
| Semantic err in TFT | Total bearers modification failure - Network-initiated - Semantic error in Traffic Flow Template operation |
| Syntact err in TFT | Total bearers modification failure - Network-initiated - syntax error in Traffic Flow Template operation |
| Semantic err in fltr | Total bearers modification failure - Network-initiated - Semantic error in packet filter |
| Syntact err in fltr | Total bearers modification failure - Network-initiated - syntax error in packet filter |
| No memory available | Total bearers modification failure - Network-initiated - No memory available |
| System failure | Total bearers modification failure - Network-initiated - System failure |
| Dedicated Bearers Rejected By Reason: | |
| UE-initiated Bearer Rejects | Total dedicated bearers rejected - UE-initiated |
| No resource | Total dedicated bearers rejected - UE-initiated - No resource |
| NW-initiated Bearer Rejects | Total dedicated bearers rejected - Network-initiated |
| No resource | Total dedicated bearers rejected - Network-initiated - No resource |
| No mem available | Total dedicated bearers rejected - Network-initiated - No memory available |
| System failure | Total dedicated bearers rejected - Network-initiated - System failure |
| Dedicated Bearers Released By Reason: | |
| Network initiated release | Total dedicated bearers released - Network-initiated |
| Admin disconnect | Total dedicated bearers released - Network-initiated - Admindisconnect |
| GTP-U error ind | Total dedicated bearers released - Network-initiated - GTP-Uerror |
| MME initiated release | Total dedicated bearers released - Network-initiated - MME initiated release |
| Default Bearer release | Total dedicated bearers released - Network-initiated - Default bearer release |

| Field | Description |
|--|---|
| IP Address Allocation Statistics: | |
| Total IPv4 addrs allocated | Total IPv4 addresses allocated |
| Local pool assignment | Total IPv4 addresses allocated - Local pool address assignment |
| Static addr assignment | Total IPv4 addresses allocated - Static address assignment |
| Radius provided assignment | Total IPv4 addresses allocated - RADIUS provided address assignment |
| Total IPv6 addrs allocated | Total IPv6 addresses allocated |
| Stateless auto config | Total IPv6 address allocated - Stateless auto config |
| Local pool assignment | Total IPv6 addresses allocated - Local pool address assignment |
| Static addr assignment | Total IPv6 addresses allocated - Static address assignment |
| Radius provided assignment | Total IPv6 addresses allocated - RADIUS provided address assignment |
| SGi tunneling statistics: | |
| Total IPv4 tunnel sessions: | |
| IP-in-IP Tunnels: | |
| Active | SGi tunneling Statistics - IPv4 IP-in-IP tunnel sessions active |
| Setup | SGi tunneling Statistics - IPv4 IP-in-IP tunnel sessions setup |
| Released | SGi tunneling Statistics - IPv4 IP-in-IP tunnel sessions released |
| GRE Tunnels: | |
| Active | SGi tunneling Statistics - IPv4 GRE tunnel sessions active |
| Setup | SGi tunneling Statistics - IPv4 GRE tunnel sessions setup |
| Released | SGi tunneling Statistics - IPv4 GRE tunnel sessions released |
| Total IPv6 tunneled sessions: | |
| 6to4 Tunnels: | |
| Active | SGi tunneling Statistics - IPv6 6to4 tunnel sessions active |
| Setup | SGi tunneling Statistics - IPv6 6to4 tunnel sessions setup |
| Released | SGi tunneling Statistics - IPv6 6to4 tunnel sessions released |
| Handover Statistics: | |
| Intra Technology handover: | |

| Field | Description |
|-----------------------------------|---|
| Inter SGSN handover: | |
| Attempted | Total number of inter-SGSN handover attempts |
| Succeeded | Total number of successful inter-SGSN handovers |
| Failed | Total number of failed inter-SGSN handovers |
| Inter SGW handover: | |
| Attempted | Total number of inter-SGW handover attempts |
| Succeeded | Total number of successful inter-SGW handovers |
| Failed | Total number of failed inter-SGW handovers |
| Inter HSGW handover: | |
| Attempted | Total number of inter-HSGW handover attempts |
| Succeeded | Total number of successful inter-HSGW handovers |
| Failed | Total number of failed inter-HSGW handovers |
| Inter Technology handover: | |
| GNGP-to-LTE handover: | |
| Attempted | Total number of Gn/Gp to LTE attempted handovers |
| Succeeded | Total number of Gn/Gp to LTE successful handovers |
| Failed | Total number of Gn/Gp to LTE failed handovers |
| LTE-to-GNGP handover: | |
| Attempted | Total number of LTE to Gn/Gp attempted handovers |
| Succeeded | Total number of LTE to Gn/Gp successful handovers |
| Failed | Total number of LTE to Gn/Gp failed handovers |
| LTE-to-eHRPD handover: | |
| Attempted | Total number of LTE to eHRPD attempted handovers |
| Succeeded | Total number of LTE to eHRPD successful handovers |
| Failed | Total number of LTE to eHRPD failed handovers |
| eHRPD-to-LTE handover: | |
| Attempted | Total number of eHRPD to LTE attempted handovers |
| Succeeded | Total number of eHRPD to LTE successful handovers |

| Field | Description |
|-----------------------------------|---|
| Failed | Total number of eHPRD to LTE failed handovers |
| LTE-to-S2bPMIP handover: | |
| Attempted | Total number of LTE to S2bPMIP attempted handovers |
| Succeeded | Total number of LTE to S2bPMIP successful handovers |
| Failed | Total number of LTE to S2bPMIP failed handovers |
| S2bPMIP-to-LTE handover: | |
| Attempted | Total number of S2bPMIP to LTE attempted handovers |
| Succeeded | Total number of S2bPMIP to LTE successful handovers |
| Failed | Total number of S2bPMIP to LTE failed handovers |
| eHPRD-to-S2bPMIP handover: | |
| Attempted | Total number of eHPRD to S2bPMIP attempted handovers |
| Succeeded | Total number of eHPRD to S2bPMIP successful handovers |
| Failed | Total number of eHPRD to S2bPMIP failed handovers |
| S2bPMIP-to-eHPRD handover: | |
| Attempted | Total number of S2bPMIP to eHPRD attempted handovers |
| Succeeded | Total number of S2bPMIP to eHPRD successful handovers |
| Failed | Total number of S2bPMIP to eHPRD failed handovers |
| S2bGTP-to-LTE handover: | |
| Attempted | Total number of S2bGTP to LTE attempted handovers |
| Succeeded | Total number of S2bGTP to LTE successful handovers |
| Failed | Total number of S2bGTP to LTE failed handovers |
| LTE-to-S2bGTP handover: | |
| Attempted | Total number of LTE to S2bGTP attempted handovers |
| Succeeded | Total number of LTE to S2bGTP successful handovers |
| Failed | Total number of LTE to S2bGTP failed handovers |
| S2bGTP-to-eHPRD handover: | |
| Attempted | Total number of S2bGTP to eHPRD attempted handovers |
| Succeeded | Total number of S2bGTP to eHPRD successful handovers |

| Field | Description |
|---|--|
| Failed | Total number of S2bGTP to eHPRD failed handovers |
| EHRPD-to-S2bGTP handover: | |
| Attempted | Total number of eHPRD to S2bGTP attempted handovers |
| Succeeded | Total number of eHPRD to S2bGTP successful handovers |
| Failed | Total number of eHPRD to S2bGTP failed handovers |
| GNGP-to-S4SGSN handover: | |
| Attempted | Total number of GNGP-to-S4SGSN attempted handovers |
| Succeeded | Total number of GNGP-to-S4SGSN successful handovers |
| Failed | Total number of GNGP-to-S4SGSN failed handovers |
| S4SGSN-to-GNGP handover: | |
| Attempted | Total number of S4SGSN-to-GNGP attempted handovers |
| Succeeded | Total number of S4SGSN-to-GNGP successful handovers |
| Failed | Total number of S4SGSN-to-GNGP failed handovers |
| S4SGSN-to-LTE handover: | |
| Attempted | Total number of S4SGSN-to-LTE attempted handovers |
| Succeeded | Total number of S4SGSN-to-LTE successful handovers |
| Failed | Total number of S4SGSN-to-LTE failed handovers |
| LTE-to-S4SGSN handover: | |
| Attempted | Total number of LTE-to-S4SGSN attempted handovers |
| Succeeded | Total number of LTE-to-S4SGSN successful handovers |
| Failed | Total number of LTE-to-S4SGSN failed handovers |
| P-CSCF Restoration Indications received: | |
| | <p>The total number of P-CSCF Restoration indications received (HSS Triggered and PCRF Triggered) at service level.</p> <p>The total number of triggers received on any interface (MME/PCRF/S6b) = Basic + Extended + Ignored (ignored for reasons such as restoration already in progress, license not present, validation check fails, or call not connected).</p> |
| HSS Triggered Restoration: | |
| MME Triggered Restoration | Tracks the number of occurrences of P-CSCF Restoration Required Indications received from the MME/S-GW through a modify bearer request. |

| Field | Description |
|--|--|
| Basic Restoration Performed | The total number of basic P-CSCF Restorations performed for restoration indications received from the MME/S-GW. |
| Extension Restoration Performed | The total number of extended P-CSCF Restorations performed for restoration indications received from the MME/S-GW. |
| S6b Triggered Restoration | The total number of P-CSCF Restoration Required Indications received from the s6b AAA server through a RAR for a WLAN. |
| Basic Restoration Performed | The total number of basic P-CSCF Restorations performed for restoration indications received from an s6b AAA server through a RAR for a WLAN. |
| Extension Restoration Performed | The total number of extended P-CSCF Restorations performed for restoration indications received from an s6b AAA server through a RAR for a WLAN. |
| PCRF Triggered Restoration: | The total number of P-CSCF Restoration Required Indications received from the PCRF through RAR. |
| Basic Restoration Performed | The total number of basic P-CSCF Restorations performed for restoration indications received from PCRF through a RAR. |
| Extension Restoration Performed | The total number of extended P-CSCF Restorations performed for restoration indications received from a PCRF through a RAR. |
| Data Statistics Per Interface: | |
| S5U/S8U/S2bU/Gn/Gp Total Data Statistics: | |
| Uplink: | |
| Total Pkts | The total number of uplink packets forwarded. |
| Std QCI (Non-GBR) | The total number of uplink packets forwarded with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of uplink packets forwarded with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of uplink packets forwarded with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of uplink packets forwarded with a non-standard QoS Class Index (GBR). |
| Total Bytes | The total number of uplink bytes forwarded. |
| Std QCI (Non-GBR) | The total number of uplink bytes forwarded with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of uplink bytes forwarded with a standard QoS Class Index. |

| Field | Description |
|------------------------|---|
| Non-Std QCI (Non-GBR) | The total number of uplink bytes forwarded with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of uplink bytes forwarded with a non-standard QoS Class Index (GBR). |
| Total Dropped Pkts | The total number of uplink packets dropped. |
| Std QCI (Non-GBR) | The total number of uplink packets dropped with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of uplink packets dropped with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of uplink packets dropped with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of uplink packets dropped with a non-standard QoS Class Index (GBR). |
| Total Dropped Bytes | The total number of uplink bytes dropped. |
| Std QCI (Non-GBR) | The total number of uplink bytes dropped with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of uplink bytes dropped with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of uplink bytes dropped with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of uplink bytes dropped with a non-standard QoS Class Index (GBR). |
| Dropped Pkts MBR Excd | The total number of uplink packets dropped due to MBR exceeded. |
| Std QCI (Non-GBR) | The total number of uplink packets dropped with a standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Std QCI (GBR) | The total number of uplink packets dropped with a standard QoS Class Index due to MBR exceeded. |
| Non-Std QCI (Non-GBR) | The total number of uplink packets dropped with a non-standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Non-Std QCI (GBR) | The total number of uplink packets dropped with a non-standard QoS Class Index (GBR) due to MBR exceeded. |
| Dropped Bytes MBR Excd | The total number of uplink bytes dropped due to MBR exceeded. |
| Std QCI (Non-GBR) | The total number of uplink bytes dropped with a standard QoS Class Index (non-GBR) due to MBR exceeded. |

| Field | Description |
|---|---|
| Std QCI (GBR) | The total number of uplink bytes dropped with a standard QoS Class Index due to MBR exceeded. |
| Non-Std QCI (Non-GBR) | The total number of uplink bytes dropped with a non-standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Non-Std QCI (GBR) | The total number of uplink bytes dropped with a non-standard QoS Class Index (GBR) due to MBR exceeded. |
| Drops Due To APN AMBR Rate Limit | |
| Packets | The total number of uplink packets dropped due to APN AMBR rate limit. |
| Bytes | The total number of uplink bytes dropped due to APN AMBR rate limit. |
| Downlink: | |
| Total Pkts | The total number of downlink packets forwarded. |
| Std QCI (Non-GBR) | The total number of downlink packets forwarded with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of downlink packets forwarded with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of downlink packets forwarded with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of downlink packets forwarded with a non-standard QoS Class Index (GBR). |
| Total Bytes | The total number of downlink bytes forwarded. |
| Std QCI (Non-GBR) | The total number of downlink bytes forwarded with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of downlink bytes forwarded with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of downlink bytes forwarded with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of downlink bytes forwarded with a non-standard QoS Class Index (GBR). |
| Total Dropped Pkts | The total number of downlink packets dropped. |
| Std QCI (Non-GBR) | The total number of downlink packets dropped with a standard QoS Class Index (non-GBR). |

| Field | Description |
|------------------------|---|
| Std QCI (GBR) | The total number of downlink packets dropped with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of downlink packets dropped with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of downlink packets dropped with a non-standard QoS Class Index (GBR). |
| Total Dropped Bytes | The total number of downlink bytes dropped. |
| Std QCI (Non-GBR) | The total number of downlink bytes dropped with a standard QoS Class Index (non-GBR). |
| Std QCI (GBR) | The total number of downlink bytes dropped with a standard QoS Class Index. |
| Non-Std QCI (Non-GBR) | The total number of downlink bytes dropped with a non-standard QoS Class Index (non-GBR). |
| Non-Std QCI (GBR) | The total number of downlink bytes dropped with a non-standard QoS Class Index (GBR). |
| Dropped Pkts MBR Excd | The total number of downlink packets dropped due to MBR exceeded. |
| Std QCI (Non-GBR) | The total number of downlink packets dropped with a standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Std QCI (GBR) | The total number of downlink packets dropped with a standard QoS Class Index due to MBR exceeded. |
| Non-Std QCI (Non-GBR) | The total number of downlink packets dropped with a non-standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Non-Std QCI (GBR) | The total number of downlink packets dropped with a non-standard QoS Class Index (GBR) due to MBR exceeded. |
| Dropped Bytes MBR Excd | The total number of downlink bytes dropped due to MBR exceeded. |
| Std QCI (Non-GBR) | The total number of downlink bytes dropped with a standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Std QCI (GBR) | The total number of downlink bytes dropped with a standard QoS Class Index due to MBR exceeded. |
| Non-Std QCI (Non-GBR) | The total number of downlink bytes dropped with a non-standard QoS Class Index (non-GBR) due to MBR exceeded. |
| Non-Std QCI (GBR) | The total number of downlink bytes dropped with a non-standard QoS Class Index (GBR) due to MBR exceeded. |

| Field | Description |
|--------------------------------------|--|
| Drops Due To APN AMBR Rate Limit | |
| Packets | The total number of downlink packets dropped due to APN AMBR rate limit. |
| Bytes | The total number of downlink bytes dropped due to APN AMBR rate limit. |
| Data Statistics Per PDN-Type: | |
| IPv4 PDNs: | |
| Uplink: | |
| Total Pkts | The total number of IPv4 PDN uplink packets (from user). |
| Total Bytes | The total number of IPv4 PDN uplink bytes (from user). |
| Downlink: | |
| Total Pkts | The total number of IPv4 PDN downlink packets (to user). |
| Total Bytes | The total number of IPv4 PDN downlink bytes (to user). |
| IPv6 PDN Data Statistics: | |
| Uplink: | |
| Total Pkts | The total number of IPv6 PDN uplink packets (from user). |
| Total Bytes | The total number of IPv6 PDN uplink bytes (from user). |
| Downlink: | |
| Total Pkts | The total number of IPv6 PDN downlink packets (to user). |
| Total Bytes | The total number of IPv6 PDN downlink bytes (to user). |
| IPv4v6 PDN Data Statistics: | |
| Uplink: | |
| Total Pkts v4 | The total number of IPv4 PDN uplink packets (from user). |
| Total Bytes v4 | The total number of IPv4 PDN uplink bytes (from user). |
| Total Pkts v6 | The total number of IPv6 PDN uplink packets (from user). |
| Total Bytes v6 | The total number of IPv6 PDN uplink bytes (from user). |
| Downlink: | |
| Total Pkts v4 | The total number of IPv4 PDN downlink packets (to user). |
| Total Bytes v4 | The total number of IPv4 PDN downlink bytes (to user). |

| Field | Description |
|--|---|
| Total Pkts v6 | The total number of IPv6 PDN downlink packets (to user). |
| Total Bytes v6 | The total number of IPv6 PDN downlink bytes (to user). |
| Packets: QCI n | The total number of uplink packets transmitted for QCI n. Where n is a QCI value of 1 through 9, or a QCI value of 65, 66, 69, or 70. |
| Non-Std QCI | The total number of non-standard QCI uplink packets transmitted. |
| Packets: QCI n | The total number of downlink packets transmitted for QCI n. Where n is a QCI value of 1 through 9, or a QCI value of 65, 66, 69, or 70. |
| Non-Std QCI | The total number of non-standard QCI downlink packets transmitted. |
| 802.1p priority marking statistics | |
| Uplink: Priority 0-7 | The total number of packets sent in the uplink direction marked with a specific (0-7) 802.1p priority. Deprecated in releases 16.0 and later. |
| Downlink: Priority 0-7 | The total number of packets sent in the downlink direction marked with a specific (0-7) 802.1p priority. Deprecated in releases 16.0 and later. |
| Priority marking statistics | |
| Uplink: Priority 0-7 | The total number of packets sent in the uplink direction marked with an internal QoS priority. |
| Downlink: Priority 0-7 | The total number of packets sent in the downlink direction marked with an internal QoS priority. |
| Dedicated Bearer Released due to Idle-Inactivity timeout: | |
| Std QCI (Non-GBR) | The number of dedicated non-Guaranteed bit rate (non-GBR) bearers with a standard QCI value that were released due to an idle-inactivity timeout. |
| Non-Std QCI (Non-GBR) | The number of dedicated non-Guaranteed bit rate (non-GBR) bearers with a non-standard QCI value that were released due to an idle-inactivity timeout. |
| Std QCI (GBR) | The number of dedicated Guaranteed Bit Rate (GBR) bearers with a standard QCI value that were released due to an idle-inactivity timeout. |
| Non-std QCI (GBR) | The number of dedicated Guaranteed Bit Rate (GBR) bearers with a non-standard QCI value that were released due to an idle-inactivity timeout. |

| Field | Description |
|--|---|
| PDNs by RAT-Type: | |
| EUTRAN | The total number of EUTRAN PDNs by RAT-Type. |
| UTRAN | The total number of UTRANs PDNs by RAT-Type. |
| GERAN | The total number of GERANs PDNs by RAT-Type. |
| WLAN | The total number of WLANs PDNs by RAT-Type. |
| Other | The total number of Others PDNs by RAT-Type. |
| SGW Restoration Statistics: | |
| PDNs Total: | |
| In Restoration State: | |
| Recovered | The total number of PDN session recovered during SGW Restoration. |
| Released | The total number of PDN sessions released during SGW Restoration. |
| Drops during SGW Restoration: | |
| Packets | The total number of packets dropped during SGW Restoration. |
| Bytes | The total number of bytes dropped uring SGW Restoration. |
| P-CSCF Restoration Indications received: (Count at Service Level) | |
| Data Statistics Per Interface | Total number of occurrences of P-CSCF Restoration Required Indications received from the MME/S-GW through a modify bearer request |
| S2bGTP-to-eHRPD handover: | |
| Attempted | Total number of S2bGTP-to-eHRPD handover attempts |
| Succeeded | Total number of successful S2bGTP-to-eHRPD handovers |
| Failed | Total number of failed S2bGTP-to-eHRPD handovers |
| eHRPD-to-S2bGTP handover: | |
| Attempted | Total number of eHRPD-to-S2bGTP handover attempts |
| Succeeded | Total number of successful eHRPD-to-S2bGTP handovers |
| Failed | Total number of failed eHRPD-to-S2bGTP handovers |

The following command output applies to releases prior to 14.0.

Table 4: show pgw-service statistics all Command Output Descriptions 0

| Field | Description |
|----------------------------------|--|
| PGW Node Level Statistics | |
| VPN Name | The name of the context in which the P-GW service is configured. |
| Total Active UE | The total number of active subscribers. |
| Total bearers active | |
| Default bearers | The total number of active default bearers using the P-GW node. |
| Non-Emergency | The total number of active default non-emergency bearers using the P-GW node. |
| Emergency | The total number of active default emergency bearers using the P-GW node. |
| Dedicated bearers | The total number of active dedicated bearers using the P-GW node. |
| UE-initiated | The total number of active UE-initiated dedicated bearers using the P-GW node. |
| Network-initiated | The total number of active network-initiated dedicated bearers using the P-GW node. |
| Non-Emergency | The total number of active non-emergency dedicated bearers using the P-GW node. |
| Emergency | The total number of active emergency dedicated bearers using the P-GW node. |
| Emergency bearers (Auth-IMSI) | The total number of authorized International Mobile Subscriber Identity (IMSI) emergency bearers active using the P-GW node. |
| Emergency bearers (Unauth-IMSI) | The total number of unauthorized International Mobile Subscriber Identity (IMSI) emergency bearers active using the P-GW node. |
| Emergency bearers (Only IMEI) | The total number of International Mobile Equipment Identity (IMEI) emergency bearers active using the P-GW node. |
| Total bearers setup | |
| Default bearers | The total number of default bearers set up using the P-GW node. |
| Non-Emergency | The total number of default non-emergency bearers set up using the P-GW node. |
| Emergency | The total number of default emergency bearers set up using the P-GW node. |
| Dedicated bearers | The total number of dedicated bearers set up using the P-GW node. |

| Field | Description |
|-------------------------------|---|
| UE-initiated | The total number of UE-initiated dedicated bearers set up using the P-GW node. |
| Network-initiated | The total number of network-initiated dedicated bearers set up using the P-GW node. |
| Non-Emergency | The total number of non-emergency dedicated bearers set up using the P-GW node. |
| Emergency | The total number of emergency dedicated bearers set up using the P-GW node. |
| Total bearers released | |
| Default bearers | The total number of default bearers released using the P-GW node. |
| Network init release | The total number of default bearers released due to an network-initiated release using the P-GW node. |
| MME init release | The total number of default bearers released due to an MME-initiated release using the P-GW node. |
| Dedicated bearers | The total number of dedicated bearers released using the P-GW node. |
| Network initiated release | The total number of dedicated bearers released due to an network-initiated release using the P-GW node. |
| S4 SGSN initiated release | The total number of dedicated bearers released due to an S4-SGSN-initiated release using the P-GW node. |
| MME initiated release | The total number of dedicated bearers released due to an MME-initiated release using the P-GW node. |
| Default bearer release | The total number of dedicated bearers released due to a default bearer release using the P-GW node. |
| Total bearers release failure | |
| Default bearers | The total number of default bearer release failures using the P-GW node. |
| Dedicated bearers | The total number of dedicated bearer release failures using the P-GW node. |
| Total bearers rejected | |
| Default bearers | The total number of default bearers rejected using the P-GW node. |
| Dedicated bearers | The total number of dedicated bearers rejected using the P-GW node. |
| UE-req reject | The total number of UE-requested bearers rejected using the P-GW node. |

| Field | Description |
|--|---|
| Network-req reject | The total number of network-requested bearers rejected using the P-GW node. |
| Total Emergency default bearer rejected | The total number of emergency default bearer rejected using the P-GW node. |
| Total Emergency dedicated bearers rejected | The total number of emergency dedicated bearer rejected using the P-GW node. |
| Total bearers modified | |
| UE-initiated mod | The total number of UE-initiated bearers modified using the P-GW node. |
| Network-initiated mod | The total number of network-initiated bearers modified using the P-GW node. |
| Total bearers modification failure | |
| UE-initiated mod fail | The total number of UE-initiated bearer modification failures using the P-GW node. |
| Network-initiated mod fail | The total number of network-initiated bearer modification failures using the P-GW node. |
| Subscriber session statistics | |
| Total bearers active | |
| Default bearers | The total number of active default bearers using the P-GW service(s) on this system. |
| Dedicated bearers | The total number of active dedicated bearers using the P-GW service(s) on this system. This counter increments for both network and UE-initiated dedicated bearers. |
| Total bearers setup | |
| Default bearers | The total number of default bearers setup using the P-GW service(s) on this system. |
| Dedicated bearers | The total number of dedicated bearers setup using the P-GW service(s) on this system. This counter increments for both network and UE-initiated dedicated bearer setup. |
| Total bearers released | |
| Default bearers | The total number of default bearers released using the P-GW service(s) on this system. |
| Network initiated release | |

| Field | Description |
|-------------------------------|--|
| Admin disconnect | The total number of default bearers released due to an administrative disconnect using the P-GW service(s) on this system. |
| GTP-U error ind | The total number of default bearers released due to a GTP-U error indication using the P-GW service(s) on this system. |
| SGW Path failure | The total number of default bearers released due to an S-GW path failure using the P-GW service(s) on this system. |
| MME Initiated release | The total number of default bearers released due to an MME initiated release using the P-GW service(s) on this system. |
| Dedicated bearers | The total number of dedicated bearers released using the P-GW service(s) on this system. |
| Network initiated release | |
| Admin disconnect | The total number of dedicated bearers released due to an administrative disconnect using the P-GW service(s) on this system. |
| GTP-U error ind | The total number of dedicated bearers released due to a GTP-U error indication using the P-GW service(s) on this system. |
| MME initiated release | The total number of dedicated bearers released due to an MME initiated release using the P-GW service(s) on this system. |
| Default bearer release | The total number of dedicated bearers released due to a default bearer release using the P-GW service(s) on this system. |
| Total bearers release failure | |
| Default bearers | The total number of default bearer release failures using the P-GW service(s) on this system. |
| Dedicated bearers | The total number of dedicated bearer release failures using the P-GW service(s) on this system. |
| Total bearers rejected: | |
| Default bearers | The total number of default bearers rejected using the P-GW service(s) on this system. |
| No Resource | The total number of default bearers rejected due to a no resource condition using the P-GW service(s) on this system. |
| Missing or unknown APN | The total number of default bearers rejected due to a missing or unknown APN using the P-GW service(s) on this system. |
| APN selection-Mode mismatch | The total number of default bearers rejected due to an APN selection mode mismatch using the P-GW service(s) on this system. |

| Field | Description |
|--------------------------------|--|
| Pref PDN-Type not supported | The total number of default bearers rejected due to a preferred PDN type not supported condition using the P-GW service(s) on this system. |
| APN restr violation | The total number of default bearers rejected due to an APN restriction violation using the P-GW service(s) on this system. |
| Subs auth failed | The total number of default bearers rejected due to a subscriber authentication failure using the P-GW service(s) on this system. |
| Subs static addr not allowed | The total number of default bearers rejected due to a disallowed subscriber static IP address using the P-GW service(s) on this system. |
| Subs static addr not alloc | The total number of default bearers rejected due to an unallocated subscriber static IP address using the P-GW service(s) on this system. |
| Dynamic addr not alloc | The total number of default bearers rejected due to an unallocated dynamic IP address using the P-GW service(s) on this system. |
| Subs static addr not present | The total number of default bearers rejected due to a missing subscriber static IP address using the P-GW service(s) on this system. |
| Dedicated bearers | The total number of dedicated bearers rejected using the P-GW service(s) on this system. |
| UE-req reject | The total number of UE-requested dedicated bearers rejected using the P-GW service(s) on this system. |
| Network-req reject | The total number of network-requested dedicated bearers rejected using the P-GW service(s) on this system. |
| Total bearers modified | |
| UE-initiated modification | The total number of UE-initiated bearers modified using the P-GW service(s) on this system. |
| QOS modification | The total number of UE-initiated bearers with a QoS modification using the P-GW service(s) on this system. |
| TFT modification | The total number of UE-initiated bearers with a TFT modification using the P-GW service(s) on this system. |
| Network-initiated modification | The total number of network-initiated bearers modified using the P-GW service(s) on this system. |
| QOS modification | The total number of network-initiated bearers with a QoS modification using the P-GW service(s) on this system. |
| TFT modification | The total number of network-initiated bearers with a TFT modification using the P-GW service(s) on this system. |

| Field | Description |
|------------------------------------|---|
| Total bearers modification failure | |
| UE-initiated mod failed | The total number of UE-initiated bearer modification failures using the P-GW service(s) on this system. |
| QOS mod fail | The total number of UE-initiated bearer modification failures due to QoS modification failures using the P-GW service(s) on this system. |
| Semantic err in TFT oper | The total number of UE-initiated bearer modification failures due to semantic errors in a TFT operation using the P-GW service(s) on this system. |
| Syntact err in TFT oper | The total number of UE-initiated bearer modification failures due to syntactic errors in a TFT operation using the P-GW service(s) on this system. |
| Semantic err in pkt filter | The total number of UE-initiated bearer modification failures due to semantic errors in a packet filter using the P-GW service(s) on this system. |
| Syntact err in pkt filter | The total number of UE-initiated bearer modification failures due to syntactic errors in a packet filter using the P-GW service(s) on this system. |
| Network-initiated mod failed | The total number of network-initiated bearer modification failures using the P-GW service(s) on this system. |
| QOS mod fail | The total number of network-initiated bearer modification failures due to QoS modification failures using the P-GW service(s) on this system. |
| Semantic err in TFT oper | The total number of network-initiated bearer modification failures due to semantic errors in a TFT operation using the P-GW service(s) on this system. |
| Syntact err in TFT oper | The total number of network-initiated bearer modification failures due to syntactic errors in a TFT operation using the P-GW service(s) on this system. |
| Semantic err in pkt filter | The total number of network-initiated bearer modification failures due to semantic errors in a packet filter using the P-GW service(s) on this system. |
| Syntact err in pkt filter | The total number of network-initiated bearer modification failures due to syntactic errors in a packet filter using the P-GW service(s) on this system. |
| Total PDN-Type stats | |
| PDN-Type IPv4 sessions | The total number of PDN-type IPv4 sessions using the P-GW service(s) on this system. |

| Field | Description |
|---|---|
| Active | The total number of active PDN-type IPv4 sessions using the P-GW service(s) on this system. |
| Setup | The total number of setup PDN-type IPv4 sessions using the P-GW service(s) on this system. |
| Released | The total number of released PDN-type IPv4 sessions using the P-GW service(s) on this system. |
| PDN-Type IPv6 sessions | The total number of PDN-type IPv6 sessions using the P-GW service(s) on this system. |
| Active | The total number of active PDN-type IPv6 sessions using the P-GW service(s) on this system. |
| Setup | The total number of setup PDN-type IPv6 sessions using the P-GW service(s) on this system. |
| Released | The total number of released PDN-type IPv6 sessions using the P-GW service(s) on this system. |
| PDN-Type IPv4v6 sessions | The total number of PDN-type IPv4v6 sessions using the P-GW service(s) on this system. |
| Active | The total number of active PDN-type IPv4v6 sessions using the P-GW service(s) on this system. |
| Setup | The total number of setup PDN-type IPv4v6 sessions using the P-GW service(s) on this system. |
| Released | The total number of released PDN-type IPv4v6 sessions using the P-GW service(s) on this system. |
| IP address allocation statistics | |
| Total IPv4 addrs allocated | The total number of IPv4 addresses allocated using the P-GW service(s) on this system. |
| Local pool add assign | The total number of local IP pool IPv4 addresses allocated using the P-GW service(s) on this system. |
| Static addr assign | The total number of static IPv4 addresses allocated using the P-GW service(s) on this system. |
| Radius provided addr assign | The total number of RADIUS-provided IPv4 addresses allocated using the P-GW service(s) on this system. |
| Total IPv6 addrs allocated | The total number of IPv6 addresses allocated using the P-GW service(s) on this system. |
| Stateless auto config | The total number of stateless address auto configuration IPv6 addresses allocated using the P-GW service(s) on this system. |

| Field | Description |
|-----------------------------------|--|
| Local pool addr assign | The total number of local IP pool IPv6 addresses allocated using the P-GW service(s) on this system. |
| Static addr assign | The total number of static IPv6 addresses allocated using the P-GW service(s) on this system. |
| Radius provided addr assign | The total number of RADIUS-provided IPv6 addresses allocated using the P-GW service(s) on this system. |
| SGi tunneling statistics | |
| Total IPv4 tunnel sessions | The total number of IPv4 tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| IP-in-IP tun sessn active | The total number of active IP-in-IP tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| IP-in-IP tun sessions setup | The total number of setup IP-in-IP tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| IP-in-IP tun sessions released | The total number of released IP-in-IP tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| GRE-tun sessions active | The total number of active GRE tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| GRE-tun sessions setup | The total number of setup GRE tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| GRE-tun session release | The total number of released GRE tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| Total IPv6 tunneled sessions | The total number of IPv6 tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| 6to4 tun sessions active | The total number of active IPv4-in-IPv6 tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| 6to4 tun session setup | The total number of setup IPv4-in-IPv6 tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| 6to4 tun sessions released | The total number of released IPv4-in-IPv6 tunnel sessions using the P-GW service(s) SGi interface(s) on this system. |
| Subscriber PLMN Statistics | |
| Home subscribers sessions | The total number of home subscriber sessions using the P-GW service(s) on this system. |
| Sessions active | The total number of active home subscriber sessions using the P-GW service(s) on this system. |

| Field | Description |
|----------------------------------|--|
| Sessions setup | The total number of setup home subscriber sessions using the P-GW service(s) on this system. |
| Sessions released | The total number of released home subscriber sessions using the P-GW service(s) on this system. |
| Roaming subscribers sessions | The total number of roaming subscriber sessions using the P-GW service(s) on this system. |
| Sessions active | The total number of active roaming subscriber sessions using the P-GW service(s) on this system. |
| Sessions setup | The total number of setup roaming subscriber sessions using the P-GW service(s) on this system. |
| Sessions released | The total number of released roaming subscriber sessions using the P-GW service(s) on this system. |
| Visiting subscribers sessions | The total number of visiting subscriber sessions using the P-GW service(s) on this system. |
| Sessions active | The total number of active visiting subscriber sessions using the P-GW service(s) on this system. |
| Sessions setup | The total number of setup visiting subscriber sessions using the P-GW service(s) on this system. |
| Sessions released | The total number of released visiting subscriber sessions using the P-GW service(s) on this system. |
| Subscriber QoS Statistics | |
| Total bearers active | |
| QCI 1 - 9 | The total number of active bearers with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of active bearers with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of active bearers with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total bearers setup | |
| QCI 1 - 9 | The total number of setup bearers with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of setup bearers with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of setup bearers with a non-standard QCI (GBR) using the P-GW service(s) on this system. |

| Field | Description |
|-----------------------------------|--|
| Total bearers released | |
| QCI 1 - 9 | The total number of released bearers with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of released bearers with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of released bearers with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Subscriber Data Statistics | |
| Total Uplink packets forwarded | |
| QCI 1 - 9 | The total number of uplink packets forwarded with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of uplink packets forwarded with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of uplink packets forwarded with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Uplink bytes forwarded | |
| QCI 1 - 9 | The total number of uplink bytes forwarded with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of uplink bytes forwarded with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of uplink bytes forwarded with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Downlink packets forwarded | |
| QCI 1 - 9 | The total number of downlink packets forwarded with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of downlink packets forwarded with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of downlink packets forwarded with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Downlink bytes forwarded | |
| QCI 1 - 9 | The total number of downlink bytes forwarded with a QoS Class Index using the P-GW service(s) on this system. |

| Field | Description |
|---|--|
| Non-Std QCI (Non-GBR) | The total number of downlink bytes forwarded with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of downlink bytes forwarded with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Uplink packets dropped | |
| QCI 1 - 9 | The total number of uplink packets dropped with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of uplink packets dropped with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of uplink packets dropped with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Uplink bytes dropped | |
| QCI 1 - 9 | The total number of uplink bytes dropped with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of uplink bytes dropped with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of uplink bytes dropped with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Downlink packets dropped | |
| QCI 1 - 9 | The total number of downlink packets dropped with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of downlink packets dropped with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of downlink packets dropped with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| Total Downlink bytes dropped | |
| QCI 1 - 9 | The total number of downlink bytes dropped with a QoS Class Index using the P-GW service(s) on this system. |
| Non-Std QCI (Non-GBR) | The total number of downlink bytes dropped with a non-standard QCI (non-GBR) using the P-GW service(s) on this system. |
| Non-Std QCI (GBR) | The total number of downlink bytes dropped with a non-standard QCI (GBR) using the P-GW service(s) on this system. |
| 802.1p priority marking statistics | |

| Field | Description |
|---|---|
| Uplink: Priority 0-7 | The total number of packets sent in the uplink direction marked with a specific (0-7) 802.1p priority. Deprecated in release 16.0 and later. |
| Downlink: Priority 0-7 | The total number of packets sent in the downlink direction marked with a specific (0-7) 802.1p priority. Deprecated in release 16.0 and later. |
| Priority marking statistics | |
| Uplink: Priority 0-7 | The total number of packets sent in the uplink direction marked with an internal QoS priority. |
| Downlink: Priority 0-7 | The total number of packets sent in the downlink direction marked with an internal QoS priority. |
| Session Discovery Req statistics | |
| Total IMSI+IP lookup | This sub-group displays the total number of event information attempted, successful, and failed for the defined session discovery request rule. |
| External-Id Present Session Statistics | |
| Active Sessions | The total number of active External-Id sessions using the P-GW service(s) on this system. |
| Total Created Sessions | The total number of created External-Id sessions using the P-GW service(s) on this system. |
| Released Sessions | The total number of released External-Id sessions using the P-GW service(s) on this system |

show pgw-service statistics all-name

Displays statistics information for all P-GW services configured on the system.

| Field | Description |
|------------------------------------|---|
| Initiated PDNs By RAT-Type: | |
| EUTRAN | The total number of EUTRAN PDNs by RAT-Type. |
| UTRAN | The total number of UTRANs PDNs by RAT-Type. |
| GERAN | The total number of GERANs PDNs by RAT-Type. |
| S2A GTP | The total number of S2A GTP PDNs by RAT-Type. |
| S2B GTP | The total number of S2B GTP PDNs by RAT-Type |

| Field | Description |
|----------------------------------|---|
| S2B PMIP | The total number of S2B PMIP PDNs by RAT-Type |
| NB-IoT | The total number of NB-IoT PDNs. |
| LTE-M | The total number of LTE-M initiated PDNs. |
| WLAN | The total number of WLANs PDNs by RAT-Type. |
| Other | The total number of Others PDNs by RAT-Type. |
| Current PDNs by RAT-Type: | |
| EUTRAN | The total number of active EUTRAN PDNs by RAT-Type. |
| UTRAN | The total number of active UTRANs PDNs by RAT-Type. |
| GERAN | The total number of active GERANs PDNs by RAT-Type. |
| WLAN | The total number of active WLAN PDNs by RAT-Type. |
| NB-IoT | The total number of active NB-ToT PDNs. |
| LTE-M | The total number of active LTE-M PDNs. |
| Other | The total number of Others PDNs by RAT-Type |