



# PCC-Service Addon Configuration Mode Commands

---

The PCC-Service Configuration Mode is used to link, consolidate and manage the policy logic for the network. The Addon mode specifies the commands related to addon instances for PCC-service.



---

**Important** This configuration mode is supported from StarOS Release 15.0 onwards.

---

## Command Modes

Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration

**configure** > **context** *context\_name* > **pcc-service** *service\_name* > **addon** *addon\_name*

Entering the above command sequence results in the following prompt:

```
[context_name]host_name(config-pcc-addon) #
```



---

**Important** The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

---



---

**Important** For information on common commands available in this configuration mode, refer to the [Common Commands](#) chapter.

---

- [associate-addon-state](#), on page 2
- [description](#), on page 3
- [duration](#), on page 4
- [status active](#), on page 5
- [time-allowance](#), on page 6
- [volume-allowance](#), on page 7

# associate-addon-state

<b>Product</b>	IPCF
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration <b>configure &gt; context</b> <i>context_name</i> > <b>pcc-service</b> <i>service_name</i> > <b>addon</b> <i>addon_name</i>
<b>Syntax Description</b>	<p><b>associate-addon-state</b> {<b>expired</b>   <b>grace</b>   <b>not-started</b>   <b>started</b>} {<b>action-set</b> <i>act_set_name</i> [<b>notification-template</b> <i>not_temp_name</i>]   <b>notification-template</b> <i>not_temp_name</i>}</p> <p><b>no associate-addon-state</b> {<b>expired</b>   <b>grace</b>   <b>not-started</b>   <b>started</b>}</p> <p><b>no</b></p> <p>Removes the configured associated addon state from this PCC service addon instance for IPCF configuration.</p> <p><b>expired</b></p> <p><b>grace</b></p> <p><b>not-started</b></p> <p><b>started</b></p> <p><b>action-set</b> <i>act_set_name</i></p> <p>The <i>act_set_name</i> must be an alphanumeric string from 1 through 63 characters.</p> <p><b>notification-template</b> <i>not_temp_name</i></p>

<b>Usage Guidelines</b>	<p>Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration.</p> <p>An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding <i>Condition-Group</i> is evaluated to <i>TRUE</i> within a subscriber policy/profile.</p> <p>A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service.</p> <p>Entering this command results in the following prompt:</p> <pre>[context_name]hostname(config-pcc-action-set)</pre>
-------------------------	--



**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

## Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

## description

<b>Product</b>	IPCF
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration <b>configure</b> > <b>context</b> <i>context_name</i> > <b>pcc-service</b> <i>service_name</i> > <b>addon</b> <i>addon_name</i>
<b>Syntax Description</b>	<b>action-set</b> <i>act_set_name</i> [ <b>-noconfirm</b> ] <b>no action-set</b> <i>act_set_name</i>

**no**

Removes the configured PCC-Action-Set from this PCC-service instance for IPCF configuration.

***act\_set\_name***

Identifies the name of the PCC-Action-Set which is to be created or modified through this command.

The *act\_set\_name* must be an alphanumerical string from 1 through 63 characters.

**-noconfirm**

Indicates that the command is to execute without any additional prompt and confirmation from the user.

<b>Usage Guidelines</b>	Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration. An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding <i>Condition-Group</i> is evaluated to <i>TRUE</i> within a subscriber policy/profile. A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service. Entering this command results in the following prompt: <pre>[context_name]hostname(config-pcc-action-set)</pre>
-------------------------	--



**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

### Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

## duration

**Product** IPCF

**Privilege** Security Administrator, Administrator

**Command Modes** Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration

```
configure > context context_name > pcc-service service_name > addon addon_name
```

**Syntax Description** **action-set** *act\_set\_name* [-noconfirm]  
**no action-set** *act\_set\_name*

**no**

Removes the configured PCC-Action-Set from this PCC-service instance for IPCF configuration.

***act\_set\_name***

Identifies the name of the PCC-Action-Set which is to be created or modified through this command.

The *act\_set\_name* must be an alphanumeric string from 1 through 63 characters.

**-noconfirm**

Indicates that the command is to execute without any additional prompt and confirmation from the user.

### Usage Guidelines

Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration.

An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding *Condition-Group* is evaluated to *TRUE* within a subscriber policy/profile.

A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service.

Entering this command results in the following prompt:

```
[context_name]hostname(config-pcc-action-set)
```



**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

### Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

## status active

<b>Product</b>	IPCF
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration <b>configure</b> > <b>context</b> <i>context_name</i> > <b>pcc-service</b> <i>service_name</i> > <b>addon</b> <i>addon_name</i>

<b>Syntax Description</b>	<b>action-set</b> <i>act_set_name</i> [ <b>-noconfirm</b> ] <b>no action-set</b> <i>act_set_name</i>
---------------------------	---

**no**

Removes the configured PCC-Action-Set from this PCC-service instance for IPCF configuration.

***act\_set\_name***

Identifies the name of the PCC-Action-Set which is to be created or modified through this command.

The *act\_set\_name* must be an alphanumerical string from 1 through 63 characters.

**-noconfirm**

Indicates that the command is to execute without any additional prompt and confirmation from the user.

### Usage Guidelines

Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration.

An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding *Condition-Group* is evaluated to *TRUE* within a subscriber policy/profile.

A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service.

Entering this command results in the following prompt:

```
[context_name]hostname(config-pcc-action-set)
```



**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

### Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

# time-allowance

<b>Product</b>	IPCF
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration <b>configure</b> > <b>context</b> <i>context_name</i> > <b>pcc-service</b> <i>service_name</i> > <b>addon</b> <i>addon_name</i>
<b>Syntax Description</b>	<b>action-set</b> <i>act_set_name</i> [ <b>-noconfirm</b> ] <b>no action-set</b> <i>act_set_name</i>

## no

Removes the configured PCC-Action-Set from this PCC-service instance for IPCF configuration.

## *act\_set\_name*

Identifies the name of the PCC-Action-Set which is to be created or modified through this command.

The *act\_set\_name* must be an alphanumeric string from 1 through 63 characters.

## **-noconfirm**

Indicates that the command is to execute without any additional prompt and confirmation from the user.

## Usage Guidelines

Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration.

An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding *Condition-Group* is evaluated to *TRUE* within a subscriber policy/profile.

A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service.

Entering this command results in the following prompt:

```
[context_name]hostname(config-pcc-action-set)
```




---

**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

---

## Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

# volume-allowance

<b>Product</b>	IPCF
<b>Privilege</b>	Security Administrator, Administrator
<b>Command Modes</b>	Exec > Global Configuration > Context Configuration > PCC Service Configuration > Addon Configuration <b>configure</b> > <b>context</b> <i>context_name</i> > <b>pcc-service</b> <i>service_name</i> > <b>addon</b> <i>addon_name</i>
<b>Syntax Description</b>	<p><b>action-set</b> <i>act_set_name</i> [<b>-noconfirm</b>]</p> <p><b>no action-set</b> <i>act_set_name</i></p> <p><b>no</b></p> <p>Removes the configured PCC-Action-Set from this PCC-service instance for IPCF configuration.</p> <p><b><i>act_set_name</i></b></p> <p>Identifies the name of the PCC-Action-Set which is to be created or modified through this command. The <i>act_set_name</i> must be an alphanumeric string from 1 through 63 characters.</p> <p><b>-noconfirm</b></p> <p>Indicates that the command is to execute without any additional prompt and confirmation from the user.</p>
<b>Usage Guidelines</b>	<p>Use this command to create/remove/configure an action-set in a PCC-service instance for IPCF Configuration. An Action-set indicates the policy and charging as well as event generation related decisions that will get activated when the corresponding <i>Condition-Group</i> is evaluated to <i>TRUE</i> within a subscriber policy/profile. A maximum of 512 PCC-Action-Sets can be configured in 1 instance of PCC-Service.</p> <p>Entering this command results in the following prompt:</p> <pre>[context_name]hostname(config-pcc-action-set)</pre>



**Important** For more information on PCC-Action-Set configuration, refer *PCC-Action-Set Configuration Mode Commands*.

## Example

Following command creates a PCC-action-set named *pcc\_act1* with in a PCC-service.

```
action-set pcc_act1
```

Following command removes a pre-configured PCC-action-set named *pcc\_act1* from a PCC-service.

```
no action-set pcc_act1
```

■ volume-allowance