



Ultra M MIB



Important

Not all aspects of this MIB are supported in this release. Refer to for information on the capabilities supported in this release.

```
-- *****
-- CISCO-ULTRAM-MIB.my
-- Copyright (c) 2017 by Cisco Systems Inc.
-- All rights reserved.
--
-- *****
CISCO-ULTRAM-MIB DEFINITIONS ::= BEGIN
IMPORTS
    MODULE-IDENTITY
    OBJECT-TYPE
    NOTIFICATION-TYPE
    Unsigned32
        FROM SNMPv2-SMI
    MODULE-COMPLIANCE
    NOTIFICATION-GROUP
    OBJECT-GROUP
        FROM SNMPv2-CONF
    TEXTUAL-CONVENTION
    DateAndTime
        FROM SNMPv2-TC
    ciscoMgmt
        FROM CISCO-SMI;
ciscoUltramMIB MODULE-IDENTITY
    LAST-UPDATED      "201707060000Z"
    ORGANIZATION      "Cisco Systems Inc."
    CONTACT-INFO
        "Cisco Systems
        Customer Service
        Postal: 170 W Tasman Drive
        San Jose CA  95134
        USA
        Tel: +1 800 553-NETS"
    DESCRIPTION
        "The MIB module to management of Cisco Ultra Services Platform
        (USP) also called Ultra-M Network Function Virtualization (NFV)
        platform. The Ultra-M platform is Cisco validated turnkey
        solution based on ETSI(European Telecommunications Standards
        Institute) NFV architetcure.
        It comprises of following architectural domains:
```

```

1. Management and Orchestration (MANO) these componets
enables infrastructure virtualization and life cycle management
of Cisco Ultra Virtual Network Functions (VNFs).
2. NFV Infrastructure (NFVI) set of physical resources to
provide NFV infrastructre for example servers switch chassis
and so on.
3. Virtualized Infrastructure Manager (VIM)
4. One or more Ultra VNFs.
Ultra-M platform provides a single point of management
(including SNMP APIs Web Console and CLI/Telnet Console) for
the resources across these domains within NFV PoD (Point of
Delivery).
This is also called Ultra-M manager throughout the context of
this MIB."
REVISION          "201707050000Z"
DESCRIPTION
  "- cultramFaultDomain changed to read-only in compliance.
  - Added a new fault code serviceFailure under
  'CultramFaultCode'.
  - Added a new notification cultramFaultClearNotif.
  - Added new notification group ciscoUltramMIBNotifyGroupExt.
  - Added new compliance group ciscoUltramMIBModuleComplianceRev01
  which deprecates ciscoUltramMIBModuleCompliance."
REVISION          "201706260000Z"
DESCRIPTION
  "Latest version of this MIB module."
 ::= { ciscoMgmt 849 }
CFaultCode ::= TEXTUAL-CONVENTION
  STATUS          current
  DESCRIPTION
    "A code identifying a class of fault."
  SYNTAX          INTEGER {
                        other(1) -- Other events
                        networkConnectivity(2) -- Network Connectivity
                                           -- Failure Events.
                        resourceUsage(3) -- Resource Usage Exhausted
                                           -- Event.
                        resourceThreshold(4) -- Resource Threshold
                                           -- crossing alarms
                        hardwareFailure(5) -- Hardware Failure Events
                        securityViolation(6) -- Security Alerts
                        configuration(7) -- Config Error Events
                        serviceFailure(8) -- Process/Service failures
                      }
CFaultSeverity ::= TEXTUAL-CONVENTION
  STATUS          current
  DESCRIPTION
    "A code used to identify the severity of a fault."
  SYNTAX          INTEGER {
                        emergency(1) -- System level FAULT impacting
                                           -- multiple VNFs/Services
                        critical(2) -- Critical Fault specific to
                                           -- VNF/Service
                        major(3) -- component level failure within
                                           -- VNF/service.
                        alert(4) -- warning condition for a service/VNF
                                           -- may eventually impact service.
                        informational(5) -- informational only does not
                                           -- impact service
                      }
CFaultDomain ::= TEXTUAL-CONVENTION
  STATUS          current
  DESCRIPTION

```

```

        "A code used to categorize Ultra-M fault domain."
SYNTAX          INTEGER {
                    hardware(1) -- Hardware including Servers L2/L3
                        -- Elements
                    vimOrchestrator(2) -- VIM under-cloud
                    vim(3) -- VIM manager such as OpenStack
                    uas(4) -- Ultra Automation Services Modules
                    vnf(5) -- VNF manager
                    vnfEM(6) -- Ultra VNF Element Manager
                    vnf(7) -- Ultra VNF
                }

-- Textual Conventions definition will be defined before this line
ciscoUltramMIBNotifs OBJECT IDENTIFIER
    ::= { ciscoUltramMIB 0 }
ciscoUltramMIBObjects OBJECT IDENTIFIER
    ::= { ciscoUltramMIB 1 }
ciscoUltramMIBConform OBJECT IDENTIFIER
    ::= { ciscoUltramMIB 2 }
-- Conformance Information Definition
ciscoUltramMIBCompliances OBJECT IDENTIFIER
    ::= { ciscoUltramMIBConform 1 }
ciscoUltramMIBGroups OBJECT IDENTIFIER
    ::= { ciscoUltramMIBConform 2 }
ciscoUltramMIBModuleCompliance MODULE-COMPLIANCE
    STATUS          deprecated
    DESCRIPTION
        "The compliance statement for entities that support
        the Cisco Ultra-M Fault Managed Objects"
    MODULE          -- this module
    MANDATORY-GROUPS {
        ciscoUltramMIBMainObjectGroup
        ciscoUltramMIBNotifyGroup
    }
    ::= { ciscoUltramMIBCompliances 1 }
ciscoUltramMIBModuleComplianceRev01 MODULE-COMPLIANCE
    STATUS          current
    DESCRIPTION
        "The compliance statement for entities that support
        the Cisco Ultra-M Fault Managed Objects."
    MODULE          -- this module
    MANDATORY-GROUPS {
        ciscoUltramMIBMainObjectGroup
        ciscoUltramMIBNotifyGroup
        ciscoUltramMIBNotifyGroupExt
    }
    OBJECT          cultramFaultDomain
    MIN-ACCESS      read-only
    DESCRIPTION
        "cultramFaultDomain is read-only."
    ::= { ciscoUltramMIBCompliances 2 }
ciscoUltramMIBMainObjectGroup OBJECT-GROUP
    OBJECTS          {
        cultramNFVIdentity
        cultramFaultDomain
        cultramFaultSource
        cultramFaultCreationTime
        cultramFaultSeverity
        cultramFaultCode
        cultramFaultDescription
    }
    STATUS          current
    DESCRIPTION
        "A collection of objects providing Ultra-M fault information."
    ::= { ciscoUltramMIBGroups 1 }

```

```

ciscoUltramMIBNotifyGroup NOTIFICATION-GROUP
    NOTIFICATIONS { cultramFaultActiveNotif }
    STATUS        current
    DESCRIPTION
        "The set of Ultra-M notifications defined by this MIB"
    ::= { ciscoUltramMIBGroups 2 }
ciscoUltramMIBNotifyGroupExt NOTIFICATION-GROUP
    NOTIFICATIONS { cultramFaultClearNotif }
    STATUS        current
    DESCRIPTION
        "The set of Ultra-M notifications defined by this MIB"
    ::= { ciscoUltramMIBGroups 3 }
cultramFaultTable OBJECT-TYPE
    SYNTAX          SEQUENCE OF CultramFaultEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "A table of Ultra-M faults. This table contains active
        faults."
    ::= { ciscoUltramMIBObjects 1 }
cultramFaultEntry OBJECT-TYPE
    SYNTAX          CultramFaultEntry
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "An entry in the Ultra-M fault table."
    INDEX           { cultramFaultIndex }
    ::= { cultramFaultTable 1 }
CultramFaultEntry ::= SEQUENCE {
    cultramFaultIndex      Unsigned32
    cultramNFVIdentity     OCTET STRING
    cultramFaultDomain     CFaultDomain
    cultramFaultSource     OCTET STRING
    cultramFaultCreationTime DateAndTime
    cultramFaultSeverity   CFaultSeverity
    cultramFaultCode       CFaultCode
    cultramFaultDescription OCTET STRING
}
cultramFaultIndex OBJECT-TYPE
    SYNTAX          Unsigned32
    MAX-ACCESS      not-accessible
    STATUS          current
    DESCRIPTION
        "This object uniquely identifies a specific instance of a
        Ultra-M fault.
        For example if two separate computes have a service level
        Failure then each compute will have a fault instance with a
        unique index."
    ::= { cultramFaultEntry 1 }
cultramNFVIdentity OBJECT-TYPE
    SYNTAX          OCTET STRING (SIZE (1..512))
    MAX-ACCESS      read-write
    STATUS          current
    DESCRIPTION
        "This object uniquely identifies the Ultra-M PoD on which this
        fault is occurring.
        For example this identity can include host-name as well
        management IP where manager node is running
        'Ultra-M-San-Francisco/172.10.185.100'."
    ::= { cultramFaultEntry 2 }
cultramFaultDomain OBJECT-TYPE
    SYNTAX          CFaultDomain
    MAX-ACCESS      read-write
    STATUS          current

```

```

DESCRIPTION
    "A unique Fault Domain that has fault."
 ::= { cultramFaultEntry 3 }
cultramFaultSource OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1..512))
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "This object uniquely identifies the resource with the fault
        domain where this fault is occurring. For example this can
        include host-name as well management IP of the resource
        'UCS-C240-Server-1/192.100.0.1'."
 ::= { cultramFaultEntry 4 }
cultramFaultCreationTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The date and time when the fault was occurred."
 ::= { cultramFaultEntry 5 }
cultramFaultSeverity OBJECT-TYPE
    SYNTAX      CFaultSeverity
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "A code identifying the perceived severity of the fault."
 ::= { cultramFaultEntry 6 }
cultramFaultCode OBJECT-TYPE
    SYNTAX      CFaultCode
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "A code uniquely identifying the fault class."
 ::= { cultramFaultEntry 7 }
cultramFaultDescription OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1..2048))
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "A human-readable message providing details about the fault."
 ::= { cultramFaultEntry 8 }
cultramFaultActiveNotif NOTIFICATION-TYPE
    OBJECTS      {
        cultramNFVIdenity
        cultramFaultDomain
        cultramFaultSource
        cultramFaultCreationTime
        cultramFaultSeverity
        cultramFaultCode
        cultramFaultDescription
    }
    STATUS      current
    DESCRIPTION
        "This notification is generated by a Ultra-M manager whenever a
        fault is active."
 ::= { ciscoUltramMIBNotifs 1 }
cultramFaultClearNotif NOTIFICATION-TYPE
    OBJECTS      {
        cultramNFVIdenity
        cultramFaultDomain
        cultramFaultSource
        cultramFaultCreationTime
        cultramFaultSeverity
        cultramFaultCode
    }

```

```
        cultramFaultDescription
    }
    STATUS          current
    DESCRIPTION
        "This notification is generated by a Ultra-M manager whenever a
        fault is cleared."
    ::= { ciscoUltramMIBNotifs 2 }
END
```