



Sample AutoVNF VNF Configuration File

```
autovnf:secure-token em-login
  user      ubuntu
  password *****
!
autovnf:secure-token admin
  user      admin
  password *****
!
autovnf:secure-token oper
  user      admin
  password *****
!
autovnf:secure-token security
  user      admin
  password *****
!
autovnf:secure-token staros
  user      admin
  password *****
!
autovnf-vnfm:secure-token netconf
  user      admin
  password *****
!
autovnf:network-catalog management-saegw
  pre-created CF-MGMT
  type      vlan
  ip-prefix 192.168.30.0/24
  dhcp      false
  ip-allocation-pool 192.168.30.200 192.168.30.202
!
!
autovnf:network-catalog orchestration-saegw
  pre-created ORCH
  type      vlan
  ip-prefix 192.168.50.0/24
  dhcp      false
  gateway   192.168.50.1
  ip-allocation-pool 192.168.50.204 192.168.50.209
!
!
autovnf:network-catalog di-internal-saegw
  pre-created DI-INTERNAL1
  type      vlan
  ip-prefix 192.168.211.0/24
  dhcp      false
  ip-allocation-pool 192.168.211.10 192.168.211.15
!
!
autovnf:network-catalog service-network-saegw-1
  pre-created SERVICE-NETWORK1
```

```

type      vlan
ip-prefix 192.168.201.0/24
dhcp      false
ip-allocation-pool 192.168.201.200 192.168.201.204
!
!
autovnf:network-catalog service-network-saegw-2
pre-created SERVICE-NETWORK2
type      vlan
ip-prefix 2600:4:200:ae21::/123
dhcp      false
ip-allocation-pool 2600:4:200:ae21::4 2600:4:200:ae21::7
!
!
autovnf:vdu-catalog em-saegw
vdu-type          element-manager
login-credential em-login
scm admin admin
scm oper oper
scm security security
ha-type           one-to-one
health-check-frequency 10
health-probe-max-miss 6
recovery-type     recovery-restart
image pre-created EM-Image-2104
flavor pre-created EM
flavor anti-affinity-placement true
!
autovnf:vdu-catalog vdu-cf-saegw
vdu-type          control-function
login-credential staros
ha-type           one-to-one
health-check-frequency 10
health-probe-max-miss 6
recovery-type     recovery-restart
image pre-created CF-Image-2104
neds netconf
ned-id            cisco-staros-nc
port-number       830
authentication    staros
!
flavor pre-created spr-cf
flavor anti-affinity-placement true
configuration staros_config.txt
apply-at day-zero
source-url file:///opt/cisco/usp/uploads/system-saegw.cfg
!
!
autovnf:vdu-catalog vdu-sf-saegw
vdu-type          session-function
upp cores         30
upp crypto-cores 0
upp service-mode vpc
upp disable-mcdma false
upp disable-numa false
upp param IFTASK_DISABLE_RESTART_OPT
value yes
upp param IFTASK_VNPU_TX_MODE value
value 1
ha-type           one-to-one
health-check-frequency 10
health-probe-max-miss 6
recovery-type     recovery-restart
image pre-created SF-Image-2104
flavor pre-created spr-sf
flavor anti-affinity-placement true
!
deployments ugp-saegw
enable-vim        false
vnfm-instance     vnfm-pre-created-esc
vim id            vim1
vim user          saegw
vim project       saegw

```

```

vnf-em vdu-id          em-saegw
vnf-em high-availability true
vnf-em ha-vip           192.168.50.203
vnf-em orchestration-network orchestration-saegw
vnf-em orchestration-fixed-ip 192.168.50.200
!
vnf-em orchestration-fixed-ip 192.168.50.201
!
vnf-em orchestration-fixed-ip 192.168.50.202
!
vnf-param type vpc
vnf-param configuration domain-name cisco.com
!
vnf-param configuration dns-servers 171.70.168.183
!
vnf-param configuration dns-servers 171.78.189.11
!
vnf-param configuration DI_INTERFACE_MTU 1500
!
vnf-param configuration alive-timeout 600
!
vnf-param internal-network di-internal-saegw
!
infra-element-groups di-chassis
instances 1
vdus CF
  vdu-ref          vdu-cf-saegw
  instances        2
  high-availability true
  ha-vip           192.168.30.202
  ha-network       management-saegw
  instance-volume 0
    volume HD-RAID1
      type   LUKS
      bus    ide
      bootable false
    !
    volume cf1-boot-2104
      type   LUKS
      bus    ide
      bootable true
    !
  !
  instance-volume 1
    volume HD-RAID2
      type   LUKS
      bus    ide
      bootable false
    !
    volume cf2-boot-2104
      type   LUKS
      bus    ide
      bootable true
    !
  !
  interfaces di_intf
    network di-internal-saegw
  !
  interfaces mgmt
    network management-saegw
    uplink-actions mount-ned-nc
  !
  allowed-address-pair 192.168.40.0/24
  allowed-address-pair 192.168.60.0/24
  !
  !
  interfaces orch
    network orchestration-saegw
  !
  !
vdus SF
  vdu-ref    vdu-sf-saegw
  instances 4

```

```
interfaces di_intf
  network di-internal-saegw
!
interfaces orch
  network orchestration-saegw
!
interfaces svc_intf1
  network service-network-saegw-1
  allowed-address-pair 0.0.0.0/0
!
!
interfaces svc_intf2
  network service-network-saegw-2
  allowed-address-pair ::/0
!
!
!
```