



boot_uas.py Help

```
./boot_uas.py --help
usage: boot_uas.py [-h] [--version] [--hostname HOSTNAME]
                  [--delete DELETE [DELETE ...]] [--recover RECOVER]
                  [--delete-uas] [--json] [--openstack] [--kvm]
                  [--autodeploy] [--autoit] [--autovnf]
                  [--os_auth_url OS_AUTH_URL]
                  [--os_tenant_name OS_TENANT_NAME]
                  [--os_tenant_id OS_TENANT_ID]
                  [--os_project_name OS_PROJECT_NAME]
                  [--os_project_id OS_PROJECT_ID]
                  [--os_project_domain_name OS_PROJECT_DOMAIN_NAME]
                  [--os_project_domain_id OS_PROJECT_DOMAIN_ID]
                  [--os_username OS_USERNAME] [--os_user_id OS_USER_ID]
                  [--os_password OS_PASSWORD]
                  [--os_user_domain_name OS_USER_DOMAIN_NAME]
                  [--os_user_domain_id OS_USER_DOMAIN_ID]
                  [--os_identity_api_version OS_IDENTITY_API_VERSION]
                  [--net NET [NET ...]] [--ip [IPADDR [IPADDR ...]]]
                  [--orch-interface ORCH_INTF] [--gateway DEFAULT_GW]
                  [--gateway_if DEFAULT_GW_IDX] [--ha] [--ha-vip HA_VIP]
                  [--ha-net HA_VIP_NET] [--ha-secret HA_SECRET]
                  [--floating-ip [FLOATING_IP]]
                  [--external-network PUBLICNET] [--flavor FLAVOR]
                  [--avail_zone AVAIL_ZONE] [--image IMAGE]
                  [--ssh_key_file SSH_KEY_FILE] [--password PASSWORD]
                  [--admin ADMIN] [--oper OPER] [--security SECURITY]

optional arguments:
  -h, --help            show this help message and exit
  --version            show program's version number and exit
  --hostname HOSTNAME  Hostname prefix
  --delete DELETE [DELETE ...]
                        Delete UAS deployment. Applicable only for OpenStack
  --recover RECOVER    Recover UAS deployment.
  --delete-uas         Deletes the UAS deployment. Applicable only for KVM
  --json              Output Data in JSON

Specify the infrastructure to be used for the UAS VM:
  --openstack          Use Openstack Infrastructure
  --kvm               Use KVM Infrastructure

Specify the type of UAS VM to be instantiated:
  --autodeploy        Boot AutoDeploy UAS type
  --autoit            Boot AutoIT UAS type
  --autovnf          Boot AutoVNF UAS type

OpenStack configuration to instantiate AutoVNF cluster.
You can either source RC file or provide them on command line:
  --os_auth_url OS_AUTH_URL
                        OS Auth-URL, defaults to env[OS_AUTH_URL].
  --os_tenant_name OS_TENANT_NAME
```

```

        OS Tenant Name, defaults to env[OS_TENANT_NAME].
--os_tenant_id OS_TENANT_ID
        OS Tenant ID, defaults to env[OS_TENANT_ID].
--os_project_name OS_PROJECT_NAME
        OS Project Name, defaults to env[OS_PROJECT_NAME].
--os_project_id OS_PROJECT_ID
        OS Project ID, defaults to env[OS_PROJECT_ID].
--os_project_domain_name OS_PROJECT_DOMAIN_NAME
        OS Project Domain Name, defaults to
env[OS_PROJECT_DOMAIN_NAME].
--os_project_domain_id OS_PROJECT_DOMAIN_ID
        OS Project Domain ID, defaults to
env[OS_PROJECT_DOMAIN_ID].
--os_username OS_USERNAME
        OS Username, defaults to env[OS_USERNAME].
--os_user_id OS_USER_ID
        OS User ID, defaults to env[OS_USER_ID].
--os_password OS_PASSWORD
        OS Password, defaults to env[OS_PASSWORD].
--os_user_domain_name OS_USER_DOMAIN_NAME
        OS User Domain Name, defaults to
env[OS_USER_DOMAIN_NAME].
--os_user_domain_id OS_USER_DOMAIN_ID
        OS User Domain ID, defaults to env[OS_USER_DOMAIN_ID].
--os_identity_api_version OS_IDENTITY_API_VERSION
        OS Identity API Version, defaults to
env[OS_IDENTITY_API_VERSION].

Networks to be used, first network is used as orchestration:
--net NET [NET ...] Ordered list of networks (name or uuid) to attach to
AutoVNF Cluster.
--ip [IPADDR [IPADDR ...]]
        Static IP, default is DHCP
--orch-interface ORCH_INTF
        Orchestration Interface

Default gateway parameters.:
--gateway DEFAULT_GW Default Gateway IP Address, needed only in case of
static IP
--gateway_if DEFAULT_GW_IDX
        Interface index to associate default route, default is
first interface.

High-Availability parameters:
--ha Enable High-Availability
--ha-vip HA_VIP Virtual IP Address (VIP) for cluster
--ha-net HA_VIP_NET Network used to assign the VIP address
--ha-secret HA_SECRET
        HA Secret for the cluster

Floating IP Parameters:
--floating-ip [FLOATING_IP]
        Enable floating IP association to VIP port
--external-network PUBLICNET
        External Network to allocate floating IP.

VM specific parameters:
--flavor FLAVOR VM Flavor (name or uuid), default is 'm1.medium'
--avail_zone AVAIL_ZONE
        The availability zone for AutoVNF placement.
--image IMAGE
        Image name or UUID from VIM

AutoVNF VM Login Parameters, if not provided, user will be prompted:
--ssh_key_file SSH_KEY_FILE
        Path to SSH key file to be used as authorised key for
login as 'ubuntu'
--password PASSWORD
        Password for login as 'ubuntu', this is required if
SSH key is not provided

AutoVNF API Access parameters, if not provided, user will be prompted:
--admin ADMIN Password for AutoVNF admin user.
--oper OPER Password for AutoVNF oper user
--security SECURITY Password for AutoVNF security user

```