



Release Notes for Cisco ASR 901 Series Aggregation Services Router for Cisco IOS Release 15.4(3)S4

First Published Date: September 2015

This release notes is for the Cisco ASR 901 Series Aggregation Services Router for Cisco IOS Release 15.4(3)S4 and contains the following sections:

- [Introduction, page 1](#)
- [System Specifications and Memory Details, page 2](#)
- [New and Changed Information, page 4](#)
- [Supported MIBs, page 4](#)
- [Caveats, page 4](#)
- [Troubleshooting, page 6](#)
- [Related Documentation, page 6](#)
- [Services and Support, page 6](#)

Introduction

The Cisco ASR 901 Series Aggregation Services Router is a cell-site access platform specifically designed to aggregate and transport mixed-generation radio access network (RAN) traffic. The router is used at the cell site edge as a part of a 2G, 3G, or 4G RAN.

The Cisco ASR 901 router helps enable a variety of RAN solutions by extending IP connectivity to devices using Global System for Mobile Communications (GSM), General Packet Radio Service (GPRS), Node Bs using High Speed Packet Access (HSPA) or Long Term Evolution (LTE), base transceiver stations (BTSs) using Enhanced Data Rates for GSM Evolution (EDGE), Code Division Multiple Access (CDMA), CDMA-2000, EVDO, or WiMAX, and other cell-site equipment.



It transparently and efficiently transports cell-site voice, data, and signaling traffic over IP using traditional T1 and E1 circuits, as well as alternative backhaul networks such as Carrier Ethernet and DSL, Ethernet in the First Mile (EFM), and WiMAX. It also supports standards-based Internet Engineering Task Force (IETF) Internet protocols over the RAN transport network, including those standardized at the Third-Generation Partnership Project (3GPP) for IP RAN transport. Custom designed for the cell site, the Cisco ASR 901 router features a small form factor, extended operating temperature, and cell-site DC input voltages.

Table 1 lists the Cisco ASR 901 1G Router model versions.

Table 1 Cisco ASR 901 1G Router Models

Power Source	TDM + Ethernet Version	Ethernet Version
DC Power	<ul style="list-style-type: none"> A901-12C-FT-D A901-4C-FT-D 	<ul style="list-style-type: none"> A901-12C-F-D A901-4C-F-D
AC Power	<ul style="list-style-type: none"> none 	<ul style="list-style-type: none"> none

Table 2 lists the Cisco ASR 901 10G Router model versions.

Table 2 Cisco ASR 901 10G Router Models

Power Source	TDM + Ethernet Version	Ethernet Version
DC Power	<ul style="list-style-type: none"> A901-6CZ-FT-D 	<ul style="list-style-type: none"> A901-6CZ-F-D A901-6CZ-FS-D
AC Power	<ul style="list-style-type: none"> A901-6CZ-FT-A 	<ul style="list-style-type: none"> A901-6CZ-F-A A901-6CZ-FS-A



Note

Some of the Cisco ASR 901 models have port based licensing. For more details, see the [Licensing](#) chapter in Cisco ASR 901 Series Aggregation Services Router Software Configuration Guide.

System Specifications and Memory Details

Table 3 lists the supported system configurations and memory details for the Cisco ASR 901 router:

Table 3 Cisco IOS Release 15.4(3)S4 Memory Details

Platform	Software Image	Flash Memory	DRAM Memory	Runs From
Cisco ASR 901 Series Aggregation Services Router TDM version	asr901-universalk9-mz	128 MB	512 MB	RAM

Table 3 Cisco IOS Release 15.4(3)S4 Memory Details

Platform	Software Image	Flash Memory	DRAM Memory	Runs From
Cisco ASR 901 Series Aggregation Services Router, Ethernet version	asr901-universalk9-mz	128 MB	512 MB	RAM
Cisco ASR 901 Series Aggregation Services Router, IPsec enabled Ethernet version	asr901sec-universalk9.mz	256 MB	512 MB	RAM

Determining the Software Version

To determine the image and version of Cisco IOS software running on your Cisco ASR 901 router, log in to the router and enter the **show version** command in the EXEC mode:

The following example shows output from Cisco ASR 901 router that supports normal IOS software.

```
ASR901_1> show version
```

```
Cisco IOS Software, 901 Software (ASR901-UNIVERSALK9-M), Version 15.4(3)S4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Wed 30-Sep-15 07:18 by prod_rel_team
```

```
ROM: System Bootstrap, Version 15.5(3r)S1, RELEASE SOFTWARE (fc1)
```

```
ASR901_1 uptime is 1 hour, 0 minutes
System returned to ROM by reload at 23:58:47 IST Wed Sep 30 2015
System restarted at 00:02:31 IST Thu Oct 1 2015
System image file is
"tftp://202.153.144.25//auto/tftp-blr-users3/pguntur/images/CCO_ASR901"
Last reload type: Normal Reload
Last reload reason: Reload Command
```

The following example shows output from Cisco ASR 901 Series Aggregation Services Router, IPsec enabled Ethernet version.

```
node6> show version
```

```
Cisco IOS Software, 901 Software (ASR901SEC-UNIVERSALK9-M), Version 15.4(3)S4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2015 by Cisco Systems, Inc.
Compiled Wed 30-Sep-15 07:44 by prod_rel_team
```

```
ROM: System Bootstrap, Version 15.5(3r)S1, RELEASE SOFTWARE (fc1)
```

```
SANR1 uptime is 2 hours, 27 minutes
System returned to ROM by reload at 22:34:33 IST Wed Sep 30 2015
System restarted at 05:06:44 IST Thu Oct 1 2015
System image file is
"tftp://202.153.144.25//auto/tftp-blr-users3/pguntur/images/CCO_Santorini"
Last reload type: Normal Reload
Last reload reason: Reload Command
```

New and Changed Information

- [New Hardware Features in Release 15.4\(3\)S4, page 4](#)
- [New Software Features in Release 15.4\(3\)S4, page 4](#)
- [Modified Software Features in Release 15.4\(3\)S4, page 4](#)

New Hardware Features in Release 15.4(3)S4

There are no new hardware features in this release.

New Software Features in Release 15.4(3)S4

There are no new software features in this release.

Modified Software Features in Release 15.4(3)S4

There are no modified features in this release.

Supported MIBs

To see the list of MIBS supported on this release, go to the following URL and search using the Image Name: <http://tools.cisco.com/ITDIT/MIBS/MainServlet>

Caveats

Caveats describe unexpected behavior in Cisco IOS software releases. Severity 1 caveats are the most serious caveats, severity 2 caveats are less serious, and severity 3 caveats are the least serious of these three severity levels. Only select severity 3 caveats are listed.

This section contains the following topics:

- [Bug Search Tool](#)
- [Open Caveats](#)
- [Resolved Caveats](#)

Bug Search Tool

The Caveats section only includes the bug ID and a short description of the bug. For details on the symptoms, conditions, and workaround for a particular bug you must use the Bug Search Tool.

Use the following link to access the tool: <https://tools.cisco.com/bugsearch/search>

You will be prompted to log into Cisco.com. After successful login, the Bug Search Tool page opens. Use the Help link in the Bug Search Tool to obtain detailed help.

Open Caveats

This section provides information about the open caveats for the Cisco ASR 901 router running Cisco IOS Release 15.4(3)S4.

Bug ID	Description
CSCuv88016	Unnecessary L3 control proto pkts sent to CPU in pure-switch scenarios
CSCuw49842	Error messages are seen on console while disabling Mcast

Resolved Caveats

This section provides information about the resolved caveats for the Cisco ASR 901 router running Cisco IOS Release 15.4(3)S4.

Bug ID	Description
CSCuu32285	"permit any any" config should override default "deny any any" FP entry
CSCut90473	Extra FP entry consumed in TCAM after removing all ACE entries from ACL
CSCuu07921	Extra IFP created by ACL for 'default deny rule' when config explicitly
CSCuu22054	untagged EVC does not pass traffic
CSCuq53991	ARP flush optimization triggered with MAC age-out on vlan
CSCuv43536	Negative counters FFFFFFFE0 with multicast data in Tengig interface
CSCut86932	observing error messages when defaulting router interface receiving igmp
CSCuv31196	Random MPLS Packet Drops With IP Multicast Over L3 Ring on ASR901
CSCut65927	ASR901 Hangs @ Autoinstall Process Starting while the device is booting
CSCur87571	Exceed action is nt working in policer having match cos as 2nd statement
CSCuv09066	Incorrect P-bit for CPU originated packets once EoMPLS VC on
CSCup66406	ASR901: OSPF prefixes more than 60 fails to advertise over IPsec tunnel
CSCuu28678	ASR901: AIS on TDM AC does not trigger L-bit to be set in SAToP CW
CSCuu28735	ASR901:incoming SAToP packets with L-bit are ignored after CEM flap
CSCuu26149	ASR901: BITS/E1 not sending out signal once the selected PTP source removed
CSCut31379	ASR901: G.8265.1 TP BMCA does not work after unconfig M1 and config M2
CSCuu56933	observing error msg when removing transport ip and clock source in ptp
CSCuu62478	Licensing infrastructure is not initialized during boot up

Troubleshooting

The following sections describe troubleshooting commands you can use with the Cisco ASR 901 Series Aggregation Services Router.

Collecting Data for Router Issues

To collect data for reporting router issues, issue the following command:

- **show tech-support**—Displays general information about the router if it reports a problem.

Collecting Data for ROMMON Issues

To collect data for ROMMON issues, issue the following command while in the EXEC mode:

- **show rom-monitor**—Displays currently selected ROM monitor.



Note

If you contact Cisco support for assistance, we recommend that you provide any crashinfo files stored in flash memory. For more information about crashinfo files, see http://www.cisco.com/en/US/products/hw/routers/ps167/products_tech_note09186a00800a6743.shtml.

Related Documentation

Documents related to the Cisco ASR 901 Series Aggregation Services Router include the following:

- *Cisco ASR 901 Series Aggregation Services Router Hardware Installation Guide*
- *Cisco ASR 901 Series Aggregation Services Router Software Configuration Guide*
- *Regulatory Compliance and Safety Information for Cisco ASR 901 Series Aggregation Services Routers*
- *Cisco ASR 901 Series Aggregation Services Router Series MIB Specifications Guide*

To access the related documentation on Cisco.com, go to:

- Cisco ASR 901 1G Router home page:
http://www.cisco.com/en/US/partner/products/ps12077/tsd_products_support_series_home.html
- Cisco ASR 901 10G Router home page:
<http://www.cisco.com/c/en/us/support/routers/asr-901-10g-series-aggregation-services-routers/tsd-products-support-series-home.html>

Services and Support

For information on obtaining documentation, using the Cisco Bug Search Tool (BST), submitting a service request, and gathering additional information, see *What's New in Cisco Product Documentation* at: <http://www.cisco.com/c/en/us/td/docs/general/whatsnew/whatsnew.html>.

Subscribe to *What's New in Cisco Product Documentation*, which lists all new and revised Cisco technical documentation as an RSS feed and delivers content directly to your desktop using a reader application. The RSS feeds are a free service.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Release Notes for Cisco ASR 901 Aggregation Series Router for Cisco IOS Release 15.4(3)S4

© 2015, Cisco Systems, Inc All rights reserved.

