



## Debug Commands

---

- [connectorctl enabledebug](#), on page 2
- [connectorctl viewdebuglogs](#), on page 3
- [connectorctl disabledebug](#), on page 4

# connectorctl enabledebug

This command enables the debug mode for the Cisco Spaces: Connector.

## Parameters

None.

## connectorctl enabledebug

---

### Usage Guidelines

```
[cmxadmin@cmxnew ~]$ connectorctl enabledebug
Please enter a Valid MAC Address [Format: xx:xx:xx:xx:xx:xx]: 00:0c:xx:xx:xx:xx
Please choose a debug level [Default: MESSAGE] [MESSAGE]:
Debug enabled successfully: MESSAGE$
```

### Related Topics

[connectorctl viewdebuglogs](#), on page 3

[connectorctl disabledebug](#), on page 4

# connectorctl viewdebuglogs

This command displays the debugs logs.

## Parameters

None.

## connectorctl viewdebuglogs

---

### Usage Guidelines

```
[cmxadmin@cmxadmin ~]$ connectorctl viewdebuglogs
Please enter the mac address:: 00:0c:xx:xx:xx:xx
2019-11-21 23:15:55 [nioEventLoopGroup-6-1] INFO com.cisco.cmx.nmsp.protomapping.MappingEngine
- tenantId: "427"
macAddress: "00: 0c :xx: xx: xx : xx"
controllerIpAddress: "10.22.244.28"
messageId: 15
measurementNotification {
  tenantId: "427"
  tenantId: "427"
  macAddress: "00:0c:xx:xx:xx:xx"
  controllerIpAddress: "10.22.244.28"
  deviceCategory {
    deviceClass: TAGS_2
  }
  transmitPower {
    value: 19
  }
}
apRssiMeasurements {
  entries {
    apMacAddress: "08 :cc: xx : xx : xx :xx"
    rssi: -29
    timestamp: 278
  }
}
```

# connectorctl disabledebug

This command disables the debug mode for the Cisco Spaces: Connector.

## Parameters

None.

## connectorctl disabledebug

---

### Usage Guidelines

```
[cmxadmin@cmxnew ~]$ connectorctl disabledebug
Please enter a Valid MAC Address [Format: xx:xx:xx:xx:xx:xx]: 00:0c:xx:xx:xx:xx
Please choose a debug level [Default: MESSAGE] [MESSAGE]:
Debug disabled successfully: MESSAGE$
```