



Show Commands: r to z

- [show radius acct detailed, on page 4](#)
- [show radius acct statistics, on page 5](#)
- [show radius auth detailed, on page 6](#)
- [show radius auth statistics, on page 7](#)
- [show radius avp-list, on page 8](#)
- [show radius summary, on page 9](#)
- [show redundancy interfaces, on page 10](#)
- [show redundancy latency, on page 11](#)
- [show redundancy mobilitymac, on page 12](#)
- [show redundancy peer-route summary, on page 13](#)
- [show redundancy peer-system statistics, on page 14](#)
- [show redundancy statistics, on page 15](#)
- [show redundancy summary, on page 16](#)
- [show redundancy timers, on page 17](#)
- [show remote-lan, on page 18](#)
- [show reset, on page 20](#)
- [show rfid client, on page 21](#)
- [show rfid config, on page 22](#)
- [show rfid detail, on page 23](#)
- [show rfid summary, on page 24](#)
- [show rf-profile summary, on page 25](#)
- [show rf-profile details, on page 26](#)
- [show rogue adhoc custom summary, on page 29](#)
- [show rogue adhoc detailed, on page 30](#)
- [show rogue adhoc friendly summary , on page 32](#)
- [show rogue adhoc malicious summary, on page 33](#)
- [show rogue adhoc unclassified summary , on page 34](#)
- [show rogue adhoc summary, on page 35](#)
- [show rogue ap clients, on page 36](#)
- [show rogue ap custom summary , on page 38](#)
- [show rogue ap detailed, on page 40](#)
- [show rogue ap friendly summary, on page 43](#)
- [show rogue ap malicious summary, on page 45](#)

- [show rogue ap summary](#), on page 47
- [show rogue ap unclassified summary](#), on page 50
- [show rogue auto-contain](#), on page 51
- [show rogue client detailed](#), on page 52
- [show rogue client summary](#), on page 53
- [show rogue ignore-list](#), on page 54
- [show rogue rule detailed](#), on page 56
- [show rogue rule summary](#), on page 58
- [show route kernel](#), on page 59
- [show route summary](#), on page 60
- [show rules](#), on page 61
- [show run-config](#), on page 62
- [show run-config startup-commands](#), on page 63
- [show serial](#), on page 64
- [show sessions](#), on page 65
- [show snmpcommunity](#), on page 66
- [show snmpengineID](#), on page 67
- [show snmptrap](#), on page 68
- [show snmpv3user](#), on page 69
- [show snmpversion](#), on page 70
- [show spanningtree port](#), on page 71
- [show spanningtree switch](#), on page 72
- [show stats port](#), on page 73
- [show stats switch](#), on page 75
- [show switchconfig](#), on page 77
- [show sysinfo](#), on page 78
- [show system iostat](#), on page 80
- [show system top](#), on page 81
- [show tacacs acct statistics](#), on page 85
- [show tacacs auth statistics](#), on page 86
- [show tacacs summary](#), on page 87
- [show tech-support](#), on page 88
- [show time](#), on page 89
- [show trapflags](#), on page 91
- [show traplog](#), on page 93
- [show tunnel profile summary](#), on page 94
- [show tunnel profile-detail](#), on page 95
- [show tunnel eogre-summary](#), on page 96
- [show tunnel eogre-statistics](#), on page 97
- [show tunnel eogre-domain-summary](#), on page 98
- [show tunnel eogre gateway](#), on page 99
- [show watchlist](#), on page 100
- [show wlan](#), on page 101
- [show wps ap-authentication summary](#), on page 106
- [show wps cids-sensor](#), on page 107
- [show wps mfp](#), on page 108

- [show wps shun-list, on page 109](#)
- [show wps signature detail, on page 110](#)
- [show wps signature events, on page 111](#)
- [show wps signature summary, on page 113](#)
- [show wps summary, on page 115](#)
- [show wps wips statistics, on page 117](#)
- [show wps wips summary, on page 118](#)
- [show wps ap-authentication summary, on page 119](#)

show radius acct detailed

show radius acct detailed

To display RADIUS accounting server information, use the **show radius acct detailed** command.

show radius acct detailed *radius_index*

Syntax Description	<i>radius_index</i>	Radius server index. The range is from 1 to 17.
Command Default	None	
Command History	Release	Modification
	8.0	This command was introduced.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display RADIUS accounting server information:

```
(Cisco Controller) > show radius acct detailed 5
Radius Index.....5
NAI Realms.....LAB.VTV.BLR.cisco.co.in
```

show radius acct statistics

To display the RADIUS accounting server statistics for the Cisco wireless LAN controller, use the **show radius acct statistics** command.

show radius acct statistics

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display RADIUS accounting server statistics:

```
(Cisco Controller) > show radius acct statistics
Accounting Servers:
Server Index..... 1
Server Address..... 10.1.17.10
Msg Round Trip Time..... 0 (1/100 second)
First Requests..... 0
Retry Requests..... 0
Accounting Responses..... 0
Malformed Msgs..... 0
Bad Authenticator Msgs..... 0
Pending Requests..... 0
Timeout Requests..... 0
Unknowntype Msgs..... 0
Other Drops..... 0
```

Related Commands	config radius acct config radius acct ipsec authentication config radius acct ipsec disable config radius acct network show radius auth statistics show radius summary
-------------------------	---

show radius auth detailed

show radius auth detailed

To display RADIUS authentication server information, use the **show radius auth detailed** command.

show radius auth detailed *radius_index*

Syntax Description	<i>radius_index</i>	Radius server index. The range is from 1 to 17.
Command Default	None	
Command History	Release	Modification
	8.0	This command was introduced.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display RADIUS authentication server information:

```
(Cisco Controller) > show radius auth detailed 1
Radius Index.....1
NAI Realms.....LAB.VTV.BLR.cisco.co.in
```

show radius auth statistics

To display the RADIUS authentication server statistics for the Cisco wireless LAN controller, use the **show radius auth statistics** command.

show radius auth statistics

This command has no arguments or keyword.

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display RADIUS authentication server statistics:

```
(Cisco Controller) > show radius auth statistics
Authentication Servers:
  Server Index..... 1
  Server Address..... 209.165.200.10
  Msg Round Trip Time..... 0 (1/100 second)
  First Requests..... 0
  Retry Requests..... 0
  Accept Responses..... 0
  Reject Responses..... 0
  Challenge Responses..... 0
  Malformed Msgs..... 0
  Bad Authenticator Msgs..... 0
  Pending Requests..... 0
  Timeout Requests..... 0
  Unknowntype Msgs..... 0
  Other Drops..... 0
```

Related Commands	config radius auth config radius auth management config radius auth network show radius summary
-------------------------	--

show radius avp-list

show radius avp-list

To display RADIUS VSA AVPs, use the **show radius avp-list** command.

show radius avp-list *profile-name*

Syntax Description	<i>profile-name</i>	Profile name for which downloaded AVPs to be shown.
Command Default	None	
Command History	Release	Modification
	8.0	This command was introduced.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display RADIUS VSA AVPs:

```
(Cisco Controller) > show radius avp-list
```

show radius summary

To display the RADIUS authentication and accounting server summary, use the **show radius summary** command.

show radius summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release Modification	
	8.3	This command was introduced.

The following example shows how to display a RADIUS authentication server summary:

```
(Cisco Controller) > show radius summary
Vendor Id Backward Compatibility..... Disabled
Credentials Caching..... Disabled
Call Station Id Type..... IP Address
Administrative Authentication via RADIUS..... Enabled
Authentication Servers
Index Type Server Address Port State Tout RFC-3576 IPsec -
AuthMod
e/Phase1/Group/Lifetime/Auth/Encr
----- -----
----- 
Accounting Servers
Index Type Server Address Port State Tout RFC-3576 IPsec -
AuthMod
e/Phase1/Group/Lifetime/Auth/Encr
----- -----
-----
```

Related Commands	show radius auth statistics
	show radius acct statistics

show redundancy interfaces

show redundancy interfaces

To display details of redundancy and service port IP addresses, use the **show redundancy interfaces** command.

show redundancy interfaces

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the redundancy and service port IP addresses information:

```
(Cisco Controller) >show redundancy interfaces

Redundancy Management IP Address..... 9.4.120.5
Peer Redundancy Management IP Address..... 9.4.120.3
Redundancy Port IP Address..... 169.254.120.5
Peer Redundancy Port IP Address..... 169.254.120.3
Peer Service Port IP Address..... 10.104.175.189
```

show redundancy latency

To display the average latency to reach the management gateway and the peer redundancy management IP address, use the **show redundancy latency** command.

show redundancy latency

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the average latency to reach the management gateway and the peer redundancy management IP address:

```
(Cisco Controller) >show redundancy latency
```

```
Network Latencies (RTT) for the Peer Reachability on the Redundancy Port in micro seconds
for the past 10 intervals
Peer Reachability Latency[ 1 ] : 524 usecs
Peer Reachability Latency[ 2 ] : 524 usecs
Peer Reachability Latency[ 3 ] : 522 usecs
Peer Reachability Latency[ 4 ] : 526 usecs
Peer Reachability Latency[ 5 ] : 524 usecs
Peer Reachability Latency[ 6 ] : 524 usecs
Peer Reachability Latency[ 7 ] : 522 usecs
Peer Reachability Latency[ 8 ] : 522 usecs
Peer Reachability Latency[ 9 ] : 526 usecs
Peer Reachability Latency[ 10 ] : 523 usecs

Network Latencies (RTT) for the Management Gateway Reachability in micro seconds for the
past 10 intervals
Gateway Reachability Latency[ 1 ] : 1347 usecs
Gateway Reachability Latency[ 2 ] : 2427 usecs
Gateway Reachability Latency[ 3 ] : 1329 usecs
Gateway Reachability Latency[ 4 ] : 2014 usecs
Gateway Reachability Latency[ 5 ] : 2675 usecs
Gateway Reachability Latency[ 6 ] : 731 usecs
Gateway Reachability Latency[ 7 ] : 1882 usecs
Gateway Reachability Latency[ 8 ] : 2853 usecs
Gateway Reachability Latency[ 9 ] : 832 usecs
Gateway Reachability Latency[ 10 ] : 3708 usecs
```

show redundancy mobilitymac

show redundancy mobilitymac

To display the High Availability (HA) mobility MAC address that is used to communicate with the peer, use the **show redundancy mobilitymac** command.

show redundancy mobilitymac

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the HA mobility MAC address used to communicate with the peer:

```
(Cisco Controller) >show redundancy mobilitymac
ff:ff:ff:ff:ff:ff
```

show redundancy peer-route summary

To display the routes assigned to the standby WLC, use the **show redundancy peer-route summary** command.

show redundancy peer-route summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display all the configured routes of the standby WLC:

```
(Cisco Controller) >show redundancy peer-route summary
Number of Routes..... 1

Destination Network          Netmask          Gateway
-----  -----
xxx.xxx.xxx.xxx            255.255.255.0  xxx.xxx.xxx.xxx
```

show redundancy peer-system statistics

show redundancy peer-system statistics

To display statistical information about the standby WLC, use the **show redundancy peer-system statistics** command.

show redundancy peer-system statistics

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	8.7	The serial number and fan status of the standby WLC are added to the output of the command.
	7.6	This command was introduced in a release earlier than Release 7.6.

(Cisco Controller) >**show redundancy peer-system statistics**

```

Peer System CPU statistics:Current CPU(s) load: 0%
Individual CPU load: 0%/1%, 0%/0%, 0%/1%, 0%/0%, 0%/0%, 0%/0%, 0%/0%, 0%/0%, 0%/1%

Peer System Memory Statistics:
Total System Memory.....: 1027727360 bytes (980.18 MB)
Used System Memory.....: 535404544 bytes (510.63 MB)
Free System Memory.....: 492322816 bytes (469.54 MB)
Bytes allocated from RTOS.....: 5550080 bytes (5.29 MB)
Chunks Free.....: 7 bytes
Number of mmaped regions.....: 86
Total space in mmaped regions.: 369500160 bytes (352.40 MB)
Total allocated space.....: 4200328 bytes (4.00 MB)
Total non-inuse space.....: 1349752 bytes (1.28 MB)
Top-most releasable space.....: 94664 bytes (92.44 KB)
Total allocated (incl mmap)....: 375050240 bytes (357.70 MB)
Total used (incl mmap).....: 373700488 bytes (356.41 MB)
Total free (incl mmap).....: 1349752 bytes (1.28 MB)

Peer system Power supply statistics:
Power Supply 1..... Present, OK
Power Supply 2..... Absent

Serial Number..... XXXXXXXXXX
Fan Status..... OK

```

show redundancy statistics

To display the statistics information of the Redundancy Manager, use the **show redundancy statistics** command.

show redundancy statistics

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Usage Guidelines	This command displays the statistics of different redundancy counters.
-------------------------	--

Local Physical Ports - Connectivity status of each physical port of the controller. 1 indicates that the port is up and 0 indicates that the port is down.

Peer Physical Ports - Connectivity status of each physical port of the peer controller. 1 indicates that the port is up and 0 indicates that the port is down.

The following example shows how to display the statistics information of the Redundancy Manager:

```
(Cisco Controller) >show redundancy statistics
```

```
Redundancy Manager Statistics

Keep Alive Request Send Counter      : 16
Keep Alive Response Receive Counter : 16

Keep Alive Request Receive Counter  : 500322
Keep Alive Response Send Counter   : 500322

Ping Request to Default GW Counter : 63360
Ping Response from Default GW Counter : 63360

Ping Request to Peer Counter       : 12
Ping Response from Peer Counter   : 3

Keep Alive Loss Counter           : 0
Default GW Loss Counter          : 0

Local Physical Ports 1...8         : 10000000
Peer Physical Ports 1...8          : 10000000
```

show redundancy summary

show redundancy summary

To display the redundancy summary information, use the **show redundancy summary** command.

show redundancy summary

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the redundancy summary information of the controller:

```
(Cisco Controller) >show redundancy summary
Redundancy Mode = SSO DISABLED
    Local State = ACTIVE
    Peer State = N/A
        Unit = Primary
        Unit ID = 88:43:E1:7E:03:80
    Redundancy State = N/A
        Mobility MAC = 88:43:E1:7E:03:80
    Network Monitor = ENABLED
    Link Encryption = DISABLED

    BulkSync Status = <Status>
    Average Redundancy Peer Reachability Latency = 1390 usecs
    Average Management Gateway Reachability Latency = 1165 usecs

    Redundancy Management IP Address..... 9.4.92.12
    Peer Redundancy Management IP Address..... 9.4.92.14
    Redundancy Port IP Address..... 169.254.92.12
    Peer Redundancy Port IP Address..... 169.254.92.14
```

show redundancy timers

To display details of the Redundancy Manager timers, use the **show redundancy timers** command.

show redundancy timers

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the details of the Redundancy Manager timers:

```
(Cisco Controller) >show redundancy timers

      Keep Alive Timer      : 100 msec
      Peer Search Timer     : 120 secs
```

show remote-lan

show remote-lan

To display information about remote LAN configuration, use the **show remote-lan** command.

show remote-lan { summary | remote-lan-id }

Syntax Description	summary	Displays a summary of all remote LANs.
	<i>remote-lan-id</i>	Remote LAN identifier.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of all remote LANs:

```
(Cisco Controller) >show remote-lan summary
Number of Remote LANS..... 2
RLAN ID RLAN Profile Name Status Interface Name
----- -----
2       remote           Disabled management
8       test              Disabled management
```

The following example shows configuration information about the remote LAN with the *remote-lan-id* 2:

```
(Cisco Controller) >show remote-lan 2
Remote LAN Identifier..... 2
Profile Name..... remote
Status..... Disabled
MAC Filtering..... Disabled
AAA Policy Override..... Disabled
Network Admission Control
    Radius-NAC State..... Disabled
    SNMP-NAC State..... Disabled
    Quarantine VLAN..... 0
    Maximum number of Associated Clients..... 0
    Number of Active Clients..... 0
    Exclusionlist..... Disabled
    Session Timeout..... Infinity
    CHD per Remote LAN..... Enabled
    Webauth DHCP exclusion..... Disabled
    Interface..... management
    Remote LAN ACL..... unconfigured
    DHCP Server..... Default
    DHCP Address Assignment Required..... Disabled
    Static IP client tunneling..... Disabled
    Radius Servers
        Authentication..... Global Servers
        Accounting..... Global Servers
        Dynamic Interface..... Disabled
    Security
        Web Based Authentication..... Enabled
```

```
ACL..... Unconfigured
Web Authentication server precedence:
 1..... local
 2..... radius
 3..... ldap
Web-Passthrough..... Disabled
Conditional Web Redirect..... Disabled
Splash-Page Web Redirect..... Disabled
```

show reset

show reset

To display the scheduled system reset parameters, use the **show reset** command.

show reset

Syntax Description This command has no arguments or keywords.

Command Default None.

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display the scheduled system reset parameters:

```
> show reset
System reset is scheduled for Mar 27 01 :01 :01 2010
Current local time and date is Mar 24 02:57:44 2010
A trap will be generated 10 minutes before each scheduled system reset.
Use 'reset system cancel' to cancel the reset.
Configuration will be saved before the system reset.
```

Related Commands

- reset system at**
- reset system in**
- reset system cancel**
- reset system notify-time**

show rfid client

To display the radio frequency identification (RFID) tags that are associated to the controller as clients, use the **show rfid client** command.

show rfid client

Syntax Description This command has no arguments or keywords.

Command Default None.

Usage Guidelines When the RFID tag is not in client mode, the above fields are blank.

This example shows how to display the RFID tag that is associated to the controller as clients:

```
> show rfid client
-----
          Heard
-----  -----
RFID Mac      VENDOR   Sec Ago Associated AP   Chnl   Client State
-----  -----
00:14:7e:00:0b:b1    Pango        35     AP0019.e75c.fef4    1       Probing
```

Related Commands

- config rfid status**
- config rfid timeout**
- show rfid config**
- show rfid detail**
- show rfid summary**

show rfid config

show rfid config

To display the current radio frequency identification (RFID) configuration settings, use the **show rfid config** command.

show rfid config

Syntax Description This command has no arguments or keywords.

Command Default None.

This example shows how to display the current RFID configuration settings:

```
> show rfid config
RFID Tag Data Collection ..... Enabled
RFID Tag Auto-Timeout ..... Enabled
RFID Client Data Collection ..... Disabled
RFID Data Timeout ..... 200 seconds
```

Related Commands

- config rfid status**
- config rfid timeout**
- show rfid client**
- show rfid detail**
- show rfid summary**

show rfid detail

To display detailed radio frequency identification (RFID) information for a specified tag, use the **show rfid detail** command.

show rfid detail mac_address

Syntax Description	<i>mac_address</i>	MAC address of an RFID tag.
---------------------------	--------------------	-----------------------------

Command Default	None.
------------------------	-------

This example shows how to display detailed RFID information:

```
> show rfid detail 00:12:b8:00:20:52
RFID address..... 00:12:b8:00:20:52
Vendor..... G2
Last Heard..... 51 seconds ago
Packets Received..... 2
Bytes Received..... 324
Cisco Type..... Content Header
=====
Version..... 0
Tx Power..... 12 dBm
Channel..... 1
Reg Class..... 12
Burst Length..... 1
CCX Payload
=====
Last Sequence Control..... 0
Payload length..... 127
Last Sequence Control..... 0
Payload length..... 127
Payload Data Hex Dump
01 09 00 00 00 00 0b 85 52 52 52 02 07 4b ff ff
7f ff ff ff 03 14 00 12 7b 10 48 53 c1 f7 51 4b
50 ba 5b 97 27 80 00 67 00 01 03 05 01 42 34 00
00 03 05 02 42 5c 00 00 03 05 03 42 82 00 00 03
05 04 42 96 00 00 03 05 05 00 00 00 55 03 05 06
42 be 00 00 03 02 07 05 03 12 08 10 00 01 02 03
04 05 06 07 08 09 0a 0b 0c 0d 0e 0f 03 0d 09 03
08 05 07 a8 02 00 10 00 23 b2 4e 03 02 0a 03
Nearby AP Statistics:
lap1242-2(slot 0, chan 1) 50 seconds ago.... -76 dBm
lap1242(slot 0, chan 1) 50 seconds ago.... -65 dBm
```

Related Commands	config rfid status config rfid timeout show rfid config show rfid client show rfid summary
-------------------------	--

show rfid summary

show rfid summary

To display a summary of the radio frequency identification (RFID) information for a specified tag, use the **show rfid summary** command.

show rfid summary

Syntax Description This command has no arguments or keywords.

Command Default None.

This example shows how to display a summary of RFID information:

```
> show rfid summary
Total Number of RFID      : 5
-----
RFID ID      VENDOR      Closest AP      RSSI      Time Since Last Heard
-----
00:04:f1:00:00:04 Wherenet    ap:1120      -51      858 seconds ago
00:0c:cc:5c:06:d3 Aerosct   ap:1120      -51      68 seconds ago
00:0c:cc:5c:08:45 Aerosct   AP_1130      -54      477 seconds ago
00:0c:cc:5c:08:4b Aerosct   wolverine    -54      332 seconds ago
00:0c:cc:5c:08:52 Aerosct   ap:1120      -51      699 seconds ago
```

Related Commands

- config rfid status**
- config rfid timeout**
- show rfid client**
- show rfid detail**
- show rfid config**

show rf-profile summary

To display a summary of RF profiles in the controller, use the **show rf-profile summary** command.

show rf-profile summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following is the output of the **show rf-profile summary** command:

```
(Cisco Controller) >show rf-profile summary
Number of RF Profiles..... 2
Out Of Box State..... Disabled
RF Profile Name          Band   Description           Applied
-----  -----  -----
T1a                5 GHz  <none>                 No
T1b                2.4 GHz <none>                 No
```

show rf-profile details

show rf-profile details

To display the RF profile details in the Cisco wireless LAN controller, use the **show rf-profile details** command.

show rf-profile details *rf-profile-name*

Syntax Description	<i>rf-profile-name</i>	Name of the RF profile.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
	8.0	The output was updated to include the Rx SOP threshold.
	8.5	The output was updated to include the Client Aware FRA configurations.
Command History	Release	Modification
	8.3	This command was introduced.

The following is the output of the **show rf-profile details** command::

```
(Cisco Controller) >show rf-profile details profile1
Description.....<none>
AP Group Name.....test
Radio policy.....5 GHz
11n-client-only.....disabled
Transmit Power Threshold v1.....-70 dBm
Transmit Power Threshold v2.....-67 dBm
Min Transmit Power.....-10 dBm
Max Transmit Power.....30 dBm
802.11a Operational Rates
    802.11a 6M Rate.....Mandatory
    802.11a 9M Rate.....Supported
    802.11a 12M Rate.....Mandatory
    802.11a 18M Rate.....Supported
    802.11a 24M Rate.....Mandatory
    802.11a 36M Rate.....Supported
    802.11a 48M Rate.....Supported
    802.11a 54M Rate.....Supported
Max Clients.....200

WLAN ID      Max Clients
-----      -----
1            600

--More-- or (q)uit
2            600
4            600
9            600
11           600
12           600
```

```

13          600
14          600
15          600
16          600

Trap Threshold
  Clients..... 12 clients
  Interference..... 10 %
  Noise..... -70 dBm
  Utilization..... 80 %
  Multicast Data Rate..... 0
  Rx Sop Threshold..... AUTO
  Cca Threshold..... 0 dBm
  Slot Admin State:..... Enabled

Client Aware FRA
  State..... Disabled
  Client Select Utilization Threshold..... 20%

--More-- or (q)uit
  Client Reset Utilization Threshold..... 5%

Band Select
  Probe Response..... Disabled
  Cycle Count..... 2 cycles
  Cycle Threshold..... 200 milliseconds
  Expire Suppression..... 20 seconds
  Expire Dual Band..... 60 seconds
  Client Rssi..... -80 dBm
  Client Mid Rssi..... -80 dBm

Load Balancing
  Denial..... 3 count
  Window..... 5 clients

Coverage Data
  Data..... -80 dBm
  Voice..... -80 dBm
  Minimum Client Level..... 3 clients
  Exception Level..... 25 %
  DCA Channel List..... 36,40,44,48,52,56,60,64,100,
                        104,108,112,116,120,124,128,
                        132,136,140,144,149,153,157,

--More-- or (q)uit
  161
  DCA Bandwidth..... 20
  DCA Foreign AP Contribution..... enabled
  HSR Mode..... disabled

802.11n MCS Rates
  MCS-00 Rate..... enabled
  MCS-01 Rate..... enabled
  MCS-02 Rate..... enabled
  MCS-03 Rate..... enabled
  MCS-04 Rate..... enabled
  MCS-05 Rate..... enabled
  MCS-06 Rate..... enabled
  MCS-07 Rate..... enabled
  MCS-08 Rate..... enabled
  MCS-09 Rate..... enabled
  MCS-10 Rate..... enabled
  MCS-11 Rate..... enabled
  MCS-12 Rate..... enabled

```

show rf-profile details

```
MCS-13 Rate..... enabled
MCS-14 Rate..... enabled
MCS-15 Rate..... enabled
MCS-16 Rate..... enabled

--More-- or (q)uit
MCS-17 Rate..... enabled
MCS-18 Rate..... enabled
MCS-19 Rate..... enabled
MCS-20 Rate..... enabled
MCS-21 Rate..... enabled
MCS-22 Rate..... enabled
MCS-23 Rate..... enabled
MCS-24 Rate..... enabled
MCS-25 Rate..... enabled
MCS-26 Rate..... enabled
MCS-27 Rate..... enabled
MCS-28 Rate..... enabled
MCS-29 Rate..... enabled
MCS-30 Rate..... enabled
MCS-31 Rate..... enabled
Client Network Preference..... default
```

show rogue adhoc custom summary

To display information about custom rogue ad-hoc rogue access points, use the **show rogue adhoc custom summary** command.

show rogue adhoc custom summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display details of custom rogue ad-hoc access points:

```
(Cisco Controller) > show rogue adhoc custom summary
Number of Adhocts.....0

MAC Address          State          # APs # Clients Last Heard
-----  -----  -----  -----
-----  -----  -----  -----
```

Related Commands	show rogue adhoc detailed show rogue adhoc summary show rogue adhoc friendly summary show rogue adhoc malicious summary show rogue adhoc unclassified summary config rogue adhoc
-------------------------	---

show rogue adhoc detailed

show rogue adhoc detailed

To display details of an ad-hoc rogue access point detected by the Cisco wireless LAN controller, use the **show rogue adhoc client detailed** command.

show rogue adhoc detailed *MAC_address*

Syntax Description	<i>MAC_address</i>	Adhoc rogue MAC address.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display detailed ad-hoc rogue MAC address information:

```
(Cisco Controller) > show rogue adhoc client detailed 02:61:ce:8e:a8:8c
Adhoc Rogue MAC address..... 02:61:ce:8e:a8:8c
Adhoc Rogue BSSID..... 02:61:ce:8e:a8:8c
State..... Alert
First Time Adhoc Rogue was Reported..... Tue Dec 11 20:45:45
2007
Last Time Adhoc Rogue was Reported..... Tue Dec 11 20:45:45
2007
Reported By
AP 1
MAC Address..... 00:14:1b:58:4a:e0
Name..... AP0014.1ced.2a60
Radio Type..... 802.11b
SSID..... rf4k3ap
Channel..... 3
RSSI..... -56 dBm
SNR..... 15 dB
Encryption..... Disabled
ShortPreamble..... Disabled
WPA Support..... Disabled
Last reported by this AP..... Tue Dec 11 20:45:45 2007
```

Related Commands	config rogue adhoc show rogue ignore-list show rogue rule summary
-------------------------	---

show rogue rule detailed
config rogue rule
show rogue adhoc summary

show rogue adhoc friendly summary

show rogue adhoc friendly summary

To display information about friendly rogue ad-hoc rogue access points, use the **show rogue adhoc friendly summary** command.

show rogue adhoc friendly summary

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display information about friendly rogue ad-hoc rogue access points:

```
(Cisco Controller) > show rogue adhoc friendly summary
Number of Adhoscs.....0
MAC Address          State          # APs # Clients Last Heard
-----
```

Related Commands [show rogue adhoc custom summary](#)

[show rogue adhoc detailed](#)

[show rogue adhoc summary](#)

[show rogue adhoc malicious summary](#)

[show rogue adhoc unclassified summary](#)

[config rogue adhoc](#)

show rogue adhoc malicious summary

To display information about malicious rogue ad-hoc rogue access points, use the **show rogue adhoc malicious summary** command.

show rogue adhoc malicious summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display details of malicious rogue ad-hoc rogue access points:

```
(Cisco Controller) > show rogue adhoc malicious summary
Number of Adhocts.....0

MAC Address           State          # APs # Clients Last Heard
-----  -----  -----  -----
-----  -----  -----  -----
```

Related Commands	show rogue adhoc custom summary show rogue adhoc detailed show rogue adhoc summary show rogue adhoc friendly summary show rogue adhoc unclassified summary config rogue adhoc
-------------------------	--

show rogue adhoc unclassified summary

show rogue adhoc unclassified summary

To display information about unclassified rogue ad-hoc rogue access points, use the **show rogue adhoc unclassified summary** command.

show rogue adhoc unclassified summary

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display information about unclassified rogue ad-hoc rogue access points:

```
(Cisco Controller) > show rogue adhoc unclassified summary
Number of Adhoscs.....0
MAC Address          State          # APs # Clients Last Heard
-----  -----  -----
-----  -----  -----
```

Related Commands [show rogue adhoc custom summary](#)

[show rogue adhoc detailed](#)

[show rogue adhoc summary](#)

[show rogue adhoc friendly summary](#)

[show rogue adhoc malicious summary](#)

[config rogue adhoc](#)

show rogue adhoc summary

To display a summary of the ad-hoc rogue access points detected by the Cisco wireless LAN controller, use the **show rogue adhoc summary** command.

show rogue adhoc summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display a summary of all ad-hoc rogues:

```
(Cisco Controller) > show rogue adhoc summary
Detect and report Ad-Hoc Networks..... Enabled
Client MAC Address      Adhoc BSSID      State # APs      Last Heard
-----  -----  -----  ---  -----
xx:xx:xx:xx:xx:xx      super          Alert   1           Sat Aug  9 21:12:50
2004
xx:xx:xx:xx:xx:xx          super          Alert   1           Aug  9 21:12:50
2003
xx:xx:xx:xx:xx:xx          super          Alert   1           Sat Aug  9 21:10:50
2003
```

Related Commands	config rogue adhoc show rogue ignore-list show rogue rule summary show rogue rule detailed config rogue rule show rogue adhoc detailed
-------------------------	---

show rogue ap clients

show rogue ap clients

To display details of rogue access point clients detected by the Cisco wireless LAN controller, use the **show rogue ap clients** command.

show rogue ap clients *ap_mac_address*

Syntax Description	<i>ap_mac_address</i>	Rogue access point MAC address.				
Command Default	None					
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>7.6</td> <td>This command was introduced in a release earlier than Release 7.6.</td></tr> </tbody> </table>	Release	Modification	7.6	This command was introduced in a release earlier than Release 7.6.	
Release	Modification					
7.6	This command was introduced in a release earlier than Release 7.6.					
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>8.3</td> <td>This command was introduced.</td></tr> </tbody> </table>	Release	Modification	8.3	This command was introduced.	
Release	Modification					
8.3	This command was introduced.					

The following example shows how to display details of rogue access point clients:

```
(Cisco Controller) > show rogue ap clients xx:xx:xx:xx:xx:xx
MAC Address State # APs Last Heard
-----
00:bb:cd:12:ab:ff Alert 1 Fri Nov 30 11:26:23 2007
```

Related Commands

- config rogue adhoc**
- config rogue ap classify**
- config rogue ap friendly**
- config rogue ap rldp**
- config rogue ap timeout**
- config rogue ap valid-client**
- config rogue client**
- config trapflags rogueap**
- show rogue ap detailed**
- show rogue ap summary**
- show rogue ap friendly summary**
- show rogue ap malicious summary**
- show rogue ap unclassified summary**
- show rogue client detailed**

show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary

show rogue ap custom summary

show rogue ap custom summary

To display information about custom rogue ad-hoc rogue access points, use the **show rogue ap custom summary** command.

show rogue ap custom summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release Modification	
	8.3	This command was introduced.

The following example shows how to display details of custom rogue ad-hoc rogue access points:

```
(Cisco Controller) > show rogue ap custom summary
```

Number of APs.....	0			
MAC Address	State	# APs	# Clients	Last Heard
-----	-----	-----	-----	-----
-----	-----	-----	-----	-----

Related Commands

- config rogue adhoc**
- config rogue ap classify**
- config rogue ap friendly**
- config rogue ap rldp**
- config rogue ap timeout**
- config rogue ap valid-client**
- config rogue client**
- config trapflags rogueap**
- show rogue ap clients**
- show rogue ap detailed**
- show rogue ap summary**
- show rogue ap malicious summary**
- show rogue ap unclassified summary**

```
show rogue client detailed
show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary
```

show rogue ap detailed

show rogue ap detailed

To display details of a rogue access point detected by the Cisco wireless LAN controller, use the **show rogue-ap detailed** command.

show rogue ap detailed *ap_mac_address*

Syntax Description	<i>ap_mac_address</i>	Rogue access point MAC address.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display detailed information of a rogue access point:

```
(Cisco Controller) > show rogue ap detailed xx:xx:xx:xx:xx:xx
Rogue BSSID..... 00:0b:85:63:d1:94
Is Rogue on Wired Network..... No
Classification..... Unclassified
State..... Alert
First Time Rogue was Reported..... Fri Nov 30 11:24:56
2007
Last Time Rogue was Reported..... Fri Nov 30 11:24:56
2007
Reported By
AP 1
MAC Address..... 00:12:44:bb:25:d0
Name..... flexconnect
Radio Type..... 802.11g
SSID..... edu-eap
Channel..... 6
RSSI..... -61 dBm
SNR..... -1 dB
Encryption..... Enabled
ShortPreamble..... Enabled
WPA Support..... Disabled
Last reported by this AP..... Fri Nov 30 11:24:56 2007
```

This example shows how to display detailed information of a rogue access point with a customized classification:

```
(Cisco Controller) > show rogue ap detailed xx:xx:xx:xx:xx:xx
Rogue BSSID..... 00:17:0f:34:48:a0
Is Rogue on Wired Network..... No
Classification..... custom
Severity Score ..... 1
Class Name..... VeryMalicious
Class Change by..... Rogue Rule
Classified at ..... -60 dBm
Classified by..... c4:0a:cb:a1:18:80

State..... Contained
State change by..... Rogue Rule
First Time Rogue was Reported..... Mon Jun 4 10:31:18
2012
Last Time Rogue was Reported..... Mon Jun 4 10:31:18
2012
Reported By
AP 1
MAC Address..... c4:0a:cb:a1:18:80
Name..... SHIELD-3600-2027
Radio Type..... 802.11g
SSID..... sri
Channel..... 11
RSSI..... -87 dBm
SNR..... 4 dB
Encryption..... Enabled
ShortPreamble..... Enabled
WPA Support..... Enabled
Last reported by this AP..... Mon Jun 4 10:31:18
2012
```

Related Commands

- config rogue adhoc**
- config rogue ap classify**
- config rogue ap friendly**
- config rogue ap rldp**
- config rogue ap timeout**
- config rogue ap valid-client**
- config rogue client**
- config trapflags rogueap**
- show rogue ap clients**
- show rogue ap summary**
- show rogue ap friendly summary**
- show rogue ap malicious summary**

show rogue ap detailed

show rogue ap unclassified summary
show rogue client detailed
show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary

show rogue ap friendly summary

To display a list of the friendly rogue access points detected by the controller, use the **show rogue ap friendly summary** command.

show rogue ap friendly summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display a summary of all friendly rogue access points:

```
(Cisco Controller) > show rogue ap friendly summary
Number of APs..... 1
MAC Address      State    # APs  # Clients Last Heard
-----
-----
XX:XX:XX:XX:XX:XX Internal      1     0   Tue Nov 27 13:52:04 2007
```

Related Commands	config rogue adhoc config rogue ap classify config rogue ap friendly config rogue ap rldp config rogue ap timeout config rogue ap valid-client config rogue client config trapflags rogueap show rogue ap clients show rogue ap detailed show rogue ap summary show rogue ap malicious summary show rogue ap unclassified summary
-------------------------	---

show rogue ap friendly summary

show rogue client detailed
show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary

show rogue ap malicious summary

To display a list of the malicious rogue access points detected by the controller, use the **show rogue ap malicious summary** command.

show rogue ap malicious summary

Syntax Description	This command has no arguments or keywords.				
Command Default	None				
Command History	<table border="1"><thead><tr><th>Release</th><th>Modification</th></tr></thead><tbody><tr><td>7.6</td><td>This command was introduced in a release earlier than Release 7.6.</td></tr></tbody></table>	Release	Modification	7.6	This command was introduced in a release earlier than Release 7.6.
Release	Modification				
7.6	This command was introduced in a release earlier than Release 7.6.				
Command History	<table border="1"><thead><tr><th>Release</th><th>Modification</th></tr></thead><tbody><tr><td>8.3</td><td>This command was introduced.</td></tr></tbody></table>	Release	Modification	8.3	This command was introduced.
Release	Modification				
8.3	This command was introduced.				

The following example shows how to display a summary of all malicious rogue access points:

```
(Cisco Controller) > show rogue ap malicious summary
Number of APs..... 2
MAC Address      State      # APs  # Clients Last Heard
----- - - - - -
XX:XX:XX:XX:XX:XX Alert          1    0   Tue Nov 27 13:52:04 2007
XX:XX:XX:XX:XX:XX Alert          1    0   Tue Nov 27 13:52:04 2007
```

Related Commands	
	config rogue adhoc
	config rogue ap classify
	config rogue ap friendly
	config rogue ap rldp
	config rogue ap timeout
	config rogue ap valid-client
	config rogue client
	config trapflags rogueap
	show rogue ap clients
	show rogue ap detailed
	show rogue ap summary
	show rogue ap friendly summary
	show rogue ap unclassified summary

show rogue ap malicious summary

show rogue client detailed
show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary

show rogue ap summary

To display a summary of the rogue access points detected by the Cisco wireless LAN controller, use the **show rogue-ap summary** command.

show rogue ap summary {ssid | channel}

Syntax Description	<i>ssid</i>	Displays specific user-configured SSID of the rogue access point.
	<i>channel</i>	Displays specific user-configured radio type and channel of the rogue access point.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
	8.0	The new keywords SSID and channel are added.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display a summary of all rogue access points:

```
(Cisco Controller) > show rogue ap summary

Rogue Location Discovery Protocol..... Disabled
Rogue ap timeout..... 1200
Rogue on wire Auto-Contain..... Disabled
Rogue using our SSID Auto-Contain..... Disabled
Valid client on rogue AP Auto-Contain..... Disabled
Rogue AP timeout..... 1200
Rogue Detection Report Interval..... 10
Rogue Detection Min Rssi..... -128
Rogue Detection Transient Interval..... 0
Rogue Detection Client Num Thershodl..... 0
Total Rogues(AP+Ad-hoc) supported..... 2000
Total Rogues classified..... 729

MAC Address      Classification      # APs # Clients Last Heard
-----          -----
xx:xx:xx:xx:xx:xx friendly           1     0     Thu Aug 4 18:57:11 2005
xx:xx:xx:xx:xx:xx malicious          1     0     Thu Aug 4 19:00:11 2005
xx:xx:xx:xx:xx:xx malicious          1     0     Thu Aug 4 18:57:11 2005
xx:xx:xx:xx:xx:xx malicious          1     0     Thu Aug 4 18:57:11 2005
```

The following example shows how to display a summary of all rogue access points with SSID as extended parameter.

show rogue ap summary(Cisco Controller) > **show rogue ap summary ssid**

MAC Address	Class	State	SSID	Security
xx:xx:xx:xx:xx:xx	Unclassified	Alert	xxx	Open
xx:xx:xx:xx:xx:xx	Unclassified	Alert	xxx	Open
xx:xx:xx:xx:xx:xx	Pending	Pending	xxx	Open
xx:xx:xx:xx:xx:xx	Unclassified	Alert	xxx	WEP/WPA

The following example shows how to display a summary of all rogue access points with channel as extended parameter.

(Cisco Controller) > **show rogue ap summary channel**

MAC Address	Class	State	Det	RadioType	Channel	RSSI(last/Max)
xx:xx:xx:xx:xx:xx	Unclassified	Alert	802.11g	11	-53	/ -48
xx:xx:xx:xx:xx:xx	Unclassified	Alert	802.11g	11	-53	/ -48
xx:xx:xx:xx:xx:xx	Unclassified	Alert	802.11a	149	-74	/ -69
xx:xx:xx:xx:xx:xx	Unclassified	Alert	802.11a	149	-74	/ -69
xx:xx:xx:xx:xx:xx	Unclassified	Alert	802.11a	149	-74	/ -69

The following example shows how to display a summary of all rogue access points with both SSID and channel as extended parameters.

(Cisco Controller) > **show rogue ap summary ssid channel**

MAC Address	Class	State	SSID	Security	Det	RadioType
Channel	RSSI (last/Max)					
xx:xx:xx:xx:xx:xx	Unclassified	Alert	dd	WEP/WPA	802.11n5G	
56 -73 / -62						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	SSID IS HIDDEN	Open	802.11a	
149 -68 / -66						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	wlan16	WEP/WPA	802.11n5G	
149 -71 / -71						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	wlan15	WEP/WPA	802.11n5G	
149 -71 / -71						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	wlan14	WEP/WPA	802.11n5G	
149 -71 / -71						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	wlan13	WEP/WPA	802.11n5G	
149 -71 / -70						
xx:xx:xx:xx:xx:xx	Unclassified	Alert	wlan12	WEP/WPA	802.11n5G	
149 -71 / -71						

Related Commands

- config rogue adhoc**
- config rogue ap classify**
- config rogue ap friendly**
- config rogue ap rldp**
- config rogue ap timeout**
- config rogue ap valid-client**
- config rogue client**
- config trapflags rogueap**
- show rogue ap clients**

show rogue ap detailed
show rogue ap friendly summary
show rogue ap malicious summary
show rogue ap unclassified summary
show rogue client detailed
show rogue client summary
show rogue ignore-list
show rogue rule detailed
show rogue rule summary

show rogue ap unclassified summary

show rogue ap unclassified summary

To display a list of the unclassified rogue access points detected by the controller, use the **show rogue ap unclassified summary** command.

show rogue ap unclassified summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release Modification	
	8.3	This command was introduced.

The following example shows how to display a list of all unclassified rogue access points:

```
(Cisco Controller) > show rogue ap unclassified summary
Number of APs..... 164
MAC Address      State # APs # Clients Last Heard
-----
XX:XX:XX:XX:XX:XX Alert 1 0 Fri Nov 30 11:12:52 2007
XX:XX:XX:XX:XX:XX Alert 1 0 Fri Nov 30 11:29:01 2007
XX:XX:XX:XX:XX:XX Alert 1 0 Fri Nov 30 11:26:23 2007
XX:XX:XX:XX:XX:XX Alert 1 0 Fri Nov 30 11:26:23 2007
```

show rogue auto-contain

To display information about rogue auto-containment, use the **show rogue auto-contain** command.

show rogue auto-contain

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display information about rogue auto-containment:

```
(Cisco Controller) > show rogue auto-contain
Containment Level..... 3
monitor_ap_only..... false
```

Related Commands	config rogue adhoc config rogue auto-contain level
-------------------------	---

show rogue client detailed

show rogue client detailed

To display details of a rogue client detected by a Cisco wireless LAN controller, use the **show rogue client detailed** command.

show rogue client detailed *Rogue_AP MAC_address*

Syntax Description	<i>Rogue_AP</i>	Rogue AP address.
	<i>MAC_address</i>	Rogue client MAC address.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
	8.1	The <i>Rogue_AP</i> parameter to the show rogue client detailed command is added.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display detailed information for a rogue client:

```
(Cisco Controller) > show rogue client detailed xx:xx:xx:xx:xx:xx
Rogue BSSID..... 00:0b:85:23:ea:d1
State..... Alert
First Time Rogue was Reported..... Mon Dec 3 21:50:36 2007
Last Time Rogue was Reported..... Mon Dec 3 21:50:36 2007
Rogue Client IP address..... Not known
Reported By
AP 1
MAC Address..... 00:15:c7:82:b6:b0
Name..... AP0016.47b2.31ea
Radio Type..... 802.11a
RSSI..... -71 dBm
SNR..... 23 dB
Channel..... 149
Last reported by this AP..... Mon Dec 3 21:50:36 2007
```

Related Commands	show rogue client summary show rogue ignore-list config rogue rule client config rogue rule
-------------------------	--

show rogue client summary

To display a summary of the rogue clients detected by the Cisco wireless LAN controller, use the **show rogue client summary** command.

show rogue client summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display a list of all rogue clients:

```
(Cisco Controller) > show rogue client summary
Validate rogue clients against AAA..... Disabled
Total Rogue Clients supported..... 2500
Total Rogue Clients present..... 3
MAC Address      State          # APs Last Heard
-----
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:00:08 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:09:11 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:03:11 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:03:11 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:09:11 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 18:57:08 2005
xx:xx:xx:xx:xx:xx Alert          1   Thu Aug 4 19:12:08 2005
```

Related Commands	show rogue client detailed show rogue ignore-list config rogue client config rogue rule
-------------------------	--

show rogue ignore-list

show rogue ignore-list

To display a list of rogue access points that are configured to be ignored, use the **show rogue ignore-list** command.

show rogue ignore-list

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release Modification	
	8.3	This command was introduced.

The following example shows how to display a list of all rogue access points that are configured to be ignored.

```
(Cisco Controller) > show rogue ignore-list
MAC Address
-----
xx:xx:xx:xx:xx:xx
```

Related Commands	config rogue adhoc config rogue ap classify config rogue ap friendly config rogue ap rldp config rogue ap ssid config rogue ap timeout config rogue ap valid-client config rogue rule config trapflags rogueap show rogue client detailed show rogue ignore-list show rogue rule summary show rogue client summary
-------------------------	--

```
show rogue ap unclassified summary
show rogue ap malicious summary
show rogue ap friendly summary
config rogue client
show rogue ap summary
show rogue ap clients
show rogue ap detailed
config rogue rule
```

show rogue rule detailed

show rogue rule detailed

To display detailed information for a specific rogue classification rule, use the **show rogue rule detailed** command.

show rogue rule detailed *rule_name*

Syntax Description	<i>rule_name</i>	Rogue rule name.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display detailed information on a specific rogue classification rule:

```
(Cisco Controller) > show rogue rule detailed Rule2
Priority..... 2
Rule Name..... Rule2
State..... Enabled
Type..... Malicious
Severity Score..... 1
Class Name..... Very_Malicious
Notify..... All
State ..... Contain
Match Operation..... Any
Hit Count..... 352
Total Conditions..... 2
Condition 1
    type..... Client-count
    value..... 10
Condition 2
    type..... Duration
    value (seconds)..... 2000
Condition 3
    type..... Managed-ssid
    value..... Enabled
Condition 4
    type..... No-encryption
    value..... Enabled
Condition 5
    type..... Rssi
    value (dBm)..... -50
Condition 6
    type..... Ssid
    SSID Count..... 1
    SSID 1..... test
```

Related Commands

config rogue rule
show rogue ignore-list
show rogue rule summary

show rogue rule summary

show rogue rule summary

To display the rogue classification rules that are configured on the controller, use the **show rogue rule summary** command.

show rogue rule summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release Modification	
	8.3	This command was introduced.

The following example shows how to display a list of all rogue rules that are configured on the controller:

```
(Cisco Controller) > show rogue rule summary
Priority Rule Name          State    Type      Match Hit Count
----- -----
1       mtest                Enabled   Malicious All     0
2       asdfasdf              Enabled   Malicious All     0
```

The following example shows how to display a list of all rogue rules that are configured on the controller:

```
(Cisco Controller) > show rogue rule summary
Priority          Rule Name          Rule state Class Type  Notify
          State      Match Hit Count
----- -----
1           rule2          Enabled   Friendly  Global
          Alert     All     234
2           rule1          Enabled   Custom    Global
          Alert     All     0
```

Related Commands	config rogue rule
	show rogue ignore-list
	show rogue rule detailed

show route kernel

To display the kernel route cache information, use the **show route kernel** command.

show route kernel

Syntax Description This command has no arguments or keywords.

Command Default None.

This example shows how to display the kernel route cache information:

```
> show route kernel
Iface Destination Gateway Flags RefCnt Use Metric Mask MTU Window IRTT
dt10 14010100 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 28282800 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 34010100 00000000 0001 0 0 FFFFFFF00 0 0 0
eth0 02020200 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 33010100 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 0A010100 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 32010100 00000000 0001 0 0 FFFFFFF00 0 0 0
dt10 0A000000 0202020A 0003 0 0 FF000000 0 0 0
lo 7F000000 00000000 0001 0 0 FF000000 0 0 0
dt10 00000000 0A010109 0003 0 0 00000000 0 0 0
```

Related Commands

clear ap

debug arp

show arp kernel

config route add

config route delete

show route summary

show route summary

To display the routes assigned to the Cisco wireless LAN controller service port, use the **show route summary** command.

show route summary

Syntax Description This command has no arguments or keywords.

Command Default None.

Command History	Release	Modification
	8.3	This command was introduced.

8.3 This command was introduced.

This example shows how to display all the configured routes:

```
> show route summary
Number of Routes.....1
Destination Network          Genmask           Gateway
-----  -----
xxx.xxx.xxx.xxx      255.255.255.0      xxx.xxx.xxx.xxx
```

Related Commands config route

show rules

To display the active internal firewall rules, use the **show rules** command.

show rules

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display active internal firewall rules:

```
(Cisco Controller) > show rules
-----
Rule ID.....: 3
Ref count....: 0
Precedence...: 99999999
Flags........: 00000001 ( PASS )
Source IP range:
    (Local stack)
Destination IP range:
    (Local stack)
-----
Rule ID.....: 25
Ref count....: 0
Precedence...: 99999999
Flags........: 00000001 ( PASS )
Service Info
    Service name.....: GDB
    Protocol.........: 6
    Source port low...: 0
    Source port high.: 0
    Dest port low....: 1000
    Dest port high...: 1000
Source IP range:
IP High.....: 0.0.0.0
    Interface.....: ANY
Destination IP range:
    (Local stack)
```

show run-config

show run-config

To display a comprehensive view of the current Cisco wireless LAN controller configuration, use the **show run-config all** command.

show run-config {all | commands} [no-ap | commands]

Syntax Description	<table border="0"> <tr> <td>all</td><td>Shows all the commands under the show run-config.</td></tr> <tr> <td>no-ap</td><td>(Optional) Excludes access point configuration settings.</td></tr> <tr> <td>commands</td><td>(Optional) Displays a list of user-configured commands on the system.</td></tr> </table>	all	Shows all the commands under the show run-config.	no-ap	(Optional) Excludes access point configuration settings.	commands	(Optional) Displays a list of user-configured commands on the system.
all	Shows all the commands under the show run-config.						
no-ap	(Optional) Excludes access point configuration settings.						
commands	(Optional) Displays a list of user-configured commands on the system.						
Command Default	None						
Command History	<table border="0"> <tr> <td>Release</td><td>Modification</td></tr> <tr> <td>7.6</td><td>This command was introduced in a release earlier than Release 7.6.</td></tr> <tr> <td>8.2</td><td>This command was introduced.</td></tr> </table>	Release	Modification	7.6	This command was introduced in a release earlier than Release 7.6.	8.2	This command was introduced.
Release	Modification						
7.6	This command was introduced in a release earlier than Release 7.6.						
8.2	This command was introduced.						
Command History	<table border="0"> <tr> <td>Release</td><td>Modification</td></tr> <tr> <td>8.3</td><td>This command was introduced.</td></tr> </table>	Release	Modification	8.3	This command was introduced.		
Release	Modification						
8.3	This command was introduced.						
Usage Guidelines	<p>These commands have replaced the show running-config command.</p> <p>Some WLAN controllers may have no Crypto Accelerator (VPN termination module) or power supplies listed because they have no provisions for VPN termination modules or power supplies.</p> <p>The show run-config all command shows only values configured by the user. It does not show system-configured default values.</p>						

The following is a sample output of the **show run-config all** command:

```
(Cisco Controller) > show run-config all
Press Enter to continue...
System Inventory
Switch Description..... Cisco Controller
Machine Model..... FLS0923003B
Serial Number..... xx:xx:xx:xx:xx:xx
Burned-in MAC Address..... xx:xx:xx:xx:xx:xx
Crypto Accelerator 1..... Absent
Crypto Accelerator 2..... Absent
Power Supply 1..... Absent
Power Supply 2..... Present, OK
Press Enter to continue Or <Ctrl Z> to abort...
```

show run-config startup-commands

To display a comprehensive view of the current Cisco wireless LAN controller configuration, use the **show run-config startup-commands** command.

show run-config startup-commands

Syntax Description	run-config Displays the running configuration commands. startup-commands Display list of configured startup commands on Wireless LAN Controller.
Command Default	None
Command History	Release Modification 8.0
Command History	Release Modification 8.3 This command was introduced.

Usage Guidelines The configuration commands on the Wireless LAN controller are uploaded to the TFTP or NCS servers using the transfer upload process. The **show run-config startup-commands** command enables the Wireless LAN controller to generate running-configuration in CLI format. The configuration commands generated can be used as backup configuration to restore the network.

Example

The following is a sample output of the **show run-config startup-commands** command:

show run-config startup-commands

```
(Cisco Controller) >show run-config
    startup-commands

(Cisco Controller) >show run-config startup-commands

This may take some time.
Are you sure you want to proceed? (y/N) y

config location expiry tags 5
config mdns profile service add default-mdns-profile AirPrint
config mdns profile service add default-mdns-profile AirTunes
config mdns profile service add default-mdns-profile AppleTV
config mdns profile service add default-mdns-profile HP_Photosmart_Printer_1
config mdns profile service add default-mdns-profile HP_Photosmart_Printer_2
config mdns profile service add default-mdns-profile Printer
config mdns profile create default-
```

show serial

show serial

To display the serial (console) port configuration, use the **show serial** command.

show serial

Syntax Description	This command has no arguments or keywords.	
Command Default	The default values for Baud rate, Character, Flow Control, Stop Bits, Parity type of the port configuration are 9600, 8, off, 1, none.	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Command History		
	Release	Modification
	8.3	This command was introduced.

The following example shows how to display EIA-232 parameters and the serial port inactivity timeout:

```
(Cisco Controller) > show serial
Serial Port Login Timeout (minutes) ..... 45
Baud Rate..... 9600
Character Size..... 8
Flow Control:..... Disable
Stop Bits..... 1
Parity Type:..... none
```

show sessions

To display the console port login timeout and maximum number of simultaneous command-line interface (CLI) sessions, use the **show sessions** command.

show sessions

Syntax Description	This command has no arguments or keywords.	
---------------------------	--	--

Command Default	5 minutes, 5 sessions.	
------------------------	------------------------	--

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display the CLI session configuration setting:

```
> show sessions
CLI Login Timeout (minutes)..... 0
Maximum Number of CLI Sessions..... 5
```

The response indicates that the CLI sessions never time out and that the Cisco wireless LAN controller can host up to five simultaneous CLI sessions.

Related Commands	config sessions maxsessions
	config sessions timeout

show snmpcommunity

show snmpcommunity

To display Simple Network Management Protocol (SNMP) community entries, use the **show snmpcommunity** command.

show snmpcommunity

Syntax Description This command has no arguments or keywords.

Command Default None.

Command History **Release** **Modification**

Release	Modification
8.3	This command was introduced.

This example shows how to display SNMP community entries:

```
> show snmpcommunity
SNMP Community Name Client IP Address Client IP Mask      Access Mode Status
-----  -----  -----  -----  -----
public      0.0.0.0      0.0.0.0      Read Only   Enable
*****      0.0.0.0      0.0.0.0      Read/Write  Enable
```

Related Commands

- config snmp community accessmode**
- config snmp community create**
- config snmp community delete**
- config snmp community ipaddr**
- config snmp community mode**
- config snmp syscontact**

show snmpengineID

To display the SNMP engine ID, use the **show snmpengineID** command.

show snmpengineID

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None.
------------------------	-------

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display the SNMP engine ID:

```
> show snmpengineID
SNMP EngineId... ffffffffffffff
```

Related Commands	config snmp engineID
-------------------------	-----------------------------

show snmptrap

show snmptrap

To display Cisco wireless LAN controller Simple Network Management Protocol (SNMP) trap receivers and their status, use the **show snmptrap** command.

show snmptrap

Syntax Description This command has no arguments or keywords.

Command Default None.

Command History

Release	Modification
8.3	This command was introduced.

This example shows how to display SNMP trap receivers and their status:

```
> show snmptrap
SNMP Trap Receiver Name      IP Address      Status
-----  -----
xxx.xxx.xxx.xxx      xxx.xxx.xxx.xxx      Enable
```

show snmpv3user

To display Simple Network Management Protocol (SNMP) version 3 configuration, use the **show snmpv3user** command.

show snmpv3user

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None.
------------------------	-------

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display SNMP version 3 configuration information:

```
> show snmpv3user
SNMP v3 username      AccessMode  Authentication Encryption
-----  -----
default           Read/Write   HMAC-SHA       CFB-AES
```

Related Commands	config snmp v3user create
	config snmp v3user delete

show snmpversion

show snmpversion

To display which versions of Simple Network Management Protocol (SNMP) are enabled or disabled on your controller, use the **show snmpversion** command.

show snmpversion

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	Enable.
------------------------	---------

Command History	Release	Modification
------------------------	----------------	---------------------

8.3	This command was introduced.
-----	------------------------------

This example shows how to display the SNMP v1/v2/v3 status:

```
> show snmpversion
SNMP v1 Mode..... Disable
SNMP v2c Mode..... Enable
SNMP v3 Mode..... Enable
```

Related Commands	config snmp version
-------------------------	----------------------------

show spanningtree port

To display the Cisco wireless LAN controller spanning tree port configuration, use the **show spanningtree port** command.

show spanningtree port *port*

Syntax Description	<i>port</i>	Physical port number: <ul style="list-style-type: none"> • 1 through 4 on Cisco 2100 Series Wireless LAN Controller. • 1 or 2 on Cisco 4402 Series Wireless LAN Controller. • 1 through 4 on Cisco 4404 Series Wireless LAN Controller.
Command Default	The default SPT configuration output values are 800C, Disabled, 802.1D, 128, 100, Auto.	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.
Usage Guidelines	When the a Cisco 4400 Series wireless LAN controller is configured for port redundancy, the Spanning Tree Protocol (STP) must be disabled for all ports on the Cisco 4400 Series Wireless LAN Controller. STP can remain enabled on the switch connected to the Cisco 4400 Series Wireless LAN Controller.	
 Note Some WLAN controllers do not support the spanning tree function.		

The following example shows how to display spanning tree values on a per port basis:

```
(Cisco Controller) > show spanningtree port 3
STP Port ID..... 800C
STP Port State..... Disabled
STP Port Administrative Mode..... 802.1D
STP Port Priority..... 128
STP Port Path Cost..... 100
STP Port Path Cost Mode..... Auto
```

show spanningtree switch

show spanningtree switch

To display the Cisco wireless LAN controller network (DS port) spanning tree configuration, use the **show spanningtree switch** command.

show spanningtree switch

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Usage Guidelines Some WLAN controllers do not support the spanning tree function.

The following example shows how to display spanning tree values on a per switch basis:

```
(Cisco Controller) > show spanningtree switch
STP Specification..... IEEE 802.1D
STP Base MAC Address..... 00:0B:85:02:0D:20
Spanning Tree Algorithm..... Disable
STP Bridge Priority..... 32768
STP Bridge Max. Age (seconds)..... 20
STP Bridge Hello Time (seconds)..... 2
STP Bridge Forward Delay (seconds)..... 15
```

show stats port

To display physical port receive and transmit statistics, use the **show stats port** command.

show stats port {detailed port | summary port}

Syntax Description	detailed summary <i>port</i>	Displays detailed port statistics. Displays port summary statistics. Physical port number: <ul style="list-style-type: none"> • 1 through 4 on Cisco 2100 Series Wireless LAN Controllers. • 1 or 2 on Cisco 4402 Series Wireless LAN Controllers. • 1 through 4 on Cisco 4404 Series Wireless LAN Controllers. • 1 on Cisco WLCM Series Wireless LAN Controllers.
Command Default	None	
Command History	Release 7.6	Modification This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the port summary information:

```
(Cisco Controller) > show stats port summary
Packets Received Without Error..... 399958
Packets Received With Error..... 0
Broadcast Packets Received..... 8350
Packets Transmitted Without Error..... 106060
Transmit Packets Errors..... 0
Collisions Frames..... 0
Time Since Counters Last Cleared..... 2 day 11 hr 16 min 23 sec
```

The following example shows how to display the detailed port information:

```
(Cisco Controller) > show stats port detailed 1
PACKETS RECEIVED (OCTETS)
Total Bytes..... 267799881
64 byte pkts :918281
65-127 byte pkts :354016 128-255 byte pkts :1283092
```

show stats port

```

256-511 byte pkts :8406      512-1023 byte pkts :3006
1024-1518 byte pkts :1184      1519-1530 byte pkts :0
> 1530 byte pkts :2
PACKETS RECEIVED SUCCESSFULLY
Total..... 2567987
Unicast Pkts :2547844      Multicast Pkts:0      Broadcast Pkts:20143
PACKETS RECEIVED WITH MAC ERRORS
Total..... 0
Jabbers :0          Undersize :0          Alignment :0
FCS Errors:0        Overruns :0
RECEIVED PACKETS NOT FORWARDED
Total..... 0
Local Traffic Frames:0      RX Pause Frames :0
Unacceptable Frames :0      VLAN Membership :0
VLAN Viable Discards:0      MulticastTree Viable:0
ReserveAddr Discards:0
CFI Discards :0            Upstream Threshold :0
PACKETS TRANSMITTED (OCTETS)
Total Bytes..... 353831
64 byte pkts :0            65-127 byte pkts :0
128-255 byte pkts :0       256-511 byte pkts :0
512-1023 byte pkts :0      1024-1518 byte pkts :2
1519-1530 byte pkts :0     Max Info :1522
PACKETS TRANSMITTED SUCCESSFULLY
Total..... 5875
Unicast Pkts :5868      Multicast Pkts:0      Broadcast Pkts:7
TRANSMIT ERRORS
Total Errors..... 0
FCS Error :0            TX Oversized :0          Underrun Error:0
TRANSMIT DISCARDS
Total Discards..... 0
Single Coll Frames :0      Multiple Coll Frames:0
Excessive Coll Frame:0    Port Membership :0
VLAN Viable Discards:0
PROTOCOL STATISTICS
BPDUs Received :6        BPDUs Transmitted :0
802.3x RX PauseFrame:0
Time Since Counters Last Cleared..... 2 day 0 hr 39 min 59 sec

```

show stats switch

To display the network (DS port) receive and transmit statistics, use the **show stats switch** command.

show stats switch {detailed | summary}

Syntax Description	detailed	Displays detailed switch statistics.
	summary	Displays switch summary statistics.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display switch summary statistics:

```
(Cisco Controller) > show stats switch summary
Packets Received Without Error..... 136410
Broadcast Packets Received..... 18805
Packets Received With Error..... 0
Packets Transmitted Without Error..... 78002
Broadcast Packets Transmitted..... 3340
Transmit Packet Errors..... 2
Address Entries Currently In Use..... 26
VLAN Entries Currently In Use..... 1
Time Since Counters Last Cleared..... 2 day 11 hr 22 min 17 sec
```

The following example shows how to display detailed switch statistics:

```
(Cisco Controller) > show stats switch detailed
RECEIVE
Octets..... 19351718
Total Pkts..... 183468
Unicast Pkts..... 180230
Multicast Pkts..... 3219
Broadcast Pkts..... 19
Pkts Discarded..... 0
TRANSMIT
Octets..... 354251
Total Pkts..... 5882
Unicast Pkts..... 5875
Multicast Pkts..... 0
Broadcast Pkts..... 7
Pkts Discarded..... 0
ADDRESS ENTRIES
```

```
show stats switch
```

Most Ever Used.....	1
Currently In Use.....	1
VLAN ENTRIES	
Maximum.....	128
Most Ever Used.....	1
Static In Use.....	1
Dynamic In Use.....	0
VLANs Deleted.....	0
Time Since Ctrs Last Cleared.....	2 day 0 hr 43 min 22 sec

show switchconfig

To display parameters that apply to the Cisco wireless LAN controller, use the **show switchconfig** command.

show switchconfig

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	Enabled.
------------------------	----------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

This example shows how to display parameters that apply to the Cisco wireless LAN controller:

```
(Cisco Controller) >> show switchconfig
802.3x Flow Control Mode..... Disabled
FIPS prerequisite features..... Enabled
Boot Break..... Enabled
secret obfuscation..... Enabled
Strong Password Check Features:
    case-check ..... Disabled
    consecutive-check .... Disabled
    default-check ..... Disabled
    username-check ..... Disabled
```

Related Commands	config switchconfig mode config switchconfig secret-obfuscation config switchconfig strong-pwd config switchconfig flowcontrol config switchconfig fips-prerequisite show stats switch
-------------------------	---

show sysinfo

show sysinfo

To display high-level Cisco WLC information, use the **show sysinfo** command.

show sysinfo

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	8.3	This command was introduced.

This example shows a sample output of the command run on Cisco 8540 Wireless Controller using Release 8.3:

```
(Cisco Controller) >show sysinfo

Manufacturer's Name..... Cisco Systems Inc.
Product Name..... Cisco Controller
Product Version..... 8.3.100.0
RTOS Version..... 8.3.100.0
Bootloader Version..... 8.0.110.0
Emergency Image Version..... 8.0.110.0

OUI File Last Update Time..... Sun Sep 07 10:44:07 IST 2014

Build Type..... DATA + WPS

System Name..... TestSpartan8500Dev1
System Location..... 
System Contact..... 
System ObjectID..... 1.3.6.1.4.1.9.1.1615
Redundancy Mode..... Disabled
IP Address..... 8.1.4.2
IPv6 Address..... ::

System Up Time..... 0 days 17 hrs 20 mins 58 secs

--More-- or (q)uit
System Timezone Location..... 
System Stats Realtime Interval..... 5
System Stats Normal Interval..... 180

Configured Country..... Multiple Countries : IN,US
Operating Environment..... Commercial (10 to 35 C)
Internal Temp Alarm Limits..... 10 to 38 C
Internal Temperature..... +21 C
Fan Status..... OK

RAID Volume Status
Drive 0..... Good
Drive 1..... Good

State of 802.11b Network..... Enabled
State of 802.11a Network..... Enabled
```

```
Number of WLANS..... 7
Number of Active Clients..... 1

OUI Classification Failure Count..... 0

Burned-in MAC Address..... F4:CF:E2:0A:27:00
Power Supply 1..... Present, OK

--More-- or (q)uit
Power Supply 2..... Present, OK
Maximum number of APs supported..... 6000
System Nas-Id..... 
WLC MIC Certificate Types..... SHA1/SHA2
Licensing Type..... RTU
```

show system iostat

show system iostat

To display CPU statistics, input or output statistics for devices, and partitions with extended statistics of the system, use the **show system iostat** command.

show system iostat {detail | summary}

Syntax Description	detail	Provides CPU statistics, input or output statistics for devices, and partitions with extended statistics of the system.
Command Default	None	
Command History	Release	Modification
	8.0	This command was introduced.

The following is a sample output of the **show system iostat summary** command:

```
(Cisco Controller) >show system iostat summary
Linux 2.6.21_mvlgce500-octeon-mips64_octeon_v2_be (localhost) 10/11/13

avg-cpu: %user %nice %system %iowait %steal %idle
          1.13    0.00    0.27    0.08    0.00   98.52

Device:      tps    MB_read/s    MB_wrtn/s    MB_read    MB_wrtn
  cfa        1.21      0.02         0.00        15          0
```

The following is a sample output of the **show system iostat detail** command:

```
(Cisco Controller) >show system iostat detail
Linux 2.6.21_mvlgce500-octeon-mips64_octeon_v2_be (localhost) 10/11/13

avg-cpu: %user %nice %system %iowait %steal %idle
          0.87    0.00    0.21    0.06    0.00   98.86

Device:      rrqm/s    wrqm/s      r/s      w/s    rMB/s    wMB/s  avgrrq-sz avgqu-sz  await
  svctm %util
  cfa      8.42     0.15    0.84    0.09     0.01     0.00    28.79     0.02  23.41
          7.20     0.67
```

show system top

To display a list of the most CPU-intensive tasks on the system, use the **show system top** command.

show system top

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	8.0	This command was introduced.

The following is a sample output of the **show system top** command:

```
(Cisco Controller) >show system top
top - 06:16:32 up 2 min, 0 users, load average: 2.68, 1.05, 0.38
Tasks: 180 total, 1 running, 179 sleeping, 0 stopped, 0 zombie
Cpu0 : 0.0%us, 0.9%sy, 0.0%ni, 99.1%id, 0.0%wa, 0.0%hi, 0.0%si, 0.0%st
Cpu1 : 0.7%us, 0.3%sy, 0.0%ni, 98.7%id, 0.2%wa, 0.0%hi, 0.0%si, 0.0%st
Cpu2 : 0.3%us, 0.2%sy, 0.0%ni, 97.9%id, 0.7%wa, 0.0%hi, 0.9%si, 0.0%st
Cpu3 : 8.6%us, 1.0%sy, 0.0%ni, 89.1%id, 0.8%wa, 0.0%hi, 0.6%si, 0.0%st
Cpu4 : 13.8%us, 6.9%sy, 0.0%ni, 77.0%id, 0.6%wa, 0.0%hi, 1.7%si, 0.0%st
Cpu5 : 32.9%us, 0.2%sy, 0.0%ni, 65.1%id, 0.7%wa, 0.0%hi, 1.1%si, 0.0%st
Cpu6 : 0.4%us, 0.2%sy, 0.0%ni, 98.5%id, 0.7%wa, 0.0%hi, 0.2%si, 0.0%st
Cpu7 : 15.6%us, 0.6%sy, 0.0%ni, 82.4%id, 0.7%wa, 0.0%hi, 0.7%si, 0.0%st
Cpu8 : 3.8%us, 0.4%sy, 0.0%ni, 95.2%id, 0.6%wa, 0.0%hi, 0.1%si, 0.0%st
Cpu9 : 0.7%us, 0.3%sy, 0.0%ni, 97.9%id, 0.2%wa, 0.0%hi, 0.8%si, 0.0%st
Mem: 1004116k total, 681232k used, 322884k free, 220k buffers
Swap: Ok total, Ok used, Ok free, 138696k cached

          PID USER      PR  NI    VIRT    RES    SHR S %CPU %MEM     TIME+ COMMAND
 1555 root      15   0 2556 1116  816 R    7  0.1  0:00.07 top
    1 root      18   0 4420   752  628 S    0  0.1  0:09.11 init
    2 root      RT   0    0    0 S    0  0.0  0:00.00 migration/0
    3 root      RT   0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
    4 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-high/0
    5 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-timer/0
    6 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
    7 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
    8 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-block/0
    9 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-tasklet
   10 root    -51   0    0    0 S    0  0.0  0:00.00 softirq-sched/0
   11 root    -51   0    0    0 S    0  0.0  0:00.00 softirq-rcu/0
   12 root      RT   0    0    0 S    0  0.0  0:00.00 watchdog/0
   13 root     15  -10   0    0    0 S    0  0.0  0:00.00 desched/0
   14 root      RT   0    0    0 S    0  0.0  0:00.00 migration/1
   15 root      RT   0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
   16 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-high/1
   17 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-timer/1
   18 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
   19 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
   20 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-block/1
   21 root     -51   0    0    0 S    0  0.0  0:00.02 softirq-tasklet
   22 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-sched/1
   23 root     -51   0    0    0 S    0  0.0  0:00.00 softirq-rcu/1
```

show system top

```

24 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/1
25 root      5 -10   0    0    0 S    0  0.0  0:00.00 desched/1
26 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/2
27 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
28 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-high/2
29 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-timer/2
30 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
31 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
32 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-block/2
33 root      -51   0    0    0    0 S    0  0.0  0:01.19 softirq-tasklet
34 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-sched/2
35 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-rcu/2
36 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/2
37 root      5 -10   0    0    0    0 S    0  0.0  0:00.00 desched/2
38 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/3
39 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
40 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-high/3
41 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-timer/3
42 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
43 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
44 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-block/3
45 root      -51   0    0    0    0 S    0  0.0  0:00.72 softirq-tasklet
46 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-sched/3
47 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-rcu/3
48 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/3
49 root      5 -10   0    0    0    0 S    0  0.0  0:00.00 desched/3
50 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/4
51 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
52 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-high/4
53 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-timer/4
54 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
55 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
56 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-block/4
57 root      -51   0    0    0    0 S    0  0.0  0:02.20 softirq-tasklet
58 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-sched/4
59 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-rcu/4
60 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/4
61 root      5 -10   0    0    0    0 S    0  0.0  0:00.00 desched/4
62 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/5
63 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
64 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-high/5
65 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-timer/5
66 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
67 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
68 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-block/5
69 root      -51   0    0    0    0 S    0  0.0  0:01.43 softirq-tasklet
70 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-sched/5
71 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-rcu/5
72 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/5
73 root      5 -10   0    0    0    0 S    0  0.0  0:00.00 desched/5
74 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/6
75 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer
76 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-high/6
77 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-timer/6
78 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-tx/
79 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-net-rx/
80 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-block/6
81 root      -51   0    0    0    0 S    0  0.0  0:00.20 softirq-tasklet
82 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-sched/6
83 root      -51   0    0    0    0 S    0  0.0  0:00.00 softirq-rcu/6
84 root      RT  0    0    0    0 S    0  0.0  0:00.00 watchdog/6
85 root      5 -10   0    0    0    0 S    0  0.0  0:00.00 desched/6
86 root      RT  0    0    0    0 S    0  0.0  0:00.00 migration/7
87 root      RT  0    0    0    0 S    0  0.0  0:00.00 posix_cpu_timer

```

88	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-high/7
89	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-timer/7
90	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-tx/
91	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-rx/
92	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-block/7
93	root	-51	0	0	0	0 S	0	0.0	0:00.84	softirq-tasklet
94	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-sched/7
95	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-rcu/7
96	root	RT	0	0	0	0 S	0	0.0	0:00.00	watchdog/7
97	root	5	-10	0	0	0 S	0	0.0	0:00.00	desched/7
98	root	RT	0	0	0	0 S	0	0.0	0:00.00	migration/8
99	root	RT	0	0	0	0 S	0	0.0	0:00.00	posix_cpu_timer
100	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-high/8
101	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-timer/8
102	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-tx/
103	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-rx/
104	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-block/8
105	root	-51	0	0	0	0 S	0	0.0	0:00.07	softirq-tasklet
106	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-sched/8
107	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-rcu/8
108	root	RT	0	0	0	0 S	0	0.0	0:00.00	watchdog/8
109	root	5	-10	0	0	0 S	0	0.0	0:00.00	desched/8
110	root	RT	0	0	0	0 S	0	0.0	0:00.00	migration/9
111	root	RT	0	0	0	0 S	0	0.0	0:00.00	posix_cpu_timer
112	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-high/9
113	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-timer/9
114	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-tx/
115	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-net-rx/
116	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-block/9
117	root	-51	0	0	0	0 S	0	0.0	0:01.10	softirq-tasklet
118	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-sched/9
119	root	-51	0	0	0	0 S	0	0.0	0:00.00	softirq-rcu/9
120	root	RT	0	0	0	0 S	0	0.0	0:00.00	watchdog/9
121	root	5	-10	0	0	0 S	0	0.0	0:00.00	desched/9
122	root	-2	-20	0	0	0 S	0	0.0	0:01.14	events/0
123	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/1
124	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/2
125	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/3
126	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/4
127	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/5
128	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/6
129	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/7
130	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/8
131	root	-2	-20	0	0	0 S	0	0.0	0:00.00	events/9
132	root	15	-5	0	0	0 S	0	0.0	0:00.03	khelper
133	root	15	-5	0	0	0 S	0	0.0	0:00.00	kthread
165	root	20	-5	0	0	0 S	0	0.0	0:00.00	kblockd/0
166	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/1
167	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/2
168	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/3
169	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/4
170	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/5
171	root	15	-5	0	0	0 S	0	0.0	0:00.00	kblockd/6
172	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/7
173	root	20	-5	0	0	0 S	0	0.0	0:00.00	kblockd/8
174	root	10	-5	0	0	0 S	0	0.0	0:00.00	kblockd/9
212	root	21	0	0	0	0 S	0	0.0	0:00.00	pdflush
213	root	15	0	0	0	0 S	0	0.0	0:00.00	pdflush
214	root	16	-5	0	0	0 S	0	0.0	0:00.00	kswapd0
215	root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/0
216	root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/1
217	root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/2
218	root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/3
219	root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/4

show system top

220 root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/5
221 root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/6
222 root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/7
223 root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/8
224 root	10	-5	0	0	0 S	0	0.0	0:00.00	flush_filesd/9
225 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/0
226 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/1
227 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/2
228 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/3
229 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/4
230 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/5
231 root	16	-5	0	0	0 S	0	0.0	0:00.00	aio/6
232 root	20	-5	0	0	0 S	0	0.0	0:00.00	aio/7
233 root	20	-5	0	0	0 S	0	0.0	0:00.00	aio/8
234 root	20	-5	0	0	0 S	0	0.0	0:00.00	aio/9
799 root	25	0	0	0	0 S	0	0.0	0:00.00	mtdblockd
857 root	10	-5	0	0	0 S	0	0.0	0:00.04	kjournald
868 root	10	-5	0	0	0 S	0	0.0	0:00.00	kjournald
907 root	15	0	0	0	0 S	0	0.0	0:00.00	Octeon Poll Thr
920 root	18	0	4420	804	628 D	0	0.1	0:00.00	insmod
991 root	23	0	0	0	0 S	0	0.0	0:00.00	HATHREAD
1014 root	15	0	4560	992	748 S	0	0.1	0:00.00	sshd
1076 root	19	0	4484	880	748 S	0	0.1	0:00.00	gettyOrMwar
1079 root	20	0	896m	480m	20m S	0	49.0	1:42.23	switchdrvrv
1238 root	16	-5	0	0	0 S	0	0.0	0:00.00	kjournald
1245 root	0	-20	0	0	0 S	0	0.0	0:00.00	loop3
1254 root	25	0	25880	3308	2556 S	0	0.3	0:00.62	licensed
1554 root	16	0	4420	836	708 S	0	0.1	0:00.00	sh

show tacacs acct statistics

To display detailed radio frequency identification (RFID) information for a specified tag, use the **show tacacs acct statistics** command.

show tacacs acct statistics

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display detailed RFID information:

```
(Cisco Controller) > show tacacs acct statistics
Accounting Servers:
Server Index..... 1
Server Address..... 10.0.0.0
Msg Round Trip Time..... 0 (1/100 second)
First Requests..... 1
Retry Requests..... 0
Accounting Response..... 0
Accounting Request Success..... 0
Accounting Request Failure..... 0
Malformed Msgs..... 0
Bad Authenticator Msgs..... 0
Pending Requests..... -1
Timeout Requests..... 1
Unknowntype Msgs..... 0
Other Drops..... 0
```

show tacacs auth statistics

show tacacs auth statistics

To display TACACS+ server authentication statistics, use the **show tacacs auth statistics** command.

show tacacs auth statistics

Syntax Description This command has no arguments or keywords.

Command Default None

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display TACACS server authentication statistics:

```
(Cisco Controller) > show tacacs auth statistics
Authentication Servers:
Server Index..... 2
Server Address..... 10.0.0.2
Msg Round Trip Time..... 0 (msec)
First Requests..... 0
Retry Requests..... 0
Accept Responses..... 0
Reject Responses..... 0
Error Responses..... 0
Restart Responses..... 0
Follow Responses..... 0
GetData Responses..... 0
Encrypt no secret Responses..... 0
Challenge Responses..... 0
Malformed Msgs..... 0
Bad Authenticator Msgs..... 0
Pending Requests..... 0
Timeout Requests..... 0
Unknowntype Msgs..... 0
Other Drops..... 0
```

show tacacs summary

To display TACACS+ server summary information, use the **show tacacs summary** command.

show tacacs summary

Syntax Description	This command has no arguments or keywords.		
Command Default	None		
Command History	Release	Modification	
	7.6	This command was introduced in a release earlier than Release 7.6.	
Command History	Release	Modification	
	8.3	This command was introduced.	

The following example shows how to display TACACS server summary information:

```
(Cisco Controller) > show tacacs summary
Authentication Servers
Idx Server Address Port State Tout
--- -----
2 10.0.0.1 49 Enabled 30
Accounting Servers
Idx Server Address Port State Tout
--- -----
1 10.0.0.0 49 Enabled 5
Authorization Servers
Idx Server Address Port State Tout
--- -----
3 10.0.0.3 49 Enabled 5
Idx Server Address Port State Tout
--- -----
4 2001:9:6:40::623 49 Enabled 5
...
```

Related Commands	config tacacs acct config tacacs athr config tacacs auth show tacacs summary show tacacs athr statistics show tacacs auth statistics
-------------------------	---

show tech-support

show tech-support

To display Cisco wireless LAN controller variables frequently requested by Cisco Technical Assistance Center (TAC), use the **show tech-support** command.

show tech-support

Syntax Description This command has no arguments or keywords.

Command Default None.

Command History	Release	Modification
	8.3	This command was introduced.

8.3 This command was introduced.

This example shows how to display system resource information:

```
> show tech-support
Current CPU Load..... 0%
System Buffers
    Max Free Buffers..... 4608
    Free Buffers..... 4604
    Buffers In Use..... 4
Web Server Resources
    Descriptors Allocated..... 152
    Descriptors Used..... 3
    Segments Allocated..... 152
    Segments Used..... 3
System Resources
    Uptime..... 747040 Secs
    Total Ram..... 127552 Kbytes
    Free Ram..... 19540 Kbytes
    Shared Ram..... 0 Kbytes
    Buffer Ram..... 460 Kbytes
```

show time

To display the Cisco wireless LAN controller time and date, use the **show time** command.

show time

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None.
------------------------	-------

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display the controller time and date when authentication is not enabled:

```
> show time
Time..... Wed Apr 13 09:29:15 2011
Timezone delta..... 0:0
Timezone location..... (GMT +5:30) Colombo, New Delhi, Chennai, Kolkata
NTP Servers
    NTP Polling Interval..... 3600
        Index      NTP Key Index      NTP Server      NTP Msg Auth Status
    -----
        1            0                9.2.60.60        AUTH DISABLED
```

This example shows successful authentication of NTP Message results in the AUTH Success:

```
> show time
Time..... Thu Apr 7 13:56:37 2011
Timezone delta..... 0:0
Timezone location..... (GMT +5:30) Colombo, New Delhi, Chennai, Kolkata
NTP Servers
    NTP Polling Interval..... 3600
        Index      NTP Key Index      NTP Server      NTP Msg Auth Status
    -----
        1            1                9.2.60.60        AUTH SUCCESS
```

This example shows that if the packet received has errors, then the NTP Msg Auth status will show AUTH Failure:

```
> show time
Time..... Thu Apr 7 13:56:37 2011
Timezone delta..... 0:0
Timezone location..... (GMT +5:30) Colombo, New Delhi, Chennai, Kolkata
NTP Servers
    NTP Polling Interval..... 3600
        Index      NTP Key Index      NTP Server      NTP Msg Auth Status
    -----
        1            10               9.2.60.60        AUTH FAILURE
```

This example shows that if there is no response from NTP server for the packets, the NTP Msg Auth status will be blank:

show time

```
> show time
Time..... Thu Apr 7 13:56:37 2011
Timezone delta..... 0:0
Timezone location..... (GMT +5:30) Colombo, New Delhi, Chennai,
Kolkata
NTP Servers
    NTP Polling Interval..... 3600
    Index      NTP Key Index      NTP Server      NTP Msg Auth Status
-----
    1           11             9.2.60.60
```

Related Commands

config time manual
config time ntp
config time timezone
config time timezone location

show trapflags

To display the Cisco wireless LAN controller Simple Network Management Protocol (SNMP) trap flags, use the **show trapflags** command.

show trapflags

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None.
------------------------	-------

Command History	Release	Modification
	8.3	This command was introduced.

This example shows how to display controller SNMP trap flags:

```
> show trapflags
Authentication Flag..... Enable
Link Up/Down Flag..... Enable
Multiple Users Flag..... Enable
Spanning Tree Flag..... Enable
Client Related Traps
    802.11 Disassociation..... Disable
    802.11 Association..... Disabled
    802.11 Deauthenticate..... Disable
    802.11 Authenticate Failure..... Disable
    802.11 Association Failure..... Disable
    Authentication..... Disabled
    Excluded..... Disable
    Max Client Warning Threshold..... 90%
    Nac-Alert Traps..... Disabled
    RFID Related Traps
        Max RFIDs Warning Threshold..... 90%

802.11 Security related traps
    WEP Decrypt Error..... Enable
    IDS Signature Attack..... Disable

Cisco AP
    Register..... Enable
    InterfaceUp..... Enable
Auto-RF Profiles
    Load..... Enable
    Noise..... Enable
    Interference..... Enable
    Coverage..... Enable
Auto-RF Thresholds
    tx-power..... Enable
    channel..... Enable
    antenna..... Enable
AAA
    auth..... Enable
    servers..... Enable
rogueap..... Enable
adjchannel-rogueap..... Disabled
wps..... Enable
```

show trapflags

```

configsav..... Enable
IP Security
    esp-auth..... Enable
    esp-replay..... Enable
    invalidSPI..... Enable
    ike-neg..... Enable
    suite-neg..... Enable
    invalid-cookie..... Enable
Mesh
    auth failure..... Enabled
    child excluded parent..... Enabled
    parent change..... Enabled
    child moved..... Enabled
    excessive parent change..... Enabled
    onset SNR..... Enabled
    abate SNR..... Enabled
    console login..... Enabled
    excessive association..... Enabled
    default bridge group name..... Enabled
    excessive hop count..... Disabled
    excessive children..... Enabled
    sec backhaul change..... Disabled

```

Related Commands

config trapflags 802.11-Security
config trapflags aaa
config trapflags ap
config trapflags authentication
config trapflags client
config trapflags configsav
config trapflags IPsec
config trapflags linkmode

show traplog

To display the Cisco wireless LAN controller Simple Network Management Protocol (SNMP) trap log, use the **show traplog** command.

show traplog

Syntax Description	This command has no arguments or keywords.				
Command Default	None				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>7.6</td> <td>This command was introduced in a release earlier than Release 7.6.</td> </tr> </tbody> </table>	Release	Modification	7.6	This command was introduced in a release earlier than Release 7.6.
Release	Modification				
7.6	This command was introduced in a release earlier than Release 7.6.				
Command History	<table border="1"> <thead> <tr> <th>Release</th> <th>Modification</th> </tr> </thead> <tbody> <tr> <td>8.3</td> <td>This command was introduced.</td> </tr> </tbody> </table>	Release	Modification	8.3	This command was introduced.
Release	Modification				
8.3	This command was introduced.				

The following is a sample output of the **show traplog** command:

```
(Cisco Controller) > show traplog
Number of Traps Since Last Reset..... 2447
Number of Traps Since Log Last Displayed... 2447
Log System Time           Trap
-----
0 Thu Aug  4 19:54:14 2005 Rogue AP : 00:0b:85:52:62:fe detected on Base Rad
io MAC : 00:0b:85:18:b6:50  Interface no:1(802.11
b/g) with RSSI: -78 and SNR: 10
1 Thu Aug  4 19:54:14 2005 Rogue AP : 00:0b:85:52:19:d8 detected on Base Rad
io MAC : 00:0b:85:18:b6:50  Interface no:1(802.11
b/g) with RSSI: -72 and SNR: 16
2 Thu Aug  4 19:54:14 2005 Rogue AP : 00:0b:85:26:a1:8d detected on Base Rad
io MAC : 00:0b:85:18:b6:50  Interface no:1(802.11
b/g) with RSSI: -82 and SNR: 6
3 Thu Aug  4 19:54:14 2005 Rogue AP : 00:0b:85:14:b3:4f detected on Base Rad
io MAC : 00:0b:85:18:b6:50  Interface no:1(802.11
b/g) with RSSI: -56 and SNR: 30
Would you like to display more entries? (y/n)
```

show tunnel profile summary

show tunnel profile summary

To show the summary of all the profiles, use the **show tunnel profile** command.

show tunnel profile { summary | detail { <profile-name> } }

Syntax Description	<p><i>summary</i> Summary of all profiles.</p> <p><i>detail</i> Shows details of a specific profile.</p> <p><i>profile-name</i> Name of the profile.</p>				
Command Default	None				
Command History	<table border="1"> <thead> <tr> <th colspan="2">Release Modification</th> </tr> </thead> <tbody> <tr> <td>8.1</td><td>This command was introduced.</td></tr> </tbody> </table>	Release Modification		8.1	This command was introduced.
Release Modification					
8.1	This command was introduced.				

The following example shows how to display the summary of all the profiles:

```
show tunnel profile summary
```

show tunnel profile-detail

To show details of a specific profile, use the **show tunnel profile** command.

show tunnel profile detail *profile-name*

Syntax Description	detail Displays details of a specific profile. <i>profile-name</i> Name of the profile.
Command Default	None
Command History	Release Modification 8.1 This command was introduced.

The following example shows how to display specific profile details:

```
show tunnel profile detail test
```

show tunnel eogre-summary

show tunnel eogre-summary

To show the global configuration summary, use the **show tunnel eogre** command.

show tunnel eogre summary

Syntax Description	summary Displays the global configuration summary.
Command Default	None
Command History	Release Modification 8.1 This command was introduced.

The following example shows how to display the global configuration details:

```
(Cisco Controller) > show tunnel eogre summary
```

show tunnel eogre-statistics

To display the EoGRE Tunnel statistics, use the **show tunnel eogre** command.

show tunnel eogrestatistics

Syntax Description	statistics Displays the EoGRE Tunnel statistics.
Command Default	None
Command History	Release Modification

8.1 This command was introduced.

The following example shows how to display the EoGRE Tunnel statistics details:

```
show tunnel eogre statistics
```

show tunnel eogre-domain-summary

show tunnel eogre-domain-summary

To display the EoGRE domain summary, use the **show tunnel eogre** command.

show tunnel eogredomainsummary

Syntax Description	summary Displays the EoGRE domain summary.
Command Default	None
Command History	Release Modification 8.1 This command was introduced.

The following example shows how to display the EoGRE domain summary:

```
show tunnel eogre domain summary
```

show tunnel eogre gateway

To view the EoGRE tunnel gateway summary and statistics, use the **show tunnel eogre** command.

show tunnel eogre gateway {summary | statistics}

Syntax Description	summary Displays the EoGRE tunnel gateway summary. statistics Displays the EoGRE tunnel gateway statistics.						
Command Default	None						
Usage Guidelines	The show tunnel eogre gateway summary command lists details of only the FlexConnect central switching clients and Local Mode AP clients. To view the details of FlexConnect local switching clients, use the show ap eogre gateway ap-name command.						
Command History	<table><thead><tr><th>Release</th><th>Modification</th></tr></thead><tbody><tr><td>8.1</td><td>This command was introduced.</td></tr><tr><td>8.5</td><td>The statistics parameter was added.</td></tr></tbody></table>	Release	Modification	8.1	This command was introduced.	8.5	The statistics parameter was added.
Release	Modification						
8.1	This command was introduced.						
8.5	The statistics parameter was added.						

show watchlist

show watchlist

To display the client watchlist, use the **show watchlist** command.

show watchlist

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

Command History	Release	Modification
	8.3	This command was introduced.

The following example shows how to display the client watchlist information:

```
(Cisco Controller) >show watchlist
client watchlist state is disabled
```

show wlan

To display configuration information for a specified wireless LAN or a foreign access point, or to display wireless LAN summary information, use the **show wlan** command.

show wlan { apgroups | summary | wlan_id | foreignAp | lobby-admin-access }

Syntax Description	apgroups Displays access point group information. summary Displays a summary of all wireless LANs. wlan_id Displays the configuration of a WLAN. The Wireless LAN id to 512. foreignAp Displays the configuration for support of foreign access points. lobby-admin-access Display all wlans that have lobby-admin-access enabled.						
Command Default	None						
Usage Guidelines	For 802.1X client security type, which creates the PMK cache, the maximum session timeout that can be set is 86400 seconds when the session timeout is disabled. For other client security such as open, WebAuth, and PSK for which the PMK cache is not created, the session timeout value is shown as infinite when session timeout is disabled.						
Command History	<table border="1"> <thead> <tr> <th>Release</th><th>Modification</th></tr> </thead> <tbody> <tr> <td>7.6</td><td>This command was introduced in a release earlier than Release 7.6.</td></tr> <tr> <td>8.4</td><td>Shows WLANs which have lobby-admin-access enabled.</td></tr> </tbody> </table>	Release	Modification	7.6	This command was introduced in a release earlier than Release 7.6.	8.4	Shows WLANs which have lobby-admin-access enabled.
Release	Modification						
7.6	This command was introduced in a release earlier than Release 7.6.						
8.4	Shows WLANs which have lobby-admin-access enabled.						
Command History	<table border="1"> <thead> <tr> <th>Release</th><th>Modification</th></tr> </thead> <tbody> <tr> <td>8.3</td><td>This command was introduced.</td></tr> </tbody> </table>	Release	Modification	8.3	This command was introduced.		
Release	Modification						
8.3	This command was introduced.						

The following example shows how to display a summary of wireless LANs for wlan_id 1:

```
(Cisco Controller) >show wlan 1
WLAN Identifier..... 1
Profile Name..... aicha
Network Name (SSID)..... aicha
Status..... Enabled
MAC Filtering..... Disabled
Broadcast SSID..... Enabled
AAA Policy Override..... Disabled
Network Admission Control
    RADIUS Profiling Status ..... Disabled
    DHCP ..... Disabled
    HTTP ..... Disabled
Client Profiling Status ..... Disabled
    DHCP ..... Disabled
    HTTP ..... Disabled
```

show wlan

Radius-NAC State.....	Enabled
SNMP-NAC State.....	Enabled
Quarantine VLAN.....	0
Maximum number of Associated Clients.....	0
Maximum number of Clients per AP Radio.....	200
Number of Active Clients.....	0
Exclusionlist Timeout.....	60 seconds
Session Timeout.....	1800 seconds
User Idle Timeout.....	300 seconds
User Idle Threshold.....	0 Bytes
NAS-identifier.....	Talwar1
CHD per WLAN.....	Enabled
Weauth DHCP exclusion.....	Disabled
Interface.....	management
Multicast Interface.....	Not Configured
WLAN IPv4 ACL.....	unconfigured
WLAN IPv6 ACL.....	unconfigured
mDNS Status.....	Disabled
mDNS Profile Name.....	unconfigured
DHCP Server.....	Default
DHCP Address Assignment Required.....	Disabled
Static IP client tunneling.....	Enabled
PMIPv6 Mobility Type.....	none
Quality of Service.....	Silver (best effort)
Per-SSID Rate Limits.....	Upstream Downstream
Average Data Rate.....	0 0
Average Realtime Data Rate.....	0 0
Burst Data Rate.....	0 0
Burst Realtime Data Rate.....	0 0
Per-Client Rate Limits.....	Upstream Downstream
Average Data Rate.....	0 0
Average Realtime Data Rate.....	0 0
Burst Data Rate.....	0 0
Burst Realtime Data Rate.....	0 0
Scan Defer Priority.....	4,5,6
Scan Defer Time.....	100 milliseconds
WMM.....	Allowed
WMM UAPSD Compliant Client Support.....	Disabled
Media Stream Multicast-direct.....	Disabled
CCX - AironetIE Support.....	Enabled
CCX - Gratuitous ProbeResponse (GPR).....	Disabled
CCX - Diagnostics Channel Capability.....	Disabled
Dot11-Phone Mode (7920).....	Disabled
Wired Protocol.....	None
Passive Client Feature.....	Disabled
IPv6 Support.....	Disabled
Peer-to-Peer Blocking Action.....	Disabled
Radio Policy.....	All
DTIM period for 802.11a radio.....	1
DTIM period for 802.11b radio.....	1
Radius Servers	
Authentication.....	Global Servers
Accounting.....	Global Servers
Interim Update.....	Disabled
Dynamic Interface.....	Disabled
Local EAP Authentication.....	Enabled (Profile 'Controller_Local_EAP')
Radius NAI-Realm.....	Enabled
Security	
802.11 Authentication:.....	Open System
FT Support.....	Disabled
Static WEP Keys.....	Disabled
802.1X.....	Disabled
Wi-Fi Protected Access (WPA/WPA2).....	Enabled
WPA (SSN IE).....	Enabled

TKIP Cipher.....	Disabled
AES Cipher.....	Enabled
WPA2 (RSN IE).....	Enabled
TKIP Cipher.....	Disabled
AES Cipher.....	Enabled
Auth Key Management	
802.1x.....	Enabled
PSK.....	Disabled
CCKM.....	Enabled
FT(802.11r).....	Disabled
FT-PSK(802.11r).....	Disabled
PMF-1X(802.11w).....	Enabled
PMF-PSK(802.11w).....	Disabled
FT Reassociation Timeout.....	20
FT Over-The-Air mode.....	Enabled
FT Over-The-Ds mode.....	Enabled
GTK Randomization.....	Disabled
SKC Cache Support.....	Disabled
CCKM TSF Tolerance.....	1000
Wi-Fi Direct policy configured.....	Disabled
EAP-Passthrough.....	Disabled
CKIP	Disabled
IP Security.....	Disabled
IP Security Passthru.....	Disabled
Web Based Authentication.....	Disabled
Web-Passthrough.....	Disabled
Conditional Web Redirect.....	Disabled
Splash-Page Web Redirect.....	Disabled
Auto Anchor.....	Disabled
FlexConnect Local Switching.....	Enabled
flexconnect Central Dhcp Flag.....	Disabled
flexconnect nat-pat Flag.....	Disabled
flexconnect Dns Override Flag.....	Disabled
FlexConnect Vlan based Central Switching	Disabled
FlexConnect Local Authentication.....	Disabled
FlexConnect Learn IP Address.....	Enabled
Client MFP.....	Optional
PMF.....	Disabled
PMF Association Comeback Time.....	1
PMF SA Query RetryTimeout.....	200
Tkip MIC Countermeasure Hold-down Timer.....	60
Call Snooping.....	Disabled
Roamed Call Re-Anchor Policy.....	Disabled
SIP CAC Fail Send-486-Busy Policy.....	Enabled
SIP CAC Fail Send Dis-Association Policy.....	Disabled
KTS based CAC Policy.....	Disabled
Band Select.....	Disabled
Load Balancing.....	Disabled
Mobility Anchor List	
WLAN ID IP Address Status	
-----	-----
802.11u.....	Enabled
Network Access type.....	Chargeable Public Network
Internet service.....	Enabled
Network Authentication type.....	Not Applicable
HESSID.....	00:00:00:00:00:00
IP Address Type Configuration	
IPv4 Address type.....	Available
IPv6 Address type.....	Not Known
Roaming Consortium List	
Index OUI List In Beacon	
-----	-----
1 313131 Yes	

show wlan

```

2          DDBBCC      No
3          DDDDDD      Yes
Realm configuration summary
  Realm index..... 1
  Realm name..... jobin
    EAP index..... 1
    EAP method..... Unsupported
Index  Inner Authentication      Authentication Method
-----  -----
  1          Credential Type      SIM
  2  Tunneled Eap Credential Type      SIM
  3          Credential Type      SIM
  4          Credential Type      USIM
  5          Credential Type      Hardware Token
  6          Credential Type      SoftToken
Domain name configuration summary
Index  Domain name
-----
  1  rom3
  2  ram
  3  rom1

Hotspot 2.0..... Enabled

Operator name configuration summary
Index  Language  Operator name
-----  -----
  1        ros      Robin

Port config summary
Index  IP protocol  Port number  Status
-----  -----
  1          1          0          Closed
  2          1          0          Closed
  3          1          0          Closed
  4          1          0          Closed
  5          1          0          Closed
  6          1          0          Closed
  7          1          0          Closed
WAN Metrics Info
  Link status..... Up
  Symmetric Link..... No
  Downlink speed..... 4 kbps
  Uplink speed..... 4 kbps

MSAP Services..... Disabled
Local Policy
-----
Priority  Policy Name
-----
  1        Teacher_access_policy

```

The following example shows how to display a summary of all WLANs:

```
(Cisco Controller) >show wlan summary
Number of WLANs..... 1

WLAN ID  WLAN Profile Name / SSID      Status      Interface Name      PMIPv6
Mobility
-----
-----
  1        apsso / apsso      Disabled      management      none
```

The following example shows how to display the configuration for support of foreign access points:

```
(Cisco Controller) >show wlan foreignap
Foreign AP support is not enabled.
```

The following example shows how to display the AP groups:

```
(Cisco Controller) >show wlan apgroups
Total Number of AP Groups..... 1
Site Name..... APUser
Site Description..... <none>
Venue Name..... Not configured
Venue Group Code..... Unspecified
Venue Type Code..... Unspecified
Language Code..... Not configured
AP Operating Class..... 83,84,112,113,115,116,117,118,123
RF Profile
-----
2.4 GHz band..... <none>
5 GHz band..... <none>
WLAN ID      Interface      Network Admission Control      Radio Policy
-----      -----      -----
14          int_4          Disabled          All
AP Name      Slots      AP Model      Ethernet MAC      Location      Port
Country     Priority
-----      -----      -----      -----
Ibiza        2          AIR-CAP2602I-A-K9    44:2b:03:9a:8a:73  default location  1
US          1
Larch        2          AIR-CAP3502E-A-K9    f8:66:f2:ab:23:95  default location  1
US          1
Zest         2          AIR-CAP3502I-A-K9    00:22:90:91:6d:b6      ren  1
US          1
Number of Clients..... 1
MAC Address      AP Name      Status      Device Type
-----      -----
24:77:03:89:9b:f8      ap2      Associated      Android
```

show wps ap-authentication summary

show wps ap-authentication summary

To display the access point neighbor authentication configuration on the controller, use the **show wps ap-authentication summary** command.

show wps ap-authentication summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of the Wireless Protection System (WPS) access point neighbor authentication:

```
(Cisco Controller) > show wps ap-authentication summary
AP neighbor authentication is <disabled>.
Authentication alarm threshold is 1.
RF-Network Name: <B1>
```

Related Commands config wps ap-authentication

show wps cids-sensor

To display Intrusion Detection System (IDS) sensor summary information or detailed information on a specified Wireless Protection System (WPS) IDS sensor, use the **show wps cids-sensor** command.

show wps cids-sensor {summary | detail *index*}

Syntax Description	summary	Displays a summary of sensor settings.
	detail	Displays all settings for the selected sensor.
	<i>index</i>	IDS sensor identifier.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display all settings for the selected sensor:

Related Commands config wps ap-authentication

show wps mfp

show wps mfp

To display Management Frame Protection (MFP) information, use the **show wps mfp** command.

show wps mfp {summary | statistics}

Syntax Description	summary	Displays the MFP configuration and status.
	statistics	Displays MFP statistics.
Command Default	None	
Command History		
	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of the MFP configuration and status:

```
(Cisco Controller) > show wps mfp summary
Global Infrastructure MFP state..... DISABLED (*all infrastructure
settings are overridden)
Controller Time Source Valid..... False
WLAN ID WLAN Name WLAN Status Infra. Protection Client Protection
----- -----
1 homeap Disabled *Enabled Optional but inactive
(WPA2 not configured)
2 7921 Enabled *Enabled Optional but inactive
(WPA2 not configured)
3 open1 Enabled *Enabled Optional but inactive
(WPA2 not configured)
4 7920 Enabled *Enabled Optional but inactive
(WPA2 not configured)
AP Name Infra. Validation Operational --Infra. Capability--
Validation Radio State Protection Validation
----- -----
AP1252AG-EW *Enabled b/g Down Full Full
a Down Full Full
```

The following example shows how to display the MFP statistics:

```
(Cisco Controller) > show wps mfp statistics
BSSID Radio Validator AP Last Source Addr Found Error Type
Count Frame Types
----- -----
no errors
```

Related Commands config wps mfp

show wps shun-list

To display the Intrusion Detection System (IDS) sensor shun list, use the **show wps shun-list** command.

show wps shun-list

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the IDS system sensor shun list:

```
(Cisco Controller) > show wps shun-list
```

Related Commands	config wps shun-list re-sync
-------------------------	-------------------------------------

show wps signature detail

show wps signature detail

To display installed signatures, use the **show wps signature detail** command.

show wps signature detail *sig-id*

Syntax Description	<i>sig-id</i>	Signature ID of an installed signature.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

This example shows how to display information on the attacks detected by standard signature 1:

```
(Cisco Controller) > show wps signature detail 1
Signature-ID..... 1
Precedence..... 1
Signature Name..... Bcast deauth
Type..... standard
FrameType..... management
State..... enabled
Action..... report
Tracking..... per Signature and Mac
Signature Frequency..... 500 pkts/interval
Signature Mac Frequency..... 300 pkts/interval
Interval..... 10 sec
Quiet Time..... 300 sec
Description..... Broadcast Deauthentication Frame
Patterns:
    0 (Header) :0x0:0x0
    4 (Header) :0x0:0x0
```

Related Commands

- config wps signature**
- config wps signature frequency**
- config wps signature mac-frequency**
- config wps signature interval**
- config wps signature quiet-time**
- config wps signature reset**
- show wps signature events**
- show wps signature summary**
- show wps summary**

show wps signature events

To display more information about the attacks detected by a particular standard or custom signature, use the **show wps signature events** command.

```
show wps signature events {summary | {standard | custom} precedenceID {summary | detailed}}
```

Syntax Description	summary	Displays all tracking signature summary information.
	standard	Displays Standard Intrusion Detection System (IDS) signature settings.
	custom	Displays custom IDS signature settings.
	<i>precedenceID</i>	Signature precedence identification value.
	detailed	Displays tracking source MAC address details.
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the number of attacks detected by all enabled signatures:

```
(Cisco Controller) > show wps signature events summary
Precedence   Signature Name      Type      # Events
-----       -----
1           Bcast deauth        Standard    2
2           NULL probe resp 1  Standard    1
```

This example shows how to display a summary of information on the attacks detected by standard signature 1:

```
(Cisco Controller) > show wps signature events standard 1 summary
Precedence..... 1
Signature Name..... Bcast deauth
Type..... Standard
Number of active events..... 2
Source MAC Addr      Track Method     Frequency # APs Last Heard
-----
00:a0:f8:58:60:dd  Per Signature   50          1      Wed Oct 25 15:03:05
2006
00:a0:f8:58:60:dd  Per Mac        30          1      Wed Oct 25 15:02:53
2006
```

show wps signature events

Related Commands

config wps signature frequency
config wps signature mac-frequency
config wps signature interval
config wps signature quiet-time
config wps signature reset
config wps signature
show wps signature summary
show wps summary

show wps signature summary

To see individual summaries of all of the standard and custom signatures installed on the controller, use the **show wps signature summary** command.

show wps signature summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of all of the standard and custom signatures:

```
(Cisco Controller) > show wps signature summary
Signature-ID..... 1
Precedence..... 1
Signature Name..... Bcast deauth
Type..... standard
FrameType..... management
State..... enabled
Action..... report
Tracking..... per Signature and Mac
Signature Frequency..... 50 pkts/interval
Signature Mac Frequency..... 30 pkts/interval
Interval..... 1 sec
Quiet Time..... 300 sec
Description..... Broadcast
Deauthentication Frame
Patterns:
    0 (Header) :0x00c0:0x00ff
    4 (Header) :0x01:0x01
...
```

Related Commands	config wps signature frequency config wps signature interval config wps signature quiet-time config wps signature reset show wps signature events show wps summary config wps signature mac-frequency
-------------------------	---

show wps signature summary

config wps signature

show wps summary

To display Wireless Protection System (WPS) summary information, use the **show wps summary** command.

show wps summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display WPS summary information:

```
(Cisco Controller) > show wps summary
Auto-Immune
    Auto-Immune..... Disabled
Client Exclusion Policy
    Excessive 802.11-association failures..... Enabled
    Excessive 802.11-authentication failures..... Enabled
    Excessive 802.1x-authentication..... Enabled
    IP-theft..... Enabled
    Excessive Web authentication failure..... Enabled
Trusted AP Policy
    Management Frame Protection..... Disabled
    Mis-configured AP Action..... Alarm Only
        Enforced encryption policy..... none
        Enforced preamble policy..... none
        Enforced radio type policy..... none
        Validate SSID..... Disabled
    Alert if Trusted AP is missing..... Disabled
    Trusted AP timeout..... 120
Untrusted AP Policy
    Rogue Location Discovery Protocol..... Disabled
    RLDP Action..... Alarm Only
    Rogue APs
        Rogues AP advertising my SSID..... Alarm Only
        Detect and report Ad-Hoc Networks..... Enabled
    Rogue Clients
        Validate rogue clients against AAA..... Enabled
        Detect trusted clients on rogue APs..... Alarm Only
        Rogue AP timeout..... 1300
Signature Policy
    Signature Processing..... Enabled
...
```

show wps summary**Related Commands**

config wps signature frequency
config wps signature interval
config wps signature quiet-time
config wps signature reset
show wps signature events
show wps signature mac-frequency
show wps summary
config wps signature
config wps signature interval

show wps wips statistics

To display the current state of the Cisco Wireless Intrusion Prevention System (wIPS) operation on the controller, use the **show wps wips statistics** command.

show wps wips statistics

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display the statistics of the wIPS operation:

```
(Cisco Controller) > show wps wips statistics
Policy Assignment Requests..... 1
Policy Assignment Responses..... 1
Policy Update Requests..... 0
Policy Update Responses..... 0
Policy Delete Requests..... 0
Policy Delete Responses..... 0
Alarm Updates..... 13572
Device Updates..... 8376
Device Update Requests..... 0
Device Update Responses..... 0
Forensic Updates..... 1001
Invalid WIPS Payloads..... 0
Invalid Messages Received..... 0
NMSP Transmitted Packets..... 22950
NMSP Transmit Packets Dropped..... 0
NMSP Largest Packet..... 1377
```

Related Commands	config 802.11 enable config ap mode config ap monitor-mode show ap config show ap monitor-mode summary show wps wips summary
-------------------------	---

show wps wips summary

show wps wips summary

To display the adaptive Cisco Wireless Intrusion Prevention System (wIPS) configuration that the Wireless Control System (WCS) forwards to the controller, use the **show wps wips summary** command.

show wps wips summary

Syntax Description	This command has no arguments or keywords.	
Command Default	None	
Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of the wIPS configuration:

```
(Cisco Controller) > show wps wips summary
Policy Name..... Default
Policy Version..... 3
```

Related Commands	config 802.11 enable config ap mode config ap monitor-mode show ap config show ap monitor-mode summary show wps wips statistics
-------------------------	--

show wps ap-authentication summary

To display the access point neighbor authentication configuration on the controller, use the **show wps ap-authentication summary** command.

show wps ap-authentication summary

Syntax Description	This command has no arguments or keywords.
---------------------------	--

Command Default	None
------------------------	------

Command History	Release	Modification
	7.6	This command was introduced in a release earlier than Release 7.6.

The following example shows how to display a summary of the Wireless Protection System (WPS) access point neighbor authentication:

```
(Cisco Controller) > show wps ap-authentication summary
AP neighbor authentication is <disabled>.
Authentication alarm threshold is 1.
RF-Network Name: <B1>
```

Related Commands	config wps ap-authentication
-------------------------	-------------------------------------

show wps ap-authentication summary