

Aironet Extensions IE (CCX IE)

- Information About Aironet Extensions Information Element, on page 1
- Configuring Aironet Extensions IE (GUI), on page 1
- Configuring Aironet Extensions IE (CLI), on page 2
- Verifying the Addition of AP Name, on page 3

Information About Aironet Extensions Information Element

The Cisco Aironet Extensions Information Element (IE) is an attribute used by Cisco devices for better connectivity. It contains information such as the AP name, device type, radio type, AP load, and the number of associated clients, in the beacon and probe responses of the WLAN. The Cisco Client Extensions use this information to associate with the best AP.

The Aironet Extensions IE configuration is disabled by default. With this feature you can set the AP name not through enabling the whole IE extension, but by just inserting just the AP name.



Note

WLAN shutdown is required only when configuring Aironet Extensions (CCX IE) through the CLI. If CCX IE is enabled via the WebUI, WLAN shutdown is not necessary.

Configuring Aironet Extensions IE (GUI)

Procedure

- Step 1 Choose Configuration > Tags & Profiles > WLANs.
- Step 2 In the WLANs window, click Add.
- Step 3 In the Add WLAN window, under the Advanced tab, check the Aironet IE check box to enable Aironet IE on the WLAN.
- Step 4 Click Apply to Device.

Configuring Aironet Extensions IE (CLI)

Perform this procedure to create a WLAN and enable the Aironet Extensions IE feature on the WLAN:



Note

For more information about the open configuration models, refer to the Programmability Configuration Guide, Cisco IOS XE Amsterdam 17.1.x.

Procedure

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example:	
	Device# configure terminal	
Step 2	wlan profile-name wlan-id [ssid]	Specifies the WLAN name and ID:
	Example: Device(config) # wlan mywlan 34 mywlan-ssid	• <i>profile-name</i> : Profile name. The range is from 1 to 32 alphanumeric characters.
		• wlan-id: WLAN ID. The range is from 1 to 512.
		• <i>ssid</i> : Service Set Identifier (SSID) for this WLAN. If the SSID is not specified, the WLAN profile name is set as the SSID.
		Note By default, the WLAN is disabled.
Step 3	<pre>[no] ccx aironet-iesupport Example: Device(config-wlan)#ccx aironet-iesupport</pre>	Configures the Cisco Client Extensions option
		and sets the support of Aironet IE on the WLAN.
		(Use the no form of this command to disable the configuration.)

What to do next

- **1.** Create a policy tag. For more information about creating policy tags, refer to *Configuring a Policy Tag* (*CLI*).
- **2.** Map the policy tag to the AP. For more information about mapping a policy tag to the AP, refer to *Attaching a Policy Tag and Site Tag to an AP (CLI)*.

Verifying the Addition of AP Name

The following example shows how to verify the addition of the AP Name (using Open Configuration) in the beacon without enabling IE:

```
Device# show wlan id 1
WLAN Profile Name : wlan-test
______
Identifier
                                          : 1
Description
Network Name (SSID)
                                         : wlan2
                                         : Disabled
Status
Broadcast SSID
                                          : Enabled
Advertise-Apname
                                          : Enabled
Universal AP Admin
                                         : Disabled
Max Associated Clients per WLAN
Max Associated Clients per AP per WLAN
Max Associated Clients per AP Radio per WLAN : 200
Number of Active Clients
CHD per WLAN
                                          : Enabled
MMW
                                          : Allowed
Channel Scan Defer Priority:
 Priority (default)
                                          : 5
 Priority (default)
                                          : 6
Scan Defer Time (msecs)
                                          : 100
Media Stream Multicast-direct
                                         : Disabled
CCX - AironetIe Support
                                      : Enabled
                                         : Disabled
Peer-to-Peer Blocking Action
```

Verifying the Addition of AP Name