



OFDMA Support for 11ax Access Points

- [Information About OFDMA Support for 11ax Access Points, on page 1](#)
- [Configuring 11AX \(GUI\), on page 2](#)
- [Configuring Channel Width, on page 2](#)
- [Configuring 802.11ax Radio Parameters \(GUI\), on page 3](#)
- [Configuring 802.11ax Radio Parameters \(CLI\), on page 3](#)
- [Setting up the 802.11ax Radio Parameters, on page 4](#)
- [Configuring OFDMA on a WLAN, on page 5](#)
- [Verifying Channel Width, on page 6](#)
- [Verifying Client Details, on page 7](#)
- [Verifying Radio Configuration, on page 8](#)

Information About OFDMA Support for 11ax Access Points

The Cisco Catalyst 9100 series access points are the next generation WiFi 802.11ax access point, which is ideal for high-density high-definition applications.

The IEEE 802.11ax protocol aims to improve user experience and network performance in high density deployments for both 2.4 GHz and 5 GHz. The 802.11ax APs supports transmission or reception to more than one client simultaneously using Orthogonal Frequency Division Multiplexing (OFDMA).

The IEEE 802.11ax supports uplink MU-MIMO and also adds OFDMA for multiple users in the uplink and downlink. All the users in IEEE 802.11ax OFDMA have the same time allocations and it ends at the same time. In MU-MIMO and OFDMA, multiple stations (STAs) either simultaneously transmit to a single STA or simultaneously receive from a single STA independent data streams over the same radio frequencies.

Supported Modes on 11ax Access Points

The following AP modes are supported:

- Local mode
- Flex-connect mode
- Bridge mode
- Flex+Mesh mode

Configuring 11AX (GUI)

You can configure 11ax for the frequencies, 5 GHz and 2.4 GHz.

Procedure

-
- | | |
|---------------|---|
| Step 1 | Choose Configuration > Radio Configurations > High Throughput. |
| Step 2 | Click the 5 GHz Band tab.
a) Expand the 11ax section.
b) Select the Enable 11ax and Multiple Bssid check boxes, if required.
c) Check either the Select All check box to configure all the data rates or select the desired options from the available data rates list. |
| Step 3 | Click the 2.4 GHz Band tab.
a) Expand the 11ax section.
b) Select the Enable 11ax and Multiple Bssid check boxes, if required.
c) Check either the Select All check box to configure all the data rates or select the desired options from the available data rates list. |
-

Configuring Channel Width

Procedure

	Command or Action	Purpose
Step 1	configure terminal Example: Device# configure terminal	Enters the global configuration mode.
Step 2	ap dot11 { 24ghz 5ghz } rrm channel dca chan-width 160 Example: Device(config)# ap dot11 5ghz rrm channel dca chan-width 160	Configures channel width for 802.11 radios as 160. Use the no form of the command to disable the configuration. Note Cisco Catalyst 9115 and C9120 series APs do not support 80+80 channel width. Cisco Catalyst 9117 series APs do not support OFDMA in 160 channel width.
Step 3	ap dot11 { 24ghz 5ghz } rf-profile <i>profile-name</i> Example:	Configures an RF profile and enters RF profile configuration mode.

	Command or Action	Purpose
	Device(config)# ap dot11 5ghz rf-profile ax-profile	
Step 4	channel chan-width 160 Example: Device(config-rf-profile)# channel chan-width 160	Configures the RF profile DCA channel width.

Configuring 802.11ax Radio Parameters (GUI)

Procedure

-
- Step 1** Choose **Configuration > Radio Configurations > High Throughput > 5 GHz Band > 11ax**.
- Step 2** Check or uncheck the **Enable 11 n** check box.
- Step 3** Check the check boxes for the desired MCS/(data rate) or to select all of them, check the **Select All** check box.
- Step 4** Click **Apply**.
- Step 5** Choose **Configuration > Radio Configurations > High Throughput > 2.4 GHz Band > 11ax**.
- Step 6** Check or uncheck the **Enable 11 n** check box.
- Step 7** Check the check boxes for the desired MCS/(data rate) or to select all of them, check the **Select All** check box.
- Step 8** Click **Apply**.
- Step 9** Choose **Configuration > Wireless > Access Points**.
- Step 10** Click the Access Point.
- Step 11** In the **Edit AP** dialog box, enable the **LED State** toggle button and choose the LED brightness level from the **LED Brightness Level** drop-down list.
- Step 12** Click **Update and Apply to Device**.
-

Configuring 802.11ax Radio Parameters (CLI)

Follow the procedure given below to configure radio parameters:

Procedure

	Command or Action	Purpose
Step 1	configure terminal Example: Device# configure terminal	Enters the global configuration mode.

	Command or Action	Purpose
Step 2	ap dot11 { 24ghz 5ghz 6ghz } dot11ax Example: Device(config)# ap dot11 6ghz dot11ax	Configures 802.11 6GHz dot11ax parameters. Use the no form of the command to disable the configuration.
Step 3	ap dot11 { 24ghz 5ghz 6ghz } dot11ax mcs tx index <i>index</i> spatial-stream <i>spatial-stream-value</i> Example: Device(config)# ap dot11 5ghz dot11ax mcs tx index 11 spatial-stream 8	Enables the 11ax 2.4-Ghz, 5-Ghz, or 6-Ghz band modulation and coding scheme (MCS) transmission rates.
Step 4	ap led-brightness <i>brightness-level</i> Example: Device(config)# ap led-brightness 6	(Optional) Configures the led brightness level.

Setting up the 802.11ax Radio Parameters

Procedure

	Command or Action	Purpose
Step 1	enable Example: Device# enable	Enters privileged EXEC mode.
Step 2	ap name <i>ap-name</i> led-brightness-level <i>brightness-level</i> Example: Device# ap name ax-ap led-brightness-level 6	Configures the led brightness level.
Step 3	ap name <i>ap-name</i>dot11 { 24ghz 5ghz } dot11n antenna <i>antenna-port</i> Example: Device# ap name ap1 dot11 5ghz dot11n antenna A	Configures the 802.11n - 5 GHz antenna selection. Use the no form of the command to disable the configuration.
Step 4	ap name <i>ap-name</i> dot11 { 24ghz 5ghz } channel width <i>channel-width</i> Example: Device# ap name ap1 dot11 5ghz channel width 160	Configures 802.11 channel width.

	Command or Action	Purpose
Step 5	<pre>ap name ap-name dot11 {24ghz 5ghz} secondary-80 channel-num</pre> <p>Example:</p> <pre>Device# ap name apl dot11 5ghz secondary-80 12</pre>	Configures the advanced 802.11 secondary 80Mhz channel assignment parameters.

Configuring OFDMA on a WLAN



Note For Cisco Catalyst 9115 and 9120 series APs, the configuration given below are per radio, and not per WLAN. This feature remains enabled on the controller, if it is enabled on any of the WLANs.

Procedure

	Command or Action	Purpose
Step 1	configure terminal <p>Example:</p> <pre>Device# configure terminal</pre>	Enters the global configuration mode.
Step 2	wlan wlan1 <p>Example:</p> <pre>Device(config)# wlan wlan1</pre>	Enters the WLAN configuration mode.
Step 3	dot11ax downlink-ofdma <p>Example:</p> <pre>Device(config-wlan)# dot11ax downlink-ofdma</pre>	Enables the downlink connection that uses the OFDMA technology. Use the no form of the command to disable the configuration.
Step 4	dot11ax uplink-ofdma <p>Example:</p> <pre>Device(config-wlan)# dot11ax uplink-ofdma</pre>	Enables the uplink connection that uses the OFDMA technology .
Step 5	dot11ax downlink-mumimo <p>Example:</p> <pre>Device(config-wlan)# dot11ax downlink-mumimo</pre>	Enables the downlink connection that uses the MUMIMO technology.
Step 6	dot11ax uplink-mumimo <p>Example:</p> <pre>Device(config-wlan)# dot11ax uplink-mumimo</pre>	Enables the uplink connection that uses the MUMIMO technology.

Verifying Channel Width

	Command or Action	Purpose
Step 7	dot11ax twt-broadcast-support Example: Device (config-wlan)# dot11ax twt-broadcast-support	Enables the TWT broadcast support operation.

Verifying Channel Width

To verify the channel width and other channel information, use the following **show** commands:

```
Device# show ap dot11 5ghz summary
AP Name           Mac Address      Slot   Admin State  Oper State  Channel   Width
Txpwr
-----
AP80e0.1d75.6954 80e0.1d7a.7620    1     Enabled       Up          (52)*    160
1(*)

Device# show ap dot11 dual-band summary
AP Name        Subband      Radio Mac      Status      Channel   Power Level  Slot ID
Mode
-----
kartl28021mi    All         002a.1058.38a0  Enabled     (52)*    (1)*      1
REAP

Device# show ap name <ap-name> channel
802.11b/g Current Channel      : 11
Slot ID             : 0
Allowed Channel List : 1,2,3,4,5,6,7,8,9,10,11
802.11a Current Channel ..... 52 (160 MHz)
Slot ID             : 1
Allowed Channel List : 36,40,44,48,52,56,60,64,100,104,108,112,116,132,136,140,149,153,157,161,165

Device# show ap name <ap-name> config slot <slot-num>
.
.
.

Phy OFDM Parameters
Configuration      : Automatic
Current Channel   : 52
Extension Channel : No Extension
Channel Width     : 160 MHz
Allowed Channel List :
36,40,44,48,52,56,60,64,100,104,108,112,116,132,136,140,149,153,157,161,165
TI Threshold      : 0

Device# show ap dot11 5ghz channel
.
.

DCA Sensitivity Level : MEDIUM : 15 dB
DCA 802.11n/ac Channel Width : 160 MHz
DCA Minimum Energy Limit : -95 dBm
.
```

```
Device# show ap rf-profile name <name> detail
.
.
.
Unused Channel List : 165
DCA Bandwidth : 160 MHz
DCA Foreign AP Contribution : Enabled
.
.
```

Verifying Client Details

To verify the client information, use the following **show** commands:

```
Device# show wireless client mac-address <mac-address> detail
```

```
Client MAC Address : a886.ddb2.05e9
Client IPv4 Address : 169.254.175.214
Client IPv6 Addresses : fe80::b510:a381:8099:4747
                           2009:300:300:57:4007:6abb:2c9a:61e2
Client Username: N/A
Voice Client Type : Unknown
AP MAC Address : c025.5c55.e400
AP Name: APe4c7.22b2.948e
Device Type: N/A
Device Version: N/A
AP slot : 0
Client State : Associated
Policy Profile : default-policy-profile
Flex Profile : default-flex-profile
Wireless LAN Id : 1
Wireless LAN Name: SSS_OPEN
BSSID : c025.5c55.e406
Connected For : 23 seconds
Protocol : 802.11ax - 5 GHz
Channel : 8
Client IIF-ID : 0xa0000001
Association Id : 1
Authentication Algorithm : Open System
Client CCX version : No CCX support
Session Timeout : 86400 sec (Remaining time: 86378 sec)
```

```
Device# show wireless client summary
```

Number of Local Clients: 1

MAC Address	AP Name	WLAN	State	Protocol Method
Role				
a886.ddb2.05e9	APe4c7.22b2.948e	1	Run	11ax(5) None
Local				

```
Device# show wireless stats client detail
```

Verifying Radio Configuration

```
Total Number of Clients : 1
```

```
Protocol Statistics
```

Protocol	Client Count
802.11b	: 0
802.11g	: 0
802.11a	: 0
802.11n-2.4GHz	: 0
802.11n-5 GHz	: 0
802.11ac	: 0
802.11ax-5 GHz	: 0
802.11ax-2.4 GHz	: 0
802.11ax-6 GHz	: 1

Verifying Radio Configuration

To verify the radio configuration information, use the following **show** commands:

```
Device# show ap dot11 5ghz network

802.11a Network : Enabled
.
.
.
802.11ax : Enabled
    DynamicFrag : Enabled
    MultiBssid : Disabled
802.11ax MCS Settings:
    MCS 7, Spatial Streams = 1 : Disabled
    MCS 9, Spatial Streams = 1 : Disabled
    MCS 11, Spatial Streams = 1 : Disabled
    MCS 7, Spatial Streams = 2 : Supported
    MCS 9, Spatial Streams = 2 : Supported
    MCS 11, Spatial Streams = 2 : Supported
    MCS 7, Spatial Streams = 3 : Supported
    MCS 9, Spatial Streams = 3 : Disabled
    MCS 11, Spatial Streams = 3 : Disabled
    MCS 7, Spatial Streams = 4 : Supported
    MCS 9, Spatial Streams = 4 : Supported
    MCS 11, Spatial Streams = 4 : Supported
    MCS 7, Spatial Streams = 5 : Supported
    MCS 9, Spatial Streams = 5 : Supported
    MCS 11, Spatial Streams = 5 : Supported
    MCS 7, Spatial Streams = 6 : Supported
    MCS 9, Spatial Streams = 6 : Supported
    MCS 11, Spatial Streams = 6 : Supported
    MCS 7, Spatial Streams = 7 : Supported
    MCS 9, Spatial Streams = 7 : Supported
    MCS 11, Spatial Streams = 7 : Supported
    MCS 7, Spatial Streams = 8 : Supported
    MCS 9, Spatial Streams = 8 : Supported
    MCS 11, Spatial Streams = 8 : Supported
Beacon Interval : 100
.
.
.
Maximum Number of Clients per AP Radio : 200
```

```

Device# show ap dot11 24ghz network

802.11b Network : Enabled
.
.
.
802.11axSupport..... Enabled
    dynamicFrag..... Disabled
    multiBssid..... Disabled
802.11ax : Enabled
    DynamicFrag : Enabled
    MultiBssid : Enabled
802.11ax MCS Settings:
    MCS 7, Spatial Streams = 1 : Supported
    MCS 9, Spatial Streams = 1 : Supported
    MCS 11, Spatial Streams = 1 : Supported
    MCS 7, Spatial Streams = 2 : Supported
    MCS 9, Spatial Streams = 2 : Supported
    MCS 11, Spatial Streams = 2 : Supported
    MCS 7, Spatial Streams = 3 : Supported
    MCS 9, Spatial Streams = 3 : Supported
    MCS 11, Spatial Streams = 3 : Supported
    MCS 7, Spatial Streams = 4 : Disabled
    MCS 9, Spatial Streams = 4 : Disabled
    MCS 11, Spatial Streams = 4 : Disabled
Beacon Interval : 100
.
.
.
Maximum Number of Clients per AP Radio : 200

Device# show ap dot11 6ghz network
802.11 6Ghz Network : Enabled
802.11ax : Enabled
.
.
.
802.11ax MCS Settings:
    MCS 7, Spatial Streams = 1 : Supported
    MCS 9, Spatial Streams = 1 : Supported
    MCS 11, Spatial Streams = 1 : Supported
    MCS 7, Spatial Streams = 2 : Supported
    MCS 9, Spatial Streams = 2 : Supported
    MCS 11, Spatial Streams = 2 : Supported
    MCS 7, Spatial Streams = 3 : Supported
    MCS 9, Spatial Streams = 3 : Supported
    MCS 11, Spatial Streams = 3 : Supported
    MCS 7, Spatial Streams = 4 : Supported
    MCS 9, Spatial Streams = 4 : Supported
    MCS 11, Spatial Streams = 4 : Supported
Beacon Interval : 95
.
.
.
Maximum Number of Clients per AP Radio : 200
WiFi to Cellular RSSI Threshold : -85 dbm
Client Network Preference : default

#show wlan id 1
WLAN Profile Name : wlanon66
=====
Identifier : 1
Description :
Network Name (SSID) : wlanon66
Status : Enabled

```

Verifying Radio Configuration

```

Broadcast SSID : Enabled
Advertise-Apname : Enabled
Universal AP Admin : Disabled
Max Associated Clients per WLAN : 0
Max Associated Clients per AP per WLAN : 0
Max Associated Clients per AP Radio per WLAN : 200
OKC : Enabled
Number of Active Clients : 0
CHD per WLAN : Enabled
WMM : Allowed
WiFi Direct Policy : Disabled
.

.

Operational State of Radio Bands
 2.4ghz : UP
 5ghz : UP
 6ghz : DOWN (Required config: Disable WPA2 and
Enable WPA3 & dot11ax)
DTIM period for 802.11a radio :
DTIM period for 802.11b radio :
Local EAP Authentication : Disabled
Mac Filter Authorization list name : Disabled
Mac Filter Override Authorization list name : Disabled
Accounting list name :
 802.1x authentication list name : Disabled
 802.1x authorization list name : Disabled
Security
  802.11 Authentication : Open System
.

.

802.11ac MU-MIMO : Enabled
802.11ax parameters
  802.11ax Operation Status : Enabled
  OFDMA Downlink : Enabled
  OFDMA Uplink : Enabled
  MU-MIMO Downlink : Enabled
  MU-MIMO Uplink : Enabled
  BSS Target Wake Up Time : Enabled
  BSS Target Wake Up Time Broadcast Support : Enabled
.

.


```



Note For 6-GHz radio, the 802.11ax parameters are taken from the multi BSSID profile tagged to the corresponding 6-GHz RF profile of the AP. So, the WLAN dot11ax parameters are overridden by multi BSSID profile parameters in the case of 6-GHz. There are no changes for 2.4 and 5-GHz band WLANs. They continue to use the WLAN parameters for 802.11ax.

```
Device# show ap led-brightness-level summary
```

AP Name	LED Brightness level
<hr/>	
AP00FC.BA01.CC00	Not Supported
AP70DF.2FA2.72EE	8
AP7069.5A74.6678	2
APb838.6159.e184	Not Supported