



# Analytics

---

- [Overview API, on page 2](#)
- [Path API, on page 7](#)
- [Device Count API, on page 12](#)
- [Analytics Summary Metrics API, on page 16](#)
- [Network State API, on page 23](#)
- [Now API, on page 28](#)
- [Dwell Breakdown API, on page 41](#)
- [Dwelltime API, on page 46](#)

# Overview API

## POST: Overview Data for Target Areas for Brochure View

### Description

This task retrieves overview Data for Target Areas for Brochure View

*Table 1: Parameter Details*

JSON body parameter	Description	Allowable values/formats
type	The type of data requested	<ul style="list-style-type: none"> <li>• deviceCount</li> <li>• deviceDwell</li> <li>• grossShopping</li> <li>• deviceCrossover</li> <li>• connectedDetected</li> <li>• dwellBreakdown</li> </ul>
period	The period of interest, either specified as a date range, or one of the predefined names	<ul style="list-style-type: none"> <li>• yyyy-mm-dd</li> <li>• yyyy-mm-dd;yyyy-mm-dd</li> <li>• today</li> <li>• yesterday</li> <li>• this week</li> <li>• last week</li> <li>• last 2 weeks</li> <li>• this month</li> <li>• last month</li> <li>• last 3 months</li> <li>• this year</li> <li>• last year</li> <li>• forever</li> </ul>
timeRange	The time window of interest on each day	<ul style="list-style-type: none"> <li>• HH:mm-HH:mm</li> </ul>
areas	The list of areas of interest. If none are given, all are considered	A comma-separated list of area ids, or heterarchy levels

JSON body parameter	Description	Allowable values/formats
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	<p>Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values:</p> <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>
includeStationary	Whether to include stationary devices (default=false)	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>

JSON body parameter	Description	Allowable values/formats
entirePeriod	Whether to include device visits that occur any time during the entire period or only within a single day (default=false).  Applicable only to crossover; ignored for the other metrics.	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>
connectionState	Whether to restrict to either connected or detected devices (default=all).  For Connected/Detected metric, this setting is ignored, and "all" is presumed	<ul style="list-style-type: none"> <li>• connected</li> <li>• detected</li> <li>• all</li> </ul>
percentageOf	If set, does not report absolute numbers, but relative percentage. Ignored for Crossover report	Heterarchy level
dwelLimits	The dwell time limits that specifies how dwellers should be grouped together. Values are comma seperated as key:value pairs. Key is the series name and value is the upper dwell time limit of the series.  For example, Light:5,Medium:20,Heavy:100 would mean that you consider devices that dwell for less than 5 minutes to be Light; from 5 minutes to 20 minutes to be Medium; and from 20 minutes to 100 to be Heavy. If you want to consider all dwells, pass in -1 as the value.	<ul style="list-style-type: none"> <li>• default</li> <li>• minute</li> <li>• Light:&lt;limit&gt;,Medium:&lt;limit&gt;,Heavy:&lt;limit&gt;</li> <li>• comma separated limit label:limit value</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/overview

**Requires Basic Auth**

N

## Parameters

**Table 2: Parameter Details**

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters

## Content Type

application/json

## Sample Input (JSON)

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "areas": "52",
  "type": "deviceCount"
}
```

## Sample Output (JSON)

```
{
  "startTime": "00:00",
  "previousEndDate": null,
  "startDate": "2017-03-16",
  "title": "Visitors",
  "executionTime": 32,
  "value": {
    "primary": {
      "title": "Total Visitors",
      "value": 0,
      "peakValue": 0,
      "breakdown": [
        {
          "title": "Repeat Visitors",
          "value": 0
        },
        {
          "title": "New Visitors",
          "value": 0
        }
      ]
    }
  },
  "average": {
    "title": "Total Visitors",
    "value": 0,
    "peakValue": 0,
    "breakdown": [
      {
        "title": "Repeat Visitors",
        "value": 0
      },
      {
        "title": "New Visitors",
        "value": 0
      }
    ]
  }
}
```

```
    ]
  },
  "previousTimeRange": {
    "title": "Total Visitors",
    "value": 0,
    "peakValue": 0,
    "breakdown": [
      {
        "title": "Repeat Visitors",
        "value": 0
      },
      {
        "title": "New Visitors",
        "value": 0
      }
    ]
  }
},
"areas": [
  {
    "id": 52,
    "name": "f0:25:72:3c:f8:10"
  }
],
"previousStartDate": "2017-03-15",
"endDate": null,
"endTime": "23:59"
}
```

# Path API

## POST: Paths for a Given Period and Areas

### Description

The only parameter (body) is a JSON array containing the parameters. The parameters are described below:

**Table 3: Parameter Details**

JSON parameter	Description	Allowable values/formats
period	The period of interest, either specified as a date range, or one of the predefined names	<ul style="list-style-type: none"> <li>• yyyy-mm-dd</li> <li>• yyyy-mm-dd;yyyy-mm-dd</li> <li>• today</li> <li>• yesterday</li> <li>• this week</li> <li>• last week</li> <li>• last 2 weeks</li> <li>• this month</li> <li>• last month</li> <li>• last 3 months</li> <li>• this year</li> <li>• last year</li> <li>• forever</li> </ul>
timeRange	The time window of interest on each day.	• HH:mm-HH:mm
targetArea	The ID of the target area for the paths.	The ID of the target area for the paths.
allAreas	The list of areas of interest.	A comma-separated list of area IDs <areaId-1>,<areaId-2>,<areaId-3>
granularity	The desired geographical granularity. This will replace the areas listed in 'allAreas' with their progeny on the appropriate level.	Heterarchy level

JSON parameter	Description	Allowable values/formats
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	<p>Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values:</p> <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/path



**Requires Basic Auth**

N

**Parameters***Table 4: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters.

**Content Type**

application/json

**Sample Input (JSON)**

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "granularity": "Building",
  "allAreas": "52,75,80"
}
```

**Sample Output (JSON)**

```
/* Path Output */
{
  "startTime": "00:00",
  "startDate": "2017-03-07",
  "results": [
    {
      "id": 75,
      "total": 0,
      "medianTransitionTime": 0,
      "ancestry": [
        {
          "level": "Campus",
          "name": "TagTest_Campus_1"
        }
      ],
      "area": "TagTest_Building_1",
      "direction": -1,
      "value": 0,
      "averageTransitionTime": 0
    },
    {
      "id": 80,
      "total": 0,
      "medianTransitionTime": 0,
      "ancestry": [
        {
          "level": "Campus",
          "name": "TagTest_Campus_1"
        }
      ]
    }
  ]
}
```

```

        "area": "TagTest_Building_2",
        "direction": -1,
        "value": 0,
        "averageTransitionTime": 0
    },
    {
        "id": 75,
        "total": 0,
        "medianTransitionTime": 0,
        "ancestry": [
            {
                "level": "Campus",
                "name": "TagTest_Campus_1"
            }
        ],
        "area": "TagTest_Building_1",
        "direction": 1,
        "value": 0,
        "averageTransitionTime": 0
    },
    {
        "id": 80,
        "total": 0,
        "medianTransitionTime": 0,
        "ancestry": [
            {
                "level": "Campus",
                "name": "TagTest_Campus_1"
            }
        ],
        "area": "TagTest_Building_2",
        "direction": 1,
        "value": 0,
        "averageTransitionTime": 0
    }
],
"executionTime": 88,
"requestTruncated": false,
"target": {
    "ancestry": [
        {
            "level": "Campus",
            "name": "campus"
        }
    ]
},
"total": 0,
"id": 52,
"area": "Building_0",
"pathsEnded": 0,
"totalVisits": 0,
"pathsStarted": 0,
"avgDwellPerDevice": 0,
"avgDwellPerVisit": 0,
"totalDevices": 0
},
"insights": {},
"endDate": "2017-03-07",
"endTime": "23:59",
"dataFreshness": {
    "dayOfYear": 66,
    "dayOfMonth": 7,
    "dayOfWeek": 2,
    "era": 1,
    "year": 2017,

```

```
    "minuteOfDay": 1277,
    "hourOfDay": 21,
    "weekyear": 2017,
    "monthOfYear": 3,
    "yearOfEra": 2017,
    "yearOfCentury": 17,
    "centuryOfEra": 20,
    "millisOfSecond": 782,
    "millisOfDay": 76673782,
    "secondOfMinute": 53,
    "secondOfDay": 76673,
    "minuteOfHour": 17,
    "weekOfWeekyear": 10,
    "millis": 1488921473782,
    "zone": {
      "fixed": true,
      "id": "Etc/UTC"
    },
    "chronology": {
      "zone": {
        "fixed": true,
        "id": "Etc/UTC"
      }
    },
    "afterNow": false,
    "beforeNow": false,
    "equalNow": true
  }
}
```

# Device Count API

## POST: Device Count for a Given Period and Areas

### Description

This API retrieves the device count for a given period and areas.

The only parameter (body) is a JSON array containing the parameters. The parameters are described below

**Table 5: Parameter Details**

JSON array parameter	Description	Allowable values/formats
granularity	The desired granularity. One can limit to top n results (i.e. the n values with highest count) by adding "[n]", or the n bottom results by adding "[-n]". If granularity null is specified, all heterarchy types covered by the areas are returned.	<ul style="list-style-type: none"> <li>• hourly</li> <li>• daily</li> <li>• weekly</li> <li>• monthly</li> <li>• yearly</li> <li>• tag</li> <li>• tag-name</li> <li>• heterarchy level</li> <li>• null</li> </ul>
period	The period of interest, either specified as a date range, or one of the predefined names	<ul style="list-style-type: none"> <li>• yyyy-mm-dd</li> <li>• yyyy-mm-dd;yyyy-mm-dd</li> <li>• today</li> <li>• yesterday</li> <li>• this week</li> <li>• last week</li> <li>• last 2 weeks</li> <li>• this month</li> <li>• last month</li> <li>• last 3 months</li> <li>• this year</li> <li>• last year</li> <li>• forever</li> </ul>
timeRange	The time window of interest on each day.	<ul style="list-style-type: none"> <li>• HH:mm-HH:mm</li> </ul>

JSON array parameter	Description	Allowable values/formats
aggregate	Whether to aggregate the dwell time by granularity; e.g. showing a total for each day of the week, instead of individual dates	<ul style="list-style-type: none"> <li>• none</li> <li>• sum</li> <li>• avg</li> </ul>
areas	The list of areas of interest. If none are given, all are considered	A comma-separated list of area ids, or heterarchy levels
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	<p>Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values:</p> <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>

JSON array parameter	Description	Allowable values/formats
includeStationary	Whether to include stationary devices (default=false)	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>
connectionState	Whether to restrict to either connected or detected devices (default=all)	<ul style="list-style-type: none"> <li>• connected</li> <li>• detected</li> <li>• all</li> </ul>
percentageOf	If set, does not report absolute numbers, but relative percentage	Heterarchy level
areaFilter	<p>If set, restricts the results to areas matching the filter. Use 'descendantOf' to restrict the area selection. This option is used for drill down reports. Use 'subsetOf' to restrict the granularity. This option is used with tag granularity.</p> <p>For example: descendantOf: Campus C1 has Building B1 which zone Z1 and Z2 Campus C2 has Building B2 which zone Z3 query area=Z1,Z2,Z3 and granularity=Building and areaFilter=descendantOf:C1 will return only Building B1</p> <p>For example: subsetOf: Tag T1,T2 assigned to F1, T2,T3 to F2, T3,T4 to F3 query area=F1,F2,F3 and granularity=tag and areaFilter=subsetOf:T1,T2 will return only T1,T2.</p>	<ul style="list-style-type: none"> <li>• descendantOf</li> <li>• subsetOf:comma separated ids</li> </ul>
expandAll	Include all of the elements descendants in the result	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/deviceCount

**Requires Basic Auth**

N

## Parameters

**Table 6: Parameter Details**

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters

## Content Type

application/json

## Sample Input (JSON)

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "granularity": "Building",
  "areas": "52,75,80"
}
```

## Sample Output (JSON)

```
{
  "startTime": "00:00",
  "startDate": "2017-03-16",
  "connectionState": "all",
  "results": [
    {
      "id": -1,
      "ancestry": [],
      "series": [],
      "hasChildren": false,
      "level": "SUPERZONE",
      "area": "Unknown area",
      "data": []
    }
  ],
  "interval": null,
  "executionTime": 23,
  "minValue": 2147483647,
  "endDate": "2017-03-16",
  "endTime": "23:59",
  "dataFreshness": "2017-03-16T03:00:28.833-07:00",
  "maxValue": 0
}
```

# Analytics Summary Metrics API

## GET: All summary KPI

### Description

This API retrieves summary of all KPI.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/summary

### Requires Basic Auth

N

### Parameters

None.

### Sample Output (JSON)

```
{
  "Top Building dwell": {
    "title": "Top Building dwell",
    "value": {
      "primary": "Nortech-1 (5572.52 min)",
      "secondary": [
        "SJC23 (0.00 min)",
        "SJC24 (0.00 min)",
        "Shell- CBuilding (0.00 min)"
      ],
      "supplementary": "SJC23 (0.00 min)<br>SJC24 (0.00 min)<br>Shell- CBuilding (0.00 min)<br>"
    }
  },
  "Notifications Received": {
    "title": "Notifications Received Rate (5 min avg)",
    "value": {
      "primary": "2.04 notifications/s",
      "secondary": [
        "1 min avg: 2.07",
        "15 min avg: 1.84",
        "Avg since boot: 4.23",
        "Total number of events: 3774166"
      ],
      "supplementary": "1 min avg: 2.07<br>15 min avg: 1.84<br>Avg since boot: 4.23<br>Total number of events: 3774166"
    }
  },
  "RSSI experience": {
    "title": "RSSI experience",
```



```

    "value": {
      "primary": "No devices detected",
      "secondary": [
        "No devices detected"
      ],
      "supplementary": "No devices detected"
    }
  },
  "Uptime": {
    "title": "Uptime",
    "value": {
      "primary": "10 days, 07:35",
      "secondary": [
        "Processors: 20",
        "Max mem: 4528 MiB",
        "Memory: 2849/4528 MiB",
        "Threads: 169"
      ],
      "supplementary": "Processors: 20<br/>Max mem: 4528 MiB<br/>Memory: 2849/4528
MiB<br/>Threads: 169"
    }
  },
  "Connected": {
    "title": "Connected",
    "value": {
      "primary": "1916.33%",
      "secondary": [
        "Total: 392",
        "Detected: -7120 (-1816.33%)",
        "Connected: 7512 (1916.33%)"
      ],
      "supplementary": "Total: 392<br/>Detected: -7120 (-1816.33%)<br/>Connected:
7512 (1916.33%)<br/>"
    }
  },
  "Aggregation performance": {
    "title": "Aggregation performance",
    "value": {
      "primary": "534930964.29 / 0",
      "secondary": [
        "API misses (rate): 166(0) / 0(0) <br/>",
        "API misses as % of total API calls: 9.22/□<br/>",
        "Background updates (rate): 0(0) / 0(0) <br/>"
      ],
      "supplementary": "API misses (rate): 166(0) / 0(0) <br/><br/>API misses as %
of total API calls: 9.22/□<br/><br/>Background updates (rate): 0(0) / 0(0) <br/>"
    }
  },
  "recordRefreshCounts": {
    "pathRecordsRefreshed": 0,
    "repeatRecordsRefreshed": 0,
    "derivedRecordsRefreshed": 0,
    "hourVisitsUpdated": 121942,
    "areaVisitsUpdated": 119586,
    "crossoverRecordsRefreshed": 0
  }
},
"Top Campus count": {
  "title": "Top Campus count",
  "value": {
    "primary": "Nortech Campus (356)",
    "secondary": [
      "Shell (0)",
      "System Campus (0)"
    ],
  },

```

```

    "supplementary": "Shell (0)<br/>System Campus (0)<br/>"
  }
},
"Database I/O": {
  "title": "Database I/O Rate (5 min avg)",
  "value": {
    "primary": "0.57 operations/s",
    "secondary": [
      "1 min avg: 0.07",
      "15 min avg: 0.53",
      "Avg since boot: 0.46",
      "Total number of events: 409932"
    ],
    "supplementary": "1 min avg: 0.07<br/>15 min avg: 0.53<br/>Avg since boot:
0.46<br/>Total number of events: 409932"
  }
},
"Top Floor dwell": {
  "title": "Top Floor dwell",
  "value": {
    "primary": "1st Floor (5572.53 min)",
    "secondary": [
      "1st floor (CCW remodel) (0.00 min)",
      "2nd floor (Area Addition) (0.00 min)",
      "2nd floor (CCW remodel) (0.00 min)"
    ],
    "supplementary": "1st floor (CCW remodel) (0.00 min)<br/>2nd floor (Area Addition)
(0.00 min)<br/>2nd floor (CCW remodel) (0.00 min)<br/>"
  }
},
"Active devices": {
  "title": "Active devices",
  "value": {
    "primary": 356,
    "secondary": [
      "Most recent detection: 17s ago"
    ],
    "supplementary": "Most recent detection: 17s ago"
  }
},
"Top Campus dwell": {
  "title": "Top Campus dwell",
  "value": {
    "primary": "Nortech Campus (5572.53 min)",
    "secondary": [
      "Shell (0.00 min)",
      "System Campus (0.00 min)"
    ],
    "supplementary": "Shell (0.00 min)<br/>System Campus (0.00 min)<br/>"
  }
},
"Analysis API calls": {
  "title": "Analysis API calls",
  "value": {
    "primary": "Meter not active yet",
    "secondary": [
      "Please wait while data is being collected."
    ],
    "supplementary": "Please wait while data is being collected."
  }
},
"Zone API Calls": {
  "title": "Zone API Calls",
  "value": {

```

```

    "primary": "Meter not active yet",
    "secondary": [
      "Please wait while data is being collected."
    ],
    "supplementary": "Please wait while data is being collected."
  }
},
"Top Zone dwell": {
  "title": "Top Zone dwell",
  "value": {
    "primary": "CMX Bar (5959.07 min)",
    "secondary": [
      "School (5763.90 min)",
      "Tm (4175.67 min)",
      "CMX Clinic (1783.57 min)"
    ],
    "supplementary": "School (5763.90 min)<br/>Tm (4175.67 min)<br/>CMX Clinic (1783.57 min)<br/>"
  }
},
"Top Manufacturer": {
  "title": "Top Manufacturer",
  "value": {
    "primary": "Cisco Systems, Inc (310)",
    "secondary": [
      "Aeroscout Ltd. (78)",
      "G2 Microsystems (44)",
      "Hon Hai Precision Ind. Co.,Ltd. (21)"
    ],
    "supplementary": "Aeroscout Ltd. (78)<br/>G2 Microsystems (44)<br/>Hon Hai Precision Ind. Co.,Ltd. (21)<br/>"
  }
},
"Top Zone count": {
  "title": "Top Zone count",
  "value": {
    "primary": "CMX Clinic (106)",
    "secondary": [
      "Tm (86)",
      "CMX Bar (44)",
      "School (20)"
    ],
    "supplementary": "Tm (86)<br/>CMX Bar (44)<br/>School (20)<br/>"
  }
},
"Top Building count": {
  "title": "Top Building count",
  "value": {
    "primary": "Nortech-1 (356)",
    "secondary": [
      "SJC23 (0)",
      "SJC24 (0)",
      "Shell- CBuilding (0)"
    ],
    "supplementary": "SJC23 (0)<br/>SJC24 (0)<br/>Shell- CBuilding (0)<br/>"
  }
},
"Overall Analytics API Calls": {
  "title": "Overall Analytics API Calls Rate (5 min avg)",
  "value": {
    "primary": "0.00 calls/s",
    "secondary": [
      "1 min avg: 0.00",
      "15 min avg: 0.00",
    ]
  }
}

```

```

        "Avg since boot: 0.00",
        "Total number of events: 0"
    ],
    "supplementary": "1 min avg: 0.00</br>15 min avg: 0.00</br>Avg since boot:
0.00</br>Total number of events: 0"
    }
},
"Notification processing time": {
    "title": "Notification processing time (avg duration)",
    "value": {
        "primary": "2.13 ms",
        "secondary": [
            "Min: 0 ms",
            "Max: 9 ms",
            "StDev: 0.94"
        ]
    },
    "supplementary": "Min: 0 ms</br>Max: 9 ms</br>StDev: 0.94"
    }
},
"Location API Calls": {
    "title": "Location API Calls",
    "value": {
        "primary": "Meter not active yet",
        "secondary": [
            "Please wait while data is being collected."
        ]
    },
    "supplementary": "Please wait while data is being collected."
    }
},
"Paths API Calls": {
    "title": "Paths API Calls",
    "value": {
        "primary": "Meter not active yet",
        "secondary": [
            "Please wait while data is being collected."
        ]
    },
    "supplementary": "Please wait while data is being collected."
    }
},
"Age of updated aggregation records": {
    "title": "Age of updated aggregation records",
    "value": {
        "primary": "Meter not active yet",
        "secondary": [
            "Please wait while data is being collected."
        ]
    },
    "supplementary": "Please wait while data is being collected."
    }
},
"Top Floor count": {
    "title": "Top Floor count",
    "value": {
        "primary": "1st Floor (356)",
        "secondary": [
            "1st floor (CCW remodel) (0)",
            "2nd floor (Area Addition) (0)",
            "2nd floor (CCW remodel) (0)"
        ]
    },
    "supplementary": "1st floor (CCW remodel) (0)<br/>2nd floor (Area Addition)
(0)<br/>2nd floor (CCW remodel) (0)<br/>"
    }
},
"Heterarchy": {
    "title": "Heterarchy",

```

```

"value": {
  "primary": "199 active elements",
  "secondary": [
    "Elements: 199/54 [act/inact]",
    "APs: 158/39",
    "POIs: 0/0",
    "PATHs: 0/0",
    "Floors: 8/1",
    "Tags: 19/0",
    "Userlevels: 4/0",
    "Zones: 5/12"
  ],
  "supplementary": "Elements: 199/54 [act/inact]<br/>APs: 158/39<br/>POIs: 0/0<br/>PATHs: 0/0<br/>Floors: 8/1<br/>Tags: 19/0<br/>Userlevels: 4/0<br/>Zones: 5/12"
}
}
}

```

## GET: Specific set of Summary KPIs or a list of available ones

### Description

This API retrieves a specific set of summary KPIs or a list of available ones.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/summary/:summaryItem

### Requires Basic Auth

N

### Parameters

Table 7: Parameter Details

Name	Required	Default	Type	Location	Description
summaryItem	Y	—	String	pathReplace	A comma-separated list of summary KPI to return, or 'availableMetrics' to see the list of metrics available. Use the title parameter.

### Content Type

application/json

**Sample Output (JSON)**

```
{
  "Top Building dwell": {
    "title": "Top Building dwell",
    "value": {
      "secondary": [],
      "supplementary": "",
      "primary": "Nortech Building (0.00 min)"
    }
  }
}
```

# Network State API

## POST: Breakdown of Connected and Detected Devices for a Given Period and Areas

### Description

This API gives a breakdown of connected and detected devices for a given period and areas. The only parameter (body) is a JSON array containing the parameters. The parameters are described below

*Table 8: Parameter Details*

JSON array parameter	Description	Allowable values/formats
granularity	The desired granularity. One can limit to top n results (i.e. the n values with highest count) by adding "[n]", or the n bottom results by adding "[-n]". If granularity null is specified, all heterarchy types covered by the areas are returned.	<ul style="list-style-type: none"> <li>• hourly</li> <li>• daily</li> <li>• weekly</li> <li>• monthly</li> <li>• yearly</li> <li>• tag</li> <li>• tag-name</li> <li>• heterarchy level</li> <li>• null</li> </ul>
period	The period of interest, either specified as a date range, or one of the predefined names	<ul style="list-style-type: none"> <li>• yyyy-mm-dd</li> <li>• yyyy-mm-dd;yyyy-mm-dd</li> <li>• today</li> <li>• yesterday</li> <li>• this week</li> <li>• last week</li> <li>• last 2 weeks</li> <li>• this month</li> <li>• last month</li> <li>• last 3 months</li> <li>• this year</li> <li>• last year</li> <li>• forever</li> </ul>
timeRange	The time window of interest on each day.	<ul style="list-style-type: none"> <li>• HH:mm-HH:mm</li> </ul>
aggregate	Whether to aggregate the dwell time by granularity; e.g. showing a total for each day of the week, instead of individual dates	<ul style="list-style-type: none"> <li>• none</li> <li>• sum</li> <li>• avg</li> </ul>

JSON array parameter	Description	Allowable values/formats
areas	The list of areas of interest. If none are given, all are considered	A comma-separated list of area ids, or heterarchy levels  <areaId> <areaId-1>,<areaId-2>,<areaId-3>
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values: <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>
includeStationary	Whether to include stationary devices (default=false)	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>



JSON array parameter	Description	Allowable values/formats
percentageOf	If set, does not report absolute numbers, but relative percentage	Heterarchy level
areaFilter	<p>If set, restricts the results to areas matching the filter. Use 'descendantOf' to restrict the area selection. This option is used for drill down reports. Use 'subsetOf' to restrict the granularity. This option is used with tag granularity.</p> <p>For example: descendantOf: Campus C1 has Building B1 which zone Z1 and Z2 Campus C2 has Building B2 which zone Z3 query area=Z1,Z2,Z3 and granularity=Building and areaFilter=descendantOf:C1 will return only Building B1</p> <p>For example: subsetOf: Tag T1,T2 assigned to F1, T2,T3 to F2, T3,T4 to F3 query area=F1,F2,F3 and granularity=tag and areaFilter=subsetOf:T1,T2 will return only T1,T2.</p>	<ul style="list-style-type: none"> <li>• descendantOf</li> <li>• subsetOf:comma separated ids</li> </ul>
expandAll	Include all of the elements descendants in the result	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/connectedDetected

**Requires Basic Auth**

N

**Parameters**

*Table 9: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters.

**Content Type**

application/json

**Sample Input (JSON)**

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "granularity": "hourly",
  "areas": "5786"
}
```

**Sample Output (JSON)**

```
{
  "startTime": "00:00",
  "startDate": "2017-03-16",
  "results": [
    {
      "id": 5786,
      "ancestry": [
        {
          "level": "Campus",
          "name": "Noritech Campus"
        }
      ],
      "startDate": "2017-03-16",
      "series": [
        "datetime"
      ],
      "hasChildren": true,
      "area": "Noritech-1",
      "data": [
        {
          "dwell": null,
          "values": {
            "connected": 0,
            "detected": 0
          },
          "name": null
        },
        {
          "dwell": null,
          "values": {
            "connected": 0,
            "detected": 0
          },
          "name": null
        },
        {
          "dwell": null,
          "values": {
            "connected": 0,
            "detected": 0
          },
          "name": null
        },
        {
          "dwell": null,
          "values": {
            "connected": 0,
            "detected": 0
          },
          "name": null,
          "incomplete": true
        }
      ]
    }
  ]
}
```

```
    }
  ],
  "interval": "hourly",
  "executionTime": 18,
  "insights": {
    "summary": {},
    "connected": {
      "ancestry": [
        {
          "level": "Campus",
          "name": "Noritech Campus"
        }
      ],
      "id": 5786,
      "index": 0,
      "maxDate": "2017-03-16",
      "name": "Noritech-1",
      "maxTime": "00:00",
      "maxValue": 0
    },
    "detected": {
      "ancestry": [
        {
          "level": "Campus",
          "name": "Noritech Campus"
        }
      ],
      "id": 5786,
      "index": 0,
      "maxDate": "2017-03-16",
      "name": "Noritech-1",
      "maxTime": "00:00",
      "maxValue": 0
    }
  },
  "endDate": "2017-03-16",
  "maxValues": {
    "connected": 0,
    "detected": 0
  },
  "endTime": "23:59",
  "dataFreshness": "2017-03-16T02:53:55.919-07:00",
  "minValues": {
    "connected": 0,
    "detected": 0
  }
}
```

# Now API

## GET: Retrieve the count of active clients on a floor or multiple floors right now.

### Description

The only parameter (body) is a JSON array containing the parameters.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/now/clientCount

### Requires Basic Auth

N

### Parameters

None.

### Content Type

application/json

### Sample Output (JSON)

```
{
  "total": {
    "total": 103,
    "totalNumFloors": 8
  },
  "connectionState": "all",
  "failedFloorIds": [],
  "missingFloorIds": [],
  "executionTime": 147,
  "minValue": 0,
  "data": [
    {
      "floorName": "2nd floor (CCW remodel)",
      "floorId": 207,
      "value": 0
    },
    {
      "floorName": "3rd floor (CCW remodel)",
      "floorId": 157,
      "value": 0
    },
    {
      "floorName": "3rd floor (CCW remodel)",
      "floorId": 232,
      "value": 0
    }
  ]
}
```

```

    },
    {
      "floorName": "1st floor (CCW remodel)",
      "floorId": 106,
      "value": 0
    },
    {
      "floorName": "1st floor (CCW remodel)",
      "floorId": 184,
      "value": 0
    },
    {
      "floorName": "1st Floor",
      "floorId": 11,
      "value": 103
    },
    {
      "floorName": "2nd floor (CCW remodel)",
      "floorId": 132,
      "value": 0
    },
    {
      "floorName": "2nd floor (Area Addition)",
      "floorId": 185,
      "value": 0
    }
  ],
  "date": "2017-12-17",
  "nonFloorIds": [],
  "maxValue": 103
}

```

### API History

*Table 10: API history*

Release	Modification
Cisco CMX Release 10.3	This API is introduced.

## POST: Retrieve the count of active clients on a floor or multiple floors right now

### Description

This API retrieves the count of active clients on a floor or multiple floors right now. The only parameter (body) is a JSON array containing the parameters.

**Parameters***Table 11: Parameter Details*

JSON array parameter	Description	Allowable values/formats
floors	The list of floors of interest. If none are given, all are considered.	A comma-separated list of floor ids. <floorId1>,<floorId2>,...
connectionState	Whether to restrict to either connected or detected devices (default = all)	<ul style="list-style-type: none"> <li>• connected</li> <li>• detected</li> <li>• all</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/now/clientCount

**Requires Basic Auth**

N

**Parameters***Table 12: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters.

**Content Type**

application/json

**Sample Input**

{

```
"floors": "17",
"connectionState": "all"
}
```

### Sample Output

```
{
  "total": {
    "total": 0,
    "totalNumFloors": 0
  },
  "connectionState": "all",
  "failedFloorIds": [],
  "missingFloorIds": [
    "17"
  ],
  "executionTime": 1,
  "minValue": 2147483647,
  "data": [],
  "date": "2017-03-16",
  "nonFloorIds": [],
  "maxValue": -2147483648
}
```

### API History

*Table 13: API history*

Release	Modification
Cisco CMX Release 10.3	This API is introduced.

## POST: Retrieve the breakdown of connected and detected devices for a floor right now.

### Description

This API retrieve the breakdown of connected and detected devices for a floor right now.

### HTTP Method

POST

### Resource URI

/api/analytics/v1/now/connectedDetected

### Requires Basic Auth

N

POST: Retrieve the breakdown of connected and detected devices for a floor right now.

## Parameters

*Table 14: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y		JSON array	body	JSON array containing parameters

## Content Type

application/json

## Sample Input (JSON)

```
{
  "floors": "17"
}
```

## Sample Output (JSON)

```
{
  "total": {
    "totalDetected": 0,
    "totalNumFloors": 0,
    "totalAll": 0,
    "totalConnected": 0
  },
  "startTime": "03:22",
  "startDate": "2017-03-16",
  "failedFloorIds": [],
  "missingFloorIds": [
    "17"
  ],
  "results": [],
  "interval": null,
  "executionTime": 2,
  "endDate": "2017-03-16",
  "endTime": "03:22",
  "nonFloorIds": []
}
```

## API History

*Table 15: API history*

Release	Modification
Cisco CMX Release 10.3	This API is introduced.



## GET: Retrieve the breakdown of connected and detected devices for a floor right now

### Description

The API retrieves the breakdown of connected and detected devices for a floor right now.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/now/connectedDetected

### Requires Basic Auth

N

### Parameters

None.

### Content Type

application/json

### Sample Output (JSON)

```
{
  "total": {
    "totalDetected": 98,
    "totalNumAreas": 1,
    "totalAll": 98,
    "totalConnected": 0
  },
  "startDate": "2017-12-17",
  "interval": null,
  "executionTime": 158,
  "endDate": "2017-12-17",
  "endTime": "22:36",
  "startTime": "22:36",
  "invalidLevelIds": [],
  "missingAreaIds": [],
  "results": [
    {
      "ancestry": [],
      "id": 1,
      "series": [
        "dwell"
      ],
      "hasChildren": true,
      "area": "Campus",
      "data": [
        {
          "dwell": "0-1440",
          "values": {
```

```

        "connected": 0,
        "detected": 98,
        "all": 98
      },
      "name": null
    }
  ]
},
"failedAreaIds": [],
"maxValues": {
  "connected": 0,
  "detected": 98
},
"minValues": {
  "connected": 0,
  "detected": 98
}
}

```

### API History

Table 16: API history

Release	Modification
Cisco CMX Release 10.3	This API is introduced.

## GET: Retrieve the count of active clients on a single or on multiple campuses/buildings/floors right now

### Description

The only parameter (body) is a JSON array containing the parameters.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/now/clientCount/areas

### Requires Basic Auth

N

### Parameters

None.

### Content Type

application/json

**Sample Output (JSON)**

```
{
  "invalidLevelIds": [],
  "total": {
    "total": 103,
    "totalNumAreas": 1
  },
  "missingAreaIds": [],
  "connectionState": "all",
  "failedAreaIds": [],
  "executionTime": 147,
  "minValue": 103,
  "data": [
    {
      "areaName": "Campus",
      "value": 103,
      "areaId": 1
    }
  ],
  "date": "2017-12-17",
  "maxValue": 103
}
```

**API History***Table 17: API history*

Release	Modification
Cisco CMX Release 10.4	This API is introduced.

## POST: Retrieve the count of active clients on a single or on multiple campuses/buildings/floors right now

**Description**

The only parameter (body) is a JSON array containing the parameters.

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/now/clientCount/areas

**Requires Basic Auth**

N

## Parameters

Table 18: Parameter Details

Name	Required	Default	Type	Location	Description
areas	N		string	body	The list of areas of interest. If none are given, If none are given, the root level campus is considered.
connectionState	N	all	string	body	Whether to restrict to either connected or detected devices.

## Content Type

application/json

## Sample Output (JSON)

```
{
  "invalidLevelIds": [],
  "total": {
    "total": 104,
    "totalNumAreas": 1
  },
  "missingAreaIds": [],
  "connectionState": "all",
  "failedAreaIds": [],
  "executionTime": 124,
  "minValue": 104,
  "data": [
    {
      "areaName": "Campus",
      "value": 104,
      "areaId": 1
    }
  ],
  "date": "2017-12-17",
  "maxValue": 104
}
```

## API History

Table 19: API history

Release	Modification
Cisco CMX Release 10.4	This API is introduced.

## POST: Retrieve the breakdown of connected and detected devices on a single or on multiple campuses/buildings/floors right now

### Description

This API retrieves the breakdown of connected and detected devices on a single or on multiple campuses/buildings/floors right now. The only parameter (body) is a JSON array containing the parameters.

### HTTP Method

POST

### Resource URI

/api/analytics/v1/now/connectedDetected/areas

### Requires Basic Auth

N

### Parameters

*Table 20: Parameter Details*

Name	Required	Default	Type	Location	Description
areas	N		string	body	The list of areas of interest. If none are given, the root level campus is considered.

### Content Type

application/json

### Sample Output (JSON)

```
{
  "total": {
    "totalDetected": 105,
    "totalNumAreas": 1,
    "totalAll": 105,
    "totalConnected": 0
  },
  "startDate": "2017-12-20",
  "interval": null,
  "executionTime": 160,
  "endDate": "2017-12-20",
  "endTime": "00:08",
  "startTime": "00:08",
  "invalidLevelIds": [],
  "missingAreaIds": []
}
```

```

"results": [
  {
    "ancestry": [],
    "id": 1,
    "series": [
      "dwell"
    ],
    "hasChildren": true,
    "area": "Campus",
    "data": [
      {
        "dwell": "0-1440",
        "values": {
          "connected": 0,
          "detected": 105,
          "all": 105
        },
        "name": null
      }
    ]
  }
],
"failedAreaIds": [],
"maxValues": {
  "connected": 0,
  "detected": 105
},
"minValues": {
  "connected": 0,
  "detected": 105
}
}

```

### API History

*Table 21: API history*

Release	Modification
Cisco CMX Release 10.4	This API is introduced.

## GET: Retrieve the breakdown of connected and detected devices on a single or on multiple campuses/buildings/floors right now

### Description

This API retrieves the breakdown of connected and detected devices on a single or on multiple campuses/buildings/floors right now.

### HTTP Method

GET

### Resource URI

/api/analytics/v1/now/connectedDetected/areas

**Requires Basic Auth**

N

**Parameters**

None.

**Content Type**

application/json

**Sample Output (JSON)**

```

{
  "total": {
    "totalDetected": 97,
    "totalNumAreas": 1,
    "totalAll": 97,
    "totalConnected": 0
  },
  "startDate": "2017-12-20",
  "interval": null,
  "executionTime": 158,
  "endDate": "2017-12-20",
  "endTime": "00:15",
  "startTime": "00:15",
  "invalidLevelIds": [],
  "missingAreaIds": [],
  "results": [
    {
      "ancestry": [],
      "id": 1,
      "series": [
        "dwell"
      ],
      "hasChildren": true,
      "area": "Campus",
      "data": [
        {
          "dwell": "0-1440",
          "values": {
            "connected": 0,
            "detected": 97,
            "all": 97
          },
          "name": null
        }
      ]
    }
  ],
  "failedAreaIds": [],
  "maxValues": {
    "connected": 0,
    "detected": 97
  },
  "minValues": {
    "connected": 0,
    "detected": 97
  }
}

```

## API History

*Table 22: API history*

<b>Release</b>	<b>Modification</b>
Cisco CMX Release 10.4	This API is introduced.



# Dwell Breakdown API

## POST: Breakdown of Dwell Times Spent by Devices for a Given Period and Areas

### Description

The only parameter (body) is a JSON array containing the parameters. The parameters are described below:

*Table 23: Parameter Details*

JSON Array Parameter	Description	Allowable Values/Formats
granularity	The desired granularity.	<ul style="list-style-type: none"> <li>hourly</li> <li>daily</li> <li>weekly</li> <li>monthly</li> <li>yearly</li> <li>tag</li> <li>tag-name</li> <li>heterarchy level. One can limit to top "n" results (that is, the "n" values with highest count) by adding "[n]", or the "n" bottom results by adding "[n]"</li> </ul>
period	The period of interest, specified as either a date range, or one of the predefined names.	<ul style="list-style-type: none"> <li>yyyy-mm-dd</li> <li>yyyy-mm-dd;yyyy-mm-dd</li> <li>today</li> <li>yesterday</li> <li>this week</li> <li>last week</li> <li>last 2 weeks</li> <li>this month</li> <li>last month</li> <li>last 3 months</li> <li>this year</li> <li>last year</li> <li>forever</li> </ul>
timeRange	The time window of interest on each day.	<ul style="list-style-type: none"> <li>HH:mm-HH:mm</li> </ul>

JSON Array Parameter	Description	Allowable Values/Formats
aggregate	Aggregate the dwell time by granularity, for example, showing the total dwell time for each day of the week, instead of individual dates.	<ul style="list-style-type: none"> <li>• none</li> <li>• sum</li> <li>• avg</li> </ul>
areas	The list of areas of interest. If none are provided, all are considered.	A comma-separated list of area IDs, or hierarchy levels.
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	<p>Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values:</p> <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>

JSON Array Parameter	Description	Allowable Values/Formats
includeStationary	Whether to include stationary devices (default=false).	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>
connectionState	Whether to restrict connection to either connected or detected devices (default=all).	<ul style="list-style-type: none"> <li>• connected</li> <li>• detected</li> <li>• all</li> </ul>
percentageOf	If set this parameter, does not report absolute numbers, only relative percentage.	Heterarchy level
dwellLimits	The dwell time limit that specifies how dwellers should be grouped together. Pass -1 to catch all. Example: Light: 100, Medium: 200, Heavy:-1.	<ul style="list-style-type: none"> <li>• default</li> <li>• minute</li> <li>• comma separated limit label:limit value</li> </ul>
areaFilter	<p>If set this parameter, restricts the results to areas matching the filter. Use descendantOf to restrict the area selection. This option is used for drill-down reports. Use 'subsetOf' to restrict the granularity. This option is used with tag granularity.</p> <p>For example: descendantOf: Campus C1 has Building B1 which zone Z1 and Z2 Campus C2 has Building B2 which zone Z3 query area=Z1,Z2,Z3 and granularity=Building and areaFilter=descendantOf:C1 will return only Building B1</p> <p>For example: subsetOf: Tag T1,T2 assigned to F1, T2,T3 to F2, T3,T4 to F3 query area=F1,F2,F3 and granularity=tag and areaFilter=subsetOf:T1,T2 will return only T1,T2.</p>	<ul style="list-style-type: none"> <li>• descendantOf</li> <li>• subsetOf:comma separated ids</li> </ul>
expandAll	Include all the elements descendants in the result.	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/dwellBreakdown

**Requires Basic Auth**

N

**Parameters***Table 24: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters.

**Content Type**

application/json

**Sample Input (JSON)**

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "granularity": "hourly",
  "areas": "52,75"
}
```

**Sample Output (JSON)**

```
{
  "startTime": "00:00",
  "startDate": "2017-03-16",
  "results": [
    {
      "id": 53,
      "ancestry": [
        {
          "level": "Building",
          "name": "REQ"
        },
        {
          "level": "Campus",
          "name": "Richfield"
        }
      ],
      "series": [
        "datetime",
        "dwell"
      ],
      "hasChildren": false,
      "area": "2nd Floor",
      "data": []
    },
    {
      "id": 75,
```

```
    "ancestry": [
      {
        "level": "Floor",
        "name": "Site 4"
      },
      {
        "level": "Building",
        "name": "Site 4"
      },
      {
        "level": "Campus",
        "name": "San Jose Outdoor"
      }
    ],
    "series": [
      "datetime",
      "dwell"
    ],
    "hasChildren": false,
    "area": "f4:0f:1b:1a:82:90",
    "data": []
  }
},
"interval": "hourly",
"executionTime": 0,
"insights": {
  "summary": {}
},
"endDate": "2017-03-16",
"maxValues": {},
"endTime": "23:59",
"dataFreshness": "2017-03-16T02:53:58.054-07:00",
"minValues": {}
}
```

# Dwelltime API

## POST: Dwell Time for a Given Period and Areas

### Description

This API retrieves dwell Time for a given period and areas. The only parameter is a JSON array containing the parameters. The parameters are described below

*Table 25: Parameter Details*

JSON array parameter	Description	Allowable values/formats
granularity	The desired granularity. One can limit to top n results (i.e. the n values with highest count) by adding "[n]", or the n bottom results by adding "[-n]". If granularity null is specified, all heterarchy types covered by the areas are returned.	<ul style="list-style-type: none"> <li>• hourly</li> <li>• daily</li> <li>• weekly</li> <li>• monthly</li> <li>• yearly</li> <li>• tag</li> <li>• tag-name</li> <li>• heterarchy level</li> <li>• null</li> </ul>
period	The period of interest, either specified as a date range, or one of the predefined names	<ul style="list-style-type: none"> <li>• yyyy-mm-dd</li> <li>• yyyy-mm-dd;yyyy-mm-dd</li> <li>• today</li> <li>• yesterday</li> <li>• this week</li> <li>• last week</li> <li>• last 2 weeks</li> <li>• this month</li> <li>• last month</li> <li>• last 3 months</li> <li>• this year</li> <li>• last year</li> <li>• forever</li> </ul>
timeRange	The time window of interest on each day	<ul style="list-style-type: none"> <li>• HH:mm-HH:mm</li> </ul>
aggregate	Whether to aggregate the dwell time by granularity; e.g. showing a total for each day of the week, instead of individual dates	<ul style="list-style-type: none"> <li>• none</li> <li>• sum</li> <li>• avg</li> </ul>

JSON array parameter	Description	Allowable values/formats
areas	The list of areas of interest. If none are given, all are considered	A comma-separated list of area ids, or heterarchy levels  <areaId> <areaId-1>,<areaId-2>,<areaId-3>
durationCategories	Filter devices by dwell times for which device visits specified areas. If a device's dwell time falls outside of the range, it is filtered out and not considered a visit.	Time (in minutes) in the form nn-mm where nn is the lower limit and mm the upper limit. The maximum upper limit is 1440 minutes; which is 24 hours, or a full day. Accepted Values: <ul style="list-style-type: none"> <li>• 0-240</li> <li>• 0-480</li> <li>• 0-1440</li> <li>• 5-240</li> <li>• 5-480</li> <li>• 5-1440</li> <li>• 10-240</li> <li>• 10-480</li> <li>• 10-1440</li> <li>• 15-240</li> <li>• 15-480</li> <li>• 15-1440</li> <li>• 30-240</li> <li>• 30-480</li> <li>• 30-1440</li> <li>• 45-240</li> <li>• 45-480</li> <li>• 45-1440</li> <li>• 60-240</li> <li>• 60-480</li> <li>• 60-1440</li> </ul>
includeStationary	Whether to include stationary devices	<ul style="list-style-type: none"> <li>• true</li> <li>• false</li> </ul>

JSON array parameter	Description	Allowable values/formats
connectionState	Whether to restrict to either connected or detected devices (default=all)	<ul style="list-style-type: none"> <li>connected</li> <li>detected</li> <li>all</li> </ul>
percentageOf	If set, does not report absolute numbers, but relative percentage	Heterarchy level
areaFilter	<p>If set, restricts the results to areas matching the filter. Use 'descendantOf' to restrict the area selection. This option is used for drill down reports. Use 'subsetOf' to restrict the granularity. This option is used with tag granularity.</p> <p>For example: descendantOf: Campus C1 has Building B1 which zone Z1 and Z2 Campus C2 has Building B2 which zone Z3 query area=Z1,Z2,Z3 and granularity=Building and areaFilter=descendantOf:C1 will return only Building B1</p> <p>For example: subsetOf: Tag T1,T2 assigned to F1, T2,T3 to F2, T3,T4 to F3 query area=F1,F2,F3 and granularity=tag and areaFilter=subsetOf:T1,T2 will return only T1,T2.</p>	<ul style="list-style-type: none"> <li>descendantOf</li> <li>subsetOf:comma separated ids</li> </ul>
expandAll	Include all of the elements descendants in the result	<ul style="list-style-type: none"> <li>true</li> <li>false</li> </ul>

**HTTP Method**

POST

**Resource URI**

/api/analytics/v1/deviceDwell

**Requires Basic Auth**

N

**Parameters***Table 26: Parameter Details*

Name	Required	Default	Type	Location	Description
body	Y	—	JSON array	body	JSON array containing parameters.



## Content Type

application/json

## Sample Input (JSON)

```
{
  "period": "today",
  "timeRange": "00:00-23:59",
  "granularity": "hourly",
  "areas": "52,75"
}
```

## Sample Output (JSON)

```
{
  "startTime": "00:00",
  "startDate": "2017-03-16",
  "connectionState": "all",
  "results": [
    {
      "id": 53,
      "ancestry": [
        {
          "level": "Building",
          "name": "REQ"
        },
        {
          "level": "Campus",
          "name": "Richfield"
        }
      ],
      "series": [
        "datetime"
      ],
      "hasChildren": false,
      "level": "FLOOR",
      "area": "2nd Floor",
      "data": []
    },
    {
      "id": 75,
      "ancestry": [
        {
          "level": "Floor",
          "name": "Site 4"
        },
        {
          "level": "Building",
          "name": "Site 4"
        },
        {
          "level": "Campus",
          "name": "San Jose Outdoor"
        }
      ],
      "series": [
        "datetime"
      ],
      "hasChildren": false,
      "level": "AP",
      "area": "f4:0f:1b:1a:82:90",
      "data": []
    }
  ]
}
```

```
    }  
  ],  
  "interval": "hourly",  
  "executionTime": 0,  
  "minValue": 2147483647,  
  "endDate": "2017-03-16",  
  "endTime": "23:59",  
  "dataFreshness": "2017-03-16T02:58:04.319-07:00",  
  "maxValue": 0  
}
```