



## Prerequisites

- [Prerequisites for Configuring Connector 3, on page 1](#)
- [Recommended Deployment Architecture , on page 1](#)

### Prerequisites for Configuring Connector 3

- Make sure you allow access to necessary endpoints based on the region of your Cisco Spaces account. Refer to the following table for the endpoints that must be enabled:

*Table 1: Enable Endpoints*

Cisco Spaces Account	Endpoint to be Enabled
<a href="https://dnaspaces.io">https://dnaspaces.io</a>	<a href="https://connector.dnaspaces.io">https://connector.dnaspaces.io</a>
<a href="https://dnaspaces.eu">https://dnaspaces.eu</a>	<a href="https://connector.dnaspaces.eu">https://connector.dnaspaces.eu</a>
<a href="https://ciscospaces.sg">https://ciscospaces.sg</a>	<a href="https://connector.ciscospaces.sg">https://connector.ciscospaces.sg</a>

- Connector needs to be able to reach a Domain Name System (DNS) server. If you set up an explicit proxy, ensure that Connector 3 maintains the ability to communicate through this proxy.
- VMware ESXi 7.0 or 8.0.
- VMware vCenter 7.0 or 8.0
- Virtual machine size: Standard option
- Minimum bandwidth required: 4 Mbps

### Recommended Deployment Architecture

The following is the recommended deployment architecture for connector:

- Virtual machine size (vCPU): 2
- RAM: 4 GB
- Hard Disk: 120 GB

