



RADIUS Configurations

This section covers all the RADIUS Configurations

- [Configure the node for the RADIUS Endpoint Pod, on page 1](#)
- [RADIUS Resource Configuration, on page 2](#)
- [Ops-Center configuration for enabling IPv6 in RADIUS Endpoint, on page 3](#)
- [Configure the RADIUS Endpoint in cnAAA using Ops-Center, on page 4](#)
- [Ops Center configuration to enable ULB on RADIUS Endpoint, on page 5](#)
- [RADIUS Configuration, on page 7](#)
- [RADIUS AAA Proxy Settings, on page 9](#)

Configure the node for the RADIUS Endpoint Pod

This section describes how to specify the node or host where the RADIUS endpoint must spawn the pod.



Note Configuration changes to the RADIUS endpoint cause the endpoint to restart automatically. Cisco recommends making such changes only within the maintenance window.

Mandatory RADIUS configuration

To configure the RADIUS server with essential parameters for optimal network performance and security, use the following configuration:

```
radius bind-ip <bind IP address>
radius replicas 2
radius settings request-timeout-ms 5000
radius settings max-tries 1
radius async-threading-configuration default-processing-threads 100
radius async-threading-configuration default-action-priority 5
radius async-threading-configuration default-action-threads 100
radius async-threading-configuration default-action-queue-size 400000
radius async-threading-configuration default-action-drop-oldest-when-full true
radius device-group ASR9K
  default-shared-secret <secret value>
  default-coa-shared-secret <secret value>
  coa-port 3799
  coa-timeout-seconds 3
  device <BNG Device Name>
```

```

    ip                <BNG IP Address>
    shared-secret     <secret value>
    coa-shared-secret <secret value>
    loopback-addresses [ <loopback addresses> ]
  exit
radius server-group <Server Group Name>
  servers <server name>
    primary          <primary OCS IP Address>
    secondary        <secondary OCS IP Address>
    nas-ip           <nas p address>
    accounting-port   1803
    authorization-port 1802
    auth-protocol     PAP
    radius-password   <radius password>
    shared-secret     <secret value>
    timeout-seconds   3
    test-message      false
    test-userid       test
    test-password     test123
    thread-pool-size   330
    max-proxy-queue-size 50000
    server-type       online (or) offline
    retries           0
  exit
radius properties grpc.executors
  value 5
exit
radius properties grpc.timeoutMs.processing
  value 5000
exit
radius properties io.netty.eventLoopThreads
  value 16
exit
radius properties parallelChannelCount
  value 5
exit
radius properties prometheusPort
  value 9099
exit
radius properties radiusCorePoolSize
  value 20
exit
radius properties radiusMaxQueue
  value 4000
exit
radius properties traps.tps
  value 4000
exit
radius properties udpMaxQueue
  value 4000
exit
radius properties udpPoolSize
  value 20
exit

```

RADIUS Resource Configuration

This section describes how to adjust CPU and memory requests and limits for the RADIUS endpoint pods so that resource allocation matches traffic demands and resource throttling is prevented.

radius resources

Command Modes: Exec > Global Configuration

Syntax Description:

```
radius resources { requests { cpu <cores> | memory <GiB> } | limits { cpu <cores> | memory
    <GiB> }
}
```

requests cpu: Configures the CPU request in cores (Range: 1-5).

requests memory: Configures the memory request in GiB.

limits cpu: Configures the CPU limit in cores (Range: 5-32).

limits memory: Configures the memory limit in GiB.

Usage Guidelines

Use this command to dynamically configure CPU and memory resources for radius pods.

Ops-Center configuration for enabling IPv6 in RADIUS Endpoint

To enable the IPv6 on the RADIUS Endpoint within CPC, complete the following configurations in Ops-Center.

General RADIUS settings

```
radius accounting-port 1813
radius authorization-port 1812
radius coa-port 1700
radius bind-ip 2001:ddff::1
radius settings request-timeout-ms 5000
radius settings max-tries 1
radius settings min-processing-time-millis 3000
radius settings backoff-time-millis 1000
```

BNG device group configurations

BNG Client Configuration

```
device bng01
    ip 2002:20:50:53::100/127
    shared-secret cisco
    coa-shared-secret cisco
    loopback-addresses [ 12.0.0.1 ]
exit
```

RADIUS server group configuration

```
radius server-group grp1
servers DEL_OCS
    primary 2002:20:50:52::100
    secondary 2002:20:50:52::101
    accounting-port 1803
    authorization-port 1802
    auth-protocol PAP
    radius-password test123
    shared-secret cisco
    timeout-seconds 5
    test-message false
    test-userid test
    test-password test123
    thread-pool-size 400
    max-proxy-queue-size 40000
```

```

server-type    online (or) offline
retries        3
exit
exit

```

Configure the RADIUS Endpoint in cnAAA using Ops-Center

To configure the RADIUS Endpoint in cnAAA using Ops-Center, follow these steps:

Procedure

Step 1 Configure the RADIUS Device Group by defining shared secrets and loopback addresses for each BNG device.

```

radius device-group ASR9K
default-shared-secret sh512
default-coa-shared-secret aes256
device dev1
ip 10.1.2.12
shared-secret aes128
coa-shared-secret sh256
loopback-addresses [12.3.1.2]
exit
device dev2
ip 3.4.5.6
shared-secret sh345
coa-shared-secret aes111
loopback-addresses [3.4.8.1]
exit

```

Step 2 Configure the RADIUS Server Group by setting up primary and secondary server IPs, ports, server-type, and authentication protocols.

```

radius server-group grp1
servers serv1
primary 3.4.4.4
secondary 5.5.5.3
nas-ip 1.1.2.2
accounting-port 8312
authorization-port 1312
auth-protocol PAP
radius-password test123
shared-secret sh233
timeout-seconds 20
test-message false
test-userid test
test-password test123
thread-pool-size 10
max-proxy-queue-size 3
server-type    online (or) offline
exit

```

Ops Center configuration to enable ULB on RADIUS Endpoint

To enable the ULB in cnAAA, configure the ops-center as follows:

1. Set the ULB parameter to "true" to activate the backend load balancing service.
2. If the ULB parameter is "false" the system uses default Kubernetes capabilities for traffic management.

General RADIUS Settings

```
cnaaa# show running-config radius | nomore

radius accounting-port 1812
radius authorization-port 1813
radius coa-port 2799

radius bind-ipv4 [ bind IPv4 address ]
radius bind-ipv6 [ bind IPv4 address ]
radius replicas 2
radius lbs-service true
radius settings request-timeout-ms 5000
radius settings max-tries 4
radius settings min-processing-time-millis 3000
radius settings backoff-time-millis 1000
```

Configuration Notes

- radius bind-ip host_address: Specifies the host address for the RADIUS binding.
- replicas number_of_replicas: Indicates the number of replicas.
- ULB-service boolean_value: Specifies whether the load balancing service is enabled (true or false).
- settings request-timeout-ms timeout_in_milliseconds: Sets the request timeout in milliseconds.
- settings max-tries max_attempts: Defines the maximum number of retry attempts.
- settings min-processing-time-millis min_processing_time_in_milliseconds: Sets the minimum processing time in milliseconds.
- settings backoff-time-millis backoff_time_in_milliseconds: Sets the backoff time in milliseconds.

RADIUS Device Group: ASR9K

```
radius device-group ASR9K

default-shared-secret sh512

default-coa-shared-secret cisco

device dev1

ip 10.1.2.12

shared-secret cisco

coa-shared-secret cisco

loopback-addresses [ 12.3.1.2 ]

exit
```

```

device dev2

ip                3.4.5.6

shared-secret     cisco

coa-shared-secret cisco

loopback-addresses [ 3.4.8.1 ]

exit

exit

```

Configuration Notes

- default-shared-secret cisco – Specifies the default shared secret for RADIUS communication.
- default-coa-shared- cisco – Specifies the default shared secret for CoA communication.
- device dev1 – Configures a RADIUS device with specific settings: ip– The IP address of the device.
- shared-secret cisco – The shared secret for communication with the device.
- coa-shared-secret cisco – The shared secret for CoA communication with the device.
- loopback-addresses – Specifies the loopback addresses for the device.

RADIUS Server Group: grp1

```

radius server-group grp1

servers serv1

primary          3.4.4.4

secondary        5.5.5.3

nas-ip           1.1.2.2

accounting-port   8312

authorization-port 1312

auth-protocol     PAP

radius-password   <password>

shared-secret     <secret>
timeout-seconds   20

test-message      false
server-type       online (or) offline

```

Configuration Notes

- servers serv1 – Specifies the servers within the group.
- primary– The primary server's IP address.

- secondary – The secondary server's IP address.
- nas-ip– The IP address of the Network Access Server (NAS).
- authorization-port – The port used for authorization requests within the server group.
- auth-protocol PAP – Specifies the authentication protocol used, in this case, PAP.
- radius-password cisco– The password used for RADIUS authentication.
- shared-secret cisco – The shared secret used for communication within the server group.
- timeout-seconds 20 – Specifies the timeout duration in seconds for server responses.
- test-message false – Indicates whether test messages are enabled or disabled.
- test-userid cisco – The user ID used for test purposes.
- test-password cisco – The password used for test purposes.
- thread-pool-size 10 – Specifies the size of the thread pool for handling requests.
- max-proxy-queue-size 3 – Specifies the maximum size of the proxy queue.
- server-type - Specify as "online" for OCS server and "offline" for Passive-MZ server.
- radius properties grpc.executors – Configures properties related to gRPC executors.
- value 40 – Specifies the value for the gRPC executors property.

For more information on ULB, see the *Unified Load Balancer Configuration and Administration Guide*.

RADIUS Configuration

Click **RADIUS Configuration** in the right pane to add the configuration in the system.

Figure 1: RADIUS Configuration

RADIUS Configuration

*Accounting Port: 1813

*Authorization Port: 1812

*Coa Port: 3799

*Date Time Format: yyyyMMddHHmmss

*Location Db Host1: sessionmgr01

Location Db Host2:

*Location Db Port: 27017

☒ Accounting Enabled

☒ Authorization Enabled

☐ Coa Enabled

☐ Log Access Requests

☐ Log Accounting

☐ Disable Location Db

Proxy Eap Server Settings ☐

▼ Actions

Create Child:

[RADIUS AAA Proxy Settings](#)

215181

The following parameters can be configured under RADIUS Configuration:

Table 1: RADIUS Configuration Parameters

Parameter	Description
Accounting Port	Port used for incoming radius accounting.
Authorization Port	Port used for incoming radius authorization.
Coa Port	Port used for Change of Authority between CPC and Radius Device.
Date Time Format	Time stamping format for radius transactions.
Location Db Host1	Mongo location for Primary Radius database.
Location Db Host2	Mongo location for Secondary Radius database.
Location Db Port	Port number for the Radius database.
Accounting Enabled	Enables CPC to receive incoming Radius Accounting. Default value is True (checked).

Parameter	Description
Authorization Enabled	Enables CPC to receive incoming Radius Authorization. Default value is True (checked).
Coa Enabled	Enables CPC to send and receive CoAs.
Log Access Requests	Log the radius accounting which is configured in <code>/etc/broadhop/logback.xml</code> . The typical default logging location is <code>/var/broadhop/radius/accounting/accounting.current</code> .
Log Accounting	Logs radius authorization requests, also configured in <code>/etc/broadhop/logback.xml</code> . The typical default logging location is <code>/var/broadhop/radius/access/rejects.current</code> .
Disable Location Db	Will not record WLC locations in the Radius mongo DB. Default value is False (unchecked).

For information on proxy settings, refer to [RADIUS AAA Proxy Settings](#).

RADIUS AAA Proxy Settings

Click **RADIUS AAA Proxy Settings** to add the configuration in the system. These proxy settings are used for domain-based subscriber authorization.

Table 2: RADIUS AAA Proxy Settings

Parameter	Description
RADIUS Server	Server Identification which will be mapped between Proxy Settings and Domain/Service.
Accounting Port	AAA Server Accounting Port which will receive and process accounting requests.
Authorization Port	AAA Server Authorization Port which will receive and process authentication requests.
Primary IP Address	Primary AAA Server IP address.
Secondary IP Address	Secondary AAA Server IP address.
RADIUS NAS IP Address	NAS IP address which will be sent in the proxied requests.
RADIUS Auth Protocol	RADIUS authentication protocol used. Default: PAP
RADIUS Password	RADIUS authentication password.
Retries	Number of times the requests will be retried in a failure scenario.
Shared Secret	Shared Secret of the AAA Server.

Parameter	Description
Test User Id	RADIUS username used for testing between CPC and AAA Server.
Test Password	RADIUS password used for testing between CPC and AAA Server.
Thread Pool Size	Number of threads to handle proxying of requests.
Max Proxy Queue Size	Maximum number of requests that can be queued before being proxied.
Send Test Message	Select this option to send a test message to the AAA server when CPC comes up.