



Mobile Policy Diameter Commands

- [diameter, on page 1](#)
- [diameter application, on page 1](#)
- [diameter group, on page 2](#)
- [diameter group stack, on page 3](#)
- [diameter group stack diameter-engine alt-engines, on page 4](#)
- [diameter group stack diameter-engine alt-engines primary, on page 5](#)
- [diameter group stack diameter-engine alt-engines secondary, on page 5](#)
- [diameter group stack grpc ext-svc, on page 5](#)
- [diameter group stack settings timeouts-ms, on page 6](#)
- [diameter grpc, on page 7](#)
- [diameter grpc channel, on page 7](#)
- [diameter next-hop-route next-hop-host, on page 8](#)
- [diameter settings timeouts-ms, on page 8](#)

diameter

Displays the configured Diameter stack definition.

Command Modes

Exec

Syntax Description

`show diameter`

Usage Guidelines

Use this command to view the configured Diameter stack definition.

Example

The following command displays the configured Diameter stack definition:

```
show diameter peer-status
```

diameter application

Configures the Diameter application definition.

Command Modes	Exec > Global Configuration
Syntax Description	application <i>application_name</i> { application-id <i>application_id</i> tgpp-application { false true } vendor <i>vendor_id</i> } application-id <i>application_id</i> Specify the application ID. Must be an integer. application <i>application_name</i> Specify the application abbreviation. For example, gx. Must be a string. tgpp-application { false true } Specify whether the application is a 3GPP application. Must be either "false" or "true". Default Value: false. vendor <i>vendor_id</i> Specify the vendor IDs. Must be an integer.
Usage Guidelines	Use this command to configure the Diameter application definition.

diameter group

Configures the Diameter stack group parameters.

Command Modes	Exec > Global Configuration
Syntax Description	group [group <i>group_name</i> mode <i>mode</i> repository <i>repository_name</i> stack <i>stack_name</i>] group <i>group_name</i> Specify the group and stack name. Must be a string in the pattern [a-zA-Z][a-zA-Z0-9-]*. mode <i>mode</i> Specify the mode in which the Diameter stack must run. Must be one of the following: • client

- server

Default Value: client.

repository *repository_name*

Specify the Helm repository.

Usage Guidelines

Use this command to configure the Diameter stack group.

diameter group stack

Configures the Diameter stack definition.

Command Modes

Exec > Global Configuration

Syntax Description

```
group group_name stack stack_name { application application_name | bind-ip
bind_ip_address | bind-port bind_port_number | fqdn fqdn_name | realm realm |
peer-host peer_host_name | peer-port peer_port_number | peer-realm peer_realm |
node-host node_host }
```

application *application_name*

Specify the Diameter application.

bind-ip *bind_ip_address*

Specify the IP address to use in the CER or CEA message.

Must be an IP address.

bind-port *bind_port_number*

Specify the port number to bind the server.

Must be a port number.

Default Value: 3868.

fqdn *fqdn*

Specify the fully qualified domain name (FQDN) to use in CER or CEA messages.

Must be a string.

node-host *node_host*

Specify the node host to start the stack on.

Must be a string.

peer-host *peer_host_name*

Specify the remote peer host address or FQDN.

Must be a string.

peer-port *peer_port_number*

Specify the peer port number.

Must be a port number.

Default Value: 3868.

peer-realm *peer_realm*

Specify the remote peer realm.

Must be a string.

realm *realm*

Specify the realm to use in CER or CEA messages.

Must be a string.

replicas *replica_count*

Specify the replica count.

Must be an integer.

Default Value: 1.

stack *stack_name*

Specify the stack name.

Must be a string.

Usage Guidelines

Use this command to configure the Diameter stack definition.

diameter group stack diameter-engine alt-engines

Configures the alternate Diameter engine parameters.

Command Modes

Exec > Global Configuration > Diameter Group Configuration > Stack Configuration

Syntax Description

alt-engines check-session-exists { false | true }

check-session-exists { false | true }

Specify whether to check if the session exists on the alternate-engines before forwarding requests.

Must be either "false" or "true".

Default Value: false.

Usage Guidelines

Use this command to configure the alternate Diameter engine parameters.

diameter group stack diameter-engine alt-engines primary

Configures the primary Diameter Engine parameters.

Command Modes Exec > Global Configuration > Diameter Group Configuration > Stack Configuration

Syntax Description **primary** **svc-name** *service_name* **port** *port_number*

port *port_number*

Specify the port number exposed by the external service.

Must be a port number.

Default Value: 8884.

svc-name *service_name*

Specify the external service name that represents the Diameter engine.

Usage Guidelines Use this command to configure the primary Diameter Engine parameters.

diameter group stack diameter-engine alt-engines secondary

Configures the secondary Diameter Engine parameters.

Command Modes Exec > Global Configuration > Diameter Group Configuration > Stack Configuration

Syntax Description **secondary** **svc-name** *service_name* **port** *port_number*

port *port_number*

Specify the port number exposed by the external service.

Must be a port number.

Default Value: 8884.

svc-name *service_name*

Specify the external service name that represents the Diameter engine.

Usage Guidelines Use this command to configure the secondary Diameter Engine parameters.

diameter group stack grpc ext-svc

Configures the external gRPC service parameters for the Diameter interface.

Command Modes Exec > Global Configuration

Syntax Description **ext-svc** { **port** *port_number* | **ip** *ip_address* }

ip *ip_address*

Specify the gRPC server's IP address.

Must be an IP address.

port *port_number*

Specify the port number to bind the server.

Must be a port number.

Default Value: 8868.

Usage Guidelines Use this command to configure the external gRPC service parameters for the Diameter interface.

diameter group stack settings timeouts-ms

Configures the timeout parameters for the Diameter interface.

Command Modes Exec > Global Configuration

Syntax Description **timeout-ms** [**cea** *cea_timeout* | **dpa** *dpa_timeout* | **dwa** *dwa_timeout* | **iac** *inactivity_timeout* | **request** *request_timeout* | **stop** *timeout_stop_diameter*]

cea *cea_exchange_timeout*

Specify the timeout duration for completing the CEA exchange in milliseconds.

Must be an integer.

Default Value: 10000.

dpa *dpa_timeout*

Specify the DPA timeout duration in milliseconds.

Must be an integer.

Default Value: 10000.

dwa *dwa_timeout*

Specify the DWA timeout duration in milliseconds.

Must be an integer.

Default Value: 10000.

iac *inactivity_timeout*

Specify the inactivity timeout duration in milliseconds.

Must be an integer.

Default Value: 5000.

request *request_timeout*

Specify the request timeout duration in milliseconds.

Must be an integer.

Default Value: 1750.

stop *stop_timeout*

Specify the timeout duration for stopping the Diameter interface in milliseconds.

Must be an integer.

Default Value: 9000.

Usage Guidelines

Use this command to configure the timeout duration for the Diameter interface.

Example

The following command configures the timeout duration for the Diameter interface:

```
diameter settings timeout-ms [ cea 10000 | dpa 10000 | dwa 10000 | iac 5000 | request 1750
| stop 9000 ]
```

diameter grpc

Configures the global gRPC settings.

Command Modes

Exec > Global Configuration

Syntax Description

grpc

Usage Guidelines

Use this command to configure the global gRPC settings.

Example

The following command configures the global gRPC settings:

```
diameter grpc channel count 100
```

diameter grpc channel

Configures the gRPC channels to open towards the server.

Command Modes

Exec > Global Configuration

Syntax Description

grpc channel count *channel_count*

channel *channel_count*

Specify the number of channel to open towards the server.

Must be an integer.

Default Value: 10.

Usage Guidelines

Use this command to configure the gRPC channels to open towards the server.

diameter next-hop-route next-hop-host

Configures the next-hop host name.

Command Modes

Exec > Global Configuration

Syntax Description

next_hop_realm rating *rating*

next-hop-host-name *hostname_list*

Specify the DRA hosts name list as received in the Origin-Host AVP in CER or CEA message.

Must be a string.

rating *rating*

Specify the rating that determines the priority.

Must be an integer.

Default Value: 0.

Usage Guidelines

Use this command to configure the next-hop host name.

Example

The following command configures the next-hop host name:

```
next_hop_realm rating 2
```

diameter settings timeouts-ms

Configures the timeout parameters for the Diameter interface.

Command Modes

Exec > Global Configuration

Syntax Description

timeout-ms [cea cea_timeout | dpa dpa_timeout | dwa dwa_timeout | iac inactivity_timeout | request request_timeout | stop timeout_stop_diameter]

cea *cea_exchange_timeout*

Specify the timeout duration for completing the CEA exchange in milliseconds.

Must be an integer.

Default Value: 10000.

dpa dpa_timeout

Specify the DPA timeout duration in milliseconds.

Must be an integer.

Default Value: 10000.

dwa dwa_timeout

Specify the DWA timeout duration in milliseconds.

Must be an integer.

Default Value: 10000.

iac inactivity_timeout

Specify the inactivity timeout duration in milliseconds.

Must be an integer.

Default Value: 5000.

request request_timeout

Specify the request timeout duration in milliseconds.

Must be an integer.

Default Value: 1750.

stop stop_timeout

Specify the timeout duration for stopping the Diameter interface in milliseconds.

Must be an integer.

Default Value: 9000.

Usage Guidelines

Use this command to configure the timeout duration for the Diameter interface.

Example

The following command configures the timeout duration for the Diameter interface:

```
diameter settings timeout-ms [ cea 10000 | dpa 10000 | dwa 10000 | iac 5000 | request 1750  
| stop 9000 ]
```

diameter settings timeouts-ms