



Ultra Cloud Core 5G Policy Control Function, Release 2022.02 - Release Change Reference

First Published: 2022-04-29

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at www.cisco.com/go/offices.

The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on standards documentation, or language that is used by a referenced third-party product.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2022 Cisco Systems, Inc. All rights reserved.



CONTENTS

PREFACE

About this Guide	v
Conventions Used	v
Contacting Customer Support	vi

CHAPTER 1

UCC 5G PCF - Release Change Reference	1
Features and Changes Quick Reference	1
Feature Defaults Quick Reference	1
Message Threshold Per Endpoint	2
Feature Summary and Revision History	2
Summary Data	2
Revision History	2
Feature Description	2
N5 Interface	3
Feature Summary and Revision History	3
Summary Data	3
Revision History	3
Feature Description	3
Diameter Peer Load Rebalancing	3
Feature Summary and Revision History	3
Summary Data	3
Revision History	4
Feature Description	4



About this Guide



Note The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. While any existing biased terms are being substituted, exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

This document is a part of the Ultra Cloud Core 5G Policy Control Function documentation set.

For information about available documentation, see the Ultra Cloud Core 5G Policy Control Function Documentation Map for this release at [Cisco.com](https://www.cisco.com).

- [Conventions Used, on page v](#)
- [Contacting Customer Support, on page vi](#)

Conventions Used

The following tables describe the conventions used throughout this documentation.

Notice Type	Description
Information Note	Provides information about important features or instructions.
Caution	Alerts you of potential damage to a program, device, or system.
Warning	Alerts you of potential personal injury or fatality. May also alert you of potential electrical hazards.

Typeface Conventions	Description
Text represented as a screen display	This typeface represents displays that appear on your terminal screen, for example: Login:

Typeface Conventions	Description
Text represented as commands	<p>This typeface represents commands that you enter, for example:</p> <p>show ip access-list</p> <p>This document always gives the full form of a command in lowercase letters. Commands are not case sensitive.</p>
Text represented as a command <i>variable</i>	<p>This typeface represents a variable that is part of a command, for example:</p> <p>show card <i>slot_number</i></p> <p><i>slot_number</i> is a variable representing the applicable chassis slot number.</p>
Text represented as menu or sub-menu names	<p>This typeface represents menus and sub-menus that you access within a software application, for example:</p> <p>Click the File menu, then click New</p>

Contacting Customer Support

Use the information in this section to contact customer support.

Refer to the support area of <http://www.cisco.com> for up-to-date product documentation or to submit a service request. A valid username and password are required to access this site. Please contact your Cisco sales or service representative for additional information.



CHAPTER 1

UCC 5G PCF - Release Change Reference

- [Features and Changes Quick Reference, on page 1](#)
- [Feature Defaults Quick Reference, on page 1](#)
- [Message Threshold Per Endpoint, on page 2](#)
- [N5 Interface, on page 3](#)
- [Diameter Peer Load Rebalancing, on page 3](#)

Features and Changes Quick Reference

Features / Behavior Changes	Release Introduced / Modified
N5 Interface, on page 3	2022.02.0
Message Threshold Per Endpoint, on page 2	2022.02.0
Diameter Peer Load Rebalancing, on page 3	2022.02.0

Feature Defaults Quick Reference

The following table indicates what features are enabled or disabled by default.

Feature	Default
N5 Interface	Enabled – Always on
Message Threshold Per Endpoint	Disabled – Configuration required to enable
Diameter Peer Load Rebalancing	Disabled – Configuration required to enable

Message Threshold Per Endpoint

Feature Summary and Revision History

Summary Data

Table 1: Summary Data

Applicable Product(s) or Functional Area	PCF
Applicable Platform(s)	SMI
Feature Default Setting	Disabled – Configuration required to enable
Related Documentation	<i>UCC 5G PCF Configuration and Administration Guide</i>

Revision History

Table 2: Revision History

Revision Details	Release
Enhancement introduced. PCF supports message threshold per endpoint.	2022.02.0

Feature Description

PCF supports the message threshold per endpoint.



Note Message threshold is applicable only for the configured message types in rest-endpoint.

For more information, see the [Advanced Tuning Parameters](#) chapter in the [UCC 5G PCF Configuration and Administration Guide](#).

N5 Interface

Feature Summary and Revision History

Summary Data

Table 3: Summary Data

Applicable Product(s) or Functional Area	PCF
Applicable Platform(s)	SMI
Feature Default Setting	Enabled – Always-on
Related Documentation	<i>UCC 5G PCF Configuration and Administration Guide</i>

Revision History

Table 4: Revision History

Revision Details	Release
Enhancement introduced. PCF supports N5 Interface.	2022.02.0

Feature Description

PCF supports the N5 Interface.

For more information, see the [Cisco Common Data Layer](#), [Dummy N7 Notify Request](#), [Dynamic ARP Functionality for PC and PV](#), [Dynamic ARP Functionality for PL](#), [Handling the Network Provided Location Information Requests](#), [Multiple Virtual IP Address](#), and [N5 Authorization](#) chapters in the [UCC 5G PCF Configuration and Administration Guide](#)

Diameter Peer Load Rebalancing

Feature Summary and Revision History

Summary Data

Table 5: Summary Data

Applicable Product(s) or Functional Area	PCF
--	-----

Applicable Platform(s)	SMI
Feature Default Setting	Disabled – Configuration required to enable
Related Documentation	<i>UCC 5G PCF Configuration and Administration Guide</i>

Revision History

Table 6: Revision History

Revision Details	Release
First introduced.	2022.02.0

Feature Description

PCF supports diameter peer load rebalancing.

For more information, see the [Diameter Peer Load Rebalancing](#) chapter in the [UCC 5G PCF Configuration and Administration Guide](#).