



Alerts Operation Config Mode Command Reference

- [alerts active](#), on page 1
- [alerts add-silence](#), on page 2
- [alerts add-silence matchers](#), on page 3
- [alerts delete-silence](#), on page 4
- [alerts history](#), on page 4
- [alerts silence-by-id](#), on page 4
- [alerts silences](#), on page 5

alerts active

Displays filtered list of active alerts.

Command Modes	Exec > Global Configuration
Syntax Description	<pre>active filter <i>alerts_filter</i> active { false true } silenced { false true } inhibited { false true } unprocessed { false true } receiver <i>regex</i></pre> active { false true } Specify whether to display active alerts. Must be one of the following: • false • true Default Value: true. filter <i>alerts_filter</i> Specify the alerts filter in the format <i>label expr value or regex</i>. Must be a string.

inhibited { false | true }

Specify whether to display inhibited alerts.

Must be one of the following:

- false
- true

Default Value: false.

receiver *regex*

Specify a regex matching receivers to filter alerts.

Must be a string.

silenced { false | true }

Specify whether to display silenced alerts.

Must be one of the following:

- false
- true

Default Value: false.

unprocessed { false | true }

Specify whether to display unprocessed alerts.

Must be one of the following:

- false
- true

Default Value: false.

Usage Guidelines

Use this command to view filtered list of active alerts.

alerts add-silence

Adds a silence.

Command Modes

Exec > Global Configuration

Syntax Description

add-silence *id* *silence_id* **startsAt** *silence_start_time* **endsAt** *silence_end_time*
createdBy *silence_creator_id* **comment** *additional_info*

comment *additional_info*

Specify additional information for the silence.

Must be a string.

createdBy *silence_creator_id*

Specify the silence creator identity.

Must be a string.

endsAt *silence_end_time*

Specify the silence end time.

Must be a string in the date-and-time pattern. For information on the date-and-time pattern, see the Input Pattern Types section.

id *silence_id*

Specify the silence ID to add.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

startsAt *silence_start_time*

Specify the silence start time.

Must be a string in the date-and-time pattern. For information on the date-and-time pattern, see the Input Pattern Types section.

Usage Guidelines

Use this command to add a silence.

alerts add-silence matchers

Configures the list of label values to filter alerts.

Command Modes

Exec > Global Configuration

Syntax Description

matchers *alert_label_name* **value** *filter_value* **isRegex** { **false** | **true**}

isRegex { false | true }

Specify whether the value is a regular expression or not.

Must be one of the following:

- **false**
- **true**

value *filter_value*

Specify the filter value.

Must be a string.

alert_label_name

Specify the alert label name.

Must be a string.

Usage Guidelines

Use this command to configure the list of label values to filter alerts.

alerts delete-silence

Deletes specified silence.

Command Modes

Exec > Global Configuration

Syntax Description

delete-silence id *silence_id_to_delete*

id silence_id_to_delete

Specify the ID of the silence to delete.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

Usage Guidelines

Use this command to delete specified silence.

alerts history

Displays alerts history.

Command Modes

Exec > Global Configuration

Syntax Description

history filter *alerts_filter*

filter alerts_filter

Specify the comma-separated values to filter alerts.

Must be a string.

Usage Guidelines

Use this command to view alerts history.

alerts silence-by-id

Displays information about a specific silence.

Command Modes

Exec > Global Configuration

Syntax Description

silence-by-id id *silence_id*

id *silence_id*

Specify the silence ID.

Must be a string in the uuid pattern. For information on the uuid pattern, see the Input Pattern Types section.

Usage Guidelines

Use this command to view information about a specific silence.

alerts silences

Displays filtered list of silences.

Command Modes

Exec > Global Configuration

Syntax Description

silences filter *alerts_filter*

filter *alerts_filter*

Specify the alerts filter in the format *label expr value or regex*.

Must be a string.

Usage Guidelines

Use this command to view filtered list of silences.

