



Grafana Config Mode Command Reference

- [grafana](#), on page 1
- [grafana dashboards](#), on page 1
- [grafana enable-basic-auth](#), on page 2

grafana

Configures Grafana parameters.

Command Modes Exec > Global Configuration

Syntax Description `grafana enable { false | true }`

enable { false | true }

Specify to enable or disable Grafana and dashboard.

Must be one of the following:

- **false**
- **true**

Default Value: true.

Usage Guidelines Use this command to configure Grafana parameters.

grafana dashboards

Configures Git repositories containing dashboards.

Command Modes Exec > Global Configuration

Syntax Description `grafana dashboards [git_repo_name] git-url git_url`

git-url *git_url*

Specify the Git URL.

Must be a string.

git_repo_name

Specify name of the Git repository.

Must be a string.

Usage Guidelines Use this command to configure Git repositories containing dashboards.

grafana enable-basic-auth

Configure basic authentication in CEE Ops Center.

Command Modes Exec > Global Configuration

Syntax Description `grafana enable-basic-auth { false | true }`

enable-basic-auth { false | true }

Specify to enable or disable basic authentication in CEE Ops Center.

Must be one of the following:

- **false**
- **true**

Default value: **true**

Usage Guidelines Use this command to configure basic authentication in CEE Ops Center for custom Grafana dashboards.