



# Grafana Config Mode Command Reference

---

- [grafana](#), on page 1
- [grafana dashboards](#), on page 1
- [grafana enable-basic-auth](#), on page 2

## grafana

Configures Grafana parameters.

**Command Modes** Exec > Global Configuration

**Syntax Description** `grafana enable { false | true}`

**enable { false | true}**

Specify to enable or disable Grafana and dashboard.

Must be one of the following:

- **false**
- **true**

Default Value: true.

**Usage Guidelines** Use this command to configure Grafana parameters.

## grafana dashboards

Configures Git repositories containing dashboards.

**Command Modes** Exec > Global Configuration

**Syntax Description** `grafana dashboards [ git_repo_name ] git-url git_url`

**grafana enable-basic-auth****git-url *git\_url***

Specify the Git URL.

Must be a string.

**git\_repo\_name**

Specify name of the Git repository.

Must be a string.

---

**Usage Guidelines** Use this command to configure Git repositories containing dashboards.

## grafana enable-basic-auth

Configure basic authentication in CEE Ops Center.

---

**Command Modes** Exec > Global Configuration

---

**Syntax Description** **grafana enable-basic-auth { false | true}****enable-basic-auth { false | true}**

Specify to enable or disable basic authentication in CEE Ops Center.

Must be one of the following:

- **false**
- **true**

Default value: **true**

---

**Usage Guidelines** Use this command to configure basic authentication in CEE Ops Center for custom Grafana dashboards.