



# VES Adapter Config Mode Command Reference

- [ves-adapter](#), on page 1
- [ves-adapter measurement-group](#), on page 2
- [ves-adapter measurement-group measurement](#), on page 2

## ves-adapter

Configures VES Adapter parameters.

**Command Modes** Exec > Global Configuration

**Syntax Description**

```
ves-adapter enable { false | true } [ [ [ url ves_listener_url | user-name  
ves_listener_user_name | password ves_listener_password ] | measurement-interval  
measurement_interval ] | [ measurement-group [ name group_name | measurement [  
name measurement_name ] query measurement_query ] ] | measurement-group  
measurement_group_name [ measurement measurement_name | query measurement_query ] ]
```

### enable { false | true}

Specify to enable or disable the VES Adapter.

Must be one of the following:

- **false**
- **true**

Default Value: false.

### measurement-interval *measurement\_interval*

Specify the interval to fetch measurements in seconds.

Must be an integer in the range of 1-86400.

Default Value: 300.

### password *ves\_listener\_password*

Specify the VES Listener password.

**ves-adapter measurement-group**

Must be a string.

***url ves\_listener\_url***

Specify the VES Listener URL with path.

Must be a string.

***user-name ves\_listener\_user\_name***

Specify the VES Listener user name.

Must be a string.

**Usage Guidelines** Use this command to configure VES Adapter parameters.

## ves-adapter measurement-group

Configures the list of additional measurement groups.

**Command Modes** Exec > Global Configuration

**Syntax Description** **ves-adapter enable { true } measurement-group *group\_name***

***group\_name***

Specify the additional measurement group name.

Must be a string.

**Usage Guidelines** Use this command to configure the list of additional measurement groups.

## ves-adapter measurement-group measurement

Configures the list of additional measurement queries.

**Command Modes** Exec > Global Configuration

**Syntax Description** **ves-adapter enable { true } measurement-group *group\_name* { measurement\_name *query measurement\_query*}**

***query measurement\_query***

Specify the query to execute in Promo QL format.

Must be a string.

***measurement\_name***

Specify the measurement name.

Must be a string.

**Usage Guidelines** Use this command to configure the list of additional measurement queries.

ves-adapter measurement-group measurement