

ADC for Dynamic Rules

Table 1: Feature History

Feature Name	Release Information	Description
ADC Dynamic Rules over Gx	2024.02.0	UPF leverages the dynamic ADC rules for traffic matching and charging. This feature allows the service providers to manage IoT devices, such as connected cars, and charge their subscribers based on the traffic flows classified by SMF or UPF. With this traffic classification, the service providers enable service monetization. In summary, SMF first processes the dynamic ADC rules received from PCF with TDF-App-Identifier, Service ID, and Rating group. SMF then sends this information to UPF to classify ruledefs and perform charging. Default Setting: Enabled – Always-on

- Feature Description, on page 1
- How it Works, on page 1
- OAM Support, on page 2

Feature Description

UPF processes N4 messages received from SMF and installs, removes, and modifies the message entities (PDR/URR/FAR/QER) of dynamic ADC rules.

UPF matches the configured ruledef with the TDF-App-Identifier AVP received in the dynamic ADC rule as part of PDR installation from SMF. If matched, UPF classifies the packets and charges the subscribers as per the Rating Group and Service ID of the Dynamic rule PDR.

How it Works

PCRF installs a dynamic ADC rule with charging rule definition on SMF. UPF receives the N4 messages from SMF containing the dynamic ADC rule-related PDRs, URRs, QERs, and FARs. The dynamic ADC rule PDR contains the Application ID corresponding to the TDF-App-Identifier received from the PCRF and the Mute notification. UPF does not enable any Application Start/Stop triggers as Mute is enabled.

Upon receiving the N4 message, UPF matches the ruledef pointed using the Application ID/TDF-App-Identifier. UPF then charges the packets matching to this ruledef against the URR received and applies bandwidth policing based on the QER received for the dynamic ADC rule PDR.

UPF supports the following three use cases to support dynamic ADC rules:

• Installing a Dynamic ADC Rule per Subscription: Upon receiving the dynamic ADC rule from PCRF, SMF installs the rule and sends an N4 Session Establishment Request to UPF to create PDR, QER, FAR, and URR. The Create PDR Request for this dynamic ADC rule contains the TDF-App-Identifier and Mute AVP enabled for all dynamic ADC rules.

UPF matches the configured ruledef with the TDF-App-Identifier and charges the packets according to the RG/SI received in the Dynamic ADC rule. UPF does not generate the N4 Session report for APP-START/STOP, as Mute notifications are enabled from PCRF on SMF during rule install.

Modifying a Dynamic ADC Rule from PCRF/SMF: PCRF sends a Re-authorization request (RAR) to SMF along with a Dynamic ADC Rule Modification request. SMF then sends a Session Modification Request to UPF to update QER containing the updated gate status and MBR values.

UPF performs modifications of the AVPs and sends a N4 Session Modification Response to SMF.

• Removing a Dynamic ADC Rule from PCRF/SMF: UPF receives an N4 Modify Request with Remove PDRs and QERs corresponding to the dynamic ADC rule. UPF also receives Remove URRs occasionally, if it is the last rule for that Rating-Group/Service-ID.

Upon receiving the N4 Modify Request, UPF stops matching the rule for the ruledef pointed by the TDF-App-Identifier from the Session Modification Request.

For detailed information on dynamic ADC rules, see the *UCC 5G SMF Configuration and Administration Guide* applicable for the release.

OAM Support

This section describes operations, administration, and maintenance support for this feature.

Show Command Output

This section describes the show commands supported in this feature.

show subscribers user-plane-only full all

The output of the show command **show subscribers user-plane-only full all** has been enhanced to display the number of associated ADC PDRs.

```
[local]UPF1# show subscribers user-plane-only full all

Local SEID : [0x00040000000002] 1125899906842626
Remote SEID : [0x0000004bebf6665] 20380083813
State : Connected
Connect Time : Wed Apr 3 12:45:51 2024
Idle time : 00h00m07s
Access Type: uplane-ipv4v6 Network Type: IP
user-plane-service-name: user-plane-service
active-service-scheme-name:
Callid: 00004e23
Rulebase: adc1
```

```
Interface Type: N4
eMPS Session: No
eMPS Session Priority: 0
Session-Type: normal
Precedence-order: 0
Data Queue: 0
Card/Cpu: 1/0
                                       Sessmgr Instance: 1
IP address: 2001:cb0:0:3::4e:2301,11.11.0.4
Next Hop Ip Address: N/A,
Source context: EPC2-UP
                                       Destination context: ISP
PDN-Instance: cnpgw
User-plane-Sx-addr: 20.20.20.106
Control-plane-Sx-addr: 20.20.20.3
Number of associated PDRs : 4
Number of associated ADC PDRs : 2
Number of associated FARs : 4
Number of associated QERs : 3
Number of associated BARs : 0
Number of associated URRs : 5
Number of associated BLIs : 1
Uplink APN AMBR (bps) : 100000
                                     Downlink APN AMBR (bps): 100000
active input acl: n/a
                                    active output acl: n/a
active input ipv6 acl: n/a
                                     active output ipv6 acl: n/a
Bandwidth Policy: n/a
FW-and-NAT Policy: n/a
FW-and-NAT Policy ID: n/a
Firewall Policy IPv4: n/a
Firewall Policy IPv6: n/a
NAT Policy NAT44: n/a
NAT Policy NAT64: n/a
Converged Session: No
                                      Converged Peer Callid:
                                                                  n/a
Visited Call: No
Subscriber Parameters:
IMSI: 123456781300001
TMET: 123456781312381
MSISDN: 22331101101010
Rat Type: 6
Old Rat Type: n/a
MCC MNC: 123456
SGSN Address: 20.20.20.15
ULI: TAI+ECGI=21635400152163540000000d00
CF Policy ID: n/a
GX CF Policy ID: n/a
S-NSSAI: 0x01000002
Roaming Status: Homer
Old Roaming Status: n/a
                                                output pkts: 5
input pkts: 5
input bytes: 5200
                                                output bytes: 200
                                                output bytes dropped: 0
input bytes dropped: 0
input pkts dropped: 0
                                                output pkts dropped: 0
CF Buffered Uplink Packets: 0
                                                CF Buffered Downlink Packets: 0
                                               CF Buffered Downlink Bytes: 0
CF Buffered Uplink Bytes: 0
Uplink Packets in Buffer: 0
                                               Downlink Packets in Buffer: 0
Buff Over-limit Uplink Pkts: 0
                                               Buff Over-limit Downlink Pkts: 0
DDN buffered pkts : 0
                                                DDN buffered bytes : 0
DDN buffer overflow drop pkts : 0
                                                DDN buffer overflow drop bytes : 0
pk rate from user(bps): 0
                                                pk rate to user(bps): 0
ave rate from user(bps): 0
                                                ave rate to user(bps): 0
sust rate from user(bps): 0
                                               sust rate to user(bps): 0
pk rate from user(pps): 0
                                               pk rate to user(pps): 0
ave rate from user(pps): 0
                                                ave rate to user(pps): 0
sust rate from user(pps): 0
                                                sust rate to user(pps): 0
                                                ipv4 ttl exceeded: 0
ipv4 bad hdr: 0
ipv4 fragments sent: 0
                                                ipv4 could not fragment: 0
```

```
ipv4 bad length trim: 0
input pkts dropped (0 mbr): 0
                                               output pkts dropped (0 mbr): 0
ipv4 input acl drop: 0
                                               ipv4 output acl drop: 0
ipv6 input acl drop: 0
                                               ipv6 output acl drop: 0
ip source violations: 0
                                                ipv4 output no-flow drop: 0
ipv6 bad hdr: 0
                                                ipv6 bad length trim: 0
ipv4 icmp packets dropped: 0
APN AMBR Uplink Pkts Drop: 0
                                                APN AMBR Downlink Pkts Drop: 0
APN AMBR Uplink Bytes Drop: 0
                                                APN AMBR Downlink Bytes Drop: 0
APN AMBR Uplink Pkts IP pref lowered: 0
                                               APN AMBR Downlink Pkts IP pref lowered:
APN AMBR Uplink Bytes IP pref lowered: 0
                                               APN AMBR Downlink Bytes IP pref lowered:
ITC Uplink Pkts Drop: 0
                                                 ITC Downlink Pkts Drop: 0
ITC Uplink Bytes Drop: 0
                                                 ITC Downlink Bytes Drop: 0
                                                 ITC Downlink Pkts IP pref lowered: 0
ITC Uplink Pkts IP pref lowered: 0
ITC Uplink Bytes IP pref lowered: 0
                                                 ITC Downlink Bytes IP pref lowered: 0
ITC Terminated Flows:: 0
                                                 ITC Redirected Flows: 0
Flow Action Terminated Flows: 0
                                                Flow Action Redirected Flows: 0
ToS marked Uplink Pkts: 0
                                                ToS marked Downlink Pkts: 0
CC Dropped Uplink Pkts: 0
                                                CC Dropped Downlink Pkts: 0
CC Dropped Uplink bytes: 0
                                                 CC Dropped Downlink Bytes: 0
Uplink Inflight Pkts: 0
                                                 Downlink Inflight Pkts: 0
QFI Mismatch Uplink Pkts Drop: 0
                                                QFI Mismatch Downlink Pkts Drop: 0
Total QoS-Group(s) Active: 0
DNS-to-EDNS Uplink Pkts: 0
                                               DNS-to-EDNS Uplink Bytes: 0
EDNS Response Received: 0
Flow information:
  Current Active Flows:
    TCP: 1
    UDP: 0
  Total Flows:
    TCP: 1
    UDP: 0
    FP: 1
```

show subscribers user-plane-only callid callid pdr full all

The output of the show command **show subscribers user-plane-only callid** *callid* **pdr full all**has been modified to display the following new fields:

- TDF App Id
- TDF Notifications
- Total ADC PDRs found

```
[local]UPF1# show subscribers user-plane-only callid 00004e21 pdr full all
Callid: 00004e21
Interface Type: N4
IP address: 2001:cb0:0:3::4e:2301,11.11.0.4
PDR-ID:
                        0x0003
Rule Name:
                         port-2000
Rule Name: port-2000
TDF Notifications: Disabled
                        1 Match Bypassed:
Matched Bytes:
                       200 Matched Packets:
Precedence:
Source Interface:
                      Core
Source Interface Type: N/A
 SDF Filter(s):
```

```
No SDF filters present
Local F-TEID:
                       0 \times 0
Local F-TEID IP Addr:
 IPv4:
                     N/A
 IPv6:
                      N/A
 Outer header removal:
Application ID: N/A 0x80000001
 Destination Interface: Access
 Apply Action: FORWARD
 Outer Header Creation: GTP-U/UDP/IPv4
 Remote TEID: 0x3000000
 Transport Level Marking: N/A
 Transport Level Marking Options:
   Copy Inner:
                                Nο
   Copy Outer:
                                No
 Inner Packet Marking:
 Remote IP Address:
                       20.20.20.15
Remote Port:
                      N/A
                     2
Associated QERIDs:
                     Correlation-ID
 OER-IDs
0x000000003
0x00000001 0x00000001
Associated URRIDs: 4
Parent URR-ID
                          0x000000E
                     0x80000002
  0x00000011
  0x00000027
                      n/a
  0x80000002
                           n/a
  0x80000009
                           n/a
Activation Time:
                      N/A
Deactivation Time:
Bearer Level Info-id:
                           1
   5QI:
   ARP:
                          20
   Charging Id:
                         4
PDR-ID:
                        0x0004
            port-2000
Rule Name:
                        port-2000
 TDF App Id:
TDF Notifications: Disabled
            1 Match Bypassed:
Hits:
Matched Bytes:
                    5200 Matched Packets:
                      55
Precedence:
                   Access
 Source Interface:
Source Interface Type: S5U(1)
SDF Filter(s):
 No SDF filters present
                       0x8001
Local F-TEID:
Local F-TEID IP Addr:
 IPv4:
                      20.20.20.46
 IPv6:
                     N/A
Outer header removal: GTP-U/UDP/IPv4
Application ID: N/A
Associated FARID:
                     0x80000002
 Destination Interface: Core
 Apply Action: FORWARD
 Outer Header Creation:
 Remote TEID: 0x0
 Transport Level Marking:
                                N/A
 Transport Level Marking Options:
   Copy Inner:
   Copy Outer:
                                Nο
 Inner Packet Marking:
                                N/A
 Remote IP Address:
```

```
Remote Port:
                      N/A
                     2
Associated QERIDs:
 QER-IDs
                     Correlation-ID
  0x00000003
                             n/a
  0x00000001
                          0x0000000E
Associated URRIDs: 4

URR-IDs Parent URR-ID

0x00000011
                     0x80000002
  0x00000011
  0x00000027
                          n/a
  0x80000002
                           n/a
  0x80000009
                           n/a
 Activation Time:
Activation Time: N/A Deactivation Time: N/A
                      N/A
Bearer Level Info-id:
   50I:
                         5
   ARP:
                         20
   Charging Id:
                         4
PDR-ID:
                       0x0005
Rule Name:
                        ipv6rsradl
TDF App Id:
                       N/A
                      N/A
TDF Notifications:
Hits:
                        3 Match Bypassed:
                       312 Matched Packets:
Matched Bytes:
Precedence:
Source Interface: CP-function
Source Interface Type: N/A
 SDF Filter(s):
 No SDF filters present
Local F-TEID:
                     0x8000a001
Local F-TEID IP Addr:
 IPv4:
                      20.20.20.46
                     N/A
 IPv6:
 Outer header removal: GTP-U/UDP/IPv4
Application ID: N/A Associated FARID: 0x0003
 Destination Interface: Access
 Apply Action: FORWARD
 Outer Header Creation: GTP-U/UDP/IPv4
 Remote TEID: 0x3000000
 Transport Level Marking: N/A
 Transport Level Marking Options:
   Copy Inner:
                                No
   Copy Outer:
                                No
 Inner Packet Marking:
                                N/A
 Remote IP Address: 20.20.20.15
Remote Port:
                     N/A
Associated QERIDs: 1
                     Correlation-ID
 OER-IDs
  0x00000002
                               n/a
                     0
Associated URRIDs:
Activation Time:
                     N/A
Deactivation Time:
                     N/A
Bearer Level Info-id: N/A
PDR-ID:
                        0x0006
Rule Name:
                        ipv6rsraul
TDF App Id:
TDF Notifications:
                      N/A
                       0 Match Bypassed:
Hits:
                                                     0
Matched Bytes:
                        0 Matched Packets:
Precedence:
                        1
Source Interface: Access
 Source Interface Type: S5U(1)
```

```
SDF Filter(s):
 Filter 1
   Protocol:
                       ICMPV6
   Src IP Addr:
                     ANY
   Src Port:
                       ANY
   Dst IP Addr:
                       ff05::2/128
   Dst Port:
                       ANY
   SPI:
 Filter 2
                       ICMPV6
   Protocol:
   Src IP Addr:
                       ANY
   Src Port:
                       ANY
   Dst IP Addr:
                       ff02::2/128
   Dst Port:
                       ANY
   SPI:
                       Ω
 Filter 3
   Protocol:
                       ICMPV6
   Src IP Addr:
                       ANY
   Src Port:
                       ANY
                       ff01::2/128
   Dst IP Addr:
                       ANY
   Dst Port:
   SPI:
 Local F-TEID:
                       0x8001
Local F-TEID IP Addr:
 IPv4:
                      20.20.20.46
 IPv6:
                      N/A
Outer header removal: GTP-U/UDP/IPv4
 Application ID:
                       N/A
                       0x0004
Associated FARID:
 Destination Interface: CP-function
 Apply Action:
                      FORWARD
 Outer Header Creation: GTP-U/UDP/IPv4
 Remote TEID:
                       0x4
 Transport Level Marking:
 Transport Level Marking Options:
   Copy Inner:
   Copy Outer:
 Inner Packet Marking:
                                 N/A
 Remote IP Address:
                       20.20.20.3
 Remote Port:
                       N/A
Associated QERIDs:
Associated URRIDs:
                        0
Activation Time:
                       N/A
Deactivation Time:
                       N/A
Bearer Level Info-id: N/A
Total ADC PDRs found: 2
```

Total PDRs found:

show subscribers user-plane-only callid callid pdr full all