

# **Secondary RAT Usage Report in CDR Records**

- Revision History, on page 1
- Feature Description, on page 1
- Configuring Secondary RAT Usage Report through GTPP, on page 5
- Monitoring and Troubleshooting, on page 8

# **Revision History**

Revision Details	Release
Support for "Secondary RAT Usage Report in CDR Records" feature has been added in this release as well.	21.20.31
Support for "Secondary RAT Usage Report in CDR Records" feature has been added in this release as well.	21.26
First introduced	21.23.14

# **Feature Description**

Reporting issues pertaining to 5G RANSecondaryRATUsageReport occur due to lack of:

- Control in identifying whether the RANSecondaryRATUsageReport must be processed in CDRs or not. This allows the S-GW, P-GW, and SAEGW to either include these reports in the SGW-CDR or PGW- CDR or to simply ignore them.
- Number of available reports inside a CDR, if the control is active.
- Control in identifying whether Zero-volume reports must make it inside the CDR or not.

This results in billing loss of data. To overcome these reporting issues, you can trigger CLI controls using GTPP group configuration to:

• Allow the S-GW, P-GW, and SAEGW to either include the RANSecondary RAT Usage reports in the SGW-CDR or PGW-CDR or to simply ignore them.

• Identify the number of secondary RAT usage reports available inside the SGW-CDR or the PGW- CDR.

**Note** This limit must be in accordance with the system capability and ensure to consider the File-Format of the CDRs. If the configured limit exceeds, the system closes the SGW-CDR or PGW-CDR with the appropriate change-condition. For example, **max-change-condition** CDR is reused for further reports.

- Add or ignore Zero-volume reports inside the CDR.
- The CLI gtpp limit-secondary-rat-usage or hardcoded limit will be removed and the CLI gtpp limit-secondary-rat-usage is reused to control the number of records within the range 1-100.
- Provides logging when the CDR size reaches the maximum size. Through PGW-CDR counter, you can monitor the number of occurrences when the CDR exceeds its size limit.

# **Behavior Matrix**

The following table explains the new behavior of P-GW and S-GW for this feature.

CLI	P-GW	S-GW
	New Behavior	New Behavior
<b>gtpp attribute secondary-rat-usage</b> By default this CLI command is enabled in gtpp group.	P-GW sends secondary RAT usage records in CDR including zero volume records.	S-GW sends secondary RAT usage records in CDR including zero volume records.
[ no ] gtpp attribute secondary-rat-usage	P-GW does not send secondary RAT usage records in CDR.	S-GW does not send secondary RAT usage records in CDR.
<b>gtpp suppress-secondary-rat-usage</b> <b>zero-volume</b> By Default, this CLI command is disabled in gtpp group.	P-GW does not include and send zero volume secondary RAT records in CDR. P-GW sends only secondary RAT records that is having non-zero volumes.	S-GW does not include and send zero volume secondary RAT records in CDR. S-GW sends only secondary RAT records that is having non-zero volumes.
[ no ] gtpp suppress-secondary-rat-usage zero-volume	P-GW sends secondary RAT usage records including zero volume records in CDR.	S-GW sends secondary RAT usage records including zero volume records in CDR.

CLI		P-GW	S-GW	
		New Behavior	New Behavior	
<i>range_1–100.</i> If not configured, the default value is 32. By default this CLI command is enabled in gtpp		PGW generates CDR immediately when total received secondary RAT records exceeds 32 and reported cause value is <i>maximum</i> <i>change condition</i> .	S-GW generates CDR immediately when total received secondary RAT records exceeds 32 and the reported cause value is <i>maximum</i> <i>change condition</i> .	
Example: gtpp limit-secondary-rat-usage 32 Note This CLI is the		P-GW generates multiple CDRs if total received secondary RAT records are multiples of 32.	S-GW generates multiple CDRs if the total received secondary RAT records are multiples of 32.	
	modification of the exist CLI command <b>gtpp</b> <b>limit-secondary-rat-usa</b>	<b>Example</b> : If P-GW receives 100 RAT records between two triggers, <b>B</b> GW generates 3 CDRs and keeps <b>Othe remaining 4 RAT records for</b> the next CDR trigger.	<b>Example</b> : If S-GW receives 100 RAT records between two triggers, S-GW generates 3 CDRs and keeps the remaining 4 RAT records for the next CDR trigger.	
Example:gtpp limit-secondary-rat-usage 40		P-GW generates CDR immediately when total received secondary RAT records exceeds 40 and cause value is <i>maximum change</i> <i>condition</i> .	If the configured value is greater than 32 and sends 32 secondary RAT records in every CDR, Ignores <b>gtpp</b> <b>limit-secondary-rat-usage 40</b> CLI	
		P-GW generates multiple CDRs if total received secondary RAT records are multiples of 40.	command.	
		<b>Example</b> : If P-GW receives 100 RAT records between two triggers, it will generate 2 CDRs and will keep remaining 20 RAT records for the next CDR trigger.		
Example:gtpp limit-secondary-rat-usage 20		P-GW generates CDR immediately when total received secondary RAT records exceed 20 and cause value is <i>maximum change</i> <i>condition</i> .	S-GW generates CDR immediately when the total received secondary RAT records exceeds 20 and cause value is <i>maximum change</i> <i>condition.</i>	
		P-GW generates multiple CDRs if total received secondary RAT records are multiples of 20.	S-GW generates multiple CDRs if total received secondary RAT records are in multiples of 20.	
		<b>Example:</b> If P-GW receives 100 RAT records between two triggers, P-GW generates 2 CDRs and will store the remaining 20 RAT records for next CDR trigger.	<b>Example</b> : If S-GW receives 100 RAT records between two triggers, it will generate 5 CDRs.	

CLI	P-GW	S-GW	
	New Behavior	New Behavior	
[ no ] gtpp limit-secondary-rat-usage	Generates CDR immediately when the total received secondary RAT records exceed 255 and cause value is maximum change 	Ignores the [ no ] gtpp limit-secondary-rat-usage CLI and sends 32 secondary RAT records in every CDR. Behavior is similar to the gtpp limit-secondary-rat-usage 32 CLI implementation. Counter and debug logs are not required as it will never exceed the CDR size of 64k.	
	Service specific Unit Limit is sending in serviceConditionChange file	Record Closure	

# **Relationship to Other Features**

- Sessmgr Restart While Processing Secondary RAT Usage CDR Records in the *P-GW Administration Guide*.
- Secondary RAT Usage IE during GnGp handover, S-GW, and P-GW support of Secondary RAT Data Usage Report in Gz CDRs, see the 5G Non-Standalone chapter in the P-GW Administration Guide.
- P-GW support of Secondary RAT Data Usage Report in Rf CDRs, see the 5G Non-Standalone chapter in the P-GW Administration Guide.

# Limitations

This feature has the following limitations:

- Only 16 secondary RAT records per bearer are recovered for S-GW during session recovery. S-GW allows checkpointing of a maximum number of 16 secondary RAT records per bearer.
- A maximum of 142 secondary RAT records across all bearers is recovered for P-GW during session recovery. P-GW allows checkpointing of a maximum number of 142 secondary RAT records across all bearers.
- Anything beyond these numbers gets lost during session recovery.

# **Configuring Secondary RAT Usage Report through GTPP**

Use the following GTPP configurations to close Secondary RAT Usage CDR records before exceeding a buffer size.

# Enabling or Disabling the Secondary RAT Usage Report

Use the following configuration to enable or disable secondary RAT Usage report.

```
configure
  context context_name
   gtpp group group_name
   gtpp attribute secondary-rat-usage
    default gtpp attribute secondary-rat-usage
   no gtpp attribute secondary-rat-usage
   end
```

NOTES:

- gtpp attribute secondary-rat-usage: Sends an optional attribute Secondary RAT usage records.
- default gtpp attribute secondary-rat-usage: Sends an optional attribute Secondary RAT usage records by default.
- no gtpp attribute secondary-rat-usage: Does not send the optional attribute Secondary RAT usage records.

# **Controlling the Maximum Number of Entries**

When the Secondary RAT usage record reaches the maximum configured value within a CDR, the CDR closure cause occurs and uses **maxChangeCond**. The **gtpp limit-secondary-RAT-usage** CLI command controls the maximum number of Secondary RAT usage record entries in the P-GW and S-GW CDRs. If the limit is configured with a value more than 32, the partial CDRs get generated with a maximum of 32 for S-GW CDR.



Note

The existing behaviour of S-GW has a limit of 32 Secondary RAT Usage records.

The following table explains the behavior of Secondary RAT records and CDR, and the maximum limit.

SI. Number	CDR Type	Configured limit- secondary-rat-usage	Effective Maximum Limit	No. of Secondary RAT records Sent by UE	Behavior of Secondary RAT Records and CDR
1	P-GW	Less than 32 Example: 20	20	35	Partial CDR is generated with 20 secondary RAT records.
					Remaining 15 secondary RAT records sent in the next trigger.
	S-GW Less than 32 20 Example: 20	35	Partial CDR is generated with 20 Secondary RAT records.		
				Remaining 15 Secondary RAT records sent in the next trigger.	
2	P-GW 32 32	35	Partial CDR is generated with 32 Secondary RAT records.		
					Remaining 3 secondary RAT records sent in the next trigger.
	S-GW 32 32	32	35	Partial CDR is generated with 32 secondary RAT records.	
				Remaining 3 secondary RAT records sent in the next trigger.	

SI. Number	CDR Type	Configured limit- secondary-rat-usage	Effective Maximum Limit	No. of Secondary RAT records Sent by UE	Behavior of Secondary RAT Records and CDR
3	P-GW	Greater than 32 Example: 100	100	100	Partial CDR is generated with 100 secondary RAT records.
	S-GW	Greater than 32 Example: 100	32	100	Three partial CDRs are generated with 32 secondary RAT records each. Remaining 4 secondary RAT records sent in the next trigger.
4	P-GW	Not configured	255 1000	1000	Three partial CDRs are generated with 255 secondary RAT records each.
					Remaining reported Secondary RAT records become a part of CDR in the next trigger.
	S-GW	Not configured	32	1000	No partial CDR is generated.
					32 Secondary RAT records become part of the CDR in the next trigger.

Use the following configuration to control the maximum number of entries.

```
configure
context context_name
gtpp group group_name
gtpp limit-secondary-rat-usage usage_limit
default gtpp limit-secondary-rat-usage
```

```
no gtpp limit-secondary-rat-usage end
```

#### NOTES:

• gtpp limit-secondary-rat-usage *usage\_limit*: Enter a maximum number of secondary RAT reports. *usage\_limit* must be an integer in the range of 1-100. The recommended value for S-GW CDR is 32.

For example, if the limit is set to 10, then the CDR is generated once the configured value is reached.

- default gtpp limit-secondary-rat-usage: Specifies a default value of 32.
- **no gtpp limit-secondary-rat-usage**: Disables the CDR generation with limited number of secondary RAT usage information.

## Suppressing Zero-Volume Secondary RAT Usage Report

Use the following configuration to suppress zero-volume Secondary RAT Usage report.

```
configure
context context_name
gtpp group group_name
gtpp suppress-secondary-rat-usage zero-volume
default gtpp suppress-secondary-rat-usage zero-volume
no gtpp suppress-secondary-rat-usage zero-volume
end
```

#### NOTES:

- gtpp suppress-secondary-rat-usage zero-volume: Suppresses either Secondary RAT records or zero volume Secondary RAT records.
- **default gtpp suppress-secondary-rat-usage zero-volume**: Does not suppress the zero volume secondary RAT usage records.
- no gtpp suppress-secondary-rat-usage zero-volume: Does not suppress the zero volume Secondary RAT usage records.

# Monitoring and Troubleshooting

This section provides information on how to monitor and troubleshoot using show commands available in support of this feature.

## Show Commands and Outputs

This section provides information regarding show commands and their outputs for this feature.

#### show config

The output of this CLI command displays the following parameters.

Field	Description
gtpp attribute secondary-rat-usage	Specify this option to include the Secondary RAT reports field in the CDR.
gtpp suppress-secondary-rat-usage zero-volume	Enables the exclusion of the zero volume Secondary RAT reports in the CDR.
gtpp limit-secondary-rat-usage	Enables limiting the number of Secondary RAT Usage reports in CDR with the configured value.

### show config verbose

The output of this CLI command displays the following parameters.

Field	Description
gtpp attribute secondary-rat-usage	Displays the Secondary RAT usage records.
gtpp suppress-secondary-rat-usage zero-volume	Displays only Secondary RAT records that is having non-zero volumes from P-GW and S-GW.
gtpp limit-secondary-rat-usage	If total received Secondary RAT records are multiples of 10, displays multiple CDR generated by P-GW and S-GW. The reported cause value will be the maximum change condition.
no gtpp limit-secondary-rat-usage	Displays Secondary RAT records for unconfigured cause.

### show gtpp group

The output of this CLI command displays the following parameters.

Field	Description
Secondary RAT records present	Specifies whether the Secondary RAT record is present or not. The available options are: • no • yes
Limit-secondary-rat-usage	Specifies a limit for Secondary RAT usage report.

### show gtpp statistics group

The output of this CLI command displays the following parameter.

Field	Description
	Displays the total number of CDRs that exceeded size limit in P-GW.