



APPENDIX

A

Technical Specifications

This appendix provides technical specifications for the Cisco Aironet 350 Series Wireless LAN Client Adapters.

The following topics are covered in this appendix:

- Physical Specifications, [page A-2](#)
- Radio Specifications, [page A-3](#)
- Power Specifications, [page A-4](#)
- Safety and Regulatory Compliance Specifications, [page A-4](#)

Table A-1 lists the technical specifications for the Cisco Aironet 350 Series Wireless LAN Client Adapters.



- Note** If a distinction is not made between client adapter type, the specification applies to both 350 series PC and LM cards.

Table A-1 Technical Specifications for the 350 Series Client Adapters

Physical Specifications

Size

PC card	4.5 in. L x 2.1 in. W x 0.2 in. H (11.3 cm L x 5.4 cm W x 0.5 cm H)
LM card	3.4 in. L x 2.1 in. W x 0.2 in. H (8.6 cm L x 5.4 cm W x 0.5 cm H)
Weight	1.3 oz (0.037 kg)

Enclosure

PC card	Extended Type II PC card
LM card	Standard Type II PC card with RF connectors
Connector	68-pin PCMCIA
Status indicators	Green and amber LEDs; see Chapter 9
Operating temperature	-22°F to 158°F (-30°C to 70°C)
Storage temperature	-40°F to 185°F (-40°C to 85°C)
Humidity (non-operational)	95% relative humidity
Altitude	Operational 9843 ft (3000 m) @ room temperature for 2 hours Non-operational 15,000 ft (4572 m) @ room temperature for 20 hours
ESD	15 kV (human body model)

Table A-1 Technical Specifications for the 350 Series Client Adapters (continued)

Radio Specifications	
Type	Direct-sequence spread spectrum (DSSS) IEEE 802.11b compliant
Power output	100 mW (20 dBm) 50 mW (17 dBm) 30 mW (15 dBm) 20 mW (13 dBm) 5 mW (7 dBm) 1 mW (0 dBm)
	<p>Note Refer to Appendix D for limitations on radiated power (EIRP) levels in the European community and other countries.</p> <p>Note If you are using an older version of a 350 series client adapter, your power level options may be different than those listed here.</p>
Operating frequency	2.400 to 2.497 GHz (depending on the regulatory domain in which the client adapter is used)
Usable channels	2412 to 2484 MHz in 5-MHz increments
Interference rejection	-35 dB adjacent channel rejection
Data rates	1, 2, 5.5, and 11 Mbps
Modulation	Binary phase shift keying (BPSK) - 1 Mbps Quaternary phase shift keying (QPSK) - 2 Mbps Complementary code keying (CCK) - 5.5 and 11 Mbps
Receiver sensitivity	-94 dBm @ 1 Mbps -91 dBm @ 2 Mbps -89 dBm @ 5.5 Mbps -85 dBm @ 11 Mbps
Receiver delay spread (multipath)	500 ns @ 1 Mbps 400 ns @ 2 Mbps 300 ns @ 5.5 Mbps 140 ns @ 11 Mbps

Table A-1 Technical Specifications for the 350 Series Client Adapters (continued)

Range	Outdoor 2000 ft (609.6 m) @ 1 Mbps 1500 ft (457.2 m) @ 2 Mbps 1000 ft (304.8 m) @ 5.5 Mbps 800 ft (243.8 m) @ 11 Mbps
	Indoor 350 ft (106.7 m) @ 1 Mbps 250 ft (76.2 m) @ 2 Mbps 200 ft (61 m) @ 5.5 Mbps 150 ft (45.7 m) @ 11 Mbps
Note The above range numbers assume the use of a snap-on antenna with the LM card.	
Antenna	
PC card	Integrated diversity antenna
LM card	Two MMCX antenna connectors
Power Specifications	
Operational voltage	5.0 V (± 0.25 V)
Receive current steady state	Typically 250 mA
Transmit current steady state	Typically 450 mA @ 20 dBm
Sleep mode steady state	Typically 15 mA
Safety and Regulatory Compliance Specifications	
Safety	Designed to meet: <ul style="list-style-type: none">• UL 1950 Third Ed.• CSA 22.2 No. 950-95• IEC 60950 Second Ed., including Amendments 1-4 with all deviations• EN 60950 Second Ed., including Amendments 1-4
EMI and susceptibility	FCC Part 15.107 & 15.109 Class B ICES-003 Class B (Canada) EN 55022 B AS/NZS 3548 Class B VCCI Class B EN 55024
Radio approvals	FCC Part 15.247 Canada RSS-139-1, RSS-210 Japan Telec 33B EN 300.328
RF exposure	OET-65C RSS-102 ANSI C95.1