



# APPENDIX **B**

## Distribution Package Examples

---

Following are examples of valid .xml distribution package files from typical enterprise environments. The file listings are augmented with crossreferences to the features indicated in the high-level descriptions. The file, `sscAdminGuideExXml.zip`, also distributed in the `SSCAdminUtils` zip file, contains all of these examples as individual .xml files, for a convenient starting point and easy text editing.

**Note**

---

In all of the examples, the license string is functionally invalid. Replace with one appropriate to your application.

---

### High-level Descriptions

- Example B-1—Illustrates only the base elements of a distribution package. No networks are defined in this example. (Use [Example B-1](#).)
- Example B-2—illustrates the addition of minimal, nonauthenticating, open (1) Wi-Fi and (2) wired networks. (Use [Example B-2](#).)
- Example B-3—Illustrates (1) a nonauthenticating, WPA personal Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) WPA-Personal association with TKIP encryption

Such a network would be applicable to any corporate-supplied home equipment (where you configure the key) that your end-user might have for connecting to your enterprise network remotely. (Use [Example B-3](#).)

**Note**

---

Any of the following authenticating Wi-Fi network definitions can be extracted and used in a wired authenticating network by removing the `associationMode` element. Extract the following:

```
<authenticationNetwork>  
  Retain otherwise: .....  
  Remove this: <associationMode>...</associationMode>  
</authenticationNetwork>
```

---

- Example B-4—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) machine/user connection context

- (3) user password credentials obtained from an initial, one-time prompt
- (4) machine password obtained automatically from the MS Active Directory setup
- (5) single, tunneled EAP method
- (6) server certificated validation based on release 4.0 functionality

(Use [Example B-4.](#))

- Example B-5—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) machine/user connection context
  - (3) user password credentials obtained from the operating system (single-signon)
  - (4) machine credential obtained automatically from the MS Active Directory setup
  - (5) multiple, tunneled EAP methods
  - (6) server certificate validation based on multiple authentication server rules and release 4.1 (7) CA certificate deployment support

(Use [Example B-5.](#))

- Example B-6—Illustrates (1) an authenticating, Wi-Fi network with the following properties:
  - Novell domain compatible network
  - (2) user connection context
  - (3) user password credentials obtained from the OS (single-signon)
  - (4) single, tunneled EAP method
  - (5) server certificate validation based on release 4.0 functionality

(Use [Example B-6.](#))

- Example B-7—Illustrates (1) an authenticating, Wi-Fi network with the following properties:
  - (2) machine connection context
  - (3) machine credentials obtained from release 4.1 static credential support
  - (4) single, tunneled EAP method
  - (5) server certificate validation based on release 4.0 functionality

(Use [Example B-7.](#))

- Example B-8—Illustrates (1) an authenticating, Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) user client certificate credentials obtained from a smartcard
  - (4) TLS EAP method
  - (5) server certificate validation based on release 4.0 functionality

(Use [Example B-8.](#))

- Example B-9a—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) user password credentials obtained from an initial, one-time prompt
  - (4) EAP-FAST-GTC method (autonomous, authenticated PAC provisioning)
  - (5) server certificate validation for PAC provisioning based on release 4.0 functionality

(Use [Example B-9a.](#))

- Example B-9b—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) user password credentials obtained from an initial, one-time prompt
  - (4) EAP-FAST-GTC method (autonomous, unauthenticated PAC provisioning)
  - (5) server AID validation for PAC provisioning based on release 4.0 functionality
 (Use [Example B-9b](#).)
- Example B-9c—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) user password credentials obtained from an initial, one-time prompt
  - (4) FAST EAP-MSCHAPv2 method with release 4.1 manual PAC provisioning support (Cisco ACS server configured for no autonomous PAC provisioning.)
  - (5) no server validation
 (Use [Example B-9c](#).)
- Example B-10—Illustrates (1) an authenticating Wi-Fi network with the following properties:
  - (2) user connection context
  - (3) user password credentials obtained from new release 4.1 static credential support
  - (4) single, tunneled EAP method
  - (5) server certificate validation based on release 4.0 functionality
 (Use [Example B-10](#).)
- Example B-11—Illustrates (1) a wired-only version with the following properties:
  - (2) preset end-user version
  - (3) authenticating network only
  - (4) machine and user connection context
  - (5) FAST EAP method only
  - (6) server certificate validation
 (Use [Example B-11](#).)

## File Listings

### Example B-1

```
<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
    </allowedAssociationModes>
  </networkPolicy>
</configuration>
```

```

    <wpa2-Enterprise/>
    <!--legacy WEP shared key and authenticating networks-->
    <wep/>
</allowedAssociationModes>
<allowedEapMethods>
    <!--wired only-->
    <eapMd5/>
    <eapMschapv2/>
    <eapGtc/>
    <!--wired or wireless-->
    <eapFast/>
    <eapPeap/>
    <eapTls/>
    <eapTtls/>
    <leap/>
</allowedEapMethods>
<serverValidationPolicy>
    <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
    </alwaysValidate>
</serverValidationPolicy>
<allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
<allowedCredentialStorage>
    <forever/>
    <logonSession/>
    <duration>5</duration>
</allowedCredentialStorage>
<allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
<allowPublicProfileCreation>false</allowPublicProfileCreation>
<allowedClientCertificates>
    <noEkuFilter/>
</allowedClientCertificates>
</networkPolicy>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

## Example B-2

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    (2) <wiredNetwork>
      <displayName>My Corporate Wired Network</displayName>
      <openNetworkMachineConnection/>
    </wiredNetwork>
    (1) <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <openNetworkUserConnection>
        <autoConnect>true</autoConnect>
      </openNetworkUserConnection>
    </wifiNetwork>
  </networks>

```

```
</networks>
<connectionSettings>
  <simultaneousConnections>singleHomed</simultaneousConnections>
  <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
  <clientUIType>configurable</clientUIType>
  <allowLicensing>>false</allowLicensing>
  <allowedMedia>
    <wired/>
    <wifi/>
  </allowedMedia>
</userControlPolicy>
</configuration>
```

## Example B-3

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <sharedKeyNetwork>
        <userConnection>
          <keySettings>
            <wpa>
              <key>
                <ascii encrypt="true">mySecret</ascii>
              </key>
              <encryption>TKIP</encryption>
            </wpa>
          </keySettings>
        </userConnection>
      </sharedKeyNetwork>
    </wifiNetwork>
  </networks>

```

(1)

(2)

(3)

```
        </wpa>
      </keySettings>
      <autoConnect>true</autoConnect>
    </userConnection>
  </sharedKeyNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
  <simultaneousConnections>singleHomed</simultaneousConnections>
  <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
  <clientUIType>configurable</clientUIType>
  <allowLicensing>>false</allowLicensing>
  <allowedMedia>
    <wired/>
    <wifi/>
  </allowedMedia>
</userControlPolicy>
</configuration>
```

## Example B-4

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <machineUserAuthentication>
          <machine>
            <collectionMethod>
              <auto/>
            </collectionMethod>
            <useAnonymousId>true</useAnonymousId>
          </machine>
        </machineUserAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

    <user>
      <autoConnect>
        <connectBeforeLogon>true</connectBeforeLogon>
      </autoConnect>
      <collectionMethod>
(3)      <prompt>
          <credentialsStorage>
            <forever/>
          </credentialsStorage>
        </prompt>
      </collectionMethod>
      <useAnonymousId>true</useAnonymousId>
    </user>
    <eapMethods>
(5)      <eapFast>
(6)      <validateServerIdentity>true</validateServerIdentity>
          <enableFastReconnect>true</enableFastReconnect>
          <protectClientCertificate>true</protectClientCertificate>
          <innerEapMethods>
            <eapMschapv2/>
            <eapGtc/>
          </innerEapMethods>
        </eapFast>
      </eapMethods>
    </machineUserAuthentication>
    <serverValidation>
(6)      <validationRules>
          <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>
          <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
        </validationRules>
        <trustAnyRootCaFromOs/>
      </serverValidation>
      <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
      <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
      <associationMode>
        <wpa-Enterprise>TKIP</wpa-Enterprise>
      </associationMode>
    </authenticationNetwork>
  </wifiNetwork>
</networks>
<connectionSettings>
  <simultaneousConnections>singleHomed</simultaneousConnections>
  <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
  <clientUIType>configurable</clientUIType>
  <allowLicensing>false</allowLicensing>
  <allowedMedia>
    <wired/>
    <wifi/>
  </allowedMedia>
</userControlPolicy>
</configuration>

```

## Example B-5

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      (5) <eapFast/>
      (5) <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      (6) <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    (1) <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      (1) <authenticationNetwork>
        (2) <machineUserAuthentication>
          <machine>
            <collectionMethod>
              (4) <auto/>
            </collectionMethod>
            <useAnonymousId>true</useAnonymousId>
          </machine>
        </machineUserAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

<user>
  <autoConnect>
    <connectBeforeLogon>true</connectBeforeLogon>
  </autoConnect>
  <collectionMethod>
    <singleSignOn/>
  </collectionMethod>
  <useAnonymousId>true</useAnonymousId>
</user>
<eapMethods>
  <eapFast>
    <validateServerIdentity>true</validateServerIdentity>
    <enableFastReconnect>true</enableFastReconnect>
    <protectClientCertificate>true</protectClientCertificate>
    <innerEapMethods>
      <eapMschapv2/>
      <eapGtc/>
    </innerEapMethods>
  </eapFast>
  <eapPeap>
    <validateServerIdentity>true</validateServerIdentity>
    <enableFastReconnect>true</enableFastReconnect>
    <protectClientCertificate>false</protectClientCertificate>
    <innerEapMethods>
      <eapMschapv2/>
      <eapGtc/>
    </innerEapMethods>
  </eapPeap>
</eapMethods>
</machineUserAuthentication>
<serverValidation>
  <validationRules>
    <matchSubjectAlternativeName name="Cert Rule 1"
(3) match="endsWith">myCorp.com</matchSubjectAlternativeName>
    <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
    <matchSubjectAlternativeName name="Cert Rule 3"
(5) match="endsWith">myCorp2.net</matchSubjectAlternativeName>
  </validationRules>
  <trustedRootCACerts>
    <certificate>
(6) <caReference>E:\path\CaCertFile</caReference>
    </certificate>
  </trustedRootCACerts>
</serverValidation>
<interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
<nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
<associationMode>
  <wpa-Enterprise>TKIP</wpa-Enterprise>
</associationMode>
</authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
  <simultaneousConnections>singleHomed</simultaneousConnections>
  <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
  <clientUIType>configurable</clientUIType>
  <allowLicensing>false</allowLicensing>
  <allowedMedia>
    <wired/>
    <wifi/>
  </allowedMedia>

```

```
</userControlPolicy>  
</configuration>
```

## Example B-6

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>true</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <singleSignOn/>
          </collectionMethod>
        </userAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

        <useAnonymousId>true</useAnonymousId>
        <eapMethods>
(4)         <eapFast>
(5)             <validateServerIdentity>true</validateServerIdentity>
                <enableFastReconnect>true</enableFastReconnect>
                <protectClientCertificate>true</protectClientCertificate>
                <innerEapMethods>
                    <eapMschapv2/>
                    <eapGtc/>
                </innerEapMethods>
            </eapFast>
        </eapMethods>
    </userAuthentication>
    <serverValidation>
(5)         <validationRules>
                <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>
                <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
            </validationRules>
            <trustAnyRootCaFromOs/>
        </serverValidation>
        <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
        <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
        <associationMode>
            <wpa-Enterprise>TKIP</wpa-Enterprise>
        </associationMode>
    </authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

**Example B-7**

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <machineAuthentication>
          <collectionMethod>
            <static/>
          </collectionMethod>
          <useAnonymousId>true</useAnonymousId>
          <staticIdentity encrypt="true">machineName</staticIdentity>
          <staticPassword encrypt="true">machineSecret</staticPassword>
        </machineAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

(4)      <eapMethods>
          <eapPeap>
            <validateServerIdentity>true</validateServerIdentity>
            <enableFastReconnect>true</enableFastReconnect>
            <protectClientCertificate>true</protectClientCertificate>
            <innerEapMethods>
              <eapMschapv2/>
            </innerEapMethods>
          </eapPeap>
        </eapMethods>
      </machineAuthentication>
    <serverValidation>
      <validationRules>
        <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>
      </validationRules>
      <trustAnyRootCaFromOs/>
    </serverValidation>
    <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
    <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
    <associationMode>
      <wpa-Enterprise>TKIP</wpa-Enterprise>
    </associationMode>
  </authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
  <simultaneousConnections>singleHomed</simultaneousConnections>
  <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
  <clientUIType>configurable</clientUIType>
  <allowLicensing>false</allowLicensing>
  <allowedMedia>
    <wired/>
    <wifi/>
  </allowedMedia>
</userControlPolicy>
</configuration>

```

## Example B-8

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>>false</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <prompt>
              <credentialsStorage>

```

```

(3)         <logonSession/>
            </credentialsStorage>
        </prompt>
    </collectionMethod>
    <useAnonymousId>>false</useAnonymousId>
    <eapMethods>
(4)         <eapFast>
(5)             <validateServerIdentity>>true</validateServerIdentity>
                <enableFastReconnect>>true</enableFastReconnect>
                <protectClientCertificate>>true</protectClientCertificate>
                <certificateSource>
(3)                 <smartCardOnlyCertificate/>
                </certificateSource>
                <innerEapMethods>
(4)                 <eapTls>
                    <validateServerIdentity>>true</validateServerIdentity>
                </eapTls>
                </innerEapMethods>
            </eapFast>
        </eapMethods>
    </userAuthentication>
    <serverValidation>
(5)         <validationRules>
            <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
            </validationRules>
            <trustAnyRootCaFromOs/>
        </serverValidation>
        <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
        <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
        <associationMode>
            <wpa-Enterprise>TKIP</wpa-Enterprise>
        </associationMode>
    </authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

**Example B-9a**

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>>false</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <prompt>
              <credentialsStorage>

```

```

        <forever/>
        </credentialsStorage>
    </prompt>
</collectionMethod>
<useAnonymousId>true</useAnonymousId>
<eapMethods>
(4)     <eapFast>
(5)         <validateServerIdentity>true</validateServerIdentity>
            <enableFastReconnect>true</enableFastReconnect>
            <protectClientCertificate>true</protectClientCertificate>
            <innerEapMethods>
(4)         <eapGtc/>
            </innerEapMethods>
        </eapFast>
    </eapMethods>
</userAuthentication>
<serverValidation>
(5)     <validationRules>
            <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>
            <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
        </validationRules>
        <trustAnyRootCaFromOs/>
    </serverValidation>
    <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
    <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
    <associationMode>
        <wpa-Enterprise>TKIP</wpa-Enterprise>
    </associationMode>
</authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

**Example B-9b**

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>>false</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <prompt>
              <credentialsStorage>

```

```

        <forever/>
        </credentialsStorage>
    </prompt>
</collectionMethod>
<useAnonymousId>true</useAnonymousId>
<eapMethods>
(4)     <eapFast>
(5)         <validateServerIdentity>true</validateServerIdentity>
            <enableFastReconnect>true</enableFastReconnect>
            <protectClientCertificate>true</protectClientCertificate>
            <innerEapMethods>
(4)                 <eapMschapv2/>
(4)                 <eapGtc/>
            </innerEapMethods>
        </eapFast>
    </eapMethods>
</userAuthentication>
<serverValidation>
(5)     <trustedServerIds>
            <trustedServerId name="PAC AID Rule 1">
                <reference>
                    <aIdReference>E:\path\pacRefFile</aIdReference>
                    <secretKey>1234</secretKey>
                </reference>
            </trustedServerId>
        </trustedServerIds>
        <trustAnyRootCaFromOs/>
    </serverValidation>
    <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
    <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
    <associationMode>
        <wpa-Enterprise>TKIP</wpa-Enterprise>
    </associationMode>
</authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

**Example B-9c**

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <allowUserValidationControl/>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>false</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <prompt>
              <credentialsStorage>
                <forever/>
              </credentialsStorage>
            </prompt>
          </collectionMethod>
        </userAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

        </prompt>
    </collectionMethod>
    <useAnonymousId>true</useAnonymousId>
(4)    <pacs>
        <pac>
            <pacReference encrypt="true">E:\path\pacFile</pacReference>
            <secretKey encrypt="true">pacPassword</secretKey>
        </pac>
    </pacs>
    <eapMethods>
(4)    <eapFast>
(5)    <validateServerIdentity>>false</validateServerIdentity>
        <enableFastReconnect>true</enableFastReconnect>
        <protectClientCertificate>true</protectClientCertificate>
        <innerEapMethods>
(4)    <eapMschapv2/>
        </innerEapMethods>
    </eapFast>
    </eapMethods>
    </userAuthentication>
    <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
    <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
    <associationMode>
        <wpa-Enterprise>TKIP</wpa-Enterprise>
    </associationMode>
    </authenticationNetwork>
</wifiNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>true</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
    <clientUIType>configurable</clientUIType>
    <allowLicensing>>false</allowLicensing>
    <allowedMedia>
        <wired/>
        <wifi/>
    </allowedMedia>
</userControlPolicy>
</configuration>

```

**Example B-10**

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes>
      <!--open network-->
      <open/>
      <!--shared key network-->
      <wpa-Personal/>
      <wpa2-Personal/>
      <!--authenticating network-->
      <wpa-Enterprise/>
      <wpa2-Enterprise/>
      <!--legacy WEP shared key and authenticating networks-->
      <wep/>
    </allowedAssociationModes>
    <allowedEapMethods>
      <!--wired only-->
      <eapMd5/>
      <eapMschapv2/>
      <eapGtc/>
      <!--wired or wireless-->
      <eapFast/>
      <eapPeap/>
      <eapTls/>
      <eapTtls/>
      <leap/>
    </allowedEapMethods>
    <serverValidationPolicy>
      <alwaysValidate>
        <allowUserTrustedServers>true</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
      <duration>5</duration>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
    <wifiNetwork>
      <displayName>My Corporate Wi-Fi Network</displayName>
      <ssid>MyCorpNet</ssid>
      <associationRetries>3</associationRetries>
      <beaconing>true</beaconing>
      <authenticationNetwork>
        <userAuthentication>
          <autoConnect>
            <connectBeforeLogon>>false</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <static/>
          </collectionMethod>
        </userAuthentication>
      </authenticationNetwork>
    </wifiNetwork>
  </networks>

```

```

(3)         <useAnonymousId>true</useAnonymousId>
(3)         <staticIdentity encrypt="true">userName</staticIdentity>
(3)         <staticPassword encrypt="true">userSecret</staticPassword>
(4)         <eapMethods>
(4)             <eapFast>
(5)                 <validateServerIdentity>true</validateServerIdentity>
(5)                 <enableFastReconnect>true</enableFastReconnect>
(5)                 <protectClientCertificate>true</protectClientCertificate>
(5)                 <innerEapMethods>
(5)                     <eapMschapv2/>
(5)                 </innerEapMethods>
(5)             </eapFast>
(5)         </eapMethods>
(5)     </userAuthentication>
(5)     <serverValidation>
(5)         <validationRules>
(5)             <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>
(5)             <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
(5)         </validationRules>
(5)         <trustAnyRootCaFromOs/>
(5)     </serverValidation>
(5)     <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
(5)     <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
(5)     <associationMode>
(5)         <wpa-Enterprise>TKIP</wpa-Enterprise>
(5)     </associationMode>
(5) </authenticationNetwork>
(5) </wifiNetwork>
(5) </networks>
(5) <connectionSettings>
(5)     <simultaneousConnections>singleHomed</simultaneousConnections>
(5)     <validateWpaHandshake>true</validateWpaHandshake>
(5) </connectionSettings>
(5) <userControlPolicy>
(5)     <clientUIType>configurable</clientUIType>
(5)     <allowLicensing>false</allowLicensing>
(5)     <allowedMedia>
(5)         <wired/>
(5)         <wifi/>
(5)     </allowedMedia>
(5) </userControlPolicy>
</configuration>

```

## Example B-11

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="..\distributionPackage.xsd" major_version="4" minor_version="1"
maintenance_version="2">
<license>T244-YKGP-UMG5-Y2F2-5KMH-5OYX-DAR4-POND-52Z5-MHJZ-3LOD-SLYL-U5YA-IUKU-M3TC-JNO7-3MEM-LGAA</license>
  <networkPolicy>
    <allowedAssociationModes></allowedAssociationModes>
    <allowedEapMethods>
(5)     <eapFast/>
    </allowedEapMethods>
    <serverValidationPolicy>
(6)     <alwaysValidate>
        <allowUserTrustedServers>>false</allowUserTrustedServers>
      </alwaysValidate>
    </serverValidationPolicy>
    <allowUserSimultaneousConnectionsControl>>false</allowUserSimultaneousConnectionsControl>
    <allowedCredentialStorage>
      <forever/>
      <logonSession/>
    </allowedCredentialStorage>
    <allowUserWpaHandshakeValidationControl>>false</allowUserWpaHandshakeValidationControl>
    <allowPublicProfileCreation>>false</allowPublicProfileCreation>
    <allowedClientCertificates>
      <noEkuFilter/>
    </allowedClientCertificates>
  </networkPolicy>
  <networks>
(1)    <wiredNetwork>
      <displayName>My Corporate Wired Network</displayName>
(3)    <authenticationNetwork>
(4)    <machineUserAuthentication>
        <machine>
          <collectionMethod>
            <auto/>
          </collectionMethod>
          <useAnonymousId>>true</useAnonymousId>
        </machine>
        <user>
          <autoConnect>
            <connectBeforeLogon>>true</connectBeforeLogon>
          </autoConnect>
          <collectionMethod>
            <singleSignOn/>
          </collectionMethod>
          <useAnonymousId>>true</useAnonymousId>
        </user>
        <eapMethods>
(5)    <eapFast>
(6)    <validateServerIdentity>>true</validateServerIdentity>
        <enableFastReconnect>>true</enableFastReconnect>
        <protectClientCertificate>>true</protectClientCertificate>
        <innerEapMethods>
          <eapMschapv2/>
        </innerEapMethods>
        </eapFast>
      </eapMethods>
    </machineUserAuthentication>
    <serverValidation>
(6)    <validationRules>
        <matchSubjectAlternativeName name="Cert Rule 1"
match="endsWith">myCorp.com</matchSubjectAlternativeName>

```

```
        <matchSubjectName name="Cert Rule 2" match="exactly">My
Corporation</matchSubjectName>
        </validationRules>
        <trustAnyRootCaFromOs/>
    </serverValidation>
    <interactiveAuthenticationRetries>4</interactiveAuthenticationRetries>
    <nonInteractiveAuthenticationRetries>4</nonInteractiveAuthenticationRetries>
    </authenticationNetwork>
</wiredNetwork>
</networks>
<connectionSettings>
    <simultaneousConnections>singleHomed</simultaneousConnections>
    <validateWpaHandshake>false</validateWpaHandshake>
</connectionSettings>
<userControlPolicy>
(2)    <clientUIType>preset</clientUIType>
        <allowLicensing>false</allowLicensing>
(1)    <allowedMedia>
        <wired/>
        </allowedMedia>
    </userControlPolicy>
</configuration>
```

