

Ejemplo de configuración del BGP Prefix-Based Outbound Route Filtering del IPv6

Contenido

[Introducción](#)

[prerrequisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenciones](#)

[Configurar](#)

[Diagrama de la red](#)

[Configuraciones de Ejemplo](#)

[Escenario 1: Rutas de filtro basadas en la lista de prefijo con las expresiones](#)

[Verificación](#)

[Verifique el BGP Prefix-Based Outbound Route Filtering del IPv6 configurado en el modo de envío](#)

[Verifique el BGP Prefix-Based Outbound Route Filtering del IPv6 configurado adentro reciben el modo](#)

[Verifique el escenario 1: Rutas de filtro basadas en la lista de prefijo con las expresiones](#)

[Información Relacionada](#)

[Introducción](#)

Este documento proporciona una configuración de muestra usando el IPv6 que le ayude a configurar el BGP Prefix-Based Outbound Route Filtering. Esta característica utiliza el filtro de la ruta de salida BGP (ORF) envía y recibe las capacidades que minimizan el número de actualizaciones de BGP enviadas entre el Routers del par. La configuración de esta característica puede ayudar en la filtración hacia fuera de las actualizaciones de ruteo indeseadas en la fuente.

[prerrequisitos](#)

[Requisitos](#)

Asegurese que usted cumple estos requisitos antes de que usted intente esta configuración:

- Tenga una comprensión del Routing Protocol BGP y de su operación
- Tenga una comprensión del esquema de direccionamiento del IPv6

[Componentes Utilizados](#)

Este documento no tiene restricciones específicas en cuanto a versiones de software y de hardware.

Las configuraciones en este documento se basan en el Cisco 7200 Series Router con la versión del Cisco IOS ® Software 15.0(1).

[Convenciones](#)

Consulte [Convenciones de Consejos TécnicosCisco](#) para obtener más información sobre las convenciones del documento.

[Configurar](#)

En este ejemplo, el r1 del router es hacer publicidad-prefijo configurado basado ORF envía las capacidades al r2 del router. En el router del otro extremo el r2 se configura para hacer publicidad del ORF basado en prefijo recibe las capacidades al r1 del router. Antes de que la característica del BGP Prefix-Based Outbound Route Filtering se pueda habilitar para enviar o para recibir los avisos basados en prefijo ORF, las sesiones de peer BGP deben ser en servicio y las capacidades BGP ORF se deben habilitar en cada router participante antes de un router.

Este documento utiliza el comando del prefijo-[filtro orf del vecino](#) para habilitar la capacidad de la lista de prefijos ORF en el router. Este comando fue introducido en el Cisco IOS Software Release 12.0(11)ST.

Nota: Utilice la [herramienta de búsqueda de comandos \(clientes registrados solamente\)](#) para encontrar más información sobre los comandos usados en este documento.

[Diagrama de la red](#)

En este documento, se utiliza esta configuración de red:

[Configuraciones de Ejemplo](#)

En este documento, se utilizan estas configuraciones:

- [R1 del router](#)
- [R2 del router](#)

R1 del router

```
!  
hostname R1  
!  
ipv6 unicast-routing  
ipv6 cef  
!  
!  
interface Loopback1  
  no ip address  
  ipv6 address 1111::1/128  
!  
!  
interface Loopback2  
  no ip address  
  ipv6 address 2222::1/128  
!  
!
```

```
interface Serial1/0
  no ip address
  ipv6 address 2011:11:11:11::1/64
  serial restart-delay 0
!
!
router bgp 6501
  no synchronization
  no bgp default ipv4-unicast
  bgp router-id 1.1.1.1
  bgp log-neighbor-changes
  neighbor 2011:11:11:11::2 remote-as 6502
  neighbor 2011:11:11:11::2 ebgp-multihop 255
  no auto-summary
  !
  address-family ipv6
    neighbor 2011:11:11:11::2 activate
    neighbor 2011:11:11:11::2 capability orf prefix-list
send
  neighbor 2011:11:11:11::2 prefix-list FILTER_IPv6 in
  exit-address-family
!
!
ipv6 prefix-list FILTER_IPv6 seq 10 permit 1111::1/128
ipv6 prefix-list FILTER_IPv6 seq 20 permit 2222::1/128
!
!
end
```

R2 del router

```
!
hostname R2
!
!
no ip domain lookup
ipv6 unicast-routing
ipv6 cef
!
interface Loopback1
  no ip address
  ipv6 address 1010::1/128
!
!
interface Loopback2
  no ip address
  ipv6 address 2020::1/128
!
interface Serial1/0
  no ip address
  ipv6 address 2011:11:11:11::2/64
  serial restart-delay 0
!
!
router bgp 6502
  no synchronization
  bgp router-id 2.2.2.2
  bgp log-neighbor-changes
  neighbor 2011:11:11:11::1 remote-as 6501
  neighbor 2011:11:11:11::1 ebgp-multihop 255
  no auto-summary
  !
  address-family ipv6

    network 1010::1/128
```

```
network 2020::1/128
neighbor 2011:11:11:11::1 activate
neighbor 2011:11:11:11::1 capability orf prefix-list
receive neighbor 2011:11:11:11::1 prefix-list R2_list in
exit-address-family ! ipv6 prefix-list R2_list seq 10
permit 1010::1/128 ipv6 prefix-list R2_list seq 20
permit 2020::1/128 ! end
```

Escenario 1: Rutas de filtro basadas en la lista de prefijo con las expresiones

En este escenario, un Loopback Address **1000::1/45** se configura en el r1 bajo el Interface Loopback 0. Una lista de prefijo se crea para permitir cualquier ruta que sea mayor que la longitud del prefijo:: /64.

Nota: El r2 de la configuración del router sigue siendo lo mismo que previamente como se muestra dado y del r1 los cambios de configuración aquí. Los IP Addresses en este Routers siguen siendo lo mismo.

R1 del router

```
!--- Output omitted. ! interface Loopback0 no ip address
ipv6 address 1000::1/45 ! !--- Output omitted. router
bgp 6501 no synchronization bgp router-id 1.1.1.1 bgp
log-neighbor-changes neighbor 2011:11:11:11::2 remote-as
6502 neighbor 2011:11:11:11::2 ebgp-multihop 255 no
auto-summary ! address-family ipv6 network 1000::1/45
network 1111::1/128 network 2222::1/128 neighbor
2011:11:11:11::2 activate neighbor 2011:11:11:11::2
prefix-list IPV6-LONG in !--- Applies the prefix-list
and filters !--- the incoming updates from the neighbor
2011:11:11:11::2. exit-address-family ! ipv6 prefix-list
IPV6-LONG description Match any prefix longer than /64
ipv6 prefix-list IPV6-LONG seq 1 permit ::/0 ge 64 !---
seq 1 permit ::/0 ge 64 permits anything !--- that is ge
/64 subnet mask. ! end
```

Verificación

Use esta sección para confirmar que su configuración funciona correctamente.

[La herramienta Output Interpreter Tool \(clientes registrados solamente\)](#) (OIT) soporta ciertos comandos show. Utilice la OIT para ver un análisis del resultado del comando show.

Utilizan a estos comandos show de verificar la configuración:

- **show running-config** | pida el BGP
- [vecinos del unicast del show bgp ipv6](#)

Verifique el BGP Prefix-Based Outbound Route Filtering del IPv6 configurado en el modo de envío

En el r1 del router:

```
show running-config | pida el BGP
```

```

router bgp 6501
  no synchronization
  bgp router-id 1.1.1.1
  bgp log-neighbor-changes
  neighbor 2011:11:11:11::2 remote-as 6502
  neighbor 2011:11:11:11::2 ebgp-multihop 255
  no auto-summary
  !
  address-family ipv6
    neighbor 2011:11:11:11::2 activate
    neighbor 2011:11:11:11::2 capability orf prefix-list
send !--- Indicates that the neighbor 2011:11:11:11::2
!--- is configured with the prefix-based !--- ORF
feature in send mode.

```

vecinos del unicast del show bgp ipv6

```

R1#show bgp ipv6 unicast neighbors 2011:11:11:11::2 BGP
neighbor is 2011:11:11:11::2, remote AS 6502, external
link BGP version 4, remote router ID 2.2.2.2 Session
state = Established, up for 01:30:36 Last read 00:00:44,
last write 00:00:42, hold time is 180, keepalive
interval is 60 seconds BGP multisession with 2 sessions
(2 established), first up for 01:31:26 Neighbor
sessions: 2 active, is multisession capable Neighbor
capabilities: Route refresh: advertised and
received(new) on session 1, 2 Four-octets ASN
Capability: advertised and received on session 1, 2
Address family IPv4 Unicast: advertised and received
Address family IPv6 Unicast: advertised and received !---
- Output omitted. For address family: IPv6 Unicast
Session: 2011:11:11:11::2 session 2 BGP table version 1,
neighbor version 1/0 Output queue size : 0 Index 2
session 2 member 2 update-group member AF-dependant
capabilities: Outbound Route Filter (ORF) type (128)
Prefix-list: !--- Shows that the neighbor
2011:11:11:11::2 !--- is configured with the prefix-
based !--- ORF feature in send mode. Send-mode:
advertised Receive-mode: received Outbound Route Filter
(ORF): sent; Incoming update prefix filter list is
FILTER_IPv6 Sent Rcvd Prefix activity: ---- ----
Prefixes Current: 2 4 Prefixes Total: 0 0 Implicit
Withdraw: 1 0 Explicit Withdraw: 1 0 Used as bestpath:
n/a 0 Used as multipath: n/a 0 Outbound Inbound Local
Policy Denied Prefixes: ----- !--- Output
omitted.

```

Verifique el BGP Prefix-Based Outbound Route Filtering del IPv6 configurado adentro reciben el modo

En el r2 del router:

show running-config | pida el BGP

```

router bgp 6502
  no synchronization
  bgp router-id 2.2.2.2
  bgp log-neighbor-changes
  neighbor 2011:11:11:11::1 remote-as 6501
  neighbor 2011:11:11:11::1 ebgp-multihop 255
  no auto-summary
  !

```

```
address-family ipv6
  network 1010::1/128
  network 2020::1/128
  neighbor 2011:11:11:11::1 activate
  neighbor 2011:11:11:11::1 capability orf prefix-list
receive !--- Indicates that the neighbor
2011:11:11:11::1 !--- is configured with the prefix-
based !--- ORF feature in receive mode.
```

vecinos del unicast del show bgp ipv6

```
R2#show bgp ipv6 unicast nei 2011:11:11:11::1 BGP
neighbor is 2011:11:11:11::1, remote AS 6501, external
link BGP version 4, remote router ID 1.1.1.1 Session
state = Established, up for 01:47:11 Last read 00:00:44,
last write 00:00:32, hold time is 180, keepalive
interval is 60 seconds multisession with 2 sessions (2
established), first up for 01:48:02 Neighbor sessions: 2
active, is multisession capable Neighbor capabilities:
Route refresh: advertised and received(new) on session
1, 2 Four-octets ASN Capability: advertised and received
on session 1, 2 Address family IPv4 Unicast: advertised
and received Address family IPv6 Unicast: advertised and
received Multisession Capability: advertised and
received !--- Output omitted. For address family: IPv6
Unicast Session: 2011:11:11:11::1 session 2 BGP table
version 3, neighbor version 3/0 Output queue size : 0
Index 3 session 2 member 3 update-group member AF-
dependant capabilities: Outbound Route Filter (ORF) type
(128) Prefix-list: !--- Shows that the neighbor
2011:11:11:11::1 !--- is configured with the prefix-
based !--- ORF feature in receive mode. Send-mode:
received Receive-mode: advertised Outbound Route Filter
(ORF): received (2 entries) Incoming update prefix
filter list is R2_list Sent Rcvd Prefix activity: ---- -
--- Prefixes Current: 2 5 Prefixes Total: 0 0 Implicit
Withdraw: 0 0 Explicit Withdraw: 2 0 !--- Output
omitted.
```

Verifique el escenario 1: Rutas de filtro basadas en la lista de prefijo con las expresiones

Publique el comando **show bgp ipv6 route** en el r1 del router para visualizar el contenido actual de la tabla de BGP Routing del IPv6.

BGP de la show ipv6 route

```
En el r1 del router: R1#show ipv6 route bgp IPv6 Routing
Table - default - 9 entries Codes: C - Connected, L -
Local, S - Static, U - Per-user Static route B - BGP, HA
- Home Agent, MR - Mobile Router, R - RIP I1 - ISIS L1,
I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary D -
EIGRP, EX - EIGRP external, ND - Neighbor Discovery O -
OSPF Intra, OI - OSPF Inter, OE1 - OSPF ext 1, OE2 -
OSPF ext 2 ON1 - OSPF NSSA ext 1, ON2 - OSPF NSSA ext 2
B 1010::1/128 [20/0] via 2011:11:11:11::2 B 2020::1/128
[20/0] via 2011:11:11:11::2 !--- In this ouput,
1000::1/45 is not !--- displayed because the network is
lesser !--- than ::/64 prefix and its filtered.
```

Utilice el mostrar información del comando de la lista de prefijo del IPv6 de la demostración para

sobre las entradas de una lista de prefijos del IPv6 o de lista de prefijos del IPv6.

muestre la lista de prefijo del IPv6

En el r1 del router:

```
R1#show ipv6 prefix-list detail Prefix-list with the
last deletion/insertion: IPV6-LONG ipv6 prefix-list
IPV6-LONG: Description: Match any prefix longer than /64
count: 1, range entries: 1, sequences: 1 - 1, refcount:
3 seq 1 permit ::/0 ge 64 (hit count: 14, refcount: 1)
R1#show ipv6 prefix-list summary Prefix-list with the
last deletion/insertion: IPV6-LONG ipv6 prefix-list
IPV6-LONG: Description: Match any prefix longer than /64
count: 1, range entries: 1, sequences: 1 - 1, refcount:
3 R1#show ipv6 prefix-list IPV6-LONG ipv6 prefix-list
IPV6-LONG: 1 entries seq 1 permit ::/0 ge 64
```

Información Relacionada

- [Página de Soporte de BGP](#)
- [Página de soporte del IP versión 6](#)
- [Casos Prácticos de BGP](#)
- [Soporte Técnico y Documentación - Cisco Systems](#)