

Configuración de Cisco VPN Client al túnel a dos sitios remotos a través de un Hub PIX

Contenido

[Introducción](#)

[Antes de comenzar](#)

[Convenciones](#)

[prerrequisitos](#)

[Componentes Utilizados](#)

[Configurar](#)

[Diagrama de la red](#)

[Configuraciones](#)

[Verificación](#)

[Resultado del comando show](#)

[Troubleshooting](#)

[Resultado del comando debug](#)

[Información Relacionada](#)

[Introducción](#)

Este documento muestra cómo configurar un Cisco VPN Client para conectar con el interior de un PIX mientras se está conectado mediante el túnel a otro PIX. Esto se logra terminando el túnel en una interfaz diferente del PIX a la que el Cliente VPN ya está conectado.

Los clientes de VPN remotos se conectarán a snow (PIX 525) y recibirán una dirección IP incluida en el rango 12.0.0.1 - 12.0.0.34. El Cliente VPN podrá establecer una conectividad total con el interior de snow (10.0.0.0/24), así como también con el interior de otro PIX (denominado rain en esta configuración).

[Antes de comenzar](#)

[Convenciones](#)

Para obtener más información sobre las convenciones del documento, consulte [Convenciones de Consejos Técnicos de Cisco](#).

[prerrequisitos](#)

Antes de utilizar esta configuración, asegúrese de que cumple con los siguientes requisitos previos:

- **rain** La configuración para la *lluvia* se basa en la configuración de muestra [que configura un Túnel VPN PIX a PIX sencillo usando el IPSec](#). La única diferencia es que el agrupamiento de IP reservado para el cliente debe incluirse en el comando crypto map access-list. Es decir queremos proteger el tráfico que va contra nuestro LAN (11.0.0.0/24) al LAN privado remoto (10.0.0.0/24) y al cliente remoto (12.0.0.0/24).
- **snow** Para garantizar el funcionamiento correcto de esta configuración, necesita tener conectadas dos interfaces diferentes a la red "exterior", por lo general, el proveedor de servicios de Internet (ISP). Además, debe tener dos correspondencias de criptografía. Una correspondencia de criptografía se debe aplicar al intf2 (típicamente el DMZ) que duplicará la configuración de la *lluvia*; esto protegerá la red interna (10.0.0.0/24) que va al LAN remoto (11.0.0.0/24) mientras que también protege el pool del cliente VPN (12.0.0.0/24) que va al LAN remoto. La segunda correspondencia de criptografía se debe aplicar a la interfaz externa (generalmente, eth0) como una correspondencia de criptografía dinámica típica, tal como se describe en Configuración de modo, previamente compartido, del comodín de [Cisco PIX 5.1 a VPN Client con autenticación extendida](#).

Cuando el PIX (*lluvia* en este ejemplo) intenta conectar con el intf2 de (193.0.0.5), la negociación del Internet Key Exchange (IKE) fallará porque el otro PIX (*nieve*) contestará con su dirección externa de 193.0.0.1. (Esto es porque el PIX tiene típicamente una ruta predeterminado al exterior.) Para resolver el problema, agregue una ruta específica al LAN remoto a la interfaz del intf2. También agregue una ruta del host a la dirección externa del PIX remoto que va con el intf2.

Sin importar la traducción configurada en el PIX, no debe configurar ninguna traducción para el tráfico VPN (traducción nat 0). Para hacerlo, configure las dos listas de acceso (no-nat-inside y no-nat-intf2) y aplíquelas con los siguientes comandos:

```
nat (inside) 0 access-list no-nat-inside
nat (intf2) 0 access-list no-nat-intf2
```

Componentes Utilizados

La información que contiene este documento se basa en las versiones de software y hardware indicadas a continuación.

- PIX 525 con la versión 6.2(2) del Software de escudo de protección PIX de Cisco.
- PIX 515 con la versión de software del Cisco Secure PIX Firewall 6.2(2)
- Software de Cisco IOS® 7200 (C7200-JO3S56I-M), versión 12.2(6)
- Cliente Cisco VPN 3.6.1 en el Microsoft Windows 2000

La información que se presenta en este documento se originó a partir de dispositivos dentro de un ambiente de laboratorio específico. Todos los dispositivos que se utilizan en este documento se pusieron en funcionamiento con una configuración verificada (predeterminada). Si la red está funcionando, asegúrese de haber comprendido el impacto que puede tener un comando antes de ejecutarlo.

Configurar

En esta sección encontrará la información para configurar las funciones descritas en este documento.

Nota: Para obtener información adicional sobre los comandos que se utilizan en este documento,

use la Command Lookup Tool (solo para clientes [registrados](#)).

[Diagrama de la red](#)

Este documento utiliza la instalación de red que se muestra en el siguiente diagrama.

[Configuraciones](#)

Este documento usa las configuraciones detalladas a continuación.

- [snow](#)
- [rain](#)
- [carrion](#)

```

snow
nat (inside) 0 access-list no-nat-inside
nat (intf2) 0 access-list no-nat-intf2

rain
rain# write terminal
Building configuration...
: Saved
:
PIX Version 6.2(2)
nameif ethernet0 outside security0
nameif ethernet1 inside security100
nameif ethernet2 intf2 security10
nameif ethernet3 intf3 security15
nameif ethernet4 intf4 security20
nameif ethernet5 intf5 security25
enable password 8Ry2YjIyt7RRXU24 encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname rain
fixup protocol ftp 21
fixup protocol http 80
fixup protocol h323 1720
fixup protocol rsh 514
fixup protocol rtsp 554
fixup protocol smtp 25
fixup protocol sqlnet 1521
fixup protocol sip 5060
fixup protocol skinny 2000
names
access-list acl-out permit icmp any any
access-list vpn-to-snow permit ip 11.0.0.0 255.255.255.0
    10.0.0.0 255.255.255.0
access-list vpn-to-snow permit ip 11.0.0.0 255.255.255.0
    12.0.0.0 255.255.255.0
no pager
interface ethernet0 auto
interface ethernet1 auto
interface ethernet2 auto shutdown
interface ethernet3 auto shutdown
interface ethernet4 auto shutdown
interface ethernet5 auto shutdown
icmp permit any outside
mtu outside 1500
mtu inside 1500
```

```
mtu intf2 1500
mtu intf3 1500
mtu intf4 1500
mtu intf5 1500
ip address outside 10.48.66.156 255.255.255.0
ip address inside 11.0.0.1 255.255.255.0
ip address intf2 127.0.0.1 255.255.255.255
ip address intf3 127.0.0.1 255.255.255.255
ip address intf4 127.0.0.1 255.255.255.255
ip address intf5 127.0.0.1 255.255.255.255
ip audit info action alarm
ip audit attack action alarm
no failover
failover timeout 0:00:00
failover poll 15
failover ip address outside 0.0.0.0
failover ip address inside 0.0.0.0
failover ip address intf2 0.0.0.0
failover ip address intf3 0.0.0.0
failover ip address intf4 0.0.0.0
failover ip address intf5 0.0.0.0
pdm history enable
arp timeout 14400
nat (inside) 0 access-list vpn-to-snow
access-group acl-out in interface outside
route outside 10.0.0.0 255.255.255.0 193.0.0.5 1
route outside 12.0.0.0 255.255.255.0 193.0.0.5 1
route outside 193.0.0.0 255.255.255.0 10.48.66.44 1
timeout xlate 3:00:00
timeout conn 1:00:00 half-closed 0:10:00 udp 0:02:00
    rpc 0:10:00 h323 0:05:00 sip 0:30:00 sip_media
0:02:00
timeout uauth 0:05:00 absolute
aaa-server TACACS+ protocol tacacs+
aaa-server RADIUS protocol radius
no snmp-server location
no snmp-server contact
snmp-server community public
no snmp-server enable traps
no floodguard enable
sysopt connection permit-ipsec
no sysopt route dnat
crypto ipsec transform-set TRANS esp-des esp-sha-hmac
crypto map vpn-outside 10 ipsec-isakmp
crypto map vpn-outside 10 match address vpn-to-snow
crypto map vpn-outside 10 set peer 193.0.0.5
crypto map vpn-outside 10 set transform-set TRANS
crypto map vpn-outside interface outside
isakmp enable outside
isakmp key ***** address 193.0.0.5 netmask
255.255.255.255
isakmp policy 10 authentication pre-share
isakmp policy 10 encryption des
isakmp policy 10 hash sha
isakmp policy 10 group 2
isakmp policy 10 lifetime 86400
telnet timeout 5
ssh timeout 5
terminal width 80
Cryptochecksum:a2181c3b31cfcf3be90c24f622c17eed
: end
[OK]
```

carrion

```
rain# write terminal
Building configuration...
: Saved
:
PIX Version 6.2(2)
nameif ethernet0 outside security0
nameif ethernet1 inside security100
nameif ethernet2 intf2 security10
nameif ethernet3 intf3 security15
nameif ethernet4 intf4 security20
nameif ethernet5 intf5 security25
enable password 8Ry2YjIyt7RRXU24 encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname rain
fixup protocol ftp 21
fixup protocol http 80
fixup protocol h323 1720
fixup protocol rsh 514
fixup protocol rtsp 554
fixup protocol smtp 25
fixup protocol sqlnet 1521
fixup protocol sip 5060
fixup protocol skinny 2000
names
access-list acl-out permit icmp any any
access-list vpn-to-snow permit ip 11.0.0.0 255.255.255.0
    10.0.0.0 255.255.255.0
access-list vpn-to-snow permit ip 11.0.0.0 255.255.255.0
    12.0.0.0 255.255.255.0
no pager
interface ethernet0 auto
interface ethernet1 auto
interface ethernet2 auto shutdown
interface ethernet3 auto shutdown
interface ethernet4 auto shutdown
interface ethernet5 auto shutdown
icmp permit any outside
mtu outside 1500
mtu inside 1500
mtu intf2 1500
mtu intf3 1500
mtu intf4 1500
mtu intf5 1500
ip address outside 10.48.66.156 255.255.255.0
ip address inside 11.0.0.1 255.255.255.0
ip address intf2 127.0.0.1 255.255.255.255
ip address intf3 127.0.0.1 255.255.255.255
ip address intf4 127.0.0.1 255.255.255.255
ip address intf5 127.0.0.1 255.255.255.255
ip audit info action alarm
ip audit attack action alarm
no failover
failover timeout 0:00:00
failover poll 15
failover ip address outside 0.0.0.0
failover ip address inside 0.0.0.0
failover ip address intf2 0.0.0.0
failover ip address intf3 0.0.0.0
failover ip address intf4 0.0.0.0
failover ip address intf5 0.0.0.0
pdm history enable
arp timeout 14400
nat (inside) 0 access-list vpn-to-snow
access-group acl-out in interface outside
```

```
route outside 10.0.0.0 255.255.255.0 193.0.0.5 1
route outside 12.0.0.0 255.255.255.0 193.0.0.5 1
route outside 193.0.0.0 255.255.255.0 10.48.66.44 1
timeout xlate 3:00:00
timeout conn 1:00:00 half-closed 0:10:00 udp 0:02:00
    rpc 0:10:00 h323 0:05:00 sip 0:30:00 sip_media
0:02:00
timeout uauth 0:05:00 absolute
aaa-server TACACS+ protocol tacacs+
aaa-server RADIUS protocol radius
no snmp-server location
no snmp-server contact
snmp-server community public
no snmp-server enable traps
no floodguard enable
sysopt connection permit-ipsec
no sysopt route dnat
crypto ipsec transform-set TRANS esp-des esp-sha-hmac
crypto map vpn-outside 10 ipsec-isakmp
crypto map vpn-outside 10 match address vpn-to-snow
crypto map vpn-outside 10 set peer 193.0.0.5
crypto map vpn-outside 10 set transform-set TRANS
crypto map vpn-outside interface outside
isakmp enable outside
isakmp key ***** address 193.0.0.5 netmask
255.255.255.255
isakmp policy 10 authentication pre-share
isakmp policy 10 encryption des
isakmp policy 10 hash sha
isakmp policy 10 group 2
isakmp policy 10 lifetime 86400
telnet timeout 5
ssh timeout 5
terminal width 80
Cryptochecksum:a2181c3b31cfcf3be90c24f622c17eed
: end
[OK]
```

Verificación

En esta sección encontrará información que puede utilizar para confirmar que su configuración esté funcionando correctamente.

La herramienta [Output Interpreter](#) (sólo para clientes [registrados](#)) permite utilizar algunos comandos “show” y ver un análisis del resultado de estos comandos.

Resultado del comando show

salida del comando show para la nieve

```
snow# show version
```

```
Cisco PIX Firewall Version 6.2(2)
```

```
Compiled on Tue 11-Sep-01 07:45 by morlee
```

```
snow up 11 mins 19 secs
```

```
Hardware: PIX-525, 256 MB RAM, CPU Pentium III 600 MHz
```

Flash E28F128J3 @ 0x300, 16MB
BIOS Flash AM29F400B @ 0xffffd8000, 32KB

0: ethernet0: address is 0002.b945.9ff1, irq 10
1: ethernet1: address is 0002.b945.9ff2, irq 11
2: ethernet2: address is 00e0.b602.236f, irq 11
3: ethernet3: address is 00e0.b602.236e, irq 10
4: ethernet4: address is 00e0.b602.236d, irq 9
5: ethernet5: address is 00e0.b602.236c, irq 5

Licensed Features:

Failover: Enabled
VPN-DES: Enabled
VPN-3DES: Disabled
Maximum Interfaces: 8
Cut-through Proxy: Enabled
Guards: Enabled
Websense: Enabled
Inside Hosts: Unlimited
Throughput: Unlimited
ISAKMP peers: Unlimited

Serial Number: 480380577 (0x1ca206a1)
Activation Key: 0x9c2c232e 0xaaad98633 0x3667fa1b 0x76404050
snow#

snow(config)# **show route**

outside 0.0.0.0 0.0.0.0 193.0.0.2 1 OTHER static
inside 10.0.0.0 255.255.255.0 10.0.0.1 1 CONNECT static
intf2 10.48.66.156 255.255.255.255 193.0.0.6 1 OTHER static
intf2 11.0.0.0 255.255.255.0 193.0.0.6 1 OTHER static
intf3 127.0.0.1 255.255.255.255 127.0.0.1 1 CONNECT static
outside 193.0.0.0 255.255.255.252 193.0.0.1 1 CONNECT static
intf2 193.0.0.4 255.255.255.252 193.0.0.5 1 CONNECT static

snow(config)# **show access-list**

access-list acl-out permit icmp any any (hitcnt=0)
access-list acl-intf2 permit icmp any any (hitcnt=0)
access-list vpn-intf2 permit ip 10.0.0.0 255.255.255.0
11.0.0.0 255.255.255.0 (hitcnt=12)
access-list vpn-intf2 permit ip 12.0.0.0 255.255.255.0
11.0.0.0 255.255.255.0 (hitcnt=34)
access-list no-nat-inside permit ip 10.0.0.0 255.255.255.0
11.0.0.0 255.255.255.0 (hitcnt=18)
access-list no-nat-inside permit ip 10.0.0.0 255.255.255.0
12.0.0.0 255.255.255.0 (hitcnt=32)
access-list no-nat-intf2 permit ip 11.0.0.0 255.255.255.0
12.0.0.0 255.255.255.0 (hitcnt=50)
access-list dynacl6 permit ip host 193.0.0.1 host 12.0.0.1 (hitcnt=0)
access-list dynacl7 permit ip any host 12.0.0.1 (hitcnt=6)

snow(config)# **show crypto isa sa**

Total : 2
Embryonic : 0

dst	src	state	pending	created
10.48.66.156	193.0.0.5	QM_IDLE	0	1
193.0.0.1	10.48.66.76	QM_IDLE	0	2

snow(config)# **show crypto ipsec sa**

```
interface: intf2
  Crypto map tag: vpn-intf2, local addr. 193.0.0.5

local ident (addr/mask/prot/port): (10.0.0.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port): (11.0.0.0/255.255.255.0/0/0)
current_peer: 10.48.66.156
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 0, #pkts encrypt: 0, #pkts digest 0
  #pkts decaps: 0, #pkts decrypt: 0, #pkts verify 0
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0,
  #pkts decompress failed: 0
  #send errors 0, #recv errors 0

local crypto endpt.: 193.0.0.5, remote crypto endpt.: 10.48.66.156
path mtu 1500, ipsec overhead 0, media mtu 1500
current outbound spi: 0

inbound esp sas:

inbound ah sas:

inbound pcp sas:

outbound esp sas:

outbound ah sas:

outbound pcp sas:

local ident (addr/mask/prot/port): (12.0.0.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port): (11.0.0.0/255.255.255.0/0/0)
current_peer: 10.48.66.156
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 6, #pkts encrypt: 6, #pkts digest 6
  #pkts decaps: 6, #pkts decrypt: 6, #pkts verify 6
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0,
  #pkts decompress failed: 0
  #send errors 2, #recv errors 0

local crypto endpt.: 193.0.0.5, remote crypto endpt.: 10.48.66.156
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: 8312e721

inbound esp sas:
  spi: 0x661d4fad(1713196973)
  transform: esp-des esp-sha-hmac ,
  in use settings ={Tunnel, }
  slot: 0, conn id: 1, crypto map: vpn-intf2
  sa timing: remaining key lifetime (k/sec): (4607999/27978)
  IV size: 8 bytes
  replay detection support: Y

inbound ah sas:
```


inbound pcp sas:

outbound esp sas:

spi: 0x8312e721(2199054113)
transform: esp-des esp-sha-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 2, crypto map: vpn-intf2
sa timing: remaining key lifetime (k/sec): (4607999/27978)
IV size: 8 bytes
replay detection support: Y

outbound ah sas:

outbound pcp sas:

interface: outside

Crypto map tag: toOUT, local addr. 193.0.0.1

local ident (addr/mask/prot/port): (0.0.0.0/0.0.0.0/0/0)
remote ident (addr/mask/prot/port): (12.0.0.1/255.255.255.255/0/0)
current_peer: 10.48.66.76
dynamic allocated peer ip: 12.0.0.1

PERMIT, flags={}
#pkts encaps: 6, #pkts encrypt: 6, #pkts digest 6
#pkts decaps: 28, #pkts decrypt: 28, #pkts verify 28
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0,
#pkts decompress failed: 0
#send errors 0, #recv errors 0

local crypto endpt.: 193.0.0.1, remote crypto endpt.: 10.48.66.76
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: 62c47dd7

inbound esp sas:

spi: 0x331a3e87(857357959)
transform: esp-des esp-md5-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 7, crypto map: toOUT
sa timing: remaining key lifetime (k/sec): (4607996/27359)
IV size: 8 bytes
replay detection support: Y

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0x62c47dd7(1657044439)
transform: esp-des esp-md5-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 8, crypto map: toOUT
sa timing: remaining key lifetime (k/sec): (4607999/27359)

IV size: 8 bytes
replay detection support: Y

outbound ah sas:

outbound pcp sas:

local ident (addr/mask/prot/port): (193.0.0.1/255.255.255.255/0/0)
remote ident (addr/mask/prot/port): (12.0.0.1/255.255.255.255/0/0)
current_peer: 10.48.66.76
dynamic allocated peer ip: 12.0.0.1

PERMIT, flags={}
#pkts encaps: 0, #pkts encrypt: 0, #pkts digest 0
#pkts decaps: 0, #pkts decrypt: 0, #pkts verify 0
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0,
#pkts decompress failed: 0
#send errors 0, #recv errors 0

local crypto endpt.: 193.0.0.1, remote crypto endpt.: 10.48.66.76
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: 4e13c751

inbound esp sas:

spi: 0x4f3e0026(1329463334)
transform: esp-des esp-md5-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 3, crypto map: toOUT
sa timing: remaining key lifetime (k/sec): (4608000/27972)
IV size: 8 bytes
replay detection support: Y

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0x4e13c751(1309919057)
transform: esp-des esp-md5-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 4, crypto map: toOUT
sa timing: remaining key lifetime (k/sec): (4608000/27963)
IV size: 8 bytes
replay detection support: Y

outbound ah sas:

outbound pcp sas:

salida del comando show para la lluvia

rain# **show version**

Cisco PIX Firewall Version 6.2(2)

Compiled on Tue 11-Sep-01 07:45 by morlee

rain up 2 hours 23 mins

Hardware: PIX-525, 256 MB RAM, CPU Pentium III 600 MHz
Flash E28F128J3 @ 0x300, 16MB
BIOS Flash AM29F400B @ 0xfffd8000, 32KB

0: ethernet0: address is 0002.b945.a001, irq 10
1: ethernet1: address is 0002.b945.a002, irq 11
2: ethernet2: address is 00e0.b602.4797, irq 11
3: ethernet3: address is 00e0.b602.4796, irq 10
4: ethernet4: address is 00e0.b602.4795, irq 9
5: ethernet5: address is 00e0.b602.4794, irq 5

Licensed Features:

Failover: Enabled
VPN-DES: Enabled
VPN-3DES: Enabled
Maximum Interfaces: 8
Cut-through Proxy: Enabled
Guards: Enabled
Websense: Enabled
Inside Hosts: Unlimited
Throughput: Unlimited
ISAKMP peers: Unlimited

Serial Number: 480380580 (0x1ca206a4)
Activation Key: 0x3a08e996 0x3d4a15af 0x604a1272 0xd8f8e3b8

rain# **show route**

outside 10.0.0.0 255.255.255.0 193.0.0.5 1 OTHER static
outside 10.48.66.0 255.255.255.0 10.48.66.156 1 CONNECT static
inside 11.0.0.0 255.255.255.0 11.0.0.1 1 CONNECT static
outside 12.0.0.0 255.255.255.0 193.0.0.5 1 OTHER static
outside 193.0.0.0 255.255.255.0 10.48.66.44 1 OTHER static

rain# **show crypto isa sa**

Total : 2
Embryonic : 0

dst	src	state	pending	created
10.48.66.156	193.0.0.5	QM_IDLE	0	1
193.0.0.5	10.48.66.156	QM_IDLE	0	2

rain# **show crypto ipsec sa**

interface: outside
Crypto map tag: vpn-outside, local addr. 10.48.66.156

local ident (addr/mask/prot/port): (11.0.0.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port): (10.0.0.0/255.255.255.0/0/0)
current_peer: 193.0.0.5
PERMIT, flags={origin_is_acl,}
#pkts encaps: 8, #pkts encrypt: 8, #pkts digest 8
#pkts decaps: 8, #pkts decrypt: 8, #pkts verify 8
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0,
#pkts decompress failed: 0
#send errors 0, #recv errors 0

local crypto endpt.: 10.48.66.156, remote crypto endpt.: 193.0.0.5
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: 0

inbound esp sas:

inbound ah sas:

inbound pcp sas:

outbound esp sas:

outbound ah sas:

outbound pcp sas:

local ident (addr/mask/prot/port): (11.0.0.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port): (12.0.0.0/255.255.255.0/0/0)
current_peer: 193.0.0.5
PERMIT, flags={origin_is_acl,}
#pkts encaps: 22, #pkts encrypt: 22, #pkts digest 22
#pkts decaps: 22, #pkts decrypt: 22, #pkts verify 22
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0,
#pkts decompress failed: 0
#send errors 0, #recv errors 0

local crypto endpt.: 10.48.66.156, remote crypto endpt.: 193.0.0.5
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: 661d4fad

inbound esp sas:

spi: 0x8312e721(2199054113)
transform: esp-des esp-sha-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 1, crypto map: vpn-outside
sa timing: remaining key lifetime (k/sec): (4607999/27529)
IV size: 8 bytes
replay detection support: Y

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0x661d4fad(1713196973)
transform: esp-des esp-sha-hmac ,
in use settings ={Tunnel, }
slot: 0, conn id: 2, crypto map: vpn-outside
sa timing: remaining key lifetime (k/sec): (4607999/27529)
IV size: 8 bytes
replay detection support: Y

outbound ah sas:

outbound pcp sas:

salida del comando show para la carroña

```
carrion# show version
Cisco Internetwork Operating System Software
IOS (tm) RSP Software (RSP-JK903SV-M), Version 12.2(6),
  RELEASE SOFTWARE (fc2)
Copyright (c) 1986-2001 by cisco Systems, Inc.
Compiled Wed 07-Nov-01 21:44 by pwade
Image text-base: 0x600109C8, data-base: 0x61B42000

ROM: System Bootstrap, Version 11.1(2) [nitin 2],
  RELEASE SOFTWARE (fc1)
BOOTLDR: RSP Software (RSP-BOOT-M), Version 12.2(6),
  RELEASE SOFTWARE (fc2)

carrion uptime is 2 weeks, 3 days, 22 hours, 32 minutes
System returned to ROM by reload at 12:27:14 UTC Wed Oct 10 2001
System image file is "slot0:rsp-jk9o3sv-mz.122-6.bin"

cisco RSP2 (R4700) processor with 131072K/2072K bytes of memory.
R4700 CPU at 100Mhz, Implementation 33, Rev 1.0
Last reset from power-on
G.703/E1 software, Version 1.0.
G.703/JT2 software, Version 1.0.
X.25 software, Version 3.0.0.
SuperLAT software (copyright 1990 by Meridian Technology Corp).
Bridging software.
TN3270 Emulation software.
Chassis Interface.
 1 EIP controller (4 Ethernet).
 3 FSIP controllers (24 Serial).
 1 VIP2 controller (1 HSSI).
 4 Ethernet/IEEE 802.3 interface(s)
24 Serial network interface(s)
 1 HSSI network interface(s)
123K bytes of non-volatile configuration memory.

20480K bytes of Flash PCMCIA card at slot 0 (Sector size 128K).
8192K bytes of Flash internal SIMM (Sector size 256K).
No slave installed in slot 7.
Configuration register is 0x2002
```

[Troubleshooting](#)

En esta sección encontrará información que puede utilizar para solucionar problemas de configuración.

[Resultado del comando debug](#)

Nota: Antes de ejecutar un comando debug, consulte Información Importante sobre Comandos Debug.

Resultado del comando debug para snow

```
snow# show debug
```

```
debug crypto ipsec 1
debug crypto isakmp 1
debug crypto engine
debug icmp trace
debug fover status
txOff
rxOff
openOff
cableOff
txdmpOff
rxdmpOff
ifcOff
rxipOff
txipOff
getOff
putOff
verifyOff
switchOff
failOff
fmsgOff
snow# no debug icmp trace
ICMP trace off
snow#
snow#
snow#
snow#
snow# configure terminal
      ! the client is connecting !!!!!!!!!!!!!!!
Type help or '?' for a list of available commands.
snow#
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
VPN Peer: ISAKMP: Added new peer: ip:10.48.66.76 Total VPN Peers:1
VPN Peer: ISAKMP: Peer ip:10.48.66.76
      Ref cnt incremented to:1 Total VPN Peers:1
OAK_AG exchange
ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 2 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 3 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 4 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash MD5
```

```
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 5 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 6 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 7 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are acceptable. Next payload is 3
ISAKMP (0):  processing KE payload. message ID = 0

ISAKMP (0):  processing NONCE payload. message ID = 0

ISAKMP (0):  processing ID payload. message ID = 0
ISAKMP (0):  processing vendor id payload

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  remote peer supports dead peer detection

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  speaking to a Unity client

ISAKMP: Created a peer node for 10.48.66.76
ISAKMP (0): ID payload
next-payload : 10
type         : 1
protocol     : 17
port         : 500
length       : 8
ISAKMP (0): Total payload length: 12
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_AG exchange
ISAKMP (0): processing HASH payload. message ID = 0
ISAKMP (0): processing NOTIFY payload 24578 protocol 1
spi 0, message ID = 0
ISAKMP (0): processing notify INITIAL_CONTACTIPSEC(key_engine):
    got a queue event...
IPSEC(key_engine_delete_sas): rec'd delete notify from ISAKMP
IPSEC(key_engine_delete_sas): delete all SAs shared with 10.48.66.76

ISAKMP (0): SA has been authenticated
```

```
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
ISAKMP_TRANSACTION exchange
ISAKMP (0:0): processing transaction payload from 10.48.66.76.
    message ID = 0
ISAKMP: Config payload CFG_REQUEST
ISAKMP (0:0): checking request:
ISAKMP: attribute    IP4_ADDRESS (1)
ISAKMP: attribute    IP4_NETMASK (2)
ISAKMP: attribute    IP4_DNS (3)
ISAKMP: attribute    IP4_NBNS (4)
ISAKMP: attribute    ADDRESS_EXPIRY (5)
    Unsupported Attr: 5
ISAKMP: attribute    APPLICATION_VERSION (7)
    Unsupported Attr: 7
ISAKMP: attribute    UNKNOWN (28672)
    Unsupported Attr: 28672
ISAKMP: attribute    UNKNOWN (28673)
    Unsupported Attr: 28673
ISAKMP: attribute    UNKNOWN (28674)
ISAKMP: attribute    UNKNOWN (28676)
ISAKMP: attribute    UNKNOWN (28679)
    Unsupported Attr: 28679
ISAKMP: attribute    UNKNOWN (28680)
    Unsupported Attr: 28680
ISAKMP: attribute    UNKNOWN (28677)
    Unsupported Attr: 28677
ISAKMP (0:0): responding to peer config from 10.48.66.76.
    ID = 1245965288
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 2141307752

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:    authenticator is HMAC-MD5
ISAKMP:    encaps is 1
ISAKMP:    SA life type in seconds
ISAKMP:    SA life duration (VPI) of
    0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
    (prot 3, trans 3, hmac_alg 1) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDED proposal (1)
ISAKMP : Checking IPsec proposal 2

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:    authenticator is HMAC-SHA
ISAKMP:    encaps is 1
ISAKMP:    SA life type in seconds
ISAKMP:    SA life duration (VPI) of
    0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
    (prot 3, trans 3, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDED proposal (2)
ISAKMP : Checking IPsec proposal 3
```


ISAKMP: transform 1, ESP_3DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 3, hmac_alg 1) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP : Checking IPsec proposal 4

ISAKMP: transform 1, ESP_3DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-SHA
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 3, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP : Checking IPsec proposal 5

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are acceptable.
ISAKMP (0): bad SPI size of 2 octets!
ISAKMP : Checking IPsec proposal 6

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-SHA
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 2, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDED proposal (6)
ISAKMP : Checking IPsec proposal 7

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are acceptable.IPSEC(validate_proposal_request):
proposal part #1,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 193.0.0.1/255.255.255.255/0/0 (type=1),
src_proxy= 12.0.0.1/255.255.255.255/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload. message ID = 2141307752

```
ISAKMP (0): processing ID payload. message ID = 2141307752
ISAKMP (0): ID_IPV4_ADDR src 12.0.0.1 prot 0 port 0
ISAKMP (0): processing ID payload. message ID = 2141307752
ISAKMP (0): ID_IPV4_ADDR dst 193.0.0.1 prot 0 port 0 IPSEC(key_engine):
    got a queue event...
IPSEC(spi_response): getting spi 0x4f3e0026(1329463334) for SA
from    10.48.66.76 to    193.0.0.1 for prot 3

return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 2151626816

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:      authenticator is HMAC-MD5
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_AUTH_AWAITmap_alloc_entry: allocating entry 3
map_alloc_entry: allocating entry 4

ISAKMP (0): Creating IPsec SAs
    inbound SA from    10.48.66.76 to    193.0.0.1 (proxy
12.0.0.1 to    193.0.0.1)
    has spi 1329463334 and conn_id 3 and flags 4
    lifetime of 2147483 seconds
    outbound SA from    193.0.0.1 to    10.48.66.76 (proxy
193.0.0.1 to    12.0.0.1)
    has spi 1309919057 and conn_id 4 and flags 4
    lifetime of 2147483 secondsIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 193.0.0.1/0.0.0.0/0/0 (type=1),
src_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x4f3e0026(1329463334), conn_id= 3, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.1, dest= 10.48.66.76,
src_proxy= 193.0.0.1/0.0.0.0/0/0 (type=1),
dest_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x4e13c751(1309919057), conn_id= 4, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt
incremented to:2 Total VPN Peers:1
VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt
incremented to:3 Total VPN Peers:1
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_AUTH_AWAITmap_alloc_entry: allocating entry 7
map_alloc_entry: allocating entry 8

ISAKMP (0): Creating IPsec SAs
    inbound SA from    10.48.66.76 to    193.0.0.1 (proxy
12.0.0.1 to    0.0.0.0)
```

```
has spi 857357959 and conn_id 7 and flags 4
lifetime of 2147483 seconds
outbound SA from      193.0.0.1 to      10.48.66.76 (proxy
0.0.0.0 to      12.0.0.1)
has spi 1657044439 and conn_id 8 and flags 4
lifetime of 2147483 secondsIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4),
src_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x331a3e87(857357959), conn_id= 7, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.1, dest= 10.48.66.76,
src_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4),
dest_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x62c47dd7(1657044439), conn_id= 8, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt incremented to:4 Total VPN Peers:1
VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt incremented to:5 Total VPN Peers:1
return status is IKMP_NO_ERROR602301: sa created, (sa) sa_dest= 193.0.0.1,
sa_prot= 50, sa_spi= 0x4f3e0026(1329463334),
sa_trans= esp-des esp-md5-hmac , sa_conn_id= 3

602301: sa created, (sa) sa_dest= 10.48.66.76, sa_prot= 50,
sa_spi= 0x4e13c751(1309919057), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 4

602301: sa created, (sa) sa_dest= 193.0.0.1, sa_prot= 50,
sa_spi= 0x331a3e87(857357959), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 7

602301: sa created, (sa) sa_dest= 10.48.66.76, sa_prot= 50,
sa_spi= 0x62c47dd7(1657044439), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 8

ISADB: reaper checking SA 0x81153ac0, conn_id = 0
snow#
snow#
snow#
snow# 302010: 0 in use, 0 most used

snow#
snow#
snow#
snow#
snow# ! client will now ping 11.0.0.2
Type help or '?' for a list of available commands.
snow# 6
VPN Peer: ISAKMP: Added new peer: ip:10.48.66.156 Total VPN Peers:2
VPN Peer: ISAKMP: Peer ip:10.48.66.156
Ref cnt incremented to:1 Total VPN Peers:2
ISAKMP (0): beginning Main Mode exchange09001:
Built local-host intf2:11.0.0.

crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against priority 10 policy
```

```
ISAKMP:      encryption DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of 0x0 0x1 0x51 0x80
ISAKMP (0): atts are acceptable. Next payload is 0
ISAKMP (0): SA is doing pre-shared key authentication
      using id type ID_IPV4_ADDR
return status is IKMP_NO_ERROR2
702303: sa_request, (key eng. msg.
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing vendor id payload

ISAKMP (0): processing vendor id payload

ISAKMP (0): remote peer supports dead peer detection

ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload
next-payload : 8
type          : 1
protocol      : 17
port          : 500
length       : 8
ISAKMP (0): Total payload length: 12
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0): processing ID payload. message ID = 0
ISAKMP (0): processing HASH payload. message ID = 0
ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,
      M-ID of -931180733:c87f4f43IPSEC(key_engine): got a queue event...
IPSEC(spi_response): getting spi 0x661d4fad(1713196973) for SA
from 10.48.66.156 to 193.0.0.5 for prot 3

return status is IKMP_NO_ERROR
ISAKMP (0): sending INITIAL_CONTACT notify
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 3363786563

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES
ISAKMP:  attributes in transform:
ISAKMP:  encaps is 1
ISAKMP:  SA life type in seconds
ISAKMP:  SA life duration (basic) of 28800
ISAKMP:  SA life type in kilobytes
ISAKMP:  SA life duration (VPI) of 0x0 0x46 0x50 0x0
ISAKMP:  authenticator is HMAC-SHA
```

```

ISAKMP (0): atts are acceptable.IPSEC(validate_proposal_request):
  proposal part #1,
(key eng. msg.) dest= 10.48.66.156, src= 193.0.0.5,
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 0s and 0kb,
  spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload. message ID = 3363786563

ISAKMP (0): processing ID payload. message ID = 3363786563
ISAKMP (0): processing ID payload.
  message ID = 3363786563map_alloc_entry: allocating entry 1
map_alloc_entry: allocating entry 2

ISAKMP (0): Creating IPsec SAs
  inbound SA from 10.48.66.156 to 193.0.0.5 (proxy
11.0.0.0 to 12.0.0.0)
  has spi 1713196973 and conn_id 1 and flags 4
  lifetime of 28800 seconds
  lifetime of 4608000 kilobytes
  outbound SA from 193.0.0.5 to 10.48.66.156 (proxy
12.0.0.0 to 11.0.0.0)
  has spi 2199054113 and conn_id 2 and flags 4
  lifetime of 28800 seconds
  lifetime of 4608000 kilobytesIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.5, src= 10.48.66.156,
  dest_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  src_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 28800s and 4608000kb,
  spi= 0x661d4fad(1713196973), conn_id= 1, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.5, dest= 10.48.66.156,
  src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 28800s and 4608000kb,
  spi= 0x8312e721(2199054113), conn_id= 2, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.156
  Ref cnt incremented to:2 Total VPN Peers:2
VPN Peer: IPSEC: Peer ip:10.48.66.156
  Ref cnt incremented to:3 Total VPN Peers:2
return status is IKMP_NO_ERROR) src= 193.0.0.5,
  dest= 10.48.66.156, src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4), protocol= ESP,
  transform= esp-des esp-sha-hmac , lifedur= 28800s and 4608000kb,
  spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4004

602301: sa created, (sa) sa_dest= 193.0.0.5, sa_prot= 50,
  sa_spi= 0x661d4fad(1713196973), sa_trans= esp-des esp-sha-hmac ,
  sa_conn_id= 1

602301: sa created, (sa) sa_dest= 10.48.66.156, sa_prot= 50,
  sa_spi= 0x8312e721(2199054113), sa_trans= esp-des esp-sha-hmac ,
  sa_conn_id= 2

```

ejemplo del comando debug para lluvia

```

snow# show debug
debug crypto ipsec 1

```

```
debug crypto isakmp 1
debug crypto engine
debug icmp trace
debug fover status
txOff
rxOff
openOff
cableOff
txdmpOff
rxdmpOff
ifcOff
rxipOff
txipOff
getOff
putOff
verifyOff
switchOff
failOff
fmsgOff
snow# no debug icmp trace
ICMP trace off
snow#
snow#
snow#
snow#
snow# configure terminal
      ! the      client is connecting !!!!!!!!!!!!!!!
Type help or '?' for a list of available commands.
snow#
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
VPN Peer: ISAKMP: Added new peer: ip:10.48.66.76 Total VPN Peers:1
VPN Peer: ISAKMP: Peer ip:10.48.66.76
      Ref cnt incremented to:1 Total VPN Peers:1
OAK_AG exchange
ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 2 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 3 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are not acceptable. Next payload is 3
ISAKMP (0): Checking ISAKMP transform 4 against priority 10 policy
ISAKMP:      encryption 3DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
```

```
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 5 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 6 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 2
ISAKMP:      extended auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are not acceptable. Next payload is 3
ISAKMP (0):  Checking ISAKMP transform 7 against priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x20 0xc4 0x9b
ISAKMP (0):  atts are acceptable. Next payload is 3
ISAKMP (0):  processing KE payload. message ID = 0

ISAKMP (0):  processing NONCE payload. message ID = 0

ISAKMP (0):  processing ID payload. message ID = 0
ISAKMP (0):  processing vendor id payload

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  remote peer supports dead peer detection

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  speaking to a Unity client

ISAKMP: Created a peer node for 10.48.66.76
ISAKMP (0): ID payload
next-payload : 10
type         : 1
protocol     : 17
port        : 500
length      : 8
ISAKMP (0): Total payload length: 12
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_AG exchange
ISAKMP (0): processing HASH payload. message ID = 0
ISAKMP (0): processing NOTIFY payload 24578 protocol 1
spi 0, message ID = 0
ISAKMP (0): processing notify INITIAL_CONTACTIPSEC(key_engine):
    got a queue event...
IPSEC(key_engine_delete_sas): rec'd delete notify from ISAKMP
IPSEC(key_engine_delete_sas): delete all SAs shared with 10.48.66.76

ISAKMP (0): SA has been authenticated
return status is IKMP_NO_ERROR
```

```
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
ISAKMP_TRANSACTION exchange
ISAKMP (0:0): processing transaction payload from 10.48.66.76.
    message ID = 0
ISAKMP: Config payload CFG_REQUEST
ISAKMP (0:0): checking request:
ISAKMP: attribute    IP4_ADDRESS (1)
ISAKMP: attribute    IP4_NETMASK (2)
ISAKMP: attribute    IP4_DNS (3)
ISAKMP: attribute    IP4_NBNS (4)
ISAKMP: attribute    ADDRESS_EXPIRY (5)
    Unsupported Attr: 5
ISAKMP: attribute    APPLICATION_VERSION (7)
    Unsupported Attr: 7
ISAKMP: attribute    UNKNOWN (28672)
    Unsupported Attr: 28672
ISAKMP: attribute    UNKNOWN (28673)
    Unsupported Attr: 28673
ISAKMP: attribute    UNKNOWN (28674)
ISAKMP: attribute    UNKNOWN (28676)
ISAKMP: attribute    UNKNOWN (28679)
    Unsupported Attr: 28679
ISAKMP: attribute    UNKNOWN (28680)
    Unsupported Attr: 28680
ISAKMP: attribute    UNKNOWN (28677)
    Unsupported Attr: 28677
ISAKMP (0:0): responding to peer config from 10.48.66.76.
    ID = 1245965288
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 2141307752

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:    authenticator is HMAC-MD5
ISAKMP:    encaps is 1
ISAKMP:    SA life type in seconds
ISAKMP:    SA life duration (VPI) of
    0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
    (prot 3, trans 3, hmac_alg 1) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDED proposal (1)
ISAKMP : Checking IPsec proposal 2

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:    authenticator is HMAC-SHA
ISAKMP:    encaps is 1
ISAKMP:    SA life type in seconds
ISAKMP:    SA life duration (VPI) of
    0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
    (prot 3, trans 3, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDED proposal (2)
ISAKMP : Checking IPsec proposal 3

ISAKMP: transform 1, ESP_3DES
```


ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 3, hmac_alg 1) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP : Checking IPsec proposal 4

ISAKMP: transform 1, ESP_3DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-SHA
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 3, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP : Checking IPsec proposal 5

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are acceptable.
ISAKMP (0): bad SPI size of 2 octets!
ISAKMP : Checking IPsec proposal 6

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-SHA
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of
0x0 0x20 0xc4 0x9b IPSEC(validate_proposal): transform proposal
(prot 3, trans 2, hmac_alg 2) not supported

ISAKMP (0): atts not acceptable. Next payload is 0
ISAKMP (0): skipping next ANDed proposal (6)
ISAKMP : Checking IPsec proposal 7

ISAKMP: transform 1, ESP_DES
ISAKMP: attributes in transform:
ISAKMP: authenticator is HMAC-MD5
ISAKMP: encaps is 1
ISAKMP: SA life type in seconds
ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9b
ISAKMP (0): atts are acceptable.IPSEC(validate_proposal_request):
proposal part #1,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 193.0.0.1/255.255.255.255/0/0 (type=1),
src_proxy= 12.0.0.1/255.255.255.255/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload. message ID = 2141307752

ISAKMP (0): processing ID payload. message ID = 2141307752

```
ISAKMP (0): ID_IPV4_ADDR src 12.0.0.1 prot 0 port 0
ISAKMP (0): processing ID payload. message ID = 2141307752
ISAKMP (0): ID_IPV4_ADDR dst 193.0.0.1 prot 0 port 0 IPSEC(key_engine):
    got a queue event...
IPSEC(spi_response): getting spi 0x4f3e0026(1329463334) for SA
from    10.48.66.76 to    193.0.0.1 for prot 3

return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload. message ID = 2151626816

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_3DES
ISAKMP:  attributes in transform:
ISAKMP:      authenticator is HMAC-MD5
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_AUTH_AWAITmap_alloc_entry: allocating entry 3
map_alloc_entry: allocating entry 4

ISAKMP (0): Creating IPsec SAs
    inbound SA from    10.48.66.76 to    193.0.0.1 (proxy
12.0.0.1 to    193.0.0.1)
    has spi 1329463334 and conn_id 3 and flags 4
    lifetime of 2147483 seconds
    outbound SA from    193.0.0.1 to    10.48.66.76 (proxy
193.0.0.1 to    12.0.0.1)
    has spi 1309919057 and conn_id 4 and flags 4
    lifetime of 2147483 secondsIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 193.0.0.1/0.0.0.0/0/0 (type=1),
src_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x4f3e0026(1329463334), conn_id= 3, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.1, dest= 10.48.66.76,
src_proxy= 193.0.0.1/0.0.0.0/0/0 (type=1),
dest_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x4e13c751(1309919057), conn_id= 4, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt
incremented to:2 Total VPN Peers:1
VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt
incremented to:3 Total VPN Peers:1
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.76, dest 193.0.0.1
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_AUTH_AWAITmap_alloc_entry: allocating entry 7
map_alloc_entry: allocating entry 8

ISAKMP (0): Creating IPsec SAs
    inbound SA from    10.48.66.76 to    193.0.0.1 (proxy
12.0.0.1 to    0.0.0.0)
    has spi 857357959 and conn_id 7 and flags 4
```

```
lifetime of 2147483 seconds
outbound SA from      193.0.0.1 to      10.48.66.76 (proxy
0.0.0.0 to          12.0.0.1)
has spi 1657044439 and conn_id 8 and flags 4
lifetime of 2147483 secondsIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.1, src= 10.48.66.76,
dest_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4),
src_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x331a3e87(857357959), conn_id= 7, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.1, dest= 10.48.66.76,
src_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4),
dest_proxy= 12.0.0.1/0.0.0.0/0/0 (type=1),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 2147483s and 0kb,
spi= 0x62c47dd7(1657044439), conn_id= 8, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt incremented to:4 Total VPN Peers:1
VPN Peer: IPSEC: Peer ip:10.48.66.76 Ref cnt incremented to:5 Total VPN Peers:1
return status is IKMP_NO_ERROR602301: sa created, (sa) sa_dest= 193.0.0.1,
sa_prot= 50, sa_spi= 0x4f3e0026(1329463334),
sa_trans= esp-des esp-md5-hmac , sa_conn_id= 3

602301: sa created, (sa) sa_dest= 10.48.66.76, sa_prot= 50,
sa_spi= 0x4e13c751(1309919057), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 4

602301: sa created, (sa) sa_dest= 193.0.0.1, sa_prot= 50,
sa_spi= 0x331a3e87(857357959), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 7

602301: sa created, (sa) sa_dest= 10.48.66.76, sa_prot= 50,
sa_spi= 0x62c47dd7(1657044439), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 8

ISADB: reaper checking SA 0x81153ac0, conn_id = 0
snow#
snow#
snow#
snow# 302010: 0 in use, 0 most used

snow#
snow#
snow#
snow#
snow# ! client will now ping 11.0.0.2
Type help or '?' for a list of available commands.
snow# 6
VPN Peer: ISAKMP: Added new peer: ip:10.48.66.156 Total VPN Peers:2
VPN Peer: ISAKMP: Peer ip:10.48.66.156
Ref cnt incremented to:1 Total VPN Peers:2
ISAKMP (0): beginning Main Mode exchange09001:
Built local-host intf2:11.0.0.

crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against priority 10 policy
ISAKMP: encryption DES-CBC
```

```
ISAKMP:      hash SHA
ISAKMP:      default group 2
ISAKMP:      auth pre-share
ISAKMP:      life type in seconds
ISAKMP:      life duration (VPI) of  0x0 0x1 0x51 0x80
ISAKMP (0):  atts are acceptable. Next payload is 0
ISAKMP (0):  SA is doing pre-shared key authentication
      using id type ID_IPV4_ADDR
return status is IKMP_NO_ERROR2
702303: sa_request, (key eng. msg.
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0):  processing KE payload. message ID = 0

ISAKMP (0):  processing NONCE payload. message ID = 0

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  remote peer supports dead peer detection

ISAKMP (0):  processing vendor id payload

ISAKMP (0):  speaking to another IOS box!

ISAKMP (0):  ID payload
next-payload : 8
type         : 1
protocol     : 17
port         : 500
length       : 8
ISAKMP (0):  Total payload length: 12
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_MM exchange
ISAKMP (0):  processing ID payload. message ID = 0
ISAKMP (0):  processing HASH payload. message ID = 0
ISAKMP (0):  SA has been authenticated

ISAKMP (0):  beginning Quick Mode exchange,
      M-ID of -931180733:c87f4f43IPSEC(key_engine): got a queue event...
IPSEC(spi_response): getting spi 0x661d4fad(1713196973) for SA
from 10.48.66.156 to 193.0.0.5 for prot 3

return status is IKMP_NO_ERROR
ISAKMP (0):  sending INITIAL_CONTACT notify
crypto_isakmp_process_block: src 10.48.66.156, dest 193.0.0.5
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0):  processing SA payload. message ID = 3363786563

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES
ISAKMP:  attributes in transform:
ISAKMP:  encaps is 1
ISAKMP:  SA life type in seconds
ISAKMP:  SA life duration (basic) of 28800
ISAKMP:  SA life type in kilobytes
ISAKMP:  SA life duration (VPI) of  0x0 0x46 0x50 0x0
ISAKMP:  authenticator is HMAC-SHA
ISAKMP (0):  atts are acceptable.IPSEC(validate_proposal_request):
```

```

proposal part #1,
(key eng. msg.) dest= 10.48.66.156, src= 193.0.0.5,
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 0s and 0kb,
  spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload. message ID = 3363786563

ISAKMP (0): processing ID payload. message ID = 3363786563
ISAKMP (0): processing ID payload.
  message ID = 3363786563map_alloc_entry: allocating entry 1
map_alloc_entry: allocating entry 2

ISAKMP (0): Creating IPsec SAs
  inbound SA from 10.48.66.156 to 193.0.0.5 (proxy
11.0.0.0 to 12.0.0.0)
  has spi 1713196973 and conn_id 1 and flags 4
  lifetime of 28800 seconds
  lifetime of 4608000 kilobytes
  outbound SA from 193.0.0.5 to 10.48.66.156 (proxy
12.0.0.0 to 11.0.0.0)
  has spi 2199054113 and conn_id 2 and flags 4
  lifetime of 28800 seconds
  lifetime of 4608000 kilobytesIPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 193.0.0.5, src= 10.48.66.156,
  dest_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  src_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 28800s and 4608000kb,
  spi= 0x661d4fad(1713196973), conn_id= 1, keysize= 0, flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 193.0.0.5, dest= 10.48.66.156,
  src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-sha-hmac ,
  lifedur= 28800s and 4608000kb,
  spi= 0x8312e721(2199054113), conn_id= 2, keysize= 0, flags= 0x4

VPN Peer: IPSEC: Peer ip:10.48.66.156
  Ref cnt incremented to:2 Total VPN Peers:2
VPN Peer: IPSEC: Peer ip:10.48.66.156
  Ref cnt incremented to:3 Total VPN Peers:2
return status is IKMP_NO_ERROR) src= 193.0.0.5,
  dest= 10.48.66.156, src_proxy= 12.0.0.0/255.255.255.0/0/0 (type=4),
  dest_proxy= 11.0.0.0/255.255.255.0/0/0 (type=4), protocol= ESP,
  transform= esp-des esp-sha-hmac , lifedur= 28800s and 4608000kb,
  spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4004

602301: sa created, (sa) sa_dest= 193.0.0.5, sa_prot= 50,
  sa_spi= 0x661d4fad(1713196973), sa_trans= esp-des esp-sha-hmac ,
  sa_conn_id= 1

602301: sa created, (sa) sa_dest= 10.48.66.156, sa_prot= 50,
  sa_spi= 0x8312e721(2199054113), sa_trans= esp-des esp-sha-hmac ,
  sa_conn_id= 2

```

[Información Relacionada](#)

- [Página de soporte para cliente Cisco VPN](#)
- [Página de soporte de IPsec](#)

- [Página de Soporte de PIX](#)
- [Solicitudes de Comentarios \(RFC\)](#)
- [Soporte Técnico - Cisco Systems](#)