

Cómo configurar un IPSec del LAN a LAN entre un router y un PIX usando los Certificados digitales

Contenido

[Introducción](#)

[Antes de comenzar](#)

[Convenciones](#)

[prerrequisitos](#)

[Componentes Utilizados](#)

[Teoría Precedente](#)

[Diagrama de la red](#)

[Configuración del router y del escudo de protección de PIX](#)

[Configuraciones](#)

[Obtener certificados](#)

[Obtenga certificados del router](#)

[Obtener certificados en PIX](#)

[Verificación](#)

[Ejemplo de resultado de los comandos show del router](#)

[Salida de muestra de comandos show de PIX](#)

[Troubleshooting](#)

[Comandos para resolución de problemas](#)

[Ejemplo de depuración de certificado desde el router](#)

[Muestra del debug del certificado desde PIX](#)

[Ejemplo de depuración de IPSec desde el router](#)

[Depuración IPSec de ejemplo desde el PIX](#)

[Problemas posibles](#)

[Elimine los certificados y los pares de claves RSA](#)

[Información Relacionada](#)

[Introducción](#)

Este documento ilustra cómo configurar un router Cisco y un Cisco Secure PIX Firewall para implementar IPSec de LAN a LAN mediante certificados digitales. Para alcanzar esta configuración, usted necesita realizar las tareas siguientes:

1. Configure el router y el PIX.
2. Obtenga los Certificados digitales en el router y el PIX.
3. Configure el IKE y las políticas IPSec en el router y el PIX, y defina qué tráfico (tráfico

interesante) será cifrado usando el IPSec a través de una lista de acceso.

Antes de comenzar

Convenciones

Para obtener más información sobre las convenciones del documento, consulte [Convenciones de Consejos Técnicos de Cisco](#).

prerrequisitos

No hay requisitos previos específicos para este documento.

Componentes Utilizados

La información que contiene este documento se basa en las versiones de software y hardware indicadas a continuación.

- Cisco 1700 Router
- Versión de software de Cisco IOS® 12.2(6)
- Cisco PIX Firewall 520
- Versión 6.0.1 del firewall PIX.

La información que se presenta en este documento se originó a partir de dispositivos dentro de un ambiente de laboratorio específico. Todos los dispositivos que se utilizan en este documento se pusieron en funcionamiento con una configuración verificada (predeterminada). Si la red está funcionando, asegúrese de haber comprendido el impacto que puede tener un comando antes de ejecutarlo.

Teoría Precedente


En nuestro ejemplo, hemos definido la dirección de red del host A (dirección de origen) y a la dirección de red del host B (dirección destino) como el tráfico que el IPSec cifrará en el PIX. La lista de acceso en el router es la imagen espejo de la lista de acceso en el PIX.

Hemos configurado el PIX y al router de modo que los host que residen en el LAN interior de los dos dispositivos utilicen a sus direcciones privadas mientras que pasen a través del túnel IPsec. En el PIX, los comandos access-list y nat 0 funcionan de manera conjunta. Cuando el host A en la red de 192.168.4.0 va a la red de 1.1.1.0, la lista de acceso permite que el tráfico de la red de 192.168.4.0 sea cifrado sin el Network Address Translation (NAT). Sin embargo, cuando van esos mismos usuarios en cualquier parte, los traducen al direccionamiento de 172.16.172.57 con el Port Address Translation (PAT). En el router, los **comandos route-map and access-list** permiten que el tráfico de la red de 1.1.1.0 sea cifrado sin el NAT. Sin embargo, cuando va el mismo host B en cualquier parte, los traducen al direccionamiento de 172.16.172.39 a través del patente.

Para probar la configuración, hicimos ping del host A detrás del firewall PIX al host B detrás del router. Cuando el paquete del IP llegó el firewall PIX, correspondió con la lista de acceso e inició así el IPSec Negotiation. Así el PIX es el iniciador y el router es el respondedor durante el IPSec Negotiation. Para los propósitos de Troubleshooting, usted necesita examinar los debugs PIX y de la criptografía del router.

[Diagrama de la red](#)

Este documento utiliza la instalación de red que se muestra en el siguiente diagrama.



[Configuración del router y del escudo de protección de PIX](#)

[Configuraciones](#)

En esta sección encontrará la información para configurar las funciones descritas en este

documento.

- [Ejemplo de configuración del router](#)
- [Configuración de muestra PIX](#)

Ejemplo de configuración del router

```
1720-1#show running-config
Building configuration...

Current configuration : 8694 bytes
!
! Last configuration change at 20:17:48 PST Thu Jan 10
2002
! NVRAM config last updated at 20:19:27 PST Thu Jan 10
2002
!
version 12.2
no parser cache
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname 1720-1
!
no logging buffered
enable secret 5 $1$6jAs$tNxI1a/2DYFAtPLyCDXjo/
enable password ww
!
username cisco password 0 cisco
username all
memory-size iomem 15
clock timezone PST -8
ip subnet-zero
no ip domain-lookup
ip domain-name cisco.com
!
ip ssh time-out 120
ip ssh authentication-retries 3
!
!
!
crypto ca identity vpn
  enrollment retry count 20
  enrollment mode ra
  enrollment url http://171.69.89.16:80
  query url ldap://171.69.89.16
crypto ca certificate chain vpn
  certificate 3B2FD652
    308202C4 3082022D A0030201 0202043B 2FD65230 0D06092A
864886F7 0D010105
      0500302D 310B3009 06035504 06130275 73310E30 0C060355
040A1305 63697363
        6F310E30 0C060355 040B1305 736A7670 6E301E17 0D303230
31313130 33303631
          345A170D 30333031 31313033 33363134 5A304E31 0B300906
03550406 13027573
            310E300C 06035504 0A130563 6973636F 310E300C 06035504
0B130573 6A76706E
              311F301D 06092A86 4886F70D 01090216 10313732 302D312E
63697363 6F2E636F
                6D305C30 0D06092A 864886F7 0D010101 0500034B 00304802
4100A085 B4A756F8
```

CEB91F2E 52E2A23F 847EC95F 44F65AF2 EBC1F816 081CC61F
AB077482 F1FAD124
2444B9F6 6B9EC48E 1B1EB5B9 D0E802BA B9A57048 EBB8CD18
773F0203 010001A3
82011230 82010E30 0B060355 1D0F0404 030205A0 301B0603
551D1104 14301282
10313732 302D312E 63697363 6F2E636F 6D302B06 03551D10
04243022 800F3230
30323031 31313033 30363134 5A810F32 30303230 39323331
35333631 345A304F
0603551D 1F044830 463044A0 42A040A4 3E303C31 0B300906
03550406 13027573
310E300C 06035504 0A130563 6973636F 310E300C 06035504
0B130573 6A76706E
310D300B 06035504 03130443 524C3130 1F060355 1D230418
30168014 46C1609C
DBEA53EE 80A48060 1A96583B 0DF80D2F 301D0603 551D0E04
160414B1 2707AB30
F7CFDC79 C554D1AE 3208EF16 CF96ED30 09060355 1D130402
30003019 06092A86
4886F67D 07410004 0C300A1B 0456352E 30030204 B0300D06
092A8648 86F70D01
01050500 03818100 E82DE82B AE5C7F80 EB9CED1A 306F36E6
437DA791 81D53CF3
0E561C8A 7A168EDE 6728F371 3EB90B21 CC40E1F3 CA4ED98F
CDFA6E15 A2C0AA38
4AE137C7 281AA7EC AD26D550 4E4AAA0B E0C588F8 661C4031
ACF35F7B 28330B64
667E00E3 832AED7F 08D5EA3D 33CCB2BE E73DC41A B40A9B64
4CD2D98C 6943AE84
55605741 E136A6BD
quit
certificate ra-sign 3B2FD319
308202FF 30820268 A0030201 0202043B 2FD31930 0D06092A
864886F7 0D010105
0500302D 310B3009 06035504 06130275 73310E30 0C060355
040A1305 63697363
6F310E30 0C060355 040B1305 736A7670 6E301E17 0D303130
36313932 32303333
315A170D 30343036 31393232 33333331 5A304531 0B300906
03550406 13027573
310E300C 06035504 0A130563 6973636F 310E300C 06035504
0B130573 6A76706E
31163014 06035504 03130D46 69727374 204F6666 69636572
30819F30 0D06092A
864886F7 0D010101 05000381 8D003081 89028181 00E85434
395790E9 416ED13D
72F1A411 333A0984 66B8F68A 0ECA7E2B CBC40C39 A21E2D8A
5F94772D 69846720
73227891 E43D46B6 B2D1DDC5 385C5135 DB2075F1 4D252ACF
AC80DA4C 2111946F
26F7193B 8EA1CA66 8332D2A1 5310B2D7 07C985A8 0B44CE37
BC95EAFB C328D4C6
73B3B35E 0F6D25F5 DCAC6AFA 2DAAD6D1 47BB3396 E1020301
0001A382 01123082
010E300B 0603551D 0F040403 02078030 2B060355 1D100424
3022800F 32303031
30363139 32323033 33315A81 0F323030 33303732 37303233
3333315A 301B0603
551D0904 14301230 1006092A 864886F6 7D07441D 31030201
00304F06 03551D1F
04483046 3044A042 A040A43E 303C310B 30090603 55040613
02757331 0E300C06
0355040A 13056369 73636F31 0E300C06 0355040B 1305736A

```
76706E31 0D300B06
 03550403 13044352 4C31301F 0603551D 23041830 16801446
C1609CDB EA53EE80
  A480601A 96583B0D F80D2F30 1D060355 1D0E0416 04147BD2
620C611F 3AC69FB3
 155FD8F9 8A7CF353 3A583009 0603551D 13040230 00301906
092A8648 86F67D07
 4100040C 300A1B04 56352E30 030204B0 300D0609 2A864886
F70D0101 05050003
 8181003A A6431D7D 1979DDF9 CC99D8F8 CC987F67 DBF67280
2A9418E9 C6255B08
  DECDE1C2 50FCB1A6 544F1D51 C214162E E2403DAB 2F1294C4
841240ED FD6F799C
 130A0B24 AC74DD74 C60EB5CD EC648631 E0B88B3F 3D19A2E1
6492958E 9F64746E
 45C080AE E5A6C245 7827D7B1 380A6FE8 A01D9022 7F52AD9C
B596743A 853549C5 771DA2
quit
certificate ra-encrypt 3B2FD318
 308202D0 30820239 A0030201 0202043B 2FD31830 0D06092A
864886F7 0D010105
 0500302D 310B3009 06035504 06130275 73310E30 0C060355
040A1305 63697363
 6F310E30 0C060355 040B1305 736A7670 6E301E17 0D303130
36313932 32303333

 315A170D 30343036 31393232 33333331 5A304531 0B300906
03550406 13027573
 310E300C 06035504 0A130563 6973636F 310E300C 06035504
0B130573 6A76706E
 31163014 06035504 03130D46 69727374 204F6666 69636572
30819F30 0D06092A
 864886F7 0D010101 05000381 8D003081 89028181 00BFC427
727E15E9 30CB1BCB
  C0EFFF2F 3E4916D4 EC365F57 C13D1356 6388E66D 7BCCBCB9
04DA2E7C C9639F31
  AF15E7B1 E698A33C 0EB447E4 B3B72EC8 766EADCF 9883E612
AD782E39 B0603A90
 0322CE78 D6735E07 BDC022F1 1164EC9E 31FC5309 9AA9DC1D
69ECC316 8727A6CB
  ADCFB488 FF904D6D 9D9E5778 05B24D4B BB5B4F5F 4D020301
0001A381 E43081E1
 300B0603 551D0F04 04030205 20301B06 03551D09 04143012
30100609 2A864886
  F67D0744 1D310302 0100304F 0603551D 1F044830 463044A0
42A040A4 3E303C31
 0B300906 03550406 13027573 310E300C 06035504 0A130563
6973636F 310E300C
 06035504 0B130573 6A76706E 310D300B 06035504 03130443
524C3130 1F060355
 1D230418 30168014 46C1609C DBEA53EE 80A48060 1A96583B
0DF80D2F 301D0603
 551D0E04 16041400 A7C3DD9F 9FAB0A25 E1485FC7 DB88A63F
78CE4830 09060355
 1D130402 30003019 06092A86 4886F67D 07410004 0C300A1B
0456352E 30030204
  B0300D06 092A8648 86F70D01 01050500 03818100 69105382
0BE0BA59 B0CD2652
 9C6A4585 940C7882 DCEB1D1E 610B8525 0C032A76 2C8758C2
F5CA1EF4 B946848A
  C49047D5 6D1EF218 FA082A00 16CCD9FC 42DF3B05 A8EF2AAD
151637DE 67885BB2
  BA0BB6A1 308F63FF 21C3CB00 9272257A 3C292645 FD62D486
C247F067 301C2FEE
```

```
5CF6D12B 6CFA1DAA E74E8B8E 5B017A2E 5BB6C5F9
quit
certificate ca 3B2FD307
 308202E4 3082024D A0030201 0202043B 2FD30730 0D06092A
864886F7 0D010105
 0500302D 310B3009 06035504 06130275 73310E30 0C060355
040A1305 63697363
 6F310E30 0C060355 040B1305 736A7670 6E301E17 0D303130
36313932 32303234
 305A170D 32313036 31393232 33323430 5A302D31 0B300906
03550406 13027573
 310E300C 06035504 0A130563 6973636F 310E300C 06035504
0B130573 6A76706E
 30819F30 0D06092A 864886F7 0D010101 05000381 8D003081
89028181 00E8C25B
 EDF4A6EE A352B142 C16578F4 FBDAF45E 4F2F7733 8D2B8879
96138C63 1DB713BF
 753BF845 2D7E600F AAF4D75B 9E959513 BB13FF13 36696F48
86C464F2 CF854A66
 4F8E83F8 025F216B A44D4BB2 39ADD1A5 1BCCF812 09A19BDC
468EEAE1 B6C2A378
 69C81348 1A9CD61C 551216F2 8B168FBB 94CBEF37 E1D9A8F7
80BBC17F D1020301
 0001A382 010F3082 010B3011 06096086 480186F8 42010104
04030200 07304F06
 03551D1F 04483046 3044A042 A040A43E 303C310B 30090603
55040613 02757331
 0E300C06 0355040A 13056369 73636F31 0E300C06 0355040B
1305736A 76706E31
 0D300B06 03550403 13044352 4C31302B 0603551D 10042430
22800F32 30303130
 36313932 32303234 305A810F 32303231 30363139 32323332
34305A30 0B060355
 1D0F0404 03020106 301F0603 551D2304 18301680 1446C160
9CDBEA53 EE80A480
 601A9658 3B0DF80D 2F301D06 03551D0E 04160414 46C1609C
DBEA53EE 80A48060
 1A96583B 0DF80D2F 300C0603 551D1304 05300301 01FF301D
06092A86 4886F67D
 07410004 10300E1B 0856352E 303A342E 30030204 90300D06
092A8648 86F70D01
 01050500 03818100 7E3DBAC4 8CAE7D5A B19C0625 8780D222
F965A1A2 C0C25B84
 CBC5A203 BF50FAC4 9656699A 52D8CB46 40776237 87163118
8F3C0F47 D2CAA36B
 6AB34F99 AB71269E 78C0AC10 DA0B9EC5 AE448B46 701254CF
3EBC64C1 5DBB2EE5
 56C0140B B0C83497 D79FB148 80018F51 3A4B6174 590B85AA
9CE3B391 629406AA
 7CE9CC0D 01593E6B
quit
!
crypto isakmp policy 10
 hash md5
crypto isakmp identity hostname
!
!
crypto ipsec transform-set myset esp-des esp-md5-hmac
!
!
crypto map vpn 10 ipsec-isakmp
 set peer 172.16.172.34
 set transform-set myset
```

```

match address 130
!
!
!
!
!
interface Loopback0
 ip address 10.10.10.1 255.255.255.0
!
interface Loopback1
 ip address 121.1.1.1 255.255.255.0
!
interface Loopback88
 ip address 88.88.88.88 255.255.255.255
!
interface FastEthernet0
 ip address 172.16.172.39 255.255.255.240
 ip nat outside
 speed auto
 crypto map vpn
!
interface Serial0
 ip nat inside
 ip address 1.1.1.1 255.255.255.252
!
 ip nat inside source route-map nonat interface
 FastEthernet0 overload
 ip classless
 ip route 0.0.0.0 0.0.0.0 172.16.172.33
 no ip http server
 ip pim bidir-enable
!
 access-list 120 deny ip 1.1.1.0 0.0.0.255 192.168.4.0
 0.0.0.255
 access-list 120 permit ip 1.1.1.0 0.0.0.255 any
 access-list 130 permit ip 1.1.1.0 0.0.0.255 192.168.4.0
 0.0.0.255
 route-map nonat permit 10
 match ip address 120
!
 line con 0
 line aux 0
 line vty 0 4
  exec-timeout 0 0
  password cisco
  no login
 line vty 5 15
  login
!
 no scheduler allocate
end

```

Configuración de muestra PIX

```

pix520-1# write terminal
Building configuration...
: Saved
:
PIX Version 6.0(1)
nameif ethernet0 outside security0
nameif ethernet1 inside security100
enable password 2KFQnbNIdI.2KYOU encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname pix520-1
domain-name vpn.com

```



```
fixup protocol ftp 21
fixup protocol http 80
fixup protocol h323 1720
fixup protocol rsh 514
fixup protocol smtp 25
fixup protocol sqlnet 1521
fixup protocol sip 5060
fixup protocol skinny 2000
names
access-list 130 permit ip 192.168.4.0 255.255.255.0
1.1.1.0 255.255.255.0
access-list 140 permit ip 192.168.4.0 255.255.255.0
1.1.1.0 255.255.255.0
no pager
logging on
logging monitor debugging
logging buffered debugging
logging trap debugging
logging history debugging
logging host outside 192.168.2.6
interface ethernet0 auto
interface ethernet1 auto
mtu outside 1500
mtu inside 1500
ip address outside 172.16.172.34 255.255.255.240
ip address inside 192.168.4.50 255.255.255.0
ip audit info action alarm
ip audit attack action alarm
no failover
failover timeout 0:00:00
failover poll 15
failover ip address outside 0.0.0.0
failover ip address inside 0.0.0.0
pdm history enable
arp timeout 14400
global (outside) 1 172.16.172.57 netmask 255.255.255.255
nat (inside) 0 access-list 140
nat (inside) 1 0.0.0.0 0.0.0.0 0 0
route outside 0.0.0.0 0.0.0.0 172.16.172.33 1
timeout xlate 3:00:00
timeout conn 1:00:00 half-closed 0:10:00 udp 0:02:00 rpc
0:10:00
h323 0:05:00 sip 0:30:00 sip_media 0:02:00
timeout uauth 0:05:00 absolute
aaa-server TACACS+ protocol tacacs+
aaa-server RADIUS protocol radius
aaa-server mytest protocol tacacs+
aaa-server nasir protocol radius
snmp-server host outside 192.168.2.6
no snmp-server location
no snmp-server contact
snmp-server community public
snmp-server enable traps
floodguard enable
sysopt connection permit-ipsec
no sysopt route dnat
crypto ipsec transform-set myset esp-des esp-md5-hmac
crypto map mymap 5 ipsec-isakmp
crypto map mymap 5 match address 130
crypto map mymap 5 set peer 172.16.172.39
crypto map mymap 5 set transform-set myset
crypto map mymap interface outside
isakmp enable outside
isakmp policy 10 authentication rsa-sig
```

```
isakmp policy 10 encryption des
isakmp policy 10 hash md5
isakmp policy 10 group 1
isakmp policy 10 lifetime 86400
ca identity cisco 171.69.89.16:/cgi-bin 171.69.89.16
ca configure cisco ra 20 5
telnet 192.168.4.0 255.255.255.0 inside
telnet 171.69.89.82 255.255.255.255 inside
telnet 192.168.4.3 255.255.255.255 inside
telnet timeout 5
ssh 172.0.0.0 255.0.0.0 outside
ssh 171.0.0.0 255.255.255.0 outside
ssh 171.0.0.0 255.0.0.0 outside
ssh 171.0.0.0 255.0.0.0 inside
ssh timeout 60
terminal width 80
Cryptochecksum:c2d5976fc87875678356cf83b135bb8c
: end
[OK]
pix520-1#
```

[Obtener certificados](#)

[Obtenga certificados del router](#)

Esta sección describe cómo obtener los Certificados digitales en el router.

1. Configure el nombre del host del router y el Domain Name IP si esto no se ha hecho

```
Ya.pix520-1# write terminal
Building configuration...
: Saved
:
PIX Version 6.0(1)
nameif ethernet0 outside security0
nameif ethernet1 inside security100
enable password 2KFQnbNIdI.2KYOU encrypted
passwd 2KFQnbNIdI.2KYOU encrypted
hostname pix520-1
domain-name vpn.com
fixup protocol ftp 21
fixup protocol http 80
fixup protocol h323 1720
fixup protocol rsh 514
fixup protocol smtp 25
fixup protocol sqlnet 1521
fixup protocol sip 5060
fixup protocol skinny 2000
names
access-list 130 permit ip 192.168.4.0 255.255.255.0 1.1.1.0 255.255.255.0
access-list 140 permit ip 192.168.4.0 255.255.255.0 1.1.1.0 255.255.255.0
no pager
logging on
logging monitor debugging
logging buffered debugging
logging trap debugging
logging history debugging
logging host outside 192.168.2.6
interface ethernet0 auto
interface ethernet1 auto
mtu outside 1500
```

```
mtu inside 1500
ip address outside 172.16.172.34 255.255.255.240
ip address inside 192.168.4.50 255.255.255.0
ip audit info action alarm
ip audit attack action alarm
no failover
failover timeout 0:00:00
failover poll 15
failover ip address outside 0.0.0.0
failover ip address inside 0.0.0.0
pdm history enable
arp timeout 14400
global (outside) 1 172.16.172.57 netmask 255.255.255.255
nat (inside) 0 access-list 140
nat (inside) 1 0.0.0.0 0.0.0.0 0 0
route outside 0.0.0.0 0.0.0.0 172.16.172.33 1
timeout xlate 3:00:00
timeout conn 1:00:00 half-closed 0:10:00 udp 0:02:00 rpc 0:10:00
h323 0:05:00 sip 0:30:00 sip_media 0:02:00
timeout uauth 0:05:00 absolute
aaa-server TACACS+ protocol tacacs+
aaa-server RADIUS protocol radius
aaa-server mytest protocol tacacs+
aaa-server nasir protocol radius
snmp-server host outside 192.168.2.6
no snmp-server location
no snmp-server contact
snmp-server community public
snmp-server enable traps
floodguard enable
sysopt connection permit-ipsec
no sysopt route dnat
crypto ipsec transform-set myset esp-des esp-md5-hmac
crypto map mymap 5 ipsec-isakmp
crypto map mymap 5 match address 130
crypto map mymap 5 set peer 172.16.172.39
crypto map mymap 5 set transform-set myset
crypto map mymap interface outside
isakmp enable outside
isakmp policy 10 authentication rsa-sig
isakmp policy 10 encryption des
isakmp policy 10 hash md5
isakmp policy 10 group 1
isakmp policy 10 lifetime 86400
ca identity cisco 171.69.89.16:/cgi-bin 171.69.89.16
ca configure cisco ra 20 5
telnet 192.168.4.0 255.255.255.0 inside
telnet 171.69.89.82 255.255.255.255 inside
telnet 192.168.4.3 255.255.255.255 inside
telnet timeout 5
ssh 172.0.0.0 255.0.0.0 outside
ssh 171.0.0.0 255.255.255.0 outside
ssh 171.0.0.0 255.0.0.0 outside
ssh 171.0.0.0 255.0.0.0 inside
ssh timeout 60
terminal width 80
Cryptochecksum:c2d5976fc87875678356cf83b135bb8c
: end
[OK]
```

pix520-1# **Nota:** El nombre del host y el Domain Name se requieren porque el router asigna un nombre de dominio completo (FQDN) a las claves y a los Certificados usados por el IPSec, sobre la base del nombre del host y del Domain Name IP que usted asigna al

router. Por ejemplo, un certificado se nombra "router.cisco.com" basado en un nombre del host del router del "router" y un Domain Name IP del router del "cisco.com."

2. Genere el par clave RSA para el router, que se utiliza para firmar y para cifrar los mensajes de la administración de claves IKE. Usted necesita generar el par clave para obtener un certificado para el router.

```
1720-1(config)#crypto key generate rsa
The name for the keys will be: 1720-1.cisco.com
Choose the size of the key modulus in the range of 360 to 2048 for your
General Purpose Keys. Choosing a key modulus greater than 512 may take a few minutes.
```

```
How many bits in the modulus [512]:
Generating RSA keys ...
[OK]
```

1720-1(config)#**Utilice el comando show crypto key mypubkey rsa de ver el par clave RSA del router.**

```
1720-1#sh cr key mypubkey rsa
% Key pair was generated at: 19:26:22 PST Jan 10 2002
Key name: 1720-1.cisco.com
Usage: General Purpose Key
Key Data:
 305C300D 06092A86 4886F70D 01010105 00034B00 30480241 00A085B4 756F8CE
 B91F2E52 E2A23F84 7EC95F44 F65AF2EB C1F81608 1CC61FAB 077482F1 FAD12424
 44B9F66B 9EC48E1B 1EB5B9D0 E802BAB9 A57048EB B8CD1877 3F020301 0001
```

```
% Key pair was generated at: 19:26:24 PST Jan 10 2002
Key name: 1720-1.cisco.com.server
Usage: Encryption Key
Key Data:
 307C300D 06092A86 4886F70D 01010105 00036B00 30680261 00C653F7 2AE7E397
 0041E273 BFCC0E35 E7AF9874 A73B77E8 B15EF54A CA2417AD AB75BAD9 BA1540F4
 3DB849BD B70DF4D8 EBBE7ED AB93BE4B 5C1E9E6A 560A9C8A 12D7CBE3 060DBE7E
 8C1667AE 93993049 DA362602 4E4D9EF8 2F8C4777 30F9F958 7F020301 0001
```

```
1720-1#
```

3. Declare el servidor del Certification Authority (CA) para configurar los parámetros de comunicación entre el router y CA. Si estamos utilizando una autoridad de registro, después también especificamos el modo del registration authority (RA). Utilice el comando **crl optional** si usted quisiera que los Certificados de los otros pares fueran validados por el router incluso si el Listas de revocación de certificados (CRL) apropiado no es accesible al router.

```
1720-1(config)# crypto ca identity vpn
1720-1(ca-identity)#enrollment url http://171.69.89.16:80
1720-1(ca-identity)# query url ldap://171.69.89.16
1720-1(ca-identity)# enrollment retry count 20
1720-1(ca-identity)# enrollment retry period 5
1720-1(ca-identity)# enrollment mode ra
1720-1(ca-identity)#exit
```

4. El router necesita autenticar CA obteniendo el certificado autofirmado de CA que contiene la clave pública de CA. Porque CA firma su propio certificado, la clave pública de CA debe ser autenticada manualmente entrando en contacto al administrador de CA para comparar la huella dactilar del certificado de CA. En este ejemplo, autenticamos manualmente la clave pública comparando las dos huellas dactilares después de que recibamos el certificado CA, bastante que ingresandolo con un enunciado de comando.

```
1720-1(config)#cr ca authenticate
Certificate has the following attributes:
Fingerprint: 1FCDF2C8 2DEDA6AC 4819D4C4 B4CFF2F5
% Do you accept this certificate? [yes/no]: y
1720-1(config)#Utilice el comando sh crypto ca cert de ver los Certificados de CA y RA y de verificarlos que la autenticación era acertada.
```

```
1720-1#sh cr ca cert
```

RA Signature Certificate

Status: Available

!--- The authentication was successful. Certificate Serial Number: 3B2FD319 Key Usage: Signature Issuer: OU = sjvpn O = cisco C = us Subject: CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 14:03:31 PST Jun 19 2001 end date: 14:33:31 PST Jun 19 2004 Associated Identity: vpn RA KeyEncipher Certificate Status: Available

!--- The authentication was successful. Certificate Serial Number: 3B2FD318 Key Usage: Encryption Issuer: OU = sjvpn O = cisco C = us Subject: CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 14:03:31 PST Jun 19 2001 end date: 14:33:31 PST Jun 19 2004 Associated Identity: vpn CA Certificate Status: Available

!--- The authentication was successful. Certificate Serial Number: 3B2FD307 Key Usage: General Purpose Issuer: OU = sjvpn O = cisco C = us Subject: OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 14:02:40 PST Jun 19 2001 end date: 14:32:40 PST Jun 19 2021 Associated Identity: vpn

5. Obtenga un certificado firmado de CA para cada uno de los pares claves RSA del router. Si usted generó las claves de fines generales RSA, el router tiene un par clave RSA y necesita solamente un certificado. Si usted generó las claves especiales del uso RSA, después el router tiene dos pares claves RSA y necesita dos Certificados. Usted tiene que entrar en contacto al administrador de CA para conceder manualmente los certificados del router si se configura en el servidor de CA. También, si se configura el servidor de CA de modo que usted tenga que proporcionar la contraseña a la hora de la inscripción, después administrador de CA del contacto para esta contraseña. En este ejemplo, el servidor de CA fue configurado de modo que no necesitáramos proporcionar una contraseña durante la inscripción.

```
1720-1(config)#cr ca enroll vpn
%
% Start certificate enrollment ..
% Create a challenge password. You will need to verbally provide this
  password to the CA Administrator in order to revoke your certificate.
  For security reasons your password will not be saved in the configuration.
  Please make a note of it.
```

Password:

Re-enter password:

```
% The subject name in the certificate will be: 1720-1.cisco.com
% Include the router serial number in the subject name? [yes/no]: n
% Include an IP address in the subject name? [yes/no]: n
Request certificate from CA? [yes/no]: y
% Certificate request sent to Certificate Authority
% The certificate request fingerprint will be displayed.
% The 'show crypto ca certificate' command will also show the fingerprint.
```

```
1720-1(config)#      Fingerprint:  A1D6C28B 6575AD08 F0B656D4 7161F76F
```

3d09h: CRYPTO_PKI: status = 102: *certificate request pending* Después de que ejecutemos los comandos para la inscripción, el router comunica con el servidor de CA e intenta conseguir su certificado. Durante este tiempo, si el servidor de CA se configura para requerir una autenticación manual de los Certificados, después su necesidad de la voluntad de entrar en contacto al administrador de CA. Utilice el comando **sh crypto ca cert** de ver el certificado del router y de verificarlo que la inscripción ha sido acertada. En el siguiente ejemplo, los Certificados no se han aprobado.

```
1720-1#sh crypto ca cert
```

RA Signature Certificate

Status: Available

Certificate Serial Number: 3B2FD319

Key Usage: Signature

Issuer:

OU = sjvpn
O = cisco
C = us
Subject:
CN = First Officer
OU = sjvpn
O = cisco
C = us
CRL Distribution Point:
CN = CRL1, OU = sjvpn, O = cisco, C = us
Validity Date:
start date: 14:03:31 PST Jun 19 2001
end date: 14:33:31 PST Jun 19 2004
Associated Identity: vpn

RA KeyEncipher Certificate

Status: Available
Certificate Serial Number: 3B2FD318
Key Usage: Encryption
Issuer:
OU = sjvpn
O = cisco
C = us
Subject:
CN = First Officer
OU = sjvpn
O = cisco
C = us
CRL Distribution Point:
CN = CRL1, OU = sjvpn, O = cisco, C = us
Validity Date:
start date: 14:03:31 PST Jun 19 2001
end date: 14:33:31 PST Jun 19 2004
Associated Identity: vpn

CA Certificate

Status: Available
Certificate Serial Number: 3B2FD307
Key Usage: General Purpose
Issuer:
OU = sjvpn
O = cisco
C = us
Subject:
OU = sjvpn
O = cisco
C = us
CRL Distribution Point:
CN = CRL1, OU = sjvpn, O = cisco, C = us
Validity Date:
start date: 14:02:40 PST Jun 19 2001
end date: 14:32:40 PST Jun 19 2021
Associated Identity: vpn

Certificate

Subject Name Contains:
Name: 1720-1.cisco.com
Status: Pending
!--- The certificate is still pending. Key Usage: General Purpose Fingerprint: A1D6C28B
6575AD08 F0B656D4 7161F76F Associated Identity: vpn **La salida de siguiente ejemplo muestra
que el certificado se ha recibido de CA.**3d09h: %CRYPTO-6-CERTRET: *Certificate received from
Certificate Authority 1720-1#sh crypto ca cert*

Certificate

Status: Available

!--- This status indicates that the certificates were successfully received. Certificate
Serial Number: 3B2FD652 Key Usage: General Purpose Issuer: OU = sjvpn O = cisco C = us
Subject Name Contains: Name: 1720-1.cisco.com CRL Distribution Point: CN = CRL1, OU =
sjvpn, O = cisco, C = us Validity Date: start date: 19:06:14 PST Jan 10 2002 end date:
19:36:14 PST Jan 10 2003 Associated Identity: vpn RA Signature Certificate Status:
Available Certificate Serial Number: 3B2FD319 Key Usage: Signature Issuer: OU = sjvpn O =
cisco C = us Subject: CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution
Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 14:03:31 PST Jun
19 2001 end date: 14:33:31 PST Jun 19 2004 Associated Identity: vpn RA KeyEncipher
Certificate Status: Available Certificate Serial Number: 3B2FD318 Key Usage: Encryption
Issuer: OU = sjvpn O = cisco C = us Subject: CN = First Officer OU = sjvpn O = cisco C = us
CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date:
14:03:31 PST Jun 19 2001 end date: 14:33:31 PST Jun 19 2004 Associated Identity: vpn CA
Certificate Status: Available Certificate Serial Number: 3B2FD307 Key Usage: General
Purpose Issuer: OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn,
O = cisco, C = us Validity Date: start date: 14:02:40 PST Jun 19 2001 end date: 14:32:40
PST Jun 19 2021 Associated Identity: vpn

6. Usted puede pedir manualmente CA para el CRL. Para poner al día el CRL en el router, utilice el siguiente comando:

```
1720-1(config)#crypto ca crl request vpn  
1720-1(config)#exit
```

Utilice el comando `show crypto ca crls` de ver el CRL.

```
1720-1#sh crypto ca crls  
CRL Issuer Name:  
  OU = sjvpn, O = cisco, C = us  
  LastUpdate: 16:17:34 PST Jan 10 2002  
  NextUpdate: 17:17:34 PST Jan 11 2002  
  Retrieved from CRL Distribution Point:  
    LDAP: CN = CRL1, OU = sjvpn, O = cisco, C = us
```

1720-1#

7. Publique un comando `write mem` de salvar la configuración.

```
1720-1# wr m  
Building configuration?  
[OK]  
1720-1#
```

Obtener certificados en PIX

Para conseguir los Certificados en un firewall PIX, usted seguirá los mismos pasos que en el router. Sin embargo, el sintaxis del comando pix es diferente.

1. Fije el nombre del host y el Domain Name IP.

```
hostname pix520-1  
domain-name vpn.com
```

2. Genere el par clave RSA.

```
pix520-1(config)# ca generate rsa key 512  
Utilice el comando show ca mypubkey rsa de visualizar el par clave RSA.  
pix520-1(config)# sh ca mypubkey rsa
```

```
% Key pair was generated at: 04:54:34 Jan 11 2002
```

```
Key name: pix520-1.vpn.com  
Usage: General Purpose Key  
Key Data:
```

```
305c300d 06092a86 4886f70d 01010105 00034b00 30480241 009d95d5 e1147546  
1f9ef873 81a36256 4b81388b 188fbc66 40fc4c56 c1801311 ff450cca e8d715c3  
ffb8fa28 d347120f ae8a9972 3a88321c a71c1c7f ef29b810 2f020301 0001
```

```
pix520-1(config)#
```

3. Declare el servidor de CA.

```
pix520-1(config)# ca identity cisco 171.69.89.16 171.69.89.16  
pix520-1(config)# ca configure cisco ra 20 5
```

4. Autentique CA.pix520-1(config)# **ca authenticate cisco**

Certificate has the following attributes:

Fingerprint: 1fcdcf2c8 2deda6ac 4819d4c4 b4cff2f5

pix520-1(config)# **Utilice el comando show ca cert de ver el certificado de CA en el**

PIX.pix520-1(config)# sh ca cert

CA Certificate

Status: Available !--- The authentication was successful. Certificate Serial Number: 3b2fd307 Key Usage: General Purpose OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:02:40 Jun 19 2001 end date: 22:32:40 Jun 19 2021 RA Signature Certificate Status: Available !--- The authentication was successful. Certificate Serial Number: 3b2fd319 Key Usage: Signature CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:03:31 Jun 19 2001 end date: 22:33:31 Jun 19 2004 RA KeyEncipher Certificate Status: Available !--- The authentication was successful. Certificate Serial Number: 3b2fd318 Key Usage: Encryption CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:03:31 Jun 19 2001 end date: 22:33:31 Jun 19 2004

5. Pida CA para el CRL.pix520-1(config)# **ca enroll cisco 171.69.89.16**

%

% Start certificate enrollment ..

% The subject name in the certificate will be: pix520-1.vpn.com

% Certificate request sent to Certificate Authority

% The certificate request fingerprint will be displayed.

pix520-1(config)# Fingerprint: 6961df68 d3b5e667 8903a66b 969eee64

CRYPTO_PKI: status = 102: certificate request pending

CRYPTO_PKI: status = 102: certificate request pendingjEl certificado ha sido concedido por

CA!pix520-1(config)#

pix520-1(config)# **show ca cert**

Certificate

Status: Available
!--- The enrollment was successful. Certificate Serial Number: 3b2fd653 Key Usage: General Purpose Subject Name Name: pix520-1.vpn.com CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 04:13:45 Jan 11 2002 end date: 04:43:45 Jan 11 2003 RA Signature Certificate Status: Available !--- The enrollment was successful. Certificate Serial Number: 3b2fd319 Key Usage: Signature CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:03:31 Jun 19 2001 end date: 22:33:31 Jun 19 2004 CA Certificate Status: Available !--- The enrollment was successful. Certificate Serial Number: 3b2fd307 Key Usage: General Purpose OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:02:40 Jun 19 2001 end date: 22:32:40 Jun 19 2021 RA KeyEncipher Certificate Status: Available !--- The enrollment was successful. Certificate Serial Number: 3b2fd318 Key Usage: Encryption CN = First Officer OU = sjvpn O = cisco C = us CRL Distribution Point: CN = CRL1, OU = sjvpn, O = cisco, C = us Validity Date: start date: 22:03:31 Jun 19 2001 end date: 22:33:31 Jun 19 2004 pix520-1(config)# pix520-1(config)# **ca crl request cisco**

6. Utilice el comando sh ca crl de ver el CRL.pix520-1(config)# **sh ca crl**

CRL:

CRL Issuer Name:

OU = sjvpn, O = cisco, C = us

LastUpdate: 00:17:34 Jan 11 2002

NextUpdate: 01:17:34 Jan 12 2002

pix520-1(config)#

7. Para salvar los Certificados en el PIX, utilice el siguiente comando: `pix520-1(config)# ca save all`

```
pix520-1(config)#
```

Verificación

En esta sección encontrará información que puede utilizar para confirmar que su configuración esté funcionando correctamente.

La herramienta [Output Interpreter](#) (sólo para clientes [registrados](#)) permite utilizar algunos comandos "show" y ver un análisis del resultado de estos comandos.

Los comandos show pueden ser funcionados con en el PIX y el router.

- `show crypto isakmp sa`: Ver todas las asociaciones actuales de seguridad IKE (SAs) de un par.
- **muestre IPsec crypto sa** - Muestra las configuraciones usadas por las asociaciones de seguridad del IPsec actual.
- `show crypto engine connections active`: (sólo el router) muestra las conexiones actuales y la información sobre los paquetes encriptación y desencriptación.
- **muestre los crls crypto Ca** - (router solamente) muestra el CRL actual en el router.
- **muestre los Certificados Ca crypto** - (router solamente) muestra el router, el servidor de CA, y los Certificados RA en el router. También muestra el punto de distribución del certificado (CDP).
- **show ca certificates** - (PIX solamente) muestra los Certificados PIX, de CA, y RA. A diferencia del router, no muestra el CDP.
- **show ca crl** - (PIX solamente) muestra el CRL en el PIX.
- **reloj de la demostración** - Muestra la hora actual en el router/PIX (del enable mode).

Ejemplo de resultado de los comandos show del router

```
1720-1#sh cr isa sa
```

dst	src	state	conn-id	slot
172.16.172.39	172.16.172.34	QM_IDLE	110	0

```
1720-1#sh cr map
```

```
Interfaces using crypto map mymap:
```

```
Crypto Map "vpn" 10 ipsec-isakmp
```

```
Peer = 172.16.172.34
```

```
Extended IP access list 130
```

```
access-list 130 permit ip 1.1.1.0 0.0.0.255 192.168.4.0 0.0.0.255
```

```
Current peer: 172.16.172.34
```

```
Security association lifetime: 4608000 kilobytes/3600 seconds
```

```
PFS (Y/N): N
```

```
Transform sets={ myset, }
```

```
Interfaces using crypto map vpn:
```

```
FastEthernet0
```

```
Interfaces using crypto map certificate:
```

```
1720-1#sh cr isa policy
```

```
Protection suite of priority 10
```

```
encryption algorithm: DES - Data Encryption Standard
```

(56 bit keys).

hash algorithm: Message Digest 5
authentication method: Rivest-Shamir-Adleman Signature
Diffie-Hellman group: #1 (768 bit)
lifetime: 86400 seconds, no volume limit

Default protection suite

encryption algorithm: DES - Data Encryption Standard

(56 bit keys).

hash algorithm: Secure Hash Standard
authentication method: Rivest-Shamir-Adleman Signature
Diffie-Hellman group: #1 (768 bit)
lifetime: 86400 seconds, no volume limit

1720-1#

1720-1#**sh cr ipsec sa**

interface: FastEthernet0

Crypto map tag: vpn, local addr. 172.16.172.39

local ident (addr/mask/prot/port):

(1.1.1.0/255.255.255.0/0/0)

remote ident (addr/mask/prot/port):

(192.168.4.0/255.255.255.0/0/0)

current_peer: 172.16.172.34

PERMIT, flags={origin_is_acl,}

#pkts encaps: 3, #pkts encrypt: 3, #pkts digest 3

#pkts decaps: 3, #pkts decrypt: 3, #pkts verify 3

#pkts compressed: 0, #pkts decompressed: 0

#pkts not compressed: 0, #pkts compr. failed: 0,

#pkts decompress failed: 0

#send errors 0, #recv errors 0

local crypto endpt.: 172.16.172.39,

remote crypto endpt.: 172.16.172.34

path mtu 1500, media mtu 1500

current outbound spi: 3803A0C1

inbound esp sas:

spi: 0xD740971C(3611334428)

transform: esp-des esp-md5-hmac ,

in use settings = {Tunnel, }

slot: 0, conn id: 200, flow_id: 1,

crypto map: vpn

sa timing: remaining key lifetime

(k/sec): (4607999/3150)

IV size: 8 bytes

replay detection support: Y

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0x3803A0C1(939761857)

transform: esp-des esp-md5-hmac ,

in use settings = {Tunnel, }

slot: 0, conn id: 201, flow_id: 2,

crypto map: vpn

sa timing: remaining key lifetime

(k/sec): (4607999/3141)

IV size: 8 bytes

replay detection support: Y

outbound ah sas:

outbound pcp sas:

1720-1#

1720-1# **sh cr en conn ac**

ID	Interface	IP-Address	State	Algorithm	Encrypt	Decrypt
110	FastEthernet0	172.16.172.39	set	HMAC_MD5+DES_56_CB	0	0
114	FastEthernet0	172.16.172.39	alloc	NONE	0	0
115	FastEthernet0	172.16.172.39	alloc	NONE	0	0
116	FastEthernet0	172.16.172.39	alloc	NONE	0	0
117	FastEthernet0	172.16.172.39	alloc	NONE	0	0
200	FastEthernet0	172.16.172.39	set	HMAC_MD5+DES_56_CB	0	3
201	FastEthernet0	172.16.172.39	set	HMAC_MD5+DES_56_CB	3	0

1720-1#**sh clock**

01:06:41.786 PST Fri Jan 11 2002

Salida de muestra de comandos show de PIX

pix520-1# **sh cr isa sa**

Total : 1

Embryonic : 0

dst	src	state	pending	created
172.16.172.39	172.16.172.34	QM_IDLE	0	1

pix520-1#

pix520-1# **sh cr map**

Crypto Map: "mymap" interfaces: { outside }

Crypto Map "mymap" 5 ipsec-isakmp

Peer = 172.16.172.39

access-list 130 permit ip

192.168.4.0 255.255.255.0 1.1.1.0 255.255.255.0 (hitcnt=91)

Current peer: 172.16.172.39

Security association lifetime:

4608000 kilobytes/28800 seconds

PFS (Y/N): N

Transform sets={ myset, }

pix520-1# **sh cr isa policy**

Protection suite of priority 10

encryption algorithm: DES - Data Encryption Standard (56 bit keys).

hash algorithm: Message Digest 5

authentication method: Rivest-Shamir-Adleman Signature

Diffie-Hellman group: #1 (768 bit)

lifetime: 86400 seconds, no volume limit

Default protection suite

encryption algorithm: DES - Data Encryption Standard (56 bit keys).

hash algorithm: Secure Hash Standard

authentication method: Rivest-Shamir-Adleman Signature

Diffie-Hellman group: #1 (768 bit)

lifetime: 86400 seconds,

no volume limit

pix520-1#

pix520-1# **sh cr ipsec sa**

interface: outside

Crypto map tag: mymap, local addr. 172.16.172.34

```
local ident (addr/mask/prot/port):
(192.168.4.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port):
(1.1.1.0/255.255.255.0/0/0)
current_peer: 172.16.172.39
  PERMIT, flags={origin_is_acl,}
  #pkts encaps: 3, #pkts encrypt: 3, #pkts digest 3
  #pkts decaps: 3, #pkts decrypt: 3, #pkts verify 3
  #pkts compressed: 0, #pkts decompressed: 0
  #pkts not compressed: 0, #pkts compr. failed: 0,
#pkts decompress failed: 0
  #send errors 2, #recv errors 0
```

```
local crypto endpt.: 172.16.172.34, remote
crypto endpt.: 172.16.172.39
path mtu 1500, ipsec overhead 56, media mtu 1500
current outbound spi: d740971c
```

```
inbound esp sas:
spi: 0x3803a0c1(939761857)
  transform: esp-des esp-md5-hmac ,
  in use settings = {Tunnel, }
  slot: 0, conn id: 4, crypto map: mymap
  sa timing: remaining key lifetime
(k/sec): (4607999/2971)
  IV size: 8 bytes
  replay detection support: Y
```

```
inbound ah sas:
```

```
inbound pcp sas:
```

```
outbound esp sas:
spi: 0xd740971c(3611334428)
  transform: esp-des esp-md5-hmac ,
  in use settings = {Tunnel, }
  slot: 0, conn id: 3, crypto map: mymap
  sa timing: remaining key lifetime
(k/sec): (4607999/2971)
  IV size: 8 bytes
  replay detection support: Y
```

```
outbound ah sas:
```

```
outbound pcp sas:
```

```
pix520-1# pix520-1# sh cr en
Crypto Engine Connection Map:
  size = 8, free = 6, used = 2, active = 2
pix520-1#
```

```
pix520-1# sh clock
09:27:54 Jan 11 2002
pix520-1#
```

[Troubleshooting](#)

En esta sección encontrará información que puede utilizar para solucionar problemas de configuración.

[Comandos para resolución de problemas](#)

La herramienta [Output Interpreter](#) (sólo para clientes [registrados](#)) permite utilizar algunos comandos “show” y ver un análisis del resultado de estos comandos.

Nota: Antes de ejecutar un comando debug, consulte Información Importante sobre Comandos Debug.

Los debugs siguientes deben ejecutarse en ambos peeres IPsec:

- **isakmp del debug crypto** - (router y PIX) visualiza los errores durante la fase 1.
- **IPsec del debug crypto** - (router y PIX) visualiza los errores durante la fase 2.
- **debug crypto engine** – (sólo router) Muestra información del motor crypto.
- **debug crypto pki transactions** - (router solamente) muestra la información con respecto a las transacciones del Public Key Infrastructure (PKI) del router.
- **debug crypto pki messages** - (router solamente) muestra la información con respecto al PKI entrado/hacia fuera los mensajes.
- **debug crypto ca** - (PIX solamente) visualiza la información con respecto las transacciones PKI y a los mensajes de la entrada-salida.

La verificación de las asociaciones de seguridad se debe realizar en ambos pares. Realizan a los comandos pix en el enable mode; los comandos del router se ejecutan en el modo non-enable (no habilitar).

- **clear crypto isakmp sa** - (PIX) Elimina las asociaciones de seguridad de la Fase 1.
- **clear crypto isakmp** – (PIX) Elimina las asociaciones de seguridad de la Fase 2.
- **clear crypto isakmp** – (Router) Elimina las asociaciones de seguridad de la Fase 1.
- **clear crypto sa** – (Router) Elimina las asociaciones de seguridad de la Fase 2.

[Ejemplo de depuración de certificado desde el router](#)

Esto secciona las demostraciones los debugs del router cuando funcionamos con los comandos debug siguientes PKI mientras que la obtención certifica de un servidor de CA. Estos debugs fueron obtenidos durante una sesión exitosa.

```
1720-1#debug cr pki transactions
Crypto PKI Trans debugging is on
1720-1#debug cr pki messages
Crypto PKI Msg debugging is on

1720-1(config)#cr ca authenticate vpn
Certificate has the following attributes:
Fingerprint: 1FCDF2C8 2DEDA6AC 4819D4C4 B4CFF2F5
% Do you accept this certificate? [yes/no]:
08:48:10: CRYPTO_PKI: Sending CA Certificate Request:
GET /cgi-bin/pkiclient.exe?operation=GetCACert&message =vpn HTTP/1.0

08:48:10: CRYPTO_PKI: can not resolve server name/IP address
08:48:10: CRYPTO_PKI: Using unresolved IP Address 171.69.89.16
```

```

08:48:10: CRYPTO_PKI: http connection opened
08:48:11: CRYPTO_PKI: HTTP response header:
HTTP/1.1 200 OK
Date: Fri, 11 Jan 2002 19:10:53 Pacific Standard Time
Server: Entrust/VPNConnector v5.0
Connection: close
Content-Type: application/x-x509-ra-ca-certs

```

Content-Type indicates we have received CA and RA certificates.

```
08:48:11: CRYPTO_PKI:CA and RA certs:
```

```

08:48:11:      30 82 08 EA 06 09 2A 86 48 86 F7 0D 01 07 02 A0
08:48:11:      82 08 DB 30 82 08 D7 02 01 01 31 00 30 0B 06 09
08:48:11:      2A 86 48 86 F7 0D 01 07 01 A0 82 08 BF 30 82 02
!--- Hex data omitted. 08:48:11: 14 06 03 55 04 03 13 0D 46 69 72 73 74 20 4F 66 08:48:11: 66
69 63 65 72 30 81 9F 30 0D 06 09 2A 86 48 86 08:48:11: 80 01 8F 51 3A 4B 61 74 59 0B 85 AA 9C E3
B3 91 08:48:11: 62 94 06 AA 7C E9 CC 0D 01 59 3E 6B 31 00 08:48:11: 08:48:11: CRYPTO_PKI: Error:
Certificate, private key or CRL was not found while selecting certificate chain 08:48:11:
CRYPTO_PKI: WARNING: A certificate chain could not be constructed while selecting certificate
status 08:48:11: CRYPTO_PKI: Error: Certificate, private key or CRL was not found while
selecting certificate chain 08:48:11: CRYPTO_PKI: WARNING: A certificate chain could not be
constructed while selecting certificate status 08:48:11: CRYPTO_PKI: crypto_process_ra_certs()
For:vpn 08:48:11: CRYPTO_PKI: crypto_set_ra_pubkey() (using global_auth_context) 08:48:11:
CRYPTO_PKI: crypto_set_ra_pubkey() (using global_auth_context) 08:48:11: CRYPTO_PKI: transaction
GetCACert completed 08:48:11: CRYPTO_PKI: CA certificate received. 08:48:11: CRYPTO_PKI: CA
certificate received. % Please answer 'yes' or 'no'. % Do you accept this certificate? [yes/no]:

```

Y

```

1720-1(config)#
08:49:08: CRYPTO_PKI: crypto_process_ra_certs() For:vpn

```

```
1720-1(config)#cr ca enroll vpn
```

```

%
% Start certificate enrollment ..
% Create a challenge password. You will need to verbally
  provide this password to the CA Administrator in order
  to revoke your certificate. For security reasons your
  password will not be saved in the configuration.
  Please make a note of it.

```

Password:

Re-enter password:

```

% The subject name in the certificate will be: 1720-1.cisco.com
% Include the router serial number in the subject name? [yes/no]: n
% Include an IP address in the subject name? [yes/no]: n
Request certificate from CA? [yes/no]: y
% Certificate request sent to Certificate Authority
% The certificate request fingerprint will be displayed.
% The 'show crypto ca certificate' command will also show
% the fingerprint.

```

```
1720-1(config)#      Fingerprint: CB9730B0 5EAAEBCB CC04C77B 2B7F253D
```

```

08:51:09: CRYPTO_PKI: transaction PKCSReq completed
08:51:09: CRYPTO_PKI: status:
08:51:10: CRYPTO_PKI:Write out pkcs#10 content:272
08:51:10:      30 82 01 0C 30 81 B7 02 01 00 30 21 31 1F 30 1D
08:51:10:      06 09 2A 86 48 86 F7 0D 01 09 02 16 10 31 37 32
!--- Hex data omitted. 08:51:10: 8F 87 32 4A 25 27 2A 9B 17 F1 1F C5 67 1E 2A D2 08:51:10:
08:51:10: CRYPTO_PKI:Enveloped Data ... 08:51:10: 30 80 06 09 2A 86 48 86 F7 0D 01 07 03 A0 80
30 !--- Hex data omitted. 08:51:10: 2F C8 94 16 FE 2F 1B 00 00 00 00 00 00 00 00 08:51:10: 00
08:51:10: 08:51:10: CRYPTO_PKI:Signed Data 1311 bytes 08:51:10: 30 80 06 09 2A 86 48 86 F7 0D 01
07 02 A0 80 30 08:51:10: 80 02 01 01 31 0E 30 0C 06 08 2A 86 48 86 F7 0D !--- Hex data omitted.

```

08:51:10: D0 56 7D 24 59 9C DE 00 00 00 00 00 00 00 00 08:51:10: 08:51:10: CRYPTO_PKI: can not resolve server name/IP address 08:51:10: CRYPTO_PKI: Using unresolved IP Address 171.69.89.16
08:51:10: CRYPTO_PKI: http connection opened 08:51:13: CRYPTO_PKI: received msg of 656 bytes
08:51:13: CRYPTO_PKI: HTTP response header: HTTP/1.1 200 OK Date: Fri, 11 Jan 2002 19:13:55 Pacific Standard Time Server: Entrust/VPNConnector v5.0 Connection: close Content-Type: application/x-pki-message 08:51:13: CRYPTO_PKI:Received pki message: 487 types 08:51:13: 30 82 01 E3 06 09 2A 86 48 86 F7 0D 01 07 02 A0 !--- Hex data omitted. 08:51:13: E6 E3 CC 8B 6C 5E 74 9E 6A 0B 7D E1 B7 31 A0 EF 08:51:13: 02 1B C6 F3 C2 B9 86 08:51:13: 08:51:13: CRYPTO_PKI: signed attr: pki-message-type: 13 01 33 08:51:13: 08:51:13: CRYPTO_PKI: signed attr: pki-status: 13 01 33 08:51:13: 08:51:13: CRYPTO_PKI: signed attr: pki-recipient-nonce: 08:51:13: 04 20 32 46 37 30 36 35 37 45 39 44 43 31 36 31 08:51:13: 39 31 34 39 30 32 33 34 46 35 42 44 30 46 41 31 08:51:13: 46 34 08:51:13: 08:51:13: CRYPTO_PKI: signed attr: pki-transaction-id: 08:51:13: 13 20 35 33 43 46 43 31 35 30 37 36 42 33 35 42 08:51:13: 37 30 42 43 42 39 39 36 44 36 42 46 39 32 38 30 08:51:13: 37 35 08:51:13: 08:51:13: CRYPTO_PKI: status = 102: certificate request pending 08:51:13: CRYPTO_PKI:Write out getcert initial content:84 08:51:13: 30 52 30 2D 31 0B 30 09 06 03 55 04 06 13 02 75 08:51:13: 73 31 0E 30 0C 06 03 55 04 0A 13 05 63 69 73 63 08:51:13: 6F 31 0E 30 0C 06 03 55 04 0B 13 05 73 6A 76 70 08:51:13: 6E 30 21 31 1F 30 1D 06 09 2A 86 48 86 F7 0D 01 08:51:13: 09 02 16 10 31 37 32 30 2D 31 2E 63 69 73 63 6F 08:51:13: 2E 63 6F 6D 08:51:13: 08:51:13: CRYPTO_PKI:Enveloped Data ... 08:51:13: 30 80 06 09 2A 86 48 86 F7 0D 01 07 03 A0 80 30 !--- Hex data omitted. 08:51:13: 08:51:13: CRYPTO_PKI:Signed Data 1738 bytes 08:51:13: 30 80 06 09 2A 86 48 86 F7 0D 01 07 02 A0 80 30 !--- Hex data omitted. 08:51:14: 59 DA 00 00 00 00 00 00 00 00 08:51:14: 08:51:14: CRYPTO_PKI: can not resolve server name/IP address 08:51:14: CRYPTO_PKI: Using unresolved IP Address 171.69.89.16 08:51:14: CRYPTO_PKI: http connection opened 08:51:36: CRYPTO_PKI: received msg of 656 bytes 08:51:36: CRYPTO_PKI: HTTP response header: HTTP/1.1 200 OK Date: Fri, 11 Jan 2002 19:13:58 Pacific Standard Time Server: Entrust/VPNConnector v5.0 Connection: close Content-Type: application/x-pki-message 08:51:36: CRYPTO_PKI:Received pki message: 487 types 08:51:36: 30 82 01 E3 06 09 2A 86 48 86 F7 0D 01 07 02 A0 08:51:36: 82 01 D4 30 82 01 D0 02 01 01 31 0E 30 0C 06 08 !--- Hex data omitted. 08:51:36: E6 E3 CC 8B 6C 5E 74 9E 6A 0B 7D E1 B7 31 A0 EF 08:51:36: 02 1B C6 F3 C2 B9 86 08:51:36: 08:51:36: CRYPTO_PKI: signed attr: pki-message-type: 13 01 33 08:51:36: 08:51:36: CRYPTO_PKI: signed attr: pki-status: 13 01 33 08:51:36: 08:51:36: CRYPTO_PKI: signed attr: pki-recipient-nonce: 08:51:36: 04 20 32 46 37 30 36 35 37 45 39 44 43 31 36 31 08:51:36: 39 31 34 39 30 32 33 34 46 35 42 44 30 46 41 31 08:51:36: 46 34 08:51:36: 08:51:36: CRYPTO_PKI: signed attr: pki-transaction-id: 08:51:36: 13 20 35 33 43 46 43 31 35 30 37 36 42 33 35 42 08:51:36: 37 30 42 43 42 39 39 36 44 36 42 46 39 32 38 30 08:51:36: 37 35 08:51:36: 08:51:36: CRYPTO_PKI: status = 102: certificate request pending 08:51:46: CRYPTO_PKI: All sockets are closed. 08:51:56: CRYPTO_PKI: All sockets are closed. 08:52:36: CRYPTO_PKI: resend GetCertInitial, 1 08:52:36: CRYPTO_PKI: resend GetCertInitial for session: 0 08:52:36: CRYPTO_PKI: can not resolve server name/IP address 08:52:36: CRYPTO_PKI: Using unresolved IP Address 171.69.89.16 08:52:36: CRYPTO_PKI: http connection opened 08:52:38: CRYPTO_PKI: received msg of 1647 bytes 08:52:38: CRYPTO_PKI: HTTP response header: HTTP/1.1 200 OK Date: Fri, 11 Jan 2002 19:15:20 Pacific Standard Time Server: Entrust/VPNConnector v5.0 Connection: close Content-Type: application/x-pki-message 08:52:38: CRYPTO_PKI:Received pki message: 1478 types 08:52:38: 30 82 05 C2 06 09 2A 86 48 86 F7 0D 01 07 02 A0 !--- Hex data omitted. 08:52:38: B4 0D EC 6D 61 9B 08:52:38: 08:52:38: CRYPTO_PKI: signed attr: pki-message-type: 13 01 33 08:52:38: 08:52:38: CRYPTO_PKI: signed attr: pki-status: 13 01 30 08:52:38: 08:52:38: CRYPTO_PKI: signed attr: pki-recipient-nonce: 08:52:38: 04 20 32 41 35 44 31 31 42 34 43 39 46 31 34 32 08:52:38: 30 30 38 34 32 43 35 45 38 36 44 44 43 41 45 44 08:52:38: 33 34 08:52:38: 08:52:38: CRYPTO_PKI: signed attr: pki-transaction-id: 08:52:38: 13 20 35 33 43 46 43 31 35 30 37 36 42 33 35 42 08:52:38: 37 30 42 43 42 39 39 36 44 36 42 46 39 32 38 30 08:52:38: 37 35 08:52:38: 08:52:38: CRYPTO_PKI: status = 100: certificate is granted !--- Certificate is granted by the CA. 08:52:38: CRYPTO_PKI:Verified signed data 985 bytes: 08:52:38: 30 82 03 D5 06 09 2A 86 48 86 F7 0D 01 07 03 A0 !--- Hex data omitted. 08:52:38: 39 DE 0A 10 3B D1 17 30 79 83 E0 54 D9 59 47 13 08:52:38: 86 9A E5 5D F8 45 3D 61 63 08:52:38: 08:52:38: CRYPTO_PKI:Decrypted enveloped content: 08:52:38: 30 82 02 F3 06 09 2A 86 48 86 F7 0D 01 07 02 A0 08:52:38: 82 02 E4 30 82 02 E0 02 01 01 31 00 30 0B 06 09 !--- Hex data omitted. 08:52:39: CE 33 54 B3 4A 62 23 65 6E B1 83 D9 7C 24 87 A5 08:52:39: E8 FF D8 50 6F 31 00 08:52:39: 08:52:39: CRYPTO_PKI: All enrollment requests completed. 08:52:39: %CRYPTO-6-CERTRET: Certificate received from Certificate Authority 08:52:49: CRYPTO_PKI: All enrollment requests completed.

[Muestra del debug del certificado desde PIX](#)

Esto secciona las demostraciones los debugs del PIX cuando funcionamos con los comandos

debug siguientes PKI mientras que la obtención certifica de un servidor de CA. Estos debugs fueron obtenidos durante una sesión exitosa.

```
pix520-1(config)#
```

```
pix520-1(config)# debug cr ca
```

```
pix520-1(config)#
```

```
pix520-1(config)# ca configure cisco ra 20 5
```

```
pix520-1(config)# ca authenticate cisco
```

```
CI thread sleeps!
```

```
Crypto CA thread wakes up!
```

```
CRYPTO_PKI: http connection opened
```

```
Certificate has the following attributes:
```

```
Fingerprint: 1fcd2c8 2deda6ac 4819d4c4 b4cff2f5
```

```
PKI: key process suspended and continued
```

```
CRYPTO_PKI: WARNING: A certificate chain could not  
be constructed while selecting certificate status
```

```
CRYPTO_PKI: WARNING: A certificate chain could not  
be constructed while selecting certificate status
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: transaction GetCACert completed
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
Crypto CA thread sleeps!
```

```
pix520-1(config)# !
```

```
pix520-1(config)# sh ca cert
```

```
CA
```

```
CRYPTO_PKI: Name: OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = CRL1, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = CRL1, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = First Officer, OU = sjvpn, O = cisco, C = us
```

```
CRYPTO_PKI: Name: CN = CRL1, OU = sjvpn, O = cisco, C = us Certificate
```

```
Status: Available
```

```
Certificate Serial Number: 3b2fd307
```

```
Key Usage: General Purpose
```

```
OU = sjvpn
```

```
O = cisco
```

```
C = us
```

```
CRL Distribution Point:
```

```
CN = CRL1, OU = sjvpn, O = cisco, C = us
```

```
Validity Date:
```

```
start date: 22:02:40 Jun 19 2001
```

```
end date: 22:32:40 Jun 19 2021
```

```
RA Signature Certificate
```

```
Certificate Serial Number: 3b2fd319
```

```
Key Usage: Signature
```

```
CN = First Officer
```

```
OU = sjvpn
```

```
O = cisco
```

```
C = us
```

```
CRL Distribution Point:
```



```
CN = CRL1, OU = sjvpn, O = cisco, C = us
Validity Date:
  start date: 22:03:31 Jun 19 2001

  end   date: 22:33:31 Jun 19 2004
```

RA KeyEncipher Certificate

```
Status: Available
Certificate Serial Number: 3b2fd318
Key Usage: Encryption
  CN = First Officer
  OU = sjvpn
  O = cisco
  C = us
CRL Distribution Point:
  CN = CRL1, OU = sjvpn, O = cisco, C = us
Validity Date:
  start date: 22:03:31 Jun 19 2001

  end   date: 22:33:31 Jun 19 2004
```

```
pix520-1(config)#
Status: Available
```

```
pix520-1(config)# ca enroll cisco 171.69.89.16
```

```
CI thread sleeps!
% Crypto CA thread wakes up!
% Start certificate enrollment ..

% The subject name in the certificate will be: pix520-1.vpn.com

% Certificate request sent to Certificate Authority
% The certificate request fingerprint will be displayed.
```

```
pix520-1(config)#   Fingerprint:  bc923bc0 ee66b336 08a513b1 a226c5c8
```

```
CRYPTO_PKI: transaction PKCSReq completed
CRYPTO_PKI: status:
Crypto CA thread sleeps!
PKI: key process suspended and continued
CRYPTO_PKI: http connection opened
CRYPTO_PKI:  received msg of 656 bytes
CRYPTO_PKI: WARNING: Certificate, private key or CRL was
not found while selecting CRL

CRYPTO_PKI: signed attr: pki-message-type:
13 01 33
CRYPTO_PKI: signed attr: pki-status:
13 01 33
CRYPTO_PKI: signed attr: pki-recipient-nonce:
04 20 30 36 38 33 34 44 35 46 30 44 31 37 42 39 42 30 30 44
37 37 42 33 44 37 39 42 45 43 43 43 41 41
CRYPTO_PKI: signed attr: pki-transaction-id:
13 20 64 38 32 36 37 37 34 33 31 39 62 65 65 31 62 65 34 36
65 33 63 32 38 37 66 61 65 31 31 36 64 32
CRYPTO_PKI: status = 102: certificate request pending
```

```

CRYPTO_PKI: All sockets are closed.
CRYPTO_PKI: All sockets are closed.
CRYPTO_PKI: resend GetCertInitial for session: 0
CRYPTO_PKI: http connection opened
!--- The certificate has been granted by CA! CRYPTO_PKI: received msg of 1720 bytes CRYPTO_PKI:
WARNING: Certificate, private key or CRL was not found while selecting CRL PKI: key process
suspended and continued CRYPTO_PKI: signed attr: pki-message-type: 13 01 33 CRYPTO_PKI: signed
attr: pki-status: 13 01 30 CRYPTO_PKI: signed attr: pki-recipient-nonce: 04 20 34 42 41 36 31 31
31 42 42 35 42 38 42 43 44 31 36 31 34 30 34 44 45 34 45 33 33 41 34 41 46 36 CRYPTO_PKI: signed
attr: pki-transaction-id: 13 20 64 38 32 36 37 37 34 33 31 39 62 65 65 31 62 65 34 36 65 33 63
32 38 37 66 61 65 31 31 36 64 32 CRYPTO_PKI: status = 100: certificate is granted CRYPTO_PKI:
WARNING: Certificate, private key or CRL was not found while selecting CRL CRYPTO_PKI: All
enrollment requests completed. CRYPTO_PKI: All enrollment requests completed. CRYPTO_PKI:
WARNING: Certificate, private key or CRL was not found while selecting CRL

```

Ejemplo de depuración de IPsec desde el router

Esta sección muestra que los debugs del IPsec en el router durante el tiempo ambos los peeres IPsec están negociando el túnel IPsec.

```

1720-1#debug crypto ipsec
1720-1#debug crypto isakmp
1720-1#debug crypto engine
1720-1#sh debug
Cryptographic Subsystem:
  Crypto ISAKMP debugging is on
  Crypto Engine debugging is on
  Crypto IPSEC debugging is on
1720-1#

3d11h: ISAKMP (0:0): received packet from 172.16.172.34 (N) NEW SA
3d11h: ISAKMP: local port 500, remote port 500
3d11h: ISAKMP (0:110): processing SA payload. message ID = 0
3d11h: ISAKMP (0:110): Checking ISAKMP transform 1 against
priority 10 policy
3d11h: ISAKMP:      encryption DES-CBC
3d11h: ISAKMP:      hash MD5
3d11h: ISAKMP:      default group 1
3d11h: ISAKMP:      auth RSA sig
!--- IKE phase one is accepting certificates as the authentication method. 3d11h: ISAKMP
(0:110): atts are acceptable. Next payload is 3 3d11h: CryptoEngine0: generate alg parameter
3d11h: CryptoEngine0: CRYPTO_ISA_DH_CREATE(hw)(ipsec) 3d11h: CRYPTO_ENGINE: Dh phase 1 status: 0
3d11h: ISAKMP (0:110): SA is doing RSA signature authentication using id type ID_FQDN 3d11h:
ISAKMP (0:110): sending packet to 172.16.172.34 (R) MM_SA_SETUP 3d11h: ISAKMP (0:110): received
packet from 172.16.172.34 (R) MM_SA_SETUP 3d11h: ISAKMP (0:110): processing KE payload. message
ID = 0 3d11h: CryptoEngine0: generate alg parameter 3d11h: CryptoEngine0:
CRYPTO_ISA_DH_SHARE_SECRET(hw)(ipsec) 3d11h: ISAKMP (0:110): processing NONCE payload. message
ID = 0 3d11h: CryptoEngine0: calculate pkey hmac for conn id 110 3d11h: CryptoEngine0:
CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: CryptoEngine0: create ISAKMP SKEYID for conn id 110 3d11h:
CryptoEngine0: CRYPTO_ISA_SA_CREATE(hw)(ipsec) 3d11h: ISAKMP (0:110): SKEYID state generated
3d11h: ISAKMP (0:110): processing CERT_REQ payload. message ID = 0 3d11h: ISAKMP (0:110): peer
wants a CT_X509_SIGNATURE cert 3d11h: ISAKMP (0:110): peer want cert issued by OU = sjvpn, O =
cisco, C = us 3d11h: ISAKMP (0:110): processing vendor id payload 3d11h: ISAKMP (0:110):
processing vendor id payload 3d11h: ISAKMP (0:110): processing vendor id payload 3d11h: ISAKMP
(0:110): speaking to another IOS box! 3d11h: ISAKMP (0:110): sending packet to 172.16.172.34 (R)
MM_KEY_EXCH 3d11h: ISAKMP (0:110): received packet from 172.16.172.34 (R) MM_KEY_EXCH 3d11h:
CryptoEngine0: CRYPTO_ISA_IKE_DECRYPT(hw)(ipsec) 3d11h: ISAKMP (0:110): processing ID payload.
message ID = 0 3d11h: ISAKMP (0:110): processing CERT payload. message ID = 0 3d11h: ISAKMP
(0:110): processing a CT_X509_SIGNATURE cert 3d11h: ISAKMP (0:110): processing SIG payload.
message ID = 0 3d11h: ISAKMP (110): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn = pix520-
1.vpn.com 3d11h: Crypto engine 0: RSA decrypt with public key 3d11h: CryptoEngine0:
CRYPTO_RSA_PUB_DECRYPT 3d11h: CryptoEngine0: generate hmac context for conn id 110 3d11h:
CryptoEngine0: CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: ISAKMP (0:110): SA has been authenticated

```

```

with 172.16.172.34 3d11h: ISAKMP (110): ID payload next-payload : 6 type : 2 protocol : 17 port
: 500 length : 20 3d11h: ISAKMP (110): Total payload length: 24 3d11h: CryptoEngine0: generate
hmac context for conn id 110 3d11h: CryptoEngine0: CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: Crypto
engine 0: RSA encrypt with private key 3d11h: CryptoEngine0: CRYPTO_RSA_PRIV_ENCRYPT 3d11h:
CRYPTO_ENGINE: key process suspended and continued 3d11h: CryptoEngine0: clear dh number for
conn id 1 3d11h: CryptoEngine0: CRYPTO_ISA_DH_DELETE(hw)(ipsec) 3d11h: CryptoEngine0:
CRYPTO_ISA_IKE_ENCRYPT(hw)(ipsec) 3d11h: ISAKMP (0:110): sending packet to 172.16.172.34 (R)
QM_IDLE 3d11h: ISAKMP (0:110): received packet from 172.16.172.34 (R) QM_IDLE 3d11h:
CryptoEngine0: CRYPTO_ISA_IKE_DECRYPT(hw)(ipsec) 3d11h: CryptoEngine0: generate hmac context for
conn id 110 3d11h: CryptoEngine0: CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: ISAKMP (0:110):
processing HASH payload. message ID = -140325145 3d11h: ISAKMP (0:110): processing SA payload.
message ID = -140325145 3d11h: ISAKMP (0:110): Checking IPsec proposal 1 3d11h: ISAKMP:
transform 1, ESP_DES 3d11h: ISAKMP: attributes in transform: 3d11h: ISAKMP: encaps is 1 3d11h:
ISAKMP: SA life type in seconds 3d11h: ISAKMP: SA life duration (basic) of 28800 3d11h: ISAKMP:
SA life type in kilobytes 3d11h: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50 0x0 3d11h:
ISAKMP: authenticator is HMAC-MD5 3d11h: validate proposal 0 3d11h: ISAKMP (0:110): atts are
acceptable. 3d11h: IPSEC(validate_proposal_request): proposal part #1, (key eng. msg.) INBOUND
local= 172.16.172.39, remote= 172.16.172.34, local_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
remote_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-
hmac , lifedur= 0s and 0kb, spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4 3d11h: validate
proposal request 0 3d11h: ISAKMP (0:110): processing NONCE payload. message ID = -140325145
3d11h: ISAKMP (0:110): processing ID payload. message ID = -140325145 3d11h: ISAKMP (0:110):
processing ID payload. message ID = -140325145 3d11h: ISAKMP (0:110): asking for 1 spis from
ipsec 3d11h: IPSEC(key_engine): got a queue event... 3d11h: IPSEC(spi_response): getting spi
3611334428 for SA from 172.16.172.39 to 172.16.172.34 for prot 3 3d11h: ISAKMP: received ke
message (2/1) 3d11h: CryptoEngine0: generate hmac context for conn id 110 3d11h: CryptoEngine0:
CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: CryptoEngine0: CRYPTO_ISA_IKE_ENCRYPT(hw)(ipsec) 3d11h:
ISAKMP (0:110): sending packet to 172.16.172.34 (R) QM_IDLE 3d11h: ISAKMP (0:110): received
packet from 172.16.172.34 (R) QM_IDLE 3d11h: CryptoEngine0: CRYPTO_ISA_IKE_DECRYPT(hw)(ipsec)
3d11h: CryptoEngine0: generate hmac context for conn id 110 3d11h: CryptoEngine0:
CRYPTO_ISA_IKE_HMAC(hw)(ipsec) 3d11h: ipsec allocate flow 0 3d11h: ipsec allocate flow 0 3d11h:
CryptoEngine0: CRYPTO_ISA_IPSEC_KEY_CREATE(hw)(ipsec) 3d11h: CryptoEngine0:
CRYPTO_ISA_IPSEC_KEY_CREATE(hw)(ipsec) 3d11h: ISAKMP (0:110): Creating IPsec SAs 3d11h: inbound
SA from 172.16.172.34 to 172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0) 3d11h: has spi 0xD740971C
and conn_id 200 and flags 4 3d11h: lifetime of 28800 seconds 3d11h: lifetime of 4608000
kilobytes 3d11h: outbound SA from 172.16.172.39 to 172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0 )
3d11h: has spi 939761857 and conn_id 201 and flags C 3d11h: lifetime of 28800 seconds 3d11h:
lifetime of 4608000 kilobytes 3d11h: ISAKMP (0:110): deleting node -140325145 error FALSE reason
"quick mode done (await())" 3d11h: IPSEC(key_engine): got a queue event... 3d11h:
IPSEC(initialize_sas): , (key eng. msg.) INBOUND local= 172.16.172.39, remote= 172.16.172.34,
local_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.4.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac , lifedur= 28800s and 4608000kb, spi=
0xD740971C(3611334428), conn_id= 200, keysize= 0, flags= 0x4 3d11h: IPSEC(initialize_sas): ,
(key eng. msg.) OUTBOUND local= 172.16.172.39, remote= 172.16.172.34, local_proxy=
1.1.1.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac , lifedur= 28800s and 4608000kb, spi=
0x3803A0C1(939761857), conn_id= 201, keysize= 0, flags= 0xC 3d11h: IPSEC(create_sa): sa created,
(sa) sa_dest= 172.16.172.39, sa_prot= 50, sa_spi= 0xD740971C(3611334428), sa_trans= esp-des esp-
md5-hmac , sa_conn_id= 200 3d11h: IPSEC(create_sa): sa created, (sa) sa_dest= 172.16.172.34,
sa_prot= 50, sa_spi= 0x3803A0C1(939761857), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 201
3d11h: ISAKMP (0:108): purging SA., sa=811A823C, delme=811A823C 3d11h: CryptoEngine0: delete
connection 108 3d11h: CryptoEngine0: CRYPTO_ISA_SA_DELETE(hw)(ipsec) 3d11h: ISAKMP (0:107):
purging SA., sa=811FE440, delme=811FE440 3d11h: CryptoEngine0: delete connection 107 3d11h:
CryptoEngine0: CRYPTO_ISA_SA_DELETE(hw)(ipsec) 1720-1#

```

[Depuración IPsec de ejemplo desde el PIX](#)

Esta sección muestra que los debugs del IPsec en el PIX durante el tiempo ambos peers IPsec están negociando el túnel IPsec.

```

pix520-1# debug crypto ipsec
pix520-1# debug crypto isakmp
pix520-1# sh debug

```

```
debug crypto ipsec 1
debug crypto isakmp 1
debug fover status
    tx      Off
    rx      Off
    open    Off
    cable   Off
    txdmp   Off
    rxdmp   Off
    ifc     Off
    rxip    Off
    txip    Off
    get     Off
    put     Off
    verify  Off
    switch  Off
    fail    Off
    fmsg    Off
```

ISAKMP (0): beginning Main Mode exchange

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against
priority 10 policy

ISAKMP: encryption DES-CBC

ISAKMP: hash MD5

ISAKMP: default group 1

ISAKMP: auth RSA sig

ISAKMP (0): atts are acceptable. Next payload is 0

ISAKMP (0): SA is doing RSA signature authentication
using id type ID_FQDN

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing CERT_REQ payload. message ID = 0

ISAKMP (0): peer wants a CT_X509_SIGNATURE cert

ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload

next-payload : 6

type : 2

protocol : 17

port : 500

length : 20

ISAKMP (0): Total payload length: 24

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing ID payload. message ID = 0

ISAKMP (0): processing CERT payload. message ID = 0

ISAKMP (0): processing a CT_X509_SIGNATURE cert

ISAKMP (0): processing SIG payload. message ID = 0

ISAKMP (0): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn =
1720-1.cisco.com

ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,
M-ID of -140325145:f7a2cee7IPSEC(key_engine):
got a queue event...

IPSEC(spi_response): getting spi 0x3803a0c1(939761857)
for SA from 172.16.172.39 to 172.16.172.34 for prot 3

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_QM exchange

oakley_process_quick_mode:

OAK_QM_IDLE

ISAKMP (0): processing SA payload.

message ID = 4154642151

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES

ISAKMP: attributes in transform:

ISAKMP: encaps is 1

ISAKMP: SA life type in seconds

ISAKMP: SA life duration (basic) of 28800

ISAKMP: SA life type in kilobytes

ISAKMP: SA life duration (VPI)

of 0x0 0x46 0x50 0x0

ISAKMP: authenticator is HMAC-MD5

ISAKMP (0): atts are acceptable.

IPSEC(validate_proposal_request): proposal part #1,

(key eng. msg.) dest= 172.16.172.39,
src= 172.16.172.34,
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload.

message ID = 4154642151

ISAKMP (0): processing ID payload.

message ID = 4154642151

ISAKMP (0): processing ID payload.

message ID = 4154642151

ISAKMP (0): processing NOTIFY payload 24576

protocol 3 spi 3611334428,
message ID = 4154642151

ISAKMP (0): processing responder lifetime

ISAKMP (0): responder lifetime of 3600s

ISAKMP (0): Creating IPsec SAs

inbound SA from 172.16.172.39 to
172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0)
has spi 939761857 and conn_id 4 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes

outbound SA from 172.16.172.34 to
172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0)
has spi 3611334428 and conn_id 3 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes

IPSEC(key_engine): got a queue event...

IPSEC(initialize_sas): ,

```
(key eng. msg.) dest= 172.16.172.34, src= 172.16.172.39,
  dest_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
  src_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-md5-hmac ,
  lifedur= 3600s and 4608000kb,
  spi= 0x3803a0c1(939761857), conn_id= 4, keysize= 0,
flags= 0x4
IPSEC(initialize_sas): ,
  (key eng. msg.) src= 172.16.172.34, dest= 172.16.172.39,
  src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
  dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
  protocol= ESP, transform= esp-des esp-md5-hmac ,
  lifedur= 3600s and 4608000kb,
  spi= 0xd740971c(3611334428), conn_id= 3, keysize= 0,
flags= 0x4

return status is IKMP_NO_ERROR
```

```
pix520-1(config)#
```

Problemas posibles

Esta sección discute los síntomas, las causas, y las resoluciones de los errores comunes se incurren en que mientras que la obtención certifica en el router y el PIX.

Discordancia de la identidad ISAKMP

El router y el PIX asignan un FQDN a las claves y a los Certificados usados por el IPsec. Durante el IKE o la negociación de la fase 1 el router/IOS marca el FQDN en el certificado. Por lo tanto tenemos que utilizar la identidad ISAKMP como nombre de host, en vez del direccionamiento en el PIX y el router. En el siguiente ejemplo, el router/IOS está marcando para saber si hay el FQDN en el certificado.

```
pix520-1# debug crypto ipsec
pix520-1# debug crypto isakmp
pix520-1# sh debug
debug crypto ipsec 1
debug crypto isakmp 1
debug fover status
  tx      Off
  rx      Off
  open    Off
  cable   Off
  txdmp   Off
  rxdmp   Off
  ifc     Off
  rxip    Off
  txip    Off
  get     Off
  put     Off
  verify  Off
  switch  Off
  fail    Off
  fmsg    Off
```

```
ISAKMP (0): beginning Main Mode exchange
```

```
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange
ISAKMP (0): processing SA payload. message ID = 0
```

```
ISAKMP (0): Checking ISAKMP transform 1 against
priority 10 policy
ISAKMP:      encryption DES-CBC
ISAKMP:      hash MD5
ISAKMP:      default group 1
ISAKMP:      auth RSA sig
ISAKMP (0): atts are acceptable. Next payload is 0
ISAKMP (0): SA is doing RSA signature authentication
using id type ID_FQDN
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange
ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing CERT_REQ payload. message ID = 0
ISAKMP (0): peer wants a CT_X509_SIGNATURE cert
ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload
      next-payload : 6
      type          : 2
      protocol      : 17
      port          : 500
      length        : 20
ISAKMP (0): Total payload length: 24
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange
ISAKMP (0): processing ID payload. message ID = 0
ISAKMP (0): processing CERT payload. message ID = 0
ISAKMP (0): processing a CT_X509_SIGNATURE cert
ISAKMP (0): processing SIG payload. message ID = 0
ISAKMP (0): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn =
1720-1.cisco.com
ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,
M-ID of -140325145:f7a2cee7IPSEC(key_engine):
got a queue event...
IPSEC(spi_response): getting spi 0x3803a0c1(939761857)
      for SA from 172.16.172.39 to 172.16.172.34 for prot 3

return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload.
message ID = 4154642151
ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES
ISAKMP:  attributes in transform:
ISAKMP:      encaps is 1
ISAKMP:      SA life type in seconds
ISAKMP:      SA life duration (basic) of 28800
```

```
ISAKMP:      SA life type in kilobytes
ISAKMP:      SA life duration (VPI)
of 0x0 0x46 0x50 0x0
ISAKMP:      authenticator is HMAC-MD5
ISAKMP (0):  atts are acceptable.
IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) dest= 172.16.172.39,
src= 172.16.172.34,
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0):  processing NONCE payload.
message ID = 4154642151

ISAKMP (0):  processing ID payload.
message ID = 4154642151
ISAKMP (0):  processing ID payload.
message ID = 4154642151
ISAKMP (0):  processing NOTIFY payload 24576
protocol 3 spi 3611334428,
message ID = 4154642151
ISAKMP (0):  processing responder lifetime
ISAKMP (0):  responder lifetime of 3600s
ISAKMP (0):  Creating IPsec SAs
inbound SA from 172.16.172.39 to
172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0)
has spi 939761857 and conn_id 4 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes
outbound SA from 172.16.172.34 to
172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0)
has spi 3611334428 and conn_id 3 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes
IPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 172.16.172.34, src= 172.16.172.39,
dest_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
src_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0x3803a0c1(939761857), conn_id= 4, keysize= 0,
flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 172.16.172.34, dest= 172.16.172.39,
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0xd740971c(3611334428), conn_id= 3, keysize= 0,
flags= 0x4

return status is IKMP_NO_ERROR
```

```
pix520-1(config)#
```

Debugs del router:

```
pix520-1# debug crypto ipsec
pix520-1# debug crypto isakmp
pix520-1# sh debug
```



```
debug crypto ipsec 1
debug crypto isakmp 1
debug fover status
    tx      Off
    rx      Off
    open    Off
    cable   Off
    txdmp   Off
    rxdmp   Off
    ifc     Off
    rxip    Off
    txip    Off
    get     Off
    put     Off
    verify  Off
    switch  Off
    fail    Off
    fmsg    Off
```

ISAKMP (0): beginning Main Mode exchange

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against
priority 10 policy

ISAKMP: encryption DES-CBC

ISAKMP: hash MD5

ISAKMP: default group 1

ISAKMP: auth RSA sig

ISAKMP (0): atts are acceptable. Next payload is 0

ISAKMP (0): SA is doing RSA signature authentication
using id type ID_FQDN

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing CERT_REQ payload. message ID = 0

ISAKMP (0): peer wants a CT_X509_SIGNATURE cert

ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload

next-payload : 6

type : 2

protocol : 17

port : 500

length : 20

ISAKMP (0): Total payload length: 24

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_MM exchange

ISAKMP (0): processing ID payload. message ID = 0

ISAKMP (0): processing CERT payload. message ID = 0

ISAKMP (0): processing a CT_X509_SIGNATURE cert

ISAKMP (0): processing SIG payload. message ID = 0

ISAKMP (0): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn =
1720-1.cisco.com

ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,
M-ID of -140325145:f7a2cee7IPSEC(key_engine):
got a queue event...

IPSEC(spi_response): getting spi 0x3803a0c1(939761857)
for SA from 172.16.172.39 to 172.16.172.34 for prot 3

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34

OAK_QM exchange

oakley_process_quick_mode:

OAK_QM_IDLE

ISAKMP (0): processing SA payload.

message ID = 4154642151

ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES

ISAKMP: attributes in transform:

ISAKMP: encaps is 1

ISAKMP: SA life type in seconds

ISAKMP: SA life duration (basic) of 28800

ISAKMP: SA life type in kilobytes

ISAKMP: SA life duration (VPI)

of 0x0 0x46 0x50 0x0

ISAKMP: authenticator is HMAC-MD5

ISAKMP (0): atts are acceptable.

IPSEC(validate_proposal_request): proposal part #1,

(key eng. msg.) dest= 172.16.172.39,
src= 172.16.172.34,
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload.

message ID = 4154642151

ISAKMP (0): processing ID payload.

message ID = 4154642151

ISAKMP (0): processing ID payload.

message ID = 4154642151

ISAKMP (0): processing NOTIFY payload 24576

protocol 3 spi 3611334428,
message ID = 4154642151

ISAKMP (0): processing responder lifetime

ISAKMP (0): responder lifetime of 3600s

ISAKMP (0): Creating IPsec SAs

inbound SA from 172.16.172.39 to
172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0)
has spi 939761857 and conn_id 4 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes

outbound SA from 172.16.172.34 to
172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0)
has spi 3611334428 and conn_id 3 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes

IPSEC(key_engine): got a queue event...

IPSEC(initialize_sas): ,

```
(key eng. msg.) dest= 172.16.172.34, src= 172.16.172.39,
dest_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
src_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0x3803a0c1(939761857), conn_id= 4, keysize= 0,
flags= 0x4
```

```
IPSEC(initialize_sas): ,
```

```
(key eng. msg.) src= 172.16.172.34, dest= 172.16.172.39,
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0xd740971c(3611334428), conn_id= 3, keysize= 0,
flags= 0x4
```

```
return status is IKMP_NO_ERROR
```

```
pix520-1(config)#
```

Debugs PIX:

```
pix520-1# debug crypto ipsec
```

```
pix520-1# debug crypto isakmp
```

```
pix520-1# sh debug
```

```
debug crypto ipsec 1
```

```
debug crypto isakmp 1
```

```
debug fover status
```

```
tx      Off
rx      Off
open    Off
cable   Off
txdmp   Off
rxdmp   Off
ifc     Off
rxip    Off
txip    Off
get     Off
put     Off
verify  Off
switch  Off
fail    Off
fmsg    Off
```

```
ISAKMP (0): beginning Main Mode exchange
```

```
crypto_isakmp_process_block: src 172.16.172.39,
```

```
dest 172.16.172.34
```

```
OAK_MM exchange
```

```
ISAKMP (0): processing SA payload. message ID = 0
```

```
ISAKMP (0): Checking ISAKMP transform 1 against
priority 10 policy
```

```
ISAKMP:      encryption DES-CBC
```

```
ISAKMP:      hash MD5
```

```
ISAKMP:      default group 1
```

```
ISAKMP:      auth RSA sig
```

```
ISAKMP (0): atts are acceptable. Next payload is 0
```

```
ISAKMP (0): SA is doing RSA signature authentication
using id type ID_FQDN
```

```
return status is IKMP_NO_ERROR
```

```
crypto_isakmp_process_block: src 172.16.172.39,
```

```
dest 172.16.172.34
```

```
OAK_MM exchange
```

```
ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing CERT_REQ payload. message ID = 0
ISAKMP (0): peer wants a CT_X509_SIGNATURE cert
ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload
    next-payload : 6
    type          : 2
    protocol      : 17
    port         : 500
    length       : 20
ISAKMP (0): Total payload length: 24
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange
ISAKMP (0): processing ID payload. message ID = 0
ISAKMP (0): processing CERT payload. message ID = 0
ISAKMP (0): processing a CT_X509_SIGNATURE cert
ISAKMP (0): processing SIG payload. message ID = 0
ISAKMP (0): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn =
1720-1.cisco.com
ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,
M-ID of -140325145:f7a2cee7IPSEC(key_engine):
got a queue event...
IPSEC(spi_response): getting spi 0x3803a0c1(939761857)
    for SA from 172.16.172.39 to 172.16.172.34 for prot 3

return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload.
message ID = 4154642151
ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES
ISAKMP:   attributes in transform:
ISAKMP:     encaps is 1
ISAKMP:     SA life type in seconds
ISAKMP:     SA life duration (basic) of 28800
ISAKMP:     SA life type in kilobytes
ISAKMP:     SA life duration (VPI)
of 0x0 0x46 0x50 0x0
ISAKMP:     authenticator is HMAC-MD5
ISAKMP (0): atts are acceptable.
IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) dest= 172.16.172.39,
src= 172.16.172.34,
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4
```

```

ISAKMP (0): processing NONCE payload.
message ID = 4154642151

ISAKMP (0): processing ID payload.
message ID = 4154642151
ISAKMP (0): processing ID payload.
message ID = 4154642151
ISAKMP (0): processing NOTIFY payload 24576
    protocol 3 spi 3611334428,
    message ID = 4154642151
ISAKMP (0): processing responder lifetime
ISAKMP (0): responder lifetime of 3600s
ISAKMP (0): Creating IPsec SAs
    inbound SA from 172.16.172.39 to
172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0)
    has spi 939761857 and conn_id 4 and flags 4
    lifetime of 3600 seconds
    lifetime of 4608000 kilobytes
    outbound SA from 172.16.172.34 to
172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0)
    has spi 3611334428 and conn_id 3 and flags 4
    lifetime of 3600 seconds
    lifetime of 4608000 kilobytes
IPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
    (key eng. msg.) dest= 172.16.172.34, src= 172.16.172.39,
    dest_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
    src_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
    protocol= ESP, transform= esp-des esp-md5-hmac ,
    lifedur= 3600s and 4608000kb,
    spi= 0x3803a0c1(939761857), conn_id= 4, keysize= 0,
flags= 0x4
IPSEC(initialize_sas): ,
    (key eng. msg.) src= 172.16.172.34, dest= 172.16.172.39,
    src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
    dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
    protocol= ESP, transform= esp-des esp-md5-hmac ,
    lifedur= 3600s and 4608000kb,
    spi= 0xd740971c(3611334428), conn_id= 3, keysize= 0,
flags= 0x4

return status is IKMP_NO_ERROR

pix520-1(config)#

```

[Discordancia de la Fecha y hora](#)

Los Certificados en el PIX y el router son válidos para cierto intervalo de tiempo, como se demuestra en el siguiente ejemplo.

```

pix520-1# debug crypto ipsec
pix520-1# debug crypto isakmp
pix520-1# sh debug
debug crypto ipsec 1
debug crypto isakmp 1
debug fover status
    tx      Off
    rx      Off
    open    Off
    cable   Off
    txdmp   Off
    rxdmp   Off
    ifc     Off

```

rxip Off
txip Off
get Off
put Off
verify Off
switch Off
fail Off
fmsg Off

ISAKMP (0): beginning Main Mode exchange

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange

ISAKMP (0): processing SA payload. message ID = 0

ISAKMP (0): Checking ISAKMP transform 1 against
priority 10 policy

ISAKMP: encryption DES-CBC
ISAKMP: hash MD5
ISAKMP: default group 1
ISAKMP: auth RSA sig

ISAKMP (0): atts are acceptable. Next payload is 0

ISAKMP (0): SA is doing RSA signature authentication
using id type ID_FQDN

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange

ISAKMP (0): processing KE payload. message ID = 0

ISAKMP (0): processing NONCE payload. message ID = 0

ISAKMP (0): processing CERT_REQ payload. message ID = 0

ISAKMP (0): peer wants a CT_X509_SIGNATURE cert

ISAKMP (0): processing vendor id payload

ISAKMP (0): speaking to another IOS box!

ISAKMP (0): ID payload

next-payload : 6
type : 2
protocol : 17
port : 500
length : 20

ISAKMP (0): Total payload length: 24

return status is IKMP_NO_ERROR

crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_MM exchange

ISAKMP (0): processing ID payload. message ID = 0

ISAKMP (0): processing CERT payload. message ID = 0

ISAKMP (0): processing a CT_X509_SIGNATURE cert

ISAKMP (0): processing SIG payload. message ID = 0

ISAKMP (0): sa->peer.name = , sa->peer_id.id.id_fqdn.fqdn =
1720-1.cisco.com

ISAKMP (0): SA has been authenticated

ISAKMP (0): beginning Quick Mode exchange,

M-ID of -140325145:f7a2cee7IPSEC(key_engine):

got a queue event...

IPSEC(spi_response): getting spi 0x3803a0c1(939761857)

for SA from 172.16.172.39 to 172.16.172.34 for prot 3

```
return status is IKMP_NO_ERROR
crypto_isakmp_process_block: src 172.16.172.39,
dest 172.16.172.34
OAK_QM exchange
oakley_process_quick_mode:
OAK_QM_IDLE
ISAKMP (0): processing SA payload.
message ID = 4154642151
ISAKMP : Checking IPsec proposal 1

ISAKMP: transform 1, ESP_DES
ISAKMP:  attributes in transform:
ISAKMP:  encaps is 1
ISAKMP:  SA life type in seconds
ISAKMP:  SA life duration (basic) of 28800
ISAKMP:  SA life type in kilobytes
ISAKMP:  SA life duration (VPI)
of 0x0 0x46 0x50 0x0
ISAKMP:  authenticator is HMAC-MD5
ISAKMP (0): atts are acceptable.
IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) dest= 172.16.172.39,
src= 172.16.172.34,
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 0s and 0kb,
spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x4

ISAKMP (0): processing NONCE payload.
message ID = 4154642151

ISAKMP (0): processing ID payload.
message ID = 4154642151
ISAKMP (0): processing ID payload.
message ID = 4154642151
ISAKMP (0): processing NOTIFY payload 24576
protocol 3 spi 3611334428,
message ID = 4154642151
ISAKMP (0): processing responder lifetime
ISAKMP (0): responder lifetime of 3600s
ISAKMP (0): Creating IPsec SAs
inbound SA from 172.16.172.39 to
172.16.172.34 (proxy 1.1.1.0 to 192.168.4.0)
has spi 939761857 and conn_id 4 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes
outbound SA from 172.16.172.34 to
172.16.172.39 (proxy 192.168.4.0 to 1.1.1.0)
has spi 3611334428 and conn_id 3 and flags 4
lifetime of 3600 seconds
lifetime of 4608000 kilobytes
IPSEC(key_engine): got a queue event...
IPSEC(initialize_sas): ,
(key eng. msg.) dest= 172.16.172.34, src= 172.16.172.39,
dest_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
src_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0x3803a0c1(939761857), conn_id= 4, keysize= 0,
flags= 0x4
IPSEC(initialize_sas): ,
(key eng. msg.) src= 172.16.172.34, dest= 172.16.172.39,
src_proxy= 192.168.4.0/255.255.255.0/0/0 (type=4),
```

```
dest_proxy= 1.1.1.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac ,
lifedur= 3600s and 4608000kb,
spi= 0xd740971c(3611334428), conn_id= 3, keysize= 0,
flags= 0x4
```

```
return status is IKMP_NO_ERROR
```

```
pix520-1(config)#
```

La salida del comando show siguiente también demuestra el intervalo de tiempo.

```
1720-1#sh crypto ca crls
```

```
CRL Issuer Name:
```

```
OU = sjvpn, O = cisco, C = us
LastUpdate: 16:17:34 PST Jan 10 2002
NextUpdate: 17:17:34 PST Jan 11 2002
Retrieved from CRL Distribution Point:
LDAP: CN = CRL1, OU = sjvpn, O = cisco, C = us
```

Si la fecha y hora del reloj en el router o el PIX no cae entre las fechas de inicio y fin en los Certificados y la actualización siguiente/más reciente del CRL, después usted conseguirá el error siguiente durante la negociación de la fase 1:

Debug del router:

```
1720-1#sh crypto ca crls
```

```
CRL Issuer Name:
```

```
OU = sjvpn, O = cisco, C = us
LastUpdate: 16:17:34 PST Jan 10 2002
NextUpdate: 17:17:34 PST Jan 11 2002
Retrieved from CRL Distribution Point:
LDAP: CN = CRL1, OU = sjvpn, O = cisco, C = us
```

En este ejemplo, el tiempo del router fue fijado 16:07:02 al 28 de febrero 1993, que no baja entre los tiempos válidos requeridos por CA. Para solucionar el problema, fije el momento apropiado en el router.

```
1720-1#clock set 01:05:01 january 11 2002
```

```
1720-1#sh clock
```

```
01:05:04.903 PST Fri Jan 11 2002
```

```
1720-1#
```

[Puerto 80 HTTP/TCP bloqueado](#)

El router y el PIX utilizan el puerto TCP 80 durante la autenticación y la inscripción con el servidor de CA. Si usted tiene la inscripción o problemas de autenticación, verifique que el puerto 80 HTTP/TCP no se esté bloqueando entre el router/PIX y el servidor de CA.

[PIX/Router no tiene el CRL](#)

Puesto que no especificamos el **comando crl optional** en el PIX/router, ambos dispositivos marcarán para saber si hay el CRL durante la negociación del fase uno. Si el CRL no está presente, usted verá los errores siguientes.

PIX debug:

```
1720-1#clock set 01:05:01 january 11 2002
```

```
1720-1#sh clock
```

```
01:05:04.903 PST Fri Jan 11 2002
```

```
1720-1#
```


Para resolver este problema, consiga los Certificados del servidor de CA publicando un comando de la petición del **crl Ca ca nickname**; utilizamos el **cr ca crl request Cisco**.

[Elimine los certificados y los pares de claves RSA](#)

Usted puede necesitar borrar los Certificados digitales o los pares claves RSA del router o del PIX.

[Certificados del router de la cancelación y pares claves RSA](#)

Comandos:

- **ningún ca identity crypto ca nickname** - Borre los certificados del router.
- **zeroize rsa del crypto key** - Borre el par clave RSA.

Para borrar los Certificados, siga el ejemplo abajo:

```
1720-1#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
1720-1(config)#no crypto ca identity vpn
% Removing an identity will destroy all certificates received from
the related Certificate Authority.

Are you sure you want to do this? [yes/no]: y
% Be sure to ask the CA administrator to revoke your certificates.

No enrollment sessions are currently active.
```

```
1720-1(config)#
1720-1#sh cr ca cert
1720-1#
!--- The certificates are no longer available.
```

Para borrar el par clave RSA en el router, siga el ejemplo abajo:

```
1720-1(config)#crypto key zeroize rsa
% Keys to be removed are named 1720-1.cisco.com.
Do you really want to remove these keys? [yes/no]: y
1720-1(config)#.
```

```
1720-1#sh crypto key mypubkey rsa
1720-1#
!-- The RSA key pairs are no longer available.
```

[Borre los Certificados PIX y los pares claves RSA](#)

Comandos:

- **ningún ca identity ca nickname** - Borre los Certificados del PIX.
- **zeroize rsa Ca** - Borre el par de claves RSA del PIX.

Para borrar los Certificados en el PIX, siga el ejemplo abajo:

```
pix520-1(config)# no ca identity cisco
% Removing the identity will destroy all certificates.
% Be sure to ask the CA administrator to revoke your certificates.

pix520-1(config)# sh cr ca cert
pix520-1(config)#
```

!--- The certificates are no longer available.

Para borrar el par clave RSA en el PIX, siga el ejemplo abajo:

```
pix520-1(config)# ca zeroize rsa
```

```
pix520-1(config)# sh ca mypubkey rsa
```

!--- The RSA key pairs are no longer available.

[Información Relacionada](#)

- [Página de soporte de IPsec](#)
- [Página de Soporte de PIX](#)
- [Solicitudes de Comentarios \(RFC\)](#)
- [Soporte Técnico - Cisco Systems](#)