

# Cómo configurar la autenticación de RADIUS para los VPDN

## Contenido

[Introducción](#)

[prerrequisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenciones](#)

[Antecedentes](#)

[Configurar](#)

[Diagrama de la red](#)

[Configuración del servidor](#)

[Configuración del router](#)

[Verificación](#)

[Troubleshooting](#)

[Comandos para resolución de problemas](#)

[‘Resultado de debug’](#)

[Información Relacionada](#)

## [Introducción](#)

Una red virtual de marcación privada (VPDN) permite que un servicio de marcación de red privada se extienda a servidores de acceso remoto (que se definen como concentrador de acceso [LAC]) L2TP. Cuando un cliente de Point-to-Point Protocol (PPP) se comunica con un LAC, el LAC determina que debería reenviar la sesión PPP a un L2TP Network Server (LNS) para ese cliente, el cual luego autentica al usuario y comienza la negociación PPP. Una vez que finaliza la configuración de PPP, todas las tramas se envían mediante el LAC al cliente y al LNS.

Esta configuración de muestra permite que usted utilice la autenticación de RADIUS con los VPDN. El LAC pregunta al servidor de RADIUS, determina que el LNS para remitir al usuario, y establece el túnel apropiado.

Para más información sobre los VPDN refiera [comprensión del VPDN](#).

## [prerrequisitos](#)

### [Requisitos](#)

No hay requisitos específicos para este documento.

## Componentes Utilizados

La información que contiene este documento se basa en las siguientes versiones de software y hardware.

- Versión de UNIX 2.x.x del Cisco Secure ACS y posterior o Merit RADIUS
- Software Release 11.2 y Posterior de Cisco IOS®

La información que contiene este documento se creó a partir de los dispositivos en un ambiente de laboratorio específico. Todos los dispositivos que se utilizan en este documento se pusieron en funcionamiento con una configuración verificada (predeterminada). Si la red está funcionando, asegúrese de haber comprendido el impacto que puede tener cualquier comando.

## Convenciones

Para obtener más información sobre las convenciones del documento, consulte [Convenciones de Consejos Técnicos de Cisco](#).

## Antecedentes

En este ejemplo, el usuario es "jsmith@hp.com" con la contraseña "prueba". Cuando "jsmith@hp.com" marca en el router del ISP, el router del ISP envía el "hp.com" userid al servidor de RADIUS ISP. El servidor ISP encuentra el userid "hp.com" y envía su tunnel-id ("isp"), la dirección IP del router gateway (HGW) (10.31.1.50), la contraseña ("hello") del servidor de acceso a la red (NAS) y la contraseña del gateway ("there") de regreso al router ISP.

El router del ISP inicia un túnel y conecta con 10.31.1.50 al router HGW, que autentica al usuario "HP-GW" localmente y adelante la contraseña para la identificación del usuario "ISP" ("hola") al servidor de RADIUS HGW. Una vez que se establecen los túneles, autentican al router del ISP adelante al router HGW, y el userid ("jsmith@hp.com ") y la contraseña ("prueba") del usuario que marca en este usuario en el servidor HGW. En este ejemplo, llaman al router del ISP "koala" y llaman al router HGW los "sneetches".

## Configurar

En esta sección encontrará la información para configurar las funciones descritas en este documento.

### Diagrama de la red

Este documento utiliza la configuración de red que se muestra en el siguiente diagrama.

### Configuración del servidor

### Configuración de Merit RADIUS

```
!--- The RADIUS Server must support Cisco av-pairs. !--- This user is on the ISP RADIUS server.  
hp.com Password = "cisco" Service-Type = Outbound-User, cisco-avpair = "vpdn:tunnel-id=isp",  
cisco-avpair = "vpdn:ip-addresses=10.31.1.50", cisco-avpair = "vpdn:nas-password=hello", cisco-
```

```
avpair = "vpdn:gw-password=there" !--- The next two users are on the HGW Server. isp Password =
"hello", Service-Type = Framed, Framed-Protocol = PPP jsmith@hp.com Password = "test", Service-
Type = Framed, Framed-Protocol = PPP
```

## Configuración de Secure ACS UNIX 2.x.x de Cisco

```
!--- This user is on the ISP server. # ./ViewProfile -p 9900 -u hp.com User Profile Information
user = hp.com{ profile_id = 86 profile_cycle = 1 RADIUS=Cisco { check_items= { 2="cisco" }
reply_attributes= { 9,1="vpdn:tunnel-id=isp" 9,1="vpdn:ip-addresses=10.31.1.50" 9,1="vpdn:NAS-
password=hello" 9,1="vpdn:gw-password=there" } } } !--- The next two users are on the HGW
Server. # ./ViewProfile -p 9900 -u isp User Profile Information user = isp{ profile_id = 70
profile_cycle = 1 RADIUS=Cisco { check_items= { 2="hello" } reply_attributes= { 6=2 7=1 } } } #
./ViewProfile -p 9900 -u jsmith@hp.com User Profile Information user = jsmith@hp.com{ profile_id
= 84 profile_cycle = 1 RADIUS=Cisco { check_items= { 2="test" } reply_attributes= { 6=2 7=1 } }
}
```

## Configuración del router

### Configuración del router del ISP

```
koala#show running config Building configuration...
Current configuration: ! version 11.3 no service
password-encryption service udp-small-servers service
tcp-small-servers ! hostname koala ! aaa new-model aaa
authentication ppp default if-needed RADIUS aaa
authorization network default RADIUS aaa accounting
network default start-stop RADIUS enable password ww !
vpdn enable !--- VPDN is enabled. ! interface Ethernet0
ip address 10.31.1.5 255.255.255.0 ! interface Serial0
shutdown ! interface Serial1 shutdown ! interface Async1
ip unnumbered Ethernet0 encapsulation ppp async mode
dedicated no peer default ip address no cdp enable ppp
authentication chap ! ip default-gateway 10.31.1.1 no ip
classless ip route 0.0.0.0 0.0.0.0 10.31.1.1 logging
trap debugging logging 171.68.118.101 snmp-server
community public RW snmp-server enable traps config
snmp-server host 171.68.118.105 traps public RADIUS-
server host 171.68.120.194 auth-port 1645 acct-port 1646
RADIUS-server key cisco !--- Specify RADIUS server
information on the NAS. ! line con 0 password WW line 1
password WW autoselect ppp modem InOut transport input
all stopbits 1 speed 115200 flowcontrol hardware line 2
16 autoselect during-login line aux 0 line vty 0 4 exec-
timeout 0 0 password WW ! end
```

### Configuración del router HGW

```
Sneetches#show running config Building configuration...
Current configuration: ! version 11.3 no service
password-encryption service udp-small-servers service
tcp-small-servers ! hostname Sneetches ! aaa new-model
aaa authentication ppp default RADIUS local aaa
authorization network default RADIUS local aaa
accounting network default start-stop RADIUS ! username
hp-gw password 0 there username isp password 0 hello
vpdn enable !--- Enable VPDN. vpdn incoming isp hp-gw
virtual-template 1 !--- Specify the remote host (the
network access server) !--- the local name (the home
gateway) to use for authenticating !--- and the virtual
template to use. ! interface Ethernet0 ip address
10.31.1.50 255.255.255.0 ! interface Ethernet1 no ip
address shutdown ! interface Virtual-Template1 !---
Create a virtual template interface. ip unnumbered
Ethernet0 !--- Un-number the Virtual interface to an
```

```
available LAN interface. peer default ip address pool
async !--- Use the pool "async" to assign the IP address
for incoming connections. ppp authentication chap !---
Use CHAP authentication for the incoming connection. !
interface Serial0 shutdown ! interface Serial1 shutdown
! ip local pool async 1.1.1.1 1.1.1.6 ip default-gateway
10.31.1.1 no ip classless ip route 0.0.0.0 0.0.0.0
10.31.1.1 RADIUS-server host 171.68.118.101 auth-port
1645 acct-port 1646 RADIUS-server timeout 20 RADIUS-
server key cisco !--- Specify RADIUS server information
on the NAS. ! line con 0 exec-timeout 3600 0 line aux 0
line vty 0 4 password WW ! end
```

## Verificación

Actualmente, no hay un procedimiento de verificación disponible para esta configuración.

## Troubleshooting

En esta sección encontrará información que puede utilizar para solucionar problemas de configuración.

## Comandos para resolución de problemas

La herramienta del Output Interpreter soportan a los ciertos comandos show, que permite que usted vea una análisis de la salida del comando show.

**Nota:** Antes de ejecutar un comando debug, consulte **Información Importante sobre Comandos Debug**.

- **haga el debug de la autenticación aaa** — Visualiza la información sobre el Terminal Access Controller Access Control System AAA/más la autenticación (TACACS+).
- **debug aaa authorization** — Visualiza la información sobre la autorización AAA/TACACS+.
- **debug ppp negotiation** — Muestra los paquetes PPP transmitidos durante el inicio PPP, durante el cual se negocian las opciones PPP.
- **debug RADIUS** — Visualiza la información de debugging detallada asociada al RADIUS.
- **debug vpdn errors** — Visualiza los errores que evitan que un túnel PPP sea establecido o los errores que hacen un túnel establecido ser cerrados.
- **debug vpdn events** — Muestra mensajes relativos a eventos que forman parte del establecimiento o cierre normal del túnel PPP.
- **debug vpdn l2f-errors** — Visualiza los errores del protocolo de la capa 2 que previenen el establecimiento de la capa 2 o previenen su funcionamiento normal.
- **debug vpdn l2f-events** — Visualiza los mensajes sobre los eventos que son establecimiento del túnel normal de la parte de PPP o apagan para la capa 2.
- **debug vpdn l2f-packets** — Mensajes de las visualizaciones sobre las encabezados y el estatus del Layer 2 Forwarding Protocol.
- **debug vpdn packets** — Las visualizaciones acodan 2 errores y eventos del Tunnel Protocol que sean una parte del establecimiento normal de túneles o apagan para los VPDN.
- **debug vtemplate** - Muestra información de clonación para una interfaz de acceso virtual desde el momento en que se clona desde una plantilla virtual hasta el momento en que la

interfaz de acceso virtual se cae al finalizar la llamada.

## 'Resultado de debug'

### Depuración adecuada del router del ISP

```
koala#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on RADIUS protocol debugging is on koala# %LINK-3-UPDOWN: Interface Async1, changed state to up
17:28:19: VPDN: Looking for tunnel -- hp.com -- 17:28:19: AAA/AUTHEN: create_user (0x15D28C)
user='hp.com' ruser='' port='Async1' rem_addr='' authen_type=NONE service=LOGIN priv=0 17:28:19:
AAA/AUTHOR/VPDN (982041598): Port='Async1' list='default' service=NET 17:28:19: AAA/AUTHOR/VPDN:
(982041598) user='hp.com' 17:28:19: AAA/AUTHOR/VPDN: (982041598) send AV service=ppp 17:28:19:
AAA/AUTHOR/VPDN: (982041598) send AV protocol=vpdn 17:28:19: AAA/AUTHOR/VPDN (982041598) found
list "default" 17:28:19: AAA/AUTHOR/VPDN: (982041598) Method=RADIUS 17:28:19: RADIUS:
authenticating to get author data 17:28:19: RADIUS: Computed extended port value 0:1: 17:28:19:
RADIUS: Initial Transmit id 62 171.68.120.194:1645, Access-Request, len 70 17:28:19: Attribute 4
6 0A1F0105 17:28:19: Attribute 5 6 00000001 17:28:19: Attribute 61 6 00000000 17:28:19:
Attribute 1 8 68702E63 17:28:19: Attribute 2 18 8070079C 17:28:19: Attribute 6 6 00000005
17:28:19: RADIUS: Received from id 62 171.68.120.194:1645, Access-Accept, len 143 17:28:19:
Attribute 26 26 0000000901147670 17:28:19: Attribute 26 36 00000009011E7670 17:28:19: Attribute
26 31 0000000901197670 17:28:19: Attribute 26 30 0000000901187670 !--- These messages can be
decrypted using the OI tool. !--- As of Cisco IOS Software Release 12.2(11)T, !--- the output
was changed to be readable. 17:28:19: RADIUS: saved authorization data for user 15D28C at 10EE74
17:28:19: RADIUS: cisco AVPair "vpdn:tunnel-id=isp" 17:28:19: RADIUS: cisco AVPair "vpdn:ip-
addresses=10.31.1.50" 17:28:19: RADIUS: cisco AVPair "vpdn:nas-password=hello" 17:28:19: RADIUS:
cisco AVPair "vpdn:gw-password=there" 17:28:19: AAA/AUTHOR (982041598): Post authorization
status = PASS_ADD 17:28:19: AAA/AUTHOR/VPDN: Processing AV service=ppp 17:28:19:
AAA/AUTHOR/VPDN: Processing AV protocol=vpdn 17:28:19: AAA/AUTHOR/VPDN: Processing AV tunnel-
id=isp 17:28:19: AAA/AUTHOR/VPDN: Processing AV ip-addresses=10.31.1.50 17:28:19:
AAA/AUTHOR/VPDN: Processing AV nas-password=hello 17:28:19: AAA/AUTHOR/VPDN: Processing AV gw-
password=there 17:28:19: VPDN: Get tunnel info with NAS isp GW hp.com, IP 10.31.1.50 !--- The
RADIUS server returns the attributes the !--- NAS should use for the tunnel. !--- Tunnel-id is
"ISP" and the IP address of HGW is 10.31.1.50. 17:28:19: AAA/AUTHEN: free_user (0x15D28C)
user='hp.com' ruser='' port='Async1' rem_addr='' authen_type=NONE service=LOGIN priv=0 17:28:19:
VPDN: Forward to address 10.31.1.50 17:28:19: As1 VPDN: Forwarding... 17:28:19: AAA/AUTHEN:
create_user (0x15D334) user='jsmith@hp.com' ruser='' port='Async1' rem_addr='async'
authen_type=CHAP service=PPP priv=1 17:28:19: As1 VPDN: Bind interface direction=1 17:28:19: As1
VPDN: jsmith@hp.com is forwarded 17:28:19: AAA/ACCT/NET/START User jsmith@hp.com, Port Async1,
List "" 17:28:19: AAA/ACCT/NET: Found list "default" 17:28:19: RADIUS: Computed extended port
value 0:1: 17:28:19: RADIUS: Initial Transmit id 63 171.68.120.194:1646, Accounting-Request, len
93 17:28:19: Attribute 4 6 0A1F0105 17:28:19: Attribute 5 6 00000001 17:28:19: Attribute 61 6
00000000 17:28:19: Attribute 1 15 6A736D69 17:28:19: Attribute 40 6 00000001 17:28:19: Attribute
45 6 00000002 17:28:19: Attribute 6 6 00000002 17:28:19: Attribute 44 10 30303030 17:28:19:
Attribute 7 6 7670646E 17:28:19: Attribute 41 6 00000000 17:28:19: RADIUS: Received from id 63
171.68.120.194:1646, Accounting-response, len 20 %LINEPROTO-5-UPDOWN: Line protocol on Interface
Async1, changed state to up koala# !--- The user finishes and disconnects. %LINEPROTO-5-UPDOWN:
Line protocol on Interface Async1, changed state to down %LINK-5-CHANGED: Interface Async1,
changed state to reset 17:28:48: As1 VPDN: Cleanup 17:28:48: As1 VPDN: Reset 17:28:48: As1 VPDN:
Reset 17:28:48: As1 VPDN: Unbind interface 17:28:48: AAA/ACCT/NET/STOP User jsmith@hp.com, Port
Async1: task_id=20 start_time=900759730 timezone=UTC service=vpdn disc-cause=2 disc-cause-
ext=1011 pre-bytes-in=-226131998 pre-bytes-out=-1034130241 pre-paks-in=-63570 pre-paks-out=-
64410 bytes_in=1999 bytes_out=364 paks_in=29 paks_out=12 pre-session-time=5 elapsed_time=29
data-rate=0 xmit-rate=0 17:28:48: RADIUS: Computed extended port value 0:1: 17:28:48: RADIUS:
Initial Transmit id 64 171.68.120.194:1646, Accounting-Request, len 129 17:28:48: Attribute 4 6
0A1F0105 17:28:48: Attribute 5 6 00000001 17:28:48: Attribute 61 6 00000000 17:28:48: Attribute
1 15 6A736D69 17:28:48: Attribute 40 6 00000002 17:28:48: Attribute 45 6 00000002 17:28:48:
Attribute 6 6 00000002 17:28:48: Attribute 44 10 30303030 17:28:48: Attribute 7 6 7670646E
17:28:48: Attribute 49 6 00000002 17:28:48: Attribute 42 6 000007CF 17:28:48: Attribute 43 6
0000016C 17:28:48: Attribute 47 6 0000001D 17:28:48: Attribute 48 6 0000000C 17:28:48: Attribute
46 6 0000001D 17:28:48: Attribute 41 6 00000000 17:28:48: RADIUS: Received from id 64
```

171.68.120.194:1646, Accounting-response, len 20 %LINK-3-UPDOWN: Interface Async1, changed state to down 17:28:51: AAA/AUTHEN: free\_user (0x15D334) user='jsmith@hp.com' ruser='' port='Async1' rem\_addr='async' authen\_type=CHAP service=PPP priv=1 koala#

## Depuración adecuada del router HGW'

Sneetches#**show debug** General OS: AAA Authentication debugging is on AAA Authorization debugging is on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on RADIUS protocol debugging is on Sneetches# 17:28:21: AAA/AUTHEN: create\_user (0x14A914) user='hp-gw' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: AAA/AUTHEN/START (496523999): port='' list='default' action=SENAUTH service=PPP 17:28:21: AAA/AUTHEN/START (496523999): found list default 17:28:21: AAA/AUTHEN/START (496523999): Method=RADIUS 17:28:21: RADIUS: SENDPASS not supported (action=4) 17:28:21: AAA/AUTHEN (496523999): status = ERROR 17:28:21: AAA/AUTHEN/START (496523999): Method=LOCAL 17:28:21: AAA/AUTHEN (496523999): status = PASS 17:28:21: AAA/AUTHEN: free\_user (0x14A914) user='hp-gw' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: AAA/AUTHEN: create\_user (0x14A914) user='isp' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: AAA/AUTHEN/START (3095573082): port='' list='default' action=SENAUTH service=PPP 17:28:21: AAA/AUTHEN/START (3095573082): found list default 17:28:21: AAA/AUTHEN/START (3095573082): Method=RADIUS 17:28:21: RADIUS: SENDPASS not supported (action=4) 17:28:21: AAA/AUTHEN (3095573082): status = ERROR 17:28:21: AAA/AUTHEN/START (3095573082): Method=LOCAL 17:28:21: AAA/AUTHEN (3095573082): status = PASS 17:28:21: AAA/AUTHEN: free\_user (0x14A914) user='isp' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: AAA/AUTHEN: create\_user (0x14ADB4) user='isp' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: AAA/AUTHEN/START (3506257139): port='' list='default' action=LOGIN service=PPP 17:28:21: AAA/AUTHEN/START (3506257139): found list default 17:28:21: AAA/AUTHEN/START (3506257139): Method=RADIUS 17:28:21: RADIUS: Initial Transmit id 53 171.68.118.101:1645, Access-Request, len 68 17:28:21: Attribute 4 6 0A1F0132 17:28:21: Attribute 61 6 00000000 17:28:21: Attribute 1 5 69737003 17:28:21: Attribute 3 19 10C82B7A 17:28:21: Attribute 6 6 00000002 17:28:21: Attribute 7 6 00000001 17:28:21: RADIUS: Received from id 53 171.68.118.101:1645, Access-Accept, len 32 17:28:21: Attribute 6 6 00000002 17:28:21: Attribute 7 6 00000001 17:28:21: AAA/AUTHEN (3506257139): status = PASS 17:28:21: VPDN: Chap authentication succeeded for isp 17:28:21: AAA/AUTHEN: free\_user (0x14ADB4) user='isp' ruser='' port='' rem\_addr='' authen\_type=CHAP service=PPP priv=1 17:28:21: Vif VPDN: Virtual interface created for jsmith@hp.com 17:28:21: Vif VPDN: Set to Async interface 17:28:21: Vif VPDN: Clone from Vtemplate 1 filterPPP=0 blocking %LINK-3-UPDOWN: Interface Virtual-Access1, changed state to up 17:28:23: Vif VPDN: Bind interface direction=2 17:28:23: Vif VPDN: PPP LCP accepted sent & rcv CONFACK 17:28:23: AAA/AUTHEN: create\_user (0x143368) user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem\_addr='async' authen\_type=CHAP service=PPP priv=1 17:28:23: AAA/AUTHEN/START (637397616): port='Virtual-Access1' list='' action=LOGIN service=PPP 17:28:23: AAA/AUTHEN/START (637397616): using "default" list 17:28:23: AAA/AUTHEN/START (637397616): Method=RADIUS 17:28:23: RADIUS: Computed extended port value 0:60100: 17:28:23: RADIUS: Initial Transmit id 54 171.68.118.101:1645, Access-Request, len 78 17:28:23: Attribute 4 6 0A1F0132 17:28:23: Attribute 5 6 0000EAC4 17:28:23: Attribute 1 15 6A736D69 17:28:23: Attribute 3 19 186C2AC9 17:28:23: Attribute 6 6 00000002 17:28:23: Attribute 7 6 00000001 17:28:23: RADIUS: Received from id 54 171.68.118.101:1645, Access-Accept, len 32 17:28:23: Attribute 6 6 00000002 17:28:23: Attribute 7 6 00000001 17:28:23: AAA/AUTHEN (637397616): status = PASS 17:28:23: AAA/AUTHOR/LCP Vif: Authorize LCP 17:28:23: AAA/AUTHOR/LCP Vif (1528831370): Port='Virtual-Access1' list='' service=NET 17:28:23: AAA/AUTHOR/LCP: Vif (1528831370) user='jsmith@hp.com' 17:28:23: AAA/AUTHOR/LCP: Vif (1528831370) send AV service=ppp 17:28:23: AAA/AUTHOR/LCP: Vif (1528831370) send AV protocol=lcp 17:28:23: AAA/AUTHOR/LCP (1528831370) found list "default" 17:28:23: AAA/AUTHOR/LCP: Vif (1528831370) Method=RADIUS 17:28:23: AAA/AUTHOR (1528831370): Post authorization status = PASS\_REPL 17:28:23: AAA/AUTHOR/LCP Vif: Processing AV service=ppp 17:28:23: AAA/ACCT/NET/START User jsmith@hp.com, Port Virtual-Access1, List "" 17:28:23: AAA/ACCT/NET: Found list "default" 17:28:23: AAA/AUTHOR/FSM Vif: (0): Can we start IPCP? 17:28:23: AAA/AUTHOR/FSM Vif (4249637449): Port='Virtual-Access1' list='' service=NET 17:28:23: AAA/AUTHOR/FSM: Vif (4249637449) user='jsmith@hp.com' 17:28:23: AAA/AUTHOR/FSM: Vif (4249637449) send AV service=ppp 17:28:23: AAA/AUTHOR/FSM: Vif (4249637449) send AV protocol=ip 17:28:23: AAA/AUTHOR/FSM (4249637449) found list "default" 17:28:23: AAA/AUTHOR/FSM: Vif (4249637449) Method=RADIUS 17:28:23: AAA/AUTHOR (4249637449): Post authorization status = PASS\_REPL 17:28:23: AAA/AUTHOR/FSM Vif: We can start IPCP 17:28:23: RADIUS: Computed extended port value 0:60100: 17:28:23: RADIUS: Initial Transmit id 55 171.68.118.101:1646, Accounting-Request, len 87 17:28:23: Attribute 4 6 0A1F0132 17:28:23: Attribute 5 6 0000EAC4 17:28:23: Attribute 1 15



```

6A736D69 17:28:23: Attribute 40 6 00000001 17:28:23: Attribute 45 6 00000001 17:28:23: Attribute
6 6 00000002 17:28:23: Attribute 44 10 30303030 17:28:23: Attribute 7 6 00000001 17:28:23:
Attribute 41 6 00000000 17:28:23: RADIUS: Received from id 55 171.68.118.101:1646, Accounting-
response, len 20 17:28:23: AAA/AUTHOR/IPCP Vil: Start. Her address 0.0.0.0, we want 0.0.0.0
17:28:23: AAA/AUTHOR/IPCP Vil: Processing AV service=ppp 17:28:23: AAA/AUTHOR/IPCP Vil:
Authorization succeeded 17:28:23: AAA/AUTHOR/IPCP Vil: Done. Her address 0.0.0.0, we want
0.0.0.0 17:28:23: AAA/AUTHOR/IPCP Vil: Start. Her address 0.0.0.0, we want 1.1.1.1 17:28:23:
AAA/AUTHOR/IPCP Vil: Processing AV service=ppp 17:28:23: AAA/AUTHOR/IPCP Vil: Authorization
succeeded 17:28:23: AAA/AUTHOR/IPCP Vil: Done. Her address 0.0.0.0, we want 1.1.1.1 17:28:24:
AAA/AUTHOR/IPCP Vil: Start. Her address 1.1.1.1, we want 1.1.1.1 17:28:24: AAA/AUTHOR/IPCP Vil
(923857566): Port='Virtual-Access1' list='' service=NET 17:28:24: AAA/AUTHOR/IPCP: Vil
(923857566) user='jsmith@hp.com' 17:28:24: AAA/AUTHOR/IPCP: Vil (923857566) send AV service=ppp
17:28:24: AAA/AUTHOR/IPCP: Vil (923857566) send AV protocol=ip 17:28:24: AAA/AUTHOR/IPCP: Vil
(923857566) send AV addr*1.1.1.1 17:28:24: AAA/AUTHOR/IPCP (923857566) found list "default"
17:28:24: AAA/AUTHOR/IPCP: Vil (923857566) Method=RADIUS 17:28:24: AAA/AUTHOR (923857566): Post
authorization status = PASS_REPL 17:28:24: AAA/AUTHOR/IPCP Vil: Reject 1.1.1.1, using 1.1.1.1
17:28:24: AAA/AUTHOR/IPCP Vil: Processing AV service=ppp 17:28:24: AAA/AUTHOR/IPCP Vil:
Processing AV addr*1.1.1.1 17:28:24: AAA/AUTHOR/IPCP Vil: Authorization succeeded 17:28:24:
AAA/AUTHOR/IPCP Vil: Done. Her address 1.1.1.1, we want 1.1.1.1 %LINEPROTO-5-UPDOWN: Line
protocol on Interface Virtual-Access1, changed state to up Sneetches# !--- The user finishes and
disconnects. Sneetches# 17:28:50: Vil VPDN: Reset 17:28:50: Vil VPDN: Reset %LINK-3-UPDOWN:
Interface Virtual-Access1, changed state to down 17:28:50: Vil VPDN: Cleanup 17:28:50: Vil VPDN:
Reset 17:28:50: Vil VPDN: Reset 17:28:50: Vil VPDN: Unbind interface 17:28:50: Vil VPDN: Reset
17:28:50: Vil VPDN: Reset 17:28:50: AAA/ACCT/NET/STOP User jsmith@hp.com, Port Virtual-Access1:
task_id=14 start_time=900759731 timezone=UTC service=ppp protocol=ip addr=1.1.1.1 disc-cause=2
disc-cause-ext=1011 pre-bytes-in=0 pre-bytes-out=42 pre-paks-in=0 pre-paks-out=2 bytes_in=882
bytes_out=356 paks_in=17 paks_out=11 pre-session-time=0 elapsed_time=27 data-rate=0 xmit-rate=0
17:28:50: RADIUS: Computed extended port value 0:60100: 17:28:50: RADIUS: Initial Transmit id 56
171.68.118.101:1646, Accounting-Request, len 129 17:28:50: Attribute 4 6 0A1F0132 17:28:50:
Attribute 5 6 0000EAC4 17:28:50: Attribute 1 15 6A736D69 17:28:50: Attribute 40 6 00000002
17:28:50: Attribute 45 6 00000001 17:28:50: Attribute 6 6 00000002 17:28:50: Attribute 44 10
30303030 17:28:50: Attribute 7 6 00000001 17:28:50: Attribute 8 6 01010101 17:28:50: Attribute
49 6 00000002 17:28:50: Attribute 42 6 00000372 17:28:50: Attribute 43 6 00000164 17:28:50:
Attribute 47 6 00000011 17:28:50: Attribute 48 6 0000000B 17:28:50: Attribute 46 6 0000001B
17:28:50: Attribute 41 6 00000000 17:28:50: RADIUS: Received from id 56 171.68.118.101:1646,
Accounting-response, len 20 17:28:50: AAA/AUTHEN: free_user (0x143368) user='jsmith@hp.com'
ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP service=PPP priv=1 %LINEPROTO-
5-UPDOWN: Line protocol on Interface Virtual-Access1, changed state to down Sneetches#

```

## Debugs para la falla de conexión en el router del ISP

```

koala#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is
on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on
RADIUS protocol debugging is on koala# !--- Problem 1: !--- User hp.com is not in the ISP
server: !--- There is no output on HGW router because the call has not gone that far. RADIUS:
Received from id 83 171.68.120.194:1645, Access-Reject, len 20 18:43:18: AAA/AUTHEN
(4063976505): status = FAIL !--- Problem 2: !--- User hp.com is not in the ISP server. !---
There is no output on HGW router because !--- the call has not gone that far. RADIUS: Received
from id 83 171.68.120.194:1645, Access-Reject, len 20 18:43:18: AAA/AUTHEN (4063976505): status
= FAIL !--- Problem 3: !--- Problem in tunnel definition on HGW router; in HGW configuration !--
- vpdn incoming hp-gw isp virtual-template 1 is inserted !--- instead of vpdn incoming isp hp-gw
virtual-template 1. %VPDN-5-UNREACH: L2F HGW 10.31.1.50 is unreachable VPDN: Timeout opening
tunnel to 10.31.1.50 VPDN: Free busy address 10.31.1.50 !--- Problem 4: !--- User "isp" or "hp-
gw" is removed from HGW router. %VPDN-6-AUTHENFAIL: L2F NAS koala, authentication failure for
tunnel hp-gw; Invalid key !--- Problem 5: !--- User "isp" is not in the HGW server. %VPDN-6-
AUTHENFAIL: L2F HGW , AAA authentication failure for tunnel hp-gw !--- Problem 6: !--- User
jsmith@hp.com is not in the HGW server. %VPDN-6-AUTHENFAIL: L2F HGW hp-gw, AAA authentication
failure for As1 user jsmith@hp.com; Authentication failure

```

## Debugs para las fallas de conexión en el router HGW

```

Sneetches#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging
is on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on

```

RADIUS protocol debugging is on Sneetches# *!--- Problem 1: !--- Problem in tunnel definition on the HGW router; in HGW configuration !--- vpdn incoming hp-gw isp virtual-template 1 is inserted !--- instead of vpdn incoming isp hp-gw virtual-template 1 !--- debug vpdn l2f-errors display.*  
19:25:27: L2F: Couldn't find tunnel named isp 19:25:30: L2F: Couldn't find tunnel named isp *!--- Problem 2: !--- User "isp" is removed from the HGW router. AAA/AUTHEN (3372073334): SENDAUTH no password for isp AAA/AUTHEN (3372073334): status = ERROR AAA/AUTHEN/START (3372073334): no methods left to try AAA/AUTHEN (3372073334): status = ERROR AAA/AUTHEN/START (3372073334): failed to authenticate !--- Problem 3: !--- User "hp-gw" is removed from the HGW router. AAA/AUTHEN (3999868118): SENDAUTH no password for hp-gw AAA/AUTHEN (3999868118): status = ERROR AAA/AUTHEN/START (3999868118): no methods left to try AAA/AUTHEN (3999868118): status = ERROR AAA/AUTHEN/START (3999868118): failed to authenticate !--- Problem 4: !--- User "isp" is removed from HGW RADIUS server. RADIUS: Received from id 107 171.68.118.101:1645, Access-Reject, len 46 Attribute 18 26 41757468 AAA/AUTHEN (2759462034): status = FAIL VPDN: Chap authentication failed for isp %VPDN-6-AUTHENFAIL: L2F HGW , AAA authentication failure for tunnel isp !--- Problem 5: !--- User "jsmith@hp.com" is not in the HGW server. RADIUS: Received from id 109 171.68.118.101:1645, Access-Reject, len 46 Attribute 18 26 41757468 AAA/AUTHEN (2765235576): status = FAIL %VPDN-6-AUTHENFAIL: L2F HGW hp-gw, AAA authentication failure for V11 user jsmith@hp.com; Authentication failure*

## [Información Relacionada](#)

- [Página de soporte de la tecnología de RADIUS](#)
- [Solicitudes de Comentarios \(RFC\)](#)
- [Página de soporte de producto de Cisco Secure para UNIX](#)
- [Soporte Técnico - Cisco Systems](#)