

Contenido

[Pregunta](#)

Pregunta

¿Hay una manera de prever la Conmutación por falla o el Equilibrio de carga de los servidores LDAP?

Cisco ESA se puede configurar para proporcionar la Conmutación por falla del LDAP múltiple en la balanza de la carga y para fallar sobre el modo. Abajo está un ejemplo que muestra cómo agregar las entradas múltiples del servidor LDAP en el ESA usando el comando del **ldapconfig** del CLI. Cuando se le pregunte para el nombre de host, usted puede ingresar varios host, separados por las comas:

```
mail.example.com> ldapconfig
No LDAP server configurations.
```

```
Choose the operation you want to perform:
```

```
- NEW - Create a new server configuration.
```

```
[ ]> new
```

```
Please create a name for this server configuration (Ex: "PublicLDAP"):
```

```
[ ]> PublicLDAP2
```

```
Please enter the hostname:
```

```
[ ]> ldap1.example.com, ldap2.example.com, ldap3.example.com
```

```
Use SSL to connect to the LDAP server? [N]>
```

```
Please enter the port number:
```

```
[389]>
```

```
Please enter the base or enter 'NONE':
```

```
[dc=example,dc=com]>
```

```
Select the authentication method to use for this server configuration:
```

```
1. Anonymous
```

```
2. Password based
```

```
[1]>
```

```
Name: ldapservers
```

```
Hostname: ldap1.example.com,ldap2.example.com,ldap3.example.com Port 389
```

```
Authentication Type: anonymous
```

```
Base:dc=example,dc=com
```

```
Choose the operation you want to perform:
```

```
- SERVER - Change the server for the query.
```

```
- LDAPACCEPT - Configure whether a recipient address should be accepted or bounced/dropped.
```

```
- LDAPROUTING - Configure message routing.
```

```
- MASQUERADE - Configure domain masquerading.
```

```
- LDAPGROUP - Configure whether a sender or recipient is in a specified group.
```

```
- SMTPAUTH - Configure SMTP authentication.
```

```
[ ]>
```

```
Current LDAP server configurations:
```

```
1. ldapservers:(ldap1.example.com,ldap2.example.com,ldap3.example.com:389)
```

```
Choose the operation you want to perform:
```

```
- NEW - Create a new server configuration.
```

```
- EDIT - Modify a server configuration.
```

- DELETE - Remove a server configuration.

[]>

mail.example.com> **commit**