

# Configuración de Nexus EVPN-VXLAN Multi-Site con Route Server

## Contenido

[Introducción](#)  
[Prerequisites](#)  
[Requirements](#)  
[Componentes Utilizados](#)  
[Antecedentes](#)  
[¿En qué ayuda Multi-Site?](#)  
[Otras ventajas](#)  
[Configurar](#)  
[Diagrama de la red](#)  
[Configuración de hoja 1 del sitio 1](#)  
[Configuración de la hoja 2 del sitio 1](#)  
[Configuración de la hoja 3 del sitio 1](#)  
[Configuración de la hoja 4 del sitio 1](#)  
[Configuración de Spine-1 del Sitio 1](#)  
[Configuración de la puerta de enlace fronteriza del sitio 1-1](#)  
[Configuración de la puerta de enlace fronteriza del sitio 1-2](#)  
[Servidor del router](#)  
[Configuración de Site 2 Border Gateway-1](#)  
[Configuración de Site 2 Border Gateway-2](#)  
[Configuración de Spine-1 del Sitio 2](#)  
[Configuración de la hoja 1 del sitio 2](#)  
[Configuración de hoja 2 del sitio 2](#)  
[Configuración de la hoja 3 del sitio 2](#)  
[Configuración de la hoja 4 del sitio 2](#)  
[Verificación](#)  
[Troubleshoot](#)

## Introducción

Este documento describe cómo configurar y verificar el entorno multisitio de VPN Ethernet/LAN extensible virtual (EVPN/VxLAN) en los switches Cisco Nexus 9000. Implica el análisis de fabric virtual en nodos de hojas de vPC.

Para la conectividad de sitio a sitio, se explica el concepto de servidor de ruta.

## Prerequisites

## Requirements

Cisco recomienda que tenga conocimiento sobre estos temas:

- VPN de capa 3 de switching de etiquetas multiprotocolo (MPLS)
- Protocolo de gateway fronterizo multiprotocolo (MP-BGP)
- EVPN

## Componentes Utilizados

La información que contiene este documento se basa en las siguientes versiones de software y hardware.

Todos los folletos del sitio	N9K-C9336C-FX2	NXOS: 10.2(3)
S1_Columna1	N9K-C936C	NXOS: 10.2(4)
S1_Columna2	N9K-C936C	NXOS 9.3(5)
S1_Puerta de enlace de frontera1, S2_Puerta de enlace de frontera2, S2_Puerta de enlace de frontera1	N9K-C9332C	NXOS: 9.3(9)
S1_Puerta de enlace de frontera2	N9K-C9332C	NXOS: 10.2(4)
Servidor de ruta	N9K-C9396PX	NXOS: 9.2(2)
Host 1	N3K-C3264C-E	NXOS: 9.3(5)
Host 2 y Host 3	N3K-C3264C-E	NXOS: 9.2(2)

La información que contiene este documento se creó a partir de los dispositivos en un ambiente de laboratorio específico. Todos los dispositivos que se utilizan en este documento se pusieron en funcionamiento con una configuración verificada (predeterminada). Si tiene una red en vivo, asegúrese de entender el posible impacto de cualquier comando.

## Antecedentes

El Data Center es un conjunto de recursos que contiene la potencia informática, el almacenamiento y las aplicaciones necesarias para admitir cualquier entorno empresarial. Es vital que el diseño de la infraestructura del Data Center esté correctamente planificado. En este documento se tratan los requisitos fundamentales, como las redes hospitalarias, y cómo cumplirlos o superarlos. Las implementaciones de Data Centers e infraestructuras de TI modernas necesitan alta disponibilidad (HA), capacidad de ampliación a un ritmo más rápido y alto rendimiento en todo momento.

Algunos de los requisitos vitales explorados en el espacio de diseño/arquitectura del DC incluyen:

- Fabric Extender (FEX) mejora la densidad de puertos.

- La capacidad informática se mejora gracias a la virtualización del hardware (UCS).
- El canal de puerto mejora el ancho de banda del enlace ascendente de la capa de acceso.
- vPC mejora la redundancia a nivel de chasis.
- El fabric de redes definidas por software (SDN) mejora gracias a la infraestructura centrada en aplicaciones (ACI), que automatiza la superposición y la superposición en un fabric.
- Data Center Network Manager (DCNM) mejora la rápida implementación y compatibilidad de nuevos servicios.
- El requisito de ancho de banda para las aplicaciones de largo recorrido se mejora mediante el servicio de fibra oscura o longitud de onda.
- Por encima de todo, la redundancia geográfica y la escalabilidad son atributos clave para ampliar el entorno del Data Center. Multi-Site VxLAN/EVPN nos ayuda a tener mejores soluciones de Data Center Interconnect (DCI).

## ¿En qué ayuda Multi-Site?

La conectividad externa incluye la conexión del Data Center al resto de la red: a Internet, la WAN o el campus. Todas las opciones proporcionadas para la conectividad externa son compatibles con varios arrendatarios y se centran en el transporte de capa 3 (L3) a los dominios de red externos.


- EVPN es una solución de VPN todo en uno de próxima generación.
- No solo hace el trabajo de muchas otras tecnologías VPN, sino que es mejor también.
- Integración con redes heredadas.
- Anuncio/extensión selectiva:
  - Amplíe la única capa 2 (L2): VLAN/subredes específicas que se pueden ampliar con rutas de tipo 2.
  - Amplíe el único L3: los dominios L3 específicos se pueden ampliar con rutas de tipo 5.
- Detección automática del grupo de redundancia con rutas de tipo 4.
- Alias, extracción masiva de direcciones, indicación de Multi Homing (MH) de Split Horizon (SH) con rutas de tipo 1.
- Detección automática de terminales de túnel multidifusión y tipo de túnel multidifusión (MCAST) con rutas de tipo 3.

## Otras ventajas

- Equilibrio de cargas de trabajo entre Data Centers y nubes.
- Respuesta proactiva a las interrupciones: mitiga los riesgos de desastres próximos, como huracanes e inundaciones.
- Migraciones y mantenimiento del Data Center: eventos planificados durante un período de tiempo e integración con redes heredadas.
- Backup y recuperación ante desastres como servicio (aaS).

## Configurar

### Diagrama de la red



Topología

## Configuración de hoja 1 del sitio 1

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8
ip igmp snooping vxlan

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200

```

```

vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.54 source 10.197.214.53
  virtual peer-link destination 10.102.1.9 source 10.102.1.8 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1

```

```
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-350,2001
spanning-tree port type network
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
suppress-arp
 mcast-group 231.0.0.1
member vni 4000200
suppress-arp
 mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
```

```
switchport trunk allowed vlan 100,200
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.17.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  ip address 10.102.0.5/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.102.1.8/32
  ip address 10.201.201.201/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

router ospf 100
  router-id 10.102.0.5
router bgp 100
  router-id 10.102.0.5
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.102.0.3
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended

evpn
  vni 4000100 12
  rd auto
  route-target import auto
  route-target export auto
  vni 4000200 12
  rd auto
  route-target import auto
```

```

route-target export auto
vni 4000301 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
  route-target import auto
  route-target export auto

```

## Configuración de la hoja 2 del sitio 1

```

feature nxapi
feature sftp-server
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto

```

```
route-target both auto evpn

vrf context vrf_1
vni 4000501
rd auto
address-family ipv4 unicast
  route-target both auto
  route-target both auto evpn

vrf context vrf_2
vni 4000502
rd auto
address-family ipv4 unicast
  route-target both auto
  route-target both auto evpn

vpc domain 100
peer-switch
  peer-keepalive destination 10.197.214.53 source 10.197.214.54
  virtual peer-link destination 10.102.1.8 source 10.102.1.9 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.100.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan200
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects

  fabric forwarding mode anycast-gateway
interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
```

```
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects

interface port-channel10
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-350,2001
  spanning-tree port type network
  vpc peer-link

interface port-channel100
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  mtu 9216
  vpc 100

interface nve1
  no shutdown
  host-reachability protocol bgp
  advertise virtual-rmac
  source-interface loopback1
  member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
  member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
  member vni 4000502 associate-vrf

interface Ethernet1/1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200
  mtu 9216
  channel-group 100
  no shutdown

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.18.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
```

```
ip address 10.102.0.8/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
  ip address 10.102.1.9/32
  ip address 10.201.201.201/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
icam monitor scale

router ospf 100
  router-id 10.102.0.8
router bgp 100
  router-id 10.102.0.8
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
  neighbor 10.102.0.3
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto
```

## Configuración de la hoja 3 del sitio 1

```
feature nxapi
feature bash-shell
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
feature ngoam

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
```

```
route-target both auto evpn

vpc domain 100
peer-switch
peer-keepalive destination 10.197.214.56 source 10.197.214.55
virtual peer-link destination 10.102.0.10 source 10.102.0.9 dscp 56
delay restore 150
peer-gateway
layer3 peer-router
ip arp synchronize

interface Vlan100
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.100.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan200
no shutdown
mtu 9216
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel12
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
vpc 2

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500,2001
spanning-tree port type network
vpc peer-link

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
suppress-arp
mcast-group 231.0.0.1
member vni 4000200
suppress-arp
mcast-group 231.0.0.2
```

```
member vni 4000502 associate-vrf

interface Ethernet1/1
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 200,300-305
    mtu 9216
    no shutdown

interface Ethernet1/2
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.19.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    no shutdown

interface Ethernet1/24
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200
    channel-group 2 mode active
    no shutdown

interface loopback0
    ip address 10.102.0.9/32
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback1
    ip address 10.102.1.10/32
    ip address 10.202.202.202/32 secondary
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback100
    vrf member vrf_2
    ip address 10.15.100.2/24

router ospf 100
    router-id 10.102.0.9
    router bgp 100
        router-id 10.102.0.9
        log-neighbor-changes
        address-family l2vpn evpn
            advertise-pip
        neighbor 10.102.0.2
            remote-as 100
            update-source loopback0
            address-family ipv4 unicast
            address-family ipv6 unicast
                send-community
                send-community extended
            address-family l2vpn evpn
                send-community
                send-community extended
        neighbor 10.102.0.3
            remote-as 100
            update-source loopback0
            address-family ipv4 unicast
```

```

address-family ipv6 unicast
  send-community
  send-community extended
address-family l2vpn evpn
  send-community
  send-community extended
    vrf vrf_2
address-family ipv4 unicast
  network 10.15.100.2/32
  network 192.168.100.0/24
neighbor 192.168.100.253
  remote-as 65111
  update-source loopback100
  ebgp-multipath 10
  address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

## Configuración de la hoja 4 del sitio 1

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay
feature ngoam

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

```

```
vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.55 source 10.197.214.56
  virtual peer-link destination 10.102.0.9 source 10.102.0.10 dscp 56
  delay restore 150
  peer-gateway
  layer3 peer-router
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
```

```
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel12
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
vpc 2

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500,2001
spanning-tree port type network
vpc peer-link

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
suppress-arp
mcast-group 231.0.0.1
member vni 4000200
suppress-arp
mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
switchport trunk allowed vlan 200,300-305
mtu 9216
no shutdown

interface Ethernet1/2
mtu 9216
port-type fabric
medium p2p
ip address 192.168.20.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200
```

```
channel-group 2 mode active
no shutdown

interface loopback0
  ip address 10.102.0.10/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.102.1.6/32
  ip address 10.202.202.202/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback100
  vrf member vrf_2
  ip address 10.15.100.1/24

router ospf 100
  router-id 10.102.0.10
router bgp 100
  router-id 10.102.0.10
  log-neighbor-changes
  address-family ipv4 unicast
  address-family ipv4 mvpn
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.102.0.3
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
vrf vrf_2
  address-family ipv4 unicast
    network 10.15.100.1/32
    network 192.168.100.0/24
  neighbor 192.168.100.253
    remote-as 65111
    update-source loopback100
    ebgp-multipath 3
    address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
```

```

route-target export auto
vni 4000200 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000301 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
  route-target import auto
  route-target export auto

```

## Configuración de Spine-1 del Sitio 1

```

feature nxapi
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan
feature vn-segment-vlan-based
feature lacp

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1

interface Ethernet1/1
  mtu 9216
  medium p2p
  ip address 192.168.17.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/2
  mtu 9216
  medium p2p
  ip address 192.168.18.11/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/3
  mtu 9216
  port-type fabric
  medium p2p

```

```
ip address 192.168.19.11/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
interface Ethernet1/4
mtu 9216
medium p2p
ip address 192.168.20.11/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
interface Ethernet1/5
mtu 9216
medium p2p
ip address 192.168.15.11/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
interface Ethernet1/6
mtu 9216
medium p2p
ip address 192.168.16.11/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown
```

```
interface loopback0
description "anycast RP address"
ip address 10.102.0.2/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale
```

```
router ospf 100
  router-id 10.102.0.2
router bgp 100
  router-id 10.102.0.2
  log-neighbor-changes
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family l2vpn evpn
  neighbor 10.31.1.1
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
      route-reflector-client
    address-family l2vpn evpn
      send-community
      send-community extended
      route-reflector-client
  neighbor 10.31.1.2
```

```
remote-as 100
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
  send-community
  send-community extended
  route-reflector-client
address-family l2vpn evpn
  send-community
  send-community extended
  route-reflector-client
neighbor 10.102.0.5
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.8
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.9
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.102.0.10
  remote-as 100
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
    route-reflector-client
  address-family l2vpn evpn
    send-community
    send-community extended
    route-reflector-client
neighbor 10.133.133.133
  remote-as 100
```

```

update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
  send-community
send-community extended
  route-reflector-client
address-family l2vpn evpn
  send-community
  send-community extended
route-reflector-client

```

## Configuración de la puerta de enlace fronteriza del sitio 1-1

```

S1-Bg1# show run
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay
evpn multisite border-gateway 100
  delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.1111.2222

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001

vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999

```

```
rd auto
address-family ipv4 unicast
  route-target both auto
  route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan303
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.13.254/24
  no ipv6 redirects
```

```
fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface nve1
    no shutdown
    host-reachability protocol bgp
    source-interface loopback1
    multisite border-gateway interface loopback100
    member vni 4000100
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.1
    member vni 4000200
        suppress-arp
        multisite ingress-replication
        mcast-group 231.0.0.2
    member vni 4000502 associate-vrf

interface Ethernet1/1
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.15.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    no shutdown
    evpn multisite fabric-tracking

interface Ethernet1/3
    mtu 9216
    ip address 10.150.150.1/24 tag 54321
    ip router ospf 100 area 0.0.0.0
    no shutdown
    evpn multisite dci-tracking

interface loopback0
    ip address 10.31.1.1/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback1
    ip address 10.133.133.133/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode

interface loopback100
    description "Multi-site VIP"
    ip address 10.100.100.1/32 tag 54321
    ip router ospf 100 area 0.0.0.0
    ip pim sparse-mode
    icam monitor scale

router ospf 100
```

```

router-id 10.31.1.1
router bgp 100
  router-id 10.31.1.1
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-TO-SITE-EXT-DCI
  address-family ipv4 mvpn
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
    address-family ipv4 mvpn
      send-community
      send-community extended
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      rewrite-evpn-rt-asn
  neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.150.150.2
    remote-as 300
    address-family ipv4 unicast
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

Configuración de la puerta de enlace fronteriza del sitio 1-2

```
S1_B2#
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay
evpn multisite border-gateway 100
    delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.2222.4444

ip pim rp-address 10.102.0.2 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
    vn-segment 4000100
vlan 200
    vn-segment 4000200
vlan 301
    vn-segment 4000301
vlan 302
    vn-segment 4000302
vlan 303
    vn-segment 4000303
vlan 350
    name L3-VNI
    vn-segment 4000999
vlan 2001
    vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
    match tag 54321
route-map RETAIN-NEXT-HOP permit 10
    set ip next-hop unchanged

vrf context L3VNI4000999
    vni 4000999
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn

vrf context vrf_1
    vni 4000501
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn

vrf context vrf_2
    vni 4000502
    rd auto
    address-family ipv4 unicast
        route-target both auto
        route-target both auto evpn
```

```
interface Vlan100
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.100.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan200
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.200.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan301
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.11.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan302
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.12.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface nve1
    no shutdown
    host-reachability protocol bgp
    source-interface loopback1
    multisite border-gateway interface loopback100
    member vni 4000100
        suppress-arp
        multisite ingress-replication
```

```
    mcast-group 231.0.0.1
      member vni 4000200
        suppress-arp
        multisite ingress-replication
      mcast-group 231.0.0.2
      member vni 4000502 associate-vrf

interface Ethernet1/1
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.16.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown
  evpn multisite fabric-tracking

interface Ethernet1/3
  mtu 9216
  ip address 10.150.151.1/24 tag 54321
  ip router ospf 100 area 0.0.0.0
  no shutdown
  evpn multisite dci-tracking

interface loopback0
  ip address 10.31.1.2/32 tag 54321
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.134.134.134/32 tag 54321
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback100
  description "Multi-site VIP"
  ip address 10.100.100.1/32 tag 54321
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 100
  router-id 10.31.1.2
router bgp 100
  router-id 10.31.1.2
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
  address-family ipv4 mvpn
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
  address-family ipv4 mvpn
    send-community
    send-community extended
    rewrite-rt-asn
  address-family l2vpn evpn
    send-community
```

```

    send-community extended
    rewrite-evpn-rt-asn
neighbor 10.102.0.2
    remote-as 100
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
        send-community
        send-community extended
    address-family l2vpn evpn
        send-community
        send-community extended
neighbor 10.150.151.2
    remote-as 300
    address-family ipv4 unicast
evpn
    vni 4000100 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000200 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000301 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000302 12
        rd auto
        route-target import auto
        route-target export auto
    vni 4000303 12
        rd auto
        route-target import auto
        route-target export auto
S1_B2#

```

## Servidor del router

```

Router_Server#
nv overlay evpn
feature ospf
feature bgp
feature pim
feature interface-vlan

vlan 1

route-map REDIST-TO-SITE-EXT-DCI permit 10
    match tag 54321
route-map RETAIN-NEXT-HOP permit 10
    set ip next-hop unchanged

interface Ethernet2/1
    no switchport

```

```
ip address 10.150.150.2/24
no shutdown

interface Ethernet2/2
  no switchport
  ip address 10.150.151.2/24
  no shutdown

interface Ethernet2/4
  no switchport
  ip address 10.150.152.2/24
  no shutdown

interface Ethernet2/5
  no switchport
  mtu 9216
  ip address 10.150.153.2/24
  no shutdown

interface loopback0
  ip address 10.32.1.1/32 tag 54321

router bgp 300
  router-id 10.32.1.1
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
    maximum-paths 2
    retain route-target all
  address-family l2vpn evpn
    retain route-target all
  neighbor 10.31.1.1
    remote-as 100
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-evpn-rt-asn
  neighbor 10.31.1.2
    remote-as 100
    update-source loopback0
    ebgp-multipath 5
    address-family ipv4 unicast
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      route-map RETAIN-NEXT-HOP out
      rewrite-evpn-rt-asn
  neighbor 10.31.1.3
    remote-as 200
    update-source loopback0
    ebgp-multipath 5
```

```

address-family ipv4 unicast
  send-community
  send-community extended
  route-map RETAIN-NEXT-HOP out
  rewrite-rt-asn
address-family l2vpn evpn
  send-community
  send-community extended
  route-map RETAIN-NEXT-HOP out
  rewrite-evpn-rt-asn
neighbor 10.31.1.4
  remote-as 200
  update-source loopback0
  ebgp-multipath 5
  address-family ipv4 unicast
  address-family ipv4 mvpn
    send-community
    send-community extended
    route-map RETAIN-NEXT-HOP out
    rewrite-rt-asn
  address-family l2vpn evpn
    send-community
    send-community extended
    route-map RETAIN-NEXT-HOP out
    rewrite-evpn-rt-asn
neighbor 10.150.150.1
  remote-as 100
  address-family ipv4 unicast
neighbor 10.150.151.1
  remote-as 100
  address-family ipv4 unicast
neighbor 10.150.152.1
  remote-as 200
  address-family ipv4 unicast
neighbor 10.150.153.1
  remote-as 200
  address-family ipv4 unicast
Router_Server#

```

## Configuración de Site 2 Border Gateway-1

```

cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature nv overlay
evpn multisite border-gateway 200

fabric forwarding anycast-gateway-mac 0000.2222.4444

ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

```

```
vlan 1,100,200,300-350,2000-2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2000
  vn-segment 2000
vlan 2001
  vn-segment 4000502

route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
```

```
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface nve1
no shutdown
host-reachability protocol bgp
source-interface loopback1
multisite border-gateway interface loopback100
member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
mtu 9216
port-type fabric
medium p2p
ip address 192.168.17.12/24
ip ospf network point-to-point
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
no shutdown
evpn multisite fabric-tracking
```

```

interface Ethernet1/3
  mtu 9216
  ip address 10.150.152.1/24 tag 54321
  ip router ospf 200 area 0.0.0.0
  no shutdown
  evpn multisite dci-tracking

interface loopback0
  ip address 10.31.1.3/32 tag 54321
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.135.135.135/32 tag 54321
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode

interface loopback100
  description "Multi-site VIP"
  ip address 10.100.100.2/32 tag 54321
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 200
router bgp 200
  router-id 10.31.1.3
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
      send-community
      send-community extended
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      rewrite-evpn-rt-asn
  neighbor 10.103.0.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.150.152.2
    remote-as 300
    address-family ipv4 unicast
evpn
  vni 4000100 12
  rd auto
  route-target import auto
  route-target export auto
  vni 4000200 12

```

```

rd auto
route-target import auto
route-target export auto
vni 4000301 12
rd auto
route-target import auto
route-target export auto
vni 4000302 12
rd auto
route-target import auto
route-target export auto
vni 4000303 12
rd auto
route-target import auto
route-target export auto

```

## Configuración de Site 2 Border Gateway-2

```

S2-BG2#
cfs ipv4 distribute
feature ngmvpn
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature lldp
feature bfd
feature nv overlay
evpn multisite border-gateway 200
delay-restore time 300

fabric forwarding anycast-gateway-mac 0000.2222.4444
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,301-303,350,2000-2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2000
  vn-segment 2000
vlan 2001
  vn-segment 4000502

```

```
route-map REDIST-TO-SITE-EXT-DCI permit 10
  match tag 54321
route-map RETAIN-NEXT-HOP permit 10
  set ip next-hop unchanged

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn
```

```
interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
```

```
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface nve1
no shutdown
host-reachability protocol bgp
source-interface loopback1
multisite border-gateway interface loopback100
member vni 4000100
    suppress-arp
    multisite ingress-replication
    mcast-group 231.0.0.1
member vni 4000200
    suppress-arp
    multisite ingress-replication
    mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
mtu 9216
port-type fabric
medium p2p
ip address 192.168.18.12/24
ip ospf network point-to-point
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
no shutdown
evpn multisite fabric-tracking

interface Ethernet1/3
mtu 9216
ip address 10.150.153.1/24 tag 54321
ip router ospf 200 area 0.0.0.0
no shutdown
evpn multisite dci-tracking

interface loopback0
ip address 10.31.1.4/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode

interface loopback1
```

```
ip address 10.136.136.136/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode

interface loopback100
description "Multi-site VIP"
ip address 10.100.100.2/32 tag 54321
ip router ospf 200 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 200
router bgp 200
  router-id 10.31.1.4
  log-neighbor-changes
  address-family ipv4 unicast
    redistribute direct route-map REDIST-T0-SITE-EXT-DCI
  address-family l2vpn evpn
  neighbor 10.32.1.1
    remote-as 300
    update-source loopback0
    ebgp-multipath 5
    peer-type fabric-external
      send-community
      send-community extended
      rewrite-rt-asn
    address-family l2vpn evpn
      send-community
      send-community extended
      rewrite-evpn-rt-asn
  neighbor 10.103.0.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.150.153.2
    remote-as 300
    address-family ipv4 unicast

evpn
vni 4000100 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000200 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000301 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000302 12
  rd auto
  route-target import auto
  route-target export auto
vni 4000303 12
  rd auto
```

```
route-target import auto
route-target export auto
S2-BG2#
```

## Configuración de Spine-1 del Sitio 2

```
S2-Spine1#
feature nxapi
cfs ipv4 distribute
cfs eth distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature ngoam

ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

interface Ethernet1/1
  mtu 9216
  medium p2p
  ip address 192.168.0.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/2
  mtu 9216
  medium p2p
  ip address 192.168.1.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/3
  mtu 9216
  medium p2p
  ip address 192.168.2.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/4
  mtu 9216
  medium p2p
  ip address 192.168.3.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
```

```
ip pim sparse-mode
no shutdown

interface Ethernet1/5
  mtu 9216
  medium p2p
  ip address 192.168.17.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface Ethernet1/6
  mtu 9216
  medium p2p
  ip address 192.168.18.11/24
  ip ospf network point-to-point
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  description "anycast RP address"
  ip address 10.103.0.3/32
  ip router ospf 200 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 200
  router-id 10.202.0.3
router bgp 200
  router-id 10.103.0.3
  log-neighbor-changes
  address-family ipv4 unicast
  address-family ipv6 unicast
  address-family ipv4 mvpn
  address-family l2vpn evpn
  neighbor 10.31.1.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.31.1.4
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.103.0.5
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
```

```

send-community
send-community extended
route-reflector-client
address-family l2vpn evpn
send-community
send-community extended
route-reflector-client
neighbor 10.103.0.8
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
send-community
send-community extended
route-reflector-client
address-family l2vpn evpn
send-community
send-community extended
route-reflector-client
neighbor 10.103.0.9
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
route-reflector-client
address-family l2vpn evpn
send-community
send-community extended
route-reflector-client
neighbor 10.103.0.10
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
route-reflector-client
address-family l2vpn evpn
send-community
send-community extended
route-reflector-client
S2-Spine1#

```

## Configuración de la hoja 1 del sitio 2

```

feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan

```

```
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

route-map DIRECT permit 10
  match tag 12345
route-map DIRECT deny 90
vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.63
  virtual peer-link destination 10.103.1.9 source 10.103.1.8 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize
```

```
interface Vlan100
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.100.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan200
    no shutdown
    mtu 9216
    vrf member vrf_2
    no ip redirects
    ip address 192.168.200.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan301
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.11.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan302
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.12.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface port-channel10
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-500
    spanning-tree port type network
    vpc peer-link

interface port-channel100
```

```
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
suppress-arp
mcast-group 231.0.0.1
member vni 4000200
suppress-arp
mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/2
mtu 9216
port-type fabric
medium p2p
ip address 192.168.0.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface loopback0
ip address 10.103.0.5/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.8/32
ip address 10.103.201.201/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.5
router bgp 200
router-id 10.103.0.5
log-neighbor-changes
address-family ipv4 mvpn
address-family l2vpn evpn
advertise-pip
neighbor 10.103.0.2
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
```

```

    send-community
    send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
neighbor 10.103.0.3
  remote-as 200
  update-source loopback0
  address-family ipv4 unicast
  address-family ipv6 unicast
    send-community
    send-community extended
  address-family l2vpn evpn
    send-community
    send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

## Configuración de hoja 2 del sitio 2

```

S2-Leaf2#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

```

```

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.62
  virtual peer-link destination 10.103.1.8 source 10.103.1.9 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216

```

```
vrf member vrf_2
no ip redirects
ip address 192.168.200.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan301
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.12.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan303
no shutdown
mtu 9216
vrf member vrf_1
no ip redirects
ip address 172.16.13.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan2001
no shutdown
mtu 9000
vrf member vrf_2
no ip redirects
ip forward
ipv6 address use-link-local-only
no ipv6 redirects

interface port-channel10
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-500
spanning-tree port type network
vpc peer-link

interface port-channel100
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
vpc 100

interface nve1
no shutdown
host-reachability protocol bgp
advertise virtual-rmac
source-interface loopback1
member vni 4000100
```

```
suppress-arp
  mcast-group 231.0.0.1
member vni 4000200
  suppress-arp
  mcast-group 231.0.0.2
member vni 4000502 associate-vrf

interface Ethernet1/1
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-305
  mtu 9216
  channel-group 100
  no shutdown

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
  ip address 192.168.1.12/24
  ip ospf network point-to-point
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  no shutdown

interface loopback0
  ip address 10.103.0.8/32
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode

interface loopback1
  ip address 10.103.1.9/32
  ip address 10.103.201.201/32 secondary
  ip router ospf 100 area 0.0.0.0
  ip pim sparse-mode
  icam monitor scale

router ospf 100
  router-id 10.102.0.8
router bgp 200
  router-id 10.103.0.8
  log-neighbor-changes
  address-family l2vpn evpn
    advertise-pip
  neighbor 10.103.0.2
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
      send-community
      send-community extended
    address-family l2vpn evpn
      send-community
      send-community extended
  neighbor 10.103.0.3
    remote-as 200
    update-source loopback0
    address-family ipv4 unicast
    address-family ipv6 unicast
    address-family ipv4 mvpn
      send-community
      send-community extended
```

```

address-family l2vpn evpn
  send-community
    send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto
S2-Leaf2#

```

## Configuración de la hoja 3 del sitio 2

```

S2-leaf3#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303

```

```

vlan 350
  name L3-VNI
  vn-segment 4000999
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.65
  virtual peer-link destination 10.103.1.6 source 10.103.1.10 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize

interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects

```

```
ip address 172.16.11.254/24
no ipv6 redirects
fabric forwarding mode anycast-gateway

interface Vlan302
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.12.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan303
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.13.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway

interface Vlan2001
  no shutdown
  mtu 9000
  vrf member vrf_2
  no ip redirects
  ip forward
  ipv6 address use-link-local-only
  no ipv6 redirects

interface port-channel10
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-500
  spanning-tree port type network
  vpc peer-link

interface port-channel100
  switchport
  switchport mode trunk
  switchport trunk allowed vlan 100,200,300-305
  mtu 9216
  vpc 100

interface nve1
  no shutdown
  host-reachability protocol bgp
  advertise virtual-rmac
  source-interface loopback1
  member vni 4000100
    suppress-arp
    mcast-group 231.0.0.1
  member vni 4000200
    suppress-arp
    mcast-group 231.0.0.2
  member vni 4000502 associate-vrf

interface Ethernet1/2
  mtu 9216
  port-type fabric
  medium p2p
```

```
ip address 192.168.2.12/24
ip ospf network point-to-point
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
no shutdown

interface Ethernet1/23
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface loopback0
ip address 10.103.0.9/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.10/32
ip address 10.103.202.202/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.9
router bgp 200
router-id 10.103.0.9
log-neighbor-changes
address-family ipv4 mvpn
address-family l2vpn evpn
advertise-pip
neighbor 10.103.0.2
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
neighbor 10.103.0.3
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
send-community
send-community extended
address-family l2vpn evpn
send-community
```

```

    send-community extended
evpn
  vni 4000100 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
  vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto

```

## Configuración de la hoja 4 del sitio 2

```

S2-Leaf4#
feature nxapi
cfs ipv4 distribute
nv overlay evpn
feature ospf
feature bgp
feature pim
feature fabric forwarding
feature interface-vlan
feature vn-segment-vlan-based
feature lacp
feature vpc
feature nv overlay

fabric forwarding anycast-gateway-mac 0000.1111.2222
ip pim rp-address 10.103.0.3 group-list 224.0.0.0/4
ip pim ssm range 232.0.0.0/8

vlan 1,100,200,300-350,2001
vlan 100
  vn-segment 4000100
vlan 200
  vn-segment 4000200
vlan 301
  vn-segment 4000301
vlan 302
  vn-segment 4000302
vlan 303
  vn-segment 4000303
vlan 350
  name L3-VNI
  vn-segment 4000999

```

```
vlan 2001
  vn-segment 4000502

vrf context L3VNI4000999
  vni 4000999
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_1
  vni 4000501
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vrf context vrf_2
  vni 4000502
  rd auto
  address-family ipv4 unicast
    route-target both auto
    route-target both auto evpn

vpc domain 100
  peer-switch
  peer-keepalive destination 10.197.214.64
  virtual peer-link destination 10.103.1.10 source 10.103.1.6 dscp 56
  delay restore 150
  peer-gateway
  ip arp synchronize
```

```
interface Vlan100
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.100.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan200
  no shutdown
  mtu 9216
  vrf member vrf_2
  no ip redirects
  ip address 192.168.200.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan301
  no shutdown
  mtu 9216
  vrf member vrf_1
  no ip redirects
  ip address 172.16.11.254/24
  no ipv6 redirects
  fabric forwarding mode anycast-gateway
```

```
interface Vlan302
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.12.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan303
    no shutdown
    mtu 9216
    vrf member vrf_1
    no ip redirects
    ip address 172.16.13.254/24
    no ipv6 redirects
    fabric forwarding mode anycast-gateway

interface Vlan2001
    no shutdown
    mtu 9000
    vrf member vrf_2
    no ip redirects
    ip forward
    ipv6 address use-link-local-only
    no ipv6 redirects

interface port-channel10
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-500
    spanning-tree port type network
    vpc peer-link

interface port-channel100
    switchport
    switchport mode trunk
    switchport trunk allowed vlan 100,200,300-305
    mtu 9216
    vpc 100

interface nve1
    no shutdown
    host-reachability protocol bgp
    advertise virtual-rmac
    source-interface loopback1
    member vni 4000100
        suppress-arp
        mcast-group 231.0.0.1
    member vni 4000200
        suppress-arp
        mcast-group 231.0.0.2
    member vni 4000502 associate-vrf

interface Ethernet1/2
    mtu 9216
    port-type fabric
    medium p2p
    ip address 192.168.3.12/24
    ip ospf network point-to-point
    ip router ospf 100 area 0.0.0.0
```

```
ip pim sparse-mode
no shutdown

interface Ethernet1/23
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface Ethernet1/24
switchport
switchport mode trunk
switchport trunk allowed vlan 100,200,300-305
mtu 9216
channel-group 100
no shutdown

interface loopback0
ip address 10.103.0.10/32
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode

interface loopback1
ip address 10.103.1.6/32
ip address 10.103.202.202/32 secondary
ip router ospf 100 area 0.0.0.0
ip pim sparse-mode
icam monitor scale

router ospf 100
router-id 10.102.0.10
router bgp 200
router-id 10.102.0.10
log-neighbor-changes
address-family l2vpn evpn
advertise-pip
neighbor 10.103.0.2
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
address-family ipv4 mvpn
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
neighbor 10.103.0.3
remote-as 200
update-source loopback0
address-family ipv4 unicast
address-family ipv6 unicast
send-community
send-community extended
address-family l2vpn evpn
send-community
send-community extended
evpn
vni 4000100 12
rd auto
```

```

    route-target import auto
    route-target export auto
vni 4000200 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000301 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000302 12
    rd auto
    route-target import auto
    route-target export auto
vni 4000303 12
    rd auto
    route-target import auto
    route-target export auto
S2-Leaf4#

```

## Verificación

Use esta sección para confirmar que su configuración funciona correctamente.

[Cisco CLI Analyzer](#) (sólo para clientes registrados) admite determinados `show` comandos. Utilice Cisco CLI Analyzer para ver un análisis de `show` resultado del comando.

```

<#root>

Host2#
show ip int brief

IP Interface Status for VRF "default"(1)
Interface          IP Address      Interface Status
Vlan100            192.168.100.102 protocol-up/link-up/admin-up
Vlan200            192.168.200.102 protocol-up/link-up/admin-up
Lo100              10.2.3.4        protocol-up/link-up/admin-up
Host2#
Host2#

```

```

<#root>

Host2#
ping 192.168.200.103

PING 192.168.200.103 (192.168.200.103): 56 data bytes
64 bytes from 192.168.200.103: icmp_seq=0 ttl=254 time=1.21 ms
64 bytes from 192.168.200.103: icmp_seq=1 ttl=254 time=0.627 ms
64 bytes from 192.168.200.103: icmp_seq=2 ttl=254 time=0.74 ms
64 bytes from 192.168.200.103: icmp_seq=3 ttl=254 time=0.737 ms
64 bytes from 192.168.200.103: icmp_seq=4 ttl=254 time=0.542 ms

```

```
--- 192.168.200.103 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.542/0.771/1.21 ms
```

```
Host2#
```

```
Host2#
```

```
Host2#
```

```
ping 192.168.100.103
```

```
PING 192.168.100.103 (192.168.100.103): 56 data bytes
64 bytes from 192.168.100.103: icmp_seq=0 ttl=254 time=1.195 ms
64 bytes from 192.168.100.103: icmp_seq=1 ttl=254 time=0.613 ms
64 bytes from 192.168.100.103: icmp_seq=2 ttl=254 time=0.575 ms
64 bytes from 192.168.100.103: icmp_seq=3 ttl=254 time=0.522 ms
64 bytes from 192.168.100.103: icmp_seq=4 ttl=254 time=0.534 ms
--- 192.168.100.103 ping statistics ---
```

```
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.522/0.687/1.195 ms
```

```
Host2#
```

```
Host2#
```

```
Host2#
```

```
ping 192.168.100.100
```

```
PING 192.168.100.100 (192.168.100.100): 56 data bytes
64 bytes from 192.168.100.100: icmp_seq=0 ttl=254 time=1.029 ms
64 bytes from 192.168.100.100: icmp_seq=1 ttl=254 time=0.561 ms
64 bytes from 192.168.100.100: icmp_seq=2 ttl=254 time=0.579 ms
64 bytes from 192.168.100.100: icmp_seq=3 ttl=254 time=0.511 ms
64 bytes from 192.168.100.100: icmp_seq=4 ttl=254 time=0.496 ms
--- 192.168.100.100 ping statistics ---
```

```
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.496/0.635/1.029 ms
```

```
Host2#
```

```
Host2#
```

```
Host2#
```

```
ping 192.168.200.100
```

```
PING 192.168.200.100 (192.168.200.100): 56 data bytes
64 bytes from 192.168.200.100: icmp_seq=0 ttl=254 time=1.263 ms
64 bytes from 192.168.200.100: icmp_seq=1 ttl=254 time=0.816 ms
64 bytes from 192.168.200.100: icmp_seq=2 ttl=254 time=0.735 ms
64 bytes from 192.168.200.100: icmp_seq=3 ttl=254 time=0.659 ms
64 bytes from 192.168.200.100: icmp_seq=4 ttl=254 time=0.634 ms
--- 192.168.200.100 ping statistics ---
```

```
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.634/0.821/1.263 ms
```

```
Host2#
```

```
<#root>
```

```
HOST_3(config)#  
HOST_3(config)#
```

```
ping 192.168.100.100
```

```
PING 192.168.100.100 (192.168.100.100): 56 data bytes
```

```
64 bytes from 192.168.100.100: icmp_seq=0 ttl=254 time=1.319 ms
64 bytes from 192.168.100.100: icmp_seq=1 ttl=254 time=0.77 ms
64 bytes from 192.168.100.100: icmp_seq=2 ttl=254 time=0.505 ms
64 bytes from 192.168.100.100: icmp_seq=3 ttl=254 time=0.542 ms
64 bytes from 192.168.100.100: icmp_seq=4 ttl=254 time=0.486 ms
--- 192.168.100.100 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.486/0.724/1.319 ms
HOST_3(config)#

HOST_3(config)# ping 192.168.100.102

PING 192.168.100.102 (192.168.100.102): 56 data bytes
64 bytes from 192.168.100.102: icmp_seq=0 ttl=254 time=1.304 ms
64 bytes from 192.168.100.102: icmp_seq=1 ttl=254 time=0.853 ms
64 bytes from 192.168.100.102: icmp_seq=2 ttl=254 time=0.845 ms
64 bytes from 192.168.100.102: icmp_seq=3 ttl=254 time=0.564 ms
64 bytes from 192.168.100.102: icmp_seq=4 ttl=254 time=0.55 ms
--- 192.168.100.102 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.55/0.823/1.304 ms
HOST_3(config)#
HOST_3(config)#
HOST_3(config)#

ping 192.168.200.102

PING 192.168.200.102 (192.168.200.102): 56 data bytes
64 bytes from 192.168.200.102: icmp_seq=0 ttl=254 time=0.997 ms
64 bytes from 192.168.200.102: icmp_seq=1 ttl=254 time=0.766 ms
64 bytes from 192.168.200.102: icmp_seq=2 ttl=254 time=0.84 ms
64 bytes from 192.168.200.102: icmp_seq=3 ttl=254 time=0.734 ms
64 bytes from 192.168.200.102: icmp_seq=4 ttl=254 time=0.592 ms
--- 192.168.200.102 ping statistics ---
5 packets transmitted, 5 packets received, 0.00% packet loss
round-trip min/avg/max = 0.592/0.785/0.997 ms
HOST_3(config)#

HOST_3(config)#
ping 192.168.200.100

PING 192.168.200.100 (192.168.200.100): 56 data bytes
36 bytes from 192.168.200.103: Destination Host Unreachable
Request 0 timed out
64 bytes from 192.168.200.100: icmp_seq=1 ttl=254 time=1.376 ms
64 bytes from 192.168.200.100: icmp_seq=2 ttl=254 time=0.806 ms
64 bytes from 192.168.200.100: icmp_seq=3 ttl=254 time=0.77 ms
64 bytes from 192.168.200.100: icmp_seq=4 ttl=254 time=0.793 ms
--- 192.168.200.100 ping statistics ---
5 packets transmitted, 4 packets received, 20.00% packet loss
round-trip min/avg/max = 0.77/0.936/1.376 ms
HOST_3(config)#

```

## Troubleshoot

En esta sección encontrará información que puede utilizar para solucionar problemas de configuración.

[Cisco CLI Analyzer](#) (sólo para clientes registrados) admite determinados `show` comandos. Utilice Cisco CLI Analyzer para ver un análisis de `show` resultado del comando.

<#root>

Host2#

`show ip arp`

Flags: \* - Adjacencies learnt on non-active FHRP router  
+ - Adjacencies synced via CFSoE  
# - Adjacencies Throttled for Glean  
CP - Added via L2RIB, Control plane Adjacencies  
PS - Added via L2RIB, Peer Sync  
RO - Re-Originated Peer Sync Entry  
D - Static Adjacencies attached to down interface

IP ARP Table for context default

Total number of entries: 8

Address	Age	MAC Address	Interface	Flags
192.168.100.100	00:06:52	6c8b.d3ff.00a7	Vlan100	
192.168.100.103	00:07:54	6c8b.d3fe.ecb5	Vlan100	
192.168.100.104	00:07:01	6c8b.d3fe.df3b	Vlan100	
192.168.100.254	00:08:01	0000.1111.2222	Vlan100	
192.168.200.100	00:14:46	6c8b.d3ff.00a7	Vlan200	
192.168.200.103	00:07:07	6c8b.d3fe.ecb5	Vlan200	
192.168.200.104	00:07:31	6c8b.d3fe.df3b	Vlan200	
192.168.200.254	00:07:07	0000.1111.2222	Vlan200	

Host2#

Host2#

`show mac address-table`

Legend:

\* - primary entry, G - Gateway MAC, (R) - Routed MAC, O - Overlay MAC  
age - seconds since last seen,+ - primary entry using vPC Peer-Link,  
(T) - True, (F) - False, C - ControlPlane MAC, ~ - vsan

VLAN	MAC Address	Type	age	Secure	NTFY	Ports
*	0000.1111.2222	dynamic	0	F	F	Po2
*	6c8b.d3fe.df3b	dynamic	0	F	F	Po2
*	6c8b.d3fe.ecb5	dynamic	0	F	F	Po2
*	6c8b.d3ff.00a7	dynamic	0	F	F	Po2
*	0000.1111.2222	dynamic	0	F	F	Po2
*	6c8b.d3fe.df3b	dynamic	0	F	F	Po2
*	6c8b.d3fe.ecb5	dynamic	0	F	F	Po2
*	6c8b.d3ff.00a7	dynamic	0	F	F	Po2
G	-	6c8b.d3fe.ff09	static	-	F	sup-eth1(R)
G	100	6c8b.d3fe.ff09	static	-	F	sup-eth1(R)
G	200	6c8b.d3fe.ff09	static	-	F	sup-eth1(R)

Host2#

Host2#

<#root>

```

HOST_3(config)#  

show ip arp  
  

Flags: * - Adjacencies learnt on non-active FHRP router  

      + - Adjacencies synced via CFSoE  

      # - Adjacencies Throttled for Glean  

      CP - Added via L2RIB, Control plane Adjacencies  

      PS - Added via L2RIB, Peer Sync  

      RO - Re-Originated Peer Sync Entry  

      D - Static Adjacencies attached to down interface  

IP ARP Table for context default  

Total number of entries: 8  

Address          Age      MAC Address      Interface      Flags  

192.168.200.100 00:00:07 6c8b.d3ff.00a7  Vlan200  

192.168.200.102 00:11:41 6c8b.d3fe.fff09  Vlan200  

192.168.200.104 00:18:38 6c8b.d3fe.df3b   Vlan200  

192.168.200.254 00:12:19 0000.1111.2222  Vlan200  

192.168.100.100 00:07:16 6c8b.d3ff.00a7  Vlan100  

192.168.100.102 00:11:51 6c8b.d3fe.fff09  Vlan100  

192.168.100.104 00:15:06 6c8b.d3fe.df3b   Vlan100  

192.168.100.254 00:11:37 0000.1111.2222  Vlan100
HOST_3(config)#

```

```

<#root>  

S1-Leaf1#  

show bgp 12vpn evpn  
  

BGP routing table information for VRF default, address family L2VPN EVPN  

BGP table version is 3291, Local Router ID is 10.102.0.5  

Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best  

Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected  

Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup, 2 - best2  

Network          Next Hop          Metric      LocPrf      Weight Path  

Route Distinguisher: 100:4000100  

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdbd]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272  

          10.100.100.1          100          0 300 200 i  

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272  

          10.100.100.1          100          0 300 200 i  

Route Distinguisher: 100:4000200

```

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272			
10.100.100.1	100	0	300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272			
10.100.100.1	100	0	300 200

Route Distinguisher: 10.31.1.1:32867

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			
10.133.133.133	100	0	

Route Distinguisher: 10.31.1.1:32967

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			
10.133.133.133	100	0	i

Route Distinguisher: 10.31.1.2:32867

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216			
10.134.134.134	100	0	i

Route Distinguisher: 10.31.1.2:32967

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216			
10.134.134.134	100	0	i

Route Distinguisher: 10.102.0.5:32867 (L2VNI 4000100)

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216				
10.133.133.133	100	0	i	
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216				
10.134.134.134	100	0	i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216				
10.202.202.202	100	0	i	
*>i	10.202.202.202	100	0	i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216				
10.201.201.201	100	32768	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216				
10.202.202.202	100	0	i	
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216				
10.100.100.1	100	0	300 200 i	

```

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>1[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
    10.201.201.201                               100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.202.202.202                               100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272
    10.100.100.1                                100      0 300 200 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
    10.202.202.202                               100      0 i
*>i
    10.202.202.202                               100      0 i
*>1[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272
    10.201.201.201                               100      32768 i

```

Route Distinguisher: 10.102.0.5:32967 (L2VNI 4000200)

```

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216
    10.133.133.133                               100      0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216
    10.134.134.134                               100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i

* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216
    10.202.202.202                               100      0 i
*>i
    10.202.202.202                               100      0 i
*>1[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216
    10.201.201.201                               100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216
    10.202.202.202                               100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.3aef]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
    10.100.100.1                                100      0 300 200 i
*>1[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
    10.201.201.201                               100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.202.202.202                               100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
    10.100.100.1                                100      0 300 200 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272
    10.100.100.1                                100      0 300 200 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
    10.202.202.202                               100      0 i
*>i
    10.202.202.202                               100      0 i
*>1[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
    10.201.201.201                               100      32768 i

```

Route Distinguisher: 10.102.0.9:5

\*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224  
                   10.102.1.10                  100          0 i

\*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224  
                   10.102.1.10                  100          0 i

Route Distinguisher: 10.102.0.9:32867

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272  
                   10.202.202.202                  100          0 i

Route Distinguisher: 10.102.0.9:32967

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272  
                   10.202.202.202                  100          0 i

Route Distinguisher: 10.102.0.10:5

\*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224  
                   10.102.1.6                  100          0 i

\*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224  
                   10.102.1.6                  100          0 i

Route Distinguisher: 10.102.0.10:32867

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272  
                   10.202.202.202                  100          0 i

Route Distinguisher: 10.102.0.10:32967

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272  
                   10.202.202.202                  100          0 i

Route Distinguisher: 10.102.0.5:5 (L3VNI 4000502)

\*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216  
                   10.201.201.201                  100          32768 i

\*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216  
                   10.202.202.202                  100          0 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272  
                   10.100.100.1                  100          0 300 200 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272  
                   10.100.100.1                  100          0 300 200 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272  
                   10.100.100.1                  100          0 300 200 i

\*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272  
                   10.100.100.1                  100          0 300 200 i

```

* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
          10.202.202.202           100      0 i
*>i          10.202.202.202           100      0 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
          10.202.202.202           100      0 i
*>i          10.202.202.202           100      0 i
* i[5]:[0]:[0]:[24]:[192.168.100.0]/224
          10.102.1.6             100      0 i
*>i          10.102.1.10            100      0 i
*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224
          10.102.1.6             100      0 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224
          10.102.1.10            100      0 i
S1-Leaf1#

```

<#root>

S1-Leaf1#

**show vpc brief**

**Legend:**

(*) - local vPC is down, forwarding via vPC peer-link	
vPC domain id	: 100
Peer status	: peer adjacency formed ok
vPC keep-alive status	: peer is alive
Configuration consistency status	: success
Per-vlan consistency status	: success
Type-2 consistency status	: success
vPC role	: secondary
Number of vPCs configured	: 1
Peer Gateway	: Enabled
Dual-active excluded VLANs	: -
Graceful Consistency Check	: Enabled
Auto-recovery status	: Disabled
Delay-restore status	: Timer is off.(timeout = 150s)
Delay-restore SVI status	: Timer is off.(timeout = 10s)
Delay-restore Orphan-port status	: Timer is off.(timeout = 0s)
Operational Layer3 Peer-router	: Disabled
Virtual-peerlink mode	: Enabled

**vPC Peer-link status**

id	Port	Status	Active vlans
--	--	--	--
1	Po10	up	100,200,300-350,2001

**vPC status**

Id	Port	Status	Consistency	Reason	Active vlans
--	--	--	--	--	--
100	Po100	up	success	success	100,200

Please check "show vpc consistency-parameters vpc <vpc-num>" for the consistency reason of down vpc and for type-2 consistency reasons for any vpc.

S1-Leaf1#

```
<#root>
```

```
S1-Leaf1#  
S1-Leaf1#
```

```
show ip int brief
```

```
IP Interface Status for VRF "default"(1)
Interface          IP Address      Interface Status
Lo0                10.102.0.5    protocol-up/link-up/admin-up
Lo1                10.102.1.8    protocol-up/link-up/admin-up
Eth1/2              192.168.17.12  protocol-up/link-up/admin-up
S1-Leaf1#
```

```
<#root>
```

```
S2-Leaf1#
```

```
show bgp l2vpn evpn
```

```
BGP routing table information for VRF default, address family L2VPN EVPN
BGP table version is 4016, Local Router ID is 10.103.0.5
Status: s-suppressed, x-deleted, S-stale, d-dampened, h-history, *-valid, >-best
Path type: i-internal, e-external, c-confed, l-local, a-aggregate, r-redist, I-injected
Origin codes: i - IGP, e - EGP, ? - incomplete, | - multipath, & - backup, 2 - best2
```

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 200:4000100					
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272	10.100.100.2	100	0	300	100 i

```
Route Distinguisher: 200:4000200
```

*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0	300	100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216					

	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272	10.100.100.2	100	0 300 100 i
	10.100.100.2	100	0 300 100 i
 Route Distinguisher: 200:4000502			
*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224	10.100.100.2	100	0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224	10.100.100.2	100	0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224	10.100.100.2	100	0 300 100 i
	10.100.100.2	100	0 300 100 i
 Route Distinguisher: 10.31.1.3:32867			
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
 Route Distinguisher: 10.31.1.3:32967			
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
 Route Distinguisher: 10.31.1.4:32867			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
	10.136.136.136	100	0 i
 Route Distinguisher: 10.31.1.4:32967			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
	10.136.136.136	100	0 i
 Route Distinguisher: 10.102.0.10:5			
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
	10.103.202.202	100	0 i
 Route Distinguisher: 10.102.0.10:32867			
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272	10.103.202.202	100	0 i
	10.103.202.202	100	0 i
 Route Distinguisher: 10.102.0.10:32967			
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272	10.103.202.202	100	0 i
	10.103.202.202	100	0 i
 Route Distinguisher: 10.103.0.5:32867 (L2VNI 4000100)			
*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
	10.136.136.136	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216			

	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i	10.103.202.202	100	0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216	10.103.201.201	100	32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>l[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216	10.103.201.201	100	32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272	10.103.202.202	100	0 i
*>i	10.103.202.202	100	0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.100.103]/272	10.103.201.201	100	32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272	10.100.100.2	100	0 300 100 i

Route Distinguisher: 10.103.0.5:32967 (L2VNI 4000200)

*>i[2]:[0]:[0]:[48]:[10b3.d5c7.9fdb]:[0]:[0.0.0.0]/216	10.136.136.136	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.3785]:[0]:[0.0.0.0]/216	10.135.135.135	100	0 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.383d]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[4ce1.75f7.38c7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i	10.103.202.202	100	0 i
*>l[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[0]:[0.0.0.0]/216	10.103.201.201	100	32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76c6.a673]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216	10.103.202.202	100	0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0907]:[0]:[0.0.0.0]/216	10.100.100.2	100	0 300 100 i

```

*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
    10.103.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0adb]:[0]:[0.0.0.0]/216
    10.100.100.2                                100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.118f]:[0]:[0.0.0.0]/216
    10.100.100.2                                100      0 300 100 i
* i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
    10.103.202.202                                100      0 i
*>i
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ecb5]:[32]:[192.168.200.103]/272
    10.103.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
    10.100.100.2                                100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
    10.100.100.2                                100      0 300 100 i

```

Route Distinguisher: 10.103.0.9:5

```

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i

```

Route Distinguisher: 10.103.0.9:32867

```

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
    10.103.202.202                                100      0 i

```

Route Distinguisher: 10.103.0.9:32967

```

*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
    10.103.202.202                                100      0 i

```

Route Distinguisher: 10.103.0.5:5 (L3VNI 4000502)

```

*>i[2]:[0]:[0]:[48]:[cc7f.76d4.2ebf]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.04c3]:[0]:[0.0.0.0]/216
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[cc7f.76fa.0a3f]:[0]:[0.0.0.0]/216
    10.103.201.201                                100      32768 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.100.104]/272
    10.103.202.202                                100      0 i
*>i
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.df3b]:[32]:[192.168.200.104]/272
    10.103.202.202                                100      0 i
*>i
    10.103.202.202                                100      0 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.100.102]/272
    10.100.100.2                                100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3fe.ff09]:[32]:[192.168.200.102]/272
    10.100.100.2                                100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.100.100]/272
    10.100.100.2                                100      0 300 100 i
*>i[2]:[0]:[0]:[48]:[6c8b.d3ff.00a7]:[32]:[192.168.200.100]/272
    10.100.100.2                                100      0 300 100 i
*>i[5]:[0]:[0]:[24]:[192.168.100.0]/224
    10.100.100.2                                100      0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.1]/224
    10.100.100.2                                100      0 300 100 i
*>i[5]:[0]:[0]:[32]:[10.15.100.2]/224

```

10.100.100.2 100 0 300 100 i  
S2-Leaf1#

## Acerca de esta traducción

Cisco ha traducido este documento combinando la traducción automática y los recursos humanos a fin de ofrecer a nuestros usuarios en todo el mundo contenido en su propio idioma.

Tenga en cuenta que incluso la mejor traducción automática podría no ser tan precisa como la proporcionada por un traductor profesional.

Cisco Systems, Inc. no asume ninguna responsabilidad por la precisión de estas traducciones y recomienda remitirse siempre al documento original escrito en inglés (insertar vínculo URL).