

Schéma des informations d'identification Vault

Table des matières

```
{
  "type": "object",
  "properties": {
    "targetIp": {
      "type": "string",
      "description": "IP address or hostname of the target device(s). Supports wildcards (e.g., 5.0.*.*)",
    },
    "credentials": {
      "type": "object",
      "description": "Object containing protocol-specific credentials.",
      "properties": {
        "snmpv2c": {
          "type": "object",
          "description": "SNMPv2c credentials.",
          "properties": {
            "read": {
              "type": "string",
              "description": "SNMP Read Community"
            }
          },
          "required": ["read"]
        },
        "snmpv3": {
          "type": "object",
          "description": "SNMPv3 credentials.",
          "properties": {
            "user": {
              "type": "string",
              "description": "SNMPv3 User"
            },
            "authAlgorithm": {
              "type": "string",
              "description": "Authentication Algorithm (optional)"
            },
            "authPassword": {
              "type": "string",
              "description": "Authentication Password (required if authAlgorithm is provided)"
            },
            "privacyAlgorithm": {
              "type": "string",
              "description": "Privacy Algorithm (optional)"
            },
            "privacyPassword": {
              "type": "string",
              "description": "Privacy Password (required if privacyAlgorithm is provided)"
            },
            "engineId": {
              "type": "string",
            }
          }
        }
      }
    }
  }
}
```

```

        "description": "SNMP Engine ID (optional)"
    },
    "required": ["user"]
},
"sshv1": {
    "type": "object",
    "description": "SSHv1 credentials.",
    "properties": {
        "user": {
            "type": "string",
            "description": "Username"
        },
        "password": {
            "type": "string",
            "description": "Password (optional if enablePassword is provided)"
        },
        "enableUser": {
            "type": "string",
            "description": "Enable Username (optional)"
        },
        "enablePassword": {
            "type": "string",
            "description": "Enable Password (required if password is not provided)"
        },
        "port": {
            "type": "integer",
            "description": "Port (optional, default = 22)"
        }
    },
    "required": ["user"]
},
"sshv2": {
    "type": "object",
    "description": "SSHv2 credentials.",
    "properties": {
        "user": {
            "type": "string",
            "description": "Username"
        },
        "password": {
            "type": "string",
            "description": "Password (optional if enablePassword is provided)"
        },
        "enableUser": {
            "type": "string",
            "description": "Enable Username (optional)"
        },
        "enablePassword": {
            "type": "string",
            "description": "Enable Password (required if password is not provided)"
        },
        "port": {
            "type": "integer",
            "description": "Port (optional, default = 22)"
        }
    },
    "required": ["user"]
},

```

```

"telnet": {
  "type": "object",
  "description": "Telnet credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username"
    },
    "password": {
      "type": "string",
      "description": "Password (optional if enablePassword is provided)"
    },
    "enableUser": {
      "type": "string",
      "description": "Enable Username (optional)"
    },
    "enablePassword": {
      "type": "string",
      "description": "Enable Password (required if password is not provided)"
    },
    "port": {
      "type": "integer",
      "description": "Port (optional, default = 23)"
    }
  },
  "required": ["user"]
},
"http": {
  "type": "object",
  "description": "HTTP credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username (optional)"
    },
    "password": {
      "type": "string",
      "description": "Password (optional)"
    },
    "port": {
      "type": "integer",
      "description": "Port (optional, default = 80)"
    }
  }
},
"https": {
  "type": "object",
  "description": "HTTPS credentials.",
  "properties": {
    "user": {
      "type": "string",
      "description": "Username (optional)"
    },
    "password": {
      "type": "string",
      "description": "Password (optional)"
    },
    "port": {
      "type": "integer",

```

```
        "description": "Port (optional, default = 443)"
      }
    }
  },
  "additionalProperties": false
},
"required": ["targetIp", "credentials"],
"additionalProperties": false
}
```

À propos de cette traduction

Cisco a traduit ce document en traduction automatisée vérifiée par une personne dans le cadre d'un service mondial permettant à nos utilisateurs d'obtenir le contenu d'assistance dans leur propre langue.

Il convient cependant de noter que même la meilleure traduction automatisée ne sera pas aussi précise que celle fournie par un traducteur professionnel.