

IKEv1/IKEv2 entre le Cisco IOS et l'exemple strongSwan de configuration

Contenu

[Introduction](#)

[Conditions préalables](#)

[Conditions requises](#)

[Composants utilisés](#)

[Configurez](#)

[Diagramme du réseau](#)

[Open Source L2L IPSec VPN](#)

[IKEv1 entre le Cisco IOS et strongSwan](#)

[Configuration Cisco IOS](#)

[configuration strongSwan](#)

[IKEv2 entre le Cisco IOS et strongSwan](#)

[Configuration Cisco IOS](#)

[configuration strongSwan](#)

[Vérifiez](#)

[Dépannez](#)

[IKEv1 entre le Cisco IOS et strongSwan](#)

[Cisco IOS](#)

[Établissement de tunnel déclenché par Cisco IOS](#)

[Cisco IOS : Compteurs d'IPSec de contrôle](#)

[Cisco IOS : Vérifiez les paramètres IKEv1 et d'IPSec](#)

[strongSwan : Établissement de tunnel](#)

[strongSwan : Vérifiez l'état de la connexion d'IPSec](#)

[strongSwan : Vérifiez la stratégie IPSec](#)

[IKEv2 entre le Cisco IOS et strongSwan](#)

[Cisco IOS](#)

[Établissement de tunnel déclenché par Cisco IOS](#)

[Cisco IOS : Compteurs d'IPSec de contrôle](#)

[Cisco IOS : Vérifiez les paramètres IKEv2 et d'IPSec](#)

[strongSwan : Établissement de tunnel](#)

[strongSwan : Vérifiez l'état de la connexion d'IPSec](#)

[strongSwan : Vérifiez la stratégie IPSec](#)

[Les informations relatives](#)

Introduction

Ce document fournit un exemple de configuration pour un entre réseaux locaux (L2L) VPN entre le Cisco IOS® et strongSwan. La version 1 (IKEv1) d'échange de clés Internet (IKE) et des configurations de la version 2 d'échange de clés Internet (IKE) (IKEv2) sont présentées.

Conditions préalables

Conditions requises

Cisco vous recommande de prendre connaissance des rubriques suivantes :

- Connaissance de base au sujet des configurations de Linux
- La connaissance au sujet des configurations du VPN sur le Cisco IOS
- La connaissance au sujet de ces protocoles : IKEv1IKEv2IPSec (IPSec)

Composants utilisés

Les informations contenues dans ce document sont basées sur les versions de logiciel suivantes :

- Cisco IOS version 15.3T
- 5.0.4 strongSwan
- Kernel Linux 3.2.12

Configurez

Diagramme du réseau

La topologie est identique pour les deux exemples, qui est un tunnel L2L entre le Cisco IOS et strongSwan.

Le trafic est protégé entre 192.168.1.0/24<->192.168.2.0/24.

Open Source L2L IPSec VPN

Il y a plusieurs projets opens sources qui utilisent l'Échange de clés Internet (IKE) et les protocoles IPsecs pour construire les tunnels sécurisés L2L :

- Libérez le réseau sécurisé d'étendu (freeS/WAN) : historique, pas activement mis à jour
- ipsec-outils : le raton laveur - ne prend en charge pas IKEv2, des kernel Linux plus anciens 2.6
- Openswan : support très de base IKEv2, kernel Linux plus anciens 2.6 et API plus tôt, pas activement mis à jour
- strongSwan : supports IKEv2 et extensions EAP/mobility, nouveaux kernel Linux 3.x et plus tard cette utilisation NETKEY API (qui est le nom pour l'implémentation indigène d'IPSec au noyau 2.6 et plus tard), activement mis à jour, bien documenté

Actuellement, le meilleur choix est habituellement strongSwan. Il est semblable dans la configuration à Openswan pourtant il y a plusieurs différences mineures. Ce guide se concentre sur strongSwan et la configuration Cisco IOS.

IKEv1 entre le Cisco IOS et strongSwan

Configuration Cisco IOS

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 5
crypto isakmp key cisco address 172.16.10.2

crypto ipsec transform-set TS esp-aes esp-sha-hmac
mode tunnel

crypto map cmap 10 ipsec-isakmp
  set peer 172.16.10.2
  set transform-set TS
  match address cryptoacl

interface Ethernet0/1
  ip address 192.168.1.1 255.255.255.0

interface Ethernet0/0
  ip address 172.16.10.1 255.255.255.0
  crypto map cmap

ip access-list extended cryptoacl
  permit ip 192.168.1.0 0.0.0.255 192.168.2.0 0.0.0.255
```

configuration strongSwan

Le côté gauche est lié à strongSwan et le côté droit est distant (Cisco IOS dans cet exemple).

/etc/ipsec.conf

```
config setup
  # strictcrpolicys=yes
  # uniqueids = no

conn %default
  ikelifetime=1440m
  keylife=60m
  rekeymargin=3m
  keyingtries=1
  keyexchange=ikev1
  authby=secret

conn ciscoios
  left=172.16.10.2 #strongswan outside address
  leftsubnet=192.168.2.0/24 #network behind strongswan
  leftid=172.16.10.2 #IKEID sent by strongswan
  leftfirewall=yes
  right=172.16.10.1 #IOS outside address
  rightsubnet=192.168.1.0/24 #network behind IOS
```

```
rightid=172.16.10.1 #IKEID sent by IOS
auto=add
ike=aes128-md5-modp1536 #P1: modp1536 = DH group 5
esp=aes128-sha1 #P2
```

Par défaut, le Cisco IOS utilise l'adresse comme ID d'IKE - qui est pourquoi des adresses ont été utilisées en tant que le 'rightid » et « leftid ». strongSwan, comme le Cisco IOS, chiffrement de la deuxième génération de supports (suite B) - ainsi il est possible d'utiliser 4096 clés de Protocole DH (Diffie-Hellman) avec AES256 et SHA512.

Pour le paramètre automatique, « ajoutez » l'argument a été utilisé. Qu'apporte le tunnel après qu'il obtienne le trafic intéressant. Afin de le commencer immédiatement, l'argument de « début » a pu être utilisé.

/etc/ipsec.secrets

```
172.16.10.2 172.16.10.1 : PSK cisco
```

Pour les deux clés IKEv1 doit être les mêmes, dans cet exemple « Cisco ».

IKEv2 entre le Cisco IOS et strongSwan

Configuration Cisco IOS

```
crypto ikev2 proposal ikev2proposal
  encryption aes-cbc-128
  integrity sha1
  group 5

crypto ikev2 policy ikev2policy
  match fvrfl any
  proposal ikev2proposal

crypto ikev2 keyring keys
  peer strongswan
  address 172.16.10.2
  pre-shared-key local cisco
  pre-shared-key remote cisco

crypto ikev2 profile ikev2profile
  match identity remote address 172.16.10.2 255.255.255.255
  authentication remote pre-share
  authentication local pre-share
  keyring local keys

crypto ipsec transform-set TS esp-aes esp-sha-hmac
  mode tunnel

crypto map cmap 10 ipsec-isakmp
  set peer 172.16.10.2
  set transform-set TS
  set ikev2-profile ikev2profile
  match address cryptoacl

interface Ethernet0/1
  ip address 192.168.1.1 255.255.255.0

interface Ethernet0/0
```

```
ip address 172.16.10.1 255.255.255.0
crypto map cmap
```

```
ip access-list extended cryptoacl
permit ip 192.168.1.0 0.0.0.255 192.168.2.0 0.0.0.255
```

configuration strongSwan

Il y a seulement deux modifications par rapport à IKEv1 : keyexchange et probablement clés.

/etc/ipsec.conf

```
config setup
    # strictcrlpolicy=yes
    # uniqueids = no

conn %default
    ikelifetime=1440m
    keylife=60m
    rekeymargin=3m
    keyingtries=1
    keyexchange=ikev1
    authby=secret

conn ciscoios
    left=172.16.10.2
    leftsubnet=192.168.2.0/24
    leftid=172.16.10.2
    leftfirewall=yes
    right=172.16.10.1
    rightsubnet=192.168.1.0/24
    rightid=172.16.10.1
    auto=add
    ike=aes128-sha1-modp1536
    esp=aes128-sha1
    keyexchange=ikev2
```

/etc/ipsec.secrets

```
config setup
    # strictcrlpolicy=yes
    # uniqueids = no

conn %default
    ikelifetime=1440m
    keylife=60m
    rekeymargin=3m
    keyingtries=1
    keyexchange=ikev1
    authby=secret

conn ciscoios
    left=172.16.10.2
    leftsubnet=192.168.2.0/24
    leftid=172.16.10.2
    leftfirewall=yes
    right=172.16.10.1
    rightsubnet=192.168.1.0/24
    rightid=172.16.10.1
    auto=add
    ike=aes128-sha1-modp1536
    esp=aes128-sha1
```

keyexchange=ikev2

Dans IKEv2, les clés pour chaque site peuvent être différentes.

Vérifiez

Voyez la section de dépannage pour les procédures de vérification.

Dépannez

Cette section fournit des informations que vous pouvez utiliser pour dépanner votre configuration.

IKEv1 entre le Cisco IOS et strongSwan

Cisco IOS

```
R1#ping 192.168.2.1 source e0/1 repeat 1
```

Établissement de tunnel déclenché par Cisco IOS

```
*May 24 18:02:48.464: IPSEC(sa_request): ,
(key eng. msg.) OUTBOUND local= 172.16.10.1:500, remote= 172.16.10.2:500,
  local_proxy= 192.168.1.0/255.255.255.0/256/0,
  remote_proxy= 192.168.2.0/255.255.255.0/256/0,
  protocol= ESP, transform= esp-aes esp-sha-hmac (Tunnel),
  lifedur= 3600s and 4608000kb,
  spi= 0x0(0), conn_id= 0, keysize= 128, flags= 0x0
*May 24 18:02:48.465: ISAKMP:(0): SA request profile is (NULL)
*May 24 18:02:48.465: ISAKMP: Created a peer struct for 172.16.10.2, peer port 500
*May 24 18:02:48.465: ISAKMP: New peer created peer = 0xF334E7E0 peer_handle =
0x80000006
*May 24 18:02:48.465: ISAKMP: Locking peer struct 0xF334E7E0, refcount 1 for
isakmp_initiator
*May 24 18:02:48.465: ISAKMP: local port 500, remote port 500
*May 24 18:02:48.465: ISAKMP: set new node 0 to QM_IDLE
*May 24 18:02:48.465: ISAKMP: Find a dup sa in the avl tree during calling
isadb_insert sa = F49C9890
*May 24 18:02:48.465: ISAKMP:(0):Can not start Aggressive mode, trying Main mode.
*May 24 18:02:48.465: ISAKMP:(0):found peer pre-shared key matching 172.16.10.2
*May 24 18:02:48.465: ISAKMP:(0): constructed NAT-T vendor-rfc3947 ID
*May 24 18:02:48.465: ISAKMP:(0): constructed NAT-T vendor-07 ID
*May 24 18:02:48.465: ISAKMP:(0): constructed NAT-T vendor-03 ID
*May 24 18:02:48.465: ISAKMP:(0): constructed NAT-T vendor-02 ID
*May 24 18:02:48.465: ISAKMP:(0):Input = IKE_MESG_FROM_IPSEC, IKE_SA_REQ_MM
*May 24 18:02:48.465: ISAKMP:(0):Old State = IKE_READY New State = IKE_I_MM1

*May 24 18:02:48.465: ISAKMP:(0): beginning Main Mode exchange
*May 24 18:02:48.465: ISAKMP:(0): sending packet to 172.16.10.2 my_port 500
peer_port 500 (I) MM_NO_STATE
*May 24 18:02:48.465: ISAKMP:(0):Sending an IKE IPv4 Packet.
*May 24 18:02:48.466: ISAKMP (0): received packet from 172.16.10.2 dport 500
sport 500 Global (I) MM_NO_STATE
```

*May 24 18:02:48.466: ISAKMP:(0):Input = IKE_MESG_FROM_PEER, IKE_MM_EXCH
*May 24 18:02:48.466: ISAKMP:(0):Old State = IKE_I_MM1 New State = IKE_I_MM2

*May 24 18:02:48.466: ISAKMP:(0): processing SA payload. message ID = 0
*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID seems Unity/DPD but major 215 mismatch
*May 24 18:02:48.466: ISAKMP:(0): vendor ID is XAUTH
*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID is DPD
*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID seems Unity/DPD but major 69 mismatch
*May 24 18:02:48.466: ISAKMP (0): vendor ID is NAT-T RFC 3947
*May 24 18:02:48.466: ISAKMP:(0):found peer pre-shared key matching 172.16.10.2
*May 24 18:02:48.466: ISAKMP:(0): local preshared key found
*May 24 18:02:48.466: ISAKMP : Scanning profiles for xauth ...
*May 24 18:02:48.466: ISAKMP:(0):Checking ISAKMP transform 1 against priority
10 policy
*May 24 18:02:48.466: ISAKMP: encryption AES-CBC
*May 24 18:02:48.466: ISAKMP: keylength of 128
*May 24 18:02:48.466: ISAKMP: hash SHA
*May 24 18:02:48.466: ISAKMP: default group 5
*May 24 18:02:48.466: ISAKMP: auth pre-share
*May 24 18:02:48.466: ISAKMP: life type in seconds
*May 24 18:02:48.466: ISAKMP: life duration (VPI) of 0x0 0x1 0x51 0x80
*May 24 18:02:48.466: ISAKMP:(0):atts are acceptable. Next payload is 0
*May 24 18:02:48.466: ISAKMP:(0):Acceptable atts:actual life: 0
*May 24 18:02:48.466: ISAKMP:(0):Acceptable atts:life: 0
*May 24 18:02:48.466: ISAKMP:(0):Fill atts in sa vpi_length:4
*May 24 18:02:48.466: ISAKMP:(0):Fill atts in sa life_in_seconds:86400
*May 24 18:02:48.466: ISAKMP:(0):Returning Actual lifetime: 86400
*May 24 18:02:48.466: ISAKMP:(0)::Started lifetime timer: 86400.

*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID seems Unity/DPD but major 215 mismatch
*May 24 18:02:48.466: ISAKMP:(0): vendor ID is XAUTH
*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID is DPD
*May 24 18:02:48.466: ISAKMP:(0): processing vendor id payload
*May 24 18:02:48.466: ISAKMP:(0): vendor ID seems Unity/DPD but major 69 mismatch
*May 24 18:02:48.466: ISAKMP (0): vendor ID is NAT-T RFC 3947
*May 24 18:02:48.466: ISAKMP:(0):Input = IKE_MESG_INTERNAL, IKE_PROCESS_MAIN_MODE
*May 24 18:02:48.466: ISAKMP:(0):Old State = IKE_I_MM2 New State = IKE_I_MM2

*May 24 18:02:48.466: ISAKMP:(0): sending packet to 172.16.10.2 my_port 500
peer_port 500 (I) MM_SA_SETUP
*May 24 18:02:48.466: ISAKMP:(0):Sending an IKE IPv4 Packet.
*May 24 18:02:48.466: ISAKMP:(0):Input = IKE_MESG_INTERNAL, IKE_PROCESS_COMPLETE
*May 24 18:02:48.466: ISAKMP:(0):Old State = IKE_I_MM2 New State = IKE_I_MM3

*May 24 18:02:48.474: ISAKMP (0): received packet from 172.16.10.2 dport 500 sport
500 Global (I) MM_SA_SETUP
*May 24 18:02:48.474: ISAKMP:(0):Input = IKE_MESG_FROM_PEER, IKE_MM_EXCH
*May 24 18:02:48.474: ISAKMP:(0):Old State = IKE_I_MM3 New State = IKE_I_MM4

*May 24 18:02:48.474: ISAKMP:(0): processing KE payload. message ID = 0
*May 24 18:02:48.482: ISAKMP:(0): processing NONCE payload. message ID = 0
*May 24 18:02:48.482: ISAKMP:(0):found peer pre-shared key matching 172.16.10.2
*May 24 18:02:48.482: ISAKMP:received payload type 20
*May 24 18:02:48.482: ISAKMP (1003): His hash no match - this node outside NAT
*May 24 18:02:48.482: ISAKMP:received payload type 20
*May 24 18:02:48.482: ISAKMP (1003): No NAT Found for self or peer
*May 24 18:02:48.482: ISAKMP:(1003):Input = IKE_MESG_INTERNAL, IKE_PROCESS_MAIN_MODE
*May 24 18:02:48.482: ISAKMP:(1003):Old State = IKE_I_MM4 New State = IKE_I_MM4

*May 24 18:02:48.482: ISAKMP:(1003):Send initial contact
*May 24 18:02:48.482: ISAKMP:(1003):SA is doing pre-shared key authentication using
id type ID_IPV4_ADDR
*May 24 18:02:48.482: ISAKMP (1003): ID payload
 next-payload : 8
 type : 1
 address : 172.16.10.1
 protocol : 17
 port : 500
 length : 12
*May 24 18:02:48.482: ISAKMP:(1003):Total payload length: 12
*May 24 18:02:48.482: ISAKMP:(1003): sending packet to 172.16.10.2 my_port 500
peer_port 500 (I) MM_KEY_EXCH
*May 24 18:02:48.482: ISAKMP:(1003):Sending an IKE IPv4 Packet.
*May 24 18:02:48.482: ISAKMP:(1003):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE
*May 24 18:02:48.482: ISAKMP:(1003):Old State = IKE_I_MM4 New State = IKE_I_MM5

*May 24 18:02:48.483: ISAKMP (1003): received packet from 172.16.10.2 dport 500
sport 500 Global (I) MM_KEY_EXCH
*May 24 18:02:48.483: ISAKMP:(1003): processing ID payload. message ID = 0
*May 24 18:02:48.483: ISAKMP (1003): ID payload
 next-payload : 8
 type : 1
 address : 172.16.10.2
 protocol : 0
 port : 0
 length : 12
*May 24 18:02:48.483: ISAKMP:(0):: peer matches *none* of the profiles
*May 24 18:02:48.483: ISAKMP:(1003): processing HASH payload. message ID = 0
*May 24 18:02:48.483: ISAKMP:(1003):SA authentication status:
 authenticated
*May 24 18:02:48.483: ISAKMP:(1003):**SA has been authenticated with 172.16.10.2**
*May 24 18:02:48.483: ISAKMP: Trying to insert a peer 172.16.10.1/172.16.10.2/500/,
and inserted successfully F334E7E0.
*May 24 18:02:48.483: ISAKMP:(1003):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH
*May 24 18:02:48.483: ISAKMP:(1003):Old State = IKE_I_MM5 New State = IKE_I_MM6

*May 24 18:02:48.483: ISAKMP:(1003):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE
*May 24 18:02:48.483: ISAKMP:(1003):Old State = IKE_I_MM6 New State = IKE_I_MM6

*May 24 18:02:48.487: ISAKMP:(1003):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE
*May 24 18:02:48.487: ISAKMP:(1003):Old State = IKE_I_MM6 New State = IKE_P1_COMPLETE

*May 24 18:02:48.487: ISAKMP:(1003):beginning Quick Mode exchange, M-ID of 2605730229
*May 24 18:02:48.487: ISAKMP:(1003):QM Initiator gets spi
*May 24 18:02:48.487: ISAKMP:(1003): sending packet to 172.16.10.2 my_port 500
peer_port 500 (I) QM_IDLE
*May 24 18:02:48.487: ISAKMP:(1003):Sending an IKE IPv4 Packet.
*May 24 18:02:48.488: ISAKMP:(1003):Node 2605730229, Input = IKE_MSG_INTERNAL,
IKE_INIT_QM
*May 24 18:02:48.488: ISAKMP:(1003):Old State = IKE_QM_READY New State = IKE_QM_I_QM1
*May 24 18:02:48.488: ISAKMP:(1003):Input = IKE_MSG_INTERNAL, IKE_PHASE1_COMPLETE
*May 24 18:02:48.488: ISAKMP:(1003):Old State = IKE_P1_COMPLETE New State =
IKE_P1_COMPLETE

*May 24 18:02:48.488: ISAKMP (1003): received packet from 172.16.10.2 dport 500
sport 500 Global (I) QM_IDLE
*May 24 18:02:48.488: ISAKMP:(1003): processing HASH payload. message ID = 2605730229
*May 24 18:02:48.488: ISAKMP:(1003): processing SA payload. message ID = 2605730229
*May 24 18:02:48.488: ISAKMP:(1003):Checking IPsec proposal 1
*May 24 18:02:48.488: ISAKMP: transform 1, ESP_AES
*May 24 18:02:48.488: ISAKMP: attributes in transform:
*May 24 18:02:48.488: ISAKMP: key length is 128
*May 24 18:02:48.488: ISAKMP: authenticator is HMAC-SHA


```

*May 24 18:02:48.488: ISAKMP:          encaps is 1 (Tunnel)
*May 24 18:02:48.488: ISAKMP:          SA life type in seconds
*May 24 18:02:48.488: ISAKMP:          SA life duration (basic) of 3600
*May 24 18:02:48.488: ISAKMP:          SA life type in kilobytes
*May 24 18:02:48.488: ISAKMP:          SA life duration (VPI) of  0x0 0x46 0x50 0x0
*May 24 18:02:48.488: ISAKMP:(1003):atts are acceptable.
*May 24 18:02:48.488: IPSEC(validate_proposal_request): proposal part #1
*May 24 18:02:48.488: IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) INBOUND local= 172.16.10.1:0, remote= 172.16.10.2:0,
  local_proxy= 192.168.1.0/255.255.255.0/256/0,
  remote_proxy= 192.168.2.0/255.255.255.0/256/0,
  protocol= ESP, transform= NONE (Tunnel),
  lifedur= 0s and 0kb,
  spi= 0x0(0), conn_id= 0, keysize= 128, flags= 0x0
*May 24 18:02:48.488: Crypto mapdb : proxy_match
  src addr      : 192.168.1.0
  dst addr      : 192.168.2.0
  protocol      : 0
  src port      : 0
  dst port      : 0
*May 24 18:02:48.488: ISAKMP:(1003): processing NONCE payload. message ID = 2605730229
*May 24 18:02:48.488: ISAKMP:(1003): processing ID payload. message ID = 2605730229
*May 24 18:02:48.488: ISAKMP:(1003): processing ID payload. message ID = 2605730229
*May 24 18:02:48.488: ISAKMP:(1003):Node 2605730229, Input = IKE_MESG_FROM_PEER,
IKE_QM_EXCH
*May 24 18:02:48.488: ISAKMP:(1003):Old State = IKE_QM_I_QM1 New State =
IKE_QM_IPSEC_INSTALL_AWAIT
*May 24 18:02:48.488: IPSEC(key_engine): got a queue event with 1 KMI message(s)
*May 24 18:02:48.488: Crypto mapdb : proxy_match
  src addr      : 192.168.1.0
  dst addr      : 192.168.2.0
  protocol      : 256
  src port      : 0
  dst port      : 0
*May 24 18:02:48.488: IPSEC(crypto_ipsec_create_ipsec_sas): Map found cmap
*May 24 18:02:48.489: IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with the
same proxies and peer 172.16.10.2
*May 24 18:02:48.489: IPSEC(create_sa): sa created,
(sa) sa_dest= 172.16.10.1, sa_proto= 50,
  sa_spi= 0x4C0D0EF0(1275924208),
  sa_trans= esp-aes esp-sha-hmac , sa_conn_id= 7
  sa_lifetime(k/sec)= (4608000/3600)
*May 24 18:02:48.489: IPSEC(create_sa): sa created,
(sa) sa_dest= 172.16.10.2, sa_proto= 50,
  sa_spi= 0xC72072C6(3340792518),
  sa_trans= esp-aes esp-sha-hmac , sa_conn_id= 8
  sa_lifetime(k/sec)= (4608000/3600)

```

Dans des phases le Protocole ISAKMP (Internet Security Association and Key Management Protocol) et IPSec il y a.

Cisco IOS : Compteurs d'IPSec de contrôle

```

R1#show crypto session detail
Crypto session current status

```

```

Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation

```

```

Interface: Ethernet0/0
Uptime: 00:00:05

```

```

Session status: UP-ACTIVE
Peer: 172.16.10.2 port 500 fvrf: (none) ivrf: (none)
  Phase1_id: 172.16.10.2
  Desc: (none)
IKEv1 SA: local 172.16.10.1/500 remote 172.16.10.2/500 Active
  Capabilities:(none) connid:1003 lifetime:23:59:54
IPSEC FLOW: permit ip 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0
  Active SAs: 2, origin: crypto map
  Inbound:  #pkts dec'ed 0 drop 0 life (KB/Sec) 4164218/3594
  Outbound: #pkts enc'ed 0 drop 0 life (KB/Sec) 4164218/3594A

```

Après 100 paquets sont envoyés :

```

R1#ping 192.168.2.1 source e0/1 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.1.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Success rate is 100 percent (100/100), round-trip min/avg/max = 4/4/5 ms
R1#

```

```

R1#show crypto session detail
Crypto session current status

```

```

Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation

```

```

Interface: Ethernet0/0
Uptime: 00:00:09
Session status: UP-ACTIVE
Peer: 172.16.10.2 port 500 fvrf: (none) ivrf: (none)
  Phase1_id: 172.16.10.2
  Desc: (none)
IKEv1 SA: local 172.16.10.1/500 remote 172.16.10.2/500 Active
  Capabilities:(none) connid:1003 lifetime:23:59:50
IPSEC FLOW: permit ip 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0
  Active SAs: 2, origin: crypto map
  Inbound:  #pkts dec'ed 100 drop 0 life (KB/Sec) 4164202/3590
  Outbound: #pkts enc'ed 100 drop 0 life (KB/Sec) 4164202/3590

```

Cisco IOS : Vérifiez les paramètres IKEv1 et d'IPSec

```

R1#show crypto isakmp sa detail

```

```

Codes: C - IKE configuration mode, D - Dead Peer Detection
       K - Keepalives, N - NAT-traversal
       T - cTCP encapsulation, X - IKE Extended Authentication
       psk - Preshared key, rsig - RSA signature
       renc - RSA encryption

```

```

IPv4 Crypto ISAKMP SA

```

C-id	Local	Remote	I-VRF	Status	Encr	Hash	Auth	DH	Lifetime	Cap.
1003	172.16.10.1	172.16.10.2		ACTIVE	aes	sha	psk	5	23:59:35	
	Engine-id:Conn-id = SW:3									

```

R1#show crypto ipsec sa

```

```

interface: Ethernet0/0
  Crypto map tag: cmap, local addr 172.16.10.1

```

```

protected vrf: (none)
local ident (addr/mask/prot/port): (192.168.1.0/255.255.255.0/0/0)
remote ident (addr/mask/prot/port): (192.168.2.0/255.255.255.0/0/0)
current_peer 172.16.10.2 port 500
  PERMIT, flags={origin_is_acl,}
#pkts encaps: 100, #pkts encrypt: 100, #pkts digest: 100
#pkts decaps: 100, #pkts decrypt: 100, #pkts verify: 100
#pkts compressed: 0, #pkts decompressed: 0
#pkts not compressed: 0, #pkts compr. failed: 0
#pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 0, #recv errors 0

local crypto endpt.: 172.16.10.1, remote crypto endpt.: 172.16.10.2
plaintext mtu 1438, path mtu 1500, ip mtu 1500, ip mtu idb Ethernet0/0
current outbound spi: 0xC72072C6(3340792518)
PFS (Y/N): N, DH group: none

inbound esp sas:
spi: 0x4C0D0EF0(1275924208)
  transform: esp-aes esp-sha-hmac ,
  in use settings ={Tunnel, }
  conn id: 7, flow_id: SW:7, sibling_flags 80000040, crypto map: cmap
  sa timing: remaining key lifetime (k/sec): (4164202/3562)
  IV size: 16 bytes
  replay detection support: Y
  Status: ACTIVE(ACTIVE)

inbound ah sas:

inbound pcp sas:

outbound esp sas:
spi: 0xC72072C6(3340792518)
  transform: esp-aes esp-sha-hmac ,
  in use settings ={Tunnel, }
  conn id: 8, flow_id: SW:8, sibling_flags 80000040, crypto map: cmap
  sa timing: remaining key lifetime (k/sec): (4164202/3562)
  IV size: 16 bytes
  replay detection support: Y
  Status: ACTIVE(ACTIVE)

outbound ah sas:

outbound pcp sas:

```

Les deux phases sont en hausse. L'index de paramètre de sécurité IPsec (SPI) est négocié. Le compteur a grimpé jusqu'à 100 après que 100 paquets soient envoyés.

strongSwan : Établissement de tunnel

```
pluton# /etc/init.d/ipsec start
```

```

May 24 20:02:48 localhost charon: 10[NET] received packet: from 172.16.10.1[500]
to 172.16.10.2[500] (168 bytes)
May 24 20:02:48 localhost charon: 10[ENC] parsed ID_PROT request 0 [ SA V V V V ]
May 24 20:02:48 localhost charon: 10[IKE] received NAT-T (RFC 3947) vendor ID
May 24 20:02:48 localhost charon: 10[IKE] received draft-ietf-ipsec-nat-t-ike-07
vendor ID
May 24 20:02:48 localhost charon: 10[IKE] received draft-ietf-ipsec-nat-t-ike-03
vendor ID
May 24 20:02:48 localhost charon: 10[IKE] received draft-ietf-ipsec-nat-t-ike-02\n
vendor ID

```

```

May 24 20:02:48 localhost charon: 10[IKE] 172.16.10.1 is initiating a Main Mode IKE_SA
May 24 20:02:48 localhost charon: 10[IKE] 172.16.10.1 is initiating a Main Mode IKE_SA
May 24 20:02:48 localhost charon: 10[ENC] generating ID_PROT response 0 [ SA V V V ]
May 24 20:02:48 localhost charon: 10[NET] sending packet: from 172.16.10.2[500] to
172.16.10.1[500] (140 bytes)
May 24 20:02:48 localhost charon: 11[NET] received packet: from 172.16.10.1[500] to
172.16.10.2[500] (348 bytes)
May 24 20:02:48 localhost charon: 11[ENC] parsed ID_PROT request 0
[ KE No V V V NAT-D NAT-D ]
May 24 20:02:48 localhost charon: 11[ENC] generating ID_PROT response 0
[ KE No NAT-D NAT-D ]
May 24 20:02:48 localhost charon: 11[NET] sending packet: from 172.16.10.2[500]
to 172.16.10.1[500] (308 bytes)
May 24 20:02:48 localhost charon: 12[NET] received packet: from 172.16.10.1[500]
to 172.16.10.2[500] (108 bytes)
May 24 20:02:48 localhost charon: 12[ENC] parsed ID_PROT request 0
[ ID HASH N(INITIAL_CONTACT) ]
May 24 20:02:48 localhost charon: 12[CFG] looking for pre-shared key peer configs
matching 172.16.10.2...172.16.10.1[172.16.10.1]
May 24 20:02:48 localhost charon: 12[CFG] selected peer config "ciscoios"
May 24 20:02:48 localhost charon: 12[IKE] IKE_SA ciscoios{2} established between
172.16.10.2[172.16.10.2]...172.16.10.1[172.16.10.1]
May 24 20:02:48 localhost charon: 12[IKE] IKE_SA ciscoios{2} established between
172.16.10.2[172.16.10.2]...172.16.10.1[172.16.10.1]
May 24 20:02:48 localhost charon: 12[IKE] scheduling reauthentication in 3289s
May 24 20:02:48 localhost charon: 12[IKE] maximum IKE_SA lifetime 3469s
May 24 20:02:48 localhost charon: 12[ENC] generating ID_PROT response 0 [ ID HASH ]
May 24 20:02:48 localhost charon: 12[NET] sending packet: from 172.16.10.2[500] to
172.16.10.1[500] (76 bytes)
May 24 20:02:48 localhost charon: 14[NET] received packet: from 172.16.10.1[500] to
172.16.10.2[500] (188 bytes)
May 24 20:02:48 localhost charon: 14[ENC] parsed QUICK_MODE request 2605730229
[ HASH SA No ID ID ]
May 24 20:02:48 localhost charon: 14[IKE] received 3600s lifetime, configured 1200s
May 24 20:02:48 localhost charon: 14[IKE] received 4608000000 lifebytes, configured 0
May 24 20:02:48 localhost charon: 14[ENC] generating QUICK_MODE response 2605730229
[ HASH SA No ID ID ]
May 24 20:02:48 localhost charon: 14[NET] sending packet: from 172.16.10.2[500] to
172.16.10.1[500] (188 bytes)
May 24 20:02:48 localhost charon: 15[NET] received packet: from 172.16.10.1[500] to
172.16.10.2[500] (60 bytes)
May 24 20:02:48 localhost charon: 15[ENC] parsed QUICK_MODE request 2605730229 [ HASH ]
May 24 20:02:48 localhost charon: 15[IKE] CHILD_SA ciscoios{2} established with SPIs
c72072c6_i 4c0d0ef0_o and TS 192.168.2.0/24 === 192.168.1.0/24
May 24 20:02:48 localhost charon: 15[IKE] CHILD_SA ciscoios{2} established with SPIs
c72072c6_i 4c0d0ef0_o and TS 192.168.2.0/24 === 192.168.1.0/24
May 24 20:02:48 localhost vpn: + 172.16.10.1 192.168.1.0/24 == 172.16.10.1 --
172.16.10.2 == 192.168.2.0/24

```

Les deux phases sont en hausse. Les SPI corrects qui protègent le trafic entre 192.168.2.0/24 et 192.168.1.0/24 sont négociés.

strongSwan : Vérifiez l'état de la connexion d'IPSec

```

pluton ~ # ipsec statusall
Status of IKE charon daemon (strongSwan 5.0.4, Linux 3.2.12-gentoo, x86_64):
  uptime: 4 minutes, since May 24 20:02:15 2013
  malloc: sbrk 393216, mmap 0, used 274064, free 119152
  worker threads: 8 of 16 idle, 7/1/0/0 working, job queue: 0/0/0/0, scheduled: 4
  loaded plugins: charon mysql sqlite aes des sha1 sha2 md5 random nonce x509
  revocation constraints pubkey pkcs1 pkcs8 pgp dnskey pem openssl gcrypt fips-prf
  gmp xcbc cmac hmac attr kernel-netlink resolve socket-default stroke updown

```

eap-identity eap-sim eap-aka eap-aka-3gpp2 eap-simaka-pseudonym eap-simaka-reauth
eap-md5 eap-gtc eap-mschapv2 eap-radius xauth-generic

Listening IP addresses:

10.0.0.100
192.168.10.1
172.16.10.2
192.168.2.1

Connections:

ciscoios: **172.16.10.2...172.16.10.1 IKEv1**
ciscoios: local: [172.16.10.2] uses pre-shared key authentication
ciscoios: remote: [172.16.10.1] uses pre-shared key authentication
ciscoios: **child: 192.168.2.0/24 === 192.168.1.0/24 TUNNEL**

Security Associations (1 up, 0 connecting):

ciscoios[2]: ESTABLISHED 4 minutes ago, 172.16.10.2[172.16.10.2]...
172.16.10.1[172.16.10.1]
ciscoios[2]: IKEv1 SPIs: 278f22e3c3e5f606_i dbb5a27f3e0eccd1_r*,
pre-shared key reauthentication in 50 minutes
ciscoios[2]: IKE proposal: **AES_CBC_128/HMAC_SHA1_96/PRF_HMAC_SHA1/MODP_1536**
ciscoios{2}: INSTALLED, TUNNEL, ESP SPIs: c72072c6_i 4c0d0ef0_o
ciscoios{2}: AES_CBC_128/HMAC_SHA1_96, 10000 bytes_i (100 pkts, 255s ago),
10000 bytes_o (100 pkts, 255s ago), rekeying in 11 minutes
ciscoios{2}: **192.168.2.0/24 === 192.168.1.0/24**

Les détails au sujet de l'ISAKMP négocié et les paramètres d'IPSec sont disponibles.

strongSwan : Vérifiez la stratégie IPSec

```
pluton ~ # ip -s xfrm policy
```

```
src 192.168.1.0/24 dst 192.168.2.0/24 uid 0
```

```
dir fwd action allow index 258 priority 1859 share any flag (0x00000000)
```

```
lifetime config:
```

```
limit: soft (INF)(bytes), hard (INF)(bytes)  
limit: soft (INF)(packets), hard (INF)(packets)  
expire add: soft 0(sec), hard 0(sec)  
expire use: soft 0(sec), hard 0(sec)
```

```
lifetime current:
```

```
0(bytes), 0(packets)  
add 2013-05-24 20:02:48 use -
```

```
tmpl src 172.16.10.1 dst 172.16.10.2
```

```
proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel  
level required share any  
enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
```

```
src 192.168.1.0/24 dst 192.168.2.0/24 uid 0
```

```
dir in action allow index 248 priority 1859 share any flag (0x00000000)
```

```
lifetime config:
```

```
limit: soft (INF)(bytes), hard (INF)(bytes)  
limit: soft (INF)(packets), hard (INF)(packets)  
expire add: soft 0(sec), hard 0(sec)  
expire use: soft 0(sec), hard 0(sec)
```

```
lifetime current:
```

```
0(bytes), 0(packets)  
add 2013-05-24 20:02:48 use 2013-05-24 20:02:56
```

```
tmpl src 172.16.10.1 dst 172.16.10.2
```

```
proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel  
level required share any  
enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
```

```
src 192.168.2.0/24 dst 192.168.1.0/24 uid 0
```

```
dir out action allow index 241 priority 1859 share any flag (0x00000000)
```

```
lifetime config:
```

```
limit: soft (INF)(bytes), hard (INF)(bytes)  
limit: soft (INF)(packets), hard (INF)(packets)  
expire add: soft 0(sec), hard 0(sec)
```

```
    expire use: soft 0(sec), hard 0(sec)
lifetime current:
    0(bytes), 0(packets)
add 2013-05-24 20:02:48 use 2013-05-24 20:02:56
tmpl src 172.16.10.2 dst 172.16.10.1
    proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel
    level required share any
    enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
```

Les détails précédents incluent des tables de stratégie interne.

IKEv2 entre le Cisco IOS et strongSwan

Cisco IOS

```
R1#ping 192.168.2.1 source e0/1 repeat 1
```

Établissement de tunnel déclenché par Cisco IOS

```
*May 24 19:14:10.485: IPSEC(sa_request): ,
(key eng. msg.) OUTBOUND local= 172.16.10.1:500, remote= 172.16.10.2:500,
  local_proxy= 192.168.1.0/255.255.255.0/256/0,
  remote_proxy= 192.168.2.0/255.255.255.0/256/0,
  protocol= ESP, transform= esp-aes esp-sha-hmac (Tunnel),
  lifedur= 3600s and 4608000kb,
  spi= 0x0(0), conn_id= 0, keysize= 128, flags= 0x0
*May 24 19:14:10.486: IKEv2:% Getting preshared key from profile keyring keys
*May 24 19:14:10.486: IKEv2:% Matched peer block 'strongswan'
*May 24 19:14:10.486: IKEv2:Searching Policy with fvrf 0, local address 172.16.10.1
*May 24 19:14:10.486: IKEv2:Found Policy 'ikev2policy'
*May 24 19:14:10.486: IKEv2:(SA ID = 1):[IKEv2 -> Crypto Engine] Computing DH public
key, DH Group 5
*May 24 19:14:10.486: IKEv2:(SA ID = 1):[Crypto Engine -> IKEv2] DH key Computation
PASSED
*May 24 19:14:10.486: IKEv2:(SA ID = 1):Request queued for computation of DH key
*May 24 19:14:10.486: IKEv2:IKEv2 initiator - no config data to send in IKE_SA_INIT exch
*May 24 19:14:10.486: IKEv2:(SA ID = 1):Generating IKE_SA_INIT message
*May 24 19:14:10.486: IKEv2:(SA ID = 1):IKE Proposal: 1, SPI size: 0
(initial negotiation),
Num. transforms: 4
  AES-CBC  SHA1  SHA96  DH_GROUP_1536_MODP/Group 5

*May 24 19:14:10.486: IKEv2:(SA ID = 1):Sending Packet [To 172.16.10.2:500/From
172.16.10.1:500/VRF i0:f0]
Initiator SPI : 9FFC38791FFEF212 - Responder SPI : 0000000000000000 Message id: 0
IKEv2 IKE_SA_INIT Exchange REQUEST
Payload contents:
  SA KE N VID VID NOTIFY(NAT_DETECTION_SOURCE_IP) NOTIFY(NAT_DETECTION_DESTINATION_IP)

*May 24 19:14:10.486: IKEv2:(SA ID = 1):Insert SA

*May 24 19:14:10.495: IKEv2:(SA ID = 1):Received Packet [From 172.16.10.2:500/To
172.16.10.1:500/VRF i0:f0]
Initiator SPI : 9FFC38791FFEF212 - Responder SPI : 6CDC17F5B0B10C1A Message id: 0
IKEv2 IKE_SA_INIT Exchange RESPONSE
Payload contents:
  SA KE N NOTIFY(NAT_DETECTION_SOURCE_IP) NOTIFY(NAT_DETECTION_DESTINATION_IP)
NOTIFY(Unknown - 16404)
```

*May 24 19:14:10.495: IKEv2:(SA ID = 1):Processing IKE_SA_INIT message
*May 24 19:14:10.495: IKEv2:(SA ID = 1):Verify SA init message
*May 24 19:14:10.495: IKEv2:(SA ID = 1):Processing IKE_SA_INIT message
*May 24 19:14:10.495: IKEv2:(SA ID = 1):Checking NAT discovery
*May 24 19:14:10.495: IKEv2:(SA ID = 1):NAT not found
*May 24 19:14:10.495: IKEv2:(SA ID = 1):[IKEv2 -> Crypto Engine] Computing DH
secret key, DH Group 5
*May 24 19:14:10.504: IKEv2:(SA ID = 1):[Crypto Engine -> IKEv2] DH key Computation
PASSED
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Request queued for computation of DH secret
*May 24 19:14:10.504: IKEv2:(SA ID = 1):[IKEv2 -> Crypto Engine] Calculate SKEYSEED
and create rekeyed IKEv2 SA
*May 24 19:14:10.504: IKEv2:(SA ID = 1):[Crypto Engine -> IKEv2] SKEYSEED
calculation and creation of
rekeyed IKEv2 SA PASSED
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Completed SA init exchange
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Check for EAP exchange
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Generate my authentication data
*May 24 19:14:10.504: IKEv2:(SA ID = 1):**Use preshared key for id 172.16.10.1,**
key len 5
*May 24 19:14:10.504: IKEv2:[IKEv2 -> Crypto Engine] Generate IKEv2 authentication
data
*May 24 19:14:10.504: IKEv2:[Crypto Engine -> IKEv2] **IKEv2 authentication data
generation PASSED**
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Get my authentication method
*May 24 19:14:10.504: IKEv2:(SA ID = 1):My authentication method is 'PSK'
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Check for EAP exchange
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Generating IKE_AUTH message
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Constructing IDi payload: '172.16.10.1'
of type 'IPv4 address'
*May 24 19:14:10.504: IKEv2:(SA ID = 1):**ESP Proposal: 1**, SPI size: 4
(IPSec negotiation),
Num. transforms: 3
AES-CBC SHA96 Don't use ESN
*May 24 19:14:10.504: IKEv2:(SA ID = 1):Building packet for encryption.
Payload contents:
VID IDi AUTH SA TSi TSr NOTIFY(INITIAL_CONTACT) NOTIFY(SET_WINDOW_SIZE)
NOTIFY(ESP_TFC_NO_SUPPORT) NOTIFY(NON_FIRST_FRAGS)
*May 24 19:14:10.505: IKEv2:(SA ID = 1):**Sending Packet**
[To 172.16.10.2:500/From 172.16.10.1:500/VRF i0:f0]
Initiator SPI : 9FFC38791FFEF212 - Responder SPI : 6CDC17F5B0B10C1A Message id: 1
IKEv2 IKE_AUTH Exchange REQUEST
Payload contents:
ENCR

*May 24 19:14:10.522: IKEv2:(SA ID = 1):**Received Packet**
[From 172.16.10.2:500/To 172.16.10.1:500/VRF i0:f0]
Initiator SPI : 9FFC38791FFEF212 - Responder SPI : 6CDC17F5B0B10C1A Message id: 1
IKEv2 IKE_AUTH Exchange RESPONSE
Payload contents:
IDr AUTH SA TSi TSr NOTIFY(Unknown - 16403)

*May 24 19:14:10.522: IKEv2:(SA ID = 1):Process auth response notify
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Searching policy based on peer's
identity '172.16.10.2' of type 'IPv4 address'
*May 24 19:14:10.522: IKEv2:Searching Policy with fvrf 0, local address 172.16.10.1
*May 24 19:14:10.522: IKEv2:Found Policy 'ikev2policy'
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Verify peer's policy
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Peer's policy verified
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Get peer's authentication method
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Peer's authentication method is 'PSK'
*May 24 19:14:10.522: IKEv2:(SA ID = 1):**Get peer's preshared key for 172.16.10.2**

```

*May 24 19:14:10.522: IKEv2:(SA ID = 1):Verify peer's authentication data
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Use preshared key for id 172.16.10.2, key len 5
*May 24 19:14:10.522: IKEv2:[IKEv2 -> Crypto Engine] Generate IKEv2 authentication data
*May 24 19:14:10.522: IKEv2:[Crypto Engine -> IKEv2] IKEv2 authentication data
generation PASSED
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Verification of peer's authentication data
PASSED
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Check for EAP exchange
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Processing IKE_AUTH message
*May 24 19:14:10.522: IKEv2:KMI/verify policy/sending to IPSec:
    prot: 3 txfm: 12 hmac 2 flags 8177 keysize 128 IDB 0x0
*May 24 19:14:10.522: IPSEC(validate_proposal_request): proposal part #1
*May 24 19:14:10.522: IPSEC(validate_proposal_request): proposal part #1,
(key eng. msg.) INBOUND local= 172.16.10.1:0, remote= 172.16.10.2:0,
    local_proxy= 192.168.1.0/255.255.255.0/256/0,
    remote_proxy= 192.168.2.0/255.255.255.0/256/0,
    protocol= ESP, transform= NONE (Tunnel),
    lifedur= 0s and 0kb,
    spi= 0x0(0), conn_id= 0, keysize= 128, flags= 0x0
*May 24 19:14:10.522: Crypto mapdb : proxy_match
    src addr      : 192.168.1.0
    dst addr      : 192.168.2.0
    protocol      : 0
    src port      : 0
    dst port      : 0
*May 24 19:14:10.522: IKEv2:(SA ID = 1):IKEV2 SA created; inserting SA into database.
SA lifetime timer (86400 sec) started
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Session with IKE ID PAIR
(172.16.10.2, 172.16.10.1) is UP
*May 24 19:14:10.522: IKEv2:IKEv2 MIB tunnel started, tunnel index 1
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Load IPSEC key material
*May 24 19:14:10.522: IKEv2:(SA ID = 1):[IKEv2 -> IPsec] Create IPsec SA into
IPsec database
*May 24 19:14:10.522: IKEv2:(SA ID = 1):Asynchronous request queued

*May 24 19:14:10.522: IKEv2:(SA ID = 1):
*May 24 19:14:10.523: IPSEC(key_engine): got a queue event with 1 KMI message(s)
*May 24 19:14:10.523: Crypto mapdb : proxy_match
    src addr      : 192.168.1.0
    dst addr      : 192.168.2.0
    protocol      : 256
    src port      : 0
    dst port      : 0
*May 24 19:14:10.523: IPSEC(crypto_ipsec_create_ipsec_sas): Map found cmap
*May 24 19:14:10.523: IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with
the same proxies and peer 172.16.10.2
*May 24 19:14:10.523: IPSEC(create_sa): sa created,
(sa) sa_dest= 172.16.10.1, sa_proto= 50,
    sa_spi= 0xDF405365(3745534821),
    sa_trans= esp-aes esp-sha-hmac , sa_conn_id= 6
    sa_lifetime(k/sec)= (4608000/3600)
*May 24 19:14:10.523: IPSEC(create_sa): sa created,
(sa) sa_dest= 172.16.10.2, sa_proto= 50,
    sa_spi= 0xC0CC116C(3234599276),
    sa_trans= esp-aes esp-sha-hmac , sa_conn_id= 5
    sa_lifetime(k/sec)= (4608000/3600)
*May 24 19:14:10.523: IPSEC: Expand action denied, notify RP
*May 24 19:14:10.523: IKEv2:(SA ID = 1):[IPsec -> IKEv2] Creation of IPsec
SA into IPsec database PASSED

```

La session IKEv2 est en hausse et IPsec SA qui protège le trafic entre 192.168.1.0/24 et 192.168.2.0/24 a été créé.

Cisco IOS : Compteurs d'IPSec de contrôle

```
R1#show crypto session detail
Crypto session current status
```

```
Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation
```

```
Interface: Ethernet0/0
Uptime: 00:00:09
Session status: UP-ACTIVE
Peer: 172.16.10.2 port 500 fvrf: (none) ivrf: (none)
  Phase1_id: 172.16.10.2
  Desc: (none)
IKEv2 SA: local 172.16.10.1/500 remote 172.16.10.2/500 Active
  Capabilities:(none) connid:1 lifetime:23:59:51
IPSEC FLOW: permit ip 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0
  Active SAs: 2, origin: crypto map
  Inbound:  #pkts dec'ed 0 drop 0 life (KB/Sec) 4375820/3590
  Outbound: #pkts enc'ed 0 drop 0 life (KB/Sec) 4375820/3590
```

Après 100 paquets sont envoyés :

```
R1#ping 192.168.2.1 source 192.168.1.1 repeat 100
Type escape sequence to abort.
Sending 100, 100-byte ICMP Echos to 192.168.2.1, timeout is 2 seconds:
Packet sent with a source address of 192.168.1.1
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
Success rate is 100 percent (100/100), round-trip min/avg/max = 1/4/5 ms
R1#
```

```
R1#show crypto session detail
Crypto session current status
```

```
Code: C - IKE Configuration mode, D - Dead Peer Detection
K - Keepalives, N - NAT-traversal, T - cTCP encapsulation
X - IKE Extended Authentication, F - IKE Fragmentation
```

```
Interface: Ethernet0/0
Uptime: 00:00:15
Session status: UP-ACTIVE
Peer: 172.16.10.2 port 500 fvrf: (none) ivrf: (none)
  Phase1_id: 172.16.10.2
  Desc: (none)
IKEv2 SA: local 172.16.10.1/500 remote 172.16.10.2/500 Active
  Capabilities:(none) connid:1 lifetime:23:59:45
IPSEC FLOW: permit ip 192.168.1.0/255.255.255.0 192.168.2.0/255.255.255.0
  Active SAs: 2, origin: crypto map
  Inbound:  #pkts dec'ed 100 drop 0 life (KB/Sec) 4375803/3585
  Outbound: #pkts enc'ed 100 drop 0 life (KB/Sec) 4375803/3585
```

Le compteur a augmenté de 100.

Cisco IOS : Vérifiez les paramètres IKEv2 et d'IPSec

Le Cisco IOS a des statistiques/détails très gentils pour la session IKEv2 :

R1#show crypto ikev2 sa detailed

IPv4 Crypto IKEv2 SA

Tunnel-id	Local	Remote	fvr/ivrf	Status
1	172.16.10.1/500	172.16.10.2/500	none/none	READY

Encr: **AES-CBC, keysize: 128, Hash: SHA96, DH Grp:5**, Auth sign: PSK, Auth verify: PSK
Life/Active Time: 86400/152 sec
CE id: 1019, Session-id: 3
Status Description: Negotiation done
Local spi: 9FFC38791FFEF212 Remote spi: 6CDC17F5B0B10C1A
Local id: 172.16.10.1
Remote id: 172.16.10.2
Local req msg id: 2 Remote req msg id: 0
Local next msg id: 2 Remote next msg id: 0
Local req queued: 2 Remote req queued: 0
Local window: 5 Remote window: 1
DPD configured for 0 seconds, retry 0
Fragmentation not configured.
Extended Authentication not configured.
NAT-T is not detected
Cisco Trust Security SGT is disabled
Initiator of SA : Yes

IPv6 Crypto IKEv2 SA

R1#show crypto ipsec sa

interface: Ethernet0/0

Crypto map tag: cmap, local addr 172.16.10.1

protected vrf: (none)

local ident (addr/mask/prot/port): (192.168.1.0/255.255.255.0/0/0)

remote ident (addr/mask/prot/port): (192.168.2.0/255.255.255.0/0/0)

current_peer 172.16.10.2 port 500

PERMIT, flags={origin_is_acl,}

#pkts encaps: 100, #pkts encrypt: 100, #pkts digest: 100

#pkts decaps: 100, #pkts decrypt: 100, #pkts verify: 100

#pkts compressed: 0, #pkts decompressed: 0

#pkts not compressed: 0, #pkts compr. failed: 0

#pkts not decompressed: 0, #pkts decompress failed: 0

#send errors 0, #recv errors 0

local crypto endpt.: 172.16.10.1, remote crypto endpt.: 172.16.10.2

plaintext mtu 1438, path mtu 1500, ip mtu 1500, ip mtu idb Ethernet0/0

current outbound spi: 0xC0CC116C(3234599276)

PFS (Y/N): N, DH group: none

inbound esp sas:

spi: 0xDF405365(3745534821)

transform: esp-aes esp-sha-hmac ,

in use settings = {Tunnel, }

conn id: 6, flow_id: SW:6, sibling_flags 80000040, crypto map: cmap

sa timing: remaining key lifetime (k/sec): (4375803/3442)

IV size: 16 bytes

replay detection support: Y

Status: ACTIVE(ACTIVE)

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0xC0CC116C(3234599276)

```
transform: esp-aes esp-sha-hmac ,
in use settings ={Tunnel, }
conn id: 5, flow_id: SW:5, sibling_flags 80000040, crypto map: cmap
sa timing: remaining key lifetime (k/sec): (4375803/3442)
IV size: 16 bytes
replay detection support: Y
Status: ACTIVE(ACTIVE)
```

outbound ah sas:

outbound pcp sas:

strongSwan : Établissement de tunnel

```
May 24 21:14:10 localhost charon: 08[NET] received packet: from 172.16.10.1[500]
to 172.16.10.2[500] (400 bytes)
May 24 21:14:10 localhost charon: 08[ENC] parsed IKE_SA_INIT request 0
[ SA KE No V V N(NATD_S_IP) N(NATD_D_IP) ]
May 24 21:14:10 localhost charon: 08[ENC] received unknown vendor
ID: 43:49:53:43:4f:2d:44:45:4c:45:54:45:2d:52:45:41:53:4f:4e
May 24 21:14:10 localhost charon: 08[ENC] received unknown vendor ID:
46:4c:45:58:56:50:4e:2d:53:55:50:50:4f:52:54:45:44
May 24 21:14:10 localhost charon: 08[IKE] 172.16.10.1 is initiating an IKE_SA
May 24 21:14:10 localhost charon: 08[IKE] 172.16.10.1 is initiating an IKE_SA
May 24 21:14:10 localhost charon: 08[ENC] generating IKE_SA_INIT response 0
[ SA KE No N(NATD_S_IP) N(NATD_D_IP) N(MULT_AUTH) ]
May 24 21:14:10 localhost charon: 08[NET] sending packet: from 172.16.10.2[500]
to 172.16.10.1[500] (376 bytes)
May 24 21:14:10 localhost charon: 07[NET] received packet: from 172.16.10.1[500]
to 172.16.10.2[500] (284 bytes)
May 24 21:14:10 localhost charon: 07[ENC] parsed IKE_AUTH request 1 [ V IDi AUTH
SA TSi TSr N(INIT_CONTACT) N(SET_WINSIZE) N(ESP_TFC_PAD_N) N(NON_FIRST_FRAG) ]
May 24 21:14:10 localhost charon: 07[CFG] looking for peer configs matching
172.16.10.2[%any]...172.16.10.1[172.16.10.1]
May 24 21:14:10 localhost charon: 07[CFG] selected peer config 'ciscoios'
May 24 21:14:10 localhost charon: 07[IKE] authentication of '172.16.10.1' with
pre-shared key successful
May 24 21:14:10 localhost charon: 07[IKE] received ESP_TFC_PADDING_NOT_SUPPORTED,
not using ESPv3 TFC padding
May 24 21:14:10 localhost charon: 07[IKE] authentication of '172.16.10.2' (myself)
with pre-shared key
May 24 21:14:10 localhost charon: 07[IKE] IKE_SA ciscoios{2} established between
172.16.10.2[172.16.10.2]...172.16.10.1[172.16.10.1]
May 24 21:14:10 localhost charon: 07[IKE] IKE_SA ciscoios{2} established between
172.16.10.2[172.16.10.2]...172.16.10.1[172.16.10.1]
May 24 21:14:10 localhost charon: 07[IKE] scheduling reauthentication in 3247s
May 24 21:14:10 localhost charon: 07[IKE] maximum IKE_SA lifetime 3427s
May 24 21:14:10 localhost charon: 07[IKE] CHILD_SA ciscoios{2} established with
SPIs c0cc116c_i df405365_o and TS 192.168.2.0/24 === 192.168.1.0/24
May 24 21:14:10 localhost charon: 07[IKE] CHILD_SA ciscoios{2} established with
SPIs c0cc116c_i df405365_o and TS 192.168.2.0/24 === 192.168.1.0/24
May 24 21:14:10 localhost vpn: + 172.16.10.1 192.168.1.0/24 == 172.16.10.1 --
172.16.10.2 == 192.168.2.0/24
```

Les détails d'établissement de tunnel regardent un bit semblable à IKEv1.

strongSwan : Vérifiez l'état de la connexion d'IPSec

```
pluton ~ # ipsec statusall
Status of IKE charon daemon (strongSwan 5.0.4, Linux 3.2.12-gentoo, x86_64):
uptime: 2 minutes, since May 24 21:13:27 2013
```

```

malloc: sbrk 393216, mmap 0, used 274864, free 118352
worker threads: 8 of 16 idle, 7/1/0/0 working, job queue: 0/0/0/0, scheduled: 4
loaded plugins: charon mysql sqlite aes des sha1 sha2 md5 random nonce x509
revocation constraints pubkey pkcs1 pkcs8 pgp dnskey pem openssl gcrypt
fips-prf gmp xcbc cmac hmac attr kernel-netlink resolve socket-default
stroke updown eap-identity eap-sim eap-aka eap-aka-3gpp2 eap-simaka-pseudonym
eap-simaka-reauth eap-md5 eap-gtc eap-mschapv2 eap-radius xauth-generic
Listening IP addresses:
10.0.0.100
192.168.10.1
192.168.2.1
172.16.10.2
Connections:
  ciscoios: 172.16.10.2...172.16.10.1 IKEv2
  ciscoios: local: [172.16.10.2] uses pre-shared key authentication
  ciscoios: remote: [172.16.10.1] uses pre-shared key authentication
  ciscoios: child: 192.168.2.0/24 === 192.168.1.0/24 TUNNEL
Security Associations (1 up, 0 connecting):
  ciscoios[2]: ESTABLISHED 116 seconds ago, 172.16.10.2[172.16.10.2]...
172.16.10.1[172.16.10.1]
  ciscoios[2]: IKEv2 SPIs: 12f2fe1f7938fc9f_i 1a0cb1b0f517dc6c_r*,
pre-shared key reauthentication in 52 minutes
  ciscoios[2]: IKE proposal: AES_CBC_128/HMAC_SHA1_96/PRF_HMAC_SHA1/MODP_1536
  ciscoios{2}: INSTALLED, TUNNEL, ESP SPIs: c0cc116c_i df405365_o
  ciscoios{2}: AES_CBC_128/HMAC_SHA1_96, 10000 bytes_i (100 pkts, 102s ago),
10000 bytes_o (100 pkts, 102s ago), rekeying in 12 minutes
  ciscoios{2}: 192.168.2.0/24 === 192.168.1.0/24

```

strongSwan : Vérifiez la stratégie IPSec

```

pluton ~ # ip -s xfrm policy
src 192.168.1.0/24 dst 192.168.2.0/24 uid 0
  dir fwd action allow index 1154 priority 1859 share any flag (0x00000000)
  lifetime config:
    limit: soft (INF)(bytes), hard (INF)(bytes)
    limit: soft (INF)(packets), hard (INF)(packets)
    expire add: soft 0(sec), hard 0(sec)
    expire use: soft 0(sec), hard 0(sec)
  lifetime current:
    0(bytes), 0(packets)
    add 2013-05-24 21:14:10 use -
  tmpl src 172.16.10.1 dst 172.16.10.2
    proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel
    level required share any
    enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
src 192.168.1.0/24 dst 192.168.2.0/24 uid 0
  dir in action allow index 1144 priority 1859 share any flag (0x00000000)
  lifetime config:
    limit: soft (INF)(bytes), hard (INF)(bytes)
    limit: soft (INF)(packets), hard (INF)(packets)
    expire add: soft 0(sec), hard 0(sec)
    expire use: soft 0(sec), hard 0(sec)
  lifetime current:
    0(bytes), 0(packets)
    add 2013-05-24 21:14:10 use 2013-05-24 21:14:23
  tmpl src 172.16.10.1 dst 172.16.10.2
    proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel
    level required share any
    enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
src 192.168.2.0/24 dst 192.168.1.0/24 uid 0
  dir out action allow index 1137 priority 1859 share any flag (0x00000000)
  lifetime config:

```

```
limit: soft (INF)(bytes), hard (INF)(bytes)
limit: soft (INF)(packets), hard (INF)(packets)
expire add: soft 0(sec), hard 0(sec)
expire use: soft 0(sec), hard 0(sec)
lifetime current:
  0(bytes), 0(packets)
  add 2013-05-24 21:14:10 use 2013-05-24 21:14:23
tmp1 src 172.16.10.2 dst 172.16.10.1
  proto esp spi 0x00000000(0) reqid 2(0x00000002) mode tunnel
  level required share any
  enc-mask ffffffff auth-mask ffffffff comp-mask ffffffff
```

Les informations relatives

- [Openswan](#)
- [documentation utilisateur strongSwan](#)
- [FlexVPN et guide de configuration de version 2 d'échange de clés Internet \(IKE\), version de Cisco IOS 15M&T](#)
- [Support et documentation techniques - Cisco Systems](#)