

Conversion de la publication à état de liaison OSPF NSSA de type 7 en type 5

Contenu

[Introduction](#)

[Conditions préalables](#)

[Conditions requises](#)

[Composants utilisés](#)

[Conventions](#)

[Configurez](#)

[Diagramme du réseau](#)

[Configurations](#)

[Vérifiez](#)

[Examiner la base de données OSPF](#)

[Dépannez](#)

[Informations connexes](#)

[Introduction](#)

Ce document montre comment Open Shortest Path First (OSPF) convertit une annonce de l'état des liaisons (LSA) NSSA de type 7 en LSA de type 5.

[Conditions préalables](#)

[Conditions requises](#)

Aucune spécification déterminée n'est requise pour ce document.

[Composants utilisés](#)

Ce document n'est pas limité à des versions de matériel et de logiciel spécifiques.

[Conventions](#)

Pour plus d'informations sur les conventions utilisées dans ce document, reportez-vous à [Conventions relatives aux conseils techniques Cisco](#).

[Configurez](#)

Cette section vous fournit des informations pour configurer les fonctionnalités décrites dans ce

document.

Note: Pour obtenir des informations supplémentaires sur les commandes utilisées dans ce document, utilisez l'[Outil de recherche de commande](#) ([clients enregistrés](#) seulement).

[Diagramme du réseau](#)

Ce document utilise la configuration réseau indiquée dans le diagramme suivant.

[Configurations](#)

Ce document utilise les configurations indiquées ici.

- [Routeur 1.1.1.1](#)
- [Routeur 2.2.2.2](#)
- [Routeur 3.3.3.3](#)

```
Routeur 1.1.1.1

Current configuration:

hostname r1.1.1.1

interface Loopback0
 ip address 1.1.1.1 255.0.0.0

interface Serial2/1/0
 ip address 5.0.0.1 255.0.0.0

interface Ethernet2/0/0
 ip address 4.0.0.1 255.0.0.0

router ospf 4
 redistribute static metric 5 metric-type 1
 network 5.0.0.0 0.255.255.255 area 1
 network 4.0.0.0 0.255.255.255 area 1
 area 1 nssa

ip route 9.0.0.0 255.0.0.0 4.0.0.2

end
```

```
Routeur 2.2.2.2

Current configuration:

hostname r2.2.2.2

interface Loopback0
 ip address 2.2.2.2 255.0.0.0

interface Serial10/1/0
 ip address 5.0.0.2 255.0.0.0

interface ATM1/0.20
 ip address 6.0.0.2 255.0.0.0

router ospf 2
```

```
network 5.0.0.0 0.255.255.255 area 1
network 6.0.0.0 0.255.255.255 area 0
area 1 nssa

end
```

Routeur 3.3.3.3

```
Current configuration:

hostname r3.3.3.3

interface Loopback0
 ip address 3.3.3.3 255.0.0.0

interface ATM2/0.20 point-to-point
 ip address 6.0.0.3 255.0.0.0

router ospf 2
 network 6.0.0.0 0.255.255.255 area 0

end
```

Vérifiez

Cette section présente des informations que vous pouvez utiliser pour vous assurer que votre configuration fonctionne correctement.

Certaines commandes **show** sont prises en charge par l'[Output Interpreter Tool](#) (clients enregistrés uniquement), qui vous permet de voir une analyse de la sortie de la commande show.

- [show ip ospf database](#) — Affiche une liste des LSAs et les tape dans une base de données d'état de lien. Cette liste affiche seulement les informations dans l'en-tête LSA.
- [show ip ospf database nssa-externe](#) — Affiche des informations seulement au sujet des LSAs externes NSSA.
- [show ip ospf database externe](#) — Affiche des informations uniquement au sujet des LSAs externes.
- [show ip ospf database \[routeur\] \[lien-état-id\]](#) — affiche une liste de tous les LSAs d'un routeur dans la base de données. Les LSAs sont produits par chaque routeur, et les liens de ces fondamentaux. Les routeurs de LSAs listent tous les, ou interfaces, avec les états et les coûts sortants des liens. Ils sont inondés seulement dans la zone de laquelle ils commencent.
- *id> récapitulatif de <lien-état de show ip ospf database* — Affiche les liens récapitulatifs de routeur de cadre de zone (ABR).
- [show ip route](#) — Affiche l'état actuel de la table de routage.

Examiner la base de données OSPF

Pour voir comment les semblent de base de données OSPF dans cet environnement de réseau, utilisez la commande de **show ip ospf database**.

```
r2.2.2.2#show ip ospf database
```

```
OSPF Router with ID (2.2.2.2) (Process ID 2)
```

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
2.2.2.2	2.2.2.2	1235	0x8000001D	0xD9FF	2
3.3.3.3	3.3.3.3	1100	0x8000000B	0x9455	2

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
4.0.0.0	2.2.2.2	1979	0x80000002	0xFDE7
5.0.0.0	2.2.2.2	1483	0x80000004	0x8864

Router Link States (Area 1)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
1.1.1.1	1.1.1.1	319	0x8000000C	0xAFA8	3
2.2.2.2	2.2.2.2	220	0x8000002F	0xD478	2

Summary Net Link States (Area 1)

Link ID	ADV Router	Age	Seq#	Checksum
6.0.0.0	2.2.2.2	1483	0x8000001C	0x7894

Type-7 AS External Link States (Area 1)

Link ID	ADV Router	Age	Seq#	Checksum	Tag
9.0.0.0	1.1.1.1	334	0x80000005	0xD738	0

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
9.0.0.0	2.2.2.2	1725	0x80000004	0x50C6	0

Pour annoncer les artères externes dans un NSSA, le routeur ASBR (Autonomous System Boundary Router) crée LSAs nssa-externe (type 7).

```
r2.2.2.2#show ip ospf database nssa-external 9.0.0.0
```

```
OSPF Router with ID (2.2.2.2) (Process ID 2)
```

Type-7 AS External Link States (Area 1)

Routing Bit Set on this LSA

LS age: 381

Options: (No TOS-capability, Type 7/5 translation, DC)

!--- This can be translated into a type 5 LSA by !--- an ABR. LS Type: AS External Link Link State ID: 9.0.0.0 (External Network Number) !--- The ASBR (Router 1.1.1.1) advertises !--- 9.0.0.0/8. Advertising Router: 1.1.1.1 !--- Router ID of the ASBR. LS Seq Number: 80000005 Checksum: 0xD738 Length: 36 Network Mask: /8 Metric Type: 1 (Comparable directly to link state metric) TOS: 0 Metric: 5 Forward Address: 4.0.0.1 !--- Forwarding address is incorrectly specified !--- as an interface on the ASBR.

L'ABR convertit le type 7 LSAs en type 5 LSAs, et propage le type 5 LSAs dans des zones normales.

```
r2.2.2.2#show ip ospf database external 9.0.0.0
```

```
OSPF Router with ID (2.2.2.2) (Process ID 2)
```

Type-5 AS External Link States

```
LS age: 1782
Options: (No TOS-capability, DC)
LS Type: AS External Link
Link State ID: 9.0.0.0 (External Network Number )
!--- Router 2.2.2.2 advertises 9.0.0.0/8. Advertising Router: 2.2.2.2 !--- When the conversion
is complete, the advertising !--- router ID becomes the ABR router ID !--- because the ABR
originates this type 5 LSA. LS Seq Number: 80000004 Checksum: 0x50C6 Length: 36 Network Mask: /8
Metric Type: 1 (Comparable directly to link state metric) TOS: 0 Metric: 5 Forward Address:
4.0.0.1 External Route Tag: 0 r2.2.2.2#show ip ospf database router 1.1.1.1
```

```
OSPF Router with ID (2.2.2.2) (Process ID 2)
```

```
Router Link States (Area 1)
```

```
Routing Bit Set on this LSA
LS age: 426
Options: (No TOS-capability, DC)
LS Type: Router Links
Link State ID: 1.1.1.1
!--- For router links, Link State ID is always the same !--- as the advertising router (next
line). Advertising Router: 1.1.1.1 LS Seq Number: 8000000C Checksum: 0xAFA8 Length: 60 AS
Boundary Router !--- Bit E in the router LSA indicates that this router !--- originates from
external LSAs. Number of Links: 3 !--- There are three links in area 1. Link connected to: a
Stub Network !--- This represents the Ethernet segment 4.0.0.0/8. (Link ID) Network/subnet
number: 4.0.0.0 (Link Data) Network Mask: 255.0.0.0 Number of TOS metrics: 0 TOS 0 Metrics: 10
!--- The OSPF cost of the Ethernet segment. Link connected to: another Router (point-to-point)
!--- Shows that Router 1.1.1.1 is a neighbor with !--- Router 2.2.2.2. (Link ID) Neighboring
Router ID: 2.2.2.2 (Link Data) Router Interface address: 5.0.0.1 !--- The interface address that
connects to Router !--- 2.2.2.2 is 5.0.0.1. Number of TOS metrics: 0 TOS 0 Metrics: 64 !--- The
OSPF cost of the link that connects !--- the two routers. Link connected to: a Stub Network !---
This represents the serial link 5.0.0.0/8. (Link ID) Network/subnet number: 5.0.0.0 (Link Data)
Network Mask: 255.0.0.0 Number of TOS metrics: 0 TOS 0 Metrics: 64 !--- The OSPF cost of the
serial link.
```

Vous pouvez voir de la sortie **grasse** ici que bien que le routeur 2.2.2.2 n'en fasse pas **redistribuer des déclarations** dans sa configuration, c'est toujours un ASBR parce qu'il convertit le type 7 LSAs en type 5 LSAs.

```
r2.2.2.2#show ip ospf database router 2.2.2.2
```

```
OSPF Router with ID (2.2.2.2) (Process ID 2)
```

```
Router Link States (Area 0)
```

```
LS age: 1361
Options: (No TOS-capability, DC)
LS Type: Router Links
Link State ID: 2.2.2.2
Advertising Router: 2.2.2.2
LS Seq Number: 8000001D
Checksum: 0xD9FF
Length: 48
Area Border Router
!--- Bit B is set in the router LSA to indicate !--- that this router is an ABR. AS Boundary
Router
!--- Bit E in the router LSA indicates that this router !--- originates from external LSAs.
Number of Links: 2 !--- There are two links in area 0. Link connected to: another Router (point-
to-point) (Link ID) Neighboring Router ID: 3.3.3.3 (Link Data) Router Interface address: 6.0.0.2
Number of TOS metrics: 0 TOS 0 Metrics: 1 Link connected to: a Stub Network (Link ID)
Network/subnet number: 6.0.0.0 (Link Data) Network Mask: 255.0.0.0 Number of TOS metrics: 0 TOS
0 Metrics: 1 Router Link States (Area 1) LS age: 346 Options: (No TOS-capability, DC) LS Type:
Router Links Link State ID: 2.2.2.2 Advertising Router: 2.2.2.2 LS Seq Number: 8000002F
Checksum: 0xD478 Length: 48 Area Border Router AS Boundary Router Number of Links: 2 Link
```

connected to: another Router (point-to-point) (Link ID) Neighboring Router ID: 1.1.1.1 (Link Data) Router Interface address: 5.0.0.2 Number of TOS metrics: 0 TOS 0 Metrics: 64 Link connected to: a Stub Network (Link ID) Network/subnet number: 5.0.0.0 (Link Data) Network Mask: 255.0.0.0 Number of TOS metrics: 0 TOS 0 Metrics: 64 r2.2.2.2#**show ip ospf database router 3.3.3.3**

OSPF Router with ID (2.2.2.2) (Process ID 2)

Router Link States (Area 0)

LS age: 1245
Options: (No TOS-capability, DC)
LS Type: Router Links
Link State ID: 3.3.3.3
Advertising Router: 3.3.3.3
LS Seq Number: 8000000B
Checksum: 0x9455
Length: 48
Number of Links: 2

Link connected to: another Router (point-to-point)
(Link ID) Neighboring Router ID: 2.2.2.2
(Link Data) Router Interface address: 6.0.0.3
Number of TOS metrics: 0
TOS 0 Metrics: 1

Link connected to: a Stub Network
(Link ID) Network/subnet number: 6.0.0.0
(Link Data) Network Mask: 255.0.0.0
Number of TOS metrics: 0
TOS 0 Metrics: 1

Pour annoncer des artères d'une zone dans des autres, l'ABR crée des LSA récapitulatifs (type 3).

r2.2.2.2#**show ip ospf database summary 4.0.0.0**

OSPF Router with ID (2.2.2.2) (Process ID 2)

Summary Net Link States (Area 0)

LS age: 172
Options: (No TOS-capability, DC)
LS Type: Summary Links(Network)
Link State ID: 4.0.0.0 (summary Network Number)
!--- The ABR (Router 2.2.2.2) advertises !--- 4.0.0.0/8 into area 0. Advertising Router: 2.2.2.2 LS Seq Number: 80000003 Checksum: 0xFBE8 Length: 28 Network Mask: /8 TOS: 0 Metric: 74
r2.2.2.2#**show ip ospf database summary 5.0.0.0**

OSPF Router with ID (2.2.2.2) (Process ID 2)

Summary Net Link States (Area 0)

LS age: 1687
Options: (No TOS-capability, DC)
LS Type: Summary Links(Network)
Link State ID: 5.0.0.0 (summary Network Number)
!--- The ABR (Router 2.2.2.2) advertises !--- 5.0.0.0/8 into area 0. Advertising Router: 2.2.2.2 LS Seq Number: 80000004 Checksum: 0x8864 Length: 28 Network Mask: /8 TOS: 0 Metric: 64
r2.2.2.2#**show ip ospf database summary 6.0.0.0**

OSPF Router with ID (2.2.2.2) (Process ID 2)

Summary Net Link States (Area 1)

```
LS age: 1697
Options: (No TOS-capability, DC)
LS Type: Summary Links(Network)
Link State ID: 6.0.0.0 (summary Network Number)
!--- The ABR (Router 2.2.2.2) advertises !--- 6.0.0.0/8 into area 1. Advertising Router:
2.2.2.2 LS Seq Number: 8000001C Checksum: 0x7894 Length: 28 Network Mask: /8 TOS: 0 Metric: 1
```

Les LSA récapitulatifs ASBR ne sont pas nécessaires dans ce cas parce que l'ABR lance le LSA externe, et l'ABR est accessible dans la zone 0. comparent cet exemple à un scénario où le NSSA était une zone normale en regardant l'exemple de base de données [comment l'OSPF propage les artères externes dans de plusieurs zones](#).

Cette sortie de table de routage affiche les différents types d'artères OSPF que 9.0.0.0 est connu en tant que par chaque routeur.

```
r1.1.1.1#show ip route 9.0.0.0
Routing entry for 9.0.0.0/8
  Known via "static", distance 1, metric 0
  Redistributing via ospf 4
  Advertised by ospf 4 metric 5 metric-type 1
  Routing Descriptor Blocks:
  * 4.0.0.2
    Route metric is 0, traffic share count is 1

r2.2.2.2#show ip route ospf
O   4.0.0.0/8 [110/74] via 5.0.0.1, 01:10:13, Serial0/1/0
O N1 9.0.0.0/8 [110/79] via 5.0.0.1, 01:07:20, Serial0/1/0

R3.3.3.3#show ip route ospf
O IA 4.0.0.0/8 [110/75] via 6.0.0.2, 02:11:14, ATM2/0.20
O IA 5.0.0.0/8 [110/65] via 6.0.0.2, 03:10:41, ATM2/0.20
O E1 9.0.0.0/8 [110/80] via 6.0.0.2, 02:08:11, ATM2/0.20
```

[Dépannez](#)

Il n'existe actuellement aucune information de dépannage spécifique pour cette configuration.

[Informations connexes](#)

- [Comment OSPF propage des routes externes dans plusieurs zones](#)
- [Guide d'explication de la base de données OSPF](#)
- [Support technique OSPF](#)
- [Page de support pour le routage IP](#)
- [Support et documentation techniques - Cisco Systems](#)