

# Configuration de MPLS VPN sur ATM avec les routeurs Cisco 7500 et les commutateurs LightStream 1010

## Contenu

[Introduction](#)

[Conditions préalables](#)

[Conditions requises](#)

[Conventions](#)

[Configurez](#)

[Diagramme du réseau](#)

[Description du réseau](#)

[Configurations](#)

[Informations connexes](#)

## [Introduction](#)

Ce document affiche comment configurer le Commutation multiprotocole par étiquette (MPLS) du réseau privé virtuel (VPN) au-dessus de l'atmosphère avec des Routeurs de Cisco 7500 comme des Routeurs de périphérie d'étiquette (LERs) et les Commutateurs de LightStream 1010 comme étiquette commutent des Routeurs (LSRs). Deux Ethernet-ont connecté des Routeurs, chacun sur un site client distant, font partie d'un VPN. Dans ce document, nous regardons les configurations de périphérique de bout en bout et les commandes show utiles.

## [Conditions préalables](#)

### [Conditions requises](#)

Aucune spécification déterminée n'est requise pour ce document.

### [Conventions](#)

Pour plus d'informations sur les conventions utilisées dans ce document, reportez-vous à [Conventions relatives aux conseils techniques Cisco](#).

## [Configurez](#)

Cette section vous fournit des informations pour configurer les fonctionnalités décrites dans ce document.

## Diagramme du réseau

Ce document utilise la configuration réseau suivante :

## Description du réseau

L'installation en cours contient ces éléments en terminologie VPN :

- Routeur de la CE = de Customer Edge
- Routeur de PE = de Provider Edge
- Routeur de P=Provider

L'installation en cours contient ces éléments en terminologie MPLS :

- LER = routeur de périphérie d'étiquette
- LSR = routeur de commutateur d'étiquette
- TDP/LDP = protocole de distribution de balise/protocole de distribution d'étiquette

## Configurations

Ce document utilise les configurations suivantes :

- PE1 et PE2 sont le LERs dans notre réseau atmosphère.
- P1 et P2 sont le LSRs.
- CE1 et CE2 sont des Routeurs de Customer Edge qui sont inconscients et n'effectuent pas le VPN ou le MPLS.
- CE1 et CE2 sont des Ethernets connectés à PE1 et à PE2 respectivement, et effectuent le Protocole RIP (Routing Information Protocol).
- PE1, PE2, P1 et P2 font le Protocole OSPF (Open Shortest Path First) et sont tous dans l'OSPF de la zone 0. sont le Protocole IGP (Interior Gateway Protocol) utilisé dans le réseau atmosphère. la Balise-commutation est utilisée sur les interfaces ATM sur chacun des quatre périphériques ATM. Le protocole de distribution de balise (Protocole TDP) assigne des balises aux artères OSPF.
- PE1 et PE2 sont des pairs du Multiprotocol Border Gateway Protocol (MP-BGP).
- Des routes RIP sont redistribuées dans MP-BGP. Artères MP-BGP redistribuées dans le RIP sur les Routeurs PE1 et PE2.
- L'installation met à jour les tables de routage distinctes de VRF dans les Routeurs PE1 et PE2.
- Le nom du VPN utilisé dans cet exemple est NOUVEAU.

### CE1

```
!  
version 12.1  
service timestamps debug datetime msec  
service timestamps log datetime msec  
  
!  
boot system flashow c4500-js-mz.121-5  
!  
  
ip subnet-zero
```

```
!  
interface Loopback0  
 ip address 10.1.1.1 255.255.255.0  
!  
interface Loopback1  
 ip address 10.2.2.2 255.255.255.0  
!  
interface Loopback2  
 ip address 10.3.3.3 255.255.255.0  
!  
interface Ethernet0  
 ip address 100.1.1.2 255.255.255.0  
 media-type 10BaseT  
!  
  
router rip  
 version 2  
 network 10.0.0.0  
 network 100.0.0.0  
 no auto-summary  
!  
ip classless  
!
```

## PE1

```
!  
version 12.1  
  
service timestamps debug uptime  
service timestamps log uptime  
!  
boot system flash slot1:rsp-jsv-mz.121-5a.bin  
!  
ip subnet-zero  
!  
ip vrf NEW  
 rd 200:1  
 route-target export 200:1  
 route-target import 200:1  
ip cef distributed  
!  
interface Loopback0  
 ip address 1.1.1.1 255.255.255.255  
!  
interface ATM2/0/0  
 mtu 1500  
 no ip address  
!  
interface ATM2/0/0.10 tag-switching  
 ip unnumbered Loopback0  
 tag-switching ip  
!  
interface Ethernet2/1/0  
 ip vrf forwarding NEW  
 ip address 100.1.1.1 255.255.255.0
```

```
!  
router ospf 100  
  no log-adjacency-changes  
  network 1.0.0.0 0.255.255.255 area 0  
  network 100.1.1.0 0.0.0.255 area 0  
!  
router rip  
  version 2  
  network 100.0.0.0  
  no auto-summary  
  !  
  address-family ipv4 vrf NEW  
  version 2  
  redistribute bgp 200 metric 0  
  network 100.0.0.0  
  no auto-summary  
  exit-address-family  
!  
router bgp 200  
  bgp log-neighbor-changes  
  neighbor 2.2.2.2 remote-as 200  
  
  neighbor 2.2.2.2 update-source Loopback0  
  no auto-summary  
  !  
  address-family ipv4 vrf NEW  
  redistribute rip  
  no auto-summary  
  no synchronization  
  exit-address-family  
  !  
  address-family vpnv4  
  neighbor 2.2.2.2 activate  
  neighbor 2.2.2.2 send-community extended  
  no auto-summary  
  exit-address-family  
!  
ip classless  
!
```

## P1

```
!  
service timestamps debug uptime  
service timestamps log uptime  
!  
ip subnet-zero  
!  
interface Loopback0  
  ip address 4.4.4.4 255.255.255.255  
  no ip directed-broadcast  
!  
interface ATM12/0/0  
  ip unnumbered Loopback0  
  no ip directed-broadcast  
  
  tag-switching ip  
!  
interface ATM12/0/1  
  ip unnumbered Loopback0
```

```
no ip directed-broadcast

tag-switching ip

!
router ospf 100
 network 4.0.0.0 0.255.255.255 area 0
!
ip classless
!
```

## P2

```
!
service timestamps debug uptime
service timestamps log uptime

!
ip subnet-zero

!
interface Loopback0
 ip address 3.3.3.3 255.255.255.255
 no ip directed-broadcast
!
interface ATM0/1/1
 ip unnumbered Loopback0
 no ip directed-broadcast

 tag-switching ip
!
interface ATM0/1/3
 ip unnumbered Loopback0
 no ip directed-broadcast

 tag-switching ip
!
router ospf 100
 network 3.0.0.0 0.255.255.255 area 0
!
ip classless
!
```

## PE2

```
!
version 12.1
service timestamps debug datetime msec
service timestamps log datetime msec

!
boot system flash0:rsp-jsv-mz.121-5a
!

ip subnet-zero

!
ip vrf NEW
 rd 200:1
 route-target export 200:1
 route-target import 200:1
ip cef distributed
```

```
!  
interface Loopback0  
 ip address 2.2.2.2 255.255.255.255  
!  
  
interface FastEthernet3/0/0  
 ip vrf forwarding NEW  
 ip address 110.1.1.1 255.255.255.0  
  
 half-duplex  
!  
  
interface ATM3/1/0.1 tag-switching  
 ip unnumbered Loopback0  
 tag-switching ip  
!  
router ospf 100  
 log-adjacency-changes  
 network 2.0.0.0 0.255.255.255 area 0  
  
!  
router rip  
 version 2  
 network 110.0.0.0  
 no auto-summary  
!  
 address-family ipv4 vrf NEW  
 version 2  
 redistribute bgp 200 metric 0  
 network 110.0.0.0  
 no auto-summary  
 exit-address-family  
!  
router bgp 200  
 bgp log-neighbor-changes  
 neighbor 1.1.1.1 remote-as 200  
  
 neighbor 1.1.1.1 update-source Loopback0  
  
 no auto-summary  
!  
 address-family ipv4 vrf NEW  
 redistribute rip  
 no auto-summary  
 no synchronization  
 exit-address-family  
!  
 address-family vpnv4  
 neighbor 1.1.1.1 activate  
 neighbor 1.1.1.1 send-community extended  
 no auto-summary  
 exit-address-family  
!  
 ip classless  
!
```

## CE2

```
!  
version 12.1  
  
service timestamps debug uptime
```

```

service timestamps log uptime
!
boot system disk0:c7100-jo3s56i-mz.121-5.T.bin
!
ip subnet-zero
!
interface Loopback0
 ip address 30.1.1.1 255.255.255.0
!
interface Loopback1
 ip address 30.2.2.2 255.255.255.0
!
interface Loopback2
 ip address 30.3.3.3 255.255.255.0
!
interface FastEthernet0/0
 ip address 110.1.1.2 255.255.255.0
!
router rip
 version 2
 network 30.0.0.0
 network 110.0.0.0
 no auto-summary
!

```

## Commandes show

Utilisez ces commandes de tester que votre réseau fonctionne correctement :

- **show ip route** - Entrées de table de Routage IP d'affichages.
- **vrf de show ip rip database** - Affiche les informations contenues dans la base de données RIP pour un VRF particulier.
- **vrf de show ip bgp vpnv4** - Les informations d'adresse des affichages VPN de la table BGP.
- **affichez le détail d'interfaces de balise-commutation** - Affiche des informations au sujet d'un ou plusieurs interfaces qui ont la fonction activée MPLS.
- **affichez les attaches de TDP de balise-commutation** - Affiche les entrées demandées de la base de données obligatoire d'étiquette atmosphère LDP.
- **affichez le vrf d'expédition-table de balise-commutation** - Vérifie la pile d'étiquette utilisée pour une artère particulière.

Le résultat présenté ci-dessous est un résultat de ces commandes entrées sur les périphériques affichés dans le schéma de réseau. Cette sortie prouve que le réseau fonctionne correctement.

## CE1

```
Cisco4500#show ip route
```

```

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route

```

Gateway of last resort is not set

```
100.0.0.0/24 is subnetted, 1 subnets
C    100.1.1.0 is directly connected, Ethernet0
110.0.0.0/24 is subnetted, 1 subnets
R    110.1.1.0 [120/1] via 100.1.1.1, 00:00:14, Ethernet0
10.0.0.0/24 is subnetted, 3 subnets
C    10.3.3.0 is directly connected, Loopback2
C    10.2.2.0 is directly connected, Loopback1
C    10.1.1.0 is directly connected, Loopback0
30.0.0.0/24 is subnetted, 3 subnets
R    30.3.3.0 [120/1] via 100.1.1.1, 00:00:14, Ethernet0
R    30.2.2.0 [120/1] via 100.1.1.1, 00:00:15, Ethernet0
R    30.1.1.0 [120/1] via 100.1.1.1, 00:00:15, Ethernet0
```

## PE1

Cisco7500a#show ip route

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP  
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area  
\* - candidate default, U - per-user static route, o - ODR  
P - periodic downloaded static route

Gateway of last resort is not set

```
1.0.0.0/32 is subnetted, 1 subnets
C    1.1.1.1 is directly connected, Loopback0
2.0.0.0/32 is subnetted, 1 subnets
O    2.2.2.2 [110/4] via 4.4.4.4, 18:17:37, ATM2/0/0.10
3.0.0.0/32 is subnetted, 1 subnets
O    3.3.3.3 [110/3] via 4.4.4.4, 18:17:37, ATM2/0/0.10
4.0.0.0/32 is subnetted, 1 subnets
O    4.4.4.4 [110/2] via 4.4.4.4, 18:17:37, ATM2/0/0.10
```

Cisco7500a#show ip route vrf NEW

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP  
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area  
\* - candidate default, U - per-user static route, o - ODR  
P - periodic downloaded static route

Gateway of last resort is not set

```
100.0.0.0/24 is subnetted, 1 subnets
C    100.1.1.0 is directly connected, Ethernet2/1/0
110.0.0.0/24 is subnetted, 1 subnets
B    110.1.1.0 [200/0] via 2.2.2.2, 00:26:11
10.0.0.0/24 is subnetted, 3 subnets
R    10.3.3.0 [120/1] via 100.1.1.2, 00:00:11, Ethernet2/1/0
R    10.2.2.0 [120/1] via 100.1.1.2, 00:00:11, Ethernet2/1/0
R    10.1.1.0 [120/1] via 100.1.1.2, 00:00:11, Ethernet2/1/0
30.0.0.0/24 is subnetted, 3 subnets
B    30.3.3.0 [200/1] via 2.2.2.2, 00:26:12
B    30.2.2.0 [200/1] via 2.2.2.2, 00:26:12
B    30.1.1.0 [200/1] via 2.2.2.2, 00:26:12
```



```

Cisco7500a#show ip rip database vrf NEW
10.0.0.0/8    auto-summary
10.1.1.0/24
    [1] via 100.1.1.2, 00:00:18, Ethernet2/1/0
10.2.2.0/24
    [1] via 100.1.1.2, 00:00:18, Ethernet2/1/0
10.3.3.0/24
    [1] via 100.1.1.2, 00:00:18, Ethernet2/1/0
30.0.0.0/8    auto-summary
30.1.1.0/24    redistributed
    [1] via 2.2.2.2,
30.2.2.0/24    redistributed
    [1] via 2.2.2.2,
30.3.3.0/24    redistributed
    [1] via 2.2.2.2,
100.0.0.0/8    auto-summary
100.1.1.0/24    directly connected, Ethernet2/1/0
110.0.0.0/8    auto-summary
110.1.1.0/24    redistributed
    [1] via 2.2.2.2,

```

```

Cisco7500a#show ip bgp vpnv4 vrf NEW

```

```

BGP table version is 17, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal
Origin codes: i - IGP, e - EGP, ? - incomplete

```

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 200:1 (default for vrf NEW)					
*> 10.1.1.0/24	100.1.1.2	1		32768	?
*> 10.2.2.0/24	100.1.1.2	1		32768	?
*> 10.3.3.0/24	100.1.1.2	1		32768	?
*>i30.1.1.0/24	2.2.2.2	1	100	0	?
*>i30.2.2.0/24	2.2.2.2	1	100	0	?
*>i30.3.3.0/24	2.2.2.2	1	100	0	?
*> 100.1.1.0/24	0.0.0.0	0		32768	?
*>i110.1.1.0/24	2.2.2.2	0	100	0	?

```

Cisco7500a#show tag-switching interfaces

```

Interface	IP	Tunnel	Operational
ATM2/0/0.10	Yes	No	Yes (ATM tagging)

```

Cisco7500a#show tag-switching interfaces detail

```

```

Interface ATM2/0/0.10:
  IP tagging enabled
  TSP Tunnel tagging not enabled
  Tagging operational
  Tagswitching turbo vector
  MTU = 4470
  ATM tagging:
    Tag VPI = 1
    Tag VCI range = 33 - 65535
    Control VC = 0/32

```

```

Cisco7500a#show tag-switching ?

```

```

 atm-tdp      ATM Tagging Protocol information
 cos-map      Show Tag CoS ATM Multi-VC CoS Map
 forwarding-table Show the Tag Forwarding Information Base (TFIB)
 interfaces   Show per-interface tag switching
 prefix-map   Show Tag CoS Prefix Map
 tdp          Tag Distribution Protocol information

```

```

Cisco7500a#show tag-switching tdp bindings

```

```

tib entry: 1.1.1.1/32, rev 2
local binding: tag: imp-null

```

```
tib entry: 2.2.2.2/32, rev 23
    local binding: tag: 27
tib entry: 3.3.3.3/32, rev 21
    local binding: tag: 26
tib entry: 4.4.4.4/32, rev 10
    local binding: tag: 28
```

#### Cisco7500a#show tag-switching atm-tdp bindings

```
Destination: 4.4.4.4/32
    Headend Router ATM2/0/0.10 (1 hop) 1/33 Active, VCD=24
Destination: 3.3.3.3/32
    Headend Router ATM2/0/0.10 (2 hops) 1/43 Active, VCD=25
Destination: 2.2.2.2/32
    Headend Router ATM2/0/0.10 (3 hops) 1/42 Active, VCD=26
Destination: 1.1.1.1/32
    Tailend Router ATM2/0/0.10 1/33 Active, VCD=24
```

#### Cisco7500a#show tag-switching forwarding-table vrf NEW

Local tag	Outgoing tag or VC	Prefix or Tunnel Id	Bytes tag switched	Outgoing interface	Next Hop
29	Aggregate	100.1.1.0/24[V]	2080		
30	Untagged	10.3.3.0/24[V]	0	Et2/1/0	100.1.1.2
31	Untagged	10.2.2.0/24[V]	0	Et2/1/0	100.1.1.2
32	Untagged	10.1.1.0/24[V]	0	Et2/1/0	100.1.1.2

## P1

#### LS1010#show ip route

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP  
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, \* - candidate default  
U - per-user static route, o - ODR  
T - traffic engineered route

Gateway of last resort is not set

```
1.0.0.0/32 is subnetted, 1 subnets
O    1.1.1.1 [110/2] via 1.1.1.1, 19:00:12, ATM12/0/0
2.0.0.0/32 is subnetted, 1 subnets
O    2.2.2.2 [110/3] via 3.3.3.3, 19:00:12, ATM12/0/1
3.0.0.0/32 is subnetted, 1 subnets
O    3.3.3.3 [110/2] via 3.3.3.3, 19:00:12, ATM12/0/1
4.0.0.0/32 is subnetted, 1 subnets
C    4.4.4.4 is directly connected, Loopback0
```

#### LS1010#show tag-switching atm-tdp bindings

```
Destination: 4.4.4.4/32
    Tailend Switch ATM12/0/0 1/33 Active -> Terminating Active
    Tailend Switch ATM12/0/1 1/34 Active -> Terminating Active
Destination: 2.2.2.2/32
    Transit ATM12/0/0 1/42 Active -> ATM12/0/1 1/35 Active
Destination: 1.1.1.1/32
    Transit ATM12/0/1 1/33 Active -> ATM12/0/0 1/33 Active
Destination: 3.3.3.3/32
    Transit ATM12/0/0 1/43 Active -> ATM12/0/1 1/34 Active
```

## P2

LS1010#show ip route

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP  
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, \* - candidate default  
U - per-user static route, o - ODR

Gateway of last resort is 10.118.1.21 to network 0.0.0.0

```
1.0.0.0/32 is subnetted, 1 subnets
O    1.1.1.1 [110/3] via 4.4.4.4, 19:46:00, ATM0/1/1
2.0.0.0/32 is subnetted, 1 subnets
O    2.2.2.2 [110/2] via 2.2.2.2, 19:46:00, ATM0/1/3
3.0.0.0/32 is subnetted, 1 subnets
C    3.3.3.3 is directly connected, Loopback0
4.0.0.0/32 is subnetted, 1 subnets
O    4.4.4.4 [110/2] via 4.4.4.4, 19:46:00, ATM0/1/1
10.0.0.0/24 is subnetted, 1 subnets
C    10.118.1.0 is directly connected, Ethernet2/0/0
S*  0.0.0.0/0 [1/0] via 10.118.1.21
```

LS1010#show tag-switching atm-tdp bindings

```
Destination: 1.1.1.1/32
  Transit ATM0/1/3 1/33 Active -> ATM0/1/1 1/33 Active
Destination: 3.3.3.3/32
  Tailend Switch ATM0/1/3 1/34 Active -> Terminating Active
  Tailend Switch ATM0/1/1 1/34 Active -> Terminating Active
Destination: 4.4.4.4/32
  Transit ATM0/1/3 1/35 Active -> ATM0/1/1 1/34 Active
Destination: 2.2.2.2/32
  Transit ATM0/1/1 1/35 Active -> ATM0/1/3 1/33 Active
```

## PE2

Cisco7500#show ip route

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP  
i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area  
\* - candidate default, U - per-user static route, o - ODR  
P - periodic downloaded static route

Gateway of last resort is not set

```
1.0.0.0/32 is subnetted, 1 subnets
O    1.1.1.1 [110/4] via 3.3.3.3, 02:58:46, ATM3/1/0.1
2.0.0.0/32 is subnetted, 1 subnets
C    2.2.2.2 is directly connected, Loopback0
3.0.0.0/32 is subnetted, 1 subnets
O    3.3.3.3 [110/2] via 3.3.3.3, 02:58:46, ATM3/1/0.1
4.0.0.0/32 is subnetted, 1 subnets
O    4.4.4.4 [110/3] via 3.3.3.3, 02:58:46, ATM3/1/0.1
```

Cisco7500#show ip route vrf NEW

Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP

i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area  
\* - candidate default, U - per-user static route, o - ODR  
P - periodic downloaded static route

Gateway of last resort is not set

```
100.0.0.0/24 is subnetted, 1 subnets
B    100.1.1.0 [200/0] via 1.1.1.1, 01:16:13
110.0.0.0/24 is subnetted, 1 subnets
C    110.1.1.0 is directly connected, FastEthernet3/0/0
10.0.0.0/24 is subnetted, 3 subnets
B    10.3.3.0 [200/1] via 1.1.1.1, 01:16:13
B    10.2.2.0 [200/1] via 1.1.1.1, 01:16:13
B    10.1.1.0 [200/1] via 1.1.1.1, 01:16:13
30.0.0.0/24 is subnetted, 3 subnets
R    30.3.3.0 [120/1] via 110.1.1.2, 00:00:16, FastEthernet3/0/0
R    30.2.2.0 [120/1] via 110.1.1.2, 00:00:17, FastEthernet3/0/0
R    30.1.1.0 [120/1] via 110.1.1.2, 00:00:17, FastEthernet3/0/0
```

Cisco7500#show ip rip database vrf NEW

```
10.0.0.0/8    auto-summary
10.1.1.0/24   redistributed
              [1] via 1.1.1.1,
10.2.2.0/24   redistributed
              [1] via 1.1.1.1,
10.3.3.0/24   redistributed
              [1] via 1.1.1.1,
30.0.0.0/8    auto-summary
30.1.1.0/24
              [1] via 110.1.1.2, 00:00:09, FastEthernet3/0/0
30.2.2.0/24
              [1] via 110.1.1.2, 00:00:09, FastEthernet3/0/0
30.3.3.0/24
              [1] via 110.1.1.2, 00:00:09, FastEthernet3/0/0
100.0.0.0/8   auto-summary
100.1.1.0/24  redistributed
              [1] via 1.1.1.1,
110.0.0.0/8   auto-summary
110.1.1.0/24  directly connected, FastEthernet3/0/0
```

Cisco7500#show ip bgp vpnv4 vrf NEW

BGP table version is 17, local router ID is 2.2.2.2  
Status codes: s suppressed, d damped, h history, \* valid, > best, i - internal  
Origin codes: i - IGP, e - EGP, ? - incomplete

Network	Next Hop	Metric	LocPrf	Weight	Path
Route Distinguisher: 200:1 (default for vrf NEW)					
*>i10.1.1.0/24	1.1.1.1	1	100	0	?
*>i10.2.2.0/24	1.1.1.1	1	100	0	?
*>i10.3.3.0/24	1.1.1.1	1	100	0	?
*> 30.1.1.0/24	110.1.1.2	1		32768	?
*> 30.2.2.0/24	110.1.1.2	1		32768	?
*> 30.3.3.0/24	110.1.1.2	1		32768	?
*>i100.1.1.0/24	1.1.1.1	0	100	0	?
*> 110.1.1.0/24	0.0.0.0	0		32768	?

Cisco7500#show tag-switching interfaces

Interface	IP	Tunnel	Operational	
ATM3/1/0.1	Yes	No	Yes	(ATM tagging)

Cisco7500#show tag-switching interfaces detail

```
Interface ATM3/1/0.1:
  IP tagging enabled
  TSP Tunnel tagging not enabled
  Tagging operational
```

```
Tagswitching turbo vector
MTU = 4470
ATM tagging:
    Tag VPI = 1
    Tag VCI range = 33 - 65535
    Control VC = 0/32
```

**Cisco7500#show tag-switching ?**

```
atm-tdp          ATM Tagging Protocol information
cos-map          Show Tag CoS ATM Multi-VC CoS Map
forwarding-table Show the Tag Forwarding Information Base (TFIB)
interfaces       Show per-interface tag switching
prefix-map       Show Tag CoS Prefix Map
tdp              Tag Distribution Protocol information
```

**Cisco7500#show tag-switching tdp bindings**

```
tib entry: 1.1.1.1/32, rev 25
    local binding: tag: 26
tib entry: 2.2.2.2/32, rev 2
    local binding: tag: imp-null
tib entry: 3.3.3.3/32, rev 27
    local binding: tag: 27
tib entry: 4.4.4.4/32, rev 29
    local binding: tag: 28
```

**Cisco7500#show tag-switching atm-tdp bindings**

```
Destination: 1.1.1.1/32
    Headend Router ATM3/1/0.1 (3 hops) 1/33 Active, VCD=8
Destination: 3.3.3.3/32
    Headend Router ATM3/1/0.1 (1 hop) 1/34 Active, VCD=6
Destination: 4.4.4.4/32
    Headend Router ATM3/1/0.1 (2 hops) 1/35 Active, VCD=7
Destination: 2.2.2.2/32
    Tailend Router ATM3/1/0.1 1/33 Active, VCD=8
```

**Cisco7500#show tag-switching forwarding-table vrf NEW**

Local tag	Outgoing tag or VC	Prefix or Tunnel Id	Bytes tag switched	Outgoing interface	Next Hop
33	Aggregate	110.1.1.0/24[V]	0		
34	Untagged	30.3.3.0/24[V]	0	Fa3/0/0	110.1.1.2
35	Untagged	30.2.2.0/24[V]	0	Fa3/0/0	110.1.1.2
36	Untagged	30.1.1.0/24[V]	0	Fa3/0/0	110.1.1.2

## CE2

**Cisco7100#show ip route**

```
Codes: C - connected, S - static, I - IGRP, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, E - EGP
       i - IS-IS, L1 - IS-IS level-1, L2 - IS-IS level-2, ia - IS-IS inter area
       * - candidate default, U - per-user static route, o - ODR
       P - periodic downloaded static route
```

Gateway of last resort is not set

```
100.0.0.0/24 is subnetted, 1 subnets
R    100.1.1.0 [120/1] via 110.1.1.1, 00:00:19, FastEthernet0/0
110.0.0.0/24 is subnetted, 1 subnets
C    110.1.1.0 is directly connected, FastEthernet0/0
10.0.0.0/24 is subnetted, 3 subnets
```

```
R      10.3.3.0 [120/1] via 110.1.1.1, 00:00:19, FastEthernet0/0
R      10.2.2.0 [120/1] via 110.1.1.1, 00:00:19, FastEthernet0/0
R      10.1.1.0 [120/1] via 110.1.1.1, 00:00:19, FastEthernet0/0
      30.0.0.0/24 is subnetted, 3 subnets
C      30.3.3.0 is directly connected, Loopback2
C      30.2.2.0 is directly connected, Loopback1
C      30.1.1.0 is directly connected, Loopback0
```

## [Informations connexes](#)

- [Réseaux privés virtuels MPLS](#)
- [Configuration d'un VPN MPLS de base](#)
- [Flux de paquets dans un environnement MPLS VPN](#)
- [Support et documentation techniques - Cisco Systems](#)