

Fichiers et dossiers clients d'itinérance Umbrella

Table des matières

[Introduction](#)

[Fenêtres](#)

[OS X](#)

Introduction

Ce document décrit l'objectif de chaque fichier et dossier installé par le client d'itinérance Umbrella pour Windows et Mac OS X. Ces informations peuvent être utilisées pour améliorer vos connaissances de travail sur le client d'itinérance Umbrella ou pour vous aider à résoudre les problèmes d'installations défectueuses.

Fenêtres

<#root>

Service Name: "Umbrella_RC"

C: \ProgramData\OpenDNS\ERC\

beacon-logs

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

Upgrades

Folder containing temp files when automatically updating to the latest version.

Config.json

Contains the unique "Device" and "Origin" ID's specific to this Umbrella roaming client. This file

OpenDNS_ERC_Service.log

Live log of the Umbrella roaming client's running process. Used for Umbrella troubleshooting.

OpenDNS_ERC_UI.log

Live log of the Umbrella roaming client's tray icon process. Used for Umbrella troubleshooting.

OrgInfo.json

Contains information about the install-time parameters specified during installations, and also co

PersistedNicDefaults.json

A file for storing the DNS settings assigned to a computer before the Umbrella roaming client initialization. We keep the information in this file in order to gracefully restore the network-defined DNS servers.

proxy_whitelist.txt

The "Internal Domains" list downloaded from the dashboard, as well as DNS Suffixes imported from the local DNS servers. Read more at [Roaming Client: Internal Domains](#).

***Network Connection Name*-resolv.conf**

Each active Network Interface on the computer will have its own .conf file, (ie: Local Area Connection). These files contain the local DNS servers that belong to which networking interface. These files contain the local DNS servers.

RoamingProfile.json

A file to be used as part of a future feature.

sync-latest.json

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umbrella roaming client synchronization.

whitelist.txt

The "Internal Domains" list downloaded from the Umbrella dashboard which is used by the Umbrella roaming client. It is a temporary file, which is used as a temporary file. Read more at [Roaming Client: Internal Domains](#).

C:\Program Files (x86)\OpenDNS\Umbrella Roaming Client

dnscryptproxy.exe

In Umbrella Roaming client 3.0 and above, this is the executable used for encrypting, authenticating, and managing DNS traffic.

dnscrypt-proxy.exe (deprecated in 2.3)

Used in Umbrella Roaming client versions before 2.3. It has been superseded by dnscryptproxy.exe.

ERCInterface.exe

The executable used for running the tray icon.

UmbrellaDiagnostic.exe

The built-in diagnostic tool which customers or Support can run for troubleshooting purposes.

***.dll**

Dynamic Load Libraries associated with running different facets of the Umbrella roaming client.

ERCInterface.exe.config

.NET framework configuration file for the ERCInterface.exe executable.

ERCSERVICE.exe.config

.NET framework configuration file for the ERCSERVICE.exe executable.

Logging.config

Configuration file used for instructing the Umbrella roaming client what to log or not log. Controls

UmbrellaDiagnostic.exe.config

.NET framework configuration file for the UmbrellaDiagnostic.exe executable.

GetNetStats.bat

A facilitating script to assist with getting information as part of the Umbrella Diagnostic tool.

OS X

<#root>

/Library/Application Support/OpenDNS Roaming Client

beacon-logs/

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

Updater.plist

Local configuration data unique to the local installation of the Umbrella roaming client.

com.opendns.osx.DNSCryptProxy.plist

The configuration file used to set runtime parameters for the dns-updater executable.

dns-updater

The executable used for encrypting, authenticating, and sending DNS queries. This executable is re

localdomains

The list of domain names that the Umbrella roaming client treats as local resources and queries the

p12.hash

Hash file to verify integrity of clientCert.p12 file.

sync-latest.plist

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umb

erc_state.plist

Data that is synced with our API to populate the Umbrella dashboard with information about the Umb

resolv_orig.conf

We use this list to keep an ordered list of DNS servers used for Internal DNS resolution. The list
VPN DNS servers first. These are the DNS servers normally found on the NIC settings which are [hid](#)

/Library/LaunchDaemons/

com.opendns.osx.RoamingClientConfigUpdater.plist

The configuration file for running the Umbrella roaming client.

/Library/LaunchAgents/

com.opendns.osx.RoamingClientMenubar.plist

The configuration file for running the menu bar icon of the Umbrella roaming client.

À propos de cette traduction

Cisco a traduit ce document en traduction automatisée vérifiée par une personne dans le cadre d'un service mondial permettant à nos utilisateurs d'obtenir le contenu d'assistance dans leur propre langue.

Il convient cependant de noter que même la meilleure traduction automatisée ne sera pas aussi précise que celle fournie par un traducteur professionnel.