L'accesso all'interfaccia utente SplunkWeb non riesce con una condizione 'imprevista'

Applicabilità

Splunk Enterprise

Descrizione

L'accesso all'interfaccia utente SplunkWeb non riesce con il messaggio seguente

```
"The server encountered an unexpected condition which prevented it from fulfilling the
request. Click here to return to Splunk homepage"
```

Indagine

L'errore seguente viene segnalato in $SPLUNK_HOME/var/log/splunk/web_service.log

```
2019-09-10 07:25:58,388 INFO [5d7741f661397e0ba470] error:323 - HEAD /favicon.ico 127.0.
8065
2019-09-10 07:25:58,390 INFO [5d7741f661397e0ba470] error:324 - 500 Internal Server Erro
The server encountered an unexpected condition which prevented it from fulfilling the re
2019-09-10 07:25:58,390 ERROR [5d7741f661397e0ba470] error:325 - Traceback (most recent
File "S:\Program Files\Splunk\Python-2.7\Lib\site-packages\cherrypy\_cprequest.py", line
self.hooks.run('before_request_body')
File "S:\Program Files\Splunk\Python-2.7\Lib\site-packages\cherrypy\_cprequest.py", line
hook()
File "S:\Program Files\Splunk\Python-2.7\Lib\site-packages\cherrypy\_cprequest.py", line
return self.callback(**self.kwargs)
File "S:\Program Files\Splunk\Python-2.7\Lib\site-packages\cherrypy\lib\sessions.py", li
timeout=timeout, domain=domain, secure=secure, httponly=httponly)
File "S:\Program Files\Splunk\Python-2.7\Lib\site-packages\cherrypy\lib\sessions.py", li
cookie[name]['expires'] = http.HTTPDate(time.time() + timeout)
TypeError: unsupported operand type(s) for +: 'float' and 'str'
```

Verificare se una stringa è stata impostata come valore di timeout in web.conf
<#root>

```
```

$SPLUNK_HOME/bin/splunk btool web list settings

```
[settings]
busyKeepAliveIdleTimeout = 12
keepAliveIdleTimeout = 7200
response.timeout = 7200
splunkdConnectionTimeout = 30
tools.sessions.timeout = 60
ui_inactivity_timeout = 60
```

Queste sono le impostazioni predefinite, anche se se se sono state modificate in una stringa (ad esempio, tools.sessions.timeout = 1h), vengono ripristinate le impostazioni predefinite e viene verificato se il problema persiste.

Risoluzione

Se tutti i valori di timeout sono validi, è possibile modificare le sessioni.py per impostare in modo esplicito max-age.

<#root>

$SPLUNK_HOME/lib/python2.7/site-packages/cherrypy/lib/sessions.py

Modificare quanto segue:

```
# We'd like to use the "max-age" param as indicated in
    # http://www.faqs.org/rfcs/rfc2109.html but IE doesn't
    # save it to disk and the session is lost if people close
    # the browser. So we have to use the old "expires" ... sigh ...
##    cookie[name]['max-age'] = timeout * 60
    if timeout:
        #cookie[name]['expires'] = http.HTTPDate(time.time() + (timeout * 60))
        # Replace Cherrypy's version of this so that cookies alwasy last for
        # 24 hours by default - Setting them to 1 hour causes problems for IE
        # users who's clocks are off from the server
        timeout = timeout * 60 # convert to seconds
        if timeout < 86400:
            timeout = 86400 # Cookies last at least 24 hours
        try:
                cookie[name]['expires'] = http.HTTPDate(time.time() + timeout)
        except TypeError:
                raise AssertionError("HTTPDate error, timeout=%s not set." % timeout)
```

A questo:

```
# http://www.faqs.org/rfcs/rfc2109.html but IE doesn't
# save it to disk and the session is lost if people close
# the browser. So we have to use the old "expires" ... sigh ...
## cookie[name]['max-age'] = timeout * 60
cookie[name]['max-age'] = 86400
###   if timeout:
        #cookie[name]['expires'] = http.HTTPDate(time.time() + (timeout * 60))
        # Replace Cherrypy's version of this so that cookies alwasy last for
        # 24 hours by default - Setting them to 1 hour causes problems for IE
        # users who's clocks are off from the server
###       timeout = timeout * 60 # convert to seconds
###       if timeout < 86400:
###           timeout = 86400 # Cookies last at least 24 hours
###       cookie[name]['expires'] = http.HTTPDate(time.time() + timeout)
```

Quindi riavviare Splunk

Informazioni su questa traduzione

Cisco ha tradotto questo documento utilizzando una combinazione di tecnologie automatiche e umane per offrire ai nostri utenti in tutto il mondo contenuti di supporto nella propria lingua. Si noti che anche la migliore traduzione automatica non sarà mai accurata come quella fornita da un traduttore professionista. Cisco Systems, Inc. non si assume alcuna responsabilità per l’accuratezza di queste traduzioni e consiglia di consultare sempre il documento originale in inglese (disponibile al link fornito).