

Cloudcenter Manager-4.8.2 サービスおよび変更されたファイルロケーションの FAQ

目次

[はじめに](#)

[管理サーバがきちんと動作するかどうか確認する方法か。](#)

[管理サーバを再起動する方法か。](#)

[hazelcast サーバを再起動する方法か。](#)

[CCM のコンフィギュレーション サーバを再起動する方法か。](#)

[CCM の通知 サーバを再起動する方法か。](#)

[CCM の cliqr Admin サービスを再開する方法か。](#)

[CloudCenter ログファイルはどこに取付けられますか。](#)

[CCM CloudCenter Configuration ウィザード Locationはどこにありますか。](#)

[CCM コンフィギュレーションはどこから構成ウィザードが実行された後保存されますか。](#)

[オオシカ logstash 設定はどこから CCM で保存されますか。](#)

概要

この資料はファイルの位置を記述したものです変更された。

管理サーバがきちんと動作するかどうか確認する方法か。

1. SSH の CloudCenter マネージャへのログイン。
2. 管理サーバがコマンドを使用して動作するかどうか確認して下さい。

```
[root@ip-172-31-78-238 sysconfig]# systemctl status mgmtserver.service
mgmtserver.service - Management Server
   Loaded: loaded (/etc/systemd/system/mgmtserver.service; enabled; vendor preset: disabled)
   Active: inactive (dead) since Fri 2017-11-10 16:55:31 UTC; 15s ago
   Process: 2732 ExecStart=/bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/mgmtserver.war
(code=killed, signal=TERM)
   Main PID: 2732 (code=killed, signal=TERM)
```

```
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: / ____| |          | ||
____|   |   |   |   | \ / |
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | |   | | ____ _ _ _ | |   ___ _
_ | | _ _ _ _ _ | \ / | _ _ _ _ _ _ _ _ _
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | |   | |/_ _ \| | | |/_ _ ` | |   / _ \
'_ \ | _/ _ \ ' _ \| | \| |/_ _ ` |'_ \ / _ ` |/_ _ \|/_ _ \|
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: | |____| | ( ) | | | ( | | ____| _/
| | | | | _/ | | | | | | ( | | | | | | _/ |
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: \____|_| \_/ \__,_| \__,_| \____\____|_|
|_| \__ \____|_|   | | | \__,_| | | \__,_| \__,_| \____|_|
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: _/ |
```

```
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: |___/
Nov 10 16:54:48 ip-172-31-78-238.ec2.internal sh[2732]: packager : (v4.8.2-SNAPSHOT), Powered by
Spring Boot : 1.5.8.RELEASE
Nov 10 16:55:31 ip-172-31-78-238.ec2.internal systemd[1]: Stopping Management Server...
Nov 10 16:55:31 ip-172-31-78-238.ec2.internal systemd[1]: Stopped Management Server.
[root@ip-172-31-78-238 sysconfig]#
```

管理サーバを再起動する方法か。

サービス全員は systemctl にそれ故に管理サーバを再起動するために systemctl コマンドを実行する必要変更しました。

```
[root@ip-172-31-78-238 sysconfig]# systemctl restart mgmtserver.service
[root@ip-172-31-78-238 sysconfig]#
```

```
-----

[root@ip-172-31-78-238 sysconfig]# systemctl status mgmtserver
mgmtserver.service - Management Server
   Loaded: loaded (/etc/systemd/system/mgmtserver.service; enabled; vendor preset: disabled)
   Active: active (running) since Fri 2017-11-10 15:19:20 UTC; 1h 27min ago
   Main PID: 601 (sh)
   CGroup: /system.slice/mgmtserver.service
           601 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/mgmtserver.war
           611 /bin/bash /usr/local/cliqr/apps/mgmtserver.war
           667 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true -
Xms2048m -Xmx4096m -Djava.security.egd=file:/dev/./urandom -jar
/usr/local/cliqr/apps/mgmtserver.war
```

```
Nov 10 15:19:20 ip-172-31-78-238.ec2.internal sh[601]: logger: Executing configuration set by
user
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: _____
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: / ____| | | |
____| | | | | \ / |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | | | _ _ _ _ _ | | | _ _ _
_ | | _ _ _ _ | \ / | _ _ _ _ _ _ _ _ _ _
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | | | / _ \| | | | / _ \| | | | / _ \|
'_ \| / _ \| | | | | \| | / _ \| ' _ \| / _ \| / _ \|
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: | | | | ( ) | | | | ( ) | | | | _/ |
| | | | _/ | | | | ( ) | | | | ( ) | | | | _/ |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: \____|_| \__ / \__,_| \__,_| \____\____|_|
|_| \__ \__|_| |_| |_| \__,_| |_| \__,_| \__,_| \__ \__|_|
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: __/ |
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: |___/
Nov 10 15:19:53 ip-172-31-78-238.ec2.internal sh[601]: packager : (v4.8.2-SNAPSHOT), Powered by
Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#
```

hazelcast サーバを再起動する方法か。

```
[root@ip-172-31-78-238 sysconfig]# systemctl restart hazelcast-server
[root@ip-172-31-78-238 sysconfig]#
[root@ip-172-31-78-238 sysconfig]# systemctl status hazelcast-server
hazelcast-server.service - Hazelcast Server
   Loaded: loaded (/etc/systemd/system/hazelcast-server.service; enabled; vendor preset:
disabled)
   Active: active (running) since Fri 2017-11-10 16:54:37 UTC; 14s ago
   Main PID: 2731 (sh)
```

```
CGroup: /system.slice/hazelcast-server.service
2731 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/hazelcast-server.jar
2735 /bin/bash /usr/local/cliqr/apps/hazelcast-server.jar
2760 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/hazelcast-
server.jar
```

```
Nov 10 16:54:37 ip-172-31-78-238.ec2.internal systemd[1]: Started Hazelcast Server.
Nov 10 16:54:37 ip-172-31-78-238.ec2.internal systemd[1]: Starting Hazelcast Server...
Nov 10 16:54:39 ip-172-31-78-238.ec2.internal sh[2731]: 16:54:39.116 [main] INFO
com.cisco.cloudcenter.hazelcast.HazelcastServer - Starting Hazelcast Server..
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: _ _ _
_ _ _
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | | | | | | |
| / | | | | | | | | | |
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | | | | | | |
| | | | | | | | | | | |
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | _ _ | / _ ` | _ / _ \ | / _ / _ ` / _ |
_ | \ _ \ / _ \ ' _ \ \ / / | / _ / _ \
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | | | | ( _ | / / _ / | ( _ | ( _ | \ _ \
| _ _ _ ) | _ / | \ v / | | ( _ | _ /
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: | _ |
| _ | \ _ , / _ \ _ | _ | \ _ \ _ , | _ _ / \ _ | | _ _ / \ _ | _ | \ _ \ _ \
Nov 10 16:54:43 ip-172-31-78-238.ec2.internal sh[2731]: CliQr Hazelcast Server : (v4.8.2-
SNAPSHOT), Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep hazelcast
cliqrus+ 2731 1 0 16:54 ? 00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/hazelcast-server.jar
cliqrus+ 2735 2731 0 16:54 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/hazelcast-
server.jar
cliqrus+ 2760 2735 6 16:54 ? 00:00:14 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/hazelcast-server.jar
root 3024 1854 0 16:58 pts/0 00:00:00 grep --color=auto hazelcast
[root@ip-172-31-78-238 sysconfig]#
```

CCM のコンフィギュレーション サーバを再起動する方法か。

```
[root@ip-172-31-78-238 sysconfig]# systemctl restart config-server
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep config-server
cliqrus+ 3096 1 0 17:00 ? 00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/config-server.jar
cliqrus+ 3100 3096 0 17:00 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/config-
server.jar
cliqrus+ 3177 3100 48 17:00 ? 00:00:16 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xmx256m -jar /usr/local/cliqr/apps/config-
server.jar
root 3300 1854 0 17:00 pts/0 00:00:00 grep --color=auto config-server
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
[root@ip-172-31-78-238 sysconfig]# systemctl status config-server
config-server.service - Config Server
Loaded: loaded (/etc/systemd/system/config-server.service; enabled; vendor preset: disabled)
```

```

Active: active (running) since Fri 2017-11-10 17:00:14 UTC; 1min 12s ago
Main PID: 3096 (sh)
CGroup: /system.slice/config-server.service
        3096 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/config-server.jar
        3100 /bin/bash /usr/local/cliqr/apps/config-server.jar
        3177 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xmx256m -jar /usr/local/cliqr/apps/config-server.jar

Nov 10 17:00:14 ip-172-31-78-238.ec2.internal systemd[1]: Starting Config Server...
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: _____
_
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: / ____|          /
_(_)          | | (_)          / ____|
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |      ___ _ _ | | _ _ _ _ _
_ _ _ | | _ _ _ _ _ | (___ _ _ _ _
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |    / _ \ | ' _ \ | / _ ` | | | |
' _/ _ ` | _ | | / _ \ | ' _ \   \___ \ / _ \ ' _ \ \ / / _ \ ' _ |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: | |____| ( ) | | | | | | ( | | | | |
| ( | | | | ( ) | | | | ____ ) | _/ | \ v / _/ |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: \____\___/|_| |_| | | \__, | \__,_|_|
\__,_| \__,_|_| \___/|_| |_| |____/ \___|_|   \/ \___|_|
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: __/ |
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: |____/
Nov 10 17:00:34 ip-172-31-78-238.ec2.internal sh[3096]: CliQr Configuration Server : (v4.8.2-
SNAPSHOT) , Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

CCM の通知 サーバを再起動する方法か。

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart notification
[root@ip-172-31-78-238 sysconfig]#

-----
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep notification
cliqrus+  3572      1  0 17:02 ?          00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/notification-server.jar
cliqrus+  3574    3572  0 17:02 ?          00:00:00 /bin/bash /usr/local/cliqr/apps/notification-
server.jar
cliqrus+  3587    3574  68 17:02 ?          00:00:31 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/notification-server.jar
root      3704    1854  0 17:03 pts/0    00:00:00 grep --color=auto notification
[root@ip-172-31-78-238 sysconfig]#

-----

[root@ip-172-31-78-238 sysconfig]#
[root@ip-172-31-78-238 sysconfig]# systemctl status notification
notification.service - Notification Server
   Loaded: loaded (/etc/systemd/system/notification.service; enabled; vendor preset: disabled)
   Active: active (running) since Fri 2017-11-10 17:02:57 UTC; 1min 16s ago
   Main PID: 3572 (sh)
   CGroup: /system.slice/notification.service
           3572 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/notification-server.jar
           3574 /bin/bash /usr/local/cliqr/apps/notification-server.jar
           3587 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar
/usr/local/cliqr/apps/notification-server.jar

Nov 10 17:02:57 ip-172-31-78-238.ec2.internal systemd[1]: Started Notification Server.
Nov 10 17:02:57 ip-172-31-78-238.ec2.internal systemd[1]: Starting Notification Server...
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: _ _ _ _ _

```

```

Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | \ | | | | ( ) / _ ( ) | |
( ) / ____|
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | \ | | ____ | | _ _ | | _ _ ____ _ _ | | _
_ _ _ _ _ | ( ____ _ _ _ _ _ _ _ _ _ _
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | . ` | / _ \ | _ | | _ | / _ / _ ` | _ |
| / _ \ | ' _ \ \ _ _ \ / _ \ ' _ \ \ / / _ \ ' _ |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | | \ | ( ) | | _ | | | | ( _ | ( _ | | | _ |
| ( ) | | | | ____ ) | _ / | \ v / _ / |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: | _ | \ _ | \ _ _ / \ _ | _ | _ |
| _ | \ _ \ _ _ , _ | \ _ | _ | \ _ _ / | _ | | _ _ _ / \ _ _ | _ | \ / \ _ _ | _ |
Nov 10 17:03:04 ip-172-31-78-238.ec2.internal sh[3572]: osmosix-notification : (v4.8.2-
SNAPSHOT), Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

CCM の cliqr Admin サービスを再開する方法が。

```

[root@ip-172-31-78-238 sysconfig]# systemctl restart cliqr-admin
[root@ip-172-31-78-238 sysconfig]#

```

```

[root@ip-172-31-78-238 sysconfig]# ps -ef | grep cliqr-admin
cliqrus+ 3736 1 0 17:05 ? 00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3737 3736 0 17:05 ? 00:00:00 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3750 3737 69 17:05 ? 00:00:22 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-admin.jar
root 3779 1854 0 17:05 pts/0 00:00:00 grep --color=auto cliqr-admin
[root@ip-172-31-78-238 sysconfig]#

```

```

[root@ip-172-31-78-238 sysconfig]# systemctl status cliqr-admin
cliqr-admin.service - Cliqr Admin
Loaded: loaded (/etc/systemd/system/cliqr-admin.service; enabled; vendor preset: disabled)
Active: active (running) since Fri 2017-11-10 17:05:28 UTC; 1min 2s ago
Main PID: 3736 (sh)
CGroup: /system.slice/cliqr-admin.service
3736 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
3737 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
3750 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-
admin.jar

```

```

Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Started Cliqr Admin.
Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Starting Cliqr Admin...
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: i ____ _
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: / ____| | | |
| | | | \ | | | | ( )
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | | | | ____ _ _ _ _ | | ____ _ _
_ _ | | _ _ _ _ _ / \ _ | | _ _ _ _ _ _ _
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | | | | / _ \ | | | | / _ ` | / _ / _ \ ' _
\ | _ / _ \ ' _ | / \ \ / _ ` | ' _ ` _ \ | | ' _ \
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | ____ | | ( ) | | _ | | ( _ | ( _ _ / |
| | | | _ / | | / ____ \ ( _ | | | | | | | | | | |
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: \ _ _ _ | _ | \ _ _ / \ _ , _ | \ _ , _ | \ _ \ _ _ | _ |
| _ | \ _ \ _ _ | _ | / / \ _ \ _ , _ | _ | | _ | _ | _ |
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#

```

CloudCenter ログファイルはどこに取付けられますか。

4.8.2 バージョンの CloudCenter マネージャのためのログの場所に変更がずっとあります。現在、ログはで見つけられます

/usr/local/cliqr/logs ディレクトリ

ファイルは capacity-manager.log が、config-server.log、mgmtserver.log、notification-server.log、cliqr-admin.log、hazelcast-server.log 含まれています

```
[root@ip-172-31-78-238 sysconfig]# systemctl restart cliqr-admin
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
[root@ip-172-31-78-238 sysconfig]# ps -ef | grep cliqr-admin
cliqrus+ 3736      1  0 17:05 ?           00:00:00 /bin/sh -c .
/etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3737    3736  0 17:05 ?           00:00:00 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
cliqrus+ 3750    3737 69 17:05 ?           00:00:22 /usr/lib/jvm/java-8-sun/bin/java -
Dsun.misc.URLClassPath.disableJarChecking=true -Xms256m -Xmx256m -
Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-admin.jar
root      3779   1854  0 17:05 pts/0     00:00:00 grep --color=auto cliqr-admin
[root@ip-172-31-78-238 sysconfig]#
```

```
-----
[root@ip-172-31-78-238 sysconfig]# systemctl status cliqr-admin
cliqr-admin.service - Cliqr Admin
  Loaded: loaded (/etc/systemd/system/cliqr-admin.service; enabled; vendor preset: disabled)
  Active: active (running) since Fri 2017-11-10 17:05:28 UTC; 1min 2s ago
  Main PID: 3736 (sh)
  CGroup: /system.slice/cliqr-admin.service
          3736 /bin/sh -c . /etc/profile.d/jdk.sh;/usr/local/cliqr/apps/cliqr-admin.jar
          3737 /bin/bash /usr/local/cliqr/apps/cliqr-admin.jar
          3750 /usr/lib/jvm/java-8-sun/bin/java -Dsun.misc.URLClassPath.disableJarChecking=true
-Xms256m -Xmx256m -Djava.security.egd=file:/dev/./urandom -jar /usr/local/cliqr/apps/cliqr-admin.jar
```

```
Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Started Cliqr Admin.
Nov 10 17:05:28 ip-172-31-78-238.ec2.internal systemd[1]: Starting Cliqr Admin...
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: i      ____  _
_
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: / ____| |              | |
| |          / \          | |          ( )
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | |      | | ____ _ _ _ | | ____ _ _
_ | | _ _ _ _ _ / \ _ | | _ _ _ _ _
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | |      | / _ \| | | / _ \| / _ \| \ '
\| _/ _ \| \ ' _ | / \ \ / _ \| ' _ \| \ \| \
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: | | ____| | ( ) | | | | ( | | ( | _/ |
| | | | _/ | | / ____ \ ( | | | | | | | | |
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: \_____|_| \____/ \__,_|\_____|_| \
_| | \_____|_| / / \_____/ |_| |_| |_| |_| |_|
Nov 10 17:05:31 ip-172-31-78-238.ec2.internal sh[3736]: Powered by Spring Boot : 1.5.8.RELEASE
[root@ip-172-31-78-238 sysconfig]#
```

CCM CloudCenter Configuration ウィザード Location はどこにありますか。

すべてのコンフィギュレーション ファイルは /usr/local/cliqr/bin ディレクトリにあります

CCM コンフィギュレーションはどこから構成ウィザードが実行された後保存されますか。

すべての設定は /etc/sysconfig ディレクトリにある mgmtserver.conf ファイルで保存されます。

オオシカ logstash 設定はどこから CCM で保存されますか。

オオシカ logstash コンフィギュレーション ファイルは filebeat ファイル名を用いる /etc/sysconfig/ ディレクトリの下にあります。

Application Version: 4.8.2/4.8.2.x