

L2TP ロード バランシングとフェールオーバー

目次

[概要](#)

[前提条件](#)

[要件](#)

[使用するコンポーネント](#)

[表記法](#)

[LNS ロード バランシング](#)

[LNS フェールオーバー](#)

[LNS ロード バランシングとフェールオーバー](#)

[評価試験](#)

[/ LNS](#)

[LAC - 設定](#)

[LNS- 設定](#)

[LAC から取得されたデバッグ](#)

[/ LNS](#)

[/ LNS](#)

[関連情報](#)

概要

このドキュメントでは、複数の L2TP ネットワーク サーバ (LNS) に対するロード バランシング機能とフェールオーバー機能を実行する L2TP アクセス コンセントレータ (LAC) の機能について説明します。

前提条件

要件

このドキュメントに関する固有の要件はありません。

使用するコンポーネント

このドキュメントは、特定のソフトウェアやハードウェアのバージョンに限定されるものではありません。

表記法

ドキュメント表記の詳細は、『[シスコテクニカルティップスの表記法](#)』を参照してください。

LNS ロード バランシング

RADIUS を使用して、LAC にバーチャル プライベート ネットワーク (VPDN) のトンネル情報を提供する場合、着信番号識別サービス (DNIS) のユーザまたはドメインを複数の LNS に転送することができます。これは、負荷分散を支援し、より高レベルの冗長性を提供するために、着信トンネルとセッションが複数の LNS にわたって共有される必要がある場合の要件です。ロード バランシング機能を有効にするには、トンネル エンドポイントとして使用できる各 LNS の IP アドレスがシスコベンダー固有属性 (VSA) の属性/値ペアに提供される必要があります。

```
Cisco:Avpair = "vpdn:ip-addresses=10.51.6.82,10.51.6.59"
```

「,」は、LAC に使用できる複数のエンドポイントがあることを示すために、デリミタとして使用されます (トンネル エンドポイントの同じ優先順位を示すためのデリミタとしてスペースを使用することもできます)。LAC は、最初に提供される非アクティブ IP アドレスをランダムに選択することにより、使用するエンドポイントを選択します。ビジイーの場合 (LAC は IP アドレスに接続できません)、次の IP アドレスが選出されます。使用できる非アクティブ IP アドレスがない場合、「オープントンネル状態」の IP アドレスに基づいて次の選択が行われ、最終的に「保留中のトンネル状態」の IP アドレスが選択されます。

LNS フェールオーバー

複数の LNS を使用する場合、Cisco IOS® ソフトウェアでは、最大 6 つのプライオリティ レベルを使用できます。「/」をデリミタとして使用して、LAC にダウンロードされた LNS に異なるプライオリティ グループを割り当てることができます。これにより、特定の LNS をプライマリ LNS として、その他をバックアップとして動作させることができます。前述のとおり、トンネル エンドポイントは、Cisco VSA 属性/値ペアで提供されます。

```
Cisco:Avpair = "vpdn:ip-addresses=10.51.6.82/10.51.6.59"
```

デリミタ「/」は、10.51.6.82 がプライオリティ グループ 1 にあり、10.51.6.59 がプライオリティ グループ 2 にあることを示します。

LNS ロード バランシングとフェールオーバー

同じプロファイルに、ロード バランシングとフェールオーバーの両方を使用することができます。これは、以下に示すように、Cisco VSA 属性/値ペア "vpdn: ip-addresses" を使用することで実現します。

```
Cisco:Avpair = "vpdn:ip-addresses=
1.1.1.1,2.2.2.2/3.3.3.3,4.4.4.4/5.5.5.5,6.6.6.6"
```

これは次のように解釈されます。

- トンネル エンドポイント 1.1.1.1 と 2.2.2.2 は、プライオリティ グループ 1 にあります
- トンネルのエンドポイント 3.3.3.3 と 4.4.4.4 は、プライオリティ グループ 2 にあります
- トンネルのエンドポイント 5.5.5.5 と 6.6.6.6 は、プライオリティ グループ 3 にあります

ロード バランシング機能は、プライオリティ グループ 1 で実行されます - 非アクティブ/非ビジイー、オープン、保留中。このプライオリティ レベルで何も使用できない場合は、次のプライオリティ レベルに移動し、選択ロジックを続行します。

評価試験

このセクションのテストは、ロード バランシングとフェールオーバー機能を使用する、以下の3つの異なるシナリオを示します。

- /LNS
- /LNS
- /LNS

シスコベンダー固有属性/値ペアを使用する LNS ロード バランシング

RADIUS プロファイル

Merit RADIUS サーバ 3.6B 上の RADIUS ユーザおよびトンネルのプロファイル：

```
2500-1 Password = "cisco"
Service-Type = Framed,
Framed-Protocol = PPP,
Framed-IP-Address = 255.255.255.255

dnis:614629 Password = "cisco"
Service-Type = Outbound,
Cisco:Avpair = "vpdn:tunnel-type=l2tp",
Cisco:Avpair = "vpdn:tunnel-id=hgw",
Cisco:Avpair = "vpdn:ip-addresses=10.51.6.82,10.51.6.59",
Cisco:Avpair = "vpdn:l2tp-tunnel-password=hello"
```

LAC - 設定

```
aaa new-model
!--- Enables Authentication, Authorization and Accounting functionality. aaa group server radius
NSA_LAB server 10.51.6.3 auth-port 1645 acct-port 0 non-standard ! aaa authentication login
default local aaa authentication ppp default local group NSA_LAB aaa authentication ppp DIAL
group NSA_LAB local aaa authorization network default group NSA_LAB local aaa authorization
network DIAL group NSA_LAB local !--- Authentication and Authorization will be implemented !---
in sequence by the methods configured. vpdn enable !--- Enables the VPDN feature. no vpdn
logging vpdn search-order dnis !--- Once LCP state is open, the dialed number is checked !--- to
see if the remote is a VPDN user. interface Serial0:15 no ip address encapsulation ppp no
logging event link-status dialer rotary-group 1 dialer-group 1 autodetect encapsulation ppp v120
no snmp trap link-status isdn switch-type primary-net5 isdn incoming-voice modem compress stac !
interface Dialer1 ip unnumbered Loopback0 encapsulation ppp no ip mroute-cache dialer-group 1
autodetect encapsulation ppp v120 !--- Allows the encapsulation type to be dynamically set if
the call !--- type is not identified in the ISDN Q.931 Lower Layer Compatibility. peer default
ip address pool default compress stac ppp authentication chap pap DIAL ppp authorization DIAL !--
-- The list-name DIAL is configured, that PPP Authentication and !--- Authorization will use.
ppp chap hostname 5300-1 !--- The name 5300-1 is used for all CHAP challenge and response on !--
- this interface. ppp multilink ! radius-server host 10.51.6.3 auth-port 1645 acct-port 1646
non-standard !--- 'non-standard' indicates that the RADIUS Server will use !--- non standard
RADIUS attributes.
```

LNS- 設定

```
aaa new-model
!--- Enables Authentication, Authorization and Accounting functionality. aaa authentication
login default local aaa authentication enable default group radius enable aaa authentication ppp
default local aaa authentication ppp vpdn group radius none aaa authorization network default
local none aaa authorization network vpdn group radius local !--- Authentication and
Authorization will be implemented !--- in sequence by the methods configured. vpdn enable !---
Enables the VPDN feature. vpdn-group 1 accept-dialin protocol l2tp virtual-template 1 local name
l2tp-gw l2tp tunnel password 7 1211001B1E04 !--- The LNS will accept connections from the LAC
using L2TP !--- using All Virtual-Access Interfaces that are created will be cloned from !---
Virtual-Template 1. The name 'l2tp-gw' is used to identify the password, !--- that will
```

authenticate the tunnel, is encrypted. interface Ethernet5/0 ip address 10.51.6.59 255.255.252.0
! interface Virtual-Template1 ip unnumbered Ethernet5/0 no ip route-cache cef peer default ip
address pool default ppp authentication chap vpdn ppp authorization vpdn ! radius-server host
10.51.6.3 auth-port 1645 acct-port 1646 non-standard *!--- 'non-standard' identifies the RADIUS
Server will be !--- using nonstandard RADIUS attributes.*

LAC から取得されたデバッグ

```
Jan 1 00:32:54.847: %LINK-3-UPDOWN: Interface Serial0:0, changed state to up
Jan 1 00:32:55.027: Se0:0 PPP: Treating connection as a callin
Jan 1 00:32:55.027: Se0:0 PPP: Phase is ESTABLISHING, Passive Open
Jan 1 00:32:55.027: Se0:0 CHAP: Using alternate hostname 5300-1
Jan 1 00:32:55.027: Se0:0 LCP: State is Listen
Jan 1 00:32:55.027: Se0:0 LCP: I CONFREQ [Listen] id 112 len 10
- snip -
Jan 1 00:32:55.063: Se0:0 LCP: State is Open Jan 1 00:32:55.063: Se0:0 PPP: Phase is
AUTHENTICATING, by this end Jan 1 00:32:55.063: Se0:0 CHAP: Using alternate hostname 5300-1 Jan
1 00:32:55.063: Se0:0 CHAP: O CHALLENGE id 14 len 27 from "5300-1" Jan 1 00:32:55.083: Se0:0
CHAP: I RESPONSE id 14 len 27 from "2500-1" Jan 1 00:32:55.083: Se0:0 PPP: Phase is FORWARDING
Jan 1 00:32:55.083: Se0:0 VPDN: Got DNIS string 614629 Jan 1 00:32:55.083: Se0:0 VPDN: Looking
for tunnel -- dnis:614629 -- Jan 1 00:32:55.083: Serial0:0 AAA/AUTHOR/VPDN (480033158):
Port='Serial0:0' list='default' service=NET Jan 1 00:32:55.083: AAA/AUTHOR/VPDN: Serial0:0
(480033158) user='dnis:614629' Jan 1 00:32:55.087: Serial0:0 AAA/AUTHOR/VPDN (480033158): send
AV service=ppp Jan 1 00:32:55.087: Serial0:0 AAA/AUTHOR/VPDN (480033158): send AV protocol=vpdn
Jan 1 00:32:55.087: Serial0:0 AAA/AUTHOR/VPDN (480033158): found list "default" Jan 1
00:32:55.087: Serial0:0 AAA/AUTHOR/VPDN (480033158): Method=NSA_LAB (radius) Jan 1 00:32:55.087:
RADIUS: Initial Transmit Serial0:0 id 50 10.51.6.3:1645, Access-Request, len 100 Jan 1
00:32:55.087: Attribute 4 6 0A330644 Jan 1 00:32:55.087: Attribute 5 6 00000000 Jan 1
00:32:55.087: Attribute 26 17 00000009020B5365 Jan 1 00:32:55.087: Attribute 61 6 00000002 Jan 1
00:32:55.087: Attribute 1 13 646E6973 Jan 1 00:32:55.087: Attribute 30 8 36313436 Jan 1
00:32:55.087: Attribute 2 18 F0AF3BC4 Jan 1 00:32:55.087: Attribute 6 6 00000005 Jan 1
00:32:55.091: RADIUS: Received from id 50 10.51.6.3:1645, Access-Accept, len 167 Jan 1
00:32:55.091: Attribute 6 6 00000005 Jan 1 00:32:55.091: Attribute 26 29 0000000901177670 Jan 1
00:32:55.091: Attribute 26 26 0000000901147670 Jan 1 00:32:55.091: Attribute 26 47
0000000901297670 Jan 1 00:32:55.091: Attribute 26 39 0000000901217670 !--- LAC receives a call,
negotiates PPP, LCP is declared Open, !--- the dialed number is queried to ascertain if this is
a VPDN customer. !--- VPDN attempts to find an existing tunnel for the user, queries RADIUS for
!--- the tunnel information. Jan 1 00:32:55.091: RADIUS: saved authorization data for user
61F40024 at 61F9813C Jan 1 00:32:55.091: RADIUS: cisco AVPair "vpdn:tunnel-type=l2tp" Jan 1
00:32:55.091: RADIUS: cisco AVPair "vpdn:tunnel-id=hgw" Jan 1 00:32:55.091: RADIUS: cisco AVPair
"vpdn:ip-addresses=10.51.6.82,10.51.6.59" Jan 1 00:32:55.095: RADIUS: cisco AVPair "vpdn:l2tp-
tunnel-password=hello" Jan 1 00:32:55.095: AAA/AUTHOR (480033158): Post authorization status =
PASS_ADD Jan 1 00:32:55.095: AAA/AUTHOR/VPDN: Processing AV service=ppp Jan 1 00:32:55.095:
AAA/AUTHOR/VPDN: Processing AV protocol=vpdn Jan 1 00:32:55.095: AAA/AUTHOR/VPDN: Processing AV
tunnel-type=l2tp Jan 1 00:32:55.095: AAA/AUTHOR/VPDN: Processing AV tunnel-id=hgw Jan 1
00:32:55.095: AAA/AUTHOR/VPDN: Processing AV ip-addresses= 10.51.6.82,10.51.6.59 Jan 1
00:32:55.095: AAA/AUTHOR/VPDN: Processing AV l2tp-tunnel-password=hello Jan 1 00:32:55.095:
Se0:0 VPDN/RPMS/: Got tunnel info for dnis:614629 Jan 1 00:32:55.095: Se0:0 VPDN/RPMS/: LAC hgw
Jan 1 00:32:55.095: Se0:0 VPDN/RPMS/: l2tp-busy-disconnect yes Jan 1 00:32:55.095: Se0:0
VPDN/RPMS/: l2tp-tunnel-password xxxxxx Jan 1 00:32:55.095: Se0:0 VPDN/RPMS/: 2 IP addresses Jan
1 00:32:55.095: Se0:0 VPDN/RPMS/: IP 10.51.6.82 Priority 1 Jan 1 00:32:55.095: Se0:0 VPDN/RPMS/:
IP 10.51.6.59 Priority 1 Jan 1 00:32:55.095: Se0:0 VPDN/: curlvl 1 Address 0: 10.51.6.82,
priority 1 Jan 1 00:32:55.095: Se0:0 VPDN/: Select non-active address 10.51.6.82, priority 1 !--
- The tunnel information is downloaded, using Cisco VSA. Two LNS IP !--- Addresses are used with
a ',' as the delimiter, indicating that both !--- have equal priority. In this case 10.51.6.82
is selected as the tunnel !--- endpoint. Jan 1 00:32:55.095: Se0:0 VPDN: Find LNS process
created Jan 1 00:32:55.095: Tnl 49467 L2TP: SM State idle Jan 1 00:32:55.095: Tnl 49467 L2TP: O
SCCRQ Jan 1 00:32:55.099: Tnl 49467 L2TP: Tunnel state change from idle to wait-ctl-reply Jan 1
00:32:55.099: Tnl 49467 L2TP: SM State wait-ctl-reply Jan 1 00:32:55.099: Se0:0 VPDN: Forward to
address 10.51.6.82 Jan 1 00:32:55.099: Se0:0 VPDN: Pending Jan 1 00:32:55.099: Se0:0 VPDN:
Process created Jan 1 00:32:55.191: Tnl 49467 L2TP: I SCCRP from l2tp-gw Jan 1 00:32:55.191: Tnl
49467 L2TP: Got a challenge from remote peer, l2tp-gw Jan 1 00:32:55.191: Tnl 49467 L2TP: Got a
response from remote peer, l2tp-gw Jan 1 00:32:55.191: Tnl 49467 L2TP: Tunnel Authentication
success Jan 1 00:32:55.191: Tnl 49467 L2TP: Tunnel state change from wait-ctl-reply to
```

established Jan 1 00:32:55.191: Tnl 49467 L2TP: O SCCCN to l2tp-gw tnlid 62193 Jan 1
00:32:55.195: Tnl 49467 L2TP: SM State established Jan 1 00:32:55.195: Tnl/Cl 49467/16 L2TP:
Session FS enabled Jan 1 00:32:55.195: Tnl/Cl 49467/16 L2TP: Session state change from idle to
wait-for-tunnel Jan 1 00:32:55.195: Se0:0 Tnl/Cl 49467/16 L2TP: Create session Jan 1
00:32:55.195: Tnl 49467 L2TP: SM State established Jan 1 00:32:55.195: Se0:0 Tnl/Cl 49467/16
L2TP: O ICRQ to l2tp-gw 62193/0 Jan 1 00:32:55.195: Se0:0 Tnl/Cl 49467/16 L2TP: Session state
change from wait-for-tunnel to wait-reply Jan 1 00:32:55.195: Se0:0 VPDN: 2500-1 is forwarded
Jan 1 00:32:55.327: Se0:0 Tnl/Cl 49467/16 L2TP: O ICCN to l2tp-gw 62193/17 **Jan 1 00:32:55.327:
Se0:0 Tnl/Cl 49467/16 L2TP: Session state change from wait-reply to established** Jan 1
00:32:56.195: %LINEPROTO-5-UPDOWN: Line protocol on Interface Serial0:0, changed state to up Jan
1 00:33:00.851: %ISDN-6-CONNECT:Interface Serial0:0 is now connected to 2500-1 Jan 1
00:33:06.111: %ISDN-6-CONNECT: Interface Serial0:1 is now connected to N/A N/A *!--- Second call
is received by the LAC, !--- the dialed number is a VPDN customer.* Jan 1 00:33:35.027: As1 LCP:
I CONFREQ [Closed] id 1 len 23 - snip - **Jan 1 00:33:39.275: As1 LCP: State is Open** Jan 1
00:33:39.275: As1 PPP: Phase is AUTHENTICATING, by this end Jan 1 00:33:39.275: As1 CHAP: Using
alternate hostname 5300-1 Jan 1 00:33:39.275: As1 CHAP: O CHALLENGE id 2 len 27 from "5300-1"
Jan 1 00:33:39.383: As1 CHAP: I RESPONSE id 2 len 25 from "paul" Jan 1 00:33:39.383: As1 PPP:
Phase is FORWARDING **Jan 1 00:33:39.383: As1 VPDN: Got DNIS string 614629 Jan 1 00:33:39.383: As1
VPDN: Looking for tunnel -- dnis:614629 --** Jan 1 00:33:39.387: Async1 AAA/AUTHOR/VPDN
(3019717950): Port='Async1' list='default' service=NET Jan 1 00:33:39.387: AAA/AUTHOR/VPDN:
Async1 (3019717950) user='dnis:614629' Jan 1 00:33:39.387: Async1 AAA/AUTHOR/VPDN (3019717950):
send AV service=ppp Jan 1 00:33:39.387: Async1 AAA/AUTHOR/VPDN (3019717950): send AV
protocol=vpdn Jan 1 00:33:39.387: Async1 AAA/AUTHOR/VPDN (3019717950): found list "default" Jan
1 00:33:39.387: Async1 AAA/AUTHOR/VPDN (3019717950): Method=NSA_LAB (radius) Jan 1 00:33:39.387:
RADIUS: Initial Transmit Async1 id 52 10.51.6.3:1645, Access-Request, len 97 Jan 1 00:33:39.387:
Attribute 4 6 0A330644 Jan 1 00:33:39.387: Attribute 5 6 00000001 Jan 1 00:33:39.387: Attribute
26 14 0000000902084173 Jan 1 00:33:39.387: Attribute 61 6 00000000 Jan 1 00:33:39.387: Attribute
1 13 646E6973 Jan 1 00:33:39.387: Attribute 30 8 36313436 Jan 1 00:33:39.387: Attribute 2 18
E9164E4C Jan 1 00:33:39.387: Attribute 6 6 00000005 Jan 1 00:33:39.391: RADIUS: Received from id
52 10.51.6.3:1645, Access-Accept, len 167 Jan 1 00:33:39.391: Attribute 6 6 00000005 Jan 1
00:33:39.391: Attribute 26 29 0000000901177670 Jan 1 00:33:39.391: Attribute 26 26
0000000901147670 Jan 1 00:33:39.391: Attribute 26 47 0000000901297670 Jan 1 00:33:39.391:
Attribute 26 39 0000000901217670 Jan 1 00:33:39.391: RADIUS: saved authorization data for user
621904CC at 61FAB9EC Jan 1 00:33:39.391: RADIUS: cisco AVPair "vpdn:tunnel-type=l2tp" Jan 1
00:33:39.391: RADIUS: cisco AVPair "vpdn:tunnel-id=hgw" Jan 1 00:33:39.391: RADIUS: cisco AVPair
"vpdn:ip-addresses=10.51.6.82,10.51.6.59" Jan 1 00:33:39.391: RADIUS: cisco AVPair "vpdn:l2tp-
tunnel-password=hello" Jan 1 00:33:39.395: AAA/AUTHOR (3019717950): Post authorization status =
PASS_ADD Jan 1 00:33:39.395: AAA/AUTHOR/VPDN: Processing AV service=ppp Jan 1 00:33:39.395:
AAA/AUTHOR/VPDN: Processing AV protocol=vpdn Jan 1 00:33:39.395: AAA/AUTHOR/VPDN: Processing AV
tunnel-type=l2tp Jan 1 00:33:39.395: AAA/AUTHOR/VPDN: Processing AV tunnel-id=hgw Jan 1
00:33:39.395: AAA/AUTHOR/VPDN: Processing AV ip-addresses=10.51.6.82,10.51.6.59 Jan 1
00:33:39.395: AAA/AUTHOR/VPDN: Processing AV l2tp-tunnel-password=hello Jan 1 00:33:39.395: As1
VPDN/RPMS/: Got tunnel info for dnis:614629 Jan 1 00:33:39.395: As1 VPDN/RPMS/: LAC hgw Jan 1
00:33:39.395: As1 VPDN/RPMS/: l2tp-busy-disconnect yes Jan 1 00:33:39.395: As1 VPDN/RPMS/: l2tp-
tunnel-password xxxxxx Jan 1 00:33:39.395: As1 VPDN/RPMS/: 2 IP addresses Jan 1 00:33:39.395:
As1 VPDN/RPMS/: IP 10.51.6.82 Priority 1 Jan 1 00:33:39.395: As1 VPDN/RPMS/: IP 10.51.6.59
Priority 1 Jan 1 00:33:39.395: As1 VPDN/: curlvl 1 Address 1: 10.51.6.59, priority 1 **Jan 1
00:33:39.395: As1 VPDN/: Select non-active address 10.51.6.59, priority 1 !--- The second non-
active endpoint is selected 10.51.6.59 !--- and the control connection is established.** Jan 1
00:33:39.395: As1 VPDN: Find LNS process created Jan 1 00:33:39.395: Tnl 20770 L2TP: SM State
idle Jan 1 00:33:39.395: Tnl 20770 L2TP: O SCCRQ Jan 1 00:33:39.399: Tnl 20770 L2TP: Tunnel
state change from idle to wait-ctl-reply Jan 1 00:33:39.399: Tnl 20770 L2TP: SM State wait-ctl-
reply **Jan 1 00:33:39.399: As1 VPDN: Forward to address 10.51.6.59** Jan 1 00:33:39.399: As1 VPDN:
Pending Jan 1 00:33:39.399: As1 VPDN: Process created Jan 1 00:33:39.399: Tnl 20770 L2TP: I
SCCRP from l2tp-gw Jan 1 00:33:39.399: Tnl 20770 L2TP: Got a challenge from remote peer, l2tp-gw
Jan 1 00:33:39.399: Tnl 20770 L2TP: Got a response from remote peer, l2tp-gw Jan 1 00:33:39.399:
Tnl 20770 L2TP: Tunnel Authentication success Jan 1 00:33:39.399: Tnl 20770 L2TP: Tunnel state
change from wait-ctl-reply to established Jan 1 00:33:39.403: Tnl 20770 L2TP: O SCCCN to l2tp-gw
tnlid 42921 Jan 1 00:33:39.403: Tnl 20770 L2TP: SM State established Jan 1 00:33:39.403: As1
VPDN: Forwarding... Jan 1 00:33:39.403: Tnl/Cl 20770/17 L2TP: Session FS enabled Jan 1
00:33:39.403: Tnl/Cl 20770/17 L2TP: Session state change from idle to wait-for-tunnel Jan 1
00:33:39.403: As1 Tnl/Cl 20770/17 L2TP: Create session Jan 1 00:33:39.403: Tnl 20770 L2TP: SM
State established Jan 1 00:33:39.403: As1 Tnl/Cl 20770/17 L2TP: O ICRQ to l2tp-gw 42921/0 Jan 1
00:33:39.403: As1 Tnl/Cl 20770/17 L2TP: Session state change from wait-for-tunnel to wait-reply

Jan 1 00:33:39.403: As1 VPDN: paul is forwarded Jan 1 00:33:39.407: As1 Tnl/Cl 20770/17 L2TP: O ICCN to l2tp-gw 42921/16 Jan 1 00:33:39.407: As1 Tnl/Cl 20770/17 L2TP: Session state change from wait-reply to established

シスコベンダー固有属性/値ペアを使用する LNS フェールオーバー

RADIUS プロファイル

Merit RADIUS サーバ 3.6B 上の RADIUS ユーザおよびトンネルのプロファイル :

```
2500-1 Password = "cisco"  
Service-Type = Framed,  
Framed-Protocol = PPP,  
Framed-IP-Address = 255.255.255.255
```

```
dnis:614629 Password = "cisco"  
Service-Type = Outbound,  
Cisco:Avpair = "vpdn:tunnel-type=l2tp",  
Cisco:Avpair = "vpdn:tunnel-id=hgw",  
Cisco:Avpair = "vpdn:ip-addresses=10.51.6.82/10.51.6.59",  
Cisco:Avpair = "vpdn:l2tp-tunnel-password=hello"
```

LAC と LNS の設定

前と同じ。

LAC から取得されたデバッグ

```
Jan 1 02:00:35.767: As2 LCP: State is Open Jan 1 02:00:35.767: As2 PPP: Phase is AUTHENTICATING,  
by this end [0 sess, 0 load] Jan 1 02:00:35.767: As2 CHAP: Using alternate hostname 5300-1 Jan 1  
02:00:35.767: As2 CHAP: O CHALLENGE id 1 len 27 from "5300-1" Jan 1 02:00:35.959: As2 CHAP: I  
RESPONSE id 1 len 25 from "paul" Jan 1 02:00:35.959: As2 PPP: Phase is FORWARDING [0 sess, 0  
load] Jan 1 02:00:35.959: As2 VPDN: Got DNIS string 614629 Jan 1 02:00:35.959: As2 VPDN: Looking  
for tunnel -- dnis:614629 -- Jan 1 02:00:35.959: AAA/AUTHOR/VPDN: Async2 (3581154520)  
user='dnis:614629' Jan 1 02:00:35.963: Async2 AAA/AUTHOR/VPDN (3581154520): send AV service=ppp  
Jan 1 02:00:35.963: Async2 AAA/AUTHOR/VPDN (3581154520): send AV protocol=vpdn Jan 1  
02:00:35.963: Async2 AAA/AUTHOR/VPDN (3581154520): found list "default" Jan 1 02:00:35.963:  
Async2 AAA/AUTHOR/VPDN (3581154520): Method=NSA_LAB (radius) Jan 1 02:00:35.963: RADIUS: Initial  
Transmit Async2 id 56 10.51.6.3:1645, Access-Request, len 109 Jan 1 02:00:35.963: Attribute 4 6  
0A330644 Jan 1 02:00:35.963: Attribute 5 6 00000000 Jan 1 02:00:35.963: Attribute 26 14  
0000000902084173 Jan 1 02:00:35.963: Attribute 61 6 00000000 Jan 1 02:00:35.963: Attribute 1 13  
646E6973 Jan 1 02:00:35.963: Attribute 30 8 36313436 Jan 1 02:00:35.963: Attribute 31 12  
31363139 Jan 1 02:00:35.963: Attribute 2 18 2A5AF04C Jan 1 02:00:35.963: Attribute 6 6 00000005  
Jan 1 02:00:35.967: RADIUS: Received from id 56 10.51.6.3:1645, Access-Accept, len 167 Jan 1  
02:00:35.967: Attribute 6 6 00000005 Jan 1 02:00:35.967: Attribute 26 29 0000000901177670 Jan 1  
02:00:35.967: Attribute 26 26 0000000901147670 Jan 1 02:00:35.967: Attribute 26 47  
0000000901297670 Jan 1 02:00:35.967: Attribute 26 39 0000000901217670 Jan 1 02:00:35.967:  
RADIUS: cisco AVPair "vpdn:tunnel-type=l2tp" Jan 1 02:00:35.967: RADIUS: cisco AVPair  
"vpdn:tunnel-id=hgw" Jan 1 02:00:35.967: RADIUS: cisco AVPair "vpdn:ip-  
addresses=10.51.6.82/10.51.6.59" Jan 1 02:00:35.967: RADIUS: cisco AVPair "vpdn:l2tp-tunnel-  
password=hello" Jan 1 02:00:35.967: AAA/AUTHOR (3581154520): Post authorization status =  
PASS_ADD Jan 1 02:00:35.967: AAA/AUTHOR/VPDN: Processing AV service=ppp Jan 1 02:00:35.967:  
AAA/AUTHOR/VPDN: Processing AV protocol=vpdn Jan 1 02:00:35.967: AAA/AUTHOR/VPDN: Processing AV  
tunnel-type=l2tp Jan 1 02:00:35.967: AAA/AUTHOR/VPDN: Processing AV tunnel-id=hgw Jan 1  
02:00:35.967: AAA/AUTHOR/VPDN: Processing AV ip-addresses= 10.51.6.82/10.51.6.59 Jan 1  
02:00:35.967: AAA/AUTHOR/VPDN: Processing AV l2tp-tunnel-password=hello !--- LAC receives a  
call, negotiates PPP, LCP is declared Open, !--- the dialed number is queried to ascertain if  
this is a VPDN customer. !--- VPDN attempts to find an existing tunnel for the user, queries  
RADIUS for !--- the tunnel information. Jan 1 02:00:35.967: As2 VPDN/RPMS/: Got tunnel info for  
dnis:614629 Jan 1 02:00:35.971: As2 VPDN/RPMS/: LAC hgw Jan 1 02:00:35.971: As2 VPDN/RPMS/:
```

l2tp-busy-disconnect yes Jan 1 02:00:35.971: As2 VPDN/RPMS/: l2tp-tunnel-password xxxxxx Jan 1 02:00:35.971: As2 VPDN/RPMS/: 2 IP addresses **Jan 1 02:00:35.971: As2 VPDN/RPMS/: IP 10.51.6.82 Priority 1 Jan 1 02:00:35.971: As2 VPDN/RPMS/: IP 10.51.6.59 Priority 2 Jan 1 02:00:35.971: As2 VPDN/:** curlvl 1 Address 0: 10.51.6.82, priority 1 **Jan 1 02:00:35.971: As2 VPDN/:** Select non-active address 10.51.6.82, priority 1 *!--- The tunnel information is downloaded, using Cisco VSA. !--- Two RADIUS server IP Address's are used with a '/' as the delimiter, !--- indicating that there are two priority groups. In this case 10.51.6.82, !--- as Priority level 1, is selected as the tunnel endpoint.* Jan 1 02:00:35.971: Tnl 17044 L2TP: SM State idle Jan 1 02:00:35.971: Tnl 17044 L2TP: O SCCRQ Jan 1 02:00:35.971: Tnl 17044 L2TP: Tunnel state change from idle to wait-ctl-reply Jan 1 02:00:35.971: Tnl 17044 L2TP: SM State wait-ctl-reply Jan 1 02:00:35.971: As2 VPDN: Find LNS process created Jan 1 02:00:35.971: As2 VPDN: Forward to address 10.51.6.82 Jan 1 02:00:35.971: As2 VPDN: Pending Jan 1 02:00:35.971: As2 VPDN: Process created Jan 1 02:00:35.983: Tnl 17044 L2TP: I SCCRP from l2tp-gw Jan 1 02:00:35.983: Tnl 17044 L2TP: Got a challenge from remote peer, l2tp-gw Jan 1 02:00:35.983: Tnl 17044 L2TP: Got a response from remote peer, l2tp-gw Jan 1 02:00:35.983: Tnl 17044 L2TP: Tunnel Authentication success **Jan 1 02:00:35.983: Tnl 17044 L2TP: Tunnel state change from wait-ctl-reply to established** Jan 1 02:00:35.983: Tnl 17044 L2TP: O SCCCN to l2tp-gw tnlid 9017 Jan 1 02:00:35.983: Tnl 17044 L2TP: SM State established Jan 1 02:00:35.983: As2 VPDN: Forwarding... Jan 1 02:00:35.987: Tnl/Cl 17044/2 L2TP: Session FS enabled Jan 1 02:00:35.987: Tnl/Cl 17044/2 L2TP: Session state change from idle to wait-for-tunnel Jan 1 02:00:35.987: As2 Tnl/Cl 17044/2 L2TP: Create session Jan 1 02:00:35.987: Tnl 17044 L2TP: SM State established Jan 1 02:00:35.987: As2 Tnl/Cl 17044/2 L2TP: O ICRQ to l2tp-gw 9017/0 Jan 1 02:00:35.987: As2 Tnl/Cl 17044/2 L2TP: Session state change from wait-for-tunnel to wait-reply Jan 1 02:00:35.987: As2 VPDN: paul is forwarded Jan 1 02:00:35.995: As2 Tnl/Cl 17044/2 L2TP: O ICCN to l2tp-gw 9017/2 **Jan 1 02:00:35.995: As2 Tnl/Cl 17044/2 L2TP: Session state change from wait-reply to established !--- The Tunnel and Session are now established. !--- A second call is received by the LAC.** **Jan 1 02:03:21.775: Se0:1 LCP: State is Open** Jan 1 02:03:21.775: Se0:1 PPP: Phase is AUTHENTICATING, by this end [0 sess, 0 load] Jan 1 02:03:21.775: Se0:1 CHAP: Using alternate hostname 5300-1 Jan 1 02:03:21.775: Se0:1 CHAP: O CHALLENGE id 1 len 27 from "5300-1" Jan 1 02:03:21.799: Se0:1 CHAP: I RESPONSE id 1 len 27 from "2500-1" Jan 1 02:03:21.799: Se0:1 PPP: Phase is FORWARDING [0 sess, 0 load] **Jan 1 02:03:21.799: Se0:1 VPDN: Got DNIS string 614629 Jan 1 02:03:21.799: Se0:1 VPDN: Looking for tunnel -- dnis:614629 --** Jan 1 02:03:21.799: Serial0:1 AAA/AUTHOR/VPDN (2106866192): Port='Serial0:1' list='default' service=NET Jan 1 02:03:21.799: AAA/AUTHOR/VPDN: Serial0:1 (2106866192) user='dnis:614629' Jan 1 02:03:21.799: Serial0:1 AAA/AUTHOR/VPDN (2106866192): send AV service=ppp Jan 1 02:03:21.799: Serial0:1 AAA/AUTHOR/VPDN (2106866192): send AV protocol=vpdn Jan 1 02:03:21.799: Serial0:1 AAA/AUTHOR/VPDN (2106866192): found list "default" Jan 1 02:03:21.799: Serial0:1 AAA/AUTHOR/VPDN (2106866192): Method=NSA_LAB (radius) Jan 1 02:03:21.803: RADIUS: Initial Transmit Serial0:1 id 60 10.51.6.3:1645, Access-Request, len 112 Jan 1 02:03:21.803: Attribute 4 6 0A330644 Jan 1 02:03:21.803: Attribute 5 6 00000001 Jan 1 02:03:21.803: Attribute 26 17 00000009020B5365 Jan 1 02:03:21.803: Attribute 61 6 00000002 Jan 1 02:03:21.803: Attribute 1 13 646E6973 Jan 1 02:03:21.803: Attribute 30 8 36313436 Jan 1 02:03:21.803: Attribute 31 12 32303835 Jan 1 02:03:21.803: Attribute 2 18 1A511187 Jan 1 02:03:21.803: Attribute 6 6 00000005 Jan 1 02:03:21.803: RADIUS: Received from id 60 10.51.6.3:1645, Access-Accept, len 167 Jan 1 02:03:21.803: Attribute 6 6 00000005 Jan 1 02:03:21.803: Attribute 26 29 0000000901177670 Jan 1 02:03:21.803: Attribute 26 26 0000000901147670 Jan 1 02:03:21.803: Attribute 26 47 0000000901297670 Jan 1 02:03:21.803: Attribute 26 39 0000000901217670 Jan 1 02:03:21.807: RADIUS: cisco AVPair "vpdn:tunnel-type=l2tp" Jan 1 02:03:21.807: RADIUS: cisco AVPair "vpdn:tunnel-id=hgw" Jan 1 02:03:21.807: RADIUS: cisco AVPair "vpdn:ip-addresses=10.51.6.82/10.51.6.59" Jan 1 02:03:21.807: RADIUS: cisco AVPair "vpdn:l2tp-tunnel-password=hello" Jan 1 02:03:21.807: AAA/AUTHOR (2106866192): Post authorization status = PASS_ADD Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV service=ppp Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV protocol=vpdn Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV tunnel-type=l2tp Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV tunnel-id=hgw Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV ip-addresses=10.51.6.82/10.51.6.59 Jan 1 02:03:21.807: AAA/AUTHOR/VPDN: Processing AV l2tp-tunnel-password=hello Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: Got tunnel info for dnis:614629 Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: LAC hgw Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: l2tp-busy-disconnect yes Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: l2tp-tunnel-password xxxxxx Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: 2 IP addresses **Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: IP 10.51.6.82 Priority 1 Jan 1 02:03:21.807: Se0:1 VPDN/RPMS/: IP 10.51.6.59 Priority 2 Jan 1 02:03:21.807: Se0:1 VPDN/:** curlvl 1 Address 0: 10.51.6.82, priority 1 **Jan 1 02:03:21.811: Se0:1 VPDN/:** Select open address 10.51.6.82, priority 1 **Jan 1 02:03:21.811: Se0:1 VPDN:** Forward to address 10.51.6.82 *!--- The tunnel information is downloaded, LNS - 10.51.6.82 is !--- selected again as the tunnel endpoint as this is in Priority level 1.* Jan 1 02:03:21.811: Se0:1 VPDN:

Forwarding... Jan 1 02:03:21.811: Tnl/Cl 17044/3 L2TP: Session state change from idle to wait-for-tunnel Jan 1 02:03:21.811: Se0:1 Tnl/Cl 17044/3 L2TP: Create session Jan 1 02:03:21.811: Tnl 17044 L2TP: SM State established Jan 1 02:03:21.811: Se0:1 Tnl/Cl 17044/3 L2TP: O ICRQ to l2tp-gw 9017/0 Jan 1 02:03:21.811: Se0:1 Tnl/Cl 17044/3 L2TP: Session state change from wait-for-tunnel to wait-reply Jan 1 02:03:21.811: Se0:1 VPDN: 2500-1 is forwarded Jan 1 02:03:21.819: Se0:1 Tnl/Cl 17044/3 L2TP: O ICCN to l2tp-gw 9017/3 Jan 1 02:03:21.819: Se0:1 Tnl/Cl 17044/3 L2TP: Session state change from wait-reply to established

シスコベンダー固有属性/値ペアを使用する LNS ロード バランシングとフェールオーバー

RADIUS プロファイル

Merit RADIUS サーバ 3.6B 上の RADIUS ユーザおよびトンネルのプロファイル :

```
2500-1 Password = "cisco"
Service-Type = Framed,
Framed-Protocol = PPP,
Framed-IP-Address = 255.255.255.255
dnis:614629 Password = "cisco"
Service-Type = Outbound,
Cisco:Avpair = "vpdn:tunnel-type=l2tp",
Cisco:Avpair = "vpdn:tunnel-id=hgw",
Cisco:Avpair = "vpdn:ip-addresses=
10.51.6.80,10.51.6.59/10.51.6.2,10.51.6.3/10.51.6.82,10.51.6.5",
Cisco:Avpair = "vpdn:l2tp-tunnel-password=hello"
```

LAC と LNS の設定

前と同じ。

LAC から取得されたデバッグ

Jan 1 00:43:11.539: %LINK-3-UPDOWN: Interface Serial0:0, changed state to up

```
Jan 1 00:43:11.755: Se0:0 LCP: State is Open Jan 1 00:43:11.755: Se0:0 PPP: Phase is
AUTHENTICATING, by this end Jan 1 00:43:11.755: Se0:0 CHAP: Using alternate hostname 5300-1 Jan
1 00:43:11.755: Se0:0 CHAP: O CHALLENGE id 18 len 27 from "5300-1" Jan 1 00:43:11.775: Se0:0
CHAP: I RESPONSE id 18 len 27 from "2500-1" Jan 1 00:43:11.775: Se0:0 PPP: Phase is FORWARDING
Jan 1 00:43:11.775: Se0:0 VPDN: Got DNIS string 614629 Jan 1 00:43:11.775: Se0:0 VPDN: Looking
for tunnel -- dnis:614629 -- Jan 1 00:43:11.775: Serial0:0 AAA/AUTHOR/VPDN (2215378044):
Port='Serial0:0' list='default' service=NET Jan 1 00:43:11.775: AAA/AUTHOR/VPDN: Serial0:0
(2215378044) user='dnis:614629' Jan 1 00:43:11.775: Serial0:0 AAA/AUTHOR/VPDN (2215378044): send
AV service=ppp Jan 1 00:43:11.775: Serial0:0 AAA/AUTHOR/VPDN (2215378044): send AV protocol=vpdn
Jan 1 00:43:11.775: Serial0:0 AAA/AUTHOR/VPDN (2215378044): found list "default" Jan 1
00:43:11.775: Serial0:0 AAA/AUTHOR/VPDN (2215378044): Method=NSA_LAB (radius) Jan 1
00:43:11.779: RADIUS: Initial Transmit Serial0:0 id 57 10.51.6.3:1645, Access-Request, len 112
Jan 1 00:43:11.779: Attribute 4 6 0A330644 Jan 1 00:43:11.779: Attribute 5 6 00000000 Jan 1
00:43:11.779: Attribute 26 17 00000009020B5365 Jan 1 00:43:11.779: Attribute 61 6 00000002 Jan 1
00:43:11.779: Attribute 1 13 646E6973 Jan 1 00:43:11.779: Attribute 30 8 36313436 Jan 1
00:43:11.779: Attribute 31 12 32303835 Jan 1 00:43:11.779: Attribute 2 18 BA50FCD1 Jan 1
00:43:11.779: Attribute 6 6 00000005 Jan 1 00:43:11.783: RADIUS: Received from id 57
10.51.6.3:1645, Access-Accept, len 208 Jan 1 00:43:11.783: Attribute 6 6 00000005 Jan 1
00:43:11.783: Attribute 26 29 0000000901177670 Jan 1 00:43:11.783: Attribute 26 26
0000000901147670 Jan 1 00:43:11.783: Attribute 26 88 0000000901527670 Jan 1 00:43:11.783:
Attribute 26 39 0000000901217670 Jan 1 00:43:11.783: RADIUS: cisco AVPair "vpdn:tunnel-
type=l2tp" Jan 1 00:43:11.783: RADIUS: cisco AVPair "vpdn:tunnel-id=hgw" Jan 1 00:43:11.783:
RADIUS: cisco AVPair "vpdn:ip-addresses=
10.51.6.80,10.51.6.59/10.51.6.2,10.51.6.3/10.51.6.82,10.51.6.5" Jan 1 00:43:11.783: RADIUS:
cisco AVPair "vpdn:l2tp-tunnel-password=hello" Jan 1 00:43:11.783: AAA/AUTHOR (2215378044): Post
```


authorization status = PASS_ADD Jan 1 00:43:11.783: AAA/AUTHOR/VPDN: Processing AV service=ppp
Jan 1 00:43:11.783: AAA/AUTHOR/VPDN: Processing AV protocol=vpdn Jan 1 00:43:11.783:
AAA/AUTHOR/VPDN: Processing AV tunnel-type=l2tp Jan 1 00:43:11.783: AAA/AUTHOR/VPDN: Processing
AV tunnel-id=hgw Jan 1 00:43:11.783: AAA/AUTHOR/VPDN: Processing AV ip-addresses=
10.51.6.80,10.51.6.59/10.51.6.2,10.51.6.3/10.51.6.82,10.51.6.5 Jan 1 00:43:11.783:
AAA/AUTHOR/VPDN: Processing AV l2tp-tunnel-password=hello Jan 1 00:43:11.783: Se0:0 VPDN/RPMS/:
Got tunnel info for dnis:614629 Jan 1 00:43:11.783: Se0:0 VPDN/RPMS/: LAC hgw Jan 1
00:43:11.787: Se0:0 VPDN/RPMS/: l2tp-busy-disconnect yes Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/:
l2tp-tunnel-password xxxxxx Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/: 6 IP addresses **Jan 1
00:43:11.787: Se0:0 VPDN/RPMS/: IP 10.51.6.80 Priority 1 Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/:
IP 10.51.6.59 Priority 1 Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/: IP 10.51.6.2 Priority 2 Jan 1
00:43:11.787: Se0:0 VPDN/RPMS/: IP 10.51.6.3 Priority 2 Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/: IP
10.51.6.82 Priority 3 Jan 1 00:43:11.787: Se0:0 VPDN/RPMS/: IP 10.51.6.5 Priority 3 !--- The
tunnel information is downloaded, using Cisco VSA. Two RADIUS !--- server IP Addresses are used
with a '/' as the delimiter for each !--- of the three priority groups. In this case, 10.51.6.82
in Priority !--- Group 3, is the tunnel endpoint that is valid.** Jan 1 00:43:11.787: Se0:0 VPDN/:
curlvl 1 Address 1: 10.51.6.59, priority 1 Jan 1 00:43:11.787: VPDN: Free busy address
10.51.6.59 **Jan 1 00:43:11.787: Se0:0 VPDN/: Select non-active address 10.51.6.59, priority 1** Jan
1 00:43:11.787: Se0:0 VPDN: Find LNS process created Jan 1 00:43:11.787: Tnl 8262 L2TP: SM State
idle **Jan 1 00:43:11.787: Tnl 8262 L2TP: O SCCRQ** Jan 1 00:43:11.787: Tnl 8262 L2TP: Tunnel state
change from idle to wait-ctl-reply Jan 1 00:43:11.787: Tnl 8262 L2TP: SM State wait-ctl-reply
Jan 1 00:43:11.787: Se0:0 VPDN: Forward to address 10.51.6.59 Jan 1 00:43:11.791: Se0:0 VPDN:
Pending Jan 1 00:43:11.791: Se0:0 VPDN: Process created **Jan 1 00:43:12.787: Tnl 8262 L2TP: O
Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0** Jan 1 00:43:12.787: Tnl 8262
L2TP: Control channel retransmit delay set to 1 seconds **Jan 1 00:43:13.787: Tnl 8262 L2TP: O
Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0** Jan 1 00:43:13.787: Tnl 8262
L2TP: Control channel retransmit delay set to 2 seconds **Jan 1 00:43:15.787: Tnl 8262 L2TP:
Timeout opening tunnel to 10.51.6.59** Jan 1 00:43:15.787: Tnl 63291 L2TP: Control channel
retransmit delay set to 4 seconds **Jan 1 00:43:15.787: Se0:0 VPDN/: curlvl 1 Address 1:
10.51.6.59, priority 1 busy !--- 10.51.6.59 is selected as the first non-active IP Address in
Priority !--- Group 1. As we cannot establish the Control Connection after the !--- 4 second
SCCRQ timeout, we select the next non-active IP !--- Address in the same Priority Group.** Jan 1
00:43:15.787: Se0:0 VPDN/: curlvl 1 Address 0: 10.51.6.80, priority 1 Jan 1 00:43:15.787: VPDN:
Free busy address 10.51.6.80 **Jan 1 00:43:15.787: Se0:0 VPDN/: Select non-active address
10.51.6.80, priority 1** Jan 1 00:43:15.787: Tnl 63291 L2TP: Tunnel state change from wait-ctl-
reply to idle Jan 1 00:43:15.787: Tnl 63291 L2TP: SM State idle Jan 1 00:43:15.787: Tnl 63291
L2TP: O SCCRQ Jan 1 00:43:15.787: Tnl 63291 L2TP: Tunnel state change from idle to wait-ctl-
reply Jan 1 00:43:15.787: Tnl 63291 L2TP: SM State wait-ctl-reply Jan 1 00:43:16.787: Tnl 63291
L2TP: O Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0 Jan 1 00:43:16.787: Tnl
63291 L2TP: Control channel retransmit delay set to 1 seconds Jan 1 00:43:17.543: %ISDN-6-
CONNECT: Interface Serial0:0 is now connected to 2085730592 Jan 1 00:43:17.787: Tnl 63291 L2TP:
O Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0 Jan 1 00:43:17.787: Tnl 63291
L2TP: Control channel retransmit delay set to 2 seconds Jan 1 00:43:19.787: Tnl 63291 L2TP:
Timeout opening tunnel to 10.51.6.80 Jan 1 00:43:19.787: Tnl 52784 L2TP: Control channel
retransmit delay set to 4 seconds Jan 1 00:43:19.787: Se0:0 VPDN/: curlvl 1 Address 0:
10.51.6.80, priority 1 busy Jan 1 00:43:19.787: Se0:0 VPDN/: curlvl 1 Address 1: 10.51.6.59,
priority 1 busy Jan 1 00:43:19.787: Se0:0 VPDN/: curlvl 2 Address 2: 10.51.6.2, priority 2 Jan 1
00:43:19.787: VPDN: Free busy address 10.51.6.2 **Jan 1 00:43:19.787: Se0:0 VPDN/: Select non-
active address 10.51.6.2, priority 2** Jan 1 00:43:19.787: Tnl 52784 L2TP: Tunnel state change
from wait-ctl-reply to idle Jan 1 00:43:19.787: Tnl 52784 L2TP: SM State idle Jan 1
00:43:19.787: Tnl 52784 L2TP: O SCCRQ Jan 1 00:43:19.787: Tnl 52784 L2TP: Tunnel state change
from idle to wait-ctl-reply Jan 1 00:43:19.787: Tnl 52784 L2TP: SM State wait-ctl-reply Jan 1
00:43:20.787: Tnl 52784 L2TP: O Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0
Jan 1 00:43:20.787: Tnl 52784 L2TP: Control channel retransmit delay set to 1 seconds Jan 1
00:43:21.671: Se0:0 CHAP: I RESPONSE id 18 len 27 from "2500-1" Jan 1 00:43:21.671: Se0:0 VPDN:
LCP state already FORWARDING/FORWARDED, silent discard Jan 1 00:43:21.787: Tnl 52784 L2TP: O
Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0 Jan 1 00:43:21.787: Tnl 52784
L2TP: Control channel retransmit delay set to 2 seconds Jan 1 00:43:23.787: Tnl 52784 L2TP:
Timeout opening tunnel to 10.51.6.2 Jan 1 00:43:23.787: Tnl 42277 L2TP: Control channel
retransmit delay set to 4 seconds Jan 1 00:43:23.787: Se0:0 VPDN/: curlvl 2 Address 2:
10.51.6.2, priority 2 busy Jan 1 00:43:23.787: Se0:0 VPDN/: curlvl 2 Address 3: 10.51.6.3,
priority 2 Jan 1 00:43:23.787: VPDN: Free busy address 10.51.6.3 **Jan 1 00:43:23.787: Se0:0
VPDN/: Select non-active address 10.51.6.3, priority 2** Jan 1 00:43:23.787: Tnl 42277 L2TP:
Tunnel state change from wait-ctl-reply to idle Jan 1 00:43:23.787: Tnl 42277 L2TP: SM State

idle Jan 1 00:43:23.787: Tnl 42277 L2TP: O SCCRQ Jan 1 00:43:23.787: Tnl 42277 L2TP: Tunnel state change from idle to wait-ctl-reply Jan 1 00:43:23.787: Tnl 42277 L2TP: SM State wait-ctl-reply Jan 1 00:43:24.787: Tnl 42277 L2TP: O Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0 Jan 1 00:43:24.787: Tnl 42277 L2TP: Control channel retransmit delay set to 1 seconds Jan 1 00:43:25.787: Tnl 42277 L2TP: O Resend SCCRQ, flg TLS, ver 2, len 128, tnl 0, cl 0, ns 0, nr 0 Jan 1 00:43:25.787: Tnl 42277 L2TP: Control channel retransmit delay set to 2 seconds Jan 1 00:43:27.787: Tnl 42277 L2TP: Timeout opening tunnel to 10.51.6.3 Jan 1 00:43:27.787: Tnl 31770 L2TP: Control channel retransmit delay set to 4 seconds Jan 1 00:43:27.787: Se0:0 VPDN/: curlvl 2 Address 3: 10.51.6.3, priority 2 busy Jan 1 00:43:27.787: Se0:0 VPDN/: curlvl 2 Address 2: 10.51.6.2, priority 2 busy Jan 1 00:43:27.787: Se0:0 VPDN/: curlvl 3 Address 4: 10.51.6.82, priority 3 **Jan 1 00:43:27.787: Se0:0 VPDN/: Select non-active address 10.51.6.82, priority 3 !--- Eventually arrive at the IP Address 10.51.6.82 in Priority Group 3. !---** As this is valid, the Control Connection and session are established. Jan 1 00:43:27.787: Tnl 31770 L2TP: Tunnel state change from wait-ctl-reply to idle Jan 1 00:43:27.787: Tnl 31770 L2TP: SM State idle Jan 1 00:43:27.787: Tnl 31770 L2TP: O SCCRQ Jan 1 00:43:27.787: Tnl 31770 L2TP: Tunnel state change from idle to wait-ctl-reply Jan 1 00:43:27.787: Tnl 31770 L2TP: SM State wait-ctl-reply Jan 1 00:43:27.799: Tnl 31770 L2TP: I SCCRP from l2tp-gw Jan 1 00:43:27.799: Tnl 31770 L2TP: Got a challenge from remote peer, l2tp-gw Jan 1 00:43:27.799: Tnl 31770 L2TP: Got a response from remote peer, l2tp-gw Jan 1 00:43:27.799: Tnl 31770 L2TP: Tunnel Authentication success **Jan 1 00:43:27.799: Tnl 31770 L2TP: Tunnel state change from wait-ctl-reply to established** Jan 1 00:43:27.799: Tnl 31770 L2TP: O SCCCN to l2tp-gw tnlid 3843 Jan 1 00:43:27.799: Tnl 31770 L2TP: SM State established Jan 1 00:43:27.799: Se0:0 VPDN: Forwarding... Jan 1 00:43:27.799: Tnl/Cl 31770/7 L2TP: Session FS enabled Jan 1 00:43:27.799: Tnl/Cl 31770/7 L2TP: Session state change from idle to wait-for-tunnel Jan 1 00:43:27.803: Se0:0 Tnl/Cl 31770/7 L2TP: Create session Jan 1 00:43:27.803: Tnl 31770 L2TP: SM State established Jan 1 00:43:27.803: Se0:0 Tnl/Cl 31770/7 L2TP: O ICRQ to l2tp-gw 3843/0 Jan 1 00:43:27.803: Se0:0 Tnl/Cl 31770/7 L2TP: Session state change from wait-for-tunnel to wait-reply Jan 1 00:43:27.803: Se0:0 VPDN: 2500-1 is forwarded Jan 1 00:43:27.811: Se0:0 Tnl/Cl 31770/7 L2TP: O ICCN to l2tp-gw 3843/9 **Jan 1 00:43:27.811: Se0:0 Tnl/Cl 31770/7 L2TP: Session state change from wait-reply to established** Jan 1 00:43:28.803: %LINEPROTO-5-UPDOWN: Line protocol on Interface Serial0:0, changed state to up

関連情報

- [ロード バランシングおよびフェールオーバー用 RADIUS Tunnel Preference](#)
- [テクニカルサポートとドキュメント - Cisco Systems](#)