

SNMP : CatOS に関する FAQ

目次

[はじめに](#)

[SNMP を使用してスイッチをリロードするには、どうすればよいですか。](#)

[関連情報](#)

概要

このドキュメントには、Cisco の機器に関する SNMP の問題についてよく寄せられる質問に対する回答、および、ユーザが SNMP に関する有用なリソースを見つけるためのガイドが記載されています。

Q. SNMP を使用してスイッチをリロードするには、どうすればよいですか。

A. 次の手順に従います。

```
sysReset = .1.3.6.1.4.1.9.2.9.9 from the CISCO-STACK-MIB.my sysReset OBJECT-TYPE
-- FROM CISCO-STACK-MIB
SYNTAX Integer { other(1), reset(2), resetMinDown(3) }
MAX-ACCESS read-write
STATUS Current
DESCRIPTION "Writing reset(2) to this object resets the control logic of all modules in the
system. Writing
resetMinDown(3) to this object resets the system with the minimal system down time. The
resetMinDown(3) is
only supported in systems with redundant supervisors."

::= { iso(1) org(3) dod(6) internet(1) private(4) enterprises(1) cisco(9) workgroup(5)
ciscoStackMIB(1) systemGrp(1) 9 }
```

リロード コマンドをサポートするには、Cisco スイッチで **set snmp community read-write private** コマンドを実行する必要があります。

この例では、IP アドレスが 10.16.99.55 のルータをリロードします。

```
sysReset = .1.3.6.1.4.1.9.2.9.9 from the CISCO-STACK-MIB.my sysReset OBJECT-TYPE
-- FROM CISCO-STACK-MIB
SYNTAX Integer { other(1), reset(2), resetMinDown(3) }
MAX-ACCESS read-write
STATUS Current
DESCRIPTION "Writing reset(2) to this object resets the control logic of all modules in the
system. Writing
resetMinDown(3) to this object resets the system with the minimal system down time. The
resetMinDown(3) is
```

only supported in systems with redundant supervisors."

```
::= { iso(1) org(3) dod(6) internet(1) private(4) enterprises(1) cisco(9) workgroup(5)  
ciscoStackMIB(1) systemGrp(1) 9 }
```

この例で使用した変数について説明します。

```
sysReset = .1.3.6.1.4.1.9.2.9.9 from the CISCO-STACK-MIB.my sysReset OBJECT-TYPE  
-- FROM CISCO-STACK-MIB  
SYNTAX Integer { other(1), reset(2), resetMinDown(3) }  
MAX-ACCESS read-write  
STATUS Current  
DESCRIPTION "Writing reset(2) to this object resets the control logic of all modules in the  
system. Writing  
resetMinDown(3) to this object resets the system with the minimal system down time. The  
resetMinDown(3) is  
only supported in systems with redundant supervisors."  
  
::= { iso(1) org(3) dod(6) internet(1) private(4) enterprises(1) cisco(9) workgroup(5)  
ciscoStackMIB(1) systemGrp(1) 9 }
```

[関連情報](#)

- [IP アプリケーション サービスのテクニカル ティップス](#)
- [テクニカルサポート - Cisco Systems](#)