



INDEX

A

access control list (ACL) [4-36, 4-52](#)
aggressive VAD [4-8](#)
Apple iPhone
 DNS
 configuration [2-40](#)
 using [2-38](#)
 using with [2-38](#)
 guidelines for use [2-38](#)
 mobile client [2-38](#)
 wireless configuration [2-46](#)
 wireless network configuration for [2-41](#)
arbitration algorithm [2-15](#)
ARP commands [8-6](#)
Assured Forwarding [4-46](#)
assured forwarding 31 (AF31) [4-34](#)
Asynchronous Transfer Mode (ATM) [7-3](#)
Asynchronous Transfer Mode Peak Cell Rate (ATM PCR) [4-4](#)
ATM and Frame Relay Service Inter-Working (SIW) [7-3](#)
audio quality [4-2](#)

B

bandwidth
 codec affect on [4-5](#)
 consumption [4-5, 4-6](#)
 for unicast connection trunk [7-21](#)
 IDC consumption of [4-6](#)
 issues [4-4](#)
 leased lines [4-44](#)
 modifying consumption [4-7](#)

multicast over GRE [7-12](#)
over-provisioning [4-36](#)
planning [4-4](#)
point-to-point lines [4-44](#)
provisioning [4-2](#)
usage [4-5, 4-6](#)
voice payload [4-7](#)
bidirectional PIM [4-2, 4-3, 4-41](#)
bridging channels
 See also mixing
broadcast queue [4-38](#)
buffering [4-37](#)
burst [4-4, 4-36](#)

C

cabling, for VIC2-2E/M interface card [3-2](#)
call flow [2-26](#)
call leg [5-1, 5-4](#)
Carrier Operated Relay [3-10](#)
Carrier Operated Relay (COR) [4-8](#)
carrier operated relay (COR) [3-8](#)
Carrier Operated Squelch [3-10](#)
Carrier Operated Squelch (COS) [3-8, 4-8](#)
central site server solution [8-1, 8-2](#)
Cisco Hoot ‘n’ Holler
 channel mixing [2-15](#)
 use with LMR [3-1](#)
Cisco IOS
 arbitration algorithm [2-15](#)
 configuration for LMR gateway [3-7](#)
 queuing techniques [4-35](#)

Cisco IPICS

benefits [1-1](#)codec [4-4](#)

components

Cisco IPICS server [1-3](#)Cisco Unified IP Phone gateway [1-4](#)IDC [1-4](#)LMR gateway [1-4](#)mobile client [1-4](#)networking components [1-4](#)overview [1-2](#)RMS [1-4, 2-1](#)deployment models [7-1](#)markets [1-1](#)multiple site model [7-2](#)overview [1-1](#)RMS configuration for mixing [2-16](#)single site model [7-1](#)voice streams supported [2-10](#)WAN deployment issues [4-2](#)Cisco IPICS capacity [6-2](#)Cisco IPICS server [1-3](#)

Cisco IP Interoperability and Collaboration System

See Cisco IPICSCisco Multicast Manager (CMM) [4-53](#)Cisco Security Agent (CSA) [4-51](#)

Cisco Unified Communications Manager

configuration overview [2-47](#)IDC, configuration for [2-36](#)using with Cisco Unified IP Phone [2-47](#)

Cisco Unified Communications Manager Express

configuration [2-47](#)IDC, configuration for [2-36](#)using with Cisco Unified IP Phone [2-47](#)

Cisco Unified IP Phone

Cisco Communications Manager Express
configuration for [2-47](#)Cisco Unified Communications Manager
configuration for [2-47](#)configuring for Cisco IPICS [2-47](#)overview [1-4](#)services [2-47](#)Class-Based Weighted Fair Queueing (CBWFQ) [4-36](#)

codec

bandwidth use [4-5](#)choosing [4-4](#)considerations [4-4](#)delay [4-5](#)G.711 [4-4](#)G.729a [4-4](#)types in Cisco IPICS [4-4](#)voice quality [4-5](#)Committed Information Rate (CIR) [4-4, 4-36, 4-37](#)compressed RTP (cRTP) [4-6](#)connection trunk [7-13](#)cRTP [4-7](#)Customer Edge Router (CE) [7-4](#)

DData MDT [7-5, 7-9](#)Data Multicast Distribution Tree (MDT) [7-4](#)Default-MDT [7-4, 7-5](#)delay [4-2, 4-34, 4-37](#)dense mode (SM) [4-2](#)

deployment scenario

central site server solution [8-1, 8-2](#)remote IDC solution [8-1](#)remote locations solution [8-1, 8-3](#)destination pattern [5-3](#)

dial peer

associated with RMS [2-13](#)call leg [5-1, 5-4](#)configuration example [2-25](#)destination pattern [5-3](#)inbound [5-2](#)inbound call leg [5-4](#)matching inbound call leg [5-4](#)

- matching outbound call leg [5-4](#)
- outbound [5-2](#)
- outbound call leg [5-4](#)
- overview [5-1](#)
- POTS [5-2](#)
- session target [5-3](#)
- VoATM (Voice over ATM) [5-2](#)
- VoFR (Voice over Frame Relay) [5-2](#)
- voice-network [5-2](#)
- Voice over IP (VoIP) [5-2](#)

dial pool [6-4](#)

dial port, usage [6-3](#)

digital signal processor (DSP) [4-8](#)

discard eligible (DE) [4-37, 4-46](#)

DNS

- Apple iPhone [2-38](#)
- Cisco Mobile Client [2-38](#)
- Cisco Multiservices Platform Series, configuration for [2-40](#)

DS0

- allocation [2-2](#)
- channel optimization [2-9](#)
- conserving resources [6-2](#)
- loopback channels [2-2](#)
- remote location requirements [2-9](#)
- resource allocation [2-9, 2-24](#)
- resource consumption [2-7, 2-22](#)
- resources [2-21](#)
- resources not required [2-21](#)
- sizing considerations [6-1](#)
- usage [6-1](#)
- use in mixing channels [2-12](#)

DSCP per-hop behaviors (Fibs) [4-45](#)

DSP

- channel optimization [2-9](#)
- signal detection [4-8](#)

dspfarm [2-9](#)

duplicate packets [2-21](#)

E

E1 interface [2-12](#)

ear and mouth (E&M)

- analog signaling types [3-4](#)
- interface [3-1](#)
- interface card [3-4](#)
- port [4-39](#)
- Type III interface [3-5](#)
- Type II interface [3-4](#)
- Type V interface [3-6](#)

EF Johnson radios, configuring serial radio control for [3-54](#)

egress policing [4-46](#)

egress shaping [4-45](#)

endpoints

- communication between [2-7, 2-11](#)
- duplicate packets [2-21](#)

expedited forwarding (EF) [4-34](#)

F

feedback tones, for trunked radios [3-63](#)

firewall [4-52](#)

following [2-3](#)

Frame Relay

- broadcast queue [4-38](#)
- Committed Information Rate (CIR) in [4-37](#)
- connection with E&M port [4-39](#)
- in WAN [7-3](#)
- IP RTP Priority [4-35](#)
- LLQ [4-36](#)
- QoS [4-36](#)

Frame Relay Traffic Shaping (FRTS) [4-37](#)

FRF.12 fragmentation and reassembly technique [4-44](#)

G

G.711 [4-4, 7-2](#)

G.729a [4-4](#)

GRE tunnel [7-11](#)

H

high latency low bandwidth connection [8-1](#)

High-Level Data Link Control (HDLC) [4-44](#)

hootie

See Cisco Hoot 'n' Holler

I

IDC

bandwidth consumption [4-6](#)

overview [1-4](#)

remote location [2-24, 4-2, 4-47](#)

remote user [2-24](#)

IDC dialer

Cisco IPICS configuration for [2-37](#)

Cisco Unified Communications Manager,
configuration for [2-36](#)

Cisco Unified Communications Manager Express,
configuration for [2-36](#)

overview [2-35](#)

IDC upload log frequency, disabling [8-7](#)

Internet Explorer, adjusting browser settings [8-7](#)

Internet Group Management Protocol (IGMP) [2-17](#)

interoperability and collaboration [1-2](#)

iPhone

See Apple iPhone

IPICS Dispatch Center

See IDC

IPICS Mobile Client

Apple iPhone [2-38](#)

DNS, using with [2-38](#)

guidelines for use [2-38](#)

overview [2-38](#)

wireless network configuration for [2-41](#)

IP precedence [4-34](#)

IP RTP Priority [4-35](#)

IPSec VPN [7-13](#)

J

jitter [4-2, 4-35, 4-37](#)

L

land mobile radio

See LMR

land mobile radio gateway

configuring for E&M communication [3-56, 3-60](#)

configuring for serial radio control [3-57, 3-62](#)

connecting

EF Johnson radio to [3-55](#)

Sprint Nextel (iDEN) handset [3-59](#)

language pack, for text to speech (TTS) [2-50](#)

LEAF [7-4](#)

leased line [7-3](#)

licences

for Cisco IPICS [6-1](#)

Link Fragmentation and Interleaving (LFI) [4-44](#)

LMR

audio connection to Cisco IPICS [3-2](#)

channel [2-16](#)

communication with endpoints [2-16](#)

endpoints in [2-9](#)

gateway

Cisco IOS configuration for [3-7](#)

overview [3-1](#)

radio interface [3-2](#)

integration with Cisco IPICS [3-1](#)

interface with Cisco IPICS [3-2](#)

recording multicast traffic [3-68](#)

use with Cisco Hoot 'n' Holler [3-1](#)

loopback [2-2, 2-11, 2-12](#)

loopback interface [4-41](#)

Low-Latency Queuing (LLQ) [4-35](#), [4-36](#), [4-37](#)

LWAPP-based wireless network [2-46](#)

M

M1:U12:M2

connection trunk [7-16](#), [8-3](#)

description [7-13](#)

unicast connection trunk [4-6](#), [7-18](#)

with multicast singularities [7-22](#)

markets, for Cisco IPICS [1-1](#)

mixing

arbitration algorithm [2-15](#)

audio [2-17](#)

channels in VTG [2-11](#)

channels using Cisco Hoot 'n' Holler [2-15](#)

DSP function [4-8](#)

example [2-15](#)

unicast streams [2-24](#)

voice streams [2-17](#), [4-8](#)

mobile client

overview [1-4](#)

MPLS

in multiple site model [7-2](#)

VPN [7-3](#)

with multicast VPN [7-3](#)

multicast [2-24](#), [4-6](#), [7-2](#)

address for VTG communication [2-11](#)

address pool [2-2](#), [2-9](#)

bandwidth [7-12](#)

bidirectional PIM [4-41](#)

call flow to unicast [2-28](#)

endpoints, communication between [2-7](#)

GRE tunnel [7-24](#)

island

overview [7-10](#)

topology [7-10](#)

M1:U12:M2 connection trunk [7-24](#)

output stream [2-15](#)

over GRE [7-11](#)

singularity

GRE tunnel [7-22](#)

M1:U12:M2 connection trunk [7-22](#)

overview [7-21](#)

multicast address, guidelines for using [4-50](#)

multicast domain [7-2](#), [7-4](#), [7-5](#)

Multicast Virtual Route Forwarding (MVRF) [7-4](#)

multicast VPN (MVPN) [7-4](#)

provider network configuration for [7-5](#)

provider network verification [7-7](#)

routing [7-5](#)

Multilink Point-to-Point Protocol (MLPPP) [4-44](#)

multiple site model

connectivity options [7-3](#)

overview [7-2](#)

topology [7-3](#)

Multiprotocol Label Switching

See MPLS

N

network

management [4-52](#)

security in [4-51](#)

networking components, overview [1-4](#)

Nuance text to speech [2-48](#)

See also text to speech (TTS)

O

over-detection [4-8](#)

over-provisioning [4-36](#)

P

packet

buffering [4-37](#)

delay [4-34](#)
 discard-eligible (DE) [4-37](#)
 drop [4-37](#)
 errors [4-2](#)
 loss [4-2, 4-34, 4-37](#)
 packet rate [4-38](#)
 Permanent Virtual Circuit (PVC) [4-3](#)
 PIM-SSM [7-4](#)
 ping-pong effect [3-63](#)
 Plain Old Telephone Service (POTS), for unicast connection [2-26](#)
 point-to-point connection [4-44](#)
 Point-to-Point Protocol (PPP) [4-44](#)
 policing [4-46](#)
 pooled radio

- allocating [3-52](#)
- configuring [3-52](#)
- overview [3-51](#)

 Protocol Independent Multicast (PIM)

- bidirectional [4-2, 4-3](#)
- dense mode (DM) [4-2](#)
- overview [4-2](#)
- sparse mode (SM) [4-2](#)

 Provider Edge Router (PE) [7-4, 7-5](#)
 Provider Router (P) [7-4](#)
 proxy channel [7-15](#)

Q

QoS

- at WAN edge [4-45](#)
- factors affecting [4-34](#)
- in enterprise [4-46](#)
- in Frame Relay network [4-36](#)
- in LAN [4-45](#)
- in multiple site model [7-3](#)
- overview [4-34](#)
- policing [4-46](#)
- queuing [4-46](#)

recommendations for networks [4-34](#)
 trust boundary [4-46](#)
 WAN, use in [4-2](#)
 with point-to-point connections [4-44](#)
 Quality of Service

- See* QoS

 queuing

- overview [4-46](#)
- techniques [4-35, 4-37](#)

 queuing techniques [4-35](#)

R

RADIUS [4-52](#)
 Real-time Transport Protocol (RTP) [4-6](#)
 recording

- multicast LMR traffic [3-68](#)
- Tap Cisco IOS configuration [3-68](#)

 redundant RMS configuration [4-9](#)
 remote IDC solution [8-1](#)
 remote IDC user [2-24](#)
 remote location [2-2, 2-9, 2-24, 4-2, 4-47](#)
 remote locations solution [8-1, 8-3](#)
 rendezvous point (RP) [4-3, 4-41](#)
 Reverse Path Forwarding (RPF) [4-3](#)
 RMS

- active [4-9](#)
- bridging [2-15](#)
- configuration example [2-3](#)
- configuration for central site deployment scenario [8-5](#)
- configuration for remote locations deployment scenario [8-5](#)
- dial peers associated with [2-13](#)
- DS0 [2-2, 2-7, 2-9](#)
- DS0 resources [2-21, 2-22](#)
- failover [4-9](#)
- fall back [4-9](#)
- function [2-2](#)

- function in Cisco IPICS [2-7](#)
 - installation options [2-2](#)
 - in WAN that is not multicast enabled [4-6](#)
 - mixing [2-15, 2-16, 2-17](#)
 - overview [1-4](#)
 - redundancy [4-9](#)
 - resource allocation [2-9](#)
 - resource consumption [2-7, 2-9](#)
 - standby [4-9](#)
 - voice port configuration [2-15](#)
 - voice ports associated with [2-13](#)
- RMS comparator [8-6](#)
- router media service
- See* RMS
- RTP, header compression [4-7](#)
-
- S**
- satellite link [8-1](#)
- Secure Socket Layer (SSL) [4-51](#)
- security
- access control list (ACL) [4-52](#)
 - Cisco Security Agent (CSA) [4-51](#)
 - firewall [4-52](#)
 - for Cisco IPICS [4-51](#)
 - RADIUS [4-52](#)
 - recommendations [4-52](#)
 - Secure Socket Layer (SSL) [4-51](#)
 - spanning tree (STP) attack mitigation [4-52](#)
 - TACACS+ [4-52](#)
- serialization [4-35](#)
- serial radio control
- EF Johnson Radios
 - components required [3-54](#)
 - configuring LMR gateway for E&M communications [3-56](#)
 - configuring LMR gateway for serial radio control [3-57](#)
 - connecting to LMR gateway [3-55](#)
 - overview [3-54](#)
 - overview [3-54](#)
- Sprint Nextel (iDEN) handsets
- components required [3-59](#)
 - configuring handset [3-60](#)
 - configuring LMR gateway for E&M communication [3-60](#)
 - configuring LMR gateway for serial radio control [3-62](#)
 - connecting to LMR gateway [3-59](#)
 - overview [3-58](#)
- service access point (SAP) broadcast [4-38](#)
- session target [5-3](#)
- shared tree
- bidirectional [4-3](#)
 - forwarding traffic [4-3](#)
 - in PIM SIM [4-3](#)
 - unidirectional [4-3](#)
- single site model
- benefits [7-2](#)
 - best practices [7-2](#)
 - design characteristics [7-1](#)
 - overview [7-1](#)
 - topology [7-2](#)
- SIP
- connection to RMS using [2-24](#)
 - in remote location [4-2](#)
 - signaling flow [2-27](#)
 - unicast call, set up [2-26](#)
- SIP provider
- for policy engine [1-4](#)
- spanning tree (STP) attack mitigation [4-52](#)
- sparse mode (SM) [4-2](#)
- Sprint Nextel (iDEN) handset
- configuring serial radio control for [3-58](#)
- Sprint Nextel (iDEN handset)
- configuring for serial radio control [3-60](#)
- Sustained Cell Rate [4-4](#)

T

T1 interface [2-12](#)

TACACS+ [4-52](#)

text to speech (TTS)

- configuration and operation [2-51](#)
- configuring language pack [2-50](#)
- installing Nuance TTS [2-49](#)
- overview [2-48](#)

Time to Live (TTL) [2-29](#)

tone control

- 2-wire configuration for single frequency [3-39](#)
- 4-wire configuration for single frequency [3-40](#)
- channel configurations in Cisco IPICS [3-50](#)
- configuration for two-ten frequencies [3-41](#)
- considerations [3-12](#)
- frequencies [3-16](#)
- manual tone configuration [3-14](#)
- native functionality [3-12](#)
- overview [3-1](#)
- phases [3-15](#)
- signaling [3-8, 3-15](#)

topology

- MPLS with multicast VPN [7-4](#)
- multicast island [7-10](#)
- multiple site model [7-3](#)
- single site model [7-2](#)

trunked radio

- feedback tones [3-63](#)
- hybrid configuration [3-64](#)

trust boundary [4-46](#)

TTS server [2-49](#)

U

UDP port [4-35](#)

under-detection [4-8](#)

unicast

- call flow to multicast [2-28](#)

connection set up [2-27](#)

connection trunk [7-18](#)

in WAN that is not multicast enabled [4-6](#)

POTS use for connection [2-26](#)

stream mixing [2-24](#)

V

VIC2-2E/M interface card

- cabling [3-2](#)
- overview [3-2](#)

virtual interface (VIF) [2-15](#)

Virtual Private Network (VPN) [7-3](#)

virtual talk group

- See* VTG

voice activation detection (VAD)

- aggressive [4-8](#)
- conventional [4-8](#)
- enabling [4-8](#)
- overview [4-8](#)
- use with LMR [3-8](#)

Voice and Video Enabled IP Security Protocol (IPSec) [7-3](#)

voice packet [4-7](#)

voice payload [4-7](#)

voice port

- associating IP address with [2-15](#)
- configuration example [2-25](#)

voice quality [4-5, 4-8, 4-34, 4-38](#)

voice stream mixing

- See* mixing

voice streams, supported in Cisco IPICS [2-10](#)

VoIP bearer traffic [4-47](#)

VoIP traffic, transmission rate [4-5](#)

VPN [7-4](#)

VTG

- about [2-11](#)
- communication between channels [2-11](#)
- creation [2-11](#)

LMR endpoints in [2-9](#)
members [2-11](#)
mixing channels in [2-15](#)
mixing of channels [2-11](#)
multicast address [2-11](#)
multicast address requirements [2-9](#)
participants speaking simultaneously [2-15](#)
restricting access [2-23](#)
RMS resource consumption [2-9](#)

W

Weighted-Fair Queuing (WFQ) [4-35](#)

