



Cisco WSDL

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:s="http://www.w3.org/2001/XMLSchema"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:tns="http://cisco.com/CiscoQuery"
xmlns:tm="http://microsoft.com/wsdl/mime/textMatching/"
xmlns:mime="http://schemas.xmlsoap.org/wsdl/mime/"
targetNamespace="http://cisco.com/CiscoQuery"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
<wsdl:types>
<s:schema elementFormDefault="qualified"
targetNamespace="http://cisco.com/CiscoQuery">

<s:complexType name="ArrayOfString">
<s:sequence>
<s:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="s:string" />
</s:sequence>
</s:complexType>
<s:element name="QuerySubscriberIn">
<s:complexType>
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="subscriberId" type="s:string"/>
<s:element minOccurs="0" maxOccurs="1" name="mappings" type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="keys" type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="values" type="tns:ArrayOfString"/>
</s:sequence>
</s:complexType>
</s:element>
<s:element name="QuerySubscriberOut">
<s:complexType>
<s:sequence>
<s:element minOccurs="0" maxOccurs="1" name="subscriberId" type="s:string"/>
<s:element minOccurs="0" maxOccurs="1" name="mappings" type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="propertiesKeys"
type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="propertiesValues"
type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="keys" type="tns:ArrayOfString"/>
<s:element minOccurs="0" maxOccurs="1" name="values" type="tns:ArrayOfString"/>
</s:sequence>
</s:complexType>
</s:element>
</s:schema>
</wsdl:types>
<wsdl:message name="QuerySubscriberSoapIn">
<wsdl:part name="parameters" element="tns:QuerySubscriberIn" />
</wsdl:message>
<wsdl:message name="QuerySubscriberSoapOut">
<wsdl:part name="parameters" element="tns:QuerySubscriberOut" />
</wsdl:message>
```

```
<wsdl:portType name="QueryServiceSoap">
<wsdl:operation name="QuerySubscriber">
<wsdl:input message="tns:QuerySubscriberSoapIn" />
<wsdl:output message="tns:QuerySubscriberSoapOut" />
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="QueryServiceSoap" type="tns:QueryServiceSoap">
<soap:binding transport="http://schemas.xmlsoap.org/soap/http" style="document" />
<wsdl:operation name="QuerySubscriber">
<soap:operation soapAction="http://cisco.com/CiscoQuery/QuerySubscriber"
style="document" />
<wsdl:input>
<soap:body use="literal" />
</wsdl:input>
<wsdl:output>
<soap:body use="literal" />
</wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="QueryService">
<documentation xmlns="http://schemas.xmlsoap.org/wsdl/">Queries subscribers
data</documentation>
<wsdl:port name="QueryServiceSoap" binding="tns:QueryServiceSoap">
<soap:address location="http://localhost:8080/axis/services/QueryServiceSoap" />
</wsdl:port>
</wsdl:service>
</wsdl:definitions>
```