

Umbrella 로밍 클라이언트 파일 및 폴더

목차

[소개](#)

[창](#)

[OS X](#)

소개

이 문서에서는 Windows 및 Mac OS X용 Umbrella 로밍 클라이언트에서 설치한 각 파일 및 폴더의 용도를 설명합니다. 이 정보를 사용하여 Umbrella 로밍 클라이언트에 대한 작업 지식을 높이거나 손상된 설치를 처리할 수 있습니다.

창

<#root>

Service Name: "Umbrella_RC"

C:\ProgramData\OpenDNS\ERC\

beacon-logs\

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

Upgrades\

Folder containing temp files when automatically updating to the latest version.

Config.json

Contains the unique "Device" and "Origin" ID's specific to this Umbrella roaming client. This file

OpenDNS_ERC_Service.log

Live log of the Umbrella roaming client's running process. Used for Umbrella troubleshooting.

OpenDNS_ERC_UI.log

Live log of the Umbrella roaming client's tray icon process. Used for Umbrella troubleshooting.

OrgInfo.json

Contains information about the install-time parameters specified during installations, and also co

PersistedNicDefaults.json

A file for storing the DNS settings assigned to a computer before the Umbrella roaming client initialization. We keep the information in this file in order to gracefully restore the network-defined DNS servers.

`proxy_whitelist.txt`

The "Internal Domains" list downloaded from the dashboard, as well as DNS Suffixes imported from the network to the local DNS servers. Read more at [Roaming Client: Internal Domains](#).

`*Network Connection Name*-resolv.conf`

Each active Network Interface on the computer will have its own .conf file, (ie: Local Area Connection). These files contain the DNS servers that belong to which networking interface. These files contain the local DNS servers.

`RoamingProfile.json`

A file to be used as part of a future feature.

`sync-latest.json`

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umbrella roaming client synchronization.

`whitelist.txt`

The "Internal Domains" list downloaded from the Umbrella dashboard which is used by the Umbrella roaming client. It is a temporary file, read from the "proxy_whitelist.txt" file, which is used as a temporary file. Read more at [Roaming Client: Internal Domains](#).

`C:\Program Files (x86)\OpenDNS\Umbrella Roaming Client\`

`dnscryptproxy.exe`

In Umbrella Roaming client 3.0 and above, this is the executable used for encrypting, authenticating, and managing DNS traffic.

`dnscrypt-proxy.exe (deprecated in 2.3)`

Used in Umbrella Roaming client versions before 2.3. It has been superseded by dnscryptproxy.exe.

`ERCInterface.exe`

The executable used for running the tray icon.

`UmbrellaDiagnostic.exe`

The built-in diagnostic tool which customers or Support can run for troubleshooting purposes.

`*.dll`

Dynamic Load Libraries associated with running different facets of the Umbrella roaming client.

`ERCInterface.exe.config`

.NET framework configuration file for the ERCInterface.exe executable.

`ERCSERVICE.exe.config`

.NET framework configuration file for the ERCSERVICE.exe executable.

Logging.config

Configuration file used for instructing the Umbrella roaming client what to log or not log. Controls

UmbrellaDiagnostic.exe.config

.NET framework configuration file for the UmbrellaDiagnostic.exe executable.

GetNetStats.bat

A facilitating script to assist with getting information as part of the Umbrella Diagnostic tool.

OS X

<#root>

/Library/Application Support/OpenDNS Roaming Client

beacon-logs/

Folder containing log files kept by the Umbrella roaming client for troubleshooting and diagnostic

Updater.plist

Local configuration data unique to the local installation of the Umbrella roaming client.

com.opendns.osx.DNSCryptProxy.plist

The configuration file used to set runtime parameters for the dns-updater executable.

dns-updater

The executable used for encrypting, authenticating, and sending DNS queries. This executable is re

localdomains

The list of domain names that the Umbrella roaming client treats as local resources and queries the

p12.hash

Hash file to verify integrity of clientCert.p12 file.

sync-latest.plist

The latest copy of the profile information specific to each Umbrella roaming client. Used for Umb

erc_state.plist

Data that is synced with our API to populate the Umbrella dashboard with information about the Umb

`resolve_orig.conf`

We use this list to keep an ordered list of DNS servers used for Internal DNS resolution. The list contains VPN DNS servers first. These are the DNS servers normally found on the NIC settings which are [hidden](#).

`/Library/LaunchDaemons/`

`com.opendns.osx.RoamingClientConfigUpdater.plist`

The configuration file for running the Umbrella roaming client.

`/Library/LaunchAgents/`

`com.opendns.osx.RoamingClientMenubar.plist`

The configuration file for running the menu bar icon of the Umbrella roaming client.

이 번역에 관하여

Cisco는 전 세계 사용자에게 다양한 언어로 지원 콘텐츠를 제공하기 위해 기계 번역 기술과 수작업 번역을 병행하여 이 문서를 번역했습니다. 아무리 품질이 높은 기계 번역이라도 전문 번역가의 번역 결과물만큼 정확하지는 않습니다. Cisco Systems, Inc.는 이 같은 번역에 대해 어떠한 책임도 지지 않으며 항상 원본 영문 문서(링크 제공됨)를 참조할 것을 권장합니다.