

Hoe kan ik ronde verbindingsstijl in Cisco e-mail security applicatie configureren?

Inhoud

Inleiding

[Hoe kan ik ronde verbindingsstijl in Cisco e-mail security applicatie \(ESA\) configureren?](#)

Inleiding

Dit document beschrijft hoe u de uitgaande verbinding op Cisco e-mail security applicatie (ESR) in ronde-robin stijl kunt balanceren.

Hoe kan ik ronde verbindingsstijl in Cisco e-mail security applicatie (ESA) configureren?

In AsyncOS kunt u ronde robin levering configureren met behulp van de opdracht **smtproutes**.
Elke nieuwe verbinding
maakt zal tussen de geconfigureerde servers springen . Merk op dat dit alleen nieuwe
verbindingen in balans maakt
gemaakt op de doelserver en niet het aantal e-mails dat naar beneden wordt gestuurd.

```
mail.example.com> smtproutes
There are no routes configured.
Choose the operation you want to perform:
- NEW - Create a new route.
- IMPORT - Import new routes from a file.
[]> new
Enter the hostname for which you want to set up a permanent route.
Partial hostnames such as ".example.com" are allowed.
Use "ALL" for the default route.
[]> ironport.com
Enter the destination hosts, separated by commas, which you want mail for
ironport.com to be delivered.
Enter /dev/null by itself if you wish to discard the mail.
[]>192.168.0.1,192.168.0.2,192.168.0.3
Mapping for ironport.com to 192.168.0.1, 192.168.0.2, 192.168.0.3 created.
There are currently 1 routes configured.
Choose the operation you want to perform:
- NEW - Create a new route.
- DELETE - Remove a route.
- PRINT - Display all routes.
- IMPORT - Import new routes from a file.
- EXPORT - Export all routes to a file.
- CLEAR - Remove all routes.
[]>
```