

IOS Router para passar um túnel IPSec de LAN para LAN através do exemplo de configuração da PANCADINHA

Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenções](#)

[Configurar](#)

[Diagrama de Rede](#)

[Configurações com NAT Transparency de IPSec](#)

[Configurações sem transparência de NAT de IPSec](#)

[Verificar](#)

[Verificar com NAT Transparency de IPSec](#)

[Verifique sem transparência de NAT de IPSec](#)

[Troubleshooting](#)

[Solucione os problemas com a transparência NAT de IPSec](#)

[Troubleshooting sem IPSec NAT Transparency](#)

[Informações Relacionadas](#)

[Introdução](#)

Este documento fornece uma configuração de exemplo de Tradução de Endereço de Porta (PAT) para permitir que seja estabelecido um túnel IPSec LAN a LAN. Aplica-se às encenações que têm somente um endereço IP público (usado em um roteador de Cisco IOS® para executar a PANCADINHA em todo o tráfego) e o precisam de passar um túnel de IPsec com ele.

Para os gateways de VPN que executam Cisco IOS Software Release mais cedo do que 12.2(13)T, a característica da transmissão do IPsec é precisada no roteador que executa a PANCADINHA para permitir completamente o Encapsulating Security Payload (ESP).

Note: Esta característica é sabida como o IPsec através do apoio do Network Address Translation (NAT) no [consultivo de software \(clientes registrados somente\)](#).

Para iniciar o túnel no correspondente local (PATed), não é necessária nenhuma configuração. A fim de iniciar o túnel em um correspondente remoto, estes comandos são necessários:

- IP da estática de origem *relação* interna nat da relação do *inside_ip esp*
- ip nat inside source static udp inside_ip 500 interface interface 500

Com relação a VPN Gateways que funcionam em um Cisco IOS Software Release posterior a 12.2(13)T, o tráfego de IPSec é encapsulado nos pacotes 4500 da porta do Protocolo de dados do usuário (UDP). Esta característica é sabida como a [transparência de NAT de IPSec](#). Para iniciar o túnel no correspondente local (PATed), não é necessária nenhuma configuração.

A fim de iniciar o túnel em um correspondente remoto, estes comandos são necessários:

- `ip nat inside source static udp inside_ip 4500 interface 4500`
- `ip nat inside source static udp inside_ip 500 interface interface 500`

[Emita o comando no crypto ipsec nat-transparency udp-encaps para desativar o IPSec NAT Transparency.](#)

Pré-requisitos

Requisitos

Não existem requisitos específicos para este documento.

Componentes Utilizados

A informação neste documento é baseada no Cisco IOS Software Release 12.3(7)T1.

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto potencial de qualquer comando.

Convenções

Para obter mais informações sobre convenções de documento, consulte as [Convenções de dicas técnicas Cisco](#).

Configurar

Nesta seção, você encontrará informações para configurar os recursos descritos neste documento.

Diagrama de Rede

Este documento utiliza a seguinte configuração de rede:

Configurações com NAT Transparency de IPSec

Este documento utiliza as seguintes configurações:

- [VPN-Gateway1](#)
- [PAT-Router](#)
- [VPN-Gateway2](#)

VPN-Gateway1

```
VPN-Gateway1#show running-config
Building configuration...

Current configuration : 1017 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname VPN-Gateway1
!

!--- VPN Gateway1 and VPN Gateway2 can be any devices
that !--- perform IPsec. For detailed information on
configuring IPsec !--- refer to IPsec Technology Support
Information. !--- IPsec configuration between VPN
Gateway1 and VPN Gateway2 !--- is beyond the scope of
this document. boot-start-marker boot-end-marker !!
clock timezone EST 0 no aaa new-model ip subnet-zero !!
ip audit po max-events 100 no ftp-server write-enable !
!!!! !--- IKE policies (phase 1). crypto isakmp
policy 10
  authentication pre-share
crypto isakmp key cisco123 address 209.165.201.2
!
!
crypto ipsec transform-set basic esp-des esp-md5-hmac
!
!--- IPsec policies (phase 1). crypto map mymap 10
ipsec-isakmp
  set peer 209.165.201.2
  set transform-set basic
  match address 101
!
!
!
interface Ethernet0/0
  ip address 192.168.1.1 255.255.255.0
!
interface Serial1/0
  ip address 209.165.200.2 255.255.255.252
  serial restart-delay 0
  crypto map mymap
!
ip classless
ip route 0.0.0.0 0.0.0.0 209.165.200.1
no ip http server
no ip http secure-server
!
!
!
access-list 101 permit ip 192.168.1.0 0.0.0.255
172.16.2.0 0.0.0.255
access-list 101 remark Crypto ACL
!
!
!
control-plane
!
!
```

```
line con 0
line aux 0
line vty 0 4
!
!
end
```

PAT-Router

```
PAT-Router#show running-config
Building configuration...

Current configuration : 971 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname PAT-Router
!
boot-start-marker
boot-end-marker
!
!
clock timezone EST 0
no aaa new-model
ip subnet-zero
!
!
ip audit po max-events 100
no ftp-server write-enable
!
!
!
!
no crypto isakmp enable
!
!
!
interface Ethernet0/0
 ip address 172.16.1.1 255.255.255.0
!--- This declares the interface as inside for NAT
purposes. ip nat inside
!
interface Serial1/0
 ip address 209.165.201.2 255.255.255.224
!--- This declares the interface as !--- outside for NAT
purposes. ip nat outside
 serial restart-delay 0
!
ip classless
ip route 0.0.0.0 0.0.0.0 209.165.201.1
ip route 172.16.0.0 255.255.0.0 172.16.1.2
no ip http server
no ip http secure-server
!
ip nat inside source list 1 interface Serial1/0 overload
!--- This allows PAT to be used for regular Internet
traffic. ip nat inside source static udp 172.16.1.2 4500
interface Serial1/0 4500
!--- This permits IPsec traffic destined for the
Serial1/0 !--- interface to be sent to the inside IP
```

```
address 172.16.1.2. ip nat inside source static udp
172.16.1.2 500 interface Serial1/0 500
!--- This allows UDP traffic for the Serial1/0 interface
to be !--- statically mapped to the inside IP address
172.16.1.2. !--- This is required for the Internet
Security Association !--- and Key Management Protocol
(ISAKMP) negotiation to be !--- initiated from VPN-
Gateway1 to VPN-Gateway2. !! access-list 1 permit
172.16.0.0 0.0.255.255
!
!
!
control-plane
!
!
line con 0
line aux 0
line vty 0 4
!
!
end
```

VPN-Gateway2

```
VPN-Gateway2#show running-config
Building configuration...

Current configuration : 986 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname VPN-Gateway2
!

!--- VPN Gateway1 and VPN Gateway2 can be any devices !-
-- that perform IPsec. For detailed information on !---
IPsec configuration refer to IPsec Technology Support
Information. !--- IPsec configuration between VPN
Gateway1 and VPN Gateway2 !--- is beyond the scope of
this document. boot-start-marker boot-end-marker !!
clock timezone EST 0 no aaa new-model ip subnet-zero !!
ip audit po max-events 100 no ftp-server write-enable !
!!!! !--- IKE policies (phase 1). crypto isakmp
policy 10
  authentication pre-share
crypto isakmp key cisco123 address 209.165.200.2
!
!
crypto ipsec transform-set basic esp-des esp-md5-hmac
!
!--- IPsec policies (phase 1). crypto map mymap 10
ipsec-isakmp
  set peer 209.165.200.2
  set transform-set basic
  match address 101
!
!
!
interface Ethernet0/0
  ip address 172.16.1.2 255.255.255.0
```

```

crypto map mymap
!
interface Ethernet1/0
 ip address 172.16.2.1 255.255.255.0
!
ip classless
ip route 0.0.0.0 0.0.0.0 172.16.1.1
no ip http server
no ip http secure-server
!
!
!
access-list 101 permit ip 172.16.2.0 0.0.0.255
192.168.1.0 0.0.0.255
access-list 101 remark Crypto ACL
!
!
!
control-plane
!
!
!
line con 0
line aux 0
line vty 0 4
!
!
end

```

Configurações sem transparência de NAT de IPSec

- [VPN-Gateway1](#)
- [PAT-Router](#)
- [VPN-Gateway2](#)

```

VPN-Gateway1
VPN-Gateway1#show running-config
Building configuration...

Current configuration : 1017 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname VPN-Gateway1
!

!--- VPN Gateway1 and VPN Gateway2 can be any devices !-
-- that perform IPSec. For detailed information on !---
IPSec configuration refer to IPSec Technology Support
Information. !--- IPSec configuration between VPN
Gateway1 and VPN Gateway2 !--- is beyond the scope of
this document. boot-start-marker boot-end-marker ! !
clock timezone EST 0 no aaa new-model ip subnet-zero ! !
ip audit po max-events 100 no ftp-server write-enable !
! ! ! ! !--- IKE policies (phase 1). crypto isakmp
policy 10
 authentication pre-share

```

```
crypto isakmp key cisco123 address 209.165.201.2
!
!
crypto ipsec transform-set basic esp-des esp-md5-hmac
!
!--- IPsec policies (phase 1). crypto map mymap 10
ipsec-isakmp
  set peer 209.165.201.2
  set transform-set basic
  match address 101
!
!
!
interface Ethernet0/0
  ip address 192.168.1.1 255.255.255.0
!
interface Serial1/0
  ip address 209.165.200.2 255.255.255.252
  serial restart-delay 0
  crypto map mymap
!
ip classless
ip route 0.0.0.0 0.0.0.0 209.165.200.1
no ip http server
no ip http secure-server
!
!
!
access-list 101 permit ip 192.168.1.0 0.0.0.255
172.16.2.0 0.0.0.255
access-list 101 remark Crypto ACL
!
!
!
control-plane
!
!
line con 0
line aux 0
line vty 0 4
!
!
end
```

PAT-Router

```
PAT-Router#show running-config
Building configuration...

Current configuration : 971 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname PAT-Router
!
boot-start-marker
boot-end-marker
!
!
clock timezone EST 0
```

```

no aaa new-model
ip subnet-zero
!
!
ip audit po max-events 100
no ftp-server write-enable
!
!
!
!
no crypto isakmp enable
!
!
!
interface Ethernet0/0
 ip address 172.16.1.1 255.255.255.0
 !--- This declares the interface as inside for NAT
 purposes. ip nat inside
!
interface Serial1/0
 ip address 209.165.201.2 255.255.255.224
 !--- This declares the interface as !--- outside for NAT
 purposes. ip nat outside
 serial restart-delay 0
!
ip classless
ip route 0.0.0.0 0.0.0.0 209.165.201.1
ip route 172.16.0.0 255.255.0.0 172.16.1.2
no ip http server
no ip http secure-server
!
ip nat inside source list 1 interface Serial1/0 overload
!--- This allows PAT to be used for regular Internet
 traffic. ip nat inside source static esp 172.16.1.2
interface Serial1/0
!--- This permits the IPSec ESP tunnel mode !---
 destined for the Serial1/0 interface to be sent !--- to
 the inside IP address 172.16.1.2. The "esp" !--- option
 allows a single ESP tunnel-mode !--- VPN setup to be
 possible. ip nat inside source static udp 172.16.1.2 500
interface Serial1/0 500
!--- This allows UDP traffic for the Serial1/0 !---
 interface to be statically mapped to the inside !--- IP
 address 172.16.1.2. This is required !--- for the ISAKMP
 negotiation to be initiated !--- from VPN-Gateway1 to
 VPN-Gateway2. !! access-list 1 permit 172.16.0.0
0.0.255.255
!
!
!
control-plane
!
!
line con 0
line aux 0
line vty 0 4
!
!
end

```

VPN-Gateway2

```
VPN-Gateway2#show running-config
```



```
Building configuration...

Current configuration : 986 bytes
!
version 12.3
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname VPN-Gateway2
!

!--- VPN Gateway1 and VPN Gateway2 can be any devices !-
-- that perform IPsec. For detailed information on !---
IPsec configuration refer to IPsec Technology Support
Information. !--- IPsec configuration between VPN
Gateway1 and VPN Gateway2 !--- is beyond the scope of
this document. boot-start-marker boot-end-marker ! !
clock timezone EST 0 no aaa new-model ip subnet-zero ! !
ip audit po max-events 100 no ftp-server write-enable !
! ! ! ! !--- IKE policies (phase 1). crypto isakmp
policy 10
    authentication pre-share
crypto isakmp key cisco123 address 209.165.200.2
!
!
crypto ipsec transform-set basic esp-des esp-md5-hmac
no crypto ipsec nat-transparency udp-encaps
!
!--- IPsec policies (phase 1). crypto map mymap 10
ipsec-isakmp
    set peer 209.165.200.2
    set transform-set basic
    match address 101
!
!
!
interface Ethernet0/0
    ip address 172.16.1.2 255.255.255.0
    crypto map mymap
!
interface Ethernet1/0
    ip address 172.16.2.1 255.255.255.0
!
ip classless
ip route 0.0.0.0 0.0.0.0 172.16.1.1
no ip http server
no ip http secure-server
!
!
!
access-list 101 permit ip 172.16.2.0 0.0.0.255
192.168.1.0 0.0.0.255
access-list 101 remark Crypto ACL
!
!
!
control-plane
!
!
line con 0
line aux 0
line vty 0 4
!
```

```
!  
end
```

Verificar

Estas seções fornecem informações que podem ser utilizadas para confirmar se a configuração está funcionando adequadamente.

A [Output Interpreter Tool \(somente clientes registrados\)](#) oferece suporte a determinados comandos show, o que permite exibir uma análise da saída do comando show.

- [Verificar com NAT Transparency de IPsec](#)
- [Verifique sem transparência de NAT de IPsec](#)

Verificar com NAT Transparency de IPsec

- **mostre isakmp cripto sa** — Indica todas as associações de segurança atuais do Internet Key Exchange (IKE) (SA) em um par.

```
VPN-Gateway1#show crypto isakmp sa  
dst          src          state          conn-id slot  
209.165.200.2 209.165.201.2 QM_IDLE        1      0
```

```
VPN-Gateway2#show crypto isakmp sa  
dst          src          state          conn-id slot  
209.165.200.2 172.16.1.2   QM_IDLE        1      0
```

- **show crypto ipsec sa** - Exibe SAs de IPsec criados entre os correspondentes.

```
VPN-Gateway1#show crypto ipsec sa  
  
!--- This command is issued after a ping !--- is attempted from PC2 to PC1. interface:  
Serial1/0 Crypto map tag: mymap, local addr. 209.165.200.2 protected vrf: local ident  
(addr/mask/prot/port): (192.168.1.0/255.255.255.0/0/0) remote ident (addr/mask/prot/port):  
(172.16.2.0/255.255.255.0/0/0) current_peer: 209.165.201.2:4500 PERMIT,  
flags={origin_is_acl,} #pkts encaps: 6, #pkts encrypt: 6, #pkts digest: 6 #pkts decaps: 6,  
#pkts decrypt: 6, #pkts verify: 6 #pkts compressed: 0, #pkts decompressed: 0 #pkts not  
compressed: 0, #pkts compr. failed: 0 #pkts not decompressed: 0, #pkts decompress failed: 0  
#send errors 0, #recv errors 0 local crypto endpt.: 209.165.200.2, remote crypto endpt.:  
209.165.201.2 path mtu 1500, media mtu 1500 current outbound spi: 9CCA0619 inbound esp sas:  
spi: 0x4E6B990F(1315674383) transform: esp-des esp-md5-hmac , in use settings = {Tunnel UDP-  
Encaps, } slot: 0, conn id: 2000, flow_id: 5, crypto map: mymap crypto engine type:  
Software, engine_id: 1 sa timing: remaining key lifetime (k/sec): (4602622/3489)  
ike_cookies: 8973C578 9C7DEB45 5C9BE6DC 7F737D09 IV size: 8 bytes replay detection support:  
Y inbound ah sas: inbound pcp sas: outbound esp sas: spi: 0x9CCA0619(2630485529) transform:  
esp-des esp-md5-hmac , in use settings = {Tunnel UDP-Encaps, } slot: 0, conn id: 2001,  
flow_id: 6, crypto map: mymap crypto engine type: Software, engine_id: 1 sa timing:  
remaining key lifetime (k/sec): (4602622/3489) ike_cookies: 8973C578 9C7DEB45 5C9BE6DC  
7F737D09 IV size: 8 bytes replay detection support: Y outbound ah sas: outbound pcp sas:  
VPN-Gateway2#show crypto ipsec sa
```

```
!--- This command is issued after a ping !--- is attempted from PC2 to PC1. interface:  
Ethernet0/0 Crypto map tag: mymap, local addr. 172.16.1.2 protected vrf: local ident  
(addr/mask/prot/port): (172.16.2.0/255.255.255.0/0/0) remote ident (addr/mask/prot/port):  
(192.168.1.0/255.255.255.0/0/0) current_peer: 209.165.200.2:4500 PERMIT,  
flags={origin_is_acl,} #pkts encaps: 23, #pkts encrypt: 23, #pkts digest: 23 #pkts decaps:  
16, #pkts decrypt: 16, #pkts verify: 16 #pkts compressed: 0, #pkts decompressed: 0 #pkts not  
compressed: 0, #pkts compr. failed: 0 #pkts not decompressed: 0, #pkts decompress failed: 0  
#send errors 7, #recv errors 0 local crypto endpt.: 172.16.1.2, remote crypto endpt.:  
209.165.200.2 path mtu 1500, media mtu 1500 current outbound spi: 4E6B990F inbound esp sas:
```

```
spi: 0x9CCA0619(2630485529) transform: esp-des esp-md5-hmac , in use settings ={Tunnel UDP-Encaps, } slot: 0, conn id: 2000, flow_id: 1, crypto map: mymap crypto engine type: Software, engine_id: 1 sa timing: remaining key lifetime (k/sec): (4384024/3481) ike_cookies: 5C9BE6DC 7F737D09 8973C578 9C7DEB45 IV size: 8 bytes replay detection support: Y inbound ah sas: inbound pcp sas: outbound esp sas: spi: 0x4E6B990F(1315674383) transform: esp-des esp-md5-hmac , in use settings ={Tunnel UDP-Encaps, } slot: 0, conn id: 2001, flow_id: 2, crypto map: mymap crypto engine type: Software, engine_id: 1 sa timing: remaining key lifetime (k/sec): (4384024/3481) ike_cookies: 5C9BE6DC 7F737D09 8973C578 9C7DEB45 IV size: 8 bytes replay detection support: Y outbound ah sas: outbound pcp sas:
```

- **show ip nat translations - Exibe as conversões NAT ativas.**

```
PAT-Router#show ip nat translations
Pro Inside global      Inside local      Outside local      Outside global
udp 209.165.201.2:500  172.16.1.2:500   ---                ---
udp 209.165.201.2:4500 172.16.1.2:4500 ---                ---
```

Verifique sem transparência de NAT de IPSec

- **show crypto isakmp sa – Exibe todas as SAs de IKE atuais em um correspondente.**

```
VPN-Gateway1#show crypto isakmp sa
dst          src          state          conn-id slot
209.165.200.2 209.165.201.2 QM_IDLE          1      0
```

```
VPN-Gateway2#show crypto isakmp sa
dst          src          state          conn-id slot
209.165.200.2 172.16.1.2   QM_IDLE          1      0
```

- **show crypto ipsec sa - Exibe SAs de IPSec criados entre os correspondentes.**

```
VPN-Gateway1#show crypto ipsec sa
```

```
!--- This command is issued after a ping !--- is attempted from PC2 to PC1. interface:
Serial1/0 Crypto map tag: mymap, local addr. 209.165.200.2 protected vrf: local ident
(addr/mask/prot/port): (192.168.1.0/255.255.255.0/0/0) remote ident (addr/mask/prot/port):
(172.16.2.0/255.255.255.0/0/0) current_peer: 209.165.201.2:500 PERMIT,
flags={origin_is_acl,} #pkts encaps: 21, #pkts encrypt: 21, #pkts digest: 21 #pkts decaps:
15, #pkts decrypt: 15, #pkts verify: 15 #pkts compressed: 0, #pkts decompressed: 0 #pkts not
compressed: 0, #pkts compr. failed: 0 #pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 4, #recv errors 0 local crypto endpt.: 209.165.200.2, remote crypto endpt.:
209.165.201.2 path mtu 1500, media mtu 1500 current outbound spi: E89A0245 inbound esp sas:
spi: 0xB5F867BC(3052955580) transform: esp-des esp-md5-hmac , in use settings ={Tunnel, }
slot: 0, conn id: 2000, flow_id: 7, crypto map: mymap crypto engine type: Software,
engine_id: 1 sa timing: remaining key lifetime (k/sec): (4538665/3553) ike_cookies: 8973C578
DD91CB42 5C9BE6DC 63813771 IV size: 8 bytes replay detection support: Y inbound ah sas:
inbound pcp sas: outbound esp sas: spi: 0xE89A0245(3902407237) transform: esp-des esp-md5-
hmac , in use settings ={Tunnel, } slot: 0, conn id: 2001, flow_id: 8, crypto map: mymap
crypto engine type: Software, engine_id: 1 sa timing: remaining key lifetime (k/sec):
(4538665/3553) ike_cookies: 8973C578 DD91CB42 5C9BE6DC 63813771 IV size: 8 bytes replay
detection support: Y outbound ah sas: outbound pcp sas: VPN-Gateway2#show crypto ipsec sa
```

```
!--- This command is issued after a ping !--- is attempted from PC2 to PC1. interface:
Ethernet0/0 Crypto map tag: mymap, local addr. 172.16.1.2 protected vrf: local ident
(addr/mask/prot/port): (172.16.2.0/255.255.255.0/0/0) remote ident (addr/mask/prot/port):
(192.168.1.0/255.255.255.0/0/0) current_peer: 209.165.200.2:500 PERMIT,
flags={origin_is_acl,} #pkts encaps: 5, #pkts encrypt: 5, #pkts digest: 5 #pkts decaps: 5,
#pkts decrypt: 5, #pkts verify: 5 #pkts compressed: 0, #pkts decompressed: 0 #pkts not
compressed: 0, #pkts compr. failed: 0 #pkts not decompressed: 0, #pkts decompress failed: 0
#send errors 1, #recv errors 0 local crypto endpt.: 172.16.1.2, remote crypto endpt.:
209.165.200.2 path mtu 1500, media mtu 1500 current outbound spi: B5F867BC inbound esp sas:
spi: 0xE89A0245(3902407237) transform: esp-des esp-md5-hmac , in use settings ={Tunnel, }
slot: 0, conn id: 2000, flow_id: 3, crypto map: mymap crypto engine type: Software,
engine_id: 1 sa timing: remaining key lifetime (k/sec): (4572084/3561) ike_cookies: 5C9BE6DC
63813771 8973C578 DD91CB42 IV size: 8 bytes replay detection support: Y inbound ah sas:
inbound pcp sas: outbound esp sas: spi: 0xB5F867BC(3052955580) transform: esp-des esp-md5-
```

```
hmac , in use settings ={Tunnel, } slot: 0, conn id: 2001, flow_id: 4, crypto map: mymap
crypto engine type: Software, engine_id: 1 sa timing: remaining key lifetime (k/sec):
(4572084/3561) ike_cookies: 5C9BE6DC 63813771 8973C578 DD91CB42 IV size: 8 bytes replay
detection support: Y outbound ah sas: outbound pcp sas:
```

- **show ip nat translations** - Exibe as conversões NAT ativas.

```
PAT-Router#show ip nat translations
Pro Inside global      Inside local      Outside local     Outside global
udp 209.165.201.2:500  172.16.1.2:500   ---              ---
esp 209.165.201.2:0    172.16.1.2:0    ---              ---
```

Troubleshooting

Esta seção fornece informações que podem ser usadas para o troubleshooting da sua configuração.

Se você estabeleceu um túnel IPSec de LAN para LAN que envolvesse a PANCADINHA (como descrito neste documento) e você continua a experimentar problemas, recolha o **resultado do debug** de cada dispositivo e a saída dos **comandos show** para a análise pelo Suporte técnico de Cisco.

Essas são informações relevantes sobre Troubleshooting para essa configuração. Para obter informações adicionais sobre do Troubleshooting, refira o [Troubleshooting de Segurança IP - Compreendendo e usando comandos debug](#) e [verificação da operação de NAT e do Troubleshooting de NAT básico](#).

os **comandos debug** e o exemplo de saída são mostrados nestas seções.

- [Solucione os problemas com a transparência NAT de IPSec](#)
- [Pesquise defeitos sem transparência de NAT de IPSec](#)

Note: [Antes de emitir comandos de depuração, consulte as informações importantes sobre eles.](#)

Solucione os problemas com a transparência NAT de IPSec

- **debug crypto ipsec** — Exibe as negociações de IPSec de fase 2
- **debug crypto isakmp** — Exibe as negociações ISAKMP da Fase 1.
- **debug ip nat detail** — Examina o NAT que está sendo executado pelo roteador.

Esse é um exemplo da saída do comando.

```
VPN-Gateway1#debug crypto ipsec
Crypto IPSEC debugging is on
VPN-Gateway1#debug crypto isakmp
Crypto ISAKMP debugging is on
VPN-Gateway1#show debug
Cryptographic Subsystem:
  Crypto ISAKMP debugging is on
  Crypto IPSEC debugging is on
```

```
!--- These debugs appeared after a ping !--- was attempted from PC2 to PC1. *Jun 27
09:31:36.159: ISAKMP (0:0): received packet from 209.165.201.2 dport 500 sport 500 Global (N)
NEW SA *Jun 27 09:31:36.159: ISAKMP: Created a peer struct for 209.165.201.2, peer port 500 *Jun
27 09:31:36.159: ISAKMP: Locking peer struct 0x2C50610, IKE refcount 1 for
crypto_isakmp_process_block *Jun 27 09:31:36.159: ISAKMP: local port 500, remote port 500 *Jun
27 09:31:36.559: insert sa successfully sa = 290B720 *Jun 27 09:31:36.559:
```

ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:31:36.559:
ISAKMP:(0:1:SW:1):Old State = IKE_READY New State = IKE_R_MM1 *Jun 27 09:31:36.619:
ISAKMP:(0:1:SW:1): processing SA payload. message ID = 0 *Jun 27 09:31:36.619:
ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor
ID seems Unity/DPD but major 157 mismatch *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID is
NAT-T v3 *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27
09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID seems Unity/DPD but major 123 mismatch *Jun 27
09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID is NAT-T v2 *Jun 27 09:31:36.619: ISAKMP: Looking for
a matching key for 209.165.201.2 in default : success *Jun 27 09:31:36.619:
ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.201.2 *Jun 27 09:31:36.619:
ISAKMP:(0:1:SW:1): local preshared key found *Jun 27 09:31:36.619: ISAKMP : Scanning profiles
for xauth ... *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1):Checking ISAKMP transform 1 against
priority 10 policy *Jun 27 09:31:36.619: ISAKMP: encryption DES-CBC *Jun 27 09:31:36.619:
ISAKMP: hash SHA *Jun 27 09:31:36.619: ISAKMP: default group 1 *Jun 27 09:31:36.619: ISAKMP:
auth pre-share *Jun 27 09:31:36.619: ISAKMP: life type in seconds *Jun 27 09:31:36.619: ISAKMP:
life duration (VPI) of 0x0 0x1 0x51 0x80 *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1):atts are
acceptable. Next payload is 0 *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): processing vendor id
payload *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID seems Unity/DPD but major 157
mismatch *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID is NAT-T v3 *Jun 27 09:31:36.619:
ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor
ID seems Unity/DPD but major 123 mismatch *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1): vendor ID is
NAT-T v2 *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_MAIN_MODE *Jun 27 09:31:36.619: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM1 New State =
IKE_R_MM1 *Jun 27 09:31:36.771: ISAKMP:(0:1:SW:1): constructed NAT-T vendor-03 ID *Jun 27
09:31:36.771: ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 500 peer_port 500 (R)
MM_SA_SETUP *Jun 27 09:31:36.771: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:31:36.771: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM1 New State =
IKE_R_MM2 *Jun 27 09:31:37.179: ISAKMP (0:134217729): received packet from 209.165.201.2 dport
500 sport 500 Global (R) MM_SA_SETUP *Jun 27 09:31:37.179: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:31:37.179: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM2
New State = IKE_R_MM3 *Jun 27 09:31:38.199: ISAKMP:(0:1:SW:1): processing KE payload. message ID
= 0 *Jun 27 09:31:38.199: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 0 *Jun 27
09:31:38.759: ISAKMP: Looking for a matching key for 209.165.201.2 in default : success *Jun 27
09:31:38.759: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.201.2 *Jun 27
09:31:38.759: ISAKMP:(0:1:SW:1):SKEYID state generated *Jun 27 09:31:38.759: ISAKMP:(0:1:SW:1):
processing vendor id payload *Jun 27 09:31:38.759: ISAKMP:(0:1:SW:1): vendor ID is Unity *Jun 27
09:31:38.759: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:38.759:
ISAKMP:(0:1:SW:1): vendor ID is DPD *Jun 27 09:31:38.759: ISAKMP:(0:1:SW:1): processing vendor
id payload *Jun 27 09:31:38.759: ISAKMP:(0:1:SW:1): speaking to another IOS box! *Jun 27
09:31:38.759: ISAKMP:received payload type 17 *Jun 27 09:31:38.759: ISAKMP:received payload type
17 *Jun 27 09:31:38.759: ISAKMP (0:134217729): NAT found, the node outside NAT *Jun 27
09:31:38.759: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27
09:31:38.759: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM3 New State = IKE_R_MM3 *Jun 27
09:31:38.891: ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 500 peer_port 500 (R)
MM_KEY_EXCH *Jun 27 09:31:38.891: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:31:38.891: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM3 New State =
IKE_R_MM4 *Jun 27 09:31:40.071: ISAKMP (0:134217729): received packet from 209.165.201.2 dport
4500 sport 4500 Global (R) MM_KEY_EXCH *Jun 27 09:31:40.071: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:31:40.071: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM4
New State = IKE_R_MM5 *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1): processing ID payload. message ID
= 0 *Jun 27 09:31:40.199: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address :
172.16.1.2 protocol : 17 port : 0 length : 12 *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1):: peer
matches *none* of the profiles *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1): processing HASH payload.
message ID = 0 *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1): processing NOTIFY_INITIAL_CONTACT
protocol 1 spi 0, message ID = 0, sa = 290B720 *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1):SA
authentication status: authenticated *Jun 27 09:31:40.199: ISAKMP:(0:1:SW:1): Process initial
contact, bring down existing phase 1 and 2 SA's with local 209.165.200.2 remote 209.165.201.2
remote port 4500 *Jun 27 09:31:40.231: IPSEC(key_engine): got a queue event with 1 kei messages
*Jun 27 09:31:40.399: ISAKMP:(0:1:SW:1):SA authentication status: authenticated *Jun 27
09:31:40.399: ISAKMP:(0:1:SW:1):SA has been authenticated with 209.165.201.2 *Jun 27
09:31:40.399: ISAKMP:(0:1:SW:1):Detected port floating to port = 4500 *Jun 27 09:31:40.399:
ISAKMP: Trying to insert a peer 209.165.200.2/209.165.201.2/4500/, and inserted successfully.
*Jun 27 09:31:40.399: ISAKMP:(0:1:SW:1):: peer matches *none* of the profiles *Jun 27
09:31:40.399: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27

09:31:40.399: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM5 New State = IKE_R_MM5 *Jun 27
09:31:40.459: ISAKMP:(0:1:SW:1):SA is doing pre-shared key authentication using id type
ID_IPV4_ADDR *Jun 27 09:31:40.459: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1
address : 209.165.200.2 protocol : 17 port : 0 length : 12 *Jun 27 09:31:40.459:
ISAKMP:(0:1:SW:1):Total payload length: 12 *Jun 27 09:31:40.459: ISAKMP:(0:1:SW:1): sending
packet to 209.165.201.2 my_port 4500 peer_port 4500 (R) MM_KEY_EXCH *Jun 27 09:31:40.459:
ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:31:40.459:
ISAKMP:(0:1:SW:1):Old State = IKE_R_MM5 New State = IKE_P1_COMPLETE *Jun 27 09:31:40.539:
ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PHASE1_COMPLETE *Jun 27 09:31:40.539:
ISAKMP:(0:1:SW:1):Old State = IKE_P1_COMPLETE New State = IKE_P1_COMPLETE *Jun 27 09:31:40.999:
ISAKMP (0:134217729): received packet from 209.165.201.2 dport 4500 sport 4500 Global (R)
QM_IDLE *Jun 27 09:31:40.999: ISAKMP: set new node 1546295295 to QM_IDLE *Jun 27 09:31:40.999:
ISAKMP:(0:1:SW:1): processing HASH payload. message ID = 1546295295 *Jun 27 09:31:40.999:
ISAKMP:(0:1:SW:1): processing SA payload. message ID = 1546295295 *Jun 27 09:31:40.999:
ISAKMP:(0:1:SW:1):Checking IPsec proposal 1 *Jun 27 09:31:40.999: ISAKMP: transform 1, ESP_DES
*Jun 27 09:31:40.999: ISAKMP: attributes in transform: *Jun 27 09:31:40.999: ISAKMP: encaps is
61443 (Tunnel-UDP) *Jun 27 09:31:40.999: ISAKMP: SA life type in seconds *Jun 27 09:31:40.999:
ISAKMP: SA life duration (basic) of 3600 *Jun 27 09:31:40.999: ISAKMP: SA life type in kilobytes
*Jun 27 09:31:40.999: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50 0x0 *Jun 27 09:31:40.999:
ISAKMP: authenticator is HMAC-MD5 *Jun 27 09:31:40.999: ISAKMP:(0:1:SW:1):atts are acceptable.
*Jun 27 09:31:40.999: IPSEC(validate_proposal_request): proposal part #1, (key eng. msg.)
INBOUND local= 209.165.200.2, remote= 209.165.201.2, local_proxy= 192.168.1.0/255.255.255.0/0/0
(type=4), remote_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des
esp-md5-hmac (Tunnel-UDP), lifedur= 0s and 0kb, spi= 0x0(0), conn_id= 0, keysize= 0, flags=
0x400 *Jun 27 09:31:40.999: IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27
09:31:40.999: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 1546295295 *Jun 27
09:31:40.999: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1546295295 *Jun 27
09:31:40.999: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1546295295 *Jun 27
09:31:40.999: ISAKMP:(0:1:SW:1): asking for 1 spis from ipsec *Jun 27 09:31:40.999:
ISAKMP:(0:1:SW:1):Node 1546295295, Input = IKE_MSG_FROM_PEER, IKE_QM_EXCH *Jun 27 09:31:40.999:
ISAKMP:(0:1:SW:1):Old State = IKE_QM_READY New State = IKE_QM_SPI_STARVE *Jun 27 09:31:41.031:
IPSEC(key_engine): got a queue event with 1 kei messages *Jun 27 09:31:41.031:
IPSEC(spi_response): getting spi 1315674383 for SA from 209.165.200.2 to 209.165.201.2 for prot
3 *Jun 27 09:31:41.079: ISAKMP: received ike message (2/1) *Jun 27 09:31:42.039:
ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 4500 peer_port 4500 (R) QM_IDLE *Jun
27 09:31:42.039: ISAKMP:(0:1:SW:1):Node 1546295295, Input = IKE_MSG_FROM_IPSEC, IKE_SPI_REPLY
*Jun 27 09:31:42.039: ISAKMP:(0:1:SW:1):Old State = IKE_QM_SPI_STARVE New State = IKE_QM_R_QM2
*Jun 27 09:31:42.311: ISAKMP (0:134217729): received packet from 209.165.201.2 dport 4500 sport
4500 Global (R) QM_IDLE *Jun 27 09:31:42.311: IPsec: Flow_switching Allocated flow for flow_id
134217733 *Jun 27 09:31:42.311: IPsec: Flow_switching Allocated flow for flow_id 134217734 *Jun
27 09:31:43.339: %CRYPTO-5-SESSION_STATUS: Crypto tunnel is UP . Peer 209.165.201.2:4500 Id:
172.16.1.2 *Jun 27 09:31:43.339: ISAKMP: Locking peer struct 0x2C50610, IPSEC refcount 1 for for
stuff_ke *Jun 27 09:31:43.339: ISAKMP:(0:1:SW:1): Creating IPsec SAs *Jun 27 09:31:43.339:
inbound SA from 209.165.201.2 to 209.165.200.2 (f/i) 0/ 0 (proxy 172.16.2.0 to 192.168.1.0) *Jun
27 09:31:43.339: has spi 0x4E6B990F and conn_id 2000 and flags 400 *Jun 27 09:31:43.339:
lifetime of 3600 seconds *Jun 27 09:31:43.339: lifetime of 4608000 kilobytes *Jun 27
09:31:43.339: has client flags 0x10 *Jun 27 09:31:43.339: outbound SA from 209.165.200.2 to
209.165.201.2 (f/i) 0/0 (proxy 192.168.1.0 to 172.16.2.0) *Jun 27 09:31:43.339: has spi -
1664481767 and conn_id 2001 and flags 408 *Jun 27 09:31:43.339: lifetime of 3600 seconds *Jun 27
09:31:43.339: lifetime of 4608000 kilobytes *Jun 27 09:31:43.339: has client flags 0x10 *Jun 27
09:31:43.339: ISAKMP:(0:1:SW:1):deleting node 1546295295 error FALSE reason "quick mode done
(await)" *Jun 27 09:31:43.339: ISAKMP:(0:1:SW:1):Node 1546295295, Input = IKE_MSG_FROM_PEER,
IKE_QM_EXCH *Jun 27 09:31:43.339: ISAKMP:(0:1:SW:1):Old State = IKE_QM_R_QM2 New State =
IKE_QM_PHASE2_COMPLETE *Jun 27 09:31:43.359: IPSEC(key_engine): got a queue event with 2 kei
messages *Jun 27 09:31:43.359: IPSEC(initialize_sas): , (key eng. msg.) INBOUND local=
209.165.200.2, remote= 209.165.201.2, local_proxy= 192.168.1.0/255.255.255.0/0/0 (type=4),
remote_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-
hmac (Tunnel-UDP), lifedur= 3600s and 4608000kb, spi= 0x4E6B990F(1315674383), conn_id=
134219728, keysize= 0, flags= 0x400 *Jun 27 09:31:43.359: IPSEC(initialize_sas): , (key eng.
msg.) OUTBOUND local= 209.165.200.2, remote= 209.165.201.2, local_proxy=
192.168.1.0/255.255.255.0/0/0 (type=4), remote_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4),
protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel-UDP), lifedur= 3600s and 4608000kb, spi=
0x9CCA0619(2630485529), conn_id= 134219729, keysize= 0, flags= 0x408 *Jun 27 09:31:43.359:
IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:31:43.359:

```
IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with the same proxies and 209.165.201.2
*Jun 27 09:31:43.359: IPSEC(mtree_add_ident): src 192.168.1.0, dest 172.16.2.0, dest_port 0 *Jun
27 09:31:43.359: IPSEC(create_sa): sa created, (sa) sa_dest= 209.165.200.2, sa_prot= 50, sa_spi=
0x4E6B990F(1315674383), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219728 *Jun 27
09:31:43.359: IPSEC(create_sa): sa created, (sa) sa_dest= 209.165.201.2, sa_prot= 50, sa_spi=
0x9CCA0619(2630485529), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219729 *Jun 27
09:32:33.359: ISAKMP:(0:1:SW:1):purging node 1546295295 VPN-Gateway2#debug crypto ipsec
Crypto IPSEC debugging is on
VPN-Gateway2#debug crypto isakmp
Crypto ISAKMP debugging is on
VPN-Gateway2#show debug
Cryptographic Subsystem:
  Crypto ISAKMP debugging is on
  Crypto IPSEC debugging is on
VPN-Gateway2#
```

```
!--- These debugs appeared after a ping !--- was attempted from PC2 to PC1. *Jun 27
09:31:35.447: IPSEC(sa_request): , (key eng. msg.) OUTBOUND local= 172.16.1.2, remote=
209.165.200.2, local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy=
192.168.1.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel),
lifedur= 3600s and 4608000kb, spi= 0x9CCA0619(2630485529), conn_id= 0, keysize= 0, flags= 0x400A
*Jun 27 09:31:35.455: ISAKMP: received ke message (1/1) *Jun 27 09:31:35.455:
ISAKMP:(0:0:N/A:0): SA request profile is (NULL) *Jun 27 09:31:35.455: ISAKMP: Created a peer
struct for 209.165.200.2, peer port 500 *Jun 27 09:31:35.455: ISAKMP: Locking peer struct
0x2C42438, IKE refcount 1 for isakmp_initiator *Jun 27 09:31:35.455: ISAKMP: local port 500,
remote port 500 *Jun 27 09:31:35.487: ISAKMP: set new node 0 to QM_IDLE *Jun 27 09:31:35.487:
insert sa successfully sa = 2CB1E80 *Jun 27 09:31:35.487: ISAKMP:(0:1:SW:1):Can not start
Aggressive mode, trying Main mode. *Jun 27 09:31:35.487: ISAKMP: Looking for a matching key for
209.165.200.2 in default : success *Jun 27 09:31:35.487: ISAKMP:(0:1:SW:1):found peer pre-shared
key matching 209.165.200.2 *Jun 27 09:31:35.487: ISAKMP:(0:1:SW:1): constructed NAT-T vendor-03
ID *Jun 27 09:31:35.487: ISAKMP:(0:1:SW:1): constructed NAT-T vendor-02 ID *Jun 27 09:31:35.487:
ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_IPSEC, IKE_SA_REQ_MM *Jun 27 09:31:35.487:
ISAKMP:(0:1:SW:1):Old State = IKE_READY New State = IKE_I_MM1 *Jun 27 09:31:35.487:
ISAKMP:(0:1:SW:1): beginning Main Mode exchange *Jun 27 09:31:35.487: ISAKMP:(0:1:SW:1): sending
packet to 209.165.200.2 my_port 500 peer_port 500 (I) MM_NO_STATE *Jun 27 09:31:36.607: ISAKMP
(0:134217729): received packet from 209.165.200.2 dport 500 sport 500 Global (I) MM_NO_STATE
*Jun 27 09:31:36.607: ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27
09:31:36.607: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM1 New State = IKE_I_MM2 *Jun 27
09:31:36.687: ISAKMP:(0:1:SW:1): processing SA payload. message ID = 0 *Jun 27 09:31:36.687:
ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1): vendor
ID seems Unity/DPD but major 157 mismatch *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1): vendor ID is
NAT-T v3 *Jun 27 09:31:36.687: ISAKMP: Looking for a matching key for 209.165.200.2 in default :
success *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.200.2
*Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1): local preshared key found *Jun 27 09:31:36.687: ISAKMP
: Scanning profiles for xauth ... *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1):Checking ISAKMP
transform 1 against priority 10 policy *Jun 27 09:31:36.687: ISAKMP: encryption DES-CBC *Jun 27
09:31:36.687: ISAKMP: hash SHA *Jun 27 09:31:36.687: ISAKMP: default group 1 *Jun 27
09:31:36.687: ISAKMP: auth pre-share *Jun 27 09:31:36.687: ISAKMP: life type in seconds *Jun 27
09:31:36.687: ISAKMP: life duration (VPI) of 0x0 0x1 0x51 0x80 *Jun 27 09:31:36.687:
ISAKMP:(0:1:SW:1):atts are acceptable. Next payload is 0 *Jun 27 09:31:36.687:
ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1): vendor
ID seems Unity/DPD but major 157 mismatch *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1): vendor ID is
NAT-T v3 *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_MAIN_MODE *Jun 27 09:31:36.687: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM2 New State =
IKE_I_MM2 *Jun 27 09:31:36.795: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 500
peer_port 500 (I) MM_SA_SETUP *Jun 27 09:31:36.795: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:31:36.795: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM2 New State =
IKE_I_MM3 *Jun 27 09:31:38.727: ISAKMP (0:134217729): received packet from 209.165.200.2 dport
500 sport 500 Global (I) MM_SA_SETUP *Jun 27 09:31:38.727: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:31:38.727: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM3
New State = IKE_I_MM4 *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): processing KE payload. message ID
= 0 *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 0 *Jun 27
09:31:38.807: ISAKMP: Looking for a matching key for 209.165.200.2 in default : success *Jun 27
09:31:38.807: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.200.2 *Jun 27
```

09:31:38.807: ISAKMP:(0:1:SW:1):SKEYID state generated *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): vendor ID is Unity *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): vendor ID is DPD *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1): speaking to another IOS box! *Jun 27 09:31:38.807: ISAKMP:received payload type 17 *Jun 27 09:31:38.807: ISAKMP (0:134217729): NAT found, the node inside NAT *Jun 27 09:31:38.807: ISAKMP:received payload type 17 *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27 09:31:38.807: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM4 New State = IKE_I_MM4 *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1):Send initial contact *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1):SA is doing pre-shared key authentication using id type ID_IPV4_ADDR *Jun 27 09:31:38.935: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address : 172.16.1.2 protocol : 17 port : 0 length : 12 *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1):Total payload length: 12 *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 4500 peer_port 4500 (I) MM_KEY_EXCH *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:31:38.935: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM4 New State = IKE_I_MM5 *Jun 27 09:31:40.307: ISAKMP (0:134217729): received packet from 209.165.200.2 dport 4500 sport 4500 Global (I) MM_KEY_EXCH *Jun 27 09:31:40.307: ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:31:40.307: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM5 New State = IKE_I_MM6 *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 0 *Jun 27 09:31:40.367: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address : 209.165.200.2 protocol : 17 port : 0 length : 12 *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1): processing HASH payload. message ID = 0 *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):SA authentication status: authenticated *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):SA has been authenticated with 209.165.200.2 *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):: peer matches *none* of the profiles *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):Setting UDP ENC peer struct 0x2940710 sa= 0x2CB1E80 *Jun 27 09:31:40.367: ISAKMP: Trying to insert a peer 172.16.1.2/209.165.200.2/4500/, and inserted successfully. *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27 09:31:40.367: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM6 New State = IKE_I_MM6 *Jun 27 09:31:40.367: ISAKMP: sending nat keepalive packet to 209.165.200.2(4500) *Jun 27 09:31:40.395: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:31:40.395: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM6 New State = IKE_P1_COMPLETE *Jun 27 09:31:40.475: ISAKMP:(0:1:SW:1):beginning Quick Mode exchange, M-ID of 1546295295 *Jun 27 09:31:40.507: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 4500 peer_port 4500 (I) QM_IDLE *Jun 27 09:31:40.507: ISAKMP:(0:1:SW:1):Node 1546295295, Input = IKE_MSG_INTERNAL, IKE_INIT_QM *Jun 27 09:31:40.507: ISAKMP:(0:1:SW:1):Old State = IKE_QM_READY New State = IKE_QM_I_QM1 *Jun 27 09:31:40.507: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PHASE1_COMPLETE *Jun 27 09:31:40.507: ISAKMP:(0:1:SW:1):Old State = IKE_P1_COMPLETE New State = IKE_P1_COMPLETE *Jun 27 09:31:41.887: ISAKMP (0:134217729): received packet from 209.165.200.2 dport 4500 sport 4500 Global (I) QM_IDLE *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1): processing HASH payload. message ID = 1546295295 *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1): processing SA payload. message ID = 1546295295 *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1):Checking IPsec proposal 1 *Jun 27 09:31:41.887: ISAKMP: transform 1, ESP_DES *Jun 27 09:31:41.887: ISAKMP: attributes in transform: *Jun 27 09:31:41.887: ISAKMP: encaps is 61443 (Tunnel-UDP) *Jun 27 09:31:41.887: ISAKMP: SA life type in seconds *Jun 27 09:31:41.887: ISAKMP: SA life duration (basic) of 3600 *Jun 27 09:31:41.887: ISAKMP: SA life type in kilobytes *Jun 27 09:31:41.887: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50 0x0 *Jun 27 09:31:41.887: ISAKMP: authenticator is HMAC-MD5 *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1):atts are acceptable. *Jun 27 09:31:41.887: IPSEC(validate_proposal_request): proposal part #1, (key eng. msg.) INBOUND local= 172.16.1.2, remote= 209.165.200.2, local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.1.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel-UDP), lifedur= 0s and 0kb, spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x400 *Jun 27 09:31:41.887: IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 1546295295 *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1546295295 *Jun 27 09:31:41.887: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1546295295 *Jun 27 09:31:41.887: IPsec: Flow_switching Allocated flow for flow_id 134217729 *Jun 27 09:31:41.887: IPsec: Flow_switching Allocated flow for flow_id 134217730 *Jun 27 09:31:41.947: %CRYPTO-5-SESSION_STATUS: Crypto tunnel is UP . Peer 209.165.200.2:4500 Id: 209.165.200.2 *Jun 27 09:31:41.947: ISAKMP: Locking peer struct 0x2C42438, IPSEC refcount 1 for for stuff_ke *Jun 27 09:31:41.947: ISAKMP:(0:1:SW:1): Creating IPsec SAs *Jun 27 09:31:41.947: inbound SA from 209.165.200.2 to 172.16.1.2 (f/i) 0/ 0 (proxy 192.168.1.0 to 172.16.2.0) *Jun 27 09:31:41.947: has spi 0x9CCA0619 and conn_id 2000 and flags 400 *Jun 27 09:31:41.947: lifetime of 3600 seconds *Jun 27

09:31:41.947: lifetime of 4608000 kilobytes *Jun 27 09:31:41.947: has client flags 0x10 *Jun 27
09:31:41.947: outbound SA from 172.16.1.2 to 209.165.200.2 (f/i) 0/0 (proxy 172.16.2.0 to
192.168.1.0) *Jun 27 09:31:41.947: has spi 1315674383 and conn_id 2001 and flags 408 *Jun 27
09:31:41.947: lifetime of 3600 seconds *Jun 27 09:31:41.947: lifetime of 4608000 kilobytes *Jun
27 09:31:41.947: has client flags 0x10 *Jun 27 09:31:41.947: ISAKMP:(0:1:SW:1): sending packet
to 209.165.200.2 my_port 4500 peer_port 4500 (I) QM_IDLE *Jun 27 09:31:41.947:
ISAKMP:(0:1:SW:1):deleting node 1546295295 error FALSE reason "" *Jun 27 09:31:41.947:
ISAKMP:(0:1:SW:1):Node 1546295295, Input = IKE_MESG_FROM_PEER, IKE_QM_EXCH *Jun 27 09:31:41.947:
ISAKMP:(0:1:SW:1):Old State = IKE_QM_I_QM1 New State = IKE_QM_PHASE2_COMPLETE *Jun 27
09:31:41.955: IPSEC(key_engine): got a queue event with 2 kei messages *Jun 27 09:31:41.955:
IPSEC(initialize_sas): , (key eng. msg.) INBOUND local= 172.16.1.2, remote= 209.165.200.2,
local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.1.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel-UDP), lifedur= 3600s and
4608000kb, spi= 0x9CCA0619(2630485529), conn_id= 134219728, keysize= 0, flags= 0x400 *Jun 27
09:31:41.955: IPSEC(initialize_sas): , (key eng. msg.) OUTBOUND local= 172.16.1.2, remote=
209.165.200.2, local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy=
192.168.1.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel-
UDP), lifedur= 3600s and 4608000kb, spi= 0x4E6B990F(1315674383), conn_id= 134219729, keysize= 0,
flags= 0x408 *Jun 27 09:31:41.955: IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf =
*Jun 27 09:31:41.955: IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with the same proxies
and 209.165.200.2 *Jun 27 09:31:41.955: IPSEC(mtree_add_ident): src 172.16.2.0, dest
192.168.1.0, dest_port 0 *Jun 27 09:31:41.955: IPSEC(create_sa): sa created, (sa) sa_dest=
172.16.1.2, sa_prot= 50, sa_spi= 0x9CCA0619(2630485529), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 134219728 *Jun 27 09:31:41.955: IPSEC(create_sa): sa created, (sa) sa_dest=
209.165.200.2, sa_prot= 50, sa_spi= 0x4E6B990F(1315674383), sa_trans= esp-des esp-md5-hmac ,
sa_conn_id= 134219729 VPN-Gateway2# *Jun 27 09:32:31.979: ISAKMP:(0:1:SW:1):purging node
1546295295 PAT-Router#**debug ip nat detail**
IP NAT detailed debugging is on
PAT-Router#**show debug**
Generic IP:
IP NAT detailed debugging is on
PAT-Router#
*!--- The "i" in this line indicates the packet is traveling from the !--- inside to the outside
(from a NAT perspective) interface. The number in !--- the brackets is the identification number
in the IP packet. This is !--- useful when correlating information with sniffer traces taken
with a !--- network analyzer while troubleshooting problems.* *Jun 27 09:31:35.375: NAT*: i: udp
(172.16.1.2, 500) -> (209.165.200.2, 500) [66] *!--- The "s" in this next line shows the source
address of the packet and how it is !--- being translated.* *Jun 27 09:31:35.375: NAT*:
s=172.16.1.2->209.165.201.2, d=209.165.200.2 [66] *Jun 27 09:31:36.475: NAT*: o: udp
(209.165.200.2, 500) -> (209.165.201.2, 500) [66] *Jun 27 09:31:36.475: NAT*: s=209.165.200.2,
d=209.165.201.2->172.16.1.2 [66] *Jun 27 09:31:36.683: NAT*: i: udp (172.16.1.2, 500) ->
(209.165.200.2, 500) [67] *Jun 27 09:31:36.683: NAT*: s=172.16.1.2->209.165.201.2,
d=209.165.200.2 [67] *Jun 27 09:31:38.595: NAT*: o: udp (209.165.200.2, 500) -> (209.165.201.2,
500) [67] *Jun 27 09:31:38.595: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [67] *Jun 27
09:31:38.823: NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500) [68] *Jun 27
09:31:38.823: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [68] *Jun 27 09:31:40.163:
NAT*: o: udp (209.165.200.2, 4500) -> (209.165.201.2, 4500) [68] *Jun 27 09:31:40.163: NAT*:
s=209.165.200.2, d=209.165.201.2->172.16.1.2 [68] *Jun 27 09:31:40.255: NAT*: i: udp
(172.16.1.2, 4500) -> (209.165.200.2, 4500) [69] *Jun 27 09:31:40.255: NAT*: s=172.16.1.2-
>209.165.201.2, d=209.165.200.2 [69] *Jun 27 09:31:40.395: NAT*: i: udp (172.16.1.2, 4500) ->
(209.165.200.2, 4500) [70] *Jun 27 09:31:40.395: NAT*: s=172.16.1.2->209.165.201.2,
d=209.165.200.2 [70] *Jun 27 09:31:41.747: NAT*: o: udp (209.165.200.2, 4500) -> (209.165.201.2,
4500) [69] *Jun 27 09:31:41.747: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [69] *Jun 27
09:31:41.839: NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500) [71] *Jun 27
09:31:41.839: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [71] *Jun 27 09:31:43.463:
NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500) [72] *Jun 27 09:31:43.463: NAT*:
s=172.16.1.2->209.165.201.2, d=209.165.200.2 [72] *Jun 27 09:31:43.523: NAT*: o: udp
(209.165.200.2, 4500) -> (209.165.201.2, 4500) [70] *Jun 27 09:31:43.523: NAT*: s=209.165.200.2,
d=209.165.201.2->172.16.1.2 [70] *Jun 27 09:33:27.975: NAT*: i: udp (172.16.1.2, 4500) ->
(209.165.200.2, 4500) [73] *Jun 27 09:33:27.975: NAT*: s=172.16.1.2->209.165.201.2,
d=209.165.200.2 [73] *Jun 27 09:33:28.067: NAT*: o: udp (209.165.200.2, 4500) -> (209.165.201.2,
4500) [71] *Jun 27 09:33:28.067: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [71] *Jun 27
09:33:28.115: NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500) [74] *Jun 27
09:33:28.115: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [74] *Jun 27 09:33:28.167:

```
NAT*: o: udp (209.165.200.2, 4500) -> (209.165.201.2, 4500) [72] *Jun 27 09:33:28.167: NAT*:
s=209.165.200.2, d=209.165.201.2->172.16.1.2 [72] *Jun 27 09:33:28.227: NAT*: i: udp
(172.16.1.2, 4500) -> (209.165.200.2, 4500) [75] *Jun 27 09:33:28.227: NAT*: s=172.16.1.2-
>209.165.201.2, d=209.165.200.2 [75] *Jun 27 09:33:28.283: NAT*: o: udp (209.165.200.2, 4500) ->
(209.165.201.2, 4500) [73] *Jun 27 09:33:28.283: NAT*: s=209.165.200.2, d=209.165.201.2-
>172.16.1.2 [73] *Jun 27 09:33:28.355: NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500)
[76] *Jun 27 09:33:28.355: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [76] *Jun 27
09:33:28.407: NAT*: o: udp (209.165.200.2, 4500) -> (209.165.201.2, 4500) [74] *Jun 27
09:33:28.407: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [74] *Jun 27 09:33:28.455:
NAT*: i: udp (172.16.1.2, 4500) -> (209.165.200.2, 4500) [77] *Jun 27 09:33:28.455: NAT*:
s=172.16.1.2->209.165.201.2, d=209.165.200.2 [77] *Jun 27 09:33:28.487: NAT*: o: udp
(209.165.200.2, 4500) -> (209.165.201.2, 4500) [75] *Jun 27 09:33:28.487: NAT*: s=209.165.200.2,
d=209.165.201.2->172.16.1.2 [75]
```

Troubleshooting sem IPSec NAT Transparency

- debug crypto ipsec — Exibe as negociações de IPSec de fase 2
- debug crypto isakmp — Exibe as negociações ISAKMP da Fase 1.
- debug ip nat detail — Examina o NAT que está sendo executado pelo roteador.

Esse é um exemplo da saída do comando.

```
VPN-Gateway1#debug crypto ipsec
Crypto IPSEC debugging is on
VPN-Gateway1#debug crypto isakmp
Crypto ISAKMP debugging is on
VPN-Gateway1#show debug
Cryptographic Subsystem:
  Crypto ISAKMP debugging is on
  Crypto IPSEC debugging is on
```

```
!--- These debugs appeared after a ping !--- was attempted from PC2 to PC1. *Jun 27
09:49:58.351: ISAKMP (0:0): received packet from 209.165.201.2 dport 500 sport 500 Global (N)
NEW SA *Jun 27 09:49:58.351: ISAKMP: Created a peer struct for 209.165.201.2, peer port 500 *Jun
27 09:49:58.351: ISAKMP: Locking peer struct 0x2C50328, IKE refcount 1 for
crypto_isakmp_process_block *Jun 27 09:49:58.351: ISAKMP: local port 500, remote port 500 *Jun
27 09:49:58.991: insert sa successfully sa = 29D2E80 *Jun 27 09:49:58.991:
ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:49:58.991:
ISAKMP:(0:1:SW:1):Old State = IKE_READY New State = IKE_R_MM1 *Jun 27 09:49:59.151:
ISAKMP:(0:1:SW:1): processing SA payload. message ID = 0 *Jun 27 09:49:59.151: ISAKMP: Looking
for a matching key for 209.165.201.2 in default : success *Jun 27 09:49:59.151:
ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.201.2 *Jun 27 09:49:59.151:
ISAKMP:(0:1:SW:1): local preshared key found *Jun 27 09:49:59.151: ISAKMP : Scanning profiles
for xauth ... *Jun 27 09:49:59.151: ISAKMP:(0:1:SW:1):Checking ISAKMP transform 1 against
priority 10 policy *Jun 27 09:49:59.151: ISAKMP: encryption DES-CBC *Jun 27 09:49:59.151:
ISAKMP: hash SHA *Jun 27 09:49:59.151: ISAKMP: default group 1 *Jun 27 09:49:59.151: ISAKMP:
auth pre-share *Jun 27 09:49:59.151: ISAKMP: life type in seconds *Jun 27 09:49:59.151: ISAKMP:
life duration (VPI) of 0x0 0x1 0x51 0x80 *Jun 27 09:49:59.151: ISAKMP:(0:1:SW:1):atts are
acceptable. Next payload is 0 *Jun 27 09:49:59.151: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_MAIN_MODE *Jun 27 09:49:59.151: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM1 New State =
IKE_R_MM1 *Jun 27 09:49:59.223: ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 500
peer_port 500 (R) MM_SA_SETUP *Jun 27 09:49:59.223: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:49:59.223: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM1 New State =
IKE_R_MM2 *Jun 27 09:49:59.711: ISAKMP (0:134217729): received packet from 209.165.201.2 dport
500 sport 500 Global (R) MM_SA_SETUP *Jun 27 09:49:59.711: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:49:59.711: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM2
New State = IKE_R_MM3 *Jun 27 09:49:59.763: ISAKMP:(0:1:SW:1): processing KE payload. message ID
= 0 *Jun 27 09:49:59.763: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 0 *Jun 27
09:49:59.911: ISAKMP: Looking for a matching key for 209.165.201.2 in default : success *Jun 27
09:49:59.911: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.201.2 *Jun 27
09:49:59.911: ISAKMP:(0:1:SW:1):SKEYID state generated *Jun 27 09:49:59.911: ISAKMP:(0:1:SW:1):
processing vendor id payload *Jun 27 09:49:59.911: ISAKMP:(0:1:SW:1): vendor ID is Unity *Jun 27
```

09:49:59.911: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:49:59.911:
ISAKMP:(0:1:SW:1): vendor ID is DPD *Jun 27 09:49:59.911: ISAKMP:(0:1:SW:1): processing vendor
id payload *Jun 27 09:49:59.911: ISAKMP:(0:1:SW:1): speaking to another IOS box! *Jun 27
09:49:59.911: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27
09:49:59.911: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM3 New State = IKE_R_MM3 *Jun 27
09:50:00.051: ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 500 peer_port 500 (R)
MM_KEY_EXCH *Jun 27 09:50:00.051: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:50:00.051: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM3 New State =
IKE_R_MM4 *Jun 27 09:50:00.743: ISAKMP (0:134217729): received packet from 209.165.201.2 dport
500 sport 500 Global (R) MM_KEY_EXCH *Jun 27 09:50:00.743: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:50:00.743: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM4
New State = IKE_R_MM5 *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1): processing ID payload. message ID
= 0 *Jun 27 09:50:00.811: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address :
172.16.1.2 protocol : 17 port : 500 length : 12 *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1):: peer
matches *none* of the profiles *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1): processing HASH payload.
message ID = 0 *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1): processing NOTIFY_INITIAL_CONTACT
protocol 1 spi 0, message ID = 0, sa = 29D2E80 *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1):SA
authentication status: authenticated *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1): Process initial
contact, bring down existing phase 1 and 2 SA's with local 209.165.200.2 remote 209.165.201.2
remote port 500 *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1):SA authentication status: authenticated
*Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1):SA has been authenticated with 209.165.201.2 *Jun 27
09:50:00.811: ISAKMP: Trying to insert a peer 209.165.200.2/209.165.201.2/500/, and inserted
successfully. *Jun 27 09:50:00.811: ISAKMP:(0:1:SW:1):: peer matches *none* of the profiles *Jun
27 09:50:00.811: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27
09:50:00.811: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM5 New State = IKE_R_MM5 *Jun 27
09:50:00.851: IPSEC(key_engine): got a queue event with 1 kei messages *Jun 27 09:50:00.963:
ISAKMP:(0:1:SW:1):SA is doing pre-shared key authentication using id type ID_IPV4_ADDR *Jun 27
09:50:00.963: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address : 209.165.200.2
protocol : 17 port : 500 length : 12 *Jun 27 09:50:00.963: ISAKMP:(0:1:SW:1):Total payload
length: 12 *Jun 27 09:50:00.963: ISAKMP:(0:1:SW:1): sending packet to 209.165.201.2 my_port 500
peer_port 500 (R) MM_KEY_EXCH *Jun 27 09:50:00.963: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PROCESS_COMPLETE *Jun 27 09:50:00.963: ISAKMP:(0:1:SW:1):Old State = IKE_R_MM5 New State =
IKE_P1_COMPLETE *Jun 27 09:50:01.043: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL,
IKE_PHASE1_COMPLETE *Jun 27 09:50:01.043: ISAKMP:(0:1:SW:1):Old State = IKE_P1_COMPLETE New
State = IKE_P1_COMPLETE *Jun 27 09:50:01.403: ISAKMP (0:134217729): received packet from
209.165.201.2 dport 500 sport 500 Global (R) QM_IDLE *Jun 27 09:50:01.403: ISAKMP: set new node
1689610294 to QM_IDLE *Jun 27 09:50:01.403: ISAKMP:(0:1:SW:1): processing HASH payload. message
ID = 1689610294 *Jun 27 09:50:01.403: ISAKMP:(0:1:SW:1): processing SA payload. message ID =
1689610294 *Jun 27 09:50:01.403: ISAKMP:(0:1:SW:1):Checking IPsec proposal 1 *Jun 27
09:50:01.403: ISAKMP: transform 1, ESP_DES *Jun 27 09:50:01.403: ISAKMP: attributes in
transform: *Jun 27 09:50:01.403: ISAKMP: encaps is 1 (Tunnel) *Jun 27 09:50:01.403: ISAKMP: SA
life type in seconds *Jun 27 09:50:01.403: ISAKMP: SA life duration (basic) of 3600 *Jun 27
09:50:01.403: ISAKMP: SA life type in kilobytes *Jun 27 09:50:01.403: ISAKMP: SA life duration
(VPI) of 0x0 0x46 0x50 0x0 *Jun 27 09:50:01.403: ISAKMP: authenticator is HMAC-MD5 *Jun 27
09:50:01.403: ISAKMP:(0:1:SW:1):atts are acceptable. *Jun 27 09:50:01.403:
IPSEC(validate_proposal_request): proposal part #1, (key eng. msg.) INBOUND local=
209.165.200.2, remote= 209.165.201.2, local_proxy= 192.168.1.0/255.255.255.0/0/0 (type=4),
remote_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-
hmac (Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x2 *Jun 27
09:50:01.403: IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:50:01.403:
ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 1689610294 *Jun 27 09:50:01.403:
ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1689610294 *Jun 27 09:50:01.403:
ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1689610294 *Jun 27 09:50:01.403:
ISAKMP:(0:1:SW:1): asking for 1 spis from ipsec *Jun 27 09:50:01.403: ISAKMP:(0:1:SW:1):Node
1689610294, Input = IKE_MSG_FROM_PEER, IKE_QM_EXCH *Jun 27 09:50:01.403: ISAKMP:(0:1:SW:1):Old
State = IKE_QM_READY New State = IKE_QM_SPI_STARVE *Jun 27 09:50:01.443: IPSEC(key_engine): got
a queue event with 1 kei messages *Jun 27 09:50:01.443: IPSEC(spi_response): getting spi
3052955580 for SA from 209.165.200.2 to 209.165.201.2 for prot 3 *Jun 27 09:50:01.463: ISAKMP:
received ke message (2/1) *Jun 27 09:50:01.971: ISAKMP:(0:1:SW:1): sending packet to
209.165.201.2 my_port 500 peer_port 500 (R) QM_IDLE *Jun 27 09:50:01.971: ISAKMP:(0:1:SW:1):Node
1689610294, Input = IKE_MSG_FROM_IPSEC, IKE_SPI_REPLY *Jun 27 09:50:01.971:
ISAKMP:(0:1:SW:1):Old State = IKE_QM_SPI_STARVE New State = IKE_QM_R_QM2 *Jun 27 09:50:02.303:
ISAKMP (0:134217729): received packet from 209.165.201.2 dport 500 sport 500 Global (R) QM_IDLE
*Jun 27 09:50:02.303: IPsec: Flow_switching Allocated flow for flow_id 134217735 *Jun 27

09:50:02.303: IPsec: Flow_switching Allocated flow for flow_id 134217736 *Jun 27 09:50:03.203:
%CRYPTO-5-SESSION_STATUS: Crypto tunnel is UP . Peer 209.165.201.2:500 Id: 172.16.1.2 *Jun 27
09:50:03.203: ISAKMP: Locking peer struct 0x2C50328, IPSEC refcount 1 for for stuff_ke *Jun 27
09:50:03.203: ISAKMP:(0:1:SW:1): Creating IPsec SAs *Jun 27 09:50:03.203: inbound SA from
209.165.201.2 to 209.165.200.2 (f/i) 0/ 0 (proxy 172.16.2.0 to 192.168.1.0) *Jun 27
09:50:03.203: has spi 0xB5F867BC and conn_id 2000 and flags 2 *Jun 27 09:50:03.203: lifetime of
3600 seconds *Jun 27 09:50:03.203: lifetime of 4608000 kilobytes *Jun 27 09:50:03.203: has
client flags 0x0 *Jun 27 09:50:03.203: outbound SA from 209.165.200.2 to 209.165.201.2 (f/i) 0/0
(proxy 192.168.1.0 to 172.16.2.0) *Jun 27 09:50:03.203: has spi -392560059 and conn_id 2001 and
flags A *Jun 27 09:50:03.203: lifetime of 3600 seconds *Jun 27 09:50:03.203: lifetime of 4608000
kilobytes *Jun 27 09:50:03.203: has client flags 0x0 *Jun 27 09:50:03.203:
ISAKMP:(0:1:SW:1):deleting node 1689610294 error FALSE reason "quick mode done (await)" *Jun 27
09:50:03.203: ISAKMP:(0:1:SW:1):Node 1689610294, Input = IKE_MSG_FROM_PEER, IKE_QM_EXCH *Jun 27
09:50:03.203: ISAKMP:(0:1:SW:1):Old State = IKE_QM_R_QM2 New State = IKE_QM_PHASE2_COMPLETE *Jun
27 09:50:03.231: IPSEC(key_engine): got a queue event with 2 kei messages *Jun 27 09:50:03.231:
IPSEC(initialize_sas): , (key eng. msg.) INBOUND local= 209.165.200.2, remote= 209.165.201.2,
local_proxy= 192.168.1.0/255.255.255.0/0/0 (type=4), remote_proxy= 172.16.2.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel), lifedur= 3600s and 4608000kb,
spi= 0xB5F867BC(3052955580), conn_id= 134219728, keysize= 0, flags= 0x2 *Jun 27 09:50:03.231:
IPSEC(initialize_sas): , (key eng. msg.) OUTBOUND local= 209.165.200.2, remote= 209.165.201.2,
local_proxy= 192.168.1.0/255.255.255.0/0/0 (type=4), remote_proxy= 172.16.2.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel), lifedur= 3600s and 4608000kb,
spi= 0xE89A0245(3902407237), conn_id= 134219729, keysize= 0, flags= 0xA *Jun 27 09:50:03.231:
IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:50:03.231:
IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with the same proxies and 209.165.201.2
*Jun 27 09:50:03.231: IPSEC(mtree_add_ident): src 192.168.1.0, dest 172.16.2.0, dest_port 0 *Jun
27 09:50:03.231: IPSEC(create_sa): sa created, (sa) sa_dest= 209.165.200.2, sa_prot= 50, sa_spi=
0xB5F867BC(3052955580), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219728 *Jun 27
09:50:03.231: IPSEC(create_sa): sa created, (sa) sa_dest= 209.165.201.2, sa_prot= 50, sa_spi=
0xE89A0245(3902407237), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219729 *Jun 27
09:50:53.231: ISAKMP:(0:1:SW:1):purging node 1689610294 VPN-Gateway2#**debug crypto ipsec**
Crypto IPSEC debugging is on
VPN-Gateway2#**debug crypto isakmp**
Crypto ISAKMP debugging is on
VPN-Gateway2#**show debug**
Cryptographic Subsystem:
Crypto ISAKMP debugging is on
Crypto IPSEC debugging is on
VPN-Gateway2#

!--- These debugs appeared after a ping !--- was attempted from PC2 to PC1. *Jun 27
09:49:57.799: IPSEC(sa_request): , (key eng. msg.) OUTBOUND local= 172.16.1.2, remote=
209.165.200.2, local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy=
192.168.1.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel),
lifedur= 3600s and 4608000kb, spi= 0xE89A0245(3902407237), conn_id= 0, keysize= 0, flags= 0x400A
*Jun 27 09:49:57.807: ISAKMP: received ke message (1/1) *Jun 27 09:49:57.807:
ISAKMP:(0:0:N/A:0): SA request profile is (NULL) *Jun 27 09:49:57.807: ISAKMP: Created a peer
struct for 209.165.200.2, peer port 500 *Jun 27 09:49:57.807: ISAKMP: Locking peer struct
0x2BEDC78, IKE refcount 1 for isakmp_initiator *Jun 27 09:49:57.807: ISAKMP: local port 500,
remote port 500 *Jun 27 09:49:57.839: ISAKMP: set new node 0 to QM_IDLE *Jun 27 09:49:57.839:
insert sa successfully sa = 2CB1E80 *Jun 27 09:49:57.839: ISAKMP:(0:1:SW:1):Can not start
Aggressive mode, trying Main mode. *Jun 27 09:49:57.839: ISAKMP: Looking for a matching key for
209.165.200.2 in default : success *Jun 27 09:49:57.839: ISAKMP:(0:1:SW:1):found peer pre-shared
key matching 209.165.200.2 *Jun 27 09:49:57.839: ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_IPSEC,
IKE_SA_REQ_MM *Jun 27 09:49:57.839: ISAKMP:(0:1:SW:1):Old State = IKE_READY New State =
IKE_I_MM1 *Jun 27 09:49:57.839: ISAKMP:(0:1:SW:1): beginning Main Mode exchange *Jun 27
09:49:57.839: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 500 peer_port 500 (I)
MM_NO_STATE *Jun 27 09:49:59.099: ISAKMP (0:134217729): received packet from 209.165.200.2 dport
500 sport 500 Global (I) MM_NO_STATE *Jun 27 09:49:59.099: ISAKMP:(0:1:SW:1):Input =
IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:49:59.099: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM1
New State = IKE_I_MM2 *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1): processing SA payload. message ID
= 0 *Jun 27 09:49:59.139: ISAKMP: Looking for a matching key for 209.165.200.2 in default :
success *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.200.2
*Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1): local preshared key found *Jun 27 09:49:59.139: ISAKMP

: Scanning profiles for xauth ... *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1):Checking ISAKMP transform 1 against priority 10 policy *Jun 27 09:49:59.139: ISAKMP: encryption DES-CBC *Jun 27 09:49:59.139: ISAKMP: hash SHA *Jun 27 09:49:59.139: ISAKMP: default group 1 *Jun 27 09:49:59.139: ISAKMP: auth pre-share *Jun 27 09:49:59.139: ISAKMP: life type in seconds *Jun 27 09:49:59.139: ISAKMP: life duration (VPI) of 0x0 0x1 0x51 0x80 *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1):atts are acceptable. Next payload is 0 *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27 09:49:59.139: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM2 New State = IKE_I_MM2 *Jun 27 09:49:59.259: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 500 peer_port 500 (I) MM_SA_SETUP *Jun 27 09:49:59.259: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:49:59.259: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM2 New State = IKE_I_MM3 *Jun 27 09:49:59.919: ISAKMP (0:134217729): received packet from 209.165.200.2 dport 500 sport 500 Global (I) MM_SA_SETUP *Jun 27 09:49:59.919: ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:49:59.919: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM3 New State = IKE_I_MM4 *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): processing KE payload. message ID = 0 *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 0 *Jun 27 09:49:59.947: ISAKMP: Looking for a matching key for 209.165.200.2 in default : success *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1):found peer pre-shared key matching 209.165.200.2 *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1):SKEYID state generated *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): vendor ID is Unity *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): vendor ID is DPD *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): processing vendor id payload *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1): speaking to another IOS box! *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27 09:49:59.947: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM4 New State = IKE_I_MM4 *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1):Send initial contact *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1):SA is doing pre-shared key authentication using id type ID_IPV4_ADDR *Jun 27 09:50:00.059: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address : 172.16.1.2 protocol : 17 port : 500 length : 12 *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1):Total payload length: 12 *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 500 peer_port 500 (I) MM_KEY_EXCH *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:50:00.059: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM4 New State = IKE_I_MM5 *Jun 27 09:50:00.827: ISAKMP (0:134217729): received packet from 209.165.200.2 dport 500 sport 500 Global (I) MM_KEY_EXCH *Jun 27 09:50:00.827: ISAKMP:(0:1:SW:1):Input = IKE_MSG_FROM_PEER, IKE_MM_EXCH *Jun 27 09:50:00.827: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM5 New State = IKE_I_MM6 *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1): processing ID payload. message ID = 0 *Jun 27 09:50:00.859: ISAKMP (0:134217729): ID payload next-payload : 8 type : 1 address : 209.165.200.2 protocol : 17 port : 500 length : 12 *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1): processing HASH payload. message ID = 0 *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1):SA authentication status: authenticated *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1):SA has been authenticated with 209.165.200.2 *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1):: peer matches *none* of the profiles *Jun 27 09:50:00.859: ISAKMP: Trying to insert a peer 172.16.1.2/209.165.200.2/500/, and inserted successfully. *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_MAIN_MODE *Jun 27 09:50:00.859: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM6 New State = IKE_I_MM6 *Jun 27 09:50:00.919: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PROCESS_COMPLETE *Jun 27 09:50:00.919: ISAKMP:(0:1:SW:1):Old State = IKE_I_MM6 New State = IKE_P1_COMPLETE *Jun 27 09:50:00.959: ISAKMP:(0:1:SW:1):beginning Quick Mode exchange, M-ID of 1689610294 *Jun 27 09:50:01.007: ISAKMP:(0:1:SW:1): sending packet to 209.165.200.2 my_port 500 peer_port 500 (I) QM_IDLE *Jun 27 09:50:01.007: ISAKMP:(0:1:SW:1):Node 1689610294, Input = IKE_MSG_INTERNAL, IKE_INIT_QM *Jun 27 09:50:01.007: ISAKMP:(0:1:SW:1):Old State = IKE_QM_READY New State = IKE_QM_I_QM1 *Jun 27 09:50:01.007: ISAKMP:(0:1:SW:1):Input = IKE_MSG_INTERNAL, IKE_PHASE1_COMPLETE *Jun 27 09:50:01.007: ISAKMP:(0:1:SW:1):Old State = IKE_P1_COMPLETE New State = IKE_P1_COMPLETE *Jun 27 09:50:01.839: ISAKMP (0:134217729): received packet from 209.165.200.2 dport 500 sport 500 Global (I) QM_IDLE *Jun 27 09:50:01.839: ISAKMP:(0:1:SW:1): processing HASH payload. message ID = 1689610294 *Jun 27 09:50:01.839: ISAKMP:(0:1:SW:1): processing SA payload. message ID = 1689610294 *Jun 27 09:50:01.839: ISAKMP:(0:1:SW:1):Checking IPsec proposal 1 *Jun 27 09:50:01.839: ISAKMP: transform 1, ESP_DES *Jun 27 09:50:01.839: ISAKMP: attributes in transform: *Jun 27 09:50:01.839: ISAKMP: encaps is 1 (Tunnel) *Jun 27 09:50:01.839: ISAKMP: SA life type in seconds *Jun 27 09:50:01.839: ISAKMP: SA life duration (basic) of 3600 *Jun 27 09:50:01.839: ISAKMP: SA life type in kilobytes *Jun 27 09:50:01.839: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50 0x0 *Jun 27 09:50:01.839: ISAKMP: authenticator is HMAC-MD5 *Jun 27 09:50:01.839: ISAKMP:(0:1:SW:1):atts are acceptable. *Jun 27 09:50:01.839: IPSEC(validate_proposal_request): proposal part #1, (key eng. msg.) INBOUND local= 172.16.1.2,

```
remote= 209.165.200.2, local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy=
192.168.1.0/255.255.255.0/0/0 (type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel),
lifedur= 0s and 0kb, spi= 0x0(0), conn_id= 0, keysize= 0, flags= 0x2 *Jun 27 09:50:01.839:
IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:50:01.839:
ISAKMP:(0:1:SW:1): processing NONCE payload. message ID = 1689610294 *Jun 27 09:50:01.839:
ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1689610294 *Jun 27 09:50:01.839:
ISAKMP:(0:1:SW:1): processing ID payload. message ID = 1689610294 *Jun 27 09:50:01.839: IPsec:
Flow_switching Allocated flow for flow_id 134217731 *Jun 27 09:50:01.839: IPsec: Flow_switching
Allocated flow for flow_id 134217732 *Jun 27 09:50:01.899: %CRYPTO-5-SESSION_STATUS: Crypto
tunnel is UP . Peer 209.165.200.2:500 Id: 209.165.200.2 *Jun 27 09:50:01.899: ISAKMP: Locking
peer struct 0x2BEDC78, IPSEC refcount 1 for for stuff_ke *Jun 27 09:50:01.899:
ISAKMP:(0:1:SW:1): Creating IPsec SAs *Jun 27 09:50:01.899: inbound SA from 209.165.200.2 to
172.16.1.2 (f/i) 0/ 0 (proxy 192.168.1.0 to 172.16.2.0) *Jun 27 09:50:01.899: has spi 0xE89A0245
and conn_id 2000 and flags 2 *Jun 27 09:50:01.899: lifetime of 3600 seconds *Jun 27
09:50:01.899: lifetime of 4608000 kilobytes *Jun 27 09:50:01.899: has client flags 0x0 *Jun 27
09:50:01.899: outbound SA from 172.16.1.2 to 209.165.200.2 (f/i) 0/0 (proxy 172.16.2.0 to
192.168.1.0) *Jun 27 09:50:01.899: has spi -1242011716 and conn_id 2001 and flags A *Jun 27
09:50:01.899: lifetime of 3600 seconds *Jun 27 09:50:01.899: lifetime of 4608000 kilobytes *Jun
27 09:50:01.899: has client flags 0x0 *Jun 27 09:50:01.899: ISAKMP:(0:1:SW:1): sending packet to
209.165.200.2 my_port 500 peer_port 500 (I) QM_IDLE *Jun 27 09:50:01.899:
ISAKMP:(0:1:SW:1):deleting node 1689610294 error FALSE reason "" *Jun 27 09:50:01.899:
ISAKMP:(0:1:SW:1):Node 1689610294, Input = IKE_MSG_FROM_PEER, IKE_QM_EXCH *Jun 27 09:50:01.899:
ISAKMP:(0:1:SW:1):Old State = IKE_QM_I_QM1 New State = IKE_QM_PHASE2_COMPLETE *Jun 27
09:50:01.907: IPSEC(key_engine): got a queue event with 2 kei messages *Jun 27 09:50:01.907:
IPSEC(initialize_sas): , (key eng. msg.) INBOUND local= 172.16.1.2, remote= 209.165.200.2,
local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.1.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel), lifedur= 3600s and 4608000kb,
spi= 0xE89A0245(3902407237), conn_id= 134219728, keysize= 0, flags= 0x2 *Jun 27 09:50:01.907:
IPSEC(initialize_sas): , (key eng. msg.) OUTBOUND local= 172.16.1.2, remote= 209.165.200.2,
local_proxy= 172.16.2.0/255.255.255.0/0/0 (type=4), remote_proxy= 192.168.1.0/255.255.255.0/0/0
(type=4), protocol= ESP, transform= esp-des esp-md5-hmac (Tunnel), lifedur= 3600s and 4608000kb,
spi= 0xB5F867BC(3052955580), conn_id= 134219729, keysize= 0, flags= 0xA *Jun 27 09:50:01.907:
IPSEC(kei_proxy): head = mymap, map->ivrf = , kei->ivrf = *Jun 27 09:50:01.907:
IPSEC(crypto_ipsec_sa_find_ident_head): reconnecting with the same proxies and 209.165.200.2
*Jun 27 09:50:01.907: IPSEC(mtree_add_ident): src 172.16.2.0, dest 192.168.1.0, dest_port 0 *Jun
27 09:50:01.907: IPSEC(create_sa): sa created, (sa) sa_dest= 172.16.1.2, sa_prot= 50, sa_spi=
0xE89A0245(3902407237), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219728 *Jun 27
09:50:01.907: IPSEC(create_sa): sa created, (sa) sa_dest= 209.165.200.2, sa_prot= 50, sa_spi=
0xB5F867BC(3052955580), sa_trans= esp-des esp-md5-hmac , sa_conn_id= 134219729 *Jun 27
09:50:51.927: ISAKMP:(0:1:SW:1):purging node 1689610294 PAT-Router#debug ip nat detail
IP NAT detailed debugging is on
PAT-Router#show debug
Generic IP:
    IP NAT detailed debugging is on
PAT-Router#
!--- The "i" in this line indicates the packet is traveling from the !--- inside to the outside
(from a NAT perspective) interface. The number in !--- the brackets is the identification number
in the IP packet. This is !--- useful when correlating information with sniffer traces taken
with a !--- network analyzer while troubleshooting problems. *Jun 27 09:49:57.727: NAT*: i: udp
(172.16.1.2, 500) -> (209.165.200.2, 500) [94] !--- The "s" in this line shows the source
address of the packet and how it is !--- being translated. *Jun 27 09:49:57.727: NAT*:
s=172.16.1.2->209.165.201.2, d=209.165.200.2 [94] *Jun 27 09:49:58.927: NAT*: o: udp
(209.165.200.2, 500) -> (209.165.201.2, 500) [100] *Jun 27 09:49:58.927: NAT*: s=209.165.200.2,
d=209.165.201.2->172.16.1.2 [100] *Jun 27 09:49:59.147: NAT*: i: udp (172.16.1.2, 500) ->
(209.165.200.2, 500) [95] *Jun 27 09:49:59.147: NAT*: s=172.16.1.2->209.165.201.2,
d=209.165.200.2 [95] *Jun 27 09:49:59.755: NAT*: o: udp (209.165.200.2, 500) -> (209.165.201.2,
500) [101] *Jun 27 09:49:59.755: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [101] *Jun
27 09:49:59.947: NAT*: i: udp (172.16.1.2, 500) -> (209.165.200.2, 500) [96] *Jun 27
09:49:59.947: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [96] *Jun 27 09:50:00.667:
NAT*: o: udp (209.165.200.2, 500) -> (209.165.201.2, 500) [102] *Jun 27 09:50:00.667: NAT*:
s=209.165.200.2, d=209.165.201.2->172.16.1.2 [102] *Jun 27 09:50:00.895: NAT*: i: udp
(172.16.1.2, 500) -> (209.165.200.2, 500) [97] *Jun 27 09:50:00.895: NAT*: s=172.16.1.2-
>209.165.201.2, d=209.165.200.2 [97] *Jun 27 09:50:01.679: NAT*: o: udp (209.165.200.2, 500) ->
(209.165.201.2, 500) [103] *Jun 27 09:50:01.679: NAT*: s=209.165.200.2, d=209.165.201.2-
```

```
>172.16.1.2 [103] *Jun 27 09:50:01.787: NAT*: i: udp (172.16.1.2, 500) -> (209.165.200.2, 500)
[98] *Jun 27 09:50:01.787: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [98] *Jun 27
09:50:23.667: NAT*: i: esp (172.16.1.2, 26556) -> (209.165.200.2, 0) [99] *Jun 27 09:50:23.667:
NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [99] *Jun 27 09:50:23.715: NAT*: o: esp
(209.165.200.2, -392560059) -> (209.165.201.2, 0) [104] *Jun 27 09:50:23.715: NAT*:
s=209.165.200.2, d=209.165.201.2->172.16.1.2 [104] *Jun 27 09:50:23.787: NAT*: i: esp
(172.16.1.2, 26556) -> (209.165.200.2, 0) [100] *Jun 27 09:50:23.787: NAT*: s=172.16.1.2-
>209.165.201.2, d=209.165.200.2 [100] *Jun 27 09:50:23.847: NAT*: o: esp (209.165.200.2, 581) ->
(209.165.201.2, 0) [105] *Jun 27 09:50:23.847: NAT*: s=209.165.200.2, d=209.165.201.2-
>172.16.1.2 [105] *Jun 27 09:50:23.915: NAT*: i: esp (172.16.1.2, 26556) -> (209.165.200.2, 0)
[101] *Jun 27 09:50:23.915: NAT*: s=172.16.1.2->209.165.201.2, d=209.165.200.2 [101] *Jun 27
09:50:23.967: NAT*: o: esp (209.165.200.2, 581) -> (209.165.201.2, 0) [106] *Jun 27
09:50:23.967: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [106] *Jun 27 09:50:24.047:
NAT*: i: esp (172.16.1.2, 26556) -> (209.165.200.2, 0) [102] *Jun 27 09:50:24.047: NAT*:
s=172.16.1.2->209.165.201.2, d=209.165.200.2 [102] *Jun 27 09:50:24.095: NAT*: o: esp
(209.165.200.2, 581) -> (209.165.201.2, 0) [107] *Jun 27 09:50:24.095: NAT*: s=209.165.200.2,
d=209.165.201.2->172.16.1.2 [107] *Jun 27 09:50:24.207: NAT*: i: esp (172.16.1.2, 26556) ->
(209.165.200.2, 0) [103] *Jun 27 09:50:24.207: NAT*: s=172.16.1.2->209.165.201.2,
d=209.165.200.2 [103] *Jun 27 09:50:24.267: NAT*: o: esp (209.165.200.2, 581) -> (209.165.201.2,
0) [108] *Jun 27 09:50:24.267: NAT*: s=209.165.200.2, d=209.165.201.2->172.16.1.2 [108]
```

[Informações Relacionadas](#)

- [Página de suporte do IPSec](#)
- [Suporte Técnico - Cisco Systems](#)