

# IOS Router: VPN fácil (EzVPN) com exemplo de configuração do modo de extensão de rede (NEM)

## Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenções](#)

[Configurar](#)

[Diagrama de Rede](#)

[Configurações](#)

[Verificar](#)

[Comandos show e exemplo de saída do Easy VPN Server do Cisco 7200](#)

[Comandos show e exemplo de saída do Easy VPN Remote de Cisco 871W](#)

[Troubleshooting](#)

[Comandos do Easy VPN Server](#)

[Comandos do Easy VPN Remote](#)

[Informações Relacionadas](#)

## Introdução

Este documento fornece uma configuração de exemplo para a IPsec entre um Cisco 871 Router e um Cisco 7200VXR Router que usa Easy VPN (EzVPN). O 7200 age conforme o Easy VPN Server e o 871 age como o Easy VPN Remote. Neste exemplo, as interfaces de loopback são utilizadas em ambos roteadores como redes privadas. Esses podem ser substituídos por outras interfaces, como FastEthernet ou Interfaces Serial quando necessário.

Para configurar o IPsec entre um PIX/ASA 7.x e um roteador Cisco 871 utilizando o Easy VPN, consulte [Exemplo de Configuração Remota de um PIX/ASA 7.x Easy VPN com um ASA 5500 como Servidor e um Cisco 871 como o Easy VPN](#).

Para configurar o IPsec entre o Cisco IOS® Easy VPN Remote Hardware Client e o PIX Easy VPN Server, consulte [Exemplo de Configuração de um IOS Easy VPN Remote Hardware Client para um PIX Easy VPN Server](#).

A fim configurar um roteador do Cisco IOS como um EzVPN no [modo de extensão de rede \(NEM\)](#) que conecta a um Cisco VPN 3000 Concentrator, refira [configurar o cliente ezvpn de Cisco no Cisco IOS com o VPN 3000 concentrator](#).

# Pré-requisitos

## Requisitos

Assegure-se de que você tenha uma compreensão básica do IPsec e de Cisco 7200/871 de sistema operacional antes que você tente esta configuração.

## Componentes Utilizados

As informações neste documento são baseadas nestas versões de software e hardware:

- O server do Cisco Easy VPN é um 7200 Router (VXR) esse Software Release 12.4(4)T1 de Cisco IOS® das corridas
- O telecontrole do Cisco Easy VPN é um 871W Router que execute o Cisco IOS Software Release 12.4(2)T1

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto potencial de qualquer comando.

## Convenções

Consulte as [Convenções de Dicas Técnicas da Cisco](#) para obter mais informações sobre convenções de documentos.

## Configurar

Nesta seção, você encontrará informações para configurar os recursos descritos neste documento.

**Nota:** Use a ferramenta [Command Lookup Tool](#) ([apenas para clientes registrados](#)) para obter mais informações sobre os comandos usados neste documento.

## Diagrama de Rede

Este documento utiliza a seguinte configuração de rede:

**Nota:** As interfaces de loopback estão simulando os PC internos.

## Configurações

Este documento utiliza as seguintes configurações:

- [Easy VPN Server \(Cisco 7200VXR Router\)](#)
- [Easy VPN Remote \(Cisco 871W Router\)](#)

<b>Easy VPN Server (Cisco 7200VXR Router)</b>
-----------------------------------------------

3-07-07-7200VXR#show running-config Building
----------------------------------------------

```

configuration... Current configuration : 2059 bytes !
version 12.4 service timestamps debug datetime msec
service timestamps log datetime msec no service
password-encryption ! hostname 3-07-07-7200VXR ! boot-
start-marker boot-end-marker ! ! !--- Enable
Authentication, Authorizing and Accounting (AAA) !---
for user authentication and group authorization. aaa
new-model ! !--- Enable the AAA commands in order !---
to enable Xauth for user authentication. aaa
authentication login userauthen local !--- Enable the
AAA commands !--- in order to enable group
authorization. aaa authorization network groupauthor
local ! aaa session-id common ! resource policy ! ip
subnet-zero ip cef ! ! !--- Define the username and
password to use for Xauth. username cisco password 0
cisco123 ! ! !--- Create an Internet Security
Association and !--- Key Management Protocol (ISAKMP)
policy for Phase 1 negotiations. crypto isakmp policy 3
encr 3des authentication pre-share group 2 ! ! !---
Create a group with the pre-shared key for IKE
authentication. crypto isakmp client configuration group
vpngrp key cisco123 ! ! !--- Create the Phase 2 policy
for actual data encryption. crypto ipsec transform-set
myset esp-3des esp-sha-hmac ! !--- Create a dynamic map
and !--- apply the transform set that was created
earlier. crypto dynamic-map dynmap 10 set transform-set
myset ! ! !--- Create the actual crypto map, !--- and
apply the AAA lists that were created earlier. !---
These commands associate the AAA commands to the crypto
map. crypto map clientmap client authentication list
userauthen crypto map clientmap isakmp authorization
list groupauthor crypto map clientmap 10 ipsec-isakmp
dynamic dynmap ! ! ! interface Loopback10 ip address
10.10.10.1 255.255.255.0 ! interface GigabitEthernet0/1
ip address 158.100.101.254 255.255.255.0 ip nat inside
ip virtual-reassembly duplex auto speed auto media-type
rj45 no negotiation auto ! interface GigabitEthernet0/2
ip address 158.100.102.254 255.255.255.0 ip nat outside
ip virtual-reassembly duplex auto speed 100 media-type
rj45 no negotiation auto ! ! ! !--- Apply the crypto map
on the interface where !--- traffic leaves the router.
interface GigabitEthernet0/3 ip address 172.16.186.186
255.255.255.0 duplex auto speed auto media-type rj45 no
negotiation auto crypto map clientmap ! interface
FastEthernet1/0 no ip address shutdown duplex half ! ip
default-gateway 172.16.186.1 ip classless ip route
0.0.0.0 0.0.0.0 172.16.186.1 no ip http server no ip
http secure-server ! ! ip nat Stateful id 10 ip nat pool
honnat 158.100.96.90 158.100.96.99 netmask 255.255.255.0
ip nat inside source route-map test pool honnat mapping-
id 10 overload ! logging alarm informational access-list
100 permit ip any any ! route-map test permit 10 match
ip address 100 ! ! ! ! control-plane ! ! ! ! !
gatekeeper shutdown ! ! line con 0 logging synchronous
stopbits 1 line aux 0 stopbits 1 line vty 0 4 ! ! end

```

### Easy VPN Remote (Cisco 871W Router)

```

3-03-06-871W#show running-config Current configuration :
1563 bytes ! version 12.4 no service pad service
timestamps debug datetime msec service timestamps log
datetime msec service password-encryption ! hostname 3-
03-06-871W ! boot-start-marker boot-end-marker ! ! no
aaa new-model ! resource policy ! ip cef ! ! ! ! ip
name-server 171.70.168.183 ! ! username cisco privilege

```

```

15 password 7 00071A150754 ! ! ! ! !--- Set the
parameters to connect to the !--- appropriate Easy VPN
group on the Easy VPN server. crypto ipsec client ezvpn
ez connect auto group vpngrp key cisco123 mode network-
extension peer 172.16.186.186 xauth userid mode
interactive ! ! ! !--- Define the inside interfaces that
will access !--- and can be accessed via Easy VPN.
interface Loopback0 ip address 10.12.130.1
255.255.255.255 crypto ipsec client ezvpn ez inside !
interface FastEthernet0 ! interface FastEthernet1 !
interface FastEthernet2 ! interface FastEthernet3 !---
Use the crypto ipsec client ezvpn <name> command on the
!--- interface that connects to the Easy VPN server !---
in order to complete the Easy VPN. interface
FastEthernet4 ip address 172.16.186.130 255.255.255.0
duplex auto speed auto crypto ipsec client ezvpn ez !
interface Dot11Radio0 no ip address shutdown speed
basic-1.0 basic-2.0 basic-5.5 6.0 9.0 basic-11.0 12.0
18.0 24.0 36.0 48.0 54.0 station-role root ! interface
Vlan1 no ip address ! ip default-gateway 172.16.186.1 ip
route 0.0.0.0 0.0.0.0 172.16.186.1 ! ! no ip http server
no ip http secure-server ! access-list 121 dynamic
testlist permit tcp any host 12.12.12.12 eq 5900 snmp-
server community presto RW ! ! ! route-map polo permit
10 ! route-map asa permit 10 ! tacacs-server host
66.94.234.13 tacacs-server directed-request ! control-
plane ! ! line con 0 no modem enable line aux 0 line vty
0 4 login ! scheduler max-task-time 5000 ! webvpn
context Default_context ssl authenticate verify all ! no
inservice ! end

```

## Verificar

Use estas seções para confirmar que sua configuração trabalha corretamente.

- [Comandos show e exemplo de saída do Easy VPN Server do Cisco 7200](#)
- [Comandos show e exemplo de saída do Easy VPN Remote de Cisco 871W](#)

A [Output Interpreter Tool \(apenas para clientes registrados\)](#) (OIT) suporta determinados comandos show. Use a OIT para exibir uma análise da saída do comando show.

## Comandos show e exemplo de saída do Easy VPN Server do Cisco 7200

- **mostre isakmp cripto sa** — Indica todas as associações de segurança atuais do Internet Key Exchange (IKE) (SA) em um par.3-07-07-7200VXR#**show crypto isakmp sa** IPv4 Crypto ISAKMP SA  
dst src state conn-id slot status 172.16.186.186 172.16.186.130 QM\_IDLE 1008 0 ACTIVE IPv6  
Crypto ISAKMP SA
- **mostre IPsec cripto sa** — Sas de IPsec dos indicadores construído entre pares.3-07-07-7200VXR#**show crypto ipsec sa** interface: GigabitEthernet0/3 Crypto map tag: clientmap, local  
addr 172.16.186.186 protected vrf: (none) local ident (addr/mask/prot/port):  
(0.0.0.0/0.0.0.0/0/0) remote ident (addr/mask/prot/port): (10.12.130.1/255.255.255.255/0/0)  
current\_peer 172.16.186.130 port 500 PERMIT, flags={ } #pkts encaps: 5, #pkts encrypt: 5,  
#pkts digest: 5 #pkts decaps: 5, #pkts decrypt: 5, #pkts verify: 5 #pkts compressed: 0,  
#pkts decompressed: 0 #pkts not compressed: 0, #pkts compr. failed: 0 #pkts not  
decompressed: 0, #pkts decompress failed: 0 #send errors 0, #recv errors 0 local crypto  
endpt.: 172.16.186.186, remote crypto endpt.: 172.16.186.130 path mtu 1500, ip mtu 1500  
current outbound spi: 0x29354010(691355664) inbound esp sas: spi: 0x6875F644(1752561220)  
transform: esp-3des esp-sha-hmac , in use settings = {Tunnel, } conn id: 11, flow\_id: SW:11,  
crypto map: clientmap sa timing: remaining key lifetime (k/sec): (4439946/3526) IV size: 8

```
bytes replay detection support: Y Status: ACTIVE inbound ah sas: inbound pcp sas: outbound
esp sas: spi: 0x29354010(691355664) transform: esp-3des esp-sha-hmac , in use settings
={Tunnel, } conn id: 12, flow_id: SW:12, crypto map: clientmap sa timing: remaining key
lifetime (k/sec): (4439946/3524) IV size: 8 bytes replay detection support: Y Status: ACTIVE
```

## Comandos show e exemplo de saída do Easy VPN Remote de Cisco 871W

- **show crypto isakmp sa** – Exibe todas as SAs de IKE atuais em um correspondente.3-03-06-871W#**show crypto isakmp sa** IPv4 Crypto ISAKMP SA dst src state conn-id slot status  
172.16.186.186 172.16.186.130 QM\_IDLE 2003 0 ACTIVE IPv6 Crypto ISAKMP SA
- **mostre IPsec cripto sa** — Sas de IPsec dos indicadores construído entre pares.3-03-06-871W#**show crypto ipsec sa** interface: FastEthernet4 Crypto map tag: FastEthernet4-head-0, local addr 172.16.186.130 protected vrf: (none) local ident (addr/mask/prot/port): (10.12.130.1/255.255.255.255/0/0) remote ident (addr/mask/prot/port): (0.0.0.0/0.0.0.0/0/0) current\_peer 172.16.186.186 port 500 PERMIT, flags={origin\_is\_acl,} #pkts encaps: 5, #pkts encrypt: 5, #pkts digest: 5 #pkts decaps: 5, #pkts decrypt: 5, #pkts verify: 5 #pkts compressed: 0, #pkts decompressed: 0 #pkts not compressed: 0, #pkts compr. failed: 0 #pkts not decompressed: 0, #pkts decompress failed: 0 #send errors 0, #recv errors 0 local crypto endpt.: 172.16.186.130, remote crypto endpt.: 172.16.186.186 path mtu 1500, ip mtu 1500 current outbound spi: 0x6875F644(1752561220) inbound esp sas: spi: 0x29354010(691355664) transform: esp-3des esp-sha-hmac , in use settings = {Tunnel, } conn id: 11, flow\_id: Motorola SEC 1.0:11, crypto map: FastEthernet4-head-0 sa timing: remaining key lifetime (k/sec): (4607687/3531) IV size: 8 bytes replay detection support: Y Status: ACTIVE inbound ah sas: inbound pcp sas: outbound esp sas: spi: 0x6875F644(1752561220) transform: esp-3des esp-sha-hmac , in use settings = {Tunnel, } conn id: 12, flow\_id: Motorola SEC 1.0:12, crypto map: FastEthernet4-head-0 sa timing: remaining key lifetime (k/sec): (4607687/3528) IV size: 8 bytes replay detection support: Y Status: ACTIVE outbound ah sas: outbound pcp sas:
- **mostre o EzVPN do cliente de IPsec de criptografia** — Indica a configuração remota do Cisco Easy VPN.3-03-06-871W#**show crypto ipsec client ezvpn** Easy VPN Remote Phase: 6 Tunnel name : ez Inside interface list: Loopback0 Outside interface: FastEthernet4 Current State: IPSEC\_ACTIVE Last Event: SOCKET\_UP Save Password: Disallowed Current EzVPN Peer: 172.16.186.186 3-03-06-871W#**ping 10.10.10.1 source 10.12.130.1** Type escape sequence to abort. Sending 5, 100-byte ICMP Echos to 10.10.10.1, timeout is 2 seconds: Packet sent with a source address of 10.12.130.1 !!!!! Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms

## Troubleshooting

Use esta seção para resolver problemas de configuração.

A [Output Interpreter Tool \(apenas para clientes registrados\)](#) (OIT) suporta determinados comandos show. Use a OIT para exibir uma análise da saída do comando show.

**Nota:** Consulte [Informações Importantes sobre Comandos de Depuração](#) antes de usar comandos debug.

Se você estabeleceu o Easy VPN Remote e o Easy VPN Server como este documento descreve e você ainda experimenta problemas, recolha o **resultado do debug** de cada dispositivo e a saída dos **comandos show** para a análise pelo Suporte técnico de Cisco.

Estas seções indicam **comandos debug** e exemplo de saída:

- [Comandos do Easy VPN Server](#)
- [Comandos do Easy VPN Remote](#)

## Comandos do Easy VPN Server

- **IPsec do debug crypto** — Indica as negociações de IPSEC de fase 2.
- **debug crypto isakmp** — Exibe as negociações ISAKMP da Fase 1.

```
3-07-07-7200VXR#debug crypto ipsec 3-07-07-7200VXR#debug crypto isakmp *May 4 00:44:19.389:
IPSEC(key_engine): got a queue event with 1 KMI message(s) *May 4 00:44:20.937: ISAKMP (0:0):
received packet from 172.16.186.130 dport 500 sport 500 Global (N) NEW SA *May 4 00:44:20.937:
ISAKMP: Created a peer struct for 172.16.186.130, peer port 500 *May 4 00:44:20.937: ISAKMP: New
peer created peer = 0x6745B8E0 peer_handle = 0x80000009 *May 4 00:44:20.937: ISAKMP: Locking
peer struct 0x6745B8E0, refcount 1 for crypto_isakmp_process_block *May 4 00:44:20.937:
ISAKMP:(0):Setting client config settings 6741FF98 *May 4 00:44:20.937: ISAKMP:(0):(Re)Setting
client xauth list and state *May 4 00:44:20.937: ISAKMP/xauth: initializing AAA request *May 4
00:44:20.937: ISAKMP: local port 500, remote port 500 *May 4 00:44:20.937: ISAKMP: Find a dup sa
in the avl tree during calling isadb_insert sa = 67369734 *May 4 00:44:20.937: ISAKMP:(0):
processing SA payload. message ID = 0 *May 4 00:44:20.937: ISAKMP:(0): processing ID payload.
message ID = 0 *May 4 00:44:20.937: ISAKMP (0:0): ID payload next-payload : 13 type : 11 group
id : vpngrp protocol : 17 port : 0 length : 14 *May 4 00:44:20.937: ISAKMP:(0):: peer matches
*none* of the profiles *May 4 00:44:20.937: ISAKMP:(0): processing vendor id payload *May 4
00:44:20.937: ISAKMP:(0): vendor ID seems Unity/DPD but major 245 mismatch *May 4 00:44:20.937:
ISAKMP (0:0): vendor ID is NAT-T v7 *May 4 00:44:20.937: ISAKMP:(0): processing vendor id
payload *May 4 00:44:20.937: ISAKMP:(0): vendor ID seems Unity/DPD but major 157 mismatch *May 4
00:44:20.937: ISAKMP:(0): vendor ID is NAT-T v3 *May 4 00:44:20.937: ISAKMP:(0): processing
vendor id payload *May 4 00:44:20.937: ISAKMP:(0): vendor ID seems Unity/DPD but major 123
mismatch *May 4 00:44:20.937: ISAKMP:(0): vendor ID is NAT-T v2 *May 4 00:44:20.937: ISAKMP:(0):
Authentication by xauth preshared *May 4 00:44:20.937: ISAKMP:(0):Checking ISAKMP transform 1
against priority 3 policy *May 4 00:44:20.937: ISAKMP: encryption AES-CBC *May 4 00:44:20.937:
ISAKMP: keylength of 128 *May 4 00:44:20.937: ISAKMP: hash SHA *May 4 00:44:20.937: ISAKMP:
default group 2 *May 4 00:44:20.937: ISAKMP: auth XAUTHInitPreShared *May 4 00:44:20.937:
ISAKMP: life type in seconds *May 4 00:44:20.937: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4
0x9B *May 4 00:44:20.937: ISAKMP:(0):Encryption algorithm offered does not match policy! *May 4
00:44:20.937: ISAKMP:(0):atts are not acceptable. Next payload is 3 *May 4 00:44:20.937:
ISAKMP:(0):Checking ISAKMP transform 2 against priority 3 policy *May 4 00:44:20.937: ISAKMP:
encryption AES-CBC *May 4 00:44:20.937: ISAKMP: keylength of 128 *May 4 00:44:20.937: ISAKMP:
hash MD5 *May 4 00:44:20.937: ISAKMP: default group 2 *May 4 00:44:20.937: ISAKMP: auth
XAUTHInitPreShared *May 4 00:44:20.937: ISAKMP: life type in seconds *May 4 00:44:20.937:
ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B *May 4 00:44:20.937: ISAKMP:(0):Encryption
algorithm offered does not match policy! *May 4 00:44:20.937: ISAKMP:(0):atts are not
acceptable. Next payload is 3 *May 4 00:44:20.937: ISAKMP:(0):Checking ISAKMP transform 3
against priority 3 policy *May 4 00:44:20.937: ISAKMP: encryption AES-CBC *May 4 00:44:20.937:
ISAKMP: keylength of 192 *May 4 00:44:20.937: ISAKMP: hash SHA *May 4 00:44:20.937: ISAKMP:
default group 2 *May 4 00:44:20.937: ISAKMP: auth XAUTHInitPreShared *May 4 00:44:20.937:
ISAKMP: life type in seconds *May 4 00:44:20.937: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4
0x9B *May 4 00:44:20.937: ISAKMP:(0):Encryption algorithm offered does not match policy! *May 4
00:44:20.937: ISAKMP:(0):atts are not acceptable. Next payload is 3 *May 4 00:44:20.937:
ISAKMP:(0):Checking ISAKMP transform 4 against priority 3 policy *May 4 00:44:20.937: ISAKMP:
encryption AES-CBC *May 4 00:44:20.937: ISAKMP: keylength of 192 *May 4 00:44:20.937: ISAKMP:
hash MD5 *May 4 00:44:20.937: ISAKMP: default group 2 *May 4 00:44:20.937: ISAKMP: auth
XAUTHInitPreShared *May 4 00:44:20.937: ISAKMP: life type in seconds *May 4 00:44:20.937:
ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B *May 4 00:44:20.937: ISAKMP:(0):Encryption
algorithm offered does not match policy! *May 4 00:44:20.937: ISAKMP:(0):atts are not
acceptable. Next payload is 3 *May 4 00:44:20.937: ISAKMP:(0):Checking ISAKMP transform 5
against priority 3 policy *May 4 00:44:20.937: ISAKMP: encryption AES-CBC *May 4 00:44:20.937:
ISAKMP: keylength of 256 *May 4 00:44:20.937: ISAKMP: hash SHA *May 4 00:44:20.937: ISAKMP:
default group 2 *May 4 00:44:20.937: ISAKMP: auth XAUTHInitPreShared *May 4 00:44:20.937:
ISAKMP: life type in seconds *May 4 00:44:20.937: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4
0x9B *May 4 00:44:20.937: ISAKMP:(0):Encryption algorithm offered does not match policy! *May 4
00:44:20.937: ISAKMP:(0):atts are not acceptable. Next payload is 3 *May 4 00:44:20.937:
ISAKMP:(0):Checking ISAKMP transform 6 against priority 3 policy *May 4 00:44:20.937: ISAKMP:
encryption AES-CBC *May 4 00:44:20.937: ISAKMP: keylength of 256 *May 4 00:44:20.941: ISAKMP:
hash MD5 *May 4 00:44:20.941: ISAKMP: default group 2 *May 4 00:44:20.941: ISAKMP: auth
XAUTHInitPreShared *May 4 00:44:20.941: ISAKMP: life type in seconds *May 4 00:44:20.941:
```

ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 7 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 128 \*May 4 00:44:20.941: ISAKMP: hash SHA \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 8 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 128 \*May 4 00:44:20.941: ISAKMP: hash MD5 \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 9 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 192 \*May 4 00:44:20.941: ISAKMP: hash SHA \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 10 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 192 \*May 4 00:44:20.941: ISAKMP: hash MD5 \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 11 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 256 \*May 4 00:44:20.941: ISAKMP: hash SHA \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 12 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption AES-CBC \*May 4 00:44:20.941: ISAKMP: keylength of 256 \*May 4 00:44:20.941: ISAKMP: hash MD5 \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth pre-share \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: ISAKMP:(0):Encryption algorithm offered does not match policy! \*May 4 00:44:20.941: ISAKMP:(0):atts are not acceptable. Next payload is 3 \*May 4 00:44:20.941: ISAKMP:(0):Checking ISAKMP transform 13 against priority 3 policy \*May 4 00:44:20.941: ISAKMP: encryption 3DES-CBC \*May 4 00:44:20.941: ISAKMP: hash SHA \*May 4 00:44:20.941: ISAKMP: default group 2 \*May 4 00:44:20.941: ISAKMP: auth XAUTHInitPreShared \*May 4 00:44:20.941: ISAKMP: life type in seconds \*May 4 00:44:20.941: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:44:20.941: **ISAKMP:(0):atts are acceptable. Next payload is 3** \*May 4 00:44:20.941: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.941: ISAKMP:(0): vendor ID seems Unity/DPD but major 245 mismatch \*May 4 00:44:20.941: ISAKMP (0:0): vendor ID is NAT-T v7 \*May 4 00:44:20.941: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.941: ISAKMP:(0): vendor ID seems Unity/DPD but major 157 mismatch \*May 4 00:44:20.941: ISAKMP:(0): vendor ID is NAT-T v3 \*May 4 00:44:20.941: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.941: ISAKMP:(0): vendor ID seems Unity/DPD but major 123 mismatch \*May 4 00:44:20.941: ISAKMP:(0): vendor ID is NAT-T v2 \*May 4 00:44:20.941: ISAKMP:(0): processing KE payload. message ID = 0 \*May 4 00:44:20.957: ISAKMP:(0): processing NONCE payload. message ID = 0 \*May 4 00:44:20.957: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.957: ISAKMP:(0): vendor ID is DPD \*May 4 00:44:20.957: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.957: ISAKMP:(0): vendor ID seems Unity/DPD but major 79 mismatch \*May 4 00:44:20.957: ISAKMP:(0): vendor ID is XAUTH \*May 4 00:44:20.957: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.957: ISAKMP:(0): claimed IOS but failed authentication \*May 4 00:44:20.957: ISAKMP:(0): processing vendor id payload \*May 4 00:44:20.957: ISAKMP:(0): vendor ID is Unity \*May 4 00:44:20.957: ISAKMP:(0):Input = IKE\_MSG\_FROM\_PEER, IKE\_AM\_EXCH \*May 4 00:44:20.957: ISAKMP:(0):Old State = IKE\_READY New State = IKE\_R\_AM\_AAA\_AWAIT \*May 4 00:44:20.957: ISAKMP:(1008): constructed NAT-T vendor-07 ID \*May 4 00:44:20.957: ISAKMP:(1008):SA is doing pre-shared key authentication plus XAUTH using id type ID\_IPV4\_ADDR \*May 4 00:44:20.957: ISAKMP (0:1008): ID payload next-payload : 10 type : 1 address

: 172.16.186.186 protocol : 17 port : 0 length : 12 \*May 4 00:44:20.957: ISAKMP:(1008):Total payload length: 12 \*May 4 00:44:20.957: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500 peer\_port 500 (R) AG\_INIT\_EXCH \*May 4 00:44:20.957: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_AAA, PRESHARED\_KEY\_REPLY \*May 4 00:44:20.957: ISAKMP:(1008):Old State = IKE\_R\_AM\_AAA\_AWAIT New State = IKE\_R\_AM2 \*May 4 00:44:20.985: ISAKMP (0:1008): received packet from 172.16.186.130 dport 500 sport 500 Global (R) AG\_INIT\_EXCH \*May 4 00:44:20.985: ISAKMP:(1008): processing HASH payload. message ID = 0 \*May 4 00:44:20.985: ISAKMP:(1008): processing NOTIFY INITIAL\_CONTACT protocol 1 spi 0, message ID = 0, sa = 67369734 \*May 4 00:44:20.985: ISAKMP:(1008):SA authentication status: authenticated \*May 4 00:44:20.985: ISAKMP:(1008):SA has been authenticated with 172.16.186.130 \*May 4 00:44:20.985: ISAKMP:(1008):SA authentication status: authenticated \*May 4 00:44:20.985: ISAKMP:(1008): Process initial contact, bring down existing phase 1 and 2 SA's with local 172.16.186.186 remote 172.16.186.130 remote port 500 \*May 4 00:44:20.985: ISAKMP:(1008):returning IP addr to the address pool \*May 4 00:44:20.985: ISAKMP: Trying to insert a peer 172.16.186.186/172.16.186.130/500/, and inserted successfully 6745B8E0. \*May 4 00:44:20.985: ISAKMP: set new node 1361385973 to CONF\_XAUTH \*May 4 00:44:20.985: ISAKMP:(1008):Sending NOTIFY RESPONDER\_LIFETIME protocol 1 spi 1722618680, message ID = 1361385973 \*May 4 00:44:20.985: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500 peer\_port 500 (R) QM\_IDLE \*May 4 00:44:20.985: ISAKMP:(1008):purging node 1361385973 \*May 4 00:44:20.985: ISAKMP: Sending phase 1 responder lifetime 86400 \*May 4 00:44:20.985: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_PEER, IKE\_AM\_EXCH \*May 4 00:44:20.985: ISAKMP:(1008):Old State = IKE\_R\_AM2 New State = **IKE\_P1\_COMPLETE** !--- Requesting Xauth. \*May 4 00:44:20.985: IPSEC(key\_engine): got a queue event with 1 KMI message(s) \*May 4 00:44:20.985: ISAKMP:(1008):Need XAUTH \*May 4 00:44:20.985: ISAKMP: set new node -605466681 to CONF\_XAUTH \*May 4 00:44:20.985: ISAKMP/xauth: request attribute XAUTH\_USER\_NAME\_V2 \*May 4 00:44:20.985: ISAKMP/xauth: request attribute XAUTH\_USER\_PASSWORD\_V2 \*May 4 00:44:20.985: ISAKMP:(1008): initiating peer config to 172.16.186.130. ID = -605466681 \*May 4 00:44:20.985: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500 peer\_port 500 (R) CONF\_XAUTH \*May 4 00:44:20.985: ISAKMP:(1008):Input = IKE\_MSG\_INTERNAL, IKE\_PHASE1\_COMPLETE \*May 4 00:44:20.985: ISAKMP:(1008):Old State = IKE\_P1\_COMPLETE New State = IKE\_XAUTH\_REQ\_SENT \*May 4 00:44:35.985: ISAKMP:(1008): retransmitting phase 2 CONF\_XAUTH -605466681 ... \*May 4 00:44:35.985: ISAKMP (0:1008): incrementing error counter on node, attempt 1 of 5: retransmit phase 2 \*May 4 00:44:35.985: ISAKMP (0:1008): incrementing error counter on sa, attempt 1 of 5: retransmit phase 2 \*May 4 00:44:35.985: ISAKMP:(1008): retransmitting phase 2 -605466681 CONF\_XAUTH \*May 4 00:44:35.985: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500 peer\_port 500 (R) CONF\_XAUTH R# 3-07-07-7200VXR# \*May 4 00:44:50.985: ISAKMP:(1008): retransmitting phase 2 CONF\_XAUTH -605466681 ... \*May 4 00:44:50.985: ISAKMP (0:1008): incrementing error counter on node, attempt 2 of 5: retransmit phase 2 \*May 4 00:44:50.985: ISAKMP (0:1008): incrementing error counter on sa, attempt 2 of 5: retransmit phase 2 \*May 4 00:44:50.985: ISAKMP:(1008): retransmitting phase 2 -605466681 CONF\_XAUTH \*May 4 00:44:50.985: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500 peer\_port 500 (R) CONF\_XAUTH 3-07-07-7200VXR# \*May 4 00:45:01.997: ISAKMP (0:1008): received packet from 172.16.186.130 dport 500 sport 500 Global (R) CONF\_XAUTH \*May 4 00:45:01.997: ISAKMP:(1008):processing transaction payload from 172.16.186.130. message ID = -605466681 \*May 4 00:45:01.997: ISAKMP: Config payload REPLY \*May 4 00:45:01.997: ISAKMP/xauth: reply attribute XAUTH\_USER\_NAME\_V2 \*May 4 00:45:01.997: ISAKMP/xauth: reply attribute XAUTH\_USER\_PASSWORD\_V2 \*May 4 00:45:01.997: ISAKMP:(1008):deleting node -605466681 error FALSE reason "Done with xauth request/reply exchange" \*May 4 00:45:01.997: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_REPLY \*May 4 00:45:01.997: ISAKMP:(1008):Old State = IKE\_XAUTH\_REQ\_SENT New State = IKE\_XAUTH\_AAA\_CONT\_LOGIN\_AWAIT \*May 4 00:45:01.997: ISAKMP: set new node 1283697340 to CONF\_XAUTH \*May 4 00:45:01.997: ISAKMP:(1008): initiating peer config to 172.16.186.130. ID = 1283697340 \*May 4 00:45:01.997: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 5 3-07-07-7200VX00 peer\_port 500 (R) CONF\_XAUTH \*May 4 00:45:01.997: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_AAA, IKE\_AAA\_CONT\_LOGIN \*May 4 00:45:01.997: ISAKMP:(1008):Old State = IKE\_XAUTH\_AAA\_CONT\_LOGIN\_AWAIT New State = IKE\_XAUTH\_SET\_SENT \*May 4 00:45:02.005: ISAKMP (0:1008): received packet from 172.16.186.130 dport 500 sport 500 Global (R) CONF\_XAUTH \*May 4 00:45:02.005: ISAKMP:(1008):processing transaction payload from 172.16.186.130. message ID = 1283697340 \*May 4 00:45:02.005: ISAKMP: Config payload ACK \*May 4 00:45:02.005: ISAKMP:(1008): XAUTH ACK Processed \*May 4 00:45:02.005: ISAKMP:(1008):deleting node 1283697340 error FALSE reason "Transaction mode done" \*May 4 00:45:02.005: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_ACK \*May 4 00:45:02.005: ISAKMP:(1008):Old State = IKE\_XAUTH\_SET\_SENT New State = IKE\_P1\_COMPLETE \*May 4 00:45:02.005: ISAKMP:(1008):Input = IKE\_MSG\_INTERNAL, IKE\_PHASE1\_COMPLETE \*May 4 00:45:02.005: ISAKMP:(1008):Old State = IKE\_P1\_COMPLETE New State = IKE\_P1\_COMPLETE \*May 4 00:45:02.005: ISAKMP (0:1008): received packet from 172.16.186.130 dport 500 sport 500 Global (R) QM\_IDLE \*May 4 00:45:02.005: ISAKMP: set new node 104696831 to QM\_IDLE \*May 4 00:45:02.005: ISAKMP:(1008):processing transaction



payload from 172.16.186.130. message ID = 104696831 \*May 4 00:45:02.005: ISAKMP: Config payload  
REQUEST \*May 4 00:45:02.005: ISAKMP:(1008):checking request: \*May 4 00:45:02.005: ISAKMP:  
MODECFG\_CONFIG\_URL \*May 4 00:45:02.005: ISAKMP: MODECFG\_CONFIG\_VERSION \*May 4 00:45:02.009:  
ISAKMP: IP4\_DNS \*May 4 00:45:02.009: ISAKMP: IP4\_DNS \*May 4 00:45:02.009: ISAKMP: IP4\_NBNS \*May  
4 00:45:02.009: ISAKMP: IP4\_NBNS \*May 4 00:45:02.009: ISAKMP: SPLIT\_INCLUDE \*May 4 00:45:02.009:  
ISAKMP: SPLIT\_DNS \*May 4 00:45:02.009: ISAKMP: DEFAULT\_DOMAIN \*May 4 00:45:02.009: ISAKMP:  
MODECFG\_SAVEPWD \*May 4 00:45:02.009: ISAKMP: INCLUDE\_LOCAL\_LAN \*May 4 00:45:02.009: ISAKMP: PFS  
\*May 4 00:45:02.009: ISAKMP: BACKUP\_SERVER \*May 4 00:45:02.009: ISAKMP: APPLICATION\_VERSION \*May  
4 00:45:02.009: ISAKMP: MODECFG-BANNER \*May 4 00:45:02.009: ISAKMP: MODECFG\_IPSEC\_INT\_CONF \*May  
4 00:45:02.009: ISAKMP/author: Author request for group vpngrpssuccessfully sent to AAA \*May 4  
00:45:02.009: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_REQUEST \*May 4 00:45:02.009:  
ISAKMP:(1008):Old State = IKE\_P1\_COMPLETE New State = IKE\_CONFIG\_AUTHOR\_AAA\_AWAIT \*May 4  
00:45:02.009: ISAKMP:(1008):Receive config attributes requested butconfig attributes not in  
crypto map. Sending empty reply. \*May 4 00:45:02.009: ISAKMP:(1008):attributes sent in message:  
\*May 4 00:45:02.009: ISAKMP: Sending APPLICATION\_VERSION string: Cisco IOS Software, 7200  
Software (C7200-ADVENTERPRISEK9-M), Version 12.4(4)T1, RELEASE SOFTWARE (fc4) Technical Support:  
http://www.cisco.com/techsupport Copyright (c) 1986-2005 by Cisco Systems, Inc. Compiled Wed 21-  
Dec-05 22:58 by ccai \*May 4 00:45:02.009: ISAKMP: Sending IPsec Interface Config reply value 0  
\*May 4 00:45:02.009: ISAKMP:(1008): responding to peer config from 172.16.186.130. ID =  
104696831 \*May 4 00:45:02.009: ISAKMP:(1008): sending packet to 172.16.186.130 my\_port 500  
peer\_port 500 (R) CONF\_ADDR \*May 4 00:45:02.009: ISAKMP:(1008):deleting node 104696831 error  
FALSE reason "No Error" \*May 4 00:45:02.009: ISAKMP:(1008):Input = IKE\_MSG\_FROM\_AAA,  
IKE\_AAA\_GROUP\_ATTR \*May 4 00:45:02.009: ISAKMP:(1008):Old State =IKE\_CONFIG\_AUTHOR\_AAA\_AWAIT  
New State = IKE\_P1\_COMPLETE \*May 4 00:45:02.009: ISAKMP:(1008):Input = IKE\_MSG\_INTERNAL,  
IKE\_PHASE1\_COMPLETE \*May 4 00:45:02.009: ISAKMP:(1008):Old State = IKE\_P1\_COMPLETE New State =  
IKE\_P1\_COMPLETE \*May 4 00:45:02.029: ISAKMP (0:1008): received packet from 172.16.186.130 dport  
500 sport 500 Global (R) QM\_IDLE \*May 4 00:45:02.029: ISAKMP: set new node -1665883002 to  
QM\_IDLE \*May 4 00:45:02.029: ISAKMP:(1008): processing HASH payload. message ID = -1665883002  
\*May 4 00:45:02.029: ISAKMP:(1008): processing SA payload. message ID = -1665883002 \*May 4  
00:45:02.029: ISAKMP:(1008):Checking IPsec proposal 1 \*May 4 00:45:02.029: ISAKMP: transform 1,  
ESP\_AES \*May 4 00:45:02.029: ISAKMP: attributes in transform: \*May 4 00:45:02.029: ISAKMP:  
encaps is 1 (Tunnel) \*May 4 00:45:02.029: ISAKMP: SA life type in seconds \*May 4 00:45:02.029:  
ISAKMP: SA life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:45:02.029: ISAKMP: SA life type  
in kilobytes \*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50 0x0 \*May 4  
00:45:02.029: ISAKMP: authenticator is HMAC-SHA \*May 4 00:45:02.029: ISAKMP: key length is 128  
\*May 4 00:45:02.029: ISAKMP:(1008):atts are acceptable. \*May 4 00:45:02.029:  
IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.029:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes esp-sha-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 128, flags= 0x0 \*May 4  
00:45:02.029: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes esp-sha-hmac } \*May 4 00:45:02.029: ISAKMP:(1008): IPsec policy invalidated  
proposal \*May 4 00:45:02.029: ISAKMP:(1008):Checking IPsec proposal 2 \*May 4 00:45:02.029:  
ISAKMP: transform 1, ESP\_AES \*May 4 00:45:02.029: ISAKMP: attributes in transform: \*May 4  
00:45:02.029: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.029: ISAKMP: SA life type in seconds  
\*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:45:02.029:  
ISAKMP: SA life type in kilobytes \*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0  
0x46 0x50 0x0 \*May 4 00:45:02.029: ISAKMP: authenticator is HMAC-MD5 \*May 4 00:45:02.029:  
ISAKMP: key length is 128 \*May 4 00:45:02.029: ISAKMP:(1008):atts are acceptable. \*May 4  
00:45:02.029: IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.029:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes esp-md5-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 128, flags= 0x0 \*May 4  
00:45:02.029: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes esp-md5-hmac } \*May 4 00:45:02.029: ISAKMP:(1008): IPsec policy invalidated  
proposal \*May 4 00:45:02.029: ISAKMP:(1008):Checking IPsec proposal 3 \*May 4 00:45:02.029:  
ISAKMP: transform 1, ESP\_AES \*May 4 00:45:02.029: ISAKMP: attributes in transform: \*May 4  
00:45:02.029: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.029: ISAKMP: SA life type in seconds  
\*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xC4 0x9B \*May 4 00:45:02.029:  
ISAKMP: SA life type in kilobytes \*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0  
0x46 0x50 0x0 \*May 4 00:45:02.029: ISAKMP: authenticator is HMAC-SHA \*May 4 00:45:02.029:  
ISAKMP: key length is 192 \*May 4 00:45:02.029: ISAKMP:(1008):atts are acceptable. \*May 4

00:45:02.029: IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.029:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes 192 esp-sha-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 192, flags= 0x0 \*May 4  
00:45:02.029: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes 192 esp-sha-hmac } \*May 4 00:45:02.029: ISAKMP:(1008): IPsec policy  
invalidated proposal \*May 4 00:45:02.029: ISAKMP:(1008):Checking IPsec proposal 4 \*May 4  
00:45:02.029: ISAKMP: transform 1, ESP\_AES \*May 4 00:45:02.029: ISAKMP: attributes in transform:  
\*May 4 00:45:02.029: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.029: ISAKMP: SA life type in  
seconds \*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9B \*May 4  
00:45:02.029: ISAKMP: SA life type in kilobytes \*May 4 00:45:02.029: ISAKMP: SA life duration  
(VPI) of 0x0 0x46 0x50 0x0 \*May 4 00:45:02.029: ISAKMP: authenticator is HMAC-MD5 \*May 4  
00:45:02.029: ISAKMP: key length is 192 \*May 4 00:45:02.029: ISAKMP:(1008):atts are acceptable.  
\*May 4 00:45:02.029: IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.029:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes 192 esp-md5-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 192, flags= 0x0 \*May 4  
00:45:02.029: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes 192 esp-md5-hmac } \*May 4 00:45:02.029: ISAKMP:(1008): IPsec policy  
invalidated proposal \*May 4 00:45:02.029: ISAKMP:(1008):Checking IPsec proposal 5 \*May 4  
00:45:02.029: ISAKMP: transform 1, ESP\_AES \*May 4 00:45:02.029: ISAKMP: attributes in transform:  
\*May 4 00:45:02.029: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.029: ISAKMP: SA life type in  
seconds \*May 4 00:45:02.029: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9B \*May 4  
00:45:02.029: ISAKMP: SA life type in kilobytes \*May 4 00:45:02.029: ISAKMP: SA life duration  
(VPI) of 0x0 0x46 0x50 0x0 \*May 4 00:45:02.029: ISAKMP: authenticator is HMAC-SHA \*May 4  
00:45:02.033: ISAKMP: key length is 256 \*May 4 00:45:02.033: ISAKMP:(1008):atts are acceptable.  
\*May 4 00:45:02.033: IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.033:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes 256 esp-sha-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 256, flags= 0x0 \*May 4  
00:45:02.033: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes 256 esp-sha-hmac } \*May 4 00:45:02.033: ISAKMP:(1008): IPsec policy  
invalidated proposal \*May 4 00:45:02.033: ISAKMP:(1008):Checking IPsec proposal 6 \*May 4  
00:45:02.033: ISAKMP: transform 1, ESP\_AES \*May 4 00:45:02.033: ISAKMP: attributes in transform:  
\*May 4 00:45:02.033: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.033: ISAKMP: SA life type in  
seconds \*May 4 00:45:02.033: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9B \*May 4  
00:45:02.033: ISAKMP: SA life type in kilobytes \*May 4 00:45:02.033: ISAKMP: SA life duration  
(VPI) of 0x0 0x46 0x50 0x0 \*May 4 00:45:02.033: ISAKMP: authenticator is HMAC-MD5 \*May 4  
00:45:02.033: ISAKMP: key length is 256 \*May 4 00:45:02.033: ISAKMP:(1008):atts are acceptable.  
\*May 4 00:45:02.033: IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.033:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-aes 256 esp-md5-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 256, flags= 0x0 \*May 4  
00:45:02.033: IPSEC(crypto\_ipsec\_process\_proposal): transform proposal not supported for  
identity: {esp-aes 256 esp-md5-hmac } \*May 4 00:45:02.033: ISAKMP:(1008): IPsec policy  
invalidated proposal \*May 4 00:45:02.033: ISAKMP:(1008):Checking IPsec proposal 7 \*May 4  
00:45:02.033: ISAKMP: transform 1, ESP\_3DES \*May 4 00:45:02.033: ISAKMP: attributes in  
transform: \*May 4 00:45:02.033: ISAKMP: encaps is 1 (Tunnel) \*May 4 00:45:02.033: ISAKMP: SA  
life type in seconds \*May 4 00:45:02.033: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xc4 0x9B  
\*May 4 00:45:02.033: ISAKMP: SA life type in kilobytes \*May 4 00:45:02.033: ISAKMP: SA life  
duration (VPI) of 0x0 0x46 0x50 0x0 \*May 4 00:45:02.033: ISAKMP: authenticator is HMAC-SHA \*May  
4 00:45:02.033: ISAKMP:(1008):atts are acceptable. \*May 4 00:45:02.033:  
IPSEC(validate\_proposal\_request): proposal part #1 \*May 4 00:45:02.033:  
IPSEC(validate\_proposal\_request): proposal part #1, (key eng. msg.) INBOUND local=  
172.16.186.186, remote= 172.16.186.130, local\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), remote\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), protocol= ESP, transform= esp-3des esp-sha-hmac  
(Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0, keysize= 0, flags= 0x0 \*May 4  
00:45:02.033: ISAKMP:(1008): processing NONCE payload. message ID = -1665883002 \*May 4  
00:45:02.033: ISAKMP:(1008): processing ID payload. message ID = -1665883002 \*May 4  
00:45:02.033: ISAKMP:(1008): processing ID payload. message ID = -1665883002 \*May 4

```

00:45:02.033: ISAKMP:(1008): asking for 1 spis from ipsec *May 4 00:45:02.033:
ISAKMP:(1008):Node -1665883002, Input = IKE_MSG_FROM_PEER, IKE_QM_EXCH *May 4 00:45:02.033:
ISAKMP:(1008):Old State = IKE_QM_READY New State = IKE_QM_SPI_STARVE *May 4 00:45:02.033:
IPSEC(key_engine): got a queue event with 1 KMI message(s) *May 4 00:45:02.033:
IPSEC(spi_response): getting spi 1752561220 for SA from 172.16.186.186 to 172.16.186.130 for
prot 3 *May 4 00:45:02.033: ISAKMP:(1008): Creating IPsec SAs *May 4 00:45:02.033: inbound SA
from 172.16.186.130 to 172.16.186.186 (f/i) 0/ 0 (proxy 10.12.130.1 to 0.0.0.0) *May 4
00:45:02.033: has spi 0x6875F644 and conn_id 0 *May 4 00:45:02.033: lifetime of 2147483 seconds
*May 4 00:45:02.033: lifetime of 4608000 kilobytes *May 4 00:45:02.033: outbound SA from
172.16.186.186 to 172.16.186.130 (f/i) 0/0 (proxy 0.0.0.0 to 10.12.130.1) *May 4 00:45:02.033:
has spi 0x29354010 and conn_id 0 *May 4 00:45:02.033: lifetime of 2147483 seconds *May 4
00:45:02.033: lifetime of 4608000 kilobytes *May 4 00:45:02.033: ISAKMP:(1008): sending packet
to 172.16.186.130 my_port 500 peer_port 500 (R) QM_IDLE *May 4 00:45:02.033: ISAKMP:(1008):Node
-1665883002, Input = IKE_MSG_FROM_IPSEC, IKE_SPI_REPLY *May 4 00:45:02.033: ISAKMP:(1008):Old
State = IKE_QM_SPI_STARVE New State = IKE_QM_R_QM2 *May 4 00:45:02.033: IPSEC(key_engine): got a
queue event with 1 KMI message(s) *May 4 00:45:02.033: IPsec: Flow_switching Allocated flow for
sibling 80000007 *May 4 00:45:02.033: IPSEC(policy_db_add_ident): src 0.0.0.0, dest 10.12.130.1,
dest_port 0 *May 4 00:45:02.033: IPSEC(create_sa): sa created, (sa) sa_dest= 172.16.186.186,
sa_proto= 50, sa_spi= 0x6875F644(1752561220), sa_trans= esp-3des esp-sha-hmac , sa_conn_id= 11
*May 4 00:45:02.033: IPSEC(create_sa): sa created, (sa) sa_dest= 172.16.186.130, sa_proto= 50,
sa_spi= 0x29354010(691355664), sa_trans= esp-3des esp-sha-hmac , sa_conn_id= 12 *May 4
00:45:02.045: ISAKMP (0:1008): received packet from 172.16.186.130 dport 500 sport 500 Global
(R) QM_IDLE *May 4 00:45:02.045: ISAKMP:(1008):deleting node -1665883002 error FALSE reason "QM
done (await)" *May 4 00:45:02.045: ISAKMP:(1008):Node -1665883002, Input = IKE_MSG_FROM_PEER,
IKE_QM_EXCH *May 4 00:45:02.045: ISAKMP:(1008):Old State = IKE_QM_R_QM2 New State =
IKE_QM_PHASE2_COMPLETE *May 4 00:45:02.045: IPSEC(key_engine): got a queue event with 1 KMI
message(s) *May 4 00:45:02.045: IPSEC(key_engine_enable_outbound): rec'd enable notify from
ISAKMP *May 4 00:45:02.045: IPSEC(key_engine_enable_outbound): enable SA with spi 691355664/50

```

## Comandos do Easy VPN Remote

- **IPsec do debug crypto** — Indica as negociações de IPSEC de fase 2.
- **debug crypto isakmp** — Exibe as negociações ISAKMP da Fase 1.

```

3-03-06-871W#debug crypto ipsec3-03-06-871W#debug crypto isakmp
*Jun  3 05:59:27.431: ISAKMP:(0): beginning Aggressive Mode exchange
*Jun  3 05:59:27.431: ISAKMP:(0): sending packet to 172.16.186.186 my_port
                    500 peer_port 500 (I) AG_INIT_EXCH
*Jun  3 05:59:27.455: ISAKMP (0:0): received packet from 172.16.186.186 dport
                    500 sport 500 Global (I) AG_INIT_EXCH
*Jun  3 05:59:27.455: ISAKMP:(0): processing SA payload. message ID = 0
*Jun  3 05:59:27.455: ISAKMP:(0): processing ID payload. message ID = 0
*Jun  3 05:59:27.455: ISAKMP (0:0): ID payload
                    next-payload : 10
                    type          : 1
                    address       : 172.16.186.186
                    protocol      : 17
                    port          : 0
                    length        : 12
*Jun  3 05:59:27.455: ISAKMP:(0):: peer matches *none* of the profiles
*Jun  3 05:59:27.455: ISAKMP:(0): processing vendor id payload
*Jun  3 05:59:27.455: ISAKMP:(0): vendor ID is Unity
*Jun  3 05:59:27.455: ISAKMP:(0): processing vendor id payload
*Jun  3 05:59:27.455: ISAKMP:(0): vendor ID is DPD
*Jun  3 05:59:27.455: ISAKMP:(0): processing vendor id payload
*Jun  3 05:59:27.455: ISAKMP:(0): speaking to another IOS box!
*Jun  3 05:59:27.455: ISAKMP:(0): local preshared key found
*Jun  3 05:59:27.455: ISAKMP : Scanning profiles for xauth ...
*Jun  3 05:59:27.455: ISAKMP:(0): Authentication by xauth preshared
*Jun  3 05:59:27.455: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65515 policy
*Jun  3 05:59:27.455: ISAKMP:      encryption 3DES-CBC
*Jun  3 05:59:27.455: ISAKMP:      hash SHA
*Jun  3 05:59:27.455: ISAKMP:      default group 2

```



\*Jun 3 05:59:27.463: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.463: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.463: ISAKMP:(0):Encryption algorithm offered does not match policy!  
\*Jun 3 05:59:27.463: ISAKMP:(0):atts are not acceptable. Next payload is 0  
\*Jun 3 05:59:27.463: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65523 policy  
\*Jun 3 05:59:27.463: ISAKMP: encryption 3DES-CBC  
\*Jun 3 05:59:27.463: ISAKMP: hash SHA  
\*Jun 3 05:59:27.463: ISAKMP: default group 2  
\*Jun 3 05:59:27.463: ISAKMP: auth XAUTHInitPreShared  
\*Jun 3 05:59:27.463: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.463: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.463: ISAKMP:(0):Encryption algorithm offered does not match policy!  
\*Jun 3 05:59:27.463: ISAKMP:(0):atts are not acceptable. Next payload is 0  
\*Jun 3 05:59:27.463: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65524 policy  
\*Jun 3 05:59:27.467: ISAKMP: encryption 3DES-CBC  
\*Jun 3 05:59:27.467: ISAKMP: hash SHA  
\*Jun 3 05:59:27.467: ISAKMP: default group 2  
\*Jun 3 05:59:27.467: ISAKMP: auth XAUTHInitPreShared  
\*Jun 3 05:59:27.467: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.467: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.467: ISAKMP:(0):Encryption algorithm offered does not match policy!  
\*Jun 3 05:59:27.467: ISAKMP:(0):atts are not acceptable. Next payload is 0  
\*Jun 3 05:59:27.467: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65525 policy  
\*Jun 3 05:59:27.467: ISAKMP: encryption 3DES-CBC  
\*Jun 3 05:59:27.467: ISAKMP: hash SHA  
\*Jun 3 05:59:27.467: ISAKMP: default group 2  
\*Jun 3 05:59:27.467: ISAKMP: auth XAUTHInitPreShared  
\*Jun 3 05:59:27.467: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.467: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.467: ISAKMP:(0):Encryption algorithm offered does not match policy!  
\*Jun 3 05:59:27.467: ISAKMP:(0):atts are not acceptable. Next payload is 0  
\*Jun 3 05:59:27.467: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65526 policy  
\*Jun 3 05:59:27.467: ISAKMP: encryption 3DES-CBC  
\*Jun 3 05:59:27.467: ISAKMP: hash SHA  
\*Jun 3 05:59:27.467: ISAKMP: default group 2  
\*Jun 3 05:59:27.467: ISAKMP: auth XAUTHInitPreShared  
\*Jun 3 05:59:27.467: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.467: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.467: ISAKMP:(0):Encryption algorithm offered does not match policy!  
\*Jun 3 05:59:27.467: ISAKMP:(0):atts are not acceptable. Next payload is 0  
\*Jun 3 05:59:27.467: ISAKMP:(0):Checking ISAKMP transform 1 against priority 65527 policy  
\*Jun 3 05:59:27.467: ISAKMP: encryption 3DES-CBC  
\*Jun 3 05:59:27.467: ISAKMP: hash SHA  
\*Jun 3 05:59:27.467: ISAKMP: default group 2  
\*Jun 3 05:59:27.467: ISAKMP: auth XAUTHInitPreShared  
\*Jun 3 05:59:27.467: ISAKMP: life type in seconds  
\*Jun 3 05:59:27.467: ISAKMP: life duration (VPI) of 0x0 0x20 0xC4 0x9B  
\*Jun 3 05:59:27.467: ISAKMP:(0):atts are acceptable. Next payload is 0 \*Jun 3 05:59:27.467:  
ISAKMP (0:0): vendor ID is NAT-T v7 \*Jun 3 05:59:27.467: ISAKMP:(0): processing KE payload.  
message ID = 0 \*Jun 3 05:59:27.475: ISAKMP:(0): processing NONCE payload. message ID = 0 \*Jun 3  
05:59:27.475: ISAKMP:(2006): processing HASH payload. message ID = 0 \*Jun 3 05:59:27.475:  
ISAKMP:(2006):SA authentication status: authenticated \*Jun 3 05:59:27.475: ISAKMP:(2006):SA has  
**been authenticated with 172.16.186.186** \*Jun 3 05:59:27.475: ISAKMP:(2006):Send initial contact  
\*Jun 3 05:59:27.475: ISAKMP:(2006): sending packet to 172.16.186.186 my\_port 500 peer\_port 500  
(I) AG\_INIT\_EXCH \*Jun 3 05:59:27.479: ISAKMP:(2006):Input = IKE\_MSG\_FROM\_PEER, IKE\_AM\_EXCH \*Jun  
3 05:59:27.479: ISAKMP:(2006):Old State = IKE\_I\_AM1 New State = IKE\_P1\_COMPLETE \*Jun 3  
05:59:27.479: ISAKMP:(2006):Need XAUTH \*Jun 3 05:59:27.479: ISAKMP:(2006):Input =  
IKE\_MSG\_INTERNAL, IKE\_PHASE1\_COMPLETE !--- Phase 1 (ISAKMP) is complete. \*Jun 3 05:59:27.479:  
ISAKMP:(2006):Old State = IKE\_P1\_COMPLETE New State = IKE\_P1\_COMPLETE !--- Xauth initiates. \*Jun  
3 05:59:27.479: ISAKMP (0:2006): received packet from 172.16.186.186 dport 500 sport 500 Global  
(I) CONF\_XAUTH \*Jun 3 05:59:27.483: ISAKMP: set new node 850198625 to CONF\_XAUTH \*Jun 3  
05:59:27.487: ISAKMP:(2006):processing transaction payload from 172.16.186.186. message ID = -  
1517216966 \*Jun 3 05:59:27.487: ISAKMP: Config payload REQUEST \*Jun 3 05:59:27.487:  
ISAKMP:(2006):checking request: \*Jun 3 05:59:27.487: ISAKMP: XAUTH\_USER\_NAME\_V2 \*Jun 3

05:59:27.487: ISAKMP: XAUTH\_USER\_PASSWORD\_V2 \*Jun 3 05:59:27.487: ISAKMP:(2006):Xauth process request \*Jun 3 05:59:27.487: ISAKMP:(2006):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_REQUEST \*Jun 3 05:59:27.487: ISAKMP:(2006):Old State = IKE\_P1\_COMPLETE New State = IKE\_XAUTH\_REPLY\_AWAIT \*Jun 3 05:59:30.242: EZVPN(ez): Pending XAuth Request, Please enter the following command: \*Jun 3 05:59:30.242: EZVPN: crypto ipsec client ezvpn xauth !--- Enter the crypto ipsec client ezvpn xauth command. 3-03-06-871W#crypto ipsec client ezvpn xauth Username: cisco Password: <omitted> \*Jun 3 06:02:46.498: username: cisco \*Jun 3 06:02:46.498: password: <omitted> \*Jun 3 06:02:46.498: ISAKMP:(2008): responding to peer config from 172.16.186.186. ID = -605466681 \*Jun 3 06:02:46.498: ISAKMP:(2008): sending packet to 172.16.186.186 my\_port 500 peer\_port 500 (I) CONF\_XAUTH \*Jun 3 06:02:46.498: ISAKMP:(2008):deleting node -605466681 error FALSE reason "Done with xauth request/reply exchange" \*Jun 3 06:02:46.498: ISAKMP:(2008):Input = IKE\_MSG\_INTERNAL, IKE\_XAUTH\_REPLY\_ATTR \*Jun 3 06:02:46.498: ISAKMP:(2008):Old State = IKE\_XAUTH\_REPLY\_AWAIT New State = IKE\_XAUTH\_REPLY\_SENT \*Jun 3 06:02:46.502: ISAKMP (0:2008): received packet from 172.16.186.186 dport 500 sport 500 Global (I) CONF\_XAUTH \*Jun 3 06:02:46.502: ISAKMP: set new node 1283697340 to CONF\_XAUTH \*Jun 3 06:02:46.502: ISAKMP:(2008):processing transaction payload from 172.16.186.186. message ID = 1283697340 \*Jun 3 06:02:46.502: ISAKMP: Config payload SET \*Jun 3 06:02:46.502: ISAKMP:(2008):Xauth process set, status = 1 \*Jun 3 06:02:46.502: ISAKMP:(2008):checking SET: \*Jun 3 06:02:46.502: ISAKMP: XAUTH\_STATUS\_V2 XAUTH-OK \*Jun 3 06:02:46.502: ISAKMP:(2008):attributes sent in message: \*Jun 3 06:02:46.502: Status: 1 \*Jun 3 06:02:46.506: ISAKMP:(2008): sending packet to 172.16.186.186 my\_port 500 peer\_port 500 (I) CONF\_XAUTH \*Jun 3 06:02:46.506: ISAKMP:(2008):deleting node 1283697340 error FALSE reason "No Error" \*Jun 3 06:02:46.506: ISAKMP:(2008):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_SET \*Jun 3 06:02:46.506: ISAKMP:(2008):Old State = IKE\_XAUTH\_REPLY\_SENT New State = IKE\_P1\_COMPLETE \*Jun 3 06:02:46.506: ISAKMP:(2008):Need config/address \*Jun 3 06:02:46.506: ISAKMP: set new node 104696831 to CONF\_ADDR \*Jun 3 06:02:46.506: ISAKMP: Sending APPLICATION\_VERSION string: Cisco IOS Software, C870 Software (C870-ADVIPSERVICESK9-M), Experimental Version 12.4(20060201:210845) [prchadal-CSCsb79792-haw\_t\_pi4 101] Copyright (c) 1986-2006 by Cisco Systems, Inc. Compiled Thu 02-Feb-06 03:19 by prchadal \*Jun 3 06:02:46.506: ISAKMP:(2008): initiating peer config to 172.16.186.186. ID = 104696831 \*Jun 3 06:02:46.506: ISAKMP:(2008): sending packet to 172.16.186.186 my\_port 500 peer\_port 500 (I) CONF\_ADDR \*Jun 3 06:02:46.506: ISAKMP:(2008):Input = IKE\_MSG\_INTERNAL, IKE\_PHASE1\_COMPLETE \*Jun 3 06:02:46.506: ISAKMP:(2008):Old State = IKE\_P1\_COMPLETE New State = IKE\_CONFIG\_MODE\_REQ\_SENT \*Jun 3 06:02:46.510: ISAKMP (0:2008): received packet from 172.16.186.186 dport 500 sport 500 Global (I) CONF\_ADDR \*Jun 3 06:02:46.514: ISAKMP:(2008):processing transaction payload from 172.16.186.186. message ID = 104696831 \*Jun 3 06:02:46.514: ISAKMP: Config payload REPLY \*Jun 3 06:02:46.514: ISAKMP(0:2008) process config reply \*Jun 3 06:02:46.514: ISAKMP:(2008):deleting node 104696831 error FALSE reason "Transaction mode done" \*Jun 3 06:02:46.514: ISAKMP:(2008):Input = IKE\_MSG\_FROM\_PEER, IKE\_CFG\_REPLY \*Jun 3 06:02:46.514: ISAKMP:(2008):Old State = IKE\_CONFIG\_MODE\_REQ\_SENT New State = IKE\_P1\_COMPLETE \*Jun 3 06:02:46.518: insert of map into mapdb AVL failed, map + ace pair already exists on the mapdb \*Jun 3 06:02:46.518: ISAKMP:(2008):Input = IKE\_MSG\_INTERNAL, IKE\_PHASE1\_COMPLETE \*Jun 3 06:02:46.518: ISAKMP:(2008):Old State = IKE\_P1\_COMPLETE New State = IKE\_P1\_COMPLETE \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and 4608000kb, spi= 0xA0FC0985(2700872069), conn\_id= 0, keysize= 128, flags= 0x2000 \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and 4608000kb, spi= 0xBB426C9(196355785), conn\_id= 0, keysize= 128, flags= 0x2000 \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and 4608000kb, spi= 0xB349BB06(3007953670), conn\_id= 0, keysize= 192, flags= 0x2000 \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and 4608000kb, spi= 0xC114CFB8(3239366584), conn\_id= 0, keysize= 192, flags= 0x2000 \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and 4608000kb, spi= 0x2ED87C62(785939554), conn\_id= 0, keysize= 256, flags= 0x2000 \*Jun 3 06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and

4608000kb, spi= 0x226A6FF3(577400819), conn\_id= 0, keysize= 256, flags= 0x2000 \*Jun 3  
06:02:46.522: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote=  
172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy=  
0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and  
4608000kb, spi= 0x29354010(691355664), conn\_id= 0, keysize= 0, flags= 0x2000 \*Jun 3  
06:02:46.526: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote=  
172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy=  
0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and  
4608000kb, spi= 0x12111E5C(303111772), conn\_id= 0, keysize= 0, flags= 0x2000 \*Jun 3  
06:02:46.526: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote=  
172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy=  
0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and  
4608000kb, spi= 0x98084B9A(2550680474), conn\_id= 0, keysize= 0, flags= 0x2000 \*Jun 3  
06:02:46.526: IPSEC(sa\_request): , (key eng. msg.) OUTBOUND local= 172.16.186.130, remote=  
172.16.186.186, local\_proxy= 10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy=  
0.0.0.0/0.0.0.0/0/0 (type=4), protocol= ESP, transform= NONE (Tunnel), lifedur= 2147483s and  
4608000kb, spi= 0x9442501B(2487373851), conn\_id= 0, keysize= 0, flags= 0x0 \*Jun 3 06:02:46.526:  
ISAKMP: set new node 0 to QM\_IDLE \*Jun 3 06:02:46.526: ISAKMP:(2008): sitting IDLE. Starting QM  
immediately (QM\_IDLE) \*Jun 3 06:02:46.526: ISAKMP:(2008):beginning Quick Mode exchange, M-ID of  
-1665883002 \*Jun 3 06:02:46.526: ISAKMP:(2008):QM Initiator gets spi \*Jun 3 06:02:46.530:  
ISAKMP:(2008): sending packet to 172.16.186.186 my\_port 500 peer\_port 500 (I) QM\_IDLE \*Jun 3  
06:02:46.530: ISAKMP:(2008):Node -1665883002, Input = IKE\_MSG\_INTERNAL, IKE\_INIT\_QM \*Jun 3  
06:02:46.530: ISAKMP:(2008):Old State = IKE\_QM\_READY New State = IKE\_QM\_I\_QM1 \*Jun 3  
06:02:46.538: ISAKMP (0:2008): received packet from 172.16.186.186 dport 500 sport 500 Global  
(I) QM\_IDLE \*Jun 3 06:02:46.538: ISAKMP:(2008): processing HASH payload. message ID = -  
1665883002 \*Jun 3 06:02:46.538: ISAKMP:(2008): processing SA payload. message ID = -1665883002  
\*Jun 3 06:02:46.538: ISAKMP:(2008):Checking IPsec proposal 1 \*Jun 3 06:02:46.538: ISAKMP:  
transform 1, ESP\_3DES \*Jun 3 06:02:46.538: ISAKMP: attributes in transform: \*Jun 3 06:02:46.538:  
ISAKMP: encaps is 1 (Tunnel) \*Jun 3 06:02:46.538: ISAKMP: SA life type in seconds \*Jun 3  
06:02:46.538: ISAKMP: SA life duration (VPI) of 0x0 0x20 0xC4 0x9B \*Jun 3 06:02:46.538: ISAKMP:  
SA life type in kilobytes \*Jun 3 06:02:46.538: ISAKMP: SA life duration (VPI) of 0x0 0x46 0x50  
0x0 \*Jun 3 06:02:46.542: ISAKMP: authenticator is HMAC-SHA \*Jun 3 06:02:46.542:  
ISAKMP:(2008):atts are acceptable. \*Jun 3 06:02:46.542: IPSEC(validate\_proposal\_request):  
proposal part #1 \*Jun 3 06:02:46.542: IPSEC(validate\_proposal\_request): proposal part #1, (key  
eng. msg.) INBOUND local= 172.16.186.130, remote= 172.16.186.186, local\_proxy=  
10.12.130.1/255.255.255.255/0/0 (type=1), remote\_proxy= 0.0.0.0/0.0.0.0/0/0 (type=4), protocol=  
ESP, transform= esp-3des esp-sha-hmac (Tunnel), lifedur= 0s and 0kb, spi= 0x0(0), conn\_id= 0,  
keysize= 0, flags= 0x0 \*Jun 3 06:02:46.542: Crypto mapdb : proxy\_match src addr : 10.12.130.1  
dst addr : 0.0.0.0 protocol : 0 src port : 0 dst port : 0 \*Jun 3 06:02:46.542: ISAKMP:(2008):  
processing NONCE payload. message ID = -1665883002 \*Jun 3 06:02:46.542: ISAKMP:(2008):  
processing ID payload. message ID = -1665883002 \*Jun 3 06:02:46.542: ISAKMP:(2008): processing  
ID payload. message ID = -1665883002 \*Jun 3 06:02:46.542: ISAKMP:(2008): processing NOTIFY  
RESPONDER\_LIFETIME protocol 3 spi 1752561220, message ID = -1665883002, sa = 83BCC9DC \*Jun 3  
06:02:46.542: ISAKMP:(2008):SA authentication status: authenticated \*Jun 3 06:02:46.542:  
ISAKMP:(2008): processing responder lifetime \*Jun 3 06:02:46.542: ISAKMP (2008): responder  
lifetime of 3600s \*Jun 3 06:02:46.542: ISAKMP:(2008): Creating IPsec SAs \*Jun 3 06:02:46.542:  
inbound SA from 172.16.186.186 to 172.16.186.130 (f/i) 0/ 0 (proxy 0.0.0.0 to 10.12.130.1) \*Jun  
3 06:02:46.542: has spi 0x29354010 and conn\_id 0 \*Jun 3 06:02:46.542: lifetime of 3590 seconds  
\*Jun 3 06:02:46.542: lifetime of 4608000 kilobytes \*Jun 3 06:02:46.546: outbound SA from  
172.16.186.130 to 172.16.186.186 (f/i) 0/0 (proxy 10.12.130.1 to 0.0.0.0) \*Jun 3 06:02:46.546:  
has spi 0x6875F644 and conn\_id 0 \*Jun 3 06:02:46.546: lifetime of 3590 seconds \*Jun 3  
06:02:46.546: lifetime of 4608000 kilobytes \*Jun 3 06:02:46.546: ISAKMP:(2008): sending packet  
to 172.16.186.186 my\_port 500 peer\_port 500 (I) QM\_IDLE \*Jun 3 06:02:46.546:  
ISAKMP:(2008):deleting node -1665883002 error FALSE reason "No Error" \*Jun 3 06:02:46.546:  
ISAKMP:(2008):Node -1665883002, Input = IKE\_MSG\_FROM\_PEER, IKE\_QM\_EXCH \*Jun 3 06:02:46.546:  
ISAKMP:(2008):Old State = IKE\_QM\_I\_QM1 New State = IKE\_QM\_PHASE2\_COMPLETE \*Jun 3 06:02:46.546:  
IPSEC(key\_engine): got a queue event with 1 KMI message(s) \*Jun 3 06:02:46.546: Crypto mapdb :  
proxy\_match src addr : 10.12.130.1 dst addr : 0.0.0.0 protocol : 0 src port : 0 dst port : 0  
\*Jun 3 06:02:46.546: IPSEC(crypto\_ipsec\_sa\_find\_ident\_head): reconnecting with the same proxies  
and peer 172.16.186.186 \*Jun 3 06:02:46.546: IPSEC(policy\_db\_add\_ident): src 10.12.130.1, dest  
0.0.0.0, dest\_port 0 \*Jun 3 06:02:46.546: IPSEC(create\_sa): sa created, (sa) sa\_dest=  
172.16.186.130, sa\_proto= 50, sa\_spi= 0x29354010(691355664), sa\_trans= esp-3des esp-sha-hmac ,  
sa\_conn\_id= 11 \*Jun 3 06:02:46.546: IPSEC(create\_sa): sa created, (sa) sa\_dest= 172.16.186.186,  
sa\_proto= 50, sa\_spi= 0x6875F644(1752561220), sa\_trans= esp-3des esp-sha-hmac , sa\_conn\_id= 12

```
*Jun 3 06:02:46.550: IPSEC(update_current_outbound_sa): updated peer 172.16.186.186 current
outbound sa to SPI 6875F644 *Jun 3 06:02:46.550: %CRYPTO-6-EZVPN_CONNECTION_UP: (Client) User=
Group=vpngrp Client_public_addr=172.16.186.130 Server_public_addr=172.16.186.186
NEM_Remote_Subnets=10.12.130.1/255.255.255.255 *Jun 3 06:02:47.130: ISAKMP: set new node -
1866551769 to QM_IDLE
```

## [Informações Relacionadas](#)

- [Sustentação do produto do Cisco Easy VPN](#)
- [IOS Router: VPN fácil \(EzVPN\) no modo de extensão de rede \(NEM\) com exemplo de configuração rachado da escavação de um túnel](#)
- [Cisco VPN Client](#)
- [Negociação IPsec/Protocolos IKE](#)
- [Suporte Técnico e Documentação - Cisco Systems](#)