

# Como eu impeço que meu ESA esteja usado como um relé aberto?

## Índice

[Pergunta](#)

## Pergunta

Como eu impeço que meu ESA esteja usado como um relé aberto?

Para fixar seu ESA da utilização como um relé aberto, se certifica de que você especificou os domínios destinatários na tabela destinatária do acesso (RATO) de seus ouvintes públicos e de que “TODA A” entrada está configurada “para rejeitar”. As entradas do RATO podem ser adicionadas através do GUI, na aba das políticas do correio. Está abaixo um exemplo que mostra como adicionar um domínio, “example.com” ao RATO através do CLI.

```
mail.example.com> listenerconfig
Currently configured listeners:
1. InboundMail (on PublicNet, 172.19.1.80) SMTP TCP Port 25 Public
2. OutboundMail (on PrivateNet, 172.19.2.80) SMTP TCP Port 25 Private
Choose the operation you want to perform:
- NEW - Create a new listener.
- EDIT - Modify a listener.
- DELETE - Remove a listener.
- SETUP - Change global settings.
[ ]> edit
Enter the name or number of the listener you wish to edit.
[ ]> 1
Name: InboundMail
Type: Public
Interface: PublicNet (172.19.1.80/24) TCP Port 25
Protocol: SMTP
Default Domain:
Max Concurrency: 1000 (TCP Queue: 50)
Domain Map: Disabled
TLS: No
SMTP Authentication: Disabled
Bounce Profile: Default
Use SenderBase For Reputation Filters and IP Profiling: Yes
Footer: None
LDAP: Off

Choose the operation you want to perform:
- NAME - Change the name of the listener.
- INTERFACE - Change the interface.
- LIMITS - Change the injection limits.
- SETUP - Configure general options.
- HOSTACCESS - Modify the Host Access Table.
- RCPTACCESS - Modify the Recipient Access Table.
- BOUNCECONFIG - Choose the bounce profile to use for messages injected on
```

this listener.

- MASQUERADE - Configure the Domain Masquerading Table.
- DOMAINMAP - Configure domain mappings.

[ ]> **rcptaccess**

Recipient Access Table

There are currently 1 recipients.

Default Access: REJECT<

Choose the operation you want to perform:

- NEW - Create a new entry.
- EDIT - Modify an entry.
- IMPORT - Import a table from a file.
- EXPORT - Export the table to a file.

[ ]> **new**

Enter the recipient address for this entry.

Hostnames such as "example.com" and "[1.2.3.4]" are allowed.

Partial hostnames such as ".example.com" are allowed.

Usernames such as "postmaster@" are allowed.

Full email addresses such as "joe@example.com" or "joe@[1.2.3.4]" are allowed.

Separate multiple addresses with commas.

[ ]> **example.com**

Select the action to apply to this address:

1. Accept
2. Reject

[1]>

Would you like to specify a custom SMTP response? [N]>

Would you like to bypass receiving control for this entry? [N]>

Recipient Access Table

There are currently 2 recipients.

Default Access: REJECT

Choose the operation you want to perform:

- NEW - Create a new entry.
- EDIT - Modify an entry.
- DELETE - Remove an entry.
- PRINT - Display all entries.
- IMPORT - Import a table from a file.
- EXPORT - Export the table to a file.
- CLEAR - Remove all entries.

[ ]> **print**

ironport.com ACCEPT

ALL REJECT

Observe que "TODA A" entrada está configurada "PARA REJEITAR". Esta entrada faz com que o sistema rejeite mensagens de todo o host que não for configurado especificamente para ser aceitado.