

Configurando a autenticação TACACS+ para VPDNs

Índice

[Introdução](#)

[Pré-requisitos](#)

[Requisitos](#)

[Componentes Utilizados](#)

[Convenções](#)

[Configurar](#)

[Diagrama de Rede](#)

[TACACS+ Configurações do servidor](#)

[Configurações do Roteador](#)

[Verificar](#)

[Troubleshooting](#)

[Comandos para Troubleshooting](#)

[Exemplo de debug](#)

[Informações Relacionadas](#)

[Introdução](#)

Uma Rede Virtual Privada de Discagem (VPDN) permite que um serviço de discagem de rede privada se estenda até os servidores de acesso remoto (definidos como o L2TP Access Concentrator [LAC]). Quando um cliente de PPP (Protocolo Ponto-a-Ponto) disca para um LAC, o LAC determina que deve encaminhar aquela sessão de PPP para um LNS (Servidor de Rede L2TP) para aquele cliente, que, em seguida, autentica o usuário e inicia a negociação de PPP. Uma vez que a instalação do PPP esteja concluída, todas os quadros são enviados pelo LAC para o cliente e o LNS.

Esta configuração de exemplo permite que você use a autenticação TACACS+ com redes dial-up privadas virtuais (VPDN). O LAC pergunta o server TACACS+, determina que LNS para enviar o usuário, e estabelece o túnel apropriado.

Para obter mais informações sobre dos VPDN, refira a [compreensão do VPDN](#).

[Pré-requisitos](#)

[Requisitos](#)

Não existem requisitos específicos para este documento.

Componentes Utilizados

As informações neste documento são baseadas nestas versões de software e hardware:

- Cisco Secure ACS para a versão UNIX 2.x.x e mais tarde ou freeware TACACS+
- Liberação 11.2 do Cisco IOS ® Software e mais atrasado

As informações neste documento foram criadas a partir de dispositivos em um ambiente de laboratório específico. Todos os dispositivos utilizados neste documento foram iniciados com uma configuração (padrão) inicial. Se a sua rede estiver ativa, certifique-se de que entende o impacto potencial de qualquer comando.

Convenções

Para obter mais informações sobre convenções de documento, consulte as [Convenções de dicas técnicas Cisco](#).

Configurar

Esta seção apresenta a informação necessária configurar as características descritas neste documento.

Neste exemplo, o usuário é "jsmith@hp.com" com senha "teste". Quando "jsmith@hp.com" disca no roteador ISP, o roteador ISP envia o "hp.com" userid ao server ISP TACACS+. O servidor ISP encontra a id de usuário de "hp.com" e envia seu id de túnel ("isp"), o endereço IP do roteador home gateway (HGW) (10.31.1.50), a senha NAS (Servidor de acesso de rede) ("saudação") e a senha de gateway ("lá") de volta ao roteador ISP.

O roteador ISP inicia um túnel e conecta-o ao roteador de HGW, que para a frente as senhas para userid "HP-GW" ("lá") e então userid "isp" ("olá!") ao server HGW TACACS+. Uma vez que os túneis são estabelecidos, o roteador ISP para a frente ao roteador de HGW o userid ("jsmith@hp.com ") e senha ("teste") do usuário que disca dentro. Este usuário é autenticado no servidor HGW. Nas configurações de amostra neste documento, o nome de host do roteador ISP é "coala" e o nome de host do roteador de HGW é "thing_one".

Nota: Para localizar informações adicionais sobre os comandos usados neste documento, utilize a Ferramenta Command Lookup (somente clientes [registrados](#)).

Diagrama de Rede

Este documento utiliza a configuração de rede mostrada neste diagrama.

TACACS+ Configurações do servidor

Este documento usa as configurações do servidor mostradas aqui.

- [Freeware TACACS+](#)
- [Cisco Secure ACS para UNIX 2.x.x](#)

Freeware TACACS+

```
!--- This user is on the ISP TACACS+ server. !--- The profile includes the Tunnel ID ("isp"),
the IP address !--- of the Peer (10.31.1.50), !--- and the passwords used to authenticate the
tunnel. !--- The ISP uses these attributes to establish the tunnel. user = hp.com { service = ppp
protocol = vpdn { tunnel-id = isp ip-addresses = "10.31.1.50" nas-password = "hello" gw-password
= "there" } } !--- The next three users are on the HGW server. user = isp { chap = cleartext
"hello" service = ppp protocol = ip { default attribute = permit } } user = hp-gw { chap =
cleartext "there" service = ppp protocol = ip { default attribute = permit } } user =
jsmith@hp.com { chap = cleartext "test" service = ppp protocol = ip { default attribute = permit
} }
```

Cisco Secure ACS para UNIX 2.x.x

```
!--- This user is on the ISP server. # ./ViewProfile -p 9900 -u hp.com User Profile Information
user = hp.com{ profile_id = 83 profile_cycle = 1 service=ppp { protocol=vpdn { set tunnel-id=isp
set ip-addresses="10.31.1.50" set nas-password="hello" set gw-password="there" } protocol=lcp {
} } } !--- The next three users are on the HGW server. !--- The next two usernames are used to
authenticate the LAC !--- during tunnel initialization. # ./ViewProfile -p 9900 -u isp User
Profile Information user = isp{ profile_id = 84 profile_cycle = 1 password = chap "*****"
service=ppp { protocol=ip { default attribute=permit } protocol=lcp { } } } # ./ViewProfile -p
9900 -u hp-gw User Profile Information user = hp-gw{ profile_id = 82 profile_cycle = 1 password
= chap "*****" service=ppp { protocol=ip { default attribute=permit } protocol=lcp { } } } !-
-- This username is used to authenticate the end user !--- after the tunnel is established. #
./ViewProfile -p 9900 -u jsmith@hp.com User Profile Information user = jsmith@hp.com{ profile_id
= 85 profile_cycle = 1 password = chap "*****" service=ppp { protocol=ip { default
attribute=permit } protocol=lcp { } } }
```

Configurações do Roteador

Este documento utiliza as configurações mostradas aqui.

- [Roteador ISP](#)
- [Roteador de HGW](#)

Configuração do roteador ISP

```
koala#show running config Building configuration...
Current configuration: ! version 11.2 no service
password-encryption service udp-small-servers service
tcp-small-servers ! hostname koala ! aaa new-model aaa
authentication ppp default tacacs+ none aaa
authorization network tacacs+ none aaa accounting
network start-stop tacacs+ enable password ww ! !---
VPDN is enabled. vpdn enable ! interface Ethernet0 ip
address 10.31.1.5 255.255.255.0 ! interface Serial0
shutdown ! interface Serial1 shutdown ! interface Async1
ip unnumbered Ethernet0 encapsulation ppp async mode
dedicated no cdp enable ppp authentication chap ! ip
default-gateway 10.31.1.1 no ip classless ip route
0.0.0.0 0.0.0.0 10.31.1.1 ! !--- Specify the TACACS
server information on the NAS. tacacs-server host
171.68.120.194 tacacs-server key cisco no tacacs-server
directed-request snmp-server community public RW snmp-
server enable traps config ! line con 0 password ww line
1 16 password ww autoselect ppp modem InOut transport
input all stopbits 1 rxspeed 115200 txspeed 115200
flowcontrol hardware line aux 0 line vty 0 4 exec-
timeout 0 0 password ww ! end
```

Configuração do roteador HGW

```
thing_one#show running config Building configuration...
Current configuration: ! version 11.2 no service
```

```

password-encryption no service udp-small-servers no
service tcp-small-servers ! hostname thing_one ! aaa
new-model aaa authentication ppp default tacacs+ none
aaa authorization network tacacs+ none enable password
ww ! !--- Enable VPDN. vpdn enable !--- Specify the
remote host ("isp" on the network access server) !---
and the local name ("hp-gw" on the home gateway) to use
to authenticate. !--- Also specify the virtual template
to use. !--- The local name and the remote host name
must match !--- the ones in the TACACS server. vpdn
incoming isp hp-gw virtual-template 1 ! interface
Loopback0 shutdown ! interface Ethernet0 ip address
10.31.1.50 255.255.255.0 ! interface Virtual-Template1
!--- Create a virtual template interface. ip unnumbered
Ethernet0 !--- Un-number the Virtual interface to an
available LAN interface. peer default ip address pool
async !--- Use the pool "async" to assign the IP address
for incoming connections. ppp authentication chap !---
Use CHAP authentication for the incoming connection. !
interface Serial0 shutdown ! interface Serial1 shutdown
! ip local pool async 15.15.15.15 no ip classless ip
route 0.0.0.0 0.0.0.0 10.31.1.1 ! tacacs-server host
171.68.118.101 no tacacs-server directed-request tacacs-
server key cisco !--- Specify the TACACS+ server
information on the NAS. ! line con 0 exec-timeout 0 0
line 1 8 line aux 0 line vty 0 4 ! end

```

Verificar

No momento, não há procedimento de verificação disponível para esta configuração.

Troubleshooting

Esta seção fornece informações que podem ser usadas para o troubleshooting da sua configuração.

Comandos para Troubleshooting

Nota: Antes de emitir **comandos debug**, consulte [Informações importantes sobre comandos debug](#).

- **debugar a autenticação aaa** — Indica a informação na autenticação do Authentication, Authorization, and Accounting (AAA) /TACACS+.
- **debug aaa authorization** — Exibe informações sobre autorização AAA/TACACS+.
- **debug ppp negotiation** - Exibe pacotes PPP transmitidos durante a inicialização de PPP, em que as opções de PPP são negociadas.
- **debugar tacacs+** — Indica o informação detalhada sobre debug associado com o TACACS+.
- **debug vpdn errors** — Indica os erros que impedem um túnel PPP esteja estabelecido ou os erros que fazem com que um túnel estabelecido se feche.
- **debug vpdn events** — Exibe mensagens sobre eventos que fazem parte do estabelecimento ou encerramento normal de túneis PPP.
- **debug vpdn l2f-errors** — Indica os erros de protocolo da camada 2 que impedem o estabelecimento da camada 2 ou impedem sua operação normal.

- **debug vpdn l2f-events** — Indica mensagens sobre os eventos que são parte de estabelecimento de túnel normal ou parada programada PPP para a camada 2.
- **debug vpdn l2f-packets** — Mensagens dos indicadores sobre encabeçamentos e estado de protocolo de encaminhamento da camada 2.
- **debug vpdn packets** — Os indicadores mergulham 2 erros e eventos do protocolo de túnel (L2TP) que são uma parte do estabelecimento normal de túnel ou uma parada programada para VPDN.
- **debug vtemplate** — exibe informações sobre clonagem de uma interface de acesso virtual do momento do clone a partir de um modelo virtual até o momento em que a interface de acesso virtual é desativada quando a chamada termina.

Exemplo de debug

Estes debugam são fornecidos para a referência.

- [Boa depuração do roteador ISP](#)
- [Boa depuração do roteador HGW](#)
- [Debuga para a falha na conexão no roteador ISP](#)
- [Debuga para falhas na conexão no roteador de HGW](#)

Boa depuração do roteador ISP

```
koala#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on
koala# %LINK-3-UPDOWN: Interface Async1, changed state to up 15:04:47: VPDN: Looking for tunnel
-- hp.com -- 15:04:47: AAA/AUTHEN: create_user (0x15FA80) user='hp.com' ruser='' port='Async1'
rem_addr='' authen_type=NONE service=LOGIN priv=0 15:04:47: AAA/AUTHOR/VPDN: : (2445181346):
user='hp.com' 15:04:47: AAA/AUTHOR/VPDN: : (2445181346): send AV service=ppp 15:04:47:
AAA/AUTHOR/VPDN: : (2445181346): send AV protocol=vpdn 15:04:47: AAA/AUTHOR/VPDN: :
(2445181346): Method=TACACS+ 15:04:47: AAA/AUTHOR/TAC+: (2445181346): user=hp.com 15:04:47:
AAA/AUTHOR/TAC+: (2445181346): send AV service=ppp 15:04:47: AAA/AUTHOR/TAC+: (2445181346): send
AV protocol=vpdn 15:04:47: TAC+: (2445181346): received author response status = PASS_ADD
15:04:47: AAA/AUTHOR (2445181346): Post authorization status = PASS_ADD 15:04:47:
AAA/AUTHOR/VPDN: Processing AV service=ppp 15:04:47: AAA/AUTHOR/VPDN: Processing AV
protocol=vpdn 15:04:47: AAA/AUTHOR/VPDN: Processing AV tunnel-id=isp 15:04:47: AAA/AUTHOR/VPDN:
Processing AV ip-addresses=10.31.1.50 15:04:47: AAA/AUTHOR/VPDN: Processing AV nas-
password=hello 15:04:47: AAA/AUTHOR/VPDN: Processing AV gw-password=there 15:04:47: VPDN: Get
tunnel info with NAS isp GW hp.com, IP 10.31.1.50 !--- The TACACS+ server returns the attributes
the !--- NAS should use for the tunnel. !--- The tunnel-id is "ISP" and the IP address of HGW is
10.31.1.50. 15:04:47: AAA/AUTHEN: free_user (0x15FA80) user='hp.com' ruser='' port='Async1'
rem_addr='' authen_type=NONE service=LOGIN priv=0 15:04:47: VPDN: Forward to address 10.31.1.50
15:04:47: As1 VPDN: Forwarding... 15:04:47: AAA/AUTHEN: create_user (0x118008)
user='jsmith@hp.com' ruser='' port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1
15:04:47: As1 VPDN: Bind interface direction=1 15:04:47: As1 VPDN: jsmith@hp.com is forwarded
%LINEPROTO-5-UPDOWN: Line protocol on Interface Async1, changed state to up 15:04:49: AAA/ACCT:
NET acct start. User jsmith@hp.com, Port Async1: Async1 !--- User finishes and disconnects.
%LINEPROTO-5-UPDOWN: Line protocol on Interface Async1, changed state to down %LINK-5-CHANGED:
Interface Async1, changed state to reset 15:05:27: As1 VPDN: Cleanup 15:05:27: As1 VPDN: Reset
15:05:27: As1 VPDN: Reset 15:05:27: As1 VPDN: Unbind interface 15:05:27: AAA/ACCT: Network acct
stop. User jsmith@hp.com, Port Async1: task_id=2 timezone=UTC service=vpdn bytes_in=1399
bytes_out=150 paks_in=27 paks_out=9 elapsed_time=38 %LINK-3-UPDOWN: Interface Async1, changed
state to down 15:05:30: AAA/AUTHEN: free_user (0x118008) user='jsmith@hp.com' ruser=''
port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1 koala#
```

Boa depuração do roteador HGW

thing_one#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is on AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on VTEMPLATE: Virtual Template debugging is on thing_one# 15:04:46: AAA/AUTHEN: create_user (0x15E6E0) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: TAC+: ver=192 id=969200103 received AUTHEN status = PASS 15:04:46: AAA/AUTHEN: free_user (0x15E6E0) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: AAA/AUTHEN (3252085483): status = PASS 15:04:46: AAA/AUTHEN: free_user (0x15CBEC) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: AAA/AUTHEN: create_user (0x15F1B8) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: AAA/AUTHEN/START (3897539709): port='' list='default' action=LOGIN service=PPP 15:04:46: AAA/AUTHEN/START (3897539709): found list default 15:04:46: AAA/AUTHEN/START (3897539709): Method=TACACS+ 15:04:46: TAC+: send AUTHEN/START packet ver=193 id=3897539709 15:04:46: TAC+: ver=192 id=3897539709 received AUTHEN status = GETPASS 15:04:46: AAA/AUTHEN: create_user (0x15E6F0) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: TAC+: ver=192 id=2306139011 received AUTHEN status = PASS 15:04:46: AAA/AUTHEN: free_user (0x15E6F0) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: AAA/AUTHEN (3897539709): status = PASS **15:04:46: VPDN: Chap authentication succeeded for isp !--- The LAC ("ISP") is succesfully authenticated.** 15:04:46: AAA/AUTHEN: free_user (0x15F1B8) user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 15:04:46: Vtl VTEMPLATE: Reuse Vtl, recycle queue size 0 15:04:46: Vtl VTEMPLATE: Set default settings with no ip address 15:04:47: Vtl VTEMPLATE: Hardware address 00e0.1e68.942c 15:04:47: Vtl VPDN: Virtual interface created for jsmith@hp.com 15:04:47: Vtl VPDN: Set to Async interface 15:04:47: Vtl VPDN: Clone from Vtemplate 1 filterPPP=0 blocking 15:04:47: Vtl VTEMPLATE: Has a new cloneblk vtemplate, now it has vtemplate 15:04:47: Vtl VTEMPLATE: Undo default settings 15:04:47: Vtl VTEMPLATE: ***** CLONE VACCESS1 ***** 15:04:47: Vtl VTEMPLATE: Clone from vtemplatel interface Virtual-Access1 no ip address encap ppp ip unnum eth 0 peer default ip address pool async ppp authen chap end %LINK-3-UPDOWN: Interface Virtual-Access1, changed state to up 15:04:48: Vtl VPDN: Bind interface direction=2 15:04:48: Vtl VPDN: PPP LCP accepted sent & rcv CONFACK 15:04:48: Vtl VPDN: Virtual interface iteration 15:04:48: AAA/AUTHEN: create_user (0x161688) user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP service=PPP priv=1 15:04:48: AAA/AUTHEN/START (580760432): port='Virtual-Access1' list='' action=LOGIN service=PPP 15:04:48: AAA/AUTHEN/START (580760432): using "default" list 15:04:48: AAA/AUTHEN/START (580760432): Method=TACACS+ 15:04:48: TAC+: send AUTHEN/START packet ver=193 id=580760432 15:04:48: Vtl VPDN: Virtual interface iteration 15:04:49: TAC+: ver=192 id=580760432 received AUTHEN status = GETPASS **!--- Authenticate user jsmith@hp.com with the TACACS+ server.** 15:04:49: AAA/AUTHEN: create_user (0x1667C0) user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP service=PPP priv=1 15:04:49: TAC+: ver=192 id=2894253624 received AUTHEN status = PASS 15:04:49: AAA/AUTHEN: free_user (0x1667C0) user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP service=PPP priv=1 15:04:49: AAA/AUTHEN (580760432): status = PASS 15:04:49: AAA/AUTHOR/LCP Vtl: Authorize LCP 15:04:49: AAA/AUTHOR/LCP: Virtual-Access1: (687698354): user='jsmith@hp.com' 15:04:49: AAA/AUTHOR/LCP: Virtual-Access1: (687698354): send AV service=ppp 15:04:49: AAA/AUTHOR/LCP: Virtual-Access1: (687698354): send AV protocol=lcp 15:04:49: AAA/AUTHOR/LCP: Virtual-Access1: (687698354): Method=TACACS+ 15:04:49: AAA/AUTHOR/TAC+: (687698354): user=jsmith@hp.com 15:04:49: AAA/AUTHOR/TAC+: (687698354): send AV service=ppp 15:04:49: AAA/AUTHOR/TAC+: (687698354): send AV protocol=lcp 15:04:49: TAC+: (687698354): received author response status = PASS_ADD 15:04:49: AAA/AUTHOR (687698354): Post authorization status = PASS_ADD 15:04:49: AAA/ACCT: NET acct start. User jsmith@hp.com, Port Virtual-Access1: Virtual-Access1 15:04:49: AAA/AUTHOR/FSM Vtl: (0): Can we start IPCP? 15:04:49: AAA/AUTHOR/FSM: Virtual-Access1: (3562892028): user='jsmith@hp.com' 15:04:49: AAA/AUTHOR/FSM: Virtual-Access1: (3562892028): send AV service=ppp 15:04:49: AAA/AUTHOR/FSM: Virtual-Access1: (3562892028): send AV protocol=ip 15:04:49: AAA/AUTHOR/FSM: Virtual-Access1: (3562892028): Method=TACACS+ 15:04:49: AAA/AUTHOR/TAC+: (3562892028): user=jsmith@hp.com 15:04:49: AAA/AUTHOR/TAC+: (3562892028): send AV service=ppp 15:04:49: AAA/AUTHOR/TAC+: (3562892028): send AV protocol=ip %LINEPROTO-5-UPDOWN: Line protocol on Interface Virtual-Access1, changed state to up 15:04:49: TAC+: (3562892028): received author response status = PASS_ADD 15:04:49: AAA/AUTHOR (3562892028): Post authorization status = PASS_ADD **!--- IPCP negotiation begins.** 15:04:49: AAA/AUTHOR/FSM Vtl: We can start IPCP 15:04:50: AAA/AUTHOR/IPCP Vtl: Start. Her address 0.0.0.0, we want 0.0.0.0 15:04:50: AAA/AUTHOR/IPCP Vtl: Processing AV service=ppp 15:04:50: AAA/AUTHOR/IPCP Vtl: Processing AV protocol=ip 15:04:50: AAA/AUTHOR/IPCP Vtl: Authorization succeeded 15:04:50: AAA/AUTHOR/IPCP Vtl: Done. Her address 0.0.0.0, we want 0.0.0.0 15:04:51: AAA/AUTHOR/IPCP Vtl: Start. Her address 0.0.0.0, we want 15.15.15.15 15:04:51: AAA/AUTHOR/IPCP Vtl: Processing AV service=ppp 15:04:51: AAA/AUTHOR/IPCP Vtl: Processing AV protocol=ip 15:04:51: AAA/AUTHOR/IPCP Vtl: Authorization succeeded 15:04:51: AAA/AUTHOR/IPCP Vtl: Done. Her

```
address 0.0.0.0, we want 15.15.15.15 15:04:51: AAA/AUTHOR/IPCP Vi1: Start. Her address
15.15.15.15, we want 15.15.15.15 15:04:51: AAA/AUTHOR/IPCP: Virtual-Access1: (3193852847):
user='jsmith@hp.com' 15:04:51: AAA/AUTHOR/IPCP: Virtual-Access1: (3193852847): send AV
service=ppp 15:04:51: AAA/AUTHOR/IPCP: Virtual-Access1: (3193852847): send AV protocol=ip
15:04:51: AAA/AUTHOR/IPCP: Virtual-Access1: (3193852847): send AV addr*15.15.15.15 15:04:51:
AAA/AUTHOR/IPCP: Virtual-Access1: (3193852847): Method=TACACS+ 15:04:51: AAA/AUTHOR/TAC+:
(3193852847): user=jsmith@hp.com 15:04:51: AAA/AUTHOR/TAC+: (3193852847): send AV service=ppp
15:04:51: AAA/AUTHOR/TAC+: (3193852847): send AV protocol=ip 15:04:51: AAA/AUTHOR/TAC+:
(3193852847): send AV addr*15.15.15.15 15:04:51: TAC+: (3193852847): received author response
status = PASS_ADD 15:04:51: AAA/AUTHOR (3193852847): Post authorization status = PASS_ADD
15:04:51: AAA/AUTHOR/IPCP Vi1: Processing AV service=ppp 15:04:51: AAA/AUTHOR/IPCP Vi1:
Processing AV protocol=ip 15:04:51: AAA/AUTHOR/IPCP Vi1: Processing AV addr*15.15.15.15
15:04:51: AAA/AUTHOR/IPCP Vi1: Authorization succeeded 15:04:51: AAA/AUTHOR/IPCP Vi1: Done. Her
address 15.15.15.15, we want 15.15.15.15 !--- User finishes and disconnects. 15:05:24: Vi1 VPDN:
Reset 15:05:24: Vi1 VPDN: Reset %LINK-3-UPDOWN: Interface Virtual-Access1, changed state to down
15:05:24: Vi1 VPDN: Cleanup 15:05:24: Vi1 VPDN: Reset 15:05:24: Vi1 VPDN: Reset 15:05:24: Vi1
VPDN: Unbind interface 15:05:24: Vi1 VTEMPLATE: Free vaccess 15:05:24: Vi1 VPDN: Reset 15:05:24:
Vi1 VPDN: Reset 15:05:24: AAA/ACCT: Network acct stop. User jsmith@hp.com, Port Virtual-Access1:
task_id=2 timezone=UTC service=ppp protocol=ip addr=15.15.15.15 bytes_in=564 bytes_out=142
paks_in=15 paks_out=8 elapsed_time=35 15:05:24: AAA/AUTHEN: free_user (0x161688)
user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP
service=PPP priv=1 %LINEPROTO-5-UPDOWN: Line protocol on Interface Virtual-Access1, changed
state to down 15:05:25: VTEMPLATE: Clean up dirty vaccess queue, size 1 15:05:25: Vi1 VTEMPLATE:
Found a dirty vaccess clone with vtemplate 15:05:25: Vi1 VTEMPLATE: ***** UNCLONE
VACCESS1 ***** 15:05:25: Vi1 VTEMPLATE: Unclone to-be-freed command#5 interface
Virtual-Access1 default ppp authen chap default peer default ip address pool async default ip
unnum eth 0 default encap ppp default ip address end 15:05:26: Vi1 VTEMPLATE: Set default
settings with no ip address 15:05:26: Vi1 VTEMPLATE: Remove cloneblk vtemplate with vtemplate
15:05:26: Vi1 VTEMPLATE: Add vaccess to recycle queue, queue size=1 thing_one#
```

[Debuga para a falha na conexão no roteador ISP](#)

```
koala#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is on
AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on
koala# !--- Problem 1: !--- The ISP TACACS+ server is down. !--- There is no output on the HGW
router !--- because the call has not gone that far. AAA/AUTHOR (3015476150): Post authorization
status = ERROR AAA/AUTHOR/VPDN: : (3015476150): Method=NOT_SET AAA/AUTHOR/VPDN: : (3015476150):
no methods left to try AAA/AUTHOR (3015476150): Post authorization status = ERROR VPDN: (hp.com)
Authorization failed, could not talk to AAA server or local tunnel problem !--- Problem 2: !---
Userid hp.com is not in the ISP server. !--- There is no output on the Gateway router !---
because the call has not gone that far. TAC+: (894828802): received author response status =
PASS_ADD AAA/AUTHOR (894828802): Post authorization status = PASS_ADD VPDN: (hp.com)
Authorization failed, had talked to AAA server; but both Tunnel ID and IP address are missing
AAA/AUTHEN: free_user (0x16A6E4) user='hp.com' ruser='' port='Async1' rem_addr=''
authen_type=NONE service=LOGIN priv=0 AAA/AUTHEN: create_user (0x16CA8C) user='jsmith@hp.com'
ruser='' port='Async1' rem_addr='async' authen_type=CHAP service=PPP priv=1 AAA/AUTHEN/START
(1904487288): port='Async1' list='' action=LOGIN service=PPP AAA/AUTHEN/START (1904487288):
using "default" list AAA/AUTHEN (1904487288): status = UNKNOWN AAA/AUTHEN/START (1904487288):
Method=TACACS+ TAC+: send AUTHEN/START packet ver=193 id=1904487288 TAC+: ver=193 id=1904487288
received AUTHEN status = FAIL AAA/AUTHEN (1904487288): status = FAIL
```

[Debuga para falhas na conexão no roteador de HGW](#)

```
thing_one#show debug General OS: AAA Authentication debugging is on AAA Authorization debugging is on
AAA Accounting debugging is on VPN: VPN events debugging is on VPN errors debugging is on
VTEMPLATE: Virtual Template debugging is on thing_one# !--- Problem 1: !--- The problem is in
the tunnel definition on HGW router. !--- In the HGW configuration, vpdn incoming hp-gw isp
virtual-template 1 !--- is inserted instead of vpdn incoming isp hp-gw virtual-template 1 !---
The debug vpdn l2f-errors command displays. L2F: Couldn't find tunnel named isp L2F: Couldn't
find tunnel named isp !--- Problem 2: !--- This message appears when User hp-gw is not in the
HGW server. TAC+: ver=192 id=1920941753 received AUTHEN status = FAIL AAA/AUTHEN: free_user
(0x138C34) user='hp-gw' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1
AAA/AUTHEN (3006335673): status = FAIL VPDN: authentication failed, couldn't find user
information for hp-gw !--- Problem 3: !--- This appears when user isp is not in the HGW server.
```

```
TAC+: ver=192 id=1917558147 received AUTHEN status = FAIL AAA/AUTHEN: free_user (0x15F20C)
user='isp' ruser='' port='' rem_addr='' authen_type=CHAP service=PPP priv=1 AAA/AUTHEN
(1949507921): status = FAIL VPDN: authentication failed, couldn't find user information for isp
!--- Problem 4: !--- This message appears when User jsmith@hp.com is !--- not in the HGW server:
TAC+: ver=192 id=755036341 received AUTHEN status = FAIL AAA/AUTHEN: free_user (0x15F89C)
user='jsmith@hp.com' ruser='' port='Virtual-Access1' rem_addr='async' authen_type=CHAP
service=PPP priv=1 AAA/AUTHEN (2606986667): status = FAIL
```

Informações Relacionadas

- [Cisco Secure ACS para página de suporte do UNIX](#)
- [Página de suporte de TACACS+](#)
- [Suporte Técnico e Documentação - Cisco Systems](#)